

SHIMAFUJI

[■ ホーム](#)
[■ 製品紹介](#)
[■ ダウンロード](#)
[■ 技術資料](#)
[■ 会社概要](#)
[■ リクルート](#)
[■ コンタクト](#)

製品紹介

SEMC5701A

SEMC5701A



SEMC5701A



Specifications	
C P U	VR5701CPU (266Mhz / 333Mhz operation) can be switched multiplied by DIP-SW
F L A S H R O M	16M bytes
S D R A M	64M bytes (128M bytes can also be selected)
R T C	RV5C348B (battery backup)
L A N	10 / 100BASE-T (1 channel) RJ-45 connector
V I D E O	VGA, XGA, SXGA corresponding high-density D-Sub15 pin
U S B	USB2.0 (TYPE-A 2-channel)
C F	1 slot TRUE-IDE mode corresponding fixed 3.3V
S O U N D	AC97 corresponding MIC input STEREO output
S E R I A L	RS-232 (D-Sub9 pin connector, 3-pin connector)
power supply	DC+5V
Case Size	Width 52mm x depth 52mm x height 45mm (excluding protrusions)
Operating temperature	0 ~ 35°C
Technical Information	1. SEMC5701 Linux-PMON instructions 2. SEMC5701 kernel

(C)2005-2013 SHIMAFUJI Electric Incorporated All Rights reserved.