

Commands Reference, Volume 3, i - m



Commands Reference, Volume 3, i - m

Seventh Edition (October 2009)

This edition applies to AIX 5L Version 5.3 and to all subsequent releases of this product until otherwise indicated in new editions.

A reader's comment form is provided at the back of this publication. If the form has been removed, address comments to Information Development, Department 04XA-905-6B013, 11501 Burnet Road, Austin, Texas 78758-3400. To send comments electronically, use this commercial Internet address: pserinfo@us.ibm.com. Any information that you supply may be used without incurring any obligation to you.

© Copyright International Business Machines Corporation 1997, 2009.

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

About This Book	. X
How to Use This Book	. X
Highlighting	. X
SO 9000	. xiv
2-Bit and 64-Bit Support for the Single UNIX Specification	. xiv
Related Information	
Alphabetical Listing of Commands	1
om3812 Command	
om3816 Command	
pm5585H-T Command	
pm5587G Command	
ostat Command	
conv Command	
d Command	
config Command	
ke Command	
kedb Command	
make Command	
mapd Daemon	
mapds Daemon	
mpfilt Command	
mportvg Command	
mptun Command	
nc Command	
ndent Command	. 36
ndxbib Command	. 39
netd Daemon	. 41
nfocmp Command	. 43
nfocenter Command	
nstall Command	
nstall_all_updates Command	
nstall_assist Command	
nstall mh Command	
nstall wizard Command	
nstallbsd Command	
nstallios Command.	
nstallp Command	. 56
nstfix Command.	. 67
nucp Command	. 69
nudocm Command	. 70
	. 71
nurecy Command	. 73
nurest Command	. 75
nurid Command	. 76
nusave Command	. 77
nutoc Command	. 80
nuumsg Command	. 80
nvscout Command	. 81
nvscoutd Command	. 84
oo Command	. 90
ostat Command	106
ocrm Command	. 113

ipcs Command																													114
ipfilter Command																													118
ipreport Command																													
ipsec_convert Command																													
ipsecstat Command																													119
ipsectrcbuf Command .																										•			120
iptrace Daemon																										•			120
isC2host Command																													_
isCChost Command																													
istat Command																													125
j2edlimit Command																													126
																													129
jobs Command																													_
join Command																													131
joinvg Command																													134
kdb Command																													135
kdestroy Command																													137
keyadd Command																													138
keycomp Command																													139
keydelete Command																													141
keyenvoy Command																													142
keylist Command																													143
keylogin Command																													144
keylogout Command																													145
keypasswd Command .																													146
keyserv Daemon																													147
kill Command																													148
killall Command																													150
kinit Command																										-	-		151
klist Command																													152
kmodctrl Command																										•	•		154
kpasswd Command																										•	•		155
krlogind Daemon																										•	•		155
krshd Daemon																									•	•	•		157
																									•	•	•		158
ksh Command																								•	•	•	•		161
ksh93 Command									•	•	•	•	•	•	•	•	•	٠.		•	•	•	•	•	•	٠			164
kvno Command									•		•	•	•			•			•	•	٠	•	•		•	•	٠		_
last Command	•	٠	٠	٠	٠	٠	٠	•	٠	٠	•	•	•	٠	•	•	•		•	•	٠	٠	٠	•	•	٠	٠		165
lastcomm Command	•	•	٠	٠	٠	٠	٠	•	٠	•	•					•	•		•	٠	٠	٠	٠	•	•	٠	٠		167
																								•		٠	٠		168
_																								•		٠	٠	-	169
_																													172
Ibxproxy Command																												-	173
ld Command																													174
Idd Command																													196
Idedit Command																													197
learn Command																													199
leave Command																													201
lecstat Command																													201
lex Command																													203
line Command																													209
link Command		•	-																									-	210
lint Command	•	•	•	•	•	-	•	•						_		-			•	•	-	-						-	211
listdgrp Command	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•	-	215
listvgbackup Command.																				•	•	•	•	•	•	•	•		216
listX11input Command .																								•	•	•	•		218
Ilbd Daemon																									•	•			219
IIDU DatiiiUII																													∠ 1 5

In Command																											220
locale Command																											222
localedef Command	-	-	-	-	-	-	-	-		-	-	-	-	-	-	-		-	-	-		-	-		-		224
lock Command																•		·			Ċ			•	•	•	226
lockd Daemon															•			•					•	•	•	•	227
locktrace Command					-							•			•	•		•			٠		•	•	•	•	229
						-	-	-	-	-	-		-	-	•			•			•		٠	•	•	٠	
logevent Command						٠	•	•	٠	•		•	•	•				•	٠	٠	•	•	٠	٠	٠	٠	230
logform Command						٠													٠	٠	٠	٠	٠	٠	٠		231
logger Command																											233
login Command																											234
logins Command																											237
logname Command																											239
logout Command																											240
look Command																											241
lookbib Command											-	-			-	-		-							-	-	242
lorder Command															•	•		•						•	•	•	242
lp Command															•			•						•	•	•	243
lp.cat, lp.set, lp.tell Command										•						•		•			٠			•	•		249
										•	•	•	•	•				•	•	•	٠	•	•	•	•		_
Ipadmin Command										•	•	•	•	•		•		•	٠	٠	٠	•	٠	٠	٠		251
lpar_netboot Command													•						٠	٠	٠	•	٠	٠	٠		259
Iparstat Command																											261
lpc Command																											266
lpd Command																											268
lpfilter Command																											270
lpforms Command																											274
Iphistory Command																											279
Ipmove Command																											282
lppchk Command																											282
Ippmgr Command										-	-							-	-		-	-	-		-		284
lpq Command											•							•	•		•	•	•	·	•		286
lpr Command											•			:			•	·	•	Ċ	•	•	•		•		289
lprm Command																		•	•	Ċ	•	•	•	•	•	•	294
lpsched Command																		•			•	•	•	•	•	•	296
•																							•	•	•	•	297
																						•	٠	٠	•	٠	301
Ipsystem Command																					•	•	•	•	•	٠	
Iptest Command																					٠	٠	٠	٠	٠	٠	303
lpusers Command	•	•				٠	•						•					•	٠	٠	٠	•	٠	٠	٠	٠	303
ls Command																										٠	305
ls-secldapcIntd Command .																											309
Isactdef Command																											310
Isallq Command																											314
Isallqdev Command																											315
Isarm command																											316
Isattr Command																											317
Isaudrec Command																											322
Isauthent Command																											327
IsC2admin Command																											327
IsCCadmin Command																											328
Iscfg Command																											328
Iscifscred Command																										•	331
																										٠	
Iscifsmnt Command																										-	332
Isclass Command																										-	333
Iscomg Command																										-	334
Iscondition Command																											
Iscondresp Command																											
Isconn Command																											346

Iscons Command																															348
Iscore Command																															349
																															350
																															352
																										·			•	·	359
																										•	•	•		•	360
																										•	•	•	•	•	360
Isfs Command																										•	•	•	•	•	361
																										•	•	•	•	•	363
•																										•	•	•	•	•	365
																										•	•	•	•	•	366
	٠																									•	•	•	٠	•	367
	٠																									•	•	•	•	•	
•	٠																									•	•	•	٠	٠	368
Islicense Command .																										٠	٠	٠	٠	٠	371
•																										٠	•	٠	٠	٠	372
Islpp Command																										٠		٠			376
Islv Command																														٠	380
Ismaster Command .																															383
																															384
Ismksysb Command .																															386
Isnamsv Command .																															388
Isnfsexp Command .																															389
Isnfsmnt Command .																															390
Isnim Command																															391
IsnIspath Command .																															394
Isparent Command .																															394
Ispath Command																															396
Isprtsv Command																															400
Isps Command																															401
Ispv Command																															403
Isque Command																															406
Isquedev Command .																										•	•	•		•	407
Isresource Command																										•	•	•		•	408
Isresponse Command																										•	•	•	•	•	411
Isrole Command																										•	•	•	•		415
Isrpdomain Command																										•	•	•	•	•	417
Isrpnode Command .																										•	•	•	•	•	420
Isrset Command	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	423
Isrsrc Command	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	423
Isrsrcdef Command	•	•	•		٠																					•	•	•	•	•	430
	٠	•			٠																					•	•	•	٠	•	436
Issavevg Command .	٠	٠	٠		٠																					٠	٠	٠	٠	٠	
Issec Command	٠	•	٠		٠																					٠	٠	٠	٠	٠	438
Issensor Command .		٠			٠																					٠	٠	٠		•	440
Isslot Command	٠				٠																					٠	•	٠	٠	٠	444
Issrc Command		٠	٠		٠	٠	٠																			٠		٠			447
Ists Command																															449
Istun Command																															451
Isuser Command																															452
Isvfs Command																															454
Isvg Command																															455
Isvgfs Command																															458
Isvirprt Command																															459
Isvmode Command .																															462
Isvpd Command																															463
Isvsd Command																															468
IswImconf Command.																															470

lvmo Command														 												473
lvmstat Command														 												475
m4 Command																										477
mach Command														 												480
machstat Command														 												480
macref Command																										481
mail, Mail, or mailx Command																									-	482
mailq Command														 											-	494
mailstats Command														 												496
make Command														 												497
makedbm Command														 												504
makedepend Command																										505
makedev Command														 												507
makekey Command														 												508
makemap Command																										509
man Command																										510
managefonts Command														 												514
mant Command																										515
mark Command																										517
mesg Command																										519
mhl Command														 												521
mhmail Command														 												523
mhpath Command																										524
migratelp Command														 												526
migratepv Command														 												527
mirrorvg Command														 												528
mirscan Command														 												531
mk_niscachemgr Command .														 												534
mk_nisd Command														 												535
mk_nispasswdd Command .														 												537
mkboot Command														 												538
mkC2admin Command														 												540
mkcatdefs Command														 												541
mkCCadmin Command																										542
mkcd Command														 												543
mkcfsmnt Command														 												548
mkcifscred Command														 												549
mkcifsmnt Command														 												550
mkcimreg Command														 												552
mkclass Command																										555
mkclient Command																										558
mkcomg Command																										560
mkcondition Command																										563
mkcondresp Command																										569
mkcosi Command																										571
mkdev Command																									-	572
mkdir Command																									-	575
mkdirhier Command																						•	•	•	-	576
mkdvd Command																						•	•	•	-	577
mkfifo Command																									-	581
mkfilt Command																									-	582
mkfont Command																										
mkfontdir Command																										
mkfs Command																										
mkgroup Command																										
mkhosts Command	•	•	•	•	•	•	•	•	•	•	•	•	•	 •	•	•	•	•	•	•	•	•	•	•	•	591

mkiscsi Command																															592
mkitab Command																															593
mkinstallp Command.																															
mkkeyserv Command																															
mkkrb5cInt Command								•	•	•	•	•	•	•	•	•	•		•	•											597
mkkrb5srv Command								•	•	•	•	•	•	•	•	•	•	•	•	•	•										599
mklost+found Command										•	•	•	•	•	•	•	•	•	•	•	•										601
										•	•	•	•	•	•	•	•	•	•	•	•										601
mklpcmd Command .										٠	•	•				•			•	•	•										
mklv Command										•	•	•	٠	٠		•	•	•	•	•	•	•									605
mklvcopy Command .											٠	٠	٠	٠	٠				٠		٠										611
mkmaster Command.										٠		٠	٠	٠																	613
mknamsv Command.								-																							615
mknetid Command .																															616
mknfs Command																															617
mknfsexp Command.																															618
mknfsmnt Command.																															621
mknfsproxy Command																															624
mknod Command																															625
mknotify Command .																															627
mkpasswd Command										•			•	•	•	•	•	•	•		•	•									628
mkpath Command										•	•	•	•	•	•	•	•		•	•	•	•									629
mkprojldap Command										•	•	•	•	•	•	•	•	•	•	•	•	•									631
mkproto Command .										•	•	•	•	•	•	•	•	•	•	•	•	•									
•										•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	633 637
mkprtldap Command.										٠	•	•			•	•			•	•	•	•									
mkprtsv Command .										٠	•	٠	•	•		•	•			•	•	٠									641
mkps Command										٠	•	٠																			644
mkqos Command																															646
mkque Command																															646
mkquedev Command																															648
mkramdisk Command																															649
mkresponse Command																															651
mkrole Command																															656
mkrpdomain Command																															658
mkrset Command																															662
mkrsrc Command																															663
mkseckrb5 Command																															667
mksecldap Command										•			•	•	•	•	•	•	•		•										
mksecpki Command .	•	•	•	•	•	•	•	•	•	•	•	•			•	•			•		•		•	•	•	•	•	•	•	•	673
. '	•	•	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	675
mkserver Command .	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	679
mkslave Command .	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	680
	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
mkssys Command		•	٠	-	٠	٠	•	٠	•	٠	•	•	٠	٠	٠	•	•	•		•		٠	•	٠	•	٠	٠	٠	•		681
mkstr Command		٠	٠	٠	٠	٠		٠	٠	٠	٠	٠											٠	٠	٠	٠		٠			684
mksysb Command .		٠			٠	٠		٠	•	•	•											٠	•	•	•	٠	٠	٠			685
mkszfile Command .																															689
mktcpip Command .																															690
mkts Command																															692
mktun Command																															693
mkuser Command																															694
mkuser.sys Command																															697
mkvg Command																															698
																															701
	-	-	-	-	-	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	•	702
mm Command																															705
mmt Command																															
mmtu Command																															
minu cominana																															105

mobip6ctrl Command																															709
mobip6reqd Daemon.																															711
monacct Command .																															712
mon-cxma Command																															713
monitord Daemon																															714
moo Command																															
more Command																															
mosy Command																															
mount Command																															
mountd Daemon																															
mpcfg Command																															
mpcstat Command .																															
mpstat Command																															
mrouted Daemon																															
msgchk Command .																															
msh Command																															
mt Command (BSD) .																															
mtrace Command																															
multibos Command .																															
mv Command																															
mvdir Command																															
mvfilt Command																															
mvt Command																															
mwm Command	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	758
Appendix. Notices .																															8∩1
Trademarks																															
iradomano	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	302
Index																															805

About This Book

This book provides end users with complete detailed information about commands for the AIX operating system. The commands are listed alphabetically and by category, and complete descriptions are given for commands and their available flags. If applicable, each command listing contains examples. This volume contains AIX commands that begin with the letters i through m. This publication is also available on the documentation CD that is shipped with the operating system.

How to Use This Book

A command is a request to perform an operation or run a program. You use commands to tell the operating system what task you want it to perform. When commands are entered, they are deciphered by a command interpreter (also known as a shell) and that task is processed.

Some commands can be entered simply by typing one word. It is also possible to combine commands so that the output from one command becomes the input for another command. This is known as pipelining.

Flags further define the actions of commands. A flag is a modifier used with the command name on the command line, usually preceded by a dash.

Commands can also be grouped together and stored in a file. These are known as shell procedures or shell scripts. Instead of executing the commands individually, you execute the file that contains the commands.

Some commands can be constructed using Web-based System Manager applications or the System Management Interface Tool (SMIT).

Highlighting

The following highlighting conventions are used in this book:

Bold Identifies commands, subroutines, keywords, files, structures, directories, and other items whose

names are predefined by the system. Also identifies graphical objects such as buttons, labels, and

icons that the user selects.

Italics Identifies parameters whose actual names or values are to be supplied by the user.

Monospace Identifies examples of specific data values, examples of text similar to what you might see

displayed, examples of portions of program code similar to what you might write as a programmer,

messages from the system, or information you should actually type.

Format

Each command may include any of the following sections:

Purpose A description of the major function of each command.

Syntax A syntax statement showing command line options.

DescriptionA discussion of the command describing in detail its function and use.

Flags
A list of command line flags and associated variables with an explanation of

how the flags modify the action of the command.

Parameters A list of command line parameters and their descriptions.

Subcommands A list of subcommands (for interactive commands) that explains their use.

Exit StatusA description of the exit values the command returns.SecuritySpecifies any permissions needed to run the command.ExamplesSpecific examples of how you can use the command.

Files A list of files used by the command.

Related Information A list of related commands in this book and related discussions in other books.

© Copyright IBM Corp. 1997, 2009

Reading Syntax Statements

Syntax statements are a way to represent command syntax and consist of symbols such as brackets ([]), braces ({ }), and vertical bars (I). The following is a sample of a syntax statement for the **unget** command:

The following conventions are used in the command syntax statements:

- · Items that must be entered literally on the command line are in **bold**. These items include the command name, flags, and literal charactors.
- · Items representing variables that must be replaced by a name are in italics. These items include parameters that follow flags and parameters that the command reads, such as Files and Directories.
- · Parameters enclosed in brackets are optional.
- · Parameters enclosed in braces are required.
- · Parameters not enclosed in either brackets or braces are required.
- A vertical bar signifies that you choose only one parameter. For example, [a | b] indicates that you can choose a, b, or nothing. Similarly, { a | b } indicates that you must choose either a or b.
- Ellipses (...) signify the parameter can be repeated on the command line.
- The dash () represents standard input.

Listing of Installable Software Packages

To list the installable software package (fileset) of an individual command use the Islpp command with the -w flag. For example, to list the fileset that owns the installp command, enter:

```
lslpp -w /usr/sbin/installp
```

Output similar to the following displays:

File	Fileset	Type
/usr/sbin/installp	bos.rte.install	File

To list the fileset that owns all file names that contain installp, enter:

```
lslpp -w "*installp*"
```

Output similar to the following displays:

File	Fileset	Type
/usr/sbin/installp /usr/clvm/sbin/linstallpv	bos.rte.install prpq.clvm	File File
/usr/lpp/bos.sysmgt/nim/methods/	/c_installp	
	<pre>bos.sysmgt.nim.client</pre>	File

Running Commands in the Background

If you are going to run a command that takes a long time to process, you can specify that the command run in the background. Background processing is a useful way to run programs that process slowly. To run a command in the background, you use the & operator at the end of the command:

Command&

Once the process is running in the background, you can continue to work and enter other commands on your system.

At times, you might want to run a command at a specified time or on a specific date. Using the cron daemon, you can schedule commands to run automatically. Or, using the at and batch commands, you can run commands at a later time or when the system load level permits.

Entering Commands

You typically enter commands following the shell prompt on the command line. The shell prompt can vary. In the following examples, \$ is the prompt.

To display a list of the contents of your current directory, you would type 1s and press the Enter key: \$ 1s

When you enter a command and it is running, the operating system does not display the shell prompt. When the command completes its action, the system displays the prompt again. This indicates that you can enter another command.

The general format for entering commands is:

```
Command Flag(s) Parameter
```

The flag alters the way a command works. Many commands have several flags. For example, if you type the -I (long) flag following the Is command, the system provides additional information about the contents of the current directory. The following example shows how to use the -I flag with the Is command:

```
$ 1s -1
```

A parameter consists of a string of characters that follows a command or a flag. It specifies data, such as the name of a file or directory, or values. In the following example, the directory named /usr/bin is a parameter:

```
$ 1s -1 /usr/bin
```

When entering commands, it is important to remember the following:

- · Commands are usually entered in lowercase.
- Flags are usually prefixed with a (minus sign).
- More than one command can be typed on the command line if the commands are separated by a; (semicolon).
- · Long sequences of commands can be continued on the next line by using the \ (backslash). The backslash is placed at the end of the first line. The following example shows the placement of the backslash:

```
$ cat /usr/ust/mydir/mydata > \
/usr/usts/yourdir/yourdata
```

When certain commands are entered, the shell prompt changes. Because some commands are actually programs (such as the telnet command), the prompt changes when you are operating within the command. Any command that you issue within a program is known as a subcommand. When you exit the program, the prompt returns to your shell prompt.

The operating system can operate with different shells (for example, Bourne, C, or Korn) and the commands that you enter are interpreted by the shell. Therefore, you must know what shell you are using so that you can enter the commands in the correct format.

Stopping Commands

If you enter a command and then decide to stop that command from running, you can halt the command from processing any further. To stop a command from processing, press the Interrupt key sequence (usually Ctrl-C or Alt-Pause). When the process is stopped, your shell prompt returns and you can then enter another command.

ISO 9000

ISO 9000 registered quality systems were used in the development and manufacturing of this product.

32-Bit and 64-Bit Support for the Single UNIX Specification

Beginning with Version 5.2, the operating system is designed to support The Open Group's Single UNIX Specification Version 3 (UNIX 03) for portability of UNIX-based operating systems. Many new interfaces, and some current ones, have been added or enhanced to meet this specification, making Version 5.2 even more open and portable for applications, while remaining compatible with previous releases of AIX. To determine the proper way to develop a UNIX 03-portable application, you may need to refer to The Open Group's UNIX 03 specification, which can be accessed online or downloaded from http://www.unix.org/ .

Related Information

The following books contain information about or related to commands:

- AIX 5L Version 5.3 Commands Reference, Volume 1
- AIX 5L Version 5.3 Commands Reference, Volume 2
- AIX 5L Version 5.3 Commands Reference, Volume 3
- · AIX 5L Version 5.3 Commands Reference, Volume 4
- AIX 5L Version 5.3 Commands Reference. Volume 5
- AIX 5L Version 5.3 Commands Reference, Volume 6
- · AIX 5L Version 5.3 Files Reference
- · Printers and printing
- Installation and migration
- · AIX 5L Version 5.3 AIX Installation in a Partitioned Environment
- · AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide
- Performance management
- · AIX 5L Version 5.3 Performance Tools Guide and Reference
- Security
- · Networks and communication management
- Operating system and device management
- AIX 5L Version 5.3 Technical Reference: Base Operating System and Extensions Volume 1
- AIX 5L Version 5.3 Technical Reference: Base Operating System and Extensions Volume 2
- AIX 5L Version 5.3 Technical Reference: Communications Volume 1
- AIX 5L Version 5.3 Technical Reference: Communications Volume 2
- AIX 5L Version 5.3 Technical Reference: Kernel and Subsystems Volume 1
- AIX 5L Version 5.3 Technical Reference: Kernel and Subsystems Volume 2
- · AIX 5L Version 5.3 Web-based System Manager Administration Guide
- Performance Toolbox Version 2 and 3 for AIX: Guide and Reference

Alphabetical Listing of Commands

ibm3812 Command

Purpose

Postprocesses the troff command output for the IBM 3812 Model 2 Pageprinter.

Syntax

ibm3812 [-altpaper] [-landscape] [-quietly] [-FDirectory] [-i] [File...]

Description

The **ibm3812** command is a postprocessor that can be used on intermediate output produced by the **troff** command.

Note: An entire page is placed in memory before it is printed.

If given one or more file names as options, the **ibm3812** command processes those files. If no file names are specified, this command acts as a filter interpreting standard input.

The **ibm3812** command's font files allow the postprocessor to send characters of more than one byte to the printer. These can be characters that require multiple bytes to represent them, such as code page and point; or, they can be characters that are composed of two or more concatenated glyphs.

For example, the character code for the \(ib\) (improper subset) special character is:

 $"\001\125\xe2\xff\xe8\xe3\%\x00\x16\001\074\xe3\xff\xea"$

The printer is in Page Map Primitive (PMP) mode when these bytes are sent, so you must use the 001 directive to introduce a character. For single-byte codes, this Generic Font Patterns command is automatically handled by the postprocessor. The % (percent sign) characters escape the bytes containing 0, which would otherwise terminate the code sequence. To obtain a literal % character, escape it with another % character so that a percent sign is displayed as %%. A single-byte % code is assumed to be a literal percent sign, so that the single-byte % character needs no special handling in the font file.

Notes:

- The ibm3812 command depends on the files with names ending in .out in the /usr/lib/font/devibm3812 directory. It does not produce usable output unless these files have been properly set up.
- 2. The postprocessor requires additional font information to be stored in the /usr/lib/font/ devibm3812/fonts file. If new fonts are added to this file, make sure that the DESC file is also updated to reflect the additional fonts and special characters.

The format of the file must be preserved. The file contains the following four fields:

- · The one- or two-letter name of the font
- · The full name of the font on the printer-font diskette
- · The one- or two-letter name of the substitute font
- · An array of five available sizes.

Flags

-altpaper Specifies that the file should be printed from the alternate paper drawer. By default, the ibm3812 command prints from the primary paper drawer.

-landscape Specifies that the file should be printed in landscape orientation, so that the wider part of the

paper is horizontally oriented. This flag rotates the page to the right by 90 degrees. By default,

the ibm3812 command prints in portrait orientation.

-quietly Suppresses all non-fatal error messages.

-FDirectory Specifies the directory holding the font files. The default file is devibm3812. The command

looks for font files in the /usr/lib/font directory by default.

-i Suppresses initialization of the printer that runs the PMP.init macro, after the job has printed.

Example

Following is an example of the **troff** command used with the **ibm3812** command:

troff file|ibm3812|qprt-dp

Files

/usr/lib/font/devibm3812/*.out /usr/lib/font/devibm3812/fonts

Contains font files for the **ibm3812** command.

Contains information about the available fonts for the **ibm3812** command.

Related Information

The ibm3816 command, troff command.

The **troff** font file format specifies description files for the troff command.

ibm3816 Command

Purpose

Postprocesses the troff command output for the IBM 3816 Pageprinter.

Syntax

ibm3816 [-altpaper] [-landscape] [-quietly] [-FDirectory] [-i] [File...]

Description

The **ibm3816** command is a postprocessor that can be used on intermediate output produced by the **troff** command.

Note: An entire page is placed in memory before it is printed.

If given one or more file names as options, the **ibm3816** command processes those files. If no file names are specified, this command acts as a filter interpreting standard input.

The **ibm3816** command's font files allow the postprocessor to send characters of more than one byte to the printer. These can be characters that require multiple bytes to represent them, such as code page and point; or, they can be characters that are composed of two or more concatenated glyphs.

For example, the character code for the \(ib (improper subset) special character is:

 $"\01\125\xe2\xff\xe8\xe3\%\x00\x16\001\074\xe3\xff\xea"$

The printer is in Page Map Primitive (PMP) mode when these bytes are sent, so you must use the 001 directive to introduce a character. For single-byte codes, this Generic Font Patterns command is automatically handled by the postprocessor. The % (percent sign) characters escape the bytes containing 0, which would otherwise terminate the code sequence. To obtain a literal % character, escape it with

another % character so that a percent sign is displayed as %. A single-byte % code is assumed to be a literal percent sign, so that the single-byte % character needs no special handling in the font file.

Notes:

- The ibm3816 command depends on the files with names ending in .out in the /usr/lib/font/devibm3816 directory. It does not produce usable output unless these files have been properly set up.
- 2. The postprocessor requires additional font information to be stored in the /usr/lib/font/ devibm3816/fonts file. If new fonts are added to this file, make sure that the DESC file is also updated to reflect the additional fonts and special characters.

The format of the file must be preserved. The file contains the following four fields:

- · The one- or two-letter name of the font
- · The full name of the font on the printer-font diskette
- · The one- or two-letter name of the substitute font
- · An array of five available sizes.

Flags

artpaper opcomed that the me official be printed from the alternate paper drawer. By deladit, the	-altpaper	Specifies that the file should be printed from the alternate paper drawer. By default, the
---	-----------	--

ibm3816 command prints from the primary paper drawer.

-landscape Specifies that the file should be printed in landscape orientation, so that the wider part of the

paper is horizontally oriented. This flag rotates the page to the right by 90 degrees. By default,

the ibm3816 command prints in portrait orientation.

-quietly Suppresses all non-fatal error messages.

-FDirectory Specifies the directory holding the font files. The default file is **devibm3816**. The command

looks for font files in the /usr/lib/font directory by default.

-i Suppresses initialization of the printer that runs the PMP.init macro, after the job has printed.

Example

Following is an example of the **troff** command used with the **ibm3816** command: troff file|ibm3816|qprt-dp

Files

/usr/lib/font/devibm3816/*.out /usr/lib/font/devibm3816/fonts Contains font files for the **ibm3816** command.

Contains information about the available fonts for the **ibm3816** command.

Related Information

The ibm3812 command, troff command.

The **troff** font file format specifies description files for the troff command.

ibm5585H-T Command

Purpose

Processes troff command output for the IBM 5585H-T printer.

Syntax

ibm5585H-T [-FDirectory] [File]

Description

The **ibm5585H-T** command processes the output of the **troff** command for output to the IBM 5585H-T printer for traditional Chinese language. This command is provided exclusively for traditional Chinese language support.

The **ibm5585H-T** command processes one or more files specified by the *File* parameter. If no file is specified, the **ibm5585H-T** command reads from standard input.

The **ibm5585H-T** command uses font files in the **/usr/lib/font/devibm5585H-T** directory that have command names ending with **.out**. The **ibm5585H-T** command does not produce correct output unless these files are provided.

Flag

-FDirectory

Specifies a directory name as the place to find font files. By default, the **ibm5585H-T** command looks for font files in the /usr/lib/font/devibm5585H-T directory.

Example

To process the reports file for the IBM 5585H-T printer, enter: troff reports | ibm5585H-T | qprt -dp

The **ibm5585H-T** command first processes the output of the **troff** command, then sends the file to a print queue.

File

/usr/lib/font/devibm5585H-T/*.out

Contains font files.

Related Information

The troff command.

The troff font file format.

ibm5587G Command

Purpose

Postprocesses **troff** command output for the IBM 5587-G01, 5584-H02, 5585-H01, 5587-H01, and 5589-H01 printers with the (32x32/24x24) cartridge installed. This command is used exclusively for Japanese Language Support.

Syntax

ibm5587G [-FDirectory] [-quietly] [File ...]

Description

The **ibm5587G** command processes the output of the **troff** command for output to the 5587-G01, 5584-H02, 5585-H01, 5587-H01, and 5589-H01 printers.

If given one or more files as options, the ibm5587G command processes those files. If no files are specified, it acts as a filter interpreting standard input.

Note: The ibm5587G command assumes that the (32x32/24x24) cartridge is installed in the printer. Incorrect output from the printer may result if the wrong cartridge is installed in the printer.

The ibm5587G command depends on the files with names ending in .out in the /usr/lib/font/ devibm5587G directory. It does not produce reasonable output unless these files have been properly set up.

Flags

-FDirectory Specifies a directory name as the place to find the font files. By default, the ibm5587G

command looks for font files in the /usr/lib/font/devibm5587G directory.

Suppresses all nonfatal error messages. -quietly

Files

/usr/lib/font/devibm5587G/*.out

Contains font files.

Related Information

The **troff** command formats text for printing on typesetting devices.

The **troff** font file format specifies description files for the troff command.

ibstat Command

Purpose

Displays operational information about one or more InfiniBand network devices.

Syntax

ibstat [-d, -h, -i, -n, -p, -v] DeviceName

Description

This command displays InfiniBand operational information pertaining to a specified Host Channel Adapter Device (HCAD). If an HCAD device name is not entered, status for all available HCADs are displayed. Select a flag to narrow down your search results. You can display specific categories of information, including Node, Port, Interface, and Debug information. You can also choose to display all of the information categories.

Flags

-d	Displays current debug setting.
-h	Displays ibstat command usage.
-i	Displays network interface information.
-n	Displays IB node information.
-р	Displays IB port information.
-v	Displays all IB device information.

The following fields display information for all valid calls:

Device Name

Displays the name of an available HCAD (for example, iba0).

Port State

Displays the current state of each HCAD port.

Down Port is disabled.

Initialized

Port is enabled and issuing training sequences.

Armed

Port is trained and attempting to configure to the active state.

Active Port is in a normal operational state.

Unknown

Port is in an invalid or unknown state.

Parameters

DeviceName

Specifies the name of the HCAD device (for example, iba0)

Exit Status

When you specify an invalid *DeviceName*, the **ibstat** command produces error messages stating that it could not connect to the device. For example:

IBSTAT: No device iba2 configured.

or

IBSTAT: Device iba3 is not available.

Examples

1. To request node and port information, enter:

```
ibstat -n -p
```

Information similar to the following is displayed:

```
______
INFINIBAND DEVICE INFORMATION (iba0)
------
IB NODE INFORMATION (iba0)
Maximum Multicast Groups:
Maximum Memory Regions:
Maximum Memory Windows:
                    256
                   3836
                    3836
IB PORT 1 INFORMATION (iba0)
Global ID Prefix:
                    fe.80.00.00.00.00.00.00
Local ID (LID):
                    0012
Port State:
                    Active
```

```
Maximum Transmission Unit Capacity:
                                       2048
Current Number of Partition Keys:
Partition Key List:
                                       ffff
 P_Key[0]:
Current Number of GUID's:
                                       1
Globally Unique ID List:
                                       00.02.55.00.00.00.46.12
 GUID[0]:
IB PORT 2 INFORMATION (iba0)
Global ID Prefix:
                                       fe.80.00.00.00.00.00.00
Local ID (LID):
                                       0011
Port State:
                                       Active
Maximum Transmission Unit Capacity:
                                       2048
Current Number of Partition Keys:
                                       1
Partition Key List:
                                       ffff
 P Key[0]:
Current Number of GUID's:
Globally Unique ID List:
 GUID[0]:
                                       00.02.55.00.00.00.46.52
```

Location

/usr/sbin/ibstat

Related Information

Internet Protocol over InfiniBand.

iconv Command

Purpose

Converts the encoding of characters from one code page encoding scheme to another.

Syntax

iconv [-cs] -f FromCode -t ToCode [FileName...]

iconv -I

Description

The **iconv** command converts the encoding of characters read from either standard input or the specified file from one coded character set to another and then writes the results to standard output. The input and output coded character sets are identified by the *FromCode* and *ToCode* parameters. The input data should consist of characters in the code set specified by the *FromCode* parameter. If the *FileName* parameter is not specified on the command line, the **iconv** command reads from standard input.

You can use a Web-based System Manager System application (wsm system fast path) to run this command. You could also use the System Management Interface Tool (SMIT) smit iconv fast path to run this command. The iconv command uses the LOCPATH environment variable to search for code-set converters of the form iconv/FromCodeSet ToCodeSet. The default value of LOCPATH is /usr/lib/nls/loc.

Flags

-c	Omits characters that cannot be converted in the input file from the output. Characters that cannot be converted include characters that are invalid in the <i>FromCode</i> of the input or that
	have no corresponding character in the <i>ToCode</i> of the output. After omitting an unconvertible
character, iconv adva	character, iconv advances to the next byte of the input to convert the next character. If -c is not
	used, iconv exits upon encountering a character that cannot be converted in the input. The
	presence or absence of -c does not affect the exit status of iconv .

-f FromCode Specifies the code set in which the input data is encoded. The space between the -f flag and

the FromCode parameter is optional.

-I Writes all supported FromCode and ToCode values to standard output.

-s Suppresses any messages written to standard error concerning invalid characters. When -s is not used, an error message is written to standard error for each unconvertible or truncated

character. The presence or absence of -s does not affect the exit status of iconv.

-t ToCode Specifies the code set to which the output data is to be converted. The space between the -t

flag and the *ToCode* parameter is optional.

FileName Specifies a file to be converted.

The list of supported code set converters is provided in "List of Converters" in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs.

Exit Status

This command returns the following exit values:

- Input data was successfully converted.
- 1 The specified conversions are not supported; the given input file cannot be opened for read; or there is a usage-syntax error.
- 2 An unusable character was encountered in the input stream.

Examples

1. To convert the contents of the **mail.x400** file from code set IBM-850 and store the results in the **mail.local** file, enter:

```
iconv - f IBM-850 - t ISO8859-1 mail.x400 > mail.local
```

2. To convert the contents of the **mail.japan** file from the 7-bit interchange (ISO2022) encoding to the Japanese EUC code set (IBM-eucJP), enter:

```
iconv -f fold7 -t IBM-eucJP mail.japan > mail.local
```

3. To convert the contents of a local file to the mail-interchange format and send mail, enter:

```
iconv -f IBM-943 -t fold7 mail.local | mail fxrojas
```

Related Information

The **genxit** command describes how to define a conversion table.

The **iconv** subroutine, **iconv_close** subroutine, and **iconv_open** subroutines provide a method to use the conversion service from within a program.

Converters Overview in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide.

For information on installing the Web-based System Manager, see Chapter 2: Installation and System Requirements in *AIX 5L Version 5.3 Web-based System Manager Administration Guide*.

Converters Overview for Programming in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide.

id Command

Purpose

Displays the system identifications of a specified user.

Syntax

id [user]

id -G [-n] [User]

id -g [-n I | [-n r] [User]

id -u [-n I | [-n r] [*User*]

Description

The **id** command writes to standard output a message containing the system identifications (ID) for a specified user. The system IDs are numbers which identify users and user groups to the system. The **id** command writes the following information, when applicable:

- · User name and real user ID
- · Name of the user's group and real group ID
- Name of user's supplementary groups and supplementary group IDs
 Supplementary group information is written only for systems supporting multiple-user groups and only if the specified user belongs to a supplementary group.

The **id** command also writes effective user and group IDs, but only for the user that invoked the **id** command. (If the *User* parameter is specified with the **id** command, the effective IDs are assumed to be identical to real IDs.) If the effective and real IDs for the invoking user are different, the **id** command writes the following effective ID information, when applicable:

- · Effective user name and effective user ID
- Name of effective user's group and effective group ID

The <code>id</code> command, when specified with the <code>-I</code> option, displays login UID. Login ID indicates the system credentials at the time of logging in to the session. Login UID indicates the user ID (numeric value) of the user, who actually logged in. The login UID is equal to the UID for a user who has logged in to the system and whose credentials remain unchanged. For example, when the user runs the <code>su</code> command, the UID for the user changes and the login UID remains the same.

The **id** command will fail if the specified user does not exist or if the command cannot read the user or group information.

Flags

The contents and format of the message written by the **id** command can be altered with the following flags:

- **-G** Specifies that the **id** command write the effective, real, and supplementary group IDs only. If there are multiple entries for the effective, real, or supplementary IDs, they are separated by a space and placed on the same line.
- -g Specifies that the id command write only the effective group ID.
- -u Specifies that the id command write only the effective user ID.
- -r Specifies that the **id** command write the real ID instead of the effective ID. This flag can be invoked with either the -g flag to write the real group ID, or the -u flag to write the real user ID.

- -n Specifies that the id command outputs the name, instead of the ID number, when it is specified with the -G,
 -g, and -u flags.
- -I Specifies that the **id** command write the login ID instead of the real or effective ID. This flag can be invoked with either the **-u** flag to write the login UID or the **-g** flag to write the primary group ID for the login user. When *username* is passed with the **-I** option, the **id** command displays the ID details of the user name instead of the login ID details.
- User Specifies the login name of a user for the **id** command. If no user is specified, the user invoking the **id** command is the default.

Security

Access Control: This program should be installed as a normal user program in the Trusted Computing Base.

Exit Status

This command returns the following exit values:

- 0 Successful completion.
- >0 An error occurred.

Examples

1. To display all system identifications for the current user, enter:

id

Output for the id command is displayed in the following format:

```
uid=1544(sah) gid=300(build) euid=0(root) egid=9(printq) groups=0(system),10(audit)
```

In this example, the user has user name sah with an ID number of 1544; a primary group name of build with an ID number of 300; an effective user name of root with an ID number of 0; an effective group name of printq with an ID number of 9; and two supplementary group names of system and audit, with ID numbers 0 and 10, respectively.

2. To display all group ID numbers for the current user, enter:

id -G

Output is displayed in the following format:

0 10 300 9

The **-G** flag writes only the group IDs for a user. In this example, user sah is a member of the system (0), audit (10), build (300), and printq (9) groups.

3. To display all group names for the current user, enter:

id -Gn

Output is displayed in the following format:

```
system audit build printq
```

The -n flag writes only the names instead of the ID numbers.

4. To display the real group name for the current user, enter:

id -gnr

Output is displayed in the following format:

build

5. To display the login UID after logging in as root and running the **su** command to user **sah**, type:

```
id -lu
```

Output is displayed in the following format:

0

6. To display the primary group name of the user who actually logged in, type:

```
id -lan
```

Output is displayed in the following format:

system

7. To display the primary group ID of the user who actually logged in, type:

```
id -lg
```

Output is displayed in the following format:

0

Files

/usr/bin/id

Contains the id command.

Related Information

The getty command, login command, setgroups command, su command, tsm command.

ifconfig Command

Purpose

Configures or displays network interface parameters for a network using TCP/IP.

Syntax

```
ifconfig Interface [ AddressFamily [ Address [ DestinationAddress ] ] [ Parameters... ] ]
ifconfig Interface [ ProtocolFamily ] Interface ProtocolFamily
ifconfig -a [ -l ] [ -d ] [ -u ] [ ProtocolFamily ]
ifconfig Interface [ tcp_low_rto rto | -tcp_low_rto ]
```

Description

You can use the **ifconfig** command to assign an address to a network interface and to configure or display the current network interface configuration information. The **ifconfig** command must be used at system startup to define the network address of each interface present on a machine. After system startup, it can also be used to redefine an interfaces address and its other operating parameters. The network interface configuration is held on the running system and must be reset at each system restart. The **ifconfig** command interprets the **IFF_MULTICAST** flag and prints its value if it is set.

An interface can receive transmissions in differing protocols, each of which may require separate naming schemes. It is necessary to specify the *AddressFamily* parameter, which may change the interpretation of the remaining parameters. The address families currently supported are **inet** and **inet6**.

For the DARPA-Internet family, **inet**, the address is either a host name present in the host name database, that is, the **/etc/hosts** file, or a DARPA-Internet address expressed in the Internet standard dotted decimal notation.

While any user can query the status of a network interface, only a user who has administrative authority can modify the configuration of those interfaces.

The ifconfig function displays the current configuration for a network interface when no optional parameters are supplied.

If a protocol family is specified, ifconfig will report only the details specific to that protocol family.

Only a super user may modify the configuration of a network interface.

Gratuitous ARP is supported for Ethernet, token-ring, and FDDI interfaces. This means when an IP address is assigned, the host sends an ARP request for its own address (the new address) to inform other machines of its address so that they can update their ARP entry immediately. It also lets hosts detect duplicate IP address. If you get a response to the ARP request, an error is logged in /var/adm/ras/errlog which can be viewed using errpt command (or using SMIT interface) for the error ID AIXIF_ARP_DUP_ADDR.

Note: Any changes made to the attributes of an interface using the ifconfig command will be lost when the system is rebooted.

Flags

-a

	ifconfig to display information about all interfaces in the system.
-d	The -d flag displays interfaces that are down. You can use the flag only with the -a or -I
	flag.
-l	This flag may be used to list all available interfaces on the system, with no other
	additional information. Use of this flag is mutually exclusive with all other flags and
	commands, except for -d and -u.

Optionally, the -a flag may be used instead of an interface name. This flag instructs

The -u flag displays interfaces that are up. You can use the flag only with the -a or -I flag. ProtocolFamily This flag specifies protocols such as tcp, udp, tcp6, udp6, icmp, and icmp6.

Parameters

Address	Specifies the network address for the network interface. For the inet family, the <i>Address</i> parameter is either a host name or an Internet address in the standard dotted decimal notation.
AddressFamily	Specifies which network address family to change. The inet and inet6 address families are currently supported. This parameter defaults to the inet address family.
DestinationAddress	Specifies the address of the correspondent on the remote end of a point-to-point

link.

Interface

Specifies the network interface configuration values to show or change. You must specify an interface with the *Interface* parameter when you use the **ifconfig** command. Abbreviations for the interfaces include:

- at for ATM (Asynchronous Transfer Mode)
- · en for Standard Ethernet (inet)
- et for IEEE 802.3 Ethernet (inet)
- gre for Generic Routing Encapsulation tunnel pseudo-interface (inet)
- tr for Token-Ring (inet)
- xt for X.25 (inet)
- · sl for serial line IP (inet)
- · lo for loopback (inet)
- · op for serial (inet)
- · vi for Virtual IP Address (inet)

Include a numeral after the abbreviation to identify the specific interface (for example, $tr\theta$).

If *Interface* is not yet loaded, **ifconfig** *Interface* loads that interface and **netstat** -in lists it. In processing a status query for *Interface*, that interface is loaded (if not already loaded) to complete the query processing.

Allows the following parameter values:

alias Establishes an additional network address for the interface. When changing network numbers, this parameter is useful for accepting packets addressed to the old interface.

allcast Sets the Token-Ring interface to broadcast to all rings on the network.

-allcast

Confines the Token-Ring interface to broadcast only to the local ring.

arp Enables the **ifconfig** command to use the Address Resolution Protocol in mapping between network-level addresses and link-level addresses. The **arp** value is the default.

-arp Disables the use of the Address Resolution Protocol.

authority

Reserved for future use.

bridge Reserved for future use.

-bridge Reserved for future use.

broadcast Address

(**inet** only) Specifies the address to use to broadcast to the network. The default broadcast address has a host part of all 1s.

checksum_offload

Enables the flag to indicate that transmit TCP checksum should be offloaded to the adapter. The command will also reset the per-interface counter that determines whether TCP should dynamically enable or disable offloading of checksum computation.

-checksum_offload

Disables transmit TCP checksum offloading.

-dad (inet6 only) Does not perform duplicate IPv6 address detection.

-debug Disables driver-dependent debug code.

Parameter

Removes the specified network address. This is used when an alias is incorrectly specified or when it is no longer needed. Incorrectly setting an ns address has the side effect of specifying the host portion of the network address. Removing all ns addresses allows you to re-specify the host portion.

device dev name

This parameter applies to ATM Network interface only. It specifies the device name this interface is associated with. Unlike Token Ring or Ethernet, in case of ATM, there is not a one-to-one correspondence between interface and device. In the case of ATM, there can be more than one interface for every device.

detach Removes an interface from the network interface list. If the last interface is detached, the network interface driver code is unloaded. In order for the interface route of an attached interface to be changed, that interface must be detached and added again with ifconfig.

Marks an interface as inactive (down), which keeps the system from down trying to transmit messages through that interface. If possible, the ifconfig command also resets the interface to disable reception of messages. Routes that use the interface, however, are not automatically disabled.

(inet6 only) The real IPv6 address is computed by replacing the last 64 eui64 bytes of the given address with the Interface Identifier.

first Puts an IPv6 address at the first place on an interface in order to select it as the source for unbound sockets. The syntax for using this parameter is.

ifconfig interface inet6 first address

firstalias

(inet6 only) Same as alias, but sets the address in front of the interface address list in order to select it as the source for unbound sockets.

group ID

Adds a group ID to the group ID list for the interface. This list is used in determining the route to use when forwarding packets that arrived on the interface.

-group ID

Removes a group ID from the group ID list for the interface. This list is used in determining the route to use when forwarding packets that arrived on the interface.

hwloop

Enables hardware loopback. The hardware loopback specifies that locally addressed packets handled by an interface should be sent out using the associated adapter.

-hwloop

Disables hardware loop-back. The hardware loop-back specifies that locally addressed packets handled by an interface should be sent out using the associated adapter.

ipdst Specifies an Internet host willing to receive IP packets encapsulating ns packets bound for a remote network. An apparent point-to-point link is constructed, and the specified address is taken as the ns address and network of the destination.

ipv6dst

Used to specify an IPv6 node that is willing to receive IPv6 packets encapsulating IPv6 or IPv4 packets through a tunnel. The apparent destination of the point to point tunnel interface may not be the real destination of the packets. At the tunnel endpoint, the decapsulated packets may then be forwarded to their final destination.

largesend

Enables one LPAR to send large data in a single packet to another LPAR. It works similarly to **largesend** over real adapters except in this case there is no TCP segmentation done. If the SEA on VIOS supports **largesend**, the LPAR can transmit large data, which will get segmented by the real adapter on SEA. Use the **chdev** command to enable the **largesend** attribute on SEA.

-largesend

Disables largesend over virtual Ethernet. This is the default.

link [0-2]

Enables special processing of the link level of the interface. These three options are interface-specific. In actual effect, however, they are generally used to select special modes of operation. An example of this is to enable SLIP compression, or to select the connector type for some Ethernet cards. Refer to the manual page for the specific driver for more information.

-link [0-2]

Disables special processing at the link level with the specified interface.

metric Number

Sets the routing metric of the interface to the value specified by the *Number* variable. The default is 0 (zero). The routing metric is used by the routing protocol (the **routed** daemon). Higher metrics have the effect of making a route less favorable. Metrics are counted as addition hops to the destination network or host.

monitor

Enables the underlying adapter to notify the interface layer of link status changes. The adapter must support link status callback notification. If multipath routing is used, alternate routes are selected when a link goes down.

-monitor

Disables adapter link status monitoring.

mtu Value

Sets the maximum IP packet size for this system. The *Value* variable can be any number from 60 through 65535, but is media dependent. See Automatic configuration of network interfaces in *Networks and communication management* for maximum transmission unit (MTU) values by interface.

netmask Mask

Specifies how much of the address to reserve for subdividing networks into subnetworks. This parameter can be used only with an address family of inet.

The Mask variable includes both the network part of the local address and the subnet part, which is taken from the host field of the address. The mask can be specified as a single hexadecimal number beginning with 0x, in standard Internet dotted decimal notation, or beginning with a name or alias that is listed in the /etc/networks file.

In the 32-bit address, the mask contains 1s (ones) for the bit positions reserved for the network and subnet parts and 0s for the bit positions that specify the host. The mask should contain at least the standard network portion, and the subnet segment should be contiguous with the network segment.

pvc This parameters applies to ATM Network interface only. It specifies that this interface will support PVC (Permanent Virtual Circuit) types of virtual connections only.

pktchain

Enables the flag to indicate that this interface can handle multiple packets chained together on the output path.

-pktchain

Disables the flag that indicates that this interface can handle multiple packets chained together on the output path.

svc c server addr

This parameter applies to ATM Network interface only. It specifies that this interface will support both SVC (Switched Virtual Circuit) and PVC types of virtual connections. It further specifies that this interface will be an ARP client. The server_addr is the list of 20 byte ATM address of the ARP servers that this client will use. The addresses are specified in the form of xx.xx....xx. The first entry is considered the Primary ARP server and the rest are considered Secondary ARP servers. The list of 20 byte ARP server addresses must separated by a comma.

site6 Sets the IPv6 site number (default is zero). This should be used only with site-local addresses on a multi-sited node.

This parameter applies to ATM Network interface only. It specifies that SVC_S this interface will support both SVC and PVC types of virtual connections. It further specifies that this interface will be the ARP server for this Logical IP Subnetwork (LIS).

security

Reserved for future use.

Reserved for future use. snap

-snap Reserved for future use.

tcp_low_rto

Enables the use of lower retransmission timeouts (RTO) for TCP connections on a low latency, fast network, such as Gigabit Ethernet and 10 Gigabit Ethernet). If the networks experience packet drops, the respective TCP connections use the rto value for RTO. The rto values range from 0-3000 ms. This runtime option must be set in the if_isno flags field. The use_isno option must also be set for this flag to be effective.

tcp_nocksum

Disables verification of the checksum of TCP data for local traffic to the subnet attached to the interface. Checksum verification of TCP, UDP and IP headers continues. Checksum verification of TCP data read or written from this interface from or to remote networks also continues.

-tcp_nocksum

Enables verification of the checksum of TCP data for local traffic to the subnet attached to the interface. This is the default.

thread (inet only) Configures dedicated kernel threads for an interface. This parameter can only be used on SMP machines that have multiple CPU's. This parameter causes input packets to be queued to a kernel thread after processing by the device driver and input demuxer. The input packet is processed in IP and TCP or UDP by the thread instead of directly on the interrupt level. Setting this parameter can improve throughput when high speed adapters bottleneck on a single CPU during interrupt processing by allowing the input packets to be processed on other CPU's running the kernel threads (improved pipelining). For some work loads, this parameter increases the per packet overhead, due to thread scheduling overhead, resulting in higher CPU utilization an possibly lower throughput. This parameter only applies to AIX 4.3.3 or later.

-thread (inet only) Disables kernel thread support that has been configured with the *thread* parameter. This parameter only applies to AIX 4.3.3 or later.

up Marks an interface as active (up). This parameter is used automatically when setting the first address for an interface. It can also be used to enable an interface after an ifconfig down command.

vipa_iflist

Adds the interfaces to the list of interfaces that should use this **vipa** as the source address in the outgoing packets.

-vipa_iflist

Removes the interfaces from the list of interfaces that are configured to use this **vipa** as the source address in the outgoing packets.

Specifies the retransmission timeout in milliseconds. The range for this value is 0-3000.

Requirement: You must set the timer_wheel_tick value of the **no** Command before setting the *rto* value using the **ifconfig** Command. The *rto* value that you specify must be equal to or a multiple of 10 times the timer_wheel_tick value that is set.

In AIX 4.3.3 and later versions, the following network options, commonly known as ISNO (Interface Specific Network Options), can be configured on a per interface basis:

rfc1323 [0 | 1]

Enables or disables TCP enhancements as specified by RFC 1323, *TCP Extensions for High Performance*. A value of 1 specifies that all TCP connections using this interface will attempt to negotiate the RFC enhancements. A value of 0 disables **rfc1323** for all connections using this interface. The SOCKETS application can override this ISNO and global behavior on individual TCP connections with the **setsockopt** subroutine.

-rfc1323

Removes the use of ISNO for **rfc1323** for this network. A SOCKETS application can override the global behavior on individual TCP connections using the **setsockopt** subroutine.

rto

tcp_mssdflt Number

Sets the default maximum segment size used in communicating with remote networks. If communicating over this interface, a socket uses *Number* as the value of the default maximum segment size.

-tcp_mssdflt

Removes the use of ISNO for tcp_mssdflt. The global value, manipulated via /usr/sbin/no, is used instead.

tcp_recvspace Size

Specifies the default socket buffer *Size* for interface sockets receiving data. The buffer size affects the window size used by TCP. (See the **no** command for more information.)

-tcp_recvspace

Removes the use of ISNO for **tcp_recvspace**. The global value is used instead.

tcp_sendspace Size

Specifies the default socket buffer *Size* for interface sockets sending data. The buffer size affects the window size used by TCP. (See the **no** command for more information.)

-tcp_sendspace

Removes the use of ISNO for tcp_sendspace. The global value is used instead.

tcp_nodelay [0 | 1]

Specifies that sockets using TCP over this interface follow the Nagle algorithm when sending data. By default, TCP follows the Nagle algorithm.

-tcp_nodelay

Removes the use of ISNO for the tcp_nodelay option.

Tip: Parameters that you set using the **ifconfig** command are lost the next time you restart your system. Use the **chdev** command to change the ODM database for each interface to make parameter changes permanent. Use the **lsattr -E -I** [interface] command to view the interface attributes and use the **chdev -I** [interface] **-a** [attribute=value] command to change the attribute. For example:

```
lsattr -E -l en0
chdev -l en0 -a tcp sendspace=65536
```

Examples

1. To query the status of a serial line IP interface, enter the command in the following format:

```
ifconfig sll
```

In this example, the interface to be queried is \$11. The result of the command looks similar to the following:

```
sl1: flags=51<UP,POINTOPOINT,RUNNING>
inet 192.9.201.3 --> 192.9.354.7 netmask ffffff00
```

2. To configure the local loop-back interface, enter the command in the following format:

```
ifconfig lo0 inet 127.0.0.1 up
```

3. To mark the local token-ring interface as down, enter the command in the following format:

```
ifconfig tr0 inet down
```

In this example, the interface to be marked is token0.

Note: Only a user with root user authority can modify the configuration of a network interface.

4. To turn rfc1323 off for all connections over en5 (assuming that the global value is 1), enter:

```
ifconfig en0 rfc1323 0
```

5. To configure a list of interfaces to use a vipa, enter:

ifconfig vi0 vipa iflist en0,en1,tr0

6. To remove interfaces that are configured to use vipa, enter:

```
ifconfig vi0 -vipa iflist en1,tr0
```

7. To find out which interfaces are configured to use a vipa, say vi0, enter:

```
ifconfig vi0
```

8. To enable link status monitoring, enter:

```
ifconfig en0 monitor
```

If the link status on adapter ent0 changes to down, the adapter notifies the interface layer, which causes the interface to also be marked as down.

9. To configure a Generic Routing Encapsulation (GRE) tunnel between the interfaces of two nodes, enter:

```
ifconfig gre0 tunnel 9.3.149.70 9.3.149.121
```

This creates a GRE tunnel between the local interface 9.3.149.70 and the remote interface 9.3.149.121. The local end of the tunnel is identified by gre0.

10. To associate an IP address with the newly created interface, enter:

```
ifconfig gre0 10.10.10.1
```

11. To configure NAT on a GRE tunnel, enter:

```
ifconfig gre0 nat toaddr 127.0.0.1 fromport 80 toport 8080
```

In this example, the original destination port of the GRE packet is 80 and the command changes the destination port to 8080 and the destination address to 127.0.0.1.

Files

/etc/host Contains the host-name database.

/etc/networks Contains network names.

Related Information

The netstat command.

The hosts file format, networks file format.

TCP/IP network interfaces, TCP/IP protocols, TCP/IP routing, Subnet addresses in *Networks and communication management*.

ike Command

Purpose

Starts, stops, and monitors IP Security dynamic tunnels which use the Internet Key Exchange Protocol (ISAKMP/Oakley).

Syntax

ike cmd=Subcommand [parameter ...]

Description

The **ike** is used to start, stop, and monitor IP Security dynamic tunnels using the Internet Key Exchange (IKE) protocol. IP Security tunnels protect IP traffic by authenticating and/or encrypting IP data. The **ike**

command performs several functions. It can activate, remove, or list IKE and IP Security tunnels. For an overview of IP Security and IKE tunnels, see Internet Protocol security in the Security.

Note: You must have root access to use the ike command.

The IKE negotiation occurs in two phases. The first phase authenticates the two parties and sets up a **Key** Management (also known as phase 1) Security Association for protecting the data that is passed during the negotiation. In this phase the key management policy is used to secure the negotiation messages. The second phase negotiates Data Management (also known as the phase 2) Security Association, which uses the data management policy to set up IP Security tunnels in the kernel for encapsulating and decapsulating data packets. The secure channel established in phase 1 can be used to protect multiple data management negotiations between 2 hosts.

The ike command is used to activate tunnels with identification and policy information which has already been entered using the ikedb command or the Web-based System Manager Graphical User Interface (GUI) under Virtual Private Networks (IP Security) in the Network application. The parameters to be used during the negotiation are entered by the user and stored in a database. The ike command allows the activation, removal and listing of tunnels that have been started using the security parameters stored in the database.

In most uses of the ike command, activation and deletion occurs for both phases, however the command allows these operations to be done separately.

Subcommands

activate

Purpose

Start the negotiation of an IKE tunnel. If phase is not specified, both a phase 1 and phase 2 tunnel are started. If IP addresses are supplied, the tunnel is setup using those IP addresses. If the IDs used during the negotiation are not IP addresses, the local and remote host IDs must be entered using the Virtual Private Networks Web-based System Manager Graphical User Interface (GUI) panels. A unique tunnel number is created. The tunnel can then be referenced by the tunnel number in the ike command to indicate the particular tunnel to be started.

Syntax

ike cmd=activate [phase=1|2] [numlist=tunnel num list] [namelist=tunnel name list] [remid=remote_id] [ipaddr=src_addr,dst_addr] [autostart]

Description

The activate subcommand works using a two phase paradigm. A phase 1 tunnel must be established before a phase 2 tunnel can be started. If a phase 1 tunnel is specified, then only the phase 1 tunnel negotiation takes place. If a phase 2 tunnel is specified, the system checks for the existence of the corresponding phase 1 tunnel before creating the phase 2 tunnel. If the phase 1 negotiation has not been started, it is started automatically.

Upon successful completion of a phase 2 tunnel, the tunnel definition and corresponding filter rules are inserted into the IP Security kernel, and the new tunnel is activated. Traffic described by the tunnel definition passing between the designated endpoints is protected by the encryption and authentication algorithms indicated by the associated IKE security policy.

Multiple phase 2 tunnels can be started under the same phase 1 tunnel. A situation where this may be desired is if different types of traffic between two endpoints need different levels of security protection. The Security Association used for the phase 1 tunnel can be shared by multiple phase 2 tunnels. The phase 2 tunnels would specify the type of traffic (by protocol and port, or subnet mask, for instance) and could have different security policies protecting them.

The **ike** command returns if either a negotiation has been initiated, an error returns, or the tunnel already exists. Since the remote host must be contacted during the negotiation and the amount of time needed to complete the negotiation is uncertain, the list subcommand should be used to determine if the negotiation was successful.

Errors that are detected during the negotiation process can be captured by using syslog.

Flags

phase Specifies the type of negotiation desired. If omitted, the **activate** subcommand activates both a phase 1 and phase 2 tunnel. The **phase** flag is an optional flag.

numlist

Initiates the **ike** tunnel number which corresponds to the desired phase 1 or phase 2 tunnel(s) to be started. The , (comma) and - (dash) characters can be used to delimit values and indicate ranges. The **list** subcommand with the database option **db** can be used to determine the tunnel number for a particular tunnel. An example using tunnel numbers is shown below:

ike cmd=activate numlist=1,3,5-7

This would start tunnels 1, 3, 5, 6 and 7.

remid

Starts phase 1 or phase 2 tunnel(s) from the local ID to the specified remote ID. **remid** could be a phase 1 ID (such as IP address, FQDN, user FQDN and X500DN), a phase 2 ID (such as IP address, subnet and IP address range) or a group ID. The , (comma) is used to delimit the subnet id and subnet mask, and the starting and ending IP address. If **remid** is a group name, a tunnel is initiated for each group member. **remid** is an optional flag and can only be used with the **activate** subcommand. It cannot be used in conjunction with the **ipaddr**, **numlist** or **namelist** flags.

- 1. To activate a phase 1 tunnel to remote IP address 9.3.97.100, type:
 - ike cmd=activate phase=1 remid=9.3.97.100
- 2. To activate a phase 2 tunnel to remote subnet ID 9.3.97.100,255.255.255.0, type:

ike cmd=activate phase=2 remid=9.3.97.100,255.255.255.0

ip_addr

Starts a phase 1 or phase 2 tunnel between the specified IP Addresses.

autostart

Causes the activation of all phase 1 and phase 2 tunnel database entries which were created with the **autostart** parameter set. The **autostart** flag does not work in conjunction with any other flags pertaining to the **activate** subcommand.

namelist

Specifies a tunnel name or comma-separated list of tunnel names to be activated. This flag requires the use of the **phase** flag.

Examples

1. To activate a phase 2 tunnel between source IP address x.x.x.x and destination IP address y.y.y.y, enter:

ike cmd=activate phase=2 ipaddr=x.x.x.x,y.y.y.y

The security policy indicated in the database for the IP addresses x.x.x.x and y.y.y.y is used for activating the tunnel.

2. To activate phase 1 tunnels for tunnels 1 and 2, enter:

ike cmd=activate phase=1 numlist=1,2

To activate phase 2 tunnels for inactive tunnels named AIXFW1_DM and remote_office in the database enter:

ike cmd=activate phase=2 namelist=AIXFW1 DM, remote office

Note: Because each phase 2 tunnel must have an associated phase 1 tunnel, a phase 1 tunnel is automatically activated before the phase 2 tunnel is activated.

list

Purpose

Monitors the status of IP Security tunnels by phase. It is also used to view tunnel entries defined in the IKE database.

Syntax

ike cmd=list [phase=1|1+|2] [numlist= tunnel_num_list] [db | role=i|r] [verbose]

Description

The list subcommand queries the Tunnel Manager and lists phase 1 and phase 2 tunnel status and information according to the result of the query. This command can also be used to view information in the Tunnel Definition database. The default behavior is to list the tunnels currently active. To list the tunnels in the database, the db option must be used.

Flags

Indicates the type and order of the tunnel(s) to be listed. A phase value of 1 results in only the requested phase 1 tunnel information being displayed. A phase value of 2 results in the information for the requested phase 2 tunnel(s) and their associated phase 1 tunnel(s) should be displayed. A phase value of 1+ means that the requested phase 1 tunnel and all associated phase 2 tunnels should be displayed. The default phase value is 1+.

numlist

Lists of the tunnel numbers which you would like to view. If omitted, the information from all tunnels is displayed. The , (comma) and - (dash) characters can be used to delimit values and indicate ranges. For example:

ike cmd=list numlist=1,3,5-7

When used in conjunction with db, tunnels from the IKE Security Policy database are

Note: Active tunnel numbers and tunnel numbers from the IKE Tunnel Definitions database do not necessarily match up. This is because a single tunnel entry in the database can correspond to multiple active tunnels.

db Shows the entries in the database. If this flag is omitted, only active tunnels are displayed. This cannot be used in conjunction with role. Supply the list of tunnel numbers which you would like to view.

Allows the display of tunnels by the point of initiation. If i is specified, then the tunnels that role were initiated by the local host are displayed. If r is specified, then the tunnels where the local host acted as a responder are displayed. If this flag is omitted, both initiator and responder tunnels are shown. This flag cannot be used in conjunction with db.

verbose

Shows extended information about the specified tunnels. If this flag is not specified, then only a concise entry for each tunnel is shown.

Examples

Note: Tunnel numbers from the database and tunnel numbers from the tunnel manager do not necessarily reflect the same tunnel.

1. To perform a concise (short form) listing of phase 1 tunnels with entries in the tunnel manger, enter:

ike cmd=list phase=1 numlist=1,2,3

These tunnels are either being negotiated, in the active state, or have expired. Only tunnels 1, 2, and 3 are listed. Tunnels can be either initiator or responder role.

2. To perform a concise (short form) listing of of the specified phase 2 tunnels in the database with each preceded by the associated phase 1 tunnel, enter:

ike cmd=list phase=2 numlist=1-3 db

These are tunnels defined in the database which may or may not be currently active in the tunnel manager. All tunnels in the database are used in the initiator role only.

3. To perform a verbose (long form) listing of a phase 1 tunnel followed by all of its associated phase 2 tunnels from the tunnel manager, enter:

ike cmd=list phase=1+ role=r verbose

Only tunnels which were activated in the responder role are listed. All available tunnel numbers are listed since no **numlist** was specified.

remove

Purpose Syntax

Deactivates specified phase 1 or phase 2 tunnel(s).

Description

ike cmd=remove [phase=1|2] [numlist= tunnel_num_list] [all]

The remove subcommand requests the deactivation of phase 1 or phase 2 tunnel(s). Because phase 2 tunnels are associated with a phase 1 tunnel, if a phase 1 tunnel is deactivated, all phase 2 tunnels under the phase 1 tunnel are not refreshed when the phase 2 tunnel lifetime expires.

Flags

phase Indicates the phase of the tunnel to be deactivated and must be specified. A phase value of 1 refers to a phase 1 tunnel and a phase value of 2 refers to a phase 2 tunnel.

numlist

Lists the tunnel numbers you would like to deactivate. The , (comma) and - (dash) characters can be used to delimit values and indicate ranges. For example: $\frac{1}{2} \left(\frac{1}{2} \right) = \frac{1}{2} \left(\frac{1}{2} \right) \left(\frac{1}$

ike cmd=remove numlist=1,3,5-7

When **numlist** is omitted, all tunnels are deactivated.

all Deactivates all active tunnels. This parameter does not work in conjunction with numlist.

Examples

1. To deactivate phase 1 tunnels numbered 1, 2, and 3, enter:

ike cmd=remove phase=1 numlist=1-3

2. To deactivate all phase 1 and phase 2 tunnels, enter:

ike cmd=remove all

3. To deactivate all phase 2 tunnels but keep all phase 1 tunnels active, enter:

ike cmd=remove phase=2 all

4. To deactivate all phase 1 tunnels (corresponding phase 2 tunnels will not be refreshed), enter: ike cmd=remove phase=1 all

log

Purpose Syntax Read the ISAKMP daemon log level from /etc/isamkpd.conf and start logging at that level.

ike cmd=log

Note: If the log level or the output file name in /etc/syslog.conf are changed, the refresh -s

syslogd command must also be run.

Description

The **log** subcommand causes the ISAKMP daemon to read the log level from **/etc/isakmpd.conf**, and a filename from **/etc/syslog.conf**. The logging level specified is set and the log output, along with other **syslog** output, is placed in the file specified.

Note: There are four valid logging levels for the ISAKMP daemon. They are **none**, **errors**, **events**, and **information**. **none** means no logging, **errors** means logging of only ISAKMP daemon errors will occur, **events** means errors and other ISAKMP daemon events will be logged, and **information** is the highest level of logging which is all inclusive.

Files

/usr/sbin/ikeLocation of the ike admin commands./etc/isakmpd.confConfiguration file for the iksakmpd daemon.

/etc/syslog.conf Provides configuration information for the **syslogd** daemon.

Related Information

The **syslog** subroutine.

The syslog.conf file.

The **syslogd** daemon.

The ikedb command.

ikedb Command

Purpose

Retrieves, updates, deletes, imports, and exports information in the IKE database.

Syntax

```
ikedb -p[F s] [ -e entity-file ] [ XML-file ]
ikedb -g[r] [ -t type [ -n name | -i ID -y ID-type ] ]
ikedb -d -t type [ -n name | -i ID -y ID-type ]
ikedb -c[F] [ -l linux-file ] [ -k secrets-file ] [ -f XML-file ]
ikedb -x
ikedb -o
```

Description

The **ikedb** command allows the user to write to (**put**) or read from (**get**) the IKE database. The input and output format is an Extensible Markup Language (XML) file. The format of an XML file is specified by its Document Type Definition (DTD). The **ikedb** command allows the user to see the DTD that is used to validate the XML file when doing a put. While entity declarations can be added to the DTD using the **-e** flag, this is the only modification to the DTD that can be made.

Any external DOCTYPE declaration in the input XML file will be ignored and any internal DOCTYPE declaration might result in an error. The rules followed to parse the XML file using the DTD are specified in the XML standard. /usr/samples/ipsec has a sample of what a typical XML file that defines common tunnel scenarios looks like.

Flags

- -p Performs a put, which writes to the database, based on the given XML-file.
 - **F** Forces a **put**, even if a specified tunnel, protection, proposal, group, or pre-shared key would overwrite one that already exists in the database. The default is for such **put** attempts to fail.
 - -s Swaps the local and remote IDs of all tunnels. This facilitates importing a tunnel generated by a peer machine. This flag only affects tunnels. This option is illegal if the remote ID of any tunnel is a group.
 - -e entity-file

Specifies the name of the file containing the <!ENTITY ...> lines as defined by *entity-file*. These lines are added to the internal DTD and allow the user to include XML files in other XML files.

XML-file

Specifies the **XML-file** to be used and must be the last argument to be displayed in the command line. The *XML-file* determines whether the write is to a tunnel, protection, proposal, group, pre-shared key, or all of these. If no *XML-file* is specified, input is read from **stdin**. A - (hyphen) can also be used to specify **stdin**.

- -g Performs a get, which displays what is stored in the IKE database. Output is sent to stdout and is in XML format, which is suitable for processing with ikedb -p.
 - -r Recursive. If this flag is specified for a phase 1 tunnel, information is also returned for all associated phase 2 tunnels and all protections and proposals associated with both sets of tunnels.
 - -t type Specifies the type of output requested. Type can have the value of any of the XML elements under AIX_VPN, such as IKETunnel, IPSecProtection, and so on. If omitted, the entire database is output.
 - -n name

Specifies the *name* of the requested object. *Name* can be the name of a proposal, protection, tunnel, or group, depending on the value of the **-t** flag. The **-n** flag is valid with all values specified by the **-t** flag, except **IKEPresharedKey**. If omitted, all objects of the specified *type* will be output.

-i *ID* Specifies the *ID* associated with a pre-shared key. The -i flag is only valid with the **IKEPresharedKey** value of the -t flag. If omitted, all objects of the specified *type* will be output. The -i flag must be used in conjunction with the -y flag.

-y ID-type

Specifies the *ID-type* defined by the **-i** flag. ID-type can be any of the legal types allowed in the XML file, such as **User_FQDN**, **IPV4_Address**, and so on. The **-y** flag must be used in conjunction with the **-i** flag.

- -d Performs a **delete** on the specified item from the database. The flags are the same as for the -g flag, except that -r is not supported.
- -c Performs a conversion from a Linux[®] IPSec configuration file to an AIX IPSec configuration file in XML format. It requires as input one or two files from Linux, a configuration file, and possibly a secrets file with pre-shared keys.
 - -F Forces a **put**, even if a specified tunnel, protection, proposal, group, or pre-shared key would overwrite one that already exists in the database. The default is for such **put** attempts to fail. The -F flag has no effect if the -f flag is also used.
 - -I linux-file

Specifies the Linux configuration file as define by *linux-file*. If no file is specified, the system looks for the **ipsec.conf** file in the current directory.

-k secrets-file

Specifies the Linux pre-shared keys file as defined by the *secrets-file* parameter. If no file is specified, the system looks for the **ipsec.secrets** file in the current directory.

-f XML-file

Specifies the XML configuration file to which the Linux configuration files are converted. The default behavior is to do a **put** directly to the IKE database. If the filename given is a hyphen (-), the results are sent to **stdout**.

- -x Performs an **expunge** on the database. This empties out the database.
- Performs an output of the DTD that specifies all elements and attributes for an XML file that is used by the ikedb command. The DTD is sent to stdout.

Files

/usr/samples/ipsec Examples of an XML file that sets up various tunnel configurations.

Examples

1. To **put** definitions to the IKE database from an XML file that has been generated on a peer machine and overwrite any existing objects in the database with the same name, type:

```
ikedb -pFs peer tunnel conf.xml
```

peer_tunnel_conf.xml is the XML file generated on a peer machine.

2. To get the definition of the phase 1 tunnel named tunnel sys1 and sys2 and all dependent phase 2 tunnels with respective proposals and protections, type:

```
ikedb -gr -t IKETunnel -n tunnel sys1 and sys2
```

3. To **delete** all preshared keys from the database, type:

```
ikedb -d -t IKEPresharedKey
```

imake Command

Purpose

C preprocessor interface to the **make** command.

Syntax

```
imake [ -DDefine ] [ -IDirectory ] [ -TTemplate ] [ -f FileName ] [ -C FileName ] [ -s FileName ] [ -e ] [ -v ]
```

Description

The imake command generates Makefiles from a template, a set of cpp macro functions, and a per-directory input file called Imakefile. This command keeps machine dependencies (such as compiler options, alternate command names, and special make command rules) separate from the descriptions of the items to build.

imake invokes cpp with any -I or -D flags passed on the command line and passes to it the following three lines:

```
#define IMAKE TEMPLATE "Imake.tmpl"
#define INCLUDE MAKEFILE "Imakefile"
#include IMAKE TEMPLATE
```

Override Imake.tmpl and Imakefile by using the -T and -f flags, respectively.

The IMAKE TEMPLATE typically reads the following files:

- · A machine-dependent parameters file in which the parameters are specified as cpp symbols
- A site-specific parameters file
- A file that defines variables
- A file containing cpp macro functions for generating make command rules
- The Imakefile (specified by INCLUDE IMAKEFILE) in the current directory.

The **Imakefile** file uses the macro functions to indicate what targets to build and the **imake** command generates the appropriate rules.

Imake configuration files contain two types of variables, imake variables and make variables. The imake variables are interpreted by cpp when the imake command is run. By convention, they are not case-sensitive. The make variables are written into the Makefile for later interpretation by the make command. By convention, make variables are uppercase.

The rules file (usually named Imake.rules in the configuration directory) contains a variety of cpp macro functions that are configured according to the current platform. The imake command replaces any occurrences of the string ``@@" with a newline character (carriage return) to support macros that generate more than one line of make rules. For example, the macro:

```
#define
         program target(program, objlist)
                                                00/
program: objlist
         $(CC) -o $@ objlist $(LDFLAGS)
```

when called with program target (foo, foo1.0 foo2.0) will expand to:

```
foo: foo1.o foo2.o 
$(CC) -o $@ foo1.o foo2.o $(LDFLAGS)
```

On systems whose cpp reduces multiple tabs and spaces to a single space, the **imake** command attempts to put back any necessary tabs (the **make** command distinguishes between tabs and spaces). For this reason, precede all colons (:) in command lines by a backslash (\).

Use with AlXwindows

AlXwindows uses the **imake** command extensively for both full builds within the source tree and builds of external software. Two special variables, TOPDIR and CURDIR, are set to make referencing files using relative path names easier. For example, the following command is generated automatically to build the **Makefile** in the **lib/X** directory (relative to the top of the sources):

To build AlXwindows programs outside the source tree, a special symbol, UseInstalled, is defined and the TOPDIR and CURDIR variables are omitted. If the configuration files are properly installed, you can use the **xmkmf** command.

The **imake** command reads the following files as used by AlXwindows.

Note: The indented format indicates files that include other files.

```
Imake.tmpl
                           generic variables
  site.def
                           site-specific, BeforeVendorCF defined
        *.cf
                           machine-specific
            *Lib.rules shared library
                         site-specific, AfterVendorCF defined
  site.def
  Imake.rules
                           rules
  Project.tmpl
                           X-specific variables
        *Lib.tmpl
                           shared library variables
Imakefile
  Library.tmpl
                           library rules
  Server.tmpl
                           server rules
  Threads.tmpl
                           multi-thread rules
```

Note: The **site.def** file is included twice, both before and after the ***.cf** file. Although most site customizations are specified after the ***.cf** file, some, such as the choice of compiler, need to be specified before, because other variable settings may depend on them.

The first time the **site.def** file is included, the **BeforeVendorCF** variable is defined, and the second time, the **AfterVendorCF** variable is defined. All code in the **site.def** file should be placed inside a **#ifdef** macro for one of these symbols.

Flags

-D Define	Passed directly to cpp to set directory-specific variables. For example, X-windows uses this flag to set the TOPDIR variable to the name of the directory containing the top of the core distribution, and the CURDIR variable to the name of the current directory, relative to the top.
-е	Indicates that the imake command should execute the generated Makefile . The default is to leave this to the user.
-f FileName	Specifies the name of the per-directory input file. The default is the Imakefile file.
-IDirectory	(Uppercase i) Passed directly to cpp to indicate the directory in which the imake template and configuration files are located.
-C FileName	Specifies the name of the .c file that is constructed in the current directory. The default is Imakefile.c.
-s FileName	Specifies the name of the make description file to be generated, without invoking the make command. If the <i>FileName</i> variable is a - (dash), the output is written to stdout . The default is to generate, but not execute, a Makefile .

-TTemplate Specifies the name of the master template file (which is usually located in the directory

specified with -I) used by the cpp command. The default is the Imake.tmpl.

-v Indicates that **imake** should print the **cpp** command line that it is using to generate the

Makefile.

Environment Variables

Note: The following environment variables may be set, but their use is not recommended because they introduce dependencies that are not readily apparent when the **imake** command is run.

IMAKEINCLUDE If defined, specifies an include argument for the C preprocessor. For example:

-I/usr/include/local

IMAKECPP If defined, specifies a valid path to a preprocessor program. For example:

/usr/local/cpp

The default is the /lib/cpp program.

IMAKEMAKE Specifies a valid path to a make program such as /usr/local/make. By default, imake uses

whatever make program is found using the execvp subroutine. This variable is only used if

the -e flag is specified.

Example

imake -I/usr/lib/X11/config -DTOPDIR=/usr/lpp/X11/Xamples

Files

/usr/tmp/tmp-imake.nnnnnn Specifies the temporary input file for the cpp preprocessor.

/usr/tmp/tmp-make.nnnnnn Specifies the temporary input file for make.

/lib/cpp The default C preprocessor.

Related Information

The make command, xmkmf command.

imapd Daemon

Purpose

Starts the Internet Message Access Protocol (IMAP) server process.

Syntax

imapd [-c]

Description

The **imapd** command is an IMAP4 server. It supports the IMAP4 remote mail access protocol. Also, it accepts commands on its standard input and responds on its standard output. You normally invoke the **imapd** command with the **inetd** daemon with those descriptors attached to a remote client connection.

The imapd command works with the existing mail infrastructure consisting of sendmail and bellmail.

Flags

-c Suppresses the reverse host name lookup.

Exit Status

All error and status information is written to a logfile if syslogd is configured for logging.

Security

The **imapd** daemon is a PAM-enabled application with a service name of *imap*. System-wide configuration to use PAM for authentication is set by modifying the value of the **auth_type** attribute, in the **usw** stanza of **/etc/security/login.cfg**, to PAM_AUTH as the root user.

The authentication mechanisms used when PAM is enabled depend on the configuration for the **imap** service in **/etc/pam.conf**. The **imapd** daemon requires **/etc/pam.conf** entries for the **auth** and **session** module types. Listed below is a recommended configuration in **/etc/pam.conf** for the **imap** service:

```
#
# AIX imap configuration
#
imap auth required /usr/lib/security/pam_aix
imap session required /usr/lib/security/pam_aix
```

Files

/usr/sbin/imapd Contains the imapd command.

/etc/services Specifies the file with port assignments for required services. The following entry must

be in this file:

imap2 143/tcp # Internet Mail Access Protocol

Related Information

The **pop3d** daemon.

imapds Daemon

Purpose

Starts the Internet Message Access Protocol (IMAP) server process over TSL/SSL.

Syntax

imapds [-c]

Description

The **imapds** command is an IMAP4 server. It supports the IMAP4 remote mail access protocol. Also, it accepts commands on its standard input and responds on its standard output. You normally invoke the **imapds** command with the **inetd** daemon with those descriptors attached to a remote client connection.

The **imapds** command works with the existing mail infrastructure consisting of **sendmail** and **bellmail**.

Flags

Suppresses the reverse host name lookup.

Exit Status

All error and status information is written to a logfile if **syslogd** is configured for logging.

Security

The **imapds** daemon is a PAM-enabled application with a service name of *imap*. System-wide configuration to use PAM for authentication is set by modifying the value of the **auth_type** attribute, in the **usw** stanza of **/etc/security/login.cfg**, to PAM_AUTH as the root user.

The authentication mechanisms used when PAM is enabled depend on the configuration for the **imap** service in **/etc/pam.conf**. The **imapds** daemon requires **/etc/pam.conf** entries for the **auth** and **session** module types. Listed below is a recommended configuration in **/etc/pam.conf** for the **imap** service:

```
#
# AIX imap configuration
#
imap auth required /usr/lib/security/pam_aix
imap session required /usr/lib/security/pam_aix
```

Files

/usr/sbin/imapds /etc/services Contains the **imapds** command.

Specifies the file with port assignments for required services. The following entry must

be in this file:

imaps 993/tcp # imap4 protocol over TLS/SSL

Related Information

The pop3ds daemon.

impfilt Command

Purpose

Imports filter rules from an export file.

Syntax

impfilt [-v 4|6] -f directory [-l filt_id_list]

Description

Use the **impfilt** command to import filter rules from text export file(s) that are generated by the **expfilt** command. IPsec filter rules for this command can be configured using the **genfilt** command, IPsec smit (IP version 4 or IP version 6), or Web-based System Manager in the Virtual Private Network submenu.

Flags

- -v IP version of the rules to be imported. The value of **4** specifies IP version 4 and the value of **6** specifies IP version 6. When this flag is not used, both IP version 4 and IP version 6 are imported.
- **-f** Specifies the directory where the imported text files are to be read.
- -I Lists the IDs of the filter rules to be imported. The filter rule IDs can be separated by ",". If this flag is not used, all filter rules for the applicable IP version(s) in the text export files will be imported.

Related Information

The expfilt command.

importvg Command

Purpose

Imports a new volume group definition from a set of physical volumes.

Syntax

importvg [-V MajorNumber] [-y VolumeGroup] [-f] [-c] [-x] | [-L VolumeGroup] [-n] [-F] [-R] [-I]
PhysicalVolume

Description

The **importvg** command makes the previously exported volume group known to the system. The *PhysicalVolume* parameter specifies only one physical volume to identify the volume group; any remaining physical volumes (those belonging to the same volume group) are found by the **importvg** command and included in the import. An imported volume group is automatically varied unless the volume group is Concurrent Capable. You must use the **varyonvg** command to activate Concurrent Capable volume groups before you access them.

When a volume group with file systems is imported, the <code>/etc/filesystems</code> file is updated with values for the new logical volumes and mount points. After importing the volume group and activating it with the <code>varyonvg</code> command, you must run the <code>fsck</code> command before the file systems can be mounted. However, the mount point information would be missing from the LVCB (logical volume control block) if it is longer than 128 characters. In this case, the <code>importvg</code> command will not be able to update the <code>/etc/filesystems</code> file with the stanza for the newly imported logical volume. You should manually edit the <code>/etc/filesystems</code> file to add a new stanza for this logical volume.

The **importvg** command changes the name of a logical volume if the name already exists in the system. It prints a message and the new name to standard error, and updates the **/etc/filesystems** file to include the new logical volume name. If the **importvg** command renames any filesystem log logical volumes, you must manually update any file systems using that log device to know about the renamed device.

Notes:

- 1. To use this command, you must either have root user authority or be a member of the **system** group.
- AIX Version 4 changed the behavior of **importvg** so that as part of the **importvg** process, the
 volume group is automatically varied on by the system after it is imported. However, if the volume
 group is Concurrent Capable then the **importvg** command prompts you to **varyonvg** the
 imported volume group manually.
- 3. A volume group with a mirrored striped logical volume cannot be back ported into a version older than AIX 4.3.3.

You can use the Volumes application in Web-based System Manager (wsm) to change volume characteristics. You could also use the System Management Interface Tool (SMIT) **smit importvg** fast path to run this command.

Flags

-c This flag is ignored. On AIX 5.2 and higher only Enhanced Concurrent Capable volume groups will be created.

-f Forces the volume group to be varied online.

-L Volume Group

-F

-1

-n

-R

-X

Takes a volume group and learns about possible changes performed to that volume group. Any new logical volumes created as a result of this command emulate the ownership, group identification, and permissions of the /dev special file for the volume group listed in the -y flag. The -L flag performs the functional equivalent of the -F and -n flags during execution.

Restrictions:

- The volume group must not be in an active state on the system executing the -L flag.
- · The volume group's disks must be unlocked on all systems that have the volume group varied on and operational. Volume groups and their disks may be unlocked, remain active and used via the varyonvg -b -u command.
- · The physical volume name provided must be of a good and known state, the disk named may not be in the missing or removed state.
- · If a logical volume name clash is detected, the command will fail. Unlike the basic **importvg** actions, clashing logical volume names will not be renamed.

Provides a fast version of importvg that checks the Volume Group Descriptor Areas of only the disks that are members of the same volume group. As a result, if a user exercises this flag, they must ensure that all physical volumes in the volume group are in a good and known state. If this flag is used on a volume group where a disk may be in missing or removed state, the command may fail or the results may be inconsistent.

Causes the **importvg** command to fail if imfs fails.

Causes the volume not to be varied at the completion of the volume group import into

the system.

Restores the ownership, group ID, and permissions of the logical volume special device files. These values will be restored only if they were set using U, G and P flags of mklv and chlv commands. This flag is applicable only for volume groups of the types big and

scalable.

-V MajorNumber Specifies the major number of the imported volume group.

This flag is ignored. On AIX 5.2 and higher only Enhanced Concurrent Capable volume

groups will be created.

Attention: This entry must be added after the entry used to initiate **srcmstr**.

-y VolumeGroup

Specifies the name to use for the new volume group. If this flag is not used, the system automatically generates a new name.

The volume group name can only contain the following characters: "A" through "Z," "a" through "z," "0" through "9," or "_" (the underscore), "-" (the minus sign), or "." (the period). All other characters are considered invalid.

Examples

1. To import the volume group bkvg from physical volume hdisk7, enter:

importvg -y bkvg hdisk7

The volume group bkvg is made known to the system.

2. To use the -L on a multi-tailed system:

Node A has the volume group datavg varied on. Node B is aware of datavg, but it is not varied on.

Node A: varyonvg -b -u datavg Node B: importvg -L datavg hdisk7

Node A: varyonvg datavg

Files

/usr/sbin Directory where the **importvg** command resides.

/tmp Directory where the temporary files are stored while the command is running.

Related Information

The exportvg command, varyonvg command.

The Logical volume storage in *Operating system and device management* explains the Logical Volume Manager, physical volumes, logical volumes, volume groups, organization, ensuring data integrity, and allocation characteristics.

For information on installing the Web-based System Manager, see Chapter 2: Installation and System Requirements in *AIX 5L Version 5.3 Web-based System Manager Administration Guide*.

The System management interface tool in *Operating system and device management* explains the structure, main menus, and tasks that are done with SMIT.

imptun Command

Purpose

Adds the exported tunnel definitions and optional user-defined filter rules associated with the tunnels to the local host.

Syntax

imptun -f directory [-t tunnel_id_list] [-v 4 | 6] [-n] [-r] [-g] [-l manual]

Description

Use the **imptun** command to add exported tunnel definitions and optional user-defined filter rules associated with the exported tunnels (files generated by the tunnel owner by using the **exptun** command) to the local host. This command can also import tunnel definitions from the exported files generated by the IBM firewall (SNG) product export command.

A new tunnel ID is generated by the local host when a tunnel is imported to the local tunnel table. The auto-generated filter rules associated with the tunnel also is generated automatically. Importing the exported user-defined filter rules is optional.

If the exported files are transmitted by diskette, it is assumed they will be loaded to a local file directory using a command such as **tar**, depending on the tunnel owner's instructions.

Flags

- **-f** Specifies the directory from where the exported files will be read.
- The suppress system auto-generated filter rule flag. If the **-g** flag is not used, the **imptun** command generates two filter rules for each imported tunnel automatically. The auto-generated filter rules allow all traffic between the two end points of the tunnel to go through the tunnel. If the **-g** flag is specified, the command only imports the tunnel ibm definitions, and the user must add user-defined filter rules to use the tunnel.
- -I Specifies the type of the tunnel(s) you want to import. If **manual** is specified, only manual tunnel(s) are imported. -n and -I flags are mutually exclusive.
- -n Specifies that the export files were generated by the IBM firewall (version 2.2) tunnel export command. This flag cannot be specified with the -v flag. The -n flag is also mutually exclusive with the -r flag.
- -r Imports the user-defined filter rules associated with the tunnels that are being imported. To use the -r flag, it must have been specified with the **exptun** command when the exported files were generated. The -r flag is mutually exclusive with the -n flag.

- Lists the set of tunnel IDs to be imported from the export files. The tunnel definitions identified by these -t tunnel IDs are added to the local host. If this flag is not used, all the tunnel definitions in the export files are added to the local host.
- Specifies the IP version of the tunnel definitions from the exported files that you wish to import. If the -v flag is not given, then all IP version 4 and IP version 6 tunnel definitions that exist in the export files are imported.

Related Information

The gentun command, chtun command, rmtun command, exptun command, mktun command, and Istun command.

inc Command

Purpose

Files new mail in a folder.

Syntax

inc [+ Folder] [-noaudit | -audit File] [-changecur | -nochangecur] [-form FormFile | -format String | [-help | [-file File | [-truncate | -notruncate | [-nosilent | -silent] [-width Number]

Description

The **inc** command files incoming mail in a specified folder and outputs a list of the messages filed. A folder is a system directory. By default, the inc command removes the new messages from your mail drop and places them in the specified folder. To file new mail without deleting the mail drop, use the -notruncate flag.

If the specified folder does not exist, the inc command prompts you for permission to create it. The system creates the folder as a subdirectory of the user's Message Handler (MH) directory. The default folder is inbox.

Note: If you do not have a Path: entry specified in your .mh profile file, the inc command creates the folder as a subdirectory of the current directory.

Filed messages are assigned consecutive message numbers starting with the next highest number in the folder. Each new message receives the protection code specified in the Msg-Protect: entry in your .mh profile file. If the Msg-Protect: entry does not exist, a protection code of 644 is assigned. If the Unseen-Sequence: entry exists, new messages are added to each sequence specified by the entry.

Flags

-audit File Copies the current date to the specified file and appends the output of the inc command

to the file.

-changecur Sets the first new message as the current message for the specified folder. This flag is

the default.

-file File Files messages from the specified file instead of the user's maildrop.

+Folder Specifies the folder in which to place new messages. By default, the system creates a

subdirectory called inbox in the user's MH directory.

-form FormFile Identifies a file that contains an alternate output format for the inc command. -format String Specifies a string that defines an alternate output format for the inc command. -help Lists the command syntax, available switches (toggles), and version information.

Note: For MH, the name of this flag must be fully spelled out.

-noaudit Suppresses recording of information about any new messages filed. This is the default.

-nochangecur
 -nosilent
 Prevents alteration of the current message for the specified folder.
 Prompts the user for any necessary information. This flag is the default.

-notruncate Prevents clearing of the mailbox or file from which the **inc** command is taking new

messages. If the **-file** flag is specified, the **-notruncate** flag is the default.

-silent Prevents prompting by the inc command for information. This flag is useful when running

the inc command in the background.

-truncate Clears the mailbox or file from which the **inc** command is taking new messages. If the

-file flag is not specified, the -truncate flag is the default.

-width Number Sets the number of columns in the command output. The default is the width of the

display.

Profile Entries

The following entries are entered in the *UserMhDirectoryl.*mh_profile file:

Alternate-Mailboxes: Specifies alternate mailboxes.

Folder-Protect: Sets the protection level for new folder directories.

Msg-Protect: Sets the protection level for new message files.

Path: Specifies the user's MH directory.

Unseen-Sequence: Specifies the sequences used to keep track of unseen messages.

Examples

1. To incorporate new mail into the default mail folder, **inbox**, enter:

inc

If the inbox folder exists, the system displays a message similar to the following:

Incorporating new mail into inbox...

65+ 04/08 jim@athena.a Meeting <<The meeting will 66 04/08 jim@athena.a Schedule <<Schedule change

In this example, two messages are filed in the inbox folder. The subject of the first message is Meeting, and the first line starts with the words The meeting will. The subject of the second message is Schedule, and the first line starts with the words Schedule change.

2. To incorporate new mail into a new folder called **testcases**, enter:

inc +testcases

The system prompts you as follows:

Create folder "/home/mary/testcases"?

If you wish to create the folder, enter:

yes

A message similar to the following is displayed:

Incorporating new mail into testcases...

67+ 04/08 jim@athena.a Meeting <<We will begin 68 04/08 jim@athena.a Schedule <<Schedule change

Files

\$HOME/.mh_profileCustomizes the MH user profile.

/etc/mh/mtstailor Tailors the MH environment to the local environment.

/var/spool/mail/\$USER Specifies the location of the mail drop.

Related Information

The **mhmail** command, **post** command, **scan** command.

The **mh** alias file format, **mh** profile file format.

Mail applications in *Networks and communication management*.

indent Command

Purpose

Reformats a C language program.

Syntax

```
indent InputFile [ OutputFile ] [ -nbad | -bad ] [ -nbap | -bap ] [ -nbbb | -bbb ] [ -nbc | -bc ] [ -br | -bl] [
-cn] [ -cdn ] [ -ncdb | -cdb ] [ -nce | -ce ] [ -cin ] [ -clin ] [ -dn ] [ -dn ] [ -ndj | -dj ] [ -nei | -ei ] [ -fa ] [
-nfa ] [ -nfc1 | -fc1 ] [ -in ] [ -nip | -ip ] [ -ln ] [ -ln ] [ -nlp | -lp ] [ -npro ] [ -npcs | -pcs ] [ -nps | -ps ] [
-npsl | -psl ] [ -nsc | -sc ] [ -nsob | -sob ] [ -nslb | -slb ] [ -st ] [ -troff ] [ -nv | -v ] [ -TType ] ...
```

Description

The **indent** command reformats a C program as specified by flags entered with the command.

If you only specify the InputFile parameter, the reformatted file is written back into the InputFile parameter and a backup copy of the InputFile parameter is written in the current directory with a .BAK filename suffix.

If you specify the OutputFile parameter, the indent command checks to make sure its name is different from the *InputFile* parameter.

To set up your own profile of defaults for the indent command, create a file called .indent.pro in your login directory or the current directory. In this file, include as many flags as desired, separated by spaces, tabs, or new lines.

Flags in the .indent.pro file in the current directory override those in your login directory (with the exception of -TType flags, which accumulate). If the indent command is run and a profile file exists, the profile file is read to set up the defaults of the program. Flags on the command line, however, override profile flags.

Comment Handling

The **indent** command assumes that any comment with a - (dash) or * (asterisk) immediately after the start of a comment marker (/*- or /**) is a comment surrounded by asterisks. Each line of the comment is left unchanged, except for its indentation. This indentation can be adjusted to account for the change in indentation of the first line of the comment.

All other comments are treated as text. The **indent** command fits as many words (separated by blanks, tabs, or new-lines) on a line as possible. Blank lines break paragraphs.

A block comment is a comment that is not to the right of the code, and extends for more than one line.

If a comment is on a line with code, it is started in the comment column set by the -cn flag. Otherwise, the comment is started at n indentation levels less than where code is currently being placed, where n is

specified by the **-d***n* flag. If the code on a line extends past the comment column, the comment starts further to the right. The right margin can be extended automatically in extreme cases.

Preprocessor Lines Handling

In general, the **indent** command leaves preprocessor lines alone. The only reformatting it does is to straighten up trailing comments. It leaves embedded comments alone. Conditional compilation (code between **#ifdef** and **#endif** lines) is recognized and the **indent** command attempts to compensate correctly for the syntactic peculiarities introduced.

C Syntax Handling

The parser built into the **indent** command attempts to cope with incomplete and misformed syntax. In particular, the use of macros like:

```
#define forever for(;;)
```

is handled properly. For best results, use the indent command on source that is syntactically correct.

Flags

Note: Flags can appear before or after file names.

- **-bad** Forces a blank line after every block of declarations.
- -nbad Suppresses a blank line after every block of declarations; active unless turned off with the -bad flag.
- **-bap** Forces a blank line after every procedure body.
- -nbap Suppresses a blank line after every procedure body; active unless turned off with the -bap flag.
- **-bbb** Forces a blank line before every block comment.
- -nbbb Suppresses a blank line before every block comment; active unless turned off with the -bbb flag.
- **-bc** Forces a new line after each comma in a declaration.
- -nbc Suppresses a new line after each comma in a declaration; active unless turned off with the -bc flag.
- -bl Formats compound statements, structure initializations, and enum initializations, as follows:

```
if (...)
{
    code
}
```

-br Formats compound statements, structure initializations, and enum initializations, as follows:

```
if (...) {
    code
}
```

This flag is active unless turned off with the -bl flag.

- **-cn** Sets the initial tab position for comments on code to the *n* variable. The default value is 33.
- **-cd***n* Sets the initial tab position for comments on declarations to the *n* variable. By default, this flag uses the value defined with the **-c** flag.
- -cdb Enables placing comment delimiters on blank lines; active unless turned off with the -ncdb flag. The -cdb flag affects only block comments, not comments to the right of code. Resulting comments look like the following:

```
/*
 * this is a comment
 */
```

-ncdb Disables placing comment delimiters on blank lines. The -ncdb flag affects only block comments, not comments to the right of code. Resulting comments look like the following:

```
/* this is a comment */
```

- -ce Enables forcing else statements to follow the immediately preceding } (left bracket); active unless turned off with the -nce flag.
- **-nce** Disables forcing **else** statements to follow the immediately preceding } (left bracket).
- **-ci***n* Indents the continuation lines *n* positions from the beginning of the first line of the statement. Expressions in parentheses have extra indentation added to indicate the nesting, unless the **-lp** flag is in effect. By default, this flag uses the value defined by the **-i** flag.

- -clin Indents the case labels *n* positions to the right of the containing flag statement. Entering -cli0.5 causes case labels to be indented half a tab stop. This option is the only one that takes a fractional argument. By default, the value is -cli0.
- -dn Controls the placement of comments that are not to the right of code with the n variable. Specifying the -d1 flag causes such comments to appear one indention level to the left of code. By default, this flag uses -d0 and comments are aligned with code. The location of comment lines relative to program code affects the comment indention.
- **-di***n* Specifies the number of positions to indent an identifier from a preceding declaration keyword with the *n* variable. By default, this flag uses **-di16**.
- -dj Left-justifies declarations.
- -ndj Indents declarations; active unless turned off with the -dj flag.
- -ei Enables special **else-if** processing; active unless turned off with the **-nei** flag. The **-ei** flag causes **if** statements following **else** statements to have the same indentation as the preceding **if** statement.
- -nei Disables special else-if processing.
- -fa Flips assign operators from old style C code to the ANSI format. This flag remains active unless turned off with the -nfa flag.

Attention: The possibility of changing the meaning of the code exists if the code was meant for the ANSI compiler. For example, A=-B becomes A-=B.

Note: Use no spaces between operators. If the user means subtraction, then the flipping is necessary; on the other hand, if the user means A equals the negative of B, the flipping alters the meaning.

- -nfa Suppresses flipping the operators. Use this flag if the code is written for an ANSI compiler.
- -fc1 Enables formatting comments that start in column 1; active unless turned off with the -nfc1 flag.
- **-nfc1** Disables formatting comments that start in column 1.
- **-i**n Sets the indentation level size. By default, the level size is 8 positions.
- -ip Enables indenting parameter declarations; active unless turned off with the -nip flag.
- **-nip** Disables indenting parameter declarations.
- -In Sets the maximum column position of comments that are to the right of the code. If the comment does not fit on a line, a maximum of 25 characters are printed.
- **-Ic***n* Sets the maximum line length for block comments to the *n* variable. By default, this flag uses the length specified with the **-I** flag.
- **-Ip** Aligns code surrounded by parentheses in continuation lines; active unless turned off with the **-nlp** flag. If a line has a left parenthesis with no matching right parenthesis on that line, continuation lines start at the position following the left parenthesis.

With the -lp flag in effect, such lines appear as follows:

Inserting two more new lines yields the following:

-nlp Leaves code surrounded by parentheses in continuation lines unaligned. With the -nlp flag in effect, such lines appear as follows:

- -npro Causes the profile files ./.indent.pro and \$HOME/.indent.pro to be ignored.
- -pcs Inserts a space between each procedure call name and the following ((left parenthesis).
- **-npcs** Suppresses a space between each procedure call name and the following ((left parenthesis); active unless turned off with the **-pcs** flag.
- -ps Inserts spaces on both sides of the pointer following the -> operator.

-nps	Suppresses spaces on both sides of the pointer following the -> operator; active unless turned off with the -ps flag.
-psl	Left-justifies the names of procedures being defined; active unless turned off with the -npsI flag. The procedure types, if any, remain on the previous lines.
-npsl	Disables left-justification of names of defined procedures.
-sc	Enables the placement of * (asterisks) to the left of comments; active unless turned off with the -nsc flag.
-nsc	Disables the placement of * (asterisks) to the left of comments.
-slb	Treats any single-line comment that is not to the right of the code as a block comment.
-nslb	Disables treating any single-line comment that is not to the right of the code as a block comment; active unless turned off with the -slb flag.
-sob	Removes optional blank lines. Works in combination with any of the following flags: -nbad , -nbap , or -nbbb . Removes only blank lines that were inserted by the -bad , -bap , or -bbb flags.
-nsob	Retains optional blank lines; active unless turned off with the -sob flag.
-st	Causes the indent command to take its input from stdin and output to stdout.
-T Type	Adds the <i>Type</i> variable to the list of type keywords. Names accumulate so -T can be specified more than once. You should specify all the types appearing in your program defined by typedef statements to produce the best output from the indent command.
-troff	Formats the C program for processing by troff . Produces a listing similar to listings produced by the vgrind command. If no output file is specified, the default is standard output, rather than formatting in place.
-v	Turns on verbose mode, which reports when one line of input is split into two or more lines of output and gives size statistics at completion.
-nv	Turns off verbose mode; active unless turned off with the -v flag.

Examples

1. To format the test.c file using the default settings of the **indent** command and place the output into the newtest.c file, enter:

indent test.c newtest.c

2. To format the test.c file so that a blank line is forced after every block of declarations and procedure body, use all other default settings, and store the output in the newtest.c file, enter:

indent test.c newtest.c -bad -bap

3. To format the test.c file using the default settings of the **indent** command and to define uint as a type keyword recognizable to the **indent** command, enter:

indent test.c newtest.c -Tuint

Files

./.indent.pro Contains the profile file.
\$HOME/.indent.pro Contains the profile file.

/usr/ccs/bin/indent Contains the indent command.

Related Information

The cb command.

Commands in Operating system and device management.

indxbib Command

Purpose

Builds an inverted index for a bibliography.

Syntax

indxbib Database ...

Description

The **indxbib** command makes an inverted index to the named database (or files) for use by the **lookbib** and refer commands. These files contain bibliographic references (or other kinds of information) separated by blank lines.

Note: The indxbib command expects the database to exist in the current working directory.

A bibliographic reference is a set of lines, constituting fields of bibliographic information. Each field starts on a line beginning with a % (percent sign), followed by a key letter, then a space character, and finally the contents of the field, which can continue until the next line starting with a % (percent sign). All key letters are ASCII characters.

The indxbib command is a shell script that calls the /usr/lib/refer/mkey and /usr/lib/refer/inv files. The first program, **mkey**, performs the following operations:

- 1. Truncates words (delimited by blanks or tabs) to six characters.
- 2. Maps uppercase to lowercase characters.
- 3. Discards words shorter than three characters.
- 4. Discards the most commonly used words according to an existing ign file. An English language file, /usr/lib/eign, has been provided with a list of common English words. It is suggested, but not necessary, that users create their own files, named ign, consisting of language-specific common words. This file, if created, should exist in the /usr/lib/nls/msg/\$LANG directory.
- 5. Discards numbers (dates) less than 1900 or greater than 2099.

Note: All dates should be indexed because many disciplines refer to literature written in the 1800s or earlier.

The second program, inv, creates in the working directory an entry file (.ia), a posting file (.ib), and a tag file (.ic).

Files

/usr/lib/eign Contains the default list of common words the **indxbib** command discards while

processing.

Database.ia Contains the entry file. Database.ib Contains the posting file. Database.ic Contains the tag file.

Environment Variables

NLSPATH Refers to a list of directory names where the message catalog files can be found.

Related Information

The addbib command, lookbib command, refer command, roffbib command, sortbib command.

inetd Daemon

Purpose

Provides Internet service management for a network.

Syntax

Note: Use SRC commands to control the **inetd** daemon from the command line. Use the **rc.tcpip** file to start the daemon with each system restart.

/usr/sbin/inetd [-d] [-t SecondsToWait] [ConfigurationFile]

Description

The /usr/sbin/inetd daemon provides Internet service management for a network. This daemon reduces system load by invoking other daemons only when they are needed and by providing several simple Internet services internally without invoking other daemons.

The **inetd** daemon starts by default each time you start your system. When the daemon starts, it reads its configuration information from the file specified in the *ConfigurationFile* parameter. If the parameter is not specified, the **inetd** daemon reads its configuration information from the /**etc/inetd.conf** file.

Once started, the **inetd** daemon listens for connections on certain Internet sockets in the **/etc/inetd.conf**. The **/etc/inetd.conf** file describes to the **inetd** daemon how Internet service requests on Internet sockets should be handled. When the **inetd** daemon receives a request on one of these sockets, it determines which service corresponds to that socket and then either handles the service request itself or invokes the appropriate server.

Subservers of the inetd Daemon

The **inetd** daemon (a subsystem) controls the following daemons (subservers):

- comsat daemon
- ftpd daemon
- · fingerd daemon
- · rlogind daemon
- · rexecd daemon
- rshd daemon
- · talkd daemon
- · telnetd daemon
- tftpd daemon
- · uucpd daemon.

The ftpd, rlogind, rexecd, rshd, talkd, telnetd, and uucpd daemons are started by default. The tftpd, fingerd, and comsat daemons are not started by default unless they are uncommented in the /etc/inetd.conf file.

Inetd Configuration File

The **/etc/inetd.conf** file can be updated by using the System Management Interface Tool (SMIT), the System Resource Controller (SRC), or by editing the **/etc/inetd.conf**.

If you change the /etc/inetd.conf, using SMIT, then the inetd daemon will be refreshed automatically and will read the new /etc/inetd.conf file. If you change the file using your favorite editor, run the refresh -s inetd or kill -1 InetdPID command to inform the inetd daemon of the changes to its configuration file.

The entries in the /etc/inetd.conf file include the following information:

Service Name Specifies the name of a valid Internet service.

Socket Type Specifies the type of Internet socket used for the Internet service. (Only stream and datagram

sockets are implemented.) Valid values are:

stream

dgram

sunrpc_udp

sunrpc_tcp

Protocol Specifies the Internet Protocol used for the Internet service. Valid values are:

tcp6

udp

udp6

Wait/Nowait Specifies whether the inetd daemon should wait for the service to complete before continuing

to listen for this type of service request.

Specifies whether the inetd daemon should wait for the service to complete before continuing Wait/Nowait

> to listen for this type of service request. SRC works like wait, but instead of forking and waiting for the child to die, it does a startsrc on the subsystem and store information about the starting of the service. When the service is removed from the inetd.conf file and inetd is

restarted, the service has a stopsrc issued to the service to stop it.

User Specifies the user name that inetd should use to start the subserver.

Path Specifies the fully qualified path name that inetd should execute to provide the service. For

services that inetd provides internally, this entry should be internal.

Command Specifies the name of the service to start and its parameters. This field is empty for internal

services.

The **inetd** daemon can be run with or without the SRC. In addition, the inetd daemon can be controlled by issuing signals using the kill command.

Flags

Sends debugging messages to the syslogd daemon.

Specifies the number of seconds to wait in the select() system call before looping. -t SecondsToWait

The SecondsToWait can be a number from 1 to 999999. Without this flag the inetd daemon will block until one of the active services is requested by a network connection. This flag should only be used when a machine is servicing many wait services like tftp and is not being used for other services. Since timing out the select() system call will cause the inetd daemon to use more CPU cycles, this flag is

not recomended for most situations.

Service Requests

The Internet service requests that are supported internally by the inetd daemon are generally used for debugging. They include the following internal services:

ECHO Returns data packets to a client host. **DISCARD** Discards received data packets.

CHARGEN Discards received data packets and sends predefined or random data.

DAYTIME Sends the current date and time in user-readable form. TIME Sends the current date and time in machine-readable form.

Related Information

The fingerd daemon, ftpd daemon, rexect daemon, rlogind daemon, rshd daemon, syslogd daemon, talkd daemon, telnetd daemon, tftpd daemon.

The inetd.conf file format, protocols file format, services file format.

TCP/IP daemons in Networks and communication management.

infocmp Command

Purpose

Manages terminfo descriptions.

Syntax

Description

The infocmp command manages terminfo descriptions. You can use this command to:

- · Compare a binary **terminfo** entry with other **terminfo** entries.
- · Print a terminfo description from the binary file.
- Rewrite a **terminfo** description to take advantage of the **use** attribute.

The **infocmp** command prints the Boolean attributes first, the numeric attributes second, and the string attributes last.

Comparing Entries

Use the **-d**, **-c**, and **-n** flags to compare entries. The **-d** flag returns the differences between entries. The **-c** flag produces a list of the capabilities that are set and in common between two entries. The **-n** flag returns a list of the capabilities that neither entry has.

To compare **terminfo** entries, you specify two or more *TermName* parameters. The **infocmp** command compares the **terminfo** description of the first *TermName* parameter with each of the descriptions for the subsequent *TermName*s specified. If a capability is defined for only one of the terminal descriptions, the value returned will depend on the type of capability. For Boolean capabilities the **infocmp** command returns an F, the command returns a -1 for integer capabilities, and null for string capabilities.

Producing a Source Listing

Use the -I (uppercase i), -L, -C, and -r flags to produce a source listing for one or more terminals. If you do not specify a *TermName* parameter, the system uses the **TERM** environment variable. You can use these source options to produce a source file for a terminfo binary when one is not available.

The I (uppercase i) flag produces a listing with the terminfo names. The -L flag produces a listing using the long C variable names listed in /usr/include/term.h.

The **-C** flag uses **termcap** names instead of terminfo capability names when producing the source listing. The **infocmp** commands translates and outputs only those **terminfo** capabilities that have a corresponding **termcap** code name. To remove this restriction, specifying the **-r** flag. This flag causes the command to output **terminfo** capabilities that cannot be translated into **termcap** format.

When using the -C and -r flags, the infocmp command notes any string parameters it was unable to convert to the termcap format. You must edit these parameters manually. The command collects all padding information for strings together and places it at the beginning of the string where termcap expects it. Mandatory padding is optional after translation. Mandatory padding is padding information with a trailing / (slash).

Note: The -C and -r flags cannot always convert a terminfo string into its equivalent termcap form. Similarly, a conversion from the **termcap** file format back into the **terminfo** file format does not necessarily reproduce the original source.

Definitions with the use Attribute

Given a list of terminal menus and the -u flag, the infocmp command compares the first terminal's description against the other terminal descriptions. The **infocmp** command then creates a new description for the first terminal using as much of the subsequent terminal descriptions as possible.

When you specify the -u flag and a list of terminal names, the infocmp command does the following:

- · Compares subsequent terminal descriptions against the first.
- Creates a description of the first terminal you specified relative to the description of the other terminals.

The new description for the first terminal will have the following:

 Capabilities that exist in the subsequent terminals but do not exist for the first terminal will appear with an @ in the resulting description.

Note: The @ implies that the capability does not exist.

- Capabilities defined in a subsequent terminal with the same value are replaced with use=<subsequent terminal>.
- · Any capabilities in the first terminal not found in any of the other terminals are printed along with the corresponding values.
- · If the first terminal has a capability whose value differs from the value found in at least one of the other terminals, the capability is printed.

You can change a description and specify a capability after the use attribute. If this capability is also found in the terminal referenced by the use attribute, the second capability takes precedence over the one referenced by the use attribute.

Changing Databases

By default, terminal descriptions appear in the system terminfo database directory, /usr/share/lib/ terminfo. You can specify a different database location with the TERMINFO environment variable. The infocmp command first checks to see if this variable exists. If the variable does not exist, the command uses the system terminfo database.

You can use the -A and -B flag with the infocmp command to override the system database. The -A flag identifies the **terminfo** database for the first *TermName* parameter. The **-B** flag identifies the database to use for any subsequent terminals you name. Together, these flags make it possible to compare descriptions for two terminals with the same name located in two different databases.

Flags

-A Directory	Identifies the terminfo database for the first <i>TermName</i> parameter.
-B Directory	Identifies the terminfo database for every <i>TermName</i> parameter except the first.
-C	Uses the termcap code names to produce the source listing. Will not list terminfo
	capabilities that cannot be translated to termcap format.

-с	not set	e capabilities that are common between the two entries. Capabilities that are are ignored. This flag can be used as a quick check to see if it is desirable to e-u flag.		
-d		e capabilities that are different between terminals. You can use this flag to the differences between similar terminal entries.		
-I (uppercase i)	Uses th	ne terminfo capability names when producing the source listing.		
-1 (numeral)		he capabilities one to a line. by default, the fields are printed several to a line aximum width of 60 characters.		
-L	Uses the source	ne long C variable name listed in /usr/include/term.h file to produce the listing.		
-n	specify both <i>Te</i>	res two entries and lists the capabilities that do not exist in either. If you do not a <i>TermName</i> parameter, the system uses the TERM environment variable for <i>ermName</i> parameters. You can use this as a quick check to see if anything t out of the description.		
-r		s the infocmp command to output terminfo capabilities that cannot be sed to termcap format. This flag is valid only with the -C flag.		
-s		ne output from the infocmp command within each capability type (Boolean, c, and string) and according to the argument below:		
	d	Sort in the order specified in the terminfo database.		
	i	Sort by terminfo name.		
	1	Sort by the long C variable name.		
	С	Sort by the termcap name.		
	If you do not specify an option with the -s flag, the command sorts each capability alphabetically by the terminfo name within each type. If you specify the -C or the -L flags with the -s flag, the capabilities are sorted by the termcap name or the long C variable name, respectively.			
-u	Compa use att	res two or more terminal descriptions and produces new descriptions using the ribute.		
-v	Prints of	out tracing information on standard error.		
-V	Prints of	out the version of the program in use on standard error and exits.		
-w Width		es the output to the specified number of characters per line. The output s as many fields as possible that can fit within the specified number of ters.		

Note: Fields are not truncated.

Examples

- - infocmp -c aixterm lft
- 2. To list all of the capabilities that are possible but do not currently exist for the current terminal, enter: infocmp -n
- 3. To produce a source listing for the lft terminal in $\boldsymbol{terminfo}$ format, enter:
 - infocmp -I lft
- 4. To produce a source listing for the terminal description my_term that is located in **/tmp** using as much of the lft description as possible, enter:

infocmp -A /tmp -u my_term lft

File

/usr/share/lib/terminfo

Contains the compiled terminal description database.

Related Information

The **tic** and **captoinfo** commands.

The **terminfo** file format.

infocenter Command

Purpose

Starts the Information Center in a browser window.

Syntax

infocenter

Description

The infocenter command starts the Information Center in a browser window. The Information Center is the primary location for finding information about your system. With the Information Center you can navigate and search the documentation. The Information Center can also be started by clicking the Information Center icon on the Help panel available from the CDE toolbar.

Note: The Information Center is available only by means of an HTML browser. If the default URL is an external address, then access to the Internet is required. The infocenter command (and the Information Center icon) activates the browser and directs the browser to the Web address of the Information Center.

The actual Information Center brought up by the command depends on how it was configured. If no Information Center files have been installed or no configuration has been done, the Information Center that appears in the browser window is the default specified in the /usr/lpp/bosinst/bos.vendor.profile file. If the Information Center has been installed on a system within an intranet, using Configuration Assistant, SMIT, or Web-based System Manager, then the server specified during the configuration process is used as the documentation server.

The Web address of the Information Center is in the /usr/lpp/bosinst/bos.vendor.profile file. If the Information Center Web address is provided in this file, it will be in the following format: export INFORMATION CENTER URL=information center url

If a line similar to this does not exist in the /usr/lpp/bosinst/bos.vendor.profile file, or if the file does not exist and the Information Center has not been configured to use a documentation server, the user will receive a message indicating that the Information Center cannot start because an Information Center URL was not found.

Files

/usr/sbin/infocenter /usr/lpp/bosinst/bos.vendor.profile

Starts the Information Center in a browser window. Contains vendor profile information including the Web address used by the infocenter command.

install Command

Purpose

Installs a command.

Syntax

/usr/bin/install [- c DirectoryA] [- f DirectoryB] [- i] [- m] [- M Mode] [- O Owner] [- G Group] [- S] [- n DirectoryC] [- o] [- s] File [Directory ...]

Description

The **install** command installs a specified file in a specific place within a file system. It is most often used in makefiles. When replacing files, the **install** command copies (or moves) each file into the appropriate directory, thereby retaining the original owner and permissions based on the behavior of the **cp** and **mv** commands. An attempt is made to change the destination to owner **bin** and group **bin**. The **-O** *Owner* and **-G** *Group* flags can be used to specify a different owner or group. The **install** command writes a message telling you exactly which files it is replacing or creating and where they are going.

You must be a super-user if you want to specify the ownership of the installed file with the -O or -G flags.

If you do not specify the *Directory* parameter, the **install** command searches a set of default directories (/usr/bin, /etc, and /usr/lib, in that order) for a file with the same name as the *File* parameter. The first time it finds one, it overwrites it with *File* and issues a message indicating that it has done so. If a match is not found, the **install** command issues a message telling you there was no match and exits with no further action. If the *File* parameter does not exist in the current directory, the **install** command displays an error message and exits with a nonzero value.

If any directories are specified on the command line, the **install** command searches them before it searches the default directories.

Flags

-c DirectoryA	Installs a new command file in the <i>DirectoryA</i> variable only if that file does not already exist there. If it finds a copy of <i>File</i> there, it issues a message and exits without overwriting the file. This flag can be used alone or with the -s , -M , -O , -G , or -S flag.
-f DirectoryB	Forces installation of <i>File</i> in <i>DirectoryB</i> whether or not <i>File</i> already exists. If the file being installed does not already exist, the command sets the permission code and owner of the new file to 755 and bin , respectively. This flag can be used alone or with the -o,-s, -M, -O, -G, or -S flag.
-G Group	Specifies a different group for the destination file. The default group is bin.
-i	Ignores the default directory list and searches only those directories specified on the command line. This flag cannot be used with the -c , -f , or -m flags.
-m	Moves the <i>File</i> parameter to the directory instead of being copied. Cannot be used with the -c , -f , -i , or -n flag.
-M Mode	Specifies the mode of the destination file.
-n DirectoryC	Installs the <i>File</i> parameter in the <i>DirectoryC</i> variable if it is not in any of the searched directories, and sets the permissions and owner of the file to 755 and bin , respectively. This flag cannot be used with the -c , -f , or -m flag.
-0	Saves the old copy of the <i>File</i> parameter by copying it into a file called OLD <i>File</i> in the same directory. This flag cannot be used with the -c flag.
-O Owner	Specifies a different owner of the destination file. The default owner is bin.
-s	Suppresses the display of all but error messages.
-S	Causes the binary to be stripped after installation.

Examples

install fixit

1. To replace a command that already exists in one of the default directories, enter:

This replaces the fixit file if it is found in the /usr/bin, /etc, or /usr/lib directory. Otherwise, the fixit file is not installed. For example, if /usr/bin/fixit exists, then this file is replaced by a copy of the file fixit in the current directory.

2. To replace a command that already exists in a specified or default directory and to preserve the old version, enter:

```
install -o fixit /etc /usr/games
```

This replaces the fixit file if it is found in the /etc or /usr/games directory or in one of the default directories. Otherwise the fixit file is not installed. If the file is replaced, the old version is preserved by renaming it OLDfixit in the directory in which it was found.

3. To replace a command that already exists in a specified directory, enter:

```
install -i fixit /home/jim/bin /home/joan/bin /usr/games
```

This replaces the fixit file if it is found in the /home/jim/bin, /home/joan/bin, or /usr/games directory. Otherwise, the file is not installed.

4. To replace a command found in a default directory or install it in a specified directory if it is not found, enter:

```
install -n /usr/bin fixit
```

This replaces the fixit file if it is found in one of the default directories. If the file is not found, it is installed as /usr/bin/fixit.

5. To install a new command, enter:

```
install -c /usr/bin fixit
```

This creates a new command by installing a copy of the fixit file as /usr/bin/fixit, but only if this file does not already exist.

6. To install a command in a specified directory whether or not it already exists, enter:

```
install -f /usr/bin -o -s fixit
```

This forces the fixit file to be installed as /usr/bin/fixit whether or not it already exists. The old version, if any, is preserved by moving it to /usr/bin/OLDfixit (a result of the -o flag). The messages that tell where the new command is installed are suppressed (a result of the -s flag).

Compatibility

For compatibility with Berkeley Software Distribution (BSD), two install commands exist. See the installbsd command.

Files

/usr/bin/install

Contains the install command.

Related Information

The chgrp command, chmod command, chown command, cp command, installbsd command, make command, mv command, strip command.

install_all_updates Command

Purpose

Updates installed software to the latest level on media and verifies the current recommended maintenance or technology level.

Syntax

install_all_updates -d Device [-p][-i][-c][-r][-n][-s][-x][-v][-N][-S][-Y][-V][-D]

Description

install_all_updates examines currently installed software and attempts to update it to the latest level that is available on the media. **install_all_updates** will not install any filesets that are present on the media, but not installed on the system except in the following situations:

- · the new filesets are installed as requisites of other filesets.
- the /var/adm/ras/bosinst.data filesets ALL_DEVICES_KERNELS to yes.

For installp images, all installp requisites are enforced.

Notes:

- Currently, install_all_updates processes installp images and rpm images. Because the rpm utility
 does not support automatic installation of requisites, some rpm software may not be installable with
 install all updates.
- install_all_updates verifies the current recommended maintenance or technology level by using the "oslevel" utility and checking with the latest recommended maintenance or technology level known to this version of install_all_updates.
- 3. If **install_all_updates** locates an update to the install utilities (the **bos.rte.install** fileset), it first installs the update and then reinvokes itself to process the remaining updates. The "-i" flag can be used to update the install utilities only, this is useful when attempting to view an accurate preview.
- 4. **install_all_updates applies** all installp updates unless the **COMMIT** flag (**-c**) is specified. For more information of **APPLY** vs. **COMMIT** please see the **installp** man page.
- 5. **install_all_updates** will by default instruct **installp** to automatically install requisites and to do any necessary filesystem expansions. The "-n" will override the install requisite default, and "-x" will override the filesystem expansion default.
- 6. The following flags apply to install pupdates only: -c, -n, -x, -v, -S, and -V.
- 7. Any library or executable program updated by an interim fix or service update which is in use by an active process will not be reflected in that process unless it is restarted. For example, an update that changes the ksh will not have the changes reflected in any ksh processes that are already running. Likewise, an update to the **libc.a** library will not be reflected in any process that is already running. In addition, any process that is using a library and does a **dlopen** operation of the same library after the library has been updated could experience inconsistencies if it is not restarted.
- 8. If an attempt is made to update a fileset that is locked by the interim fix manager (the **emgr** command), a notice will be displayed indicating which filesets are locked. The **Islpp** command shows that any locked filesets are in the EFIXLOCKED state.
- 9. If an attempt is made to update a fileset that has an installed build date more recent than the build date of the selected fileset, a message will be displayed to indicate this. For more information about build dates, see Checking fileset build dates in *Installation and migration*.

Flags

-c Instructs **installp** to commit all newly installed updates. Updates are applied by default (Please see the **installp** man page for more explanation on applying vs. committing updates).

-d Device	Specifies where the installation media can be found. This can be a hardware device such as tape or cdrom or it can be a directory that contains installation images. When installation media is a tape device it should be specified as no-rewind-on-close and no-retension-on-open.
-D	Turns on install_all_updates debug output. This flag is for debugging the install_all_updates utility and should not be used for normal operations.
-i	Update install utilities only.
-n	Instructs installp to not automatically install requisites. Automatic installation of requisites is the default behavior.
-N	Skip updating install utilities first.
	Note: This flag is not recommended unless you are debugging a related problem.
-p	Performs a preview of an action by running all preinstallation checks for the specified action. No software changes are made.
-r	Update rpm images (if possible). This flag is not set by default.
-s	Skip recommended maintenance or technology level verification. The verification is performed by default.
-S	Instructs installp to suppress multi-volume processing of cdrom media.
-v	Instructs installp to verify that all installed files in the fileset have the correct checksum value after the installation. This operation may require more time to complete the installation.
-V	Instructs installp to run in verbose output mode.
-x	Instructs installp to not automatically expand file systems. Automatic expansion of file systems is the default.
-Y	Agrees to all software license agreements which are required for software installation.

Exit Status

- 0 All **Ippmgr** related operations completed successfully.
- >0 An error occurred.

Security

Only the root user can execute install_all_updates.

Examples

1. To install all installp updates on device /dev/cd0 and to verify the current recommended maintenance or technology level, enter:

```
install_all_updates -d /dev/cd0
```

- 2. To commit install all installp updates and install any installable rpm updates in directory /images, enter: install all updates -d /images -rc
- 3. To install the latest level of install utilities on device /dev/cd0 (bos.rte.install installp fileset), enter: install_all_updates -d /dev/cd0 -i

Files

/usr/sbin/install_all_updates

Contains the install_all_updates command.

Related Information

The installp command, Islpp command, rpm command

install_assist Command

Purpose

Starts the Installation Assistant application.

Syntax

install assist

Description

The **install_assist** command starts Installation Assistant, an application designed to simplify the customization of your system after a Base Operating System (BOS) installation. The Installation Assistant guides you through post-installation tasks and, in some cases, automatically installs software packages for you. The Installation Assistant has two interfaces, ASCII and graphical. The interface that displays is based on your terminal type (defined in the **TERM** environment variable).

If your terminal type is not set, the first menu displayed by the ASCII Installation Assistant requires you to enter your terminal type (tty). If you enter a terminal type that is not valid, this menu redisplays until a valid type is entered. If you enter a valid terminal type that does not match your terminal, the next screen displayed could be unreadable. In this case, press the break key sequence to return to the Set Terminal Type screen. For most terminal types, the break key sequence is Ctrl-C.

On a system with an ASCII interface, the newly installed BOS reboots and starts the Installation Assistant to guide you through completing configuration tasks. You must have root user authority to use the Installation Assistant. To access the Installation Assistant later, type **install_assist** on the command line. You can also access it from a graphics system through the SMIT **smit assist** fast path. If there are outstanding software license agreements that must be accepted before you can continue to use the machine, the Installation Assistant prompts you to view and accept these agreements.

On a system with a graphical interface, the newly installed BOS reboots and the Configuration Assistant starts to guide you through the configuration tasks. If there are outstanding software license agreements that must be accepted before you can continue to use the machine, the Configuration Assistant prompts you to view and accept these agreements. To access the Configuration Assistant later, type **configassist** on the command line.

Most Installation Assistant tasks create or add to the **smit.log** and **smit.script** files in your home directory. (These are the same files appended when you run a SMIT session.) The commands built and run by the Installation Assistant tasks are added to the end of the **smit.log** file along with the command output. The time, name of the task, and the command (flags and parameters included) are added to the end of the **smit.script** file in a format that can easily be used to create executable shell scripts.

Example

- To start the Installation Assistant, type: install assist
- 2. To access the Configuration Assistant, type:
- 3. Access the Installation Assistant from a graphical interface, use the SMIT smit assist fast path.

Files

smit.logsmit.scriptSpecifies detailed information on your session, with time stamps.Specifies the task commands run during your session, with time stamps.

Related Information

The **configassist** command.

Configuring AIX in Installation and migration

install_mh Command

Purpose

Sets up mailbox directories.

Syntax

install mh [-auto] [-help]

Description

The install mh command sets up mailbox directories. The install mh command is not started by the user. The install_mh command is called by other programs only.

The **install mh** command starts automatically the first time you run any Message Handler (MH) command. The **install mh** command prompts you for the name of your mail directory. If the directory does not exist, the install_mh command queries you if it should be created. Upon receiving a positive response, the install_mh command creates the \$HOME/.mh_profile file and places the Path: profile entry in it. This entry identifies the location of your mailbox by specifying the directory path for your MH directory, UserMHDirectory.

Flags

-auto Creates the standard MH path without prompting.

-help Lists the command syntax, available switches (toggles), and version information.

Note: For MH, the name of this flag must be fully spelled out.

Files

\$HOME/.mh_profile

Contains the MH user profile.

Related Information

Mail applications in *Networks and communication management*.

install_wizard Command

Purpose

Invokes the Web-based System Manager Install Wizard or the SMIT install menu.

Syntax

install_wizard [-d Media]

Description

The install_wizard command invokes the Web-based System Manager Install Wizard or the SMIT install menu. This provides an easy path to the install interfaces. These interfaces show media content for installp, UDI, or ISJE products and launch the appropriate installer.

Flags

-d device or directory

The device or directory containing the images to install.

Example

To invoke the Web-based System Manager Install Wizard, insert an install CD in cd1 and type: install_wizard -d /dev/cd1

Files

/usr/sbin/install_wizard

Related Information

The **installp** command.

installbsd Command

Purpose

Installs a command (BSD version of the install command).

Syntax

/usr/bin/installbsd [-c] [-g Group] [-m Mode] [-o Owner] [-s] BinaryFileDestination

Description

The **installbsd** command installs the file specified by the *BinaryFile* parameter by moving it to a file or directory specified by the *Destination* parameter. Use of the **-c** flag copies the *BinaryFile* rather than moving it. If the specified *Destination* parameter is a directory, the *BinaryFile* is moved into the directory. If the specified *Destination* parameter already exists as a file, the **installbsd** command removes that file before the *BinaryFile* is moved. The **installbsd** command does not move a file onto itself.

Installing the file /dev/null creates an empty file.

Flags

-c	Copies the file specified by the <i>BinaryFile</i> parameter to the file or directory specified by the <i>Destination</i> parameter.
-g Group	Specifies a group for the file specified by the <i>Destination</i> parameter. The default group is staff.
-m Mode	Specifies a mode for the file specified by the <i>Destination</i> parameter. The default mode is 755. The specified mode can be an octal number or a symbolic value.
-o Owner	Specifies the owner for the file specified by the <i>Destination</i> parameter. The default owner is the root user.
-s	Causes the file specified by the BinaryFile parameter to be stripped after installation.

Examples

To install a new command called fixit, enter:

installbsd -c o mike fixit /usr/bin

This command sequence installs a new command by copying the program fixit to /usr/bin/fixit, with user mike as the owner.

Files

/usr/ucb/install /usr/bin/installbsd Hard-link to the /usr/bin/installbsd file. Contains the installbsd command.

Related Information

The chgrp command, chmod command, chown command, cp command, install command, mv command, **strip** command.

installios Command

Purpose

Sets up the environment and creates NIM resources from the Virtual I/O Server DVD to install the Virtual I/O logical partition and the Integrated Virtualization Manager.

Syntax

To set up the environment and create NIM resources for installing a Virtual I/O logical partition or Integrated Virtualization Manager:

installios [-p partition_name -i ipaddrorhostname -S subnet_mask -g gateway -d path -s system_name -r profile [-n] [-P speed] [-D duplex] [-I language] [-L location]]

To clean up tasks from the setup process:

installios -u [-f | -U]

Description

The installios command creates NIM resources from the Virtual I/O Server DVD to install a Virtual I/O logical partition and Integrated Virtualization Manager. When invoked on a NIM client, the -L flag must be specified with the location of the bos.sysmgt.nim.master fileset. The installios command configures the client as a NIM master and creates the resources from the Virtual I/O Server DVD to install the ioserver logical partition or the Integrated Virtualization Manager. After the logical partition or Integrated Virtualization Manager have been installed, the installios command can return the NIM master back to its original state by removing the created resources from the DVD or by unconfiguring the NIM master. All of the flags are optional. If no flags are specified, the installios wizard runs and the user is prompted to interactively enter the flag information.

Flags

-d path

-D duplex

Specifies the path to the installation images (/dev/cd0 or the path to a system backup of the Virtual I/O Server created by the **backupios** command. The path may also specify a remote NFS-mountable location such as hostname:/path_to_backup.

Specifies duplex (optional). This is the duplex setting with which to configure the client's network interface. This value can be full or half. The default value is full if this flag is not specified.

Forces a cleanup to deallocate and remove resources which are not yet installed on a Virtual I/O logical partition or Integrated Virtualization Manager.

-f

Specifies the client gateway (the default gateway that the -g gateway client will use during network installation of the Virtual I/O Server operating system). -i ipaddrorhostname Specifies the client IP address or hostname (the IP address or hostname with which the client's network interface will be configured for network installation of the Virtual I/O Server operating system). -I language Specifies the language (optional). This is the language in which the license agreement will be displayed before the installation. When the license is viewed, a prompt displays asking if the license is to be accepted. If the prompt is answered with y, then the installation will proceed and the Virtual I/O Server license is automatically accepted after installation. If the prompt is answered with n, the installios command exits and the installation does not proceed. If this flag is not specified, the installation proceeds, but the Virtual I/O Server will not be usable until the license is manually accepted after installation. Specifies the location of the bos.sysmgt.nim.master fileset -L location to configure a client to become a NIM master. -n Specifies that the client's network interface should not be configured. If this flag is specified, the client's network interface will not be configured with the IP settings that were specified in the flags given to the installios command after the installation has completed. Specifies the partition name. This is the name of the -p partition_name LPAR that will be installed with Virtual I/O Server operating system. This partition must be of type Virtual I/O Server and the partition name must match the name shown on the HMC; the name is not a host name. -P speed Specifies speed (optional). This is the communication speed to use when configuring the client's network interface. This value can be 10, 100, or 1000. The default value is 100 if this flag is not specified. Specifies the profile name. This is the name of the profile -r profile that will contain the hardware resources that will be installed Specifies the managed system (the name of the managed -s system_name system maintained by the HMC). This name must match the name shown on the HMC; the name is not a host -S subnet mask Specifies the client subnet mask (the subnet mask with which the client's network interface will be configured for network installation of the Virtual I/O Server operating system). -u Cleans up the environment to return the NIM master back to its original state. -U Unconfigures the NIM master.

Exit Status

The installios command was successful.

Security

You must have root authority to run the installios command

Examples

1. To create Virtual I/O resources on a NIM master for installing client 9.3.6.234, type:

```
installios -d /dev/cd0 -i 9.3.6.234 -g 9.3.6.1 -S 255.255.255.0
```

2. To create Virtual I/O resources on a NIM client for installing client 9.3.6.234 where /tmp contains the bos.sysmgt.nim.master fileset, type:

```
installios -d /dev/cd0 -i 9.3.6.234 -g 9.3.6.1 -S 255.255.255.0 -L /tmp
```

3. To clean up tasks performed while creating Virtual I/O resources, type:

```
installios -u
```

4. To clean up tasks performed during the creation of Virtual I/O resources on a logical partition which has not yet been installed, type:

```
installios -u -f
```

5. To clean up tasks and unconfigure NIM after creating Virtual I/O resources, type:

```
installios -u -U
```

Location

/usr/sbin/installios

Files

/usr/sbin/installios /etc/niminfo

Contains the installios command Contains variables used by NIM

Related Information

The nim_master_setup command, nim command, and nimconfig command.

installp Command

Purpose

Installs available software products in a compatible installation package.

Syntax

To Install with Apply Only or with Apply and Commit

```
installp [ -a | -a -c [ -N ] ] [ -eLogFile ] [ -V Number ] [ -dDevice ] [ -E ] [ -Y ] [ -b ] [ -S ] [ -B ] [ -D ] [ -I ] [
-p ] [ -Q ] [ -q ] [ -X ] [ -F | -g ] [ -O { [ r ] [ s ] [ u ] } ] [ -tSaveDirectory ] [ -w ] [ -zBlockSize ] {
FilesetName [ Level ]... | -f ListFile | all }
```

To Commit Applied Updates

```
install p - c [ -e Log File ] [ -V Number ] [ -b ] [ -g ] [ -p ] [ -v ] [ -X ] [ -O { [ r ] [ s ] [ u ] } ] [ -w ] { } \\
FilesetName [ Level ]... | -f ListFile | all }
```

To Reject Applied Updates

```
FilesetName [ Level ]... | -f ListFile }
```

To Deinstall (Remove) Installed Software

```
installp -u [ -eLogFile ] [ -VNumber ] [ -b ] [ -g ] [ -p ] [ -v ] [ -X ] [ -O { [ r ] [ s ] [ u ] } ] [ -w ] {
FilesetName [ Level ]... | -f ListFile }
```

To Clean Up a Failed Installation:

installp -C [-b] [-eLogFile]

To List All Installable Software on Media

installp { -I | -L } [-eLogFile] [-d Device] [-B] [-I] [-q] [-E] [-zBlockSize] [-O { [s] [u] }]

To List All Customer-Reported Problems Fixed with Software or Display All Supplemental Information

installp { -A| -i } [-eLogFile] [-dDevice] [-B] [-I] [-q] [-z BlockSize] [-O { [s] [u] }] { FilesetName [Level]... | -f ListFile | all }

To List Installed Updates That Are Applied But Not Committed

installp -s [-eLogFile] [-O { [r] [s] [u] }] [-w] { FilesetName [Level]... | -fListFile | all }

To List Platform Specific Installable Software on Media

installp { -I | -L } { -MPlatform } [-eLogFile] [-d Device] [-B] [-I] [-q] [-z BlockSize] [-O { [s] [u] }

Description

Notes:

- 1. The noclobber option of the Korn or C shell should be unset in the environment from which an installation is performed.
- 2. Update all can be accomplished with smitty or with install_all_updates.

The **installp** command installs and updates software.

A fileset is the lowest installable base unit. For example, bos.net.tcp.client 4.1.0.0 is a fileset. A fileset update is an image with a different modification level or a different fix level. For example, bos.net.tcp.client 4.1.0.2 and bos.net.tcp.client 4.1.1.0 are both fileset updates for bos.net.tcp.client 4.1.0.0.

When a base level (fileset) is installed on the system, it is automatically committed. You can remove a fileset regardless of the state (such as committed, broken, committed with applied updates, and committed with committed updates).

When a fileset update is applied to the system, the update is installed. The current version of that software, during installation, is saved in a special save directory on the disk so that later you can return to that version if desired. After a new version of a software product has been applied to the system, that version becomes the currently active version of the software.

Updates that have been applied to the system can be either committed or rejected at a later time. The installp -s command can be used to get a list of applied updates that can be committed or rejected.

When updates are committed with the -c flag, the user is making a commitment to that version of the software product. The saved files from all previous versions of the software product are removed from the system, making it impossible to return to a previous version of the software product. Software can be committed at the time of installation by using the -ac flags.

Note: Committing the already applied updates does not change the currently active version of a software product. It merely removes saved files for previous versions of the software product.

When a base level is removed with the -u flag, the files that are part of the software product and all its updates are removed from the system. Most cleanup of system configuration information pertaining to the product is also done, but this is dependent on the product and may not always be complete.

When a software product update is rejected with the -r flag, the current version of the software product is changed to the immediate previous version of the update. Files saved for the rejected update and any updates that were applied after it are removed from the system.

A software product that is to be removed from the system can be in any state. Product updates can be in either the applied or committed state, and they will also be removed.

If a previously interrupted installation leaves any software in a state of either applying or committing, it is necessary to perform cleanup with the -C flag before any further installations are allowed. Although the installp -C command accepts software product names on the command line without returning an error, an attempt is always made to clean up all products when the -C flag is used. An attempt is made to clean up any incomplete installations by removing those parts that were previously completed. An attempt is also made to return to the previous version of the software product, if one exists, as the currently active version. If this cannot be done, the software product is marked as broken, and unpredictable results can occur if the user attempts to use it. Therefore, it is advisable for the user to reinstall any broken software products or updates.

The -t flag specifies an alternate location for a save directory that holds files being replaced by an update. This option is primarily useful in the following two circumstances.

- · You have enough local disk space for saving replaced files but you do not want to permanently expand the root and /usr file systems.
 - In this case, you can choose to create a separate file system for the alternate save directory. When you are satisfied with the updated system and have committed all applied updates, disk space can be retrieved by deleting the save file system.
- You do not have enough local disk space for saving replaced files but you have access to ample disk space on a remote system. In this case, you can specify a directory that is mounted from a remote file system.
 - If a remote file system is used, commit the updates as soon as possible. You may want to initiate the installation action as an apply and commit operation with the -ac flags. If you want to apply only to be able to reject unwanted updates, then test the newly installed updates as soon as possible and then commit or reject them.
 - Take into account the following considerations when using an alternate save directory:
- It is recommended that you use the same alternate save location on each invocation of the installp command.
- · If an alternate save directory is used for an apply operation, make sure that the file system containing that directory remains mounted. It is highly recommended that any necessary mounts be done automatically on a reboot.
- · If an alternate save directory is missing on a commit operation, the commit takes place, and a warning is given stating that the save directory could not be deleted. In this case, you must delete the save directories that are no longer used in order to retrieve that disk space.
- If an alternate save directory is missing on reject, the reject operation cannot be done because the saved files are missing. An error is given, and the entire reject operation is canceled. If the missing save directory is not caused by a temporary situation (for example, the inability to contact a remote directory on the network) your only options are to commit the updates or leave them in an applied state permanently.
- · When doing a system backup, ensure that you back up any alternate save directories that do not reside in the root volume group.
- · The installation process safeguards users with a remote save directory from the possibility of two different systems using the same remote directory. However, use directory path names that easily and uniquely identify each user's system. For example, you can add the system's host name in the path name.

 Do not create a mksysb backup of a system with a remote save directory and then try to restore the mksysb image onto a system other than the original. In this case, using a mksysb image to install several like systems causes multiple ownership of the same remote save directory.

The **installp -A** command can be used to obtain a list of the Authorized Program Analysis Report (APAR) numbers and summaries for all customer-reported problems that are fixed in the specified software package. The **installp -i** command can be used to display supplemental information contained in files that can be a part of the specified software package.

To list all the software products and updates on the specified installation media, use the **installp -l** command. The output of the **installp** command with the **-l** flag resembles the following:

```
Level
# Fileset Name
                                        I/U Q Content
X11.adt.include 4.1.0.0
                                       T Nusr
 AIXwindows Application Development Toolkit Include F
                     4.1.0.0
  AIXwindows Application Development Toolkit Libraries
 X11.adt.motif 4.1.0.0
                                        I Nusr
  AIXwindows Application Development Toolkit Motif
 X11.adt.bitmaps 4.1.0.0
                                        I Nusr
  AIXwindows Application Development Toolkit Bitmap Fi
             4.1.0.0
                                        I Nusr
 X11.adt.ext
  AIXwindows Application Development Toolkit for X Ext
                   4.1.0.0
  AIXwindows Application Development Toolkit imake
 X11.apps.rte
                   4.1.0.0
                                        I Nusr
  AIXwindows Runtime Configuration Applications
 X11.apps.msmit
                   4.1.0.0
                                       I N usr
 AIXwindows msmit Application
```

The field descriptions are as follows:

Fileset Name Level I/U Name of the fileset to be installed. Level of the fileset to be installed.

The type of package to which the fileset belongs. The fileset can belong to an installation package or to one of several types of update packages. The package types are as follows:

- I Indicates an installation package.
- **S** Indicates a single update.
- SR Indicates a required update. Whenever the **installp** command encounters a required update, the update is automatically included in the input list.
- SF Indicates a required update. Whenever the **installp** command encounters a required update, the update is automatically included in the input list. Reserved for updates to the **installp** fileset.
- M Indicates a maintenance or technology package. This is a packaging update that contains only a list of other updates to be applied. This package delivers no files.
- **ML** Indicates an update package that identifies a new maintenance or technology level for the product. This is a cumulative set of all updates since the previous product level.

Quiescent (quiet) column. A Y indicates that running processes can be affected by the Q

installation of this fileset. Refer to the documentation supplied with the software product. An N

indicates that running processes are not affected by the installation of this fileset. A B

indicates **bosboot** and quiescent. A **b** indicates **bosboot** and not quiescent.

Content column: Content

usr,root

/usr and root file systems (AIX 3.2 and later)

/usr file system only (AIX 3.2 and later) usr

share /usr/share file system only (AIX 3.2 and later)

Output from the installp -s command, which is used to get a list of applied software fileset updates and updates that are available to be either committed or rejected, resembles the following:

Installp Status

Name	Part	Level	State
bos.net.tcp.client bos.net.tcp.client bos.rte.commands bos.rte.misc cmds	USR ROOT USR USR	4.1.0.2 4.1.0.2 4.1.0.1 4.1.0.1	APPLIED APPLIED APPLIED APPLIED
bos.rte.tty	USR	4.1.0.1	APPLIED

The field descriptions are as follows:

Name of the installed software product fileset. Name

Part The part of the fileset where:

ROOT root file system SHARE /usr/share file system USR /usr file system.

The level of the installed software product option. Level The state of the installed software product option. State

The software products and updates to be installed can be identified in one of following ways:

- by the keyword all, which indicates that all software contained on the specified installation media is to be installed
- · by a list of software product names (each of which can optionally be followed by a level) that indicates the software to be installed
- · by the -f flag followed by a file name, where each line in the file is an entry containing a software product name, optionally followed by a level, or is a comment line that begins with a # and is ignored

Note: The installp program uses the sysck command to verify files after restoring them. The sysck command does not recognize the following special characters in file names: ~, `, ', \, ", \$, ^, &, (), I, {}, [], <>, and ?. If a file name contains any of these characters, installation fails.

The FilesetName parameter can be used to specify an entire software product or any separately installable filesets within the software package. For example, bos.net is the name of a software package, and the separately installable filesets within that software package are bos.net.ncs.client, bos.net.nfs.client, and bos.net.tcp.client. If the user specifies bos.net for the FilesetName parameter, then all of the separately installable filesets listed are installed. If the user specifies bos.net.tcp.client for the FilesetName parameter, then only that fileset is installed.

The Level parameter indicates the level of the software product or update that is to be installed. The Level parameter is of the form *vv.rr.mmmm.ffff* where:

VV	is a numeric field of 1 to 2 digits that represents the version number.
rr	is a numeric field of 1 to 2 digits that represents the release number.
mmmm	is a numeric field of 1 to 4 digits that represents the modification level. Modification level is also

called maintenance level or technology level.

is a numeric field of 1 to 4 digits that represents the fix level.

If a user is installing an installation package from installation media that contains only installation packages it is not necessary to specify the level. More than one software product installation package with different levels does not often exist on the same installation medium. However, when this does occur **installp** installs the specified software product at the latest software product level when *Level* is not specified with *FilesetName*. For installation media that contain either update packages only or contain both installation and update packages, all applicable update packages that are present on the installation media for the specified *FilesetName* are also installed when *Level* is not specified. For installation media that contain both installation and update packages the user can request the installation of only installation packages or only update packages by specifying the **-I** or **-B** flags, respectively. If the user wants to install only some of the updates on the installation medium for a specific software product both *FilesetName* and *Level* for each of the updates to be installed for that software product must be specified.

You can use the following example to to install TCP/IP and one of its updates that are both contained in the /usr/sys/inst.images directory.

```
installp -a -d/usr/sys/inst.images bos.net.tcp.client 4.1.0.0
bos.net.tcp.client 4.1.0.2
```

Note: If there are duplicate filesets at the same level, **installp** uses the first one that it finds in the install table of contents (.toc). This situation can occur when **bffcreate** is used to extract images from different media to the same installation directory. For this reason, make sure that update images are not extracted to the same directory as base level images for the same fileset at the same level.

A summary report is given at the end of the **installp** output that lists the status of each of the software products that were to be installed. An example summary report for the previous **installp** command is as follows:

Installp Summary

Name	Level	Part	Event	Result
bos.net.tcp.client bos.net.tcp.client	4.1.0.0 4.1.0.0	USR ROOT	APPLY APPLY	SUCCESS SUCCESS
bos.net.tcp.client	4.1.0.2	USR	APPLY	SUCCESS

Notes:

- 1. If a previously installed level of a fileset update is in the broken state, the **-acgN** flags must be used when that fileset update is installed again.
- 2. The **installp** command cannot install a mkinstallp package or bff image that is larger than 2 GB in size. An alternative is to break the bff image into multiple packages that are less than 2 GB in size.
- 3. If an attempt is made to update a fileset that is locked by the interim fix manager (the **emgr** command), a notice is displayed indicating the filesets that are locked. The **Islpp** command shows that any locked filesets are in the EFIXLOCKED state.
- 4. If an attempt is made to update a fileset that has an installed build date more recent than the build date of the selected fileset, a message is displayed to indicate this. For more information about build dates, see Checking fileset build dates in *Installation and migration*.

Summary Report Values

The summary report identifies the name of the product option and the part of the product. Other information given includes the requested action (event) and the result of that action.

Event Values

The Event column of the summary report identifies the action that has been requested of the installp command. The following values are displayed in this column:

Event Definition

APPLY An attempt was made to apply the specified fileset.

COMMIT An attempt was made to commit the specified fileset update. REJECT An attempt was made to reject the specified fileset update. CLEANUP An attempt was made to perform cleanup for the specified fileset.

DEINSTALL An attempt was made to remove the specified fileset.

Result Values

The Result column of the summary report gives the result of installp performing the requested action. It can have the following values:

Result Definition

SUCCESS The specified action succeeded. **FAILED** The specified action failed.

CANCELLED Although preinstallation checking passed for the specified option, it was necessary to cancel the

specified action before it was begun. Interrupting the installation process with Ctrl+c can sometimes

cause a canceled action, although, in general, a Ctrl+c interrupt causes unpredictable results.

Flags

-B

Displays the APAR number and summary of all customer-reported problems that are -A

fixed in the specified software package. No installation is attempted.

Applies one or more software products or updates. This is the default action. This flag -a

can be used with the -c flag to apply and commit a software product update when

-b Prevents the system from performing a bosboot in the event that one is needed.

Indicates that the requested action should be limited to software updates.

-C Cleans up after an interrupted installation and attempts to remove all incomplete

> pieces of the previous installation. Cleanup must be performed whenever any software product or update is in a state of either applying or committing and can be run manually as needed. For backward compatibility, other flags and parameters can

be accepted with installp -C, but are ignored because all necessary cleanup is

attempted.

Commits all specified updates that are currently applied but not committed. When an -C

> update is committed all other software products it is dependent on must also be committed (unless they are already in the committed state). The specified software product is dependent on any software product that is a prerequisite or corequisite of the specified product. If the requisite software products are not in the committed state, the commit fails and error messages are displayed. The -g flag can be used to

automatically commit requisite software product updates.

-D Deletes the installation image file after the software product or update has been

> successfully installed. When the -q flag is specified, the installation image files for any products that are automatically included are also eleted. This flag is valid only with the -a or -ac flags and is not valid with the -Or flag. This flag is also only valid when the device is a directory and an installation image file on the system where the

installation is taking place.

-d Device Specifies where the installation media can be found. This can be a hardware device

> such as tape or diskette, it can be a directory that contains installation images, or it can be the installation image file itself. When the installation media is a product tape or Corrective Service tape, specified the tape device as no-rewind-on-close and no-retension-on-open. Examples of this would be /dev/rmt0.1 for a high density tape, or /dev/rmt0.5 for a low density tape. Use the options specified by the tape supplier.

The default device is /dev/rfd0.

-e LogFile

Enables event logging. The **-e** flag enables the user to append certain parts of the **installp** command output to the file specified by the *LogFile* variable. By default the output of the **installp** command goes to **stdout** and **stderr**, unless SMIT or VSM is used, in which case the output goes to the **smit.log**. The *LogFile* variable must specify an existing, writable file, and the file system in which the file resides must have enough space to store the log. The log file does not wrap.

Not all output is appended. Copyright information is still displayed to the user. Error messages are displayed on the screen and are sent to the file specified by the *LogFile* variable. A results summary of the **installp** command invocation is also displayed on the screen and sent to the *LogFile*. This flag is primarily used by NIM and BOS install to limit the output shown to the user, but keep useful information for later retrieval.

Displays software license agreements. This flag is only valid with the **-a** or **-I** flags. If the **-E** flag is specified with the **-a** flag, a new section is displayed showing the pending license agreements associated with the selected filesets. If the **-E** flag is specified with the **-I** flag, output is displayed showing the license agreements associated with all filesets on the media.

This option can be used to force the installation of a software product even if there exists a previously installed version of the software product that is the same as or newer than the version currently being installed. The **-F** flag is not valid with update packages or the **-g** flag. When you use the **-F** flag, the **-I** flag is implicit.

Reads the names of the software products from *ListFile*. If *ListFile* is a - (dash), it reads the list of names from the standard input. Software fileset names, optionally followed by a level, should be one per line of text, and any text following the second set of white spaces or tabs on a line is ignored. Output from the **installp -I** command is suitable for input to this flag.

When used to install or commit, this flag automatically installs or commits, respectively, any software products or updates that are requisites of the specified software product. When used to remove or reject software, this flag automatically removes or rejects dependents of the specified software. The **-g** flag is not valid when used with the **-F** flag.

Note: This flag also automatically pulls in a superseding update present on the media if the specified update is not present. This flag causes the newest update to be installed for a given fileset, when there are multiple superseding updates for the same fileset on the installation media.

(uppercase i) Indicates that the requested action must be limited to base level filesets.

Displays on standard output the **Ipp.instr**, **Ipp.doc**, **Ipp.README**, and **README** files on the installation media for the software product, if they exist. This flag can take a significant amount of time for a large number of filesets.

This flag is used when the **installp** command is executed from the System Management Interface Tool (SMIT) menus.

(lowercase L) Lists all the software products and their separately installable options contained on the installation media to standard output. No installation occurs. The -I flag is not valid with the -Or flag.

Displays the contents of the media by looking at the table of contents (TOC) and displaying the information in colon-separated output. This flag is used by smit and vsm to list content of the media. The format provided:

package:fileset:v.r.m.f:PTF:type:state:supersede:\
sup_ptf:sup_state:latest_sup:quiesce:Descr:\
netls_vendor_id:netls_prod_id:netls_prod_ver:relocatable:build date
Specifies the Platform value. Any of the following values can be used to list the installable software packages:

- R Specifies POWER-based platform packages only.
- N Specifies neutral packages, that is, packages that are not restricted to the POWER-based platform.
- A Specifies all packages.

-E

-F

-f ListFile

-g

-1

-i

-J

-1

-L

-MPlatform

-N

-O{[r][s][u]}

-р

-Q

-q

-r

-s

-S

-t SaveDirectory

-u

-v

Overrides saving of existing files that are replaced when installing or updating. This flag is valid only with the -ac flags. If there is a failure in the system during the installation, there is no recovery of replaced files when this flag is used.

Installs the specified part of the software product. The r indicates the / (root) part is to be installed, the s indicates the /usr/share part is to be installed, and the u indicates the /usr part is to be installed. The -O flag is not needed with standard systems because without this flag all parts are installed by default. This flag is needed for use with the installation of diskless or dataless workstations and is designed for use by the nim command. The -Or option is not valid with the -d or -I flags.

Performs a preview of an action by running all preinstallation checks for the specified action. This flag is only valid with apply, commit, reject, and remove (-a, -c, -r, and -u) flags.

Suppresses errors and warnings concerning products failing to install due to instrequisites. This flag applies only to AIX 4.2 or later.

Specifies quiet mode, which suppresses the prompt for the device, except for media volume change.

Rejects all specified software updates that are currently applied but not committed. When a software update is rejected any other software product that is dependent on it (that is, those software products that have the specified software product as a requisite) must also be rejected. The -q flag can be used to reject automatically dependent software updates. The keyword all is not valid with the reject flag (-r). For backward compatibility, the -R flag is also accepted as a reject flag. The -R cannot be used to remove base level filesets; use the -u flag.

Lists information about all software products and updates that have been applied but not committed. This list comprises the software that is available to be either committed or rejected.

Suppresses multiple volume processing when the installation device is a CD-ROM. Installation from a CD_ROM is always treated as a single volume, even if the CD-ROM contains information for a multiple volume CD set. This same suppression of multiple volume processing is performed if the INU_SINGLE_CD environment is

Specifies an alternate save directory location for files being replaced by an update.

The -t flag is only valid with an apply or an apply/commit operation for updates. This flag is not valid with the -N flag.

The -t flag is useful when there is insufficient space in the default file systems (/ and /usr) or when it is undesirable to permanently expand these file systems. It may be desirable for the specified directory to be a remote file system. A remote file system must have ample space, because the installp command cannot expand remote file systems.

Removes the specified software product and any of its installed updates from the system. The product can be in either the committed or broken state. Any software products that are dependent on the specified product must also be explicitly included in the input list unless the -q flag is also specified. Removal of any bos.rte fileset is never permitted.

Verifies that all installed files in the fileset have the correct checksum value after the installation. Installed files are always verified for correct file size after installation. Use this flag after network or remote device installations. If any errors are reported, it might be necessary to install the software product again. Post-installation requisite consistency checks are also started by this flag.

-V Number

Specifies the verbose option that provides four levels of detail for preinstallation output. The valid values for the *Number* parameter are 2, 3, or 4. The default level of verbosity, without the use of the -V flag, prints an alphabetically ordered list of FAILURES, WARNINGS, and SUCCESSES from preinstallation processing. Requisite failures are reported with emphasis on the real cause of the failure. Extraneous requisites for failed filesets are not displayed. The preinstallation output is modified by levels 2 through 4 as described below:

- Prints alphabetically ordered list of FAILURES and WARNINGS. Requisite failures are displayed with additional information describing requisite relationships between selected filesets and the requisites causing them to fail. Failing requisites suppressed under *Level 1* are displayed. Preinstallation SUCCESSES are displayed in the order in which they are processed.
- 3 Level 3 is the same as Level 2, with the exception that additional requisite information is displayed for SUCCESSES.
- 4 Level 4 is the same as Level 3 for SUCCESSES and WARNINGS. Requisite failures are displayed in a format depicting detailed requisite relationships.

Note: If verbosity level 2 or higher is used, the files that are restored on to the system is shown in the output. Because this will make **installp**'s output much more verbose, make sure that your *I* (root) filesystem does not become full when the /smit.log becomes large (if using smit to run installp).

Does not wildcard *FilesetName*. Use this flag from smit so it only installs the fileset chosen and not the filesets that match. For example, if you choose foo.rte, foo.rte.bar is not automatically pulled in, as it would be by default, without the **-w** flag. This flag applies only to AIX 4.2 or later.

Attempts to expand any file systems where there is insufficient space to do the installation. This option expands file systems based on current available space and size estimates that are provided by the software product package. Note that it is possible to exhaust available disk space during an installation even if the **-X** flag is specified, especially if other files are being created or expanded in the same file systems during an installation. Also note that any remote file systems cannot be expanded.

Agrees to required software license agreements for software to be installed. This flag is only valid with the **-a** flag.

Indicates in bytes the block size of the installation media. The default value of Size is 512.

This is the name of the software product to be installed and can specify either an entire software product or any separately installable filesets within the software product. This can be used to specify the name of a fileset or fileset update. This indicates the level of the software product or update that is to be installed and is

of the form vv.rr.mmmm.ffff. If a fileset update has an additional fix ID (also know as ptf id), that ID must also be specified in the Level as in vv.rr.mmmm.ffff.ppppppp.

-w

-X

-Y

-z BlockSize

FilesetName

Level

Return Values

A zero (0) return value indicates that all attempted installations were successful, or that no processing was required for the requested action on the requested filesets (for example, if a requested fileset was already installed).

A nonzero return value indicates that some part of the installation was not successful.

A summary report is given at the end of the **installp** output that lists the status of each of the software products that were to be installed. For those software products that could not be installed or whose installation failed, the user can search for the cause in the more detailed information that is continually displayed from the **installp** command during the installation process.

Security

Privilege Control: Only the root user can run this command.

Auditing Events:

Event Information

INSTALLP_Inst Success or failure of the apply, commit, reject, and cleanup operations.

Examples

- 1. To list all software products and installable options contained on an installation cartridge tape, type: installp -L -d /dev/rmt0.1
- 2. To list all customer-reported problems fixed by all software products on an installation tape, type: installp -A -d /dev/rmt0.1 all
- 3. To install (automatically committed) all filesets within the bos.net software package (located in the /usr/sys/inst.images directory) and expand file systems if necessary, type:

```
installp -aX -d/usr/sys/inst.images bos.net
```

4. To reinstall and commit the NFS software product option that is already installed on the system at the same level (from tape), type:

```
installp -acF -d/dev/rmt0.1 bos.net.nfs.client 4.1.0.0
```

5. To install (apply only) certain updates that are contained on diskette for the TCP/IP software product,

```
installp -a bos.net.tcp.client 4.1.0.2 bos.net.tcp.server 4.1.0.1
```

6. To remove a fileset named bos.net.tcp.server, type:

```
installp -u bos.net.tcp.server
```

7. To specify an alternate storage directory on a remote file system for a BOSNET TCP/IP update with -t/temp_space, see the following example: the save directory becomes /temp_space/My_Hostname/ usr/lpp/bos.net/bos.net.nfs.client/4.1.1.0.save.

```
mount Server_Name:/Save_Area /temp_space
installp -a -t /temp space/My Hostname \
bosnet.nfs.client 4.1.1.0
```

8. To capture a log file of all output from the installp command, use the script command as in the following example. Output is written to the typescript file in the current directory.

```
script
installp ...
<Ctrl>d
or
installp ... 2>&1 | tee /tmp/inst.out
```

In the second example, output is written to the screen and a copy is saved.

9. To preview the installation of the **bos.net.tcp.client** fileset from the CD using the **installp** command,

```
installp -pacgXd /dev/cd0 bos.net.tcp.client
```

10. To install TCP/IP and one of its updates that are both contained in the /usr/sys/inst.images, use the **installp** command as in the following example.

A summary report is given at the end of the **installp** command output that lists the status of each of the software products that were to be installed. An example summary report for the previous installp command is as follows:

Installp Summary

Name	Level	Part	Event	Result
bos.net.tcp.client bos.net.tcp.client bos.net.tcp.client	4.1.0.0 4.1.0.0 4.1.0.2	USR ROOT USR	APPLY APPLY APPLY	SUCCESS SUCCESS

Note: This summary is also saved in /var/adm/sw/installp.summary until the next installp invocation. The header file inuerr.h in the /usr/include directory describes the fields making up the records in the installp.summary file.

11. To list software products (located in the /usr/sys/inst.images directory) that are installable on POWER-based machines, type:

```
installp -1 -MR -d /usr/sys/inst.images
```

12. To update all filesets from a CD that are currently installed on the system, type:

```
lslpp -lc | awk -F ":" '{print $2}' | tail -n +2 > /tmp/lslpp
installp -agXd /dev/cd0 -e /tmp/install.log -f /tmp/lslpp
```

where the -e logs the output to the /tmp/install.log file.

Files

/dev/rfd0 /dev/rmtn /usr/sys/inst.images directory Specifies the default restore device.

Specifies the raw streaming tape interface.

Contains files in backup format for use in installing or updating a complete set or subset of software products.

Related Information

The **bffcreate** command, **inudocm** command, **inutoc** command, **Ippchk** command, **Islpp** command, **sysck** command.

instfix Command

Purpose

Installs filesets associated with keywords or fixes.

Syntax

instfix [-T [-M Platform]] [-s String] [-S] [-k Keyword | -f File] [-p] [-d Device] [-i [-c] [-q] [-t
Type] [-v] [-F]] [-a]

Description

The **instfix** command allows you to install a fix or set of fixes without knowing any information other than the Authorized Program Analysis Report (APAR) number or other unique keywords that identify the fix.

Any fix can have a single fileset or multiple filesets that comprise that fix. Fix information is organized in the Table of Contents (TOC) on the installation media. After a fix is installed, fix information is kept on the system in a fix database.

The **instfix** command can also be used to determine if a fix is installed on your system.

Note: Return codes for the **instfix** command are documented in the **/usr/include/inuerr.h** file, which is shipped with the bos.adt.include fileset. There is also a general failure code of 1 and a single reference to EACCES (13) from **/usr/include/errno.h**.

Flags

-F

-i

-a	Displays the symptom text associated with a fix. Can be combined with the -i, -k, or -f flag.
-c	Displays colon-separated output for use with -i flag. Output includes keyword name, fileset
	name, required level, installed level, status, and abstract. To display filesets that are not
	installed, the -v flag must also be used. Status values are:

Down level

Correct level =

Superseded

Not installed

-d Device Specifies the input device. Not valid with the -i and -a flags.

Returns failure unless all filesets associated with the fix are installed.

-f File Specifies the input file containing keywords or fixes. Use - (dash) for standard input. The -T flag

produces a suitable input file format for -f.

Displays whether fixes or keywords are installed. Use this flag with the either the -k or the -f flag. Installation is not attempted when the -i flag is used. If you do not specify the -k or the -f

flag, all known fixes are displayed.

-k Keyword Specifies an APAR number or keyword to be installed. Multiple keywords can be entered. A list

of keywords entered with the -k flag must be contained in quotation marks and separated with

spaces.

-M Platform Specifies that any of the Platform values may be used to list the fixes for that particular

platform.

R Specifies POWER-based platform fixes only.

N Specifies neutral fixes, that is, fixes that are not restricted to the POWER-based

platform.

Specifies all fixes.

Displays filesets associated with keywords. This flag is used with either the -k or the -f flag. -p

Installation is not attempted when the -p flag is used.

-q Specifies quiet mode. Use this flag with the -i flag. If you use the -c flag, no heading is

displayed, otherwise there is no output.

-s String Searches for and displays fixes on media containing a specified string.

Suppresses multiple volume processing when the installation device is a CD-ROM. Installation -S

from a CD ROM is always treated as a single volume, even if the CD-ROM contains

information for a multiple volume CD set. This same suppression of multiple volume processing

is performed if the INU_SINGLE_CD environment is set.

-T Displays the entire list of fixes present on the media.

-tType Used with the -i flag to limit searches to a given type. Valid types are:

preventive maintenance

Used with the -i flag to specify verbose mode. Displays information about each fileset associated with a fix or keyword. Use this flag with the -i flag to display filesets that are not

installed. An uninstalled fileset is indicated by an! (exclamation point).

Security

Privilege Control: You must be the root user to install using the instfix command, but any user can run the instfix command to query the fix database.

Examples

1. To install all filesets associated with fix IX38794 from the tape mounted on /dev/rmt0.1, type:

instfix -k IX38794 -d /dev/rmt0.1

2. To install all fixes on the media in the tape drive, type:

```
instfix -T -d /dev/rmt0.1 | instfix -d /dev/rmt0.1 -f-
```

The first part of this command lists the fixes on the media, and the second part of this command uses the list as input.

3. To list all keyword entries on the tape containing the string SCSI, type:

```
instfix -s SCSI -d /dev/rmt0.1
```

4. To inform the user on whether fixes IX38794 and IX48523 are installed, type:

```
instfix -i -k "IX38794 IX48523"
```

5. To create a list of filesets associated with fix IX12345 for bffs in the /bffs directory, type:

```
instfix -p -k IX12345 -d /bffs | installp -acgX -f- -d /bffs
```

This sequence passes the list of fixes to the **installp** command to be applied and committed. The **installp** command extends filesystems as needed with the flags shown. This example shows that you can select other **installp** flags. The **instfix** command calls **installp** if the **-p** flag is not used.

6. To list all of the fixes that are not restricted to the POWER-based platform, type:

```
instfix -T -MN -d /dev/cd0
```

Files

/usr/sbin/instfix Contains the instfix command.

/usr/lib/objrepos/fix Specifies the path to the Object Data Manager database.

Related Information

The **installp** command.

inucp Command

Purpose

Performs simple copy operations for the **installp** command. This command is used by the **installp** command and the install scripts.

Syntax

inucp -s StartDirectory [-e FinalDirectory] ListFile ProductName

Description

The **inucp** command copies the files in a file tree with its root at *StartDirectory* to the appropriate place on the *FinalDirectory* root.

Before replacing files that may already exist in the *FinalDirectory* file tree, the **inusave** command should be called to save the files until needed by the **inurecv** command.

The *ListFile* parameter specifies a list, one per line, of all the files for *ProductName*. *ListFile* is the full path name of the file that contains the relative path names of files that the product needs to have copied.

The ProductName parameter specifies the name of the software product to be copied.

Flags

-e FinalDirectory Indicates the root of the file tree that the files are to be copied to. The

FinalDirectory should be the base of the file tree. The default directory is the / (root)

directory when this flag is not specified.

-s StartDirectory Indicates the root of the file tree that the files are to be copied from.

Environment Variables

INUEXPAND This flag is set to 1 by the **installp** command if file systems are to be expanded if necessary to

do the copy (that is, the -X flag was passed). It is set to 0 if file systems are not to be expanded.

If this environment variable is not set, the default is not to expand file systems.

INUTEMPDIR This flag is set by the installp command to the path of the current temporary directory. If this flag

is not set the default is /tmp.

Error Codes

The **inucp** command returns the following error codes, which are defined in **inuerr.h**.

INUACCS One or both of StartDirectory and FinalDirectory are not directories.

INUBADAR Could not archive files in Ipp.acf file.

INUBADC1 The copy operation failed. INUBADMN Unrecognizable flag specified. INUGOOD No error conditions occurred. INUNOAP2 Could not access the ListFile. INUNODIR No write access to FinalDirectory.

INUNOLPP One or both of StartDirectory and FinalDirectory do not have the necessary permissions.

INUNOMK Could not create a needed directory.

INUNOSPC Insufficient space for the copy and INUEXPAND was not set.

INUTOOFW One or more parameters were missing. INUTOOMN Too many parameters were specified.

Security

Privilege Control: You must be the root user to run this command.

Examples

To copy all the files listed in the /usr/lpp/X11/inst_root/al list from the /usr/lpp/X11/inst_root file tree to the root directory, enter:

inucp -s /usr/lpp/X11/inst root /usr/lpp/X11/inst root/al X11

Related Information

The installp command, inurecy command, inurest command, inusave command.

inudocm Command

Purpose

Displays contents of files containing supplemental information.

Syntax

inudocm [-d Device] [-q] { ProductName ... | all }

Description

Note: This command is used by the **installp** command and is not recommended as a way to get README information.(See **installp -i**.)

The **inudocm** command is used to display supplemental information. The files from the media that are displayed, if they exist, are the **Ipp.doc** file, the **Ipp.instr** file, the **Ipp.README** file and the **README** file.

The *ProductName* parameter specifies the name of the software product being checked. Specify **all** to display information about all software products that are known to the system.

Flags

-d Device Specifies where the installation media can be found. The Device parameter can specify a hardware

device, such as a tape or diskette drive, a directory that contains installation images, or an

installation image file. The default device is $\mbox{/dev/rfd0}.$

-q Specifies quiet mode, which suppresses prompts.

Security

Privilege Control: Only a root user can run this command.

Examples

To display the update instructions for the **snaserv** software product on **/dev/rfd0**, enter:

inudocm snaserv

Files

/usr/sbin/inudocm

/usr/lpp/ProductName/lpp.instr

/usr/lpp/ProductName/lpp.README /usr/lpp/ProductName/README /usr/lpp/ProductName/lpp.doc Contains the inudocm command.

Specifies the update instructions for the software

product.

Specifies special instructions for the software product. Specifies special instructions for the software product. Specifies the updates to the documentation for the

software product.

Related Information

The **installp** command, **restore** command.

inulag Command

Purpose

Acts as the front end to the subroutines to manage license agreements.

Syntax

inulag -r [-n FilesetName | -s FileName | -p Product] [-d Description [-m MessageSpecification]] -f File

inulag -I | -q [-c | -v] [-n FilesetName | -s FileName | -p Product | -a]

inulag -u [-n FilesetName | -s FileName | -p Product]

inulag -A

inulag -D

Description

The inulag command manages software license agreements. The basic forms are license agreement registration, license agreement listing, license agreement deactivation, license agreement validation, and license agreement revalidation.

The -r flag manages software license agreement registration of a fileset installed with installp or an independently-installed product installed through another installer. The path to a file that is always installed with an independently-installed product must be specified with the -s flag when the license agreement is registered.

The -I flag lists software license agreement registrations. If the -c flag is specified, the path to the software license agreement file is displayed rather than the contents of the file.

The -q flag queries for existence of software license agreements. A return code of 0 is returned if a license agreement exists. If the -a flag is also specified, then a return code of 0 is returned if there is a pending license agreement.

Used with the -I flag to show products that have a pending license agreement.

The -u flag removes the listing of software license agreements for a fileset or independently-installed product.

The -D flag forces revalidation of software license agreements upon the next system reboot.

Flags

-a

-	esse man are a mag to error products and mare a personne agreement
-A	Registers agreements for all pending license agreements.
-c	Used with the -I flag for colon-separated listing. Cannot be used with the -v flag.
-d Description	Specifies the default description for the fileset or product to which license applies.
-D	Forces the revalidation all license agreements on the next reboot.
-f File	Specifies the pathname specification for the license agreement. A '%L' in the specification is a substitution pattern for the current locale. en_US is the default locale. A "%l" in the specification matches the first two characters of the locale unless the current locale is zh_CN , in which all five characters of the locale designation are used.
-l	Lists software license agreements.
-m MessageSpecification	Specifies the message catalog for a translated description of the form "catalog,set number,message number".
-n FilesetName	Specifies the name of a fileset registered in the software vital product database governed by the license agreement.
-p Product	Specifies the product id, a nontranslatable alphanumeric string that uniquely identifies a product.
-q	Queries for license agreements. Does not show output. The value of 0 is returned if a license agreement exists. The -q flag can be used with other flags to query for particular license agreements or pending license agreements.
-r	Registers a software license agreement. Requires the -f flag for the path to the agreement file and either the -n flag or the -s flag to indicate the fileset name or signature file containing software subject to the agreement. The -r flag cannot be used with the -I , -q , or the -u flag. License agreements are registered as pending (status='P') during system installation, and NIM SPOT installation unless the environment variable ACCEPT_LICENSES is set to yes.

-s FileName Specifies a signature file unique to installed software that identifies software not

registered in the software vital product database that is governed by the license agreement. This is for use by software products not registering into the software vital product database. This form exists for the purpose of identifying software installed but not registered in the software vital product database. The *FileName* includes the full

path to the file.

-u Removes a license agreement. This does not actually remove the license agreement

file, rather it changes the status of a license agreement associated with a fileset to inactive. Inactive license agreements do not need to be reagreed to, but they do not

show up when listing installed software licenses.

-v Used with the -I flag for verbose listing. Cannot be used with the -c flag.

Security

The agreement database is writable only by root. As a result, all flags other than the -I flag can only be used by a user operating with root user authority.

Related Information

The installp command, Islpp command, nim command.

Installing optional software products and service updates in Installation and migration

inurecy Command

Purpose

Recovers files saved by the inusave command.

Syntax

inurecv ProductName [OptionList]

Description

The **inurecv** command recovers files and archive constituent files saved from a previous **inusave** command. It uses the **update.list** and **archive.list** files from the directory specified by the **INUSAVEDIR** environment variable. The **inurecv** command recovers files saved by program-provided installation or update procedures.

The **inurecv** command is primarily called by the **installp -r** command and the **installp -C** command to recover the files for a rejected program or a program that needs to be cleaned up.

The **inurecv** command is used to recover all the files for an installable program by separate calls to **inurecv** for the root, **/usr**, and **/usr/share** file trees. The save directories for the root, **/usr**, and **/usr/share** parts of an installation are:

- /lpp/PackageName/FilesetName/V.R.M.F.save,
- /usr/lpp/PackageName/FilesetName/V.R.M.F.save , and
- /usr/share/lpp/PackageName/FilesetName/V.R.M.F.save

respectively, when set up by the **installp** command. *Level* refers to the level of the software product and has the format of vv.rr.mmmm.ffff.ppppppppp, where vv = version, rr = release, mmmm = modification, ffff = fix, and pppppppppp = fix ID (only for Version 3.2 images).

Parameters

OptionList Specifies the full path name of a stanza file that contains the names of the separately

> installable options, such as bosnet.tcp.obj, that are to be recovered for the ProductName software product. The option names in the OptionList file must be specified one per line.

ProductName Specifies the installable software product, such as bosnet, whose files are to be recovered.

Environment Variables

INUEXPAND This flag is set to 1 by the **installp** command if file systems are to be expanded if necessary to

> do the recover (that is, the -X flag was passed to installp). It is set to 0 if file systems are not to be expanded. If this environment variable is not set, the default is not to expand file systems.

INUSAVE This flag is set to 1 by the installp command if files are to be saved (that is, the -N flag was not

passed), and otherwise set to 0. The inurecy command attempts to recover files if INUSAVE is set to 1. If INUSAVE is set to 0, inurecv performs no recovery and exits with a return code of **INUGOOD**. If this environment variable is not set, the default is to attempt to recover files.

INUSAVEDIR The full path name to the directory where files are saved. If this environment variable is not set,

then the directory used is /usr/lpp/ProductName/inst_updt.save.

ODMDIR The Object Data Manager object repository where the software vital product data is saved. If this

environment variable is not set, the default directory used is /etc/objrepos.

Error Codes

INUBADC1 A copy of a file from one directory to another was unsuccessful.

INUGOOD No error conditions occurred.

INUNORP1 Unsuccessful replacement of a file in an archive file during program recovery.

INUNOSAV The save directory does not exist.

INUNOSVF A file that was saved in the save directory was not found.

Security

Privilege Control: Only the root user can run this command.

Examples

To recover all files previously saved for the **snaserv** program, enter:

inurecy snasery

Files

/Ipp/PackageName/FilesetName/V.R.M.F.save

Files saved for the root file tree.

/usr/lpp/PackageName/FilesetName/V.R.M.F.save

Files saved for the /usr file tree.

/usr/share/lpp/PackageName/FilesetName/V.R.M.F.save

Files saved for the /usr/share file tree.

Related Information

The installp command, inusave command.

inurest Command

Purpose

Performs simple archive and restore operations for the **installp** command and shell scripts. This command is used by the **installp** command and the install scripts.

Syntax

inurest [-d Device] [-q] ListFile ProductName

Description

The inurest command restores or archives all files listed in the file specified by the ListFile parameter.

If files are to be archived, there must be an archive control file, /usr/lpp/ProductName/lpp.acf, which contains entries in the following form:

ComponentFile LibraryFile.a.

If the archive control file exists, the **inurest** command compares each of the file names in the *ListFile* file to the component files listed in **/usr/lpp/***ProductName***/lpp.acf**. Whenever the **inurest** command finds a match, the file name is added to a list of files that are archived. This list is then used to archive the restored files into a copy of the corresponding archive. When the archive is finished, the copy replaces the original file.

The *ListFile* parameter specifies the full path name of a file containing the relative path names, one per line, of files that a product needs to have restored.

The *ProductName* parameter specifies the software product to be restored.

Flags

-d Device Specifies the input device. The default device is the /dev/rfd0 device.

-q Specifies quiet mode. Suppresses the prompt from **restore**.

Environment Variables

INUEXPAND This flag is set to 1 by the installp command if file systems are to be expanded if necessary to

do the restore (that is, the **-X** flag was passed). It is set to 0 if file systems are not to be expanded. If this environment variable is not set, the default is not to expand file systems.

INULIBDIR This is the directory where files that are specific to software product installation reside. If

INULIBDIR is not set the /usr/lpp/ProductName directory is used.

INUTEMPDIR The directory to use for temporary space that is needed during the execution of this command. If

this environment variable is not set, then the directory used is /tmp.

Error Codes

INUBADRC Restoration of an updated version of files was unsuccessful.

INUBADMN Unusable flag was specified.
Cannot change directory.
INUGOOD No error conditions occurred.
Unable to access the apply list.

INUNORP2 Failed replacing a constituent file in the archive file.

INUTOOFW One or more parameters are missing.

Too many parameters are specified.

Security

Privilege Control: Only the root user can run this command.

Examples

To restore all the files listed in the ac file for the snaserv program, enter:

inurest /usr/lpp/snaserv/ac snaserv

Files

\$INULIBDIR/lpp.acf

Archive control file.

Related Information

The installp command, inucp command, inurecy command, inusave command.

inurid Command

Purpose

Removes information used for installation of diskless/dataless clients from the **inst_root** directories of installed software.

Syntax

inurid [-q | -r]

Description

The inurid command is used to remove files stored in the inst_root directories of installed software.

The names of these directories are of the forms: <code>/usr/lpp/PackageName/inst_root</code> for software products and <code>/usr/lpp/PackageName/OptionName/v.r.m.f/inst_root</code> for AIX Version 4 updates.

When this command is called, the <code>inst_root</code> directories are removed for all products and updates in the committed state. Also, an indicator is stored in the Software Vital Product Data indicating that the proper <code>inst_root</code> directory information is to be removed after the completion of each future installation action, for example, actions performed by the <code>installp</code> command.

Attention: One reason a user may want to remove **inst_root** directories is to save disk space. The implication of removing these directories is that the system cannot be used as a Shared Product Object Tree (SPOT) server of diskless/dataless clients. Also, once **inst_root** directories are removed from a system, there is no way to retrieve the directories. Therefore, the system cannot later be converted to a SPOT server without reinstalling the entire operating system.

Flags

- -q Queries whether inst_root directories have been removed from the system. A return value of 0 indicates that inst_root directories have not been removed and a return value of 1 indicates that the inst_root directories have been removed.
- -r Requests inst_root directories be removed from the system.

Security

Privilege Control: You must be the root user to run this command.

Files

/usr/lib/instl/inurid

Contains the inurid command.

Related Information

The **installp** command.

inusave Command

Purpose

Saves files that are installed or updated during an installation procedure. This command is used by the installp command and the install scripts.

Syntax

inusave ListFile ProductName

Description

The inusave command saves the files and archived files that are listed in the file specified by the ListFile parameter for the *ProductName* software product. The **inusave** command is designed for use with the installp command.

The inusave command creates the /usr/lpp/PackageName/FilesetName/V.R.M.F.save directory if it does not already exist, where Level has the form vv.rr.mmmm.ffff and vv = the version, rr = the release, mmmm = the modification, and ffff = fix. This is the directory in which the installation procedures store saved files. The save directory is defined by the **INUSAVEDIR** environment variable.

The save directories for the / (root), /usr, and /usr/share parts of an installation are:

- /lpp/PackageName/FilesetName/V.R.M.F.save,
- /usr/lpp/PackageName/FilesetName/V.R.M.F.save , and
- /usr/share/lpp/PackageName/FilesetName/V.R.M.F.save

respectively, when set up by the installp command. The installp command calls inusave for each of these three directories. The ListFile parameter is the full path name of the file that lists the files that are to be saved if a current copy exists.

If a file named in the ListFile file already exists, the inusave command copies that file to the \$INUSAVEDIR/update.n file, where n is an integer assigned by the inusave command. If the file does not exist, the inusave command assumes that this entry in the ListFile parameter represents either a new file or a file to be archived or processed by the archive procedure described later in this section.

The inusave command maintains a list of saved files in the \$INUSAVEDIR/update.list file. This file is a stanza file with an entry for each saved file. Entries in the update.list file resemble the following:

```
/usr/bin/chkey:
         update.n = update.1
         option = bosnet.nfs.obj
         _{id} = 209
         reserved = 0
          scratch = 0
         1pp id = 72
```

```
private = 0
         file type = 0
         format = 1
         loc0 = /usr/bin/chkey
         size = 7800
         checksum = 44561
/usr/bin/domainname:
         update.n = update.2
         option = bosnet.nfs.obj
         _id = 210
         _reserved = 0
          scratch = 0
         \overline{1}pp id = 72
         private = 0
         file type = 0
         format = 1
         loc0 = /usr/bin/domainname
         size = 2526
         checksum = 12439
```

In the previous example /usr/bin/chkey (the name of the stanza) is the name of an original file that was saved and update.1 is the name of the file in the \$INUSAVEDIR directory to which it was copied. The file /usr/bin/chkey belongs to the bosnet.nfs.obj installable option of the software product bosnet. The stanza name and the first two items in the stanza (update.n and option) exist for each stanza in the update.list file. The remaining items in the stanza, which may vary, are information from the Software Vital Product Data (SWVPD) database.

An archived constituent file is saved if there is a valid archive control file, **Ipp.acf**, in the current directory. If the **lpp.acf** file exists, the **inusave** command compares each of the file names in *ListFile* to the constituent file names in Ipp.acf. When it finds a match, the inusave command uses the ar command to extract the constituent file from its associated archive file. It then moves the file to the **\$INUSAVEDIR/archive.** *n* file, where *n* is an integer selected by the **inusave** command.

The **inusave** command maintains a list of the extracted files that have been saved in the \$INUSAVEDIR/archive.list file. This file is a stanza file with an entry for each saved constituent file. Entries in the archive.list file resemble the following:

```
/prodx.filea:
        archive.n = archive.1
        arc name = /usr/lib/productx/libprodx.a
        option = productx.option1.obj
        id = 833
        reserved = 0
         scratch = 0
        \overline{1}pp_id = 7
        private = 0
        file\_type = 0
        format = 1
        loc0 = /prodx.filea
        loc1 = "h11,h12"
        1oc2 =
"/usr/lpp/productx.filea/s11,/usr/lpp/productx.filea/s12"
        size = 1611
        checksum = 62793
```

In the previous example /prodx.filea (the name of the stanza) is the name of the original constituent file that was saved and archive.1 is the name of the file in the \$INUSAVEDIR directory to which it was copied. The /usr/lib/productx/libprodx.a is the full path name of the archive file defined in the lpp.acf archive control file. The constituent file /prodx.filea belongs to the productx.option1.obj installable option of the software product productx. The stanza name and the first three items in the stanza (archive.n, arc_name, and option) will exist for each stanza in the archive.list file. The remaining items in the stanza, which may vary, are information from the SWVPD database.

Parameters

ListFile Specifies the full path name of the file containing a list of relative path names, one per line, of

files that are to be saved.

ProductName Specifies the installable software product whose files are to be saved.

Environment Variables

INUEXPAND This flag is set to 1 by the **installp** command if file systems are to be expanded if necessary to

do the save (that is, the -X flag was passed to installp). It is set to 0 if file systems are not to be

expanded. If this environment variable is not set, the default is not to expand file systems.

INUSAVE This flag is set to 1 by the installp command if files are to be saved (that is, the -N flag was not

passed to installp). It is set to 0 if files are not to be saved. If this environment variable is not

set, the default is to save files.

INUSAVEDIR The full path name to the directory where files are to be saved. If this environment variable is not

set, then the directory to be used is /usr/lpp/ProductName/inst_updt.save.

INUTEMPDIR The directory to use for temporary space that is needed during the execution of this command. If

this environment variable is not set, then the directory used is /tmp.

Error Codes

The following error codes are defined in /usr/include/inuerr.h:

INUBADSC A save directory could not be created.

INUBADC2 A file could not be copied from one directory to another.

INUGOOD No error conditions occurred. **INUNOAP1** Could not access *ListFile*.

INUTOOFW One or more parameters were missing.
INUTOOMN Too many parameters were specified.

Security

Privilege Control: Only the root user can run this command.

Examples

To save all the files listed in the **snaserv.al** file of the **snaserv** program, enter:

inusave /usr/lpp/snaserv/snaserv.al snaserv

Files

/usr/lpp/PackageName/lpp.acf

Specifies the archive control file.

/lpp/PackageName/FilesetName/V.R.M.F.save

Specifies the save directory for the root.

/usr/lpp/PackageName/FilesetName/V.R.M.F.save

Specifies the save directory for the /usr files.

/usr/share/lpp/PackageName/FilesetName/V.R.M.F.save

Specifies the save directory for the /usr/share files.

Related Information

The **installp** command, **inurecv** command.

inutoc Command

Purpose

Creates a .toc file for directories that have backup format file install images. This command is used by the install p command and the install scripts.

Syntax

inutoc [Directory]

Description

The **inutoc** command creates the **.toc** file in *Directory*. If a **.toc** file already exists, it is recreated with new information. The default installation image *Directory* is **/usr/sys/inst.images**. The **inutoc** command adds table of contents entries in the **.toc** file for every installation image in *Directory*.

The **installp** command and the **bffcreate** command call this command automatically upon the creation or use of an installation image in a directory without a **.toc** file.

Error Codes

INUBADIR Usage error or *Directory* did not specify a directory.

INUCHDIR Unable to change directories to *Directory*.

INUCRTOC Could not create the .toc file.

INUGOOD No errors occurred. **INUSYSFL** A system call failed.

Security

Privilege Control: Only the root user can run this command.

Examples

1. To create the .toc file for the /usr/sys/inst.images directory, enter:

inutod

2. To create a .toc file for the /tmp/images directory, enter:

inutoc /tmp/images

Files

/usr/sys/inst.images The default directory to create a .toc file.

.toc The file created by this command in the specified directory.

Related Information

The bffcreate command, installp command.

inuumsg Command

Purpose

Displays specific error or diagnostic messages provided by a software product's installation procedures. This command is used by the **installp** command and the install scripts.

Syntax

inuumsg Number [Argument1] [, Argument2] [, Argument3] [, Argument4]

Description

The **inuumsg** command displays error or diagnostic messages for a software product's installation procedures. Rather than each procedure having its own text, messages are maintained in a central message catalog, **/usr/lpp/msg/\$LANG/inuumsg.cat**. When you run the **inuumsg** command and specify the message **Number**, the error message is displayed. Up to four string arguments, **Argument1** to **Argument4**, can be substituted into the message in the appropriate location.

Exit Status

- Indicates the message was found and displayed.
- 1 Indicates the message was not found and not displayed.

Security

Privilege Control: Only the root user can run this command.

Examples

To see error message number 3, enter:

inuumsg 3

Files

/usr/lpp/msg/\$LANG/inuumsg.cat

The message catalog.

Related Information

The installp command.

invscout Command

Purpose

Surveys the host system for currently installed microcode or Vital Product Data (VPD).

Syntax

```
invscout [-v ][-c][-r][-m machine_type_and_model][-s serial_number][-catl
microcode_catalog_path][-g][-h]
```

Description

The **invscout** command executes one instance of the stand-alone version of the Inventory Scout process. The **invscoutd** command starts the server daemon side of a client-server version.

The Inventory Scout process supports two survey types:

- Microcode Survey
- Vital Product Data (VPD) Survey (-v)

Microcode Survey

A Microcode Survey gathers data from the host system on currently installed microcode for invscout-supported systems, devices and adapters. It compares the gathered microcode levels to the latest levels available, and stores the data in a Microcode Survey Upload File that can be displayed locally via the webSM GUI, or uploaded to a Web server via the Internet.

A Microcode Survey also produces a Microcode Survey Formatted Text Report File. This file can be printed or displayed on a monitor and contains a subset of the information recorded in the upload file. This subset includes information about the invscout execution itself and the levels of currently installed microcode. The -r flag causes this report also to be sent to the screen from where the command was invoked.

All of the previous reports can contain information on the following:

- system microcode
- · service microcode
- · device and adapter microcode

VPD Survey (-v)

A VPD Survey stores the system VPD in a VPD Survey Upload File that can be uploaded to a Web server via the Internet . Once on a Web server, a CGI forwards the file to a repository and produces a Web page indicating the status of the operation.

No formatted text report is available for VPD Surveys.

Survey Results Concatenation (-c)

This option concatenates two or more Microcode Survey Upload Files into a single Microcode Survey Concatenated Upload File or two or more VPD Survey Upload Files into a single VPD Survey Concatenated Upload File. A Concatenated Upload File can be uploaded to a Web server using the Internet and processed by the server CGI to give the same results as would have been obtained by uploading and processing all the component files individually. The input files can be any valid upload files but, typically, this operation is done to simplify the task of uploading the results from several host systems.

- The version of the command executing the concatenation and the versions of the commands that produced the files to be concatenated must all be the same.
- Microcode Survey Upload Files cannot be concatenated with VPD Survey Upload Files.
- · Versions 2.1.0.0 and subsequent versions of this command do not require concatenation of Microcode Survey Upload Files, because the files are processed locally.

To concatenate a set of existing Microcode Survey upload files, do the following:

- 1. Copy the files into the Microcode Survey Concatenation Input Directory.
- 2. Execute:

invscout -c

3. Find the output Microcode Survey Concatenated Upload File in the same directory as the upload file for a Microcode Survey.

To concatenate a set of existing VPD Survey upload files, do the following:

- 1. Copy the files into the VPD Survey Concatenation Input Directory.
- 2. Execute:

invscout -v -c

3. Find the output VPD Survey Concatenated Upload File in the same directory as the upload file for a VPD Survey.

Flags

Sets the survey or concatenation type to VPD (the default is Microcode).
 Concatenates existing survey upload files (the default is to perform a new

survey).

-r For a Microcode Survey, sends a copy of the formatted text report file to the

screen from which the command was invoked. This flag is ignored if either

the -v or the -c flag is used.

-m machine_type_and_model For a VPD survey, allows input of the host platform machine type and model

for hosts that use/require this information.

-s serial_number For a VPD survey, allows input of the host serial number for hosts that

use/require this information.

-g Displays the versions of this command and of the logic database currently in

use.

-q Suppresses most run-time messages.

-h Generates a help (usage) statement. If this flag is used, all other flags are

ignored.

Exit Status

This command returns the following exit values:

Indicates successful completion.
 Non-zero Indicates an error occurred.

If an error occurs, the command writes an error log.

Security

This command is owned by root, and is installed with the **setuid** bit ON so that any user can run it.

Examples

1. To run one Microcode Survey and send the results to a formatted text report file and an upload file, type:

invscout

2. To run one VPD Survey and send the results to an upload file, type:

invscout -v

3. To concatenate previously produced Microcode Survey upload files into a single upload file, type:

invscout -c

Note: Only applicable to Versions of this command prior to 2.1.0.0.

4. To concatenate previously produced VPD Survey upload files into a single upload file, type:

invscout -v -c

Files

/usr/sbin/invscout Contains the invscout command.

/var/adm/invscout/host.mup Microcode Survey Upload File. The host variable is the host name of

the system represented in the file.

/var/adm/invscout/invs.mrp Microcode Survey Formatted Text Report File.

/var/adm/invscout/host.vup VPD Survey Upload File. The host variable is the host name of the

system represented in the file.

/var/adm/invscout/invs.mic.con.inp Microcode Survey Concatenation Input Directory.

/var/adm/invscout/invs.vpd.con.inp /var/adm/invscout/invs.con.mup /var/adm/invscout/invs.con.vup /var/adm/invscout/invs.err /var/adm/invscout/microcode

/var/adm/invscout/microcode/catalog.mic /var/adm/invscout/invscout.log /var/adm/invscout/tmp

VPD Survey Concatenation Input Directory Microcode Survey Concatenated Upload File. VPD Survey Concatenated Upload File.

Error log written if the command encounters an error.

Directory for microcode-related actions. Default location for microcode

catalog file.

Default microcode catalog file.

Log file.

Holds invscout temporary files. All files in this directory are deleted at the start of every execution of this command.

Related Information

The invscoutd command.

invscoutd Command

Purpose

Launches a permanent Inventory Scout server daemon.

Syntax

invscoutd [-o] [-p Portno] [-b Bufsize] [-d maxcatsize] [-t Timeout] [-v Verblev]

Description

The invscoutd command implements a permanent Inventory Scout server daemon on one machine in the local network of the user. The usual client is a Java[™] applet running in the Web browser of the user, which was downloaded from a central Inventory Scout CGI application.

Daemon initialization involves reading command line options and several local Inventory Scout companion files. When in operation, each client-server transaction involves reading from a well-known socket for a text string and returning a text report over the same socket.

The daemon maintains a record of its actions in a log file. Depending on the specified verbosity level, the log lines may contain startup and shutdown banners, traces of each call, detailed internal program traces, and error statements. Depending on the specified verbosity level, startup banners may also be written to stderr.

Protocols

Client connections to the daemon's socket use the Internet TCP/IP protocol. In a transaction, the invoking client applet sends an action request, as a URL-encoded text string, to the server daemon. The request is by any ASCII control character (x00 to x1F), which triggers the processing of the request.

Some requests require the client to pass additional data. In these cases, the additional data immediately follow the termination byte for a length specified in the action request.

With one exception (ACTION=PING), the server daemon always returns a pseudo MIME format text report written back over the same socket connection. The pseudo MIME format is used even for error results. The daemon terminates the returned text and the transaction itself by closing the socket, resulting in an end-of-file (EOF) indication to the invoking client. The client should close the socket at its end of the connection as soon as the EOF is received.

URL-encoded message

The action request string is a standard URL-encoded string. For example:

Supported Field Names and Values

Name	Meaning/Use	Supported Values
ACTION	See the action request table that follows.	The left-hand column of the action request table constitutes a list of supported Values.
MRDM	Allows the client to provide a (cleartext) password for any ACTION that uses/requires this information. The value is case sensitive.	Any ASCII string (case sensitive).
DATALEN	This name must be present if additional binary data immediately follow an ACTION string termination byte, and must be absent if no additional data follow the termination byte. The integer value provided specifies the number of additional data bytes. If the client attempts to write more data than this, if the action does not accept the DATALEN parameter and discards any additional data, or if the action processor detects an early error, the daemon may prematurely close the client-to-server socket pipe. A transaction with n greater than a specific maximum value will immediately return an error code (see the -d command line option).	Any integer up to the value implied by the presence or absence of the -d command line option
CLIENT	Allows the client to identify itself for any ACTION that uses/requires this information.	The HSC value instructs Inventory Scout to allow certain actions that are only allowed when under the control of an HMC Inventory Scout master.
MODEL	Allows the client to inform the server of the server's model number for VPD surveys that use/require this information.	Any ASCII string of up to 25 characters (restrictions apply with some machines)
SERIAL	Allows the client to inform the server of the server's serial number for VPD surveys that use/require this information.	Any ASCII string of up to 25 characters (restrictions apply with some machines)

Notes:

- 1. Field names and their values are separated by equal signs (=).
- 2. Name=Value pairs are separated by an & character.
- 3. The Name field is always case insensitive.
- 4. The Value field is case insensitive, unless documented otherwise.
- 5. The **ACTION**=*keyword* pair must always be present.
- 6. A string between ampersands without an equal sign is parsed as a **Name** with an Empty value.
- 7. Spaces can be represented by + (plus signs).
- 8. Binary characters may be coded as the escape sequence of a percent sign followed by exactly two hexadecimal chars (%xx). This escape sequence must also be used to code URL metacharacters like the &, = (equal sign), and + (plus sign) within a Value.
- 9. The control character termination byte must always be sent by the client.

 $[&]quot;ACTION=actionword \& NAME1=value1 \& NAME2 \& NAME3=word \& xx+word+word \\ \ \ 0"$

Action Requests

Action	MRDM	Description
PING	not required	The daemon <i>immediately</i> closes the socket, causing an immediate EOF in the client. This is the only action that does not return a result code or text of any kind. Example:
		"action=ping\0"
		<e0f></e0f>
ECHO	not required	The daemon returns a text report consisting of the original unparsed request string followed by a linefeed. A password (MRDM) is not required but is echoed if provided, along with everything else. Additional data (DATALEN) is not required but is echoed if present, as is, after the request string. For the ECHO request, DATALEN is silently truncated to a maximum of 2000. Example:
		"action=ECHO&MRDM=xyz&datalen=5\0abcde"
		"RESULT=0\n" "\n"
		"action=ECHO&MRDM=xyz&datalen=5\n" "abcde" <eof></eof>
URLDECODE	not required	The daemon returns a text report of the request string after parsing, and an exact copy of any subsequent data. A password (MRDM) is not required but is parsed and returned if provided. Additional data (DATALEN) is not required but is parsed and returned if provided; however, any actual additional data beyond the request string is discarded. Each numbered line of the report exhibits one parsed Name=Value pair from the original string. Example: "action=UrlDecode&subaction=xyz\0"
		"RESULT=0\n"
		"\n" " 0: ACTION
TESTPWD	required	The daemon returns RESULT=0 if the MRDM password is valid. Otherwise it returns RESULT=2. Additional data (DATALEN) is not accepted and is discarded if present. Example:
		"ACTION=TESTPWD&MRDM=thepassword\0" "RESULT=0\n" "\n" <e0f></e0f>
VERSIONS	not required	The daemon reports the current version numbers of the Inventory Scout itself. Additional data (DATALEN) is not accepted and is discarded if present. Example: "ACTION=VERSIONS\0"
		"RESULT=0\n" "\n" "1.2.3.4\n" "5.6.7.8\n" <e0f></e0f>

Action Requests

Action	MRDM	Description
CATALOG	required	The daemon updates the scout's microcode catalog file with the file data passed. Both password and the data length parameter must be included in the request string. The daemon does not necessarily have to execute as root for this action but it must have file write permissions to /var/adm/invscout/microcode/catalog.mic. Example:
		"ACTION=CATALOG&MRDM=xyz&DATALEN=17042\0" "17042 bytes of ascii data"
		"RESULT=0\n" "\n" <e0f></e0f>
MCODES	required	The daemon executes the Microcode Survey Option. Additional data (DATALEN) is not accepted and is discarded if present. Example: "ACTION=MCODES&MRDM=xyz\0" "RESULT=0\n" "\n" "Report Line 1\n" "Report Line 2\n" : : : : : : : : : : : : : : : : : :
VPDS	required	The daemon executes the VPD Survey Option. Additional data (DATALEN) is not accepted and is discarded if present. Example: "ACTION=VPDS&MRDM=xyz\0" "RESULT=0\n" "\n" "Report Line 1\n" "Report Line 2\n" : : : : : : "Report Line N\n" <e0f></e0f>

Results

The daemon returns a text result in a pseudo MIME format. It returns a header consisting of one or more Name=Value pairs, each on a line by itself. The first Name=Value pair always is the result code in the form **RESULT**=*number*. The result code is always returned for every action, except for the PING action.

Internal scout result codes applicable only to the Java applet client are not documented in the following information.

An optional free-form text report may follow the header lines depending on the result code. If there is a free-form text report, the header is first terminated by an empty line, such as two adjacent linefeeds.

In any event, the result report is terminated by an EOF indicator after reading the last of the report text from the socket. The EOF also signifies the end of the transaction itself.

Result Codes

Result=	Description
0	Complete success.
	Daemon aborted due to memory allocation error. This can happen in either the parent server daemon or one of the service children.

Result Codes

Result=	Description
2	Service child daemon aborted because the required password (MRDM=password) was missing or not valid.
3	Service child daemon aborted because the action name-value pair (ACTION=keyword) was missing or not valid.
4	Service child daemon aborted because it was unable to reset its user ID to invscout.
21	Service child daemon aborted due to overflow of socket input buffer. The text report part of the result is a native language error message. Client must reduce the length of the request string, or kill and restart the daemon with an increased buffer size.
22	Service child daemon aborted due to socket read error. The text report part of the result is a native language error message including the system's I/O errno string. A logfile entry will also contain the system's errno string.
23	Service child daemon aborted due to socket read timeout. The text report part of the result is a native language error message. Client must send a control character termination byte after the end of the request string, and must always send as many data bytes as specified in the DATALEN parameter. The timeout period may be changed with the -t command line argument.
24	Service child daemon aborted due to premature EOF while reading request string. The text report part of the result is a native language error message. Client must send a termination byte after the end of the request string before closing the socket connection.
25	Service child daemon aborted due to missing or invalid DATALEN parameter for an action that requires it. The text report pair of the result is a native language error message. Client must send the length of the data for all actions which pass additional binary data beyond the URL-encoded request string. Most such actions also require that the DATALEN value be limited to a specific maximum size.
26	Service child daemon aborted due to regular file I/O error, such as a permissions error, out of disk space, and so on. The text report part of the result is a native language error message. Usually, the I/O problem must be corrected on the server machine before the client can attempt the action again.
27	Service child daemon aborted because it was unable to retrieve the version number for an activity that required it.

Flags

Specify any arguments, beginning with a hyphen (-). Space is not allowed between a flag and its value.

-0	Overwrites an existing logfile. If the -o flag is not specified, new logfile lines are appended to any existing logfile.
-p Portno	Changes this server's port number from the default value of 808 to Port.
-b Bufsize	Inventory Scout commands are specified as URL-encoded strings read from a TCP/IP socket into a 1024 byte fixed length buffer. The -b flag can change the buffer size to <i>Bufsize</i> bytes if future protocol changes require a larger read buffer.
-d maxcatsize	Changes the maximum microcode catalog file size from the default value of 50000 to a value that you specify.
-t Timeout	The client applet writes a control character termination byte at the end of the URL-encoded request string to indicate the end of the request. If the invscoutd daemon does not receive the termination byte within a timeout period, it aborts the transaction and closes the socket. Similarly the client must send all bytes of the additional data specified in the DATALEN parameter with sufficient speed to prevent timeout between read blocks. The -t option changes the default timeout period from 30 seconds to <i>Timeout</i> seconds.

-v Verblev

The amount of detail written to the logfile and stderr depends on the verbosity level of the daemon. Each level incorporates the messages in the lower levels; increasing the verbosity level increases the number and types of messages that are written. The verbosity level is an integer ranging from 0 to 25. The **-v** flag changes the verbosity level from the default value of 18 to *Verblev*.

Verbosity Levels

Level	Description
0	All error and status messages disabled.
5	Only fatal error messages are written. Fatal errors result in the death of the server. Usually, similar messages are written to both the <i>Logfile</i> and stderr.
10	All error messages are written. These include nonfatal errors such as protocol errors, as well as fatal errors. Nonfatal error messages are usually written only to the <i>Logfile</i> .
15	This level includes startup and shutdown banner messages. Simple banner messages are usually written to both the <i>Logfile</i> and stderr.
18	This level includes call trace status messages. Every client call results in a single trace message. This is the default level for the invscoutd daemon. Trace messages are written only to the <i>Logfile</i> .
20	This level includes program trace messages. Program traces are fairly detailed program execution status messages typically used for debugging purposes. This level is not suitable for usual production execution because over time, it floods the <i>Logfile</i> with large amounts of text. Trace messages are written only to the <i>Logfile</i> .
25	This is the maximum level and includes extensive program debug messages. This level is not suitable for usual production execution. Trace messages are written only to the <i>Logfile</i> .

Exit Status

This command returns the following exit values:

Indicates successful initializationNon-zeroIndicates unsuccessful initialization

Security

The daemon must execute as effective user ID θ (root). It is owned by root, and is installed with the "setuid" bit ON so that any user can launch it. At certain execution points, however, service children of the daemon reset their user ID to the authentication user ID invscout. The daemon does not execute unless the user invscout has been created on the host system.

By default, an accompanying cleartext password is required from the client for most operations. If the client's password does not match the system password for the authentication user ID invscout, the action exits with a return code. The authentication user ID cannot be changed.

Files

/usr/sbin/invscoutd Contains the invscoutd command /etc/security/password Host system password file /var/adm/invscout/microcode Directory for microcode-related actions and invscout/microcode Directory for microcode-related actions and invscout file /var/adm/invscout/microcode

/var/adm/invscout/microcode Directory for microcode-related actions. Default location for

/var/adm/invscout/microcode/catalog.mic microcode catalog file.

Default microcode catalog file.

/var/adm/invscout/invscout.log Log file

Related Information

The invscout command.

ioo Command

Purpose

Manages Input/Output tunable parameters.

Syntax

```
ioo [ -p | -r ] [-y]{ -o Tunable [ =NewValue ] }
ioo [ -p | -r ] [-y] {-d Tunable}
ioo [ -p | -r ] [-y] -D
ioo [ -p | -r ] -a
ioo -h [ Tunable ]
ioo -L [ Tunable ]
ioo -x [ Tunable ]
```

Note: Multiple -o, -d, -x, and -L flags are allowed.

Description

Note: The **ioo** command can only be executed by root.

The ioo command configures Input/Output tuning parameters. This command sets or displays current or next boot values for all Input/Output tuning parameters. This command can also make permanent changes or defer changes until the next reboot. Whether the command sets or displays a parameter is determined by the accompanying flag. The -o flag performs both actions. It can either display the value of a parameter or set a new value for a parameter.

If a process appears to be reading sequentially from a file, the values specified by the minpgahead parameter determine the number of pages to be read ahead when the condition is first detected. The value specified by the maxpgahead parameter sets the maximum number of pages that are read ahead, regardless of the number of preceding sequential reads.

The operating system allows tuning of the number of file system bufstructs (numfsbuf) and the amount of data processed by the write-behind algorithm (numclust).

Understanding the Effect of Changing Tunable Parameters

Misuse of the ioo command can cause performance degradation or operating-system failure. Before experimenting with ioo, you should be thoroughly familiar with Performance overview of the Virtual Memory Manager.

Before modifying any tunable parameter, you should first carefully read about all its characteristics in the Tunable Parameters section below, and follow any Refer To pointer, in order to fully understand its purpose.

You must then make sure that the Diagnosis and Tuning sections for this parameter truly apply to your situation and that changing the value of this parameter could help improve the performance of your system.

If the Diagnosis and Tuning sections both contain only "N/A", you should probably never change this parameter unless specifically directed by AIX development.

Flags

-d Tunable

-h [Tunable]

-D

-a Displays current, reboot (when used in conjunction with -r) or permanent (when used in conjunction with -p) value for all tunable parameters, one per line in pairs tunable = value. For the permanent option, a value is only displayed for a parameter if its reboot and current values are equal.

Otherwise NONE displays as the value.

Resets *Tunable* to its default value. If a *Tunable* needs to be changed (that is it is currently not set to its default value) and is of type **Bosboot** or **Reboot**, or if it is of type **Incremental** and has been changed from its default value, and **-r** is not used in combination, it is not changed but a warning displays.

Resets all tunables to their default value. If tunables needing to be changed are of type **Bosboot** or **Reboot**, or are of type **Incremental** and have been changed from their default value, and **-r** is not used in combination, they are not changed but a warning displays.

Displays help about the *Tunable* parameter if one is specified. Otherwise, displays the **ioo** command usage statement.

-L [*Tunable*] Lists the characteristics of one or all tunables, one per line, using the following format:

-o Tunable [=NewValue]

-p

Displays the value or sets *Tunable* to *NewValue*. If a *Tunable* needs to be changed (the specified value is different than current value), and is of type **Bosboot** or **Reboot**, or if it is of type **Incremental** and its current value is bigger than the specified value, and **-r** is not used in combination, it is not changed but a warning displays.

When **-r** is used in combination without a *NewValue*, the nextboot value for tunable displays. When **-p** is used in combination without a *NewValue*, a value displays only if the current and next boot values for the *Tunable* are the same. Otherwise NONE displays as the value.

Specifies that the changes apply to both the current and reboot values when used in combination with the -o, -d or -D flags. Turns on the updating of the /etc/tunables/nextboot file in addition to the updating of the current value. These combinations cannot be used on Reboot and Bosboot type parameters, their current value cannot be changed.

When used with **-a** or **-o** without specifying a new value, the values display only if the current and next boot values for a parameter are the same. Otherwise NONE displays as the value.

91

Makes changes apply to reboot values when used in combination with the -o, -d or -D flags. That -r is, turns on the updating of the /etc/tunables/nextboot file. If any parameter of type Bosboot is changed, the user is prompted to run bosboot.

When used with -a or -o without specifying a new value, next boot values for tunables display

instead of current values.

-x [Tunable] Lists characteristics of one or all tunables, one per line, using the following (spreadsheet) format:

tunable,current,default,reboot,min,max,unit,type,{dtunable }

```
where:
```

```
current = current value
default = default value
reboot = reboot value
min = minimal value
max = maximum value
unit = tunable unit of measure
type = parameter type: D (for Dynamic), S (for Static), R (for Reboot),
           B (for Bosboot), M (for Mount), I (for Incremental),
           C (for Connect), and d (for Deprecated)
dtunable = space separated list of dependent tunable parameters
```

Suppresses the confirmation prompt before executing the **bosboot** command. -у

Any change (with -o, -d or -D) to a parameter of type Mount results in a message being displayed warning you that the change is only effective for future mountings.

Any change (with -o, -d or -D flags) to a parameter of type Connect will result in inetd being restarted, and a message being displayed to warn the user that the change is only effective for future socket connections.

Any attempt to change (with -o, -d or -D) a parameter of type Bosboot or Reboot without -r, will result in an error message.

Any attempt to change (with -o, -d or -D but without -r) the current value of a parameter of type **Incremental** with a new value smaller than the current value, will result in an error message.

Tunable Parameters Type

All the tunable parameters manipulated by the tuning commands (no, nfso, vmo, ioo, raso, and schedo) have been classified into these categories:

Dynamic If the parameter can be changed at any time Static If the parameter can never be changed

Reboot If the parameter can only be changed during reboot

Bosboot If the parameter can only be changed by running bosboot and rebooting the machine Mount If changes to the parameter are only effective for future file systems or directory mounts

Incremental If the parameter can only be incremented, except at boot time

Connect If changes to the parameter are only effective for future socket connections Deprecated If changing this parameter is no longer supported by the current release of AIX.

For parameters of type Bosboot, whenever a change is performed, the tuning commands automatically prompt the user to ask if they want to execute the **bosboot** command. For parameters of type Connect, the tuning commands automatically restart the **inetd** daemon.

Note that the current set of parameters managed by the ioo command only includes Static, Dynamic, Mount and Incremental types.

Compatibility Mode

When running in pre 5.2 compatibility mode (controlled by the **pre520tune** attribute of **sys0**, see **Performance tuning enhancements for AIX 5.2** in the *Performance management*), reboot values for parameters, except those of type *Bosboot*, are not really meaningful because in this mode they are not applied at boot time.

In pre 5.2 compatibility mode, setting reboot values to tuning parameters continues to be achieved by imbedding calls to tuning commands in scripts called during the boot sequence. Parameters of type Reboot can therefore be set without the **-r** flag, so that existing scripts continue to work.

This mode is automatically turned ON when a machine is MIGRATED to AIX 5.2. For complete installations, it is turned OFF and the reboot values for parameters are set by applying the content of the /etc/tunables/nextboot file during the reboot sequence. Only in that mode are the -r and -p flags fully functional. See Kernel Tuning in AIX 5L Version 5.3 Performance Tools Guide and Reference for more information.

Tunable Parameters

j2_dynamicBufferPreallocation

Purpose:

Specifies the number of 16k slabs to preallocate when the filesystem is running low of bufstructs.

Values:

Default: 16 (256k worth)

Range: 0 to 256 Type: Dynamic

Diagnosis:

N/A

Tuning:

The value is in 16k slabs, per filesystem. The filesystem does not need remounting. The bufstructs for Enhanced JFS are now dynamic; the number of buffers that start on the paging device is controlled by **j2_nBufferPerPagerDevice**, but buffers are allocated and destroyed dynamically past this initial value. If the value of external pager filesystem I/Os blocked with no fsbuf (from vmstat -v) increases, the

j2_dynamicBufferPreallocation should be increased for that filesystem, as the I/O load on the filesystem could be exceeding the speed of preallocation. A value of 0 (zero) disables dynamic buffer allocation completely.

j2_inodeCacheSize

Purpose:

Controls the amount of memory Enhanced JFS will use for the inode cache.

Values:

Default: 400 Range: 1 to 1000 Type: Dynamic

Diagnosis:

Tuning this value is useful when accessing large numbers of files causes excessive I/O as inodes are recycled.

Tuning:

This tunable does not explicitly indicate the amount that will be used, but is instead a scaling factor. It is used in combination with the size of the main memory to determine the maximum memory usage for the inode cache. The valid values for this tunable are between 1 and 1000, inclusive. This value represents a maximum size. The system may not reach the maximum size. If the tunable is lowered, a best effort will be made to lower the size. It may not be possible to lower the size immediately, so shortly after tuning the size of the cache may be higher than the maximum. It is not recommended to set the values above 400, but the interface is provided in case it helps certain workloads. Values above 400 may exhaust the kernel heap. Similarly, low values (values below 100) may be too few depending on the workload and demands on the system. This may result in errors such as "File table full" being returned to the application. Also, on the 32-bit kernel, the ideal maximum may never be reached due to a restricted kernel heap. If this value is changed, the value for metadata cache size may need to be reconsidered if tuning for a specific workload. The inode cache controls the inode data stored in memory, so if the workload uses a large number of files, increasing the maximum size of the inode cache may help. If the workload uses few files, but the files are large, increasing the maximum size of the metadata cache may help; use the metadata cache size tunable for that. Because the inode cache is pinned memory, the cache size can be decreased if the workload uses few files. This frees the memory for use elsewhere.

j2_maxPageReadAhead

Purpose:

Specifies the maximum number of pages to be read ahead when processing a sequentially accessed file on Enhanced JFS.

Values:

Default: 128

Range: 0 to 65536 (64 K)

Type: Dynamic

Diagnosis:

N/A

Tuning:

The difference between minfree and maxfree should always be equal to or greater than j2_maxPageReadAhead. If run time decreases with higher a j2_maxPageReadAhead value, observe other applications to ensure that their performance has not deteriorated.

Refer To:

Sequential read performance tuning

j2_maxRandomWrite

Purpose:

Specifies a threshold for random writes to accumulate in RAM before subsequent pages are flushed to disk by the Enhanced JFS's write-behind algorithm. The random write-behind threshold is on a per-file basis.

Values:

Default: 0

Range: 0 to 65536 (64 K)

Type: Dynamic

Diagnosis:

N/A

Tuning:

Useful if too many pages are flushed out by $\boldsymbol{syncd}.$

j2_maxUsableMaxTransfer

Purpose:

Specifies the maximum LTG (Logical Track Group) size, in pages, that Enhanced JFS will gather into a single bufstruct. Defaults to 512, or a 2 megabyte LTG in a single bufstruct.

Values:

Default: 512 Range: 1 to 4096 Type: Mount

Diagnosis:

N/A

Tuning:

The value is in pages. It is a mount tunable. The range is 1 to 4096. The filesystem must be remounted. This tunable is not applicable on the 32-bit kernel due to heap constraints. On the 64-bit kernel, this value is the maximum size of the gather list of pages that can be collected into a single buf struct. The actual size of the gather list depends on the LTG size of the filesystem, this tunable only specifies a maximum size that Enhanced JFS will use to construct the bufstructs. Kernel heap exhaustion may occur due to the size of Enhanced JFS bufstructs. It is best to increment this value slowly, observing overall system performance after each change, to avoid kernel heap exhaustion.

j2_metadataCacheSize

Purpose:

Controls the amount of memory Enhanced JFS will use for the metadata cache.

Values:

Default: 400 Range: 1 to 1000 Type: Dynamic

Diagnosis:

Tuning this value is useful when accessing large amounts of file metadata causes excessive I/O.

Tuning:

This tunable does not explicitly indicate the amount that will be used, but is instead a scaling factor; it is used in combination with the size of the main memory to determine the maximum memory usage for the inode cache. The valid values for this tunable are between 1 and 1000, inclusive. This value represents a maximum size. The system may not reach the maximum size. If the tunable is lowered, a best effort will be made to lower the size. It may not be possible to lower the size immediately, so shortly after tuning the size of the cache may be higher than the maximum. It is not recommended to set the values above 400, but the interface is provided in case it helps certain workloads. Values above 400 may exhaust the kernel heap. Similarly, low values (values below 100) may be too few depending on the workload and demands on the system. This may result in extremely slow access times. Also, on the 32-bit kernel, the ideal maximum may never be reached due to a restricted kernel heap. If this value is changed, the value for inode cache size may need to be reconsidered if tuning for a specific workload. The inode cache controls the inode data stored in memory, so if the workload uses a large number of files, increasing the maximum size of the inode cache may help; use the inode_cache_size tunable for that. If the workload uses few files, but the files are large, increasing the maximum size of the metadata cache may help. Because the metadata cache is pinned memory, the cache size can be decreased if the workload uses small files. This frees the memory for use elsewhere.

j2_minPageReadAhead

j2_nBufferPerPagerDevice

Purpose:

Specifies the minimum number of pages to be read ahead when processing a sequentially accessed file on Enhanced JFS.

Values:

Default: 2

Range: 0 to 65536 (64 K)

Type: Dynamic

Diagnosis:

N/A

Tuning:

Useful to increase if there are lots of large sequential accesses. Observe other applications to ensure that their performance has not deteriorated. Value of 0 may be useful if I/O pattern is purely random.

Refer To:

Sequential read performance tuning

Purpose:

Specifies the minimum number of file system bufstructs for Enhanced JFS.

Values:

Default: 512

Range: 512 to 262144 (256 K)

Type: Mount

Diagnosis:

Using **vmstat -v**, look for the "external pager filesystem I/Os blocked with no fsbuf". If the kernel must wait for a free bufstruct, it puts the process on a wait list before the start I/O is issued and will wake it up once a bufstruct has become available.

Tuning:

This tunable specifies the number of bufstructs that start on the paging device. Enhanced JFS will allocate more dynamically. Ideally, this value should not be tuned, and instead j2_dynamicBufferPreallocation should be tuned. However, it may be appropriate to change this value if, when using **vmstat** -v, the value of "external pager filesystem I/Os blocked with no fsbuf" increases rapidly and j2_dynamicBufferPreallocation tuning has already been attempted. It may be appropriate to increase if striped logical volumes or disk arrays are being used.

98

j2_nonFatalCrashesSystem

Purpose:

Turns on the **j2_nonFatalCrashesSystem** flag to crash the system when Enhanced JFS corruption occurs.

Values:

Default: 0 Range: 0 or 1 Type: Mount

Diagnosis:

N/A

Tuning:

N/A

j2_nPagesPerWriteBehindCluster

Purpose:

Specifies the number of pages per cluster processed by Enhanced JFS's write behind algorithm.

Values:

Default: 32

Range: 0 to 65536 (64 K)

Type: Dynamic

Diagnosis:

N/A

Tuning:

Useful to increase if there is a need to keep more pages in RAM before scheduling them for I/O when the I/O pattern is sequential. May be appropriate to increase if striped logical volumes or disk arrays are being used.

j2_nRandomCluster

Purpose:

Specifies the distance apart (in clusters) that writes have to exceed in order for them to be considered as random by the Enhanced JFS's random write behind algorithm.

Values:

Default: 0

Range: 0 to 65536 (64 K)

Type: Dynamic

Diagnosis:

N/A

Tuning:

Useful to increase if there is a need to keep more pages in RAM before scheduling them for I/O when the I/O pattern is random and random write behind is enabled

(j2_maxRandomWrite).

j2_syncModifiedMapped

Purpose:

Syncs files that are modified through a mapping of **shmat** or **mmap** by using either the **sync** command or **sync** daemon. If set to 0, these files are skipped by the **sync** command and the **sync** daemon and must be synced using **fsync**.

Values:

Default: 1 Range: 0 or 1 Type: Dynamic

Diagnosis:

N/A

Tuning:

N/A

jfs_clread_enabled

Purpose:

This tunable controls whether JFS uses clustered reads on all files.

Values:

Default: 0 Range: 0 or 1 Type: Dynamic

Diagnosis:

N/A

Tuning:

In general, this option is not needed, but it may benefit certain workloads that have relatively random read access patterns.

jfs_use_read_lock

Purpose:

Controls whether JFS uses a shared lock when reading from a file. If this option is turned off, two processes cannot disrupt each other's read.

Values:

Default: 0 Range: 0 or 1 Type: Dynamic

Diagnosis:

N/A

Tuning:

Certain workloads may benefit from this.

lvm_bufcnt

Purpose:

Specifies the number of LVM buffers for raw physical I/Os.

Values:

Default: 9 Range: 1 to 64 Type: Dynamic

Diagnosis:

Applications performing large writes to striped raw logical volumes are not obtaining the desired throughput rate.

Tuning:

LVM splits large raw I/Os into multiple buffers of 128 K a piece. Default value of 9 means that about 1 MB I/Os can be processed without waiting for more buffers. If a system is configured to have striped raw logical volumes and is doing writes greater than 1.125 MB, increasing this value may help the throughput of the application. If performing larger than 1 MB raw I/Os, it might be useful to increase this value.

Refer To:

File system buffer tuning

Purpose:

Specifies the maximum number of pages to be read ahead when processing a sequentially accessed file.

Values:

Default: 8 (the default should be a power of two and should be greater than or equal to minpgahead)

Range: 0 to 4096 Type: Dynamic

Diagnosis:

Observe the elapsed execution time of critical sequential-I/O-dependent applications with the time command.

Tuning:

Because of limitations in the kernel, do not exceed 512 as the maximum value used. The difference between minfree and maxfree should always be equal to or greater than maxpgahead. If execution time decreases with higher maxpgahead, observe other applications to ensure that their performance has not deteriorated.

Refer To:

Sequential page read ahead

maxpgahead

maxrandwrt

Purpose:

Specifies a threshold (in 4 KB pages) for random writes to accumulate in RAM before subsequent pages are flushed to disk by the write-behind algorithm. The random write-behind threshold is on a per-file basis.

Values:

Default: 0

Range: 0 to largest_file_size_in_pages

Type: Dynamic

Diagnosis:

vmstat shows page out and I/O wait peaks on regular intervals (usually when the sync daemon is writing pages to disk).

Tuning:

Useful to set this value to 1 or higher if too much I/O occurs when **syncd** runs. Default is to have random writes stay in RAM until a sync operation. Setting maxrandwrt ensures these writes get flushed to disk before the sync operation has to occur. However, this could degrade performance because the file is then being flushed each time. Tune this option to favor interactive response time over throughput. After the threshold is reached, all subsequent pages are then immediately flushed to disk. The pages up to the threshold value stay in RAM until a sync operation. A value of 0 disables random write-behind.

Refer To:

Sequential and random write behind

Purpose:

Specifies the number of pages with which sequential read-ahead starts.

Values:

Default: 2

Range: 0 to 4096 (should be a power of two)

Type: Dynamic

Diagnosis:

Observe the elapsed execution time of critical sequential-I/O-dependent applications with time command.

Tuning:

Useful to increase if there are lots of large sequential accesses. Observe other applications to ensure that their performance has not deteriorated. Value of 0 may be useful if I/O pattern is purely random.

Refer To:

Sequential page read ahead

minpgahead

numclust

numfsbufs

Purpose:

Specifies the number of 16 k clusters processed by the sequential write-behind algorithm of the VMM.

Values:

Default: 1

Range: 0 to any positive integer

Type: Dynamic

Diagnosis:

N/A

Tuning:

Useful to increase if there is a need to keep more pages in RAM before scheduling them for I/O when the I/O pattern is sequential. May be appropriate to increase if striped logical volumes or disk arrays are being used.

Refer To:

Sequential and random write behind

Purpose:

Specifies the number of file system bufstructs.

Values:

Default: 196 (value is dependent on the size of the bufstruct) Type: Mount

Diagnosis:

A default **numfsbufs** is calculated based on the running kernel and the memory configuration of the machine. This value can be increased from the default value to a max of 2G-1. However, increasing the **numfsbufs** to a value close to 2G may cause kernel heap exhaustion. It is best to tune the **numfsbufs** incrementally, observing overall system performance as each change is made.

Tuning:

If the VMM must wait for a free bufstruct, it puts the process on the VMM wait list before the start I/O is issued and will wake it up once a bufstruct has become available. May be appropriate to increase if striped logical volumes or disk arrays are being

Refer To:

File system buffer tuning

103

pd_npages

Purpose:

Specifies the number of pages that should be deleted in one chunk from RAM when a file is deleted.

Values:

Default: 65536

Range: 1 to largest filesize_in_pages

Type: Dynamic

Diagnosis:

Real-time applications that experience sluggish response time while files are being deleted.

Tuning:

Tuning this option is only useful for real-time applications. If real-time response is critical, adjusting this option may improve response time by spreading the removal of file pages from RAM more evenly over a workload.

Refer To:

File system buffer tuning

Purpose:

When a system is low on free frames, aggressive pagehead can unnecessarily exhaust the free list and start page replacement. This tunable specifies a number of pages on the free list below which pagehead should be scaled back.

Values:

Default: 0 (Do not scale back pagehead)

Range: 0 to 4/5 of memory

Type: Dynamic

Diagnosis:

The system is paging but the expected memory usage should fit within main store, and the workload makes significant use of sequential access to files.

Tuning:

When the number of free pages in a *mempool* drops below this threshold, pageahead will be linearly scaled back, avoiding prepaging memory that would then need to be forced back out when the LRU daemon runs. Useful to increase if the system is unable to meet the memory demands under heavy read workload.

pgahd scale thresh

pv_min_pbuf

Purpose:

Specifies the minimum number of pbufs per PV that the LVM uses. This is a global value that applies to all VGs on the system.

Values:

Default: 256 on 32-bit kernel; 512 on 64-bit kernel.

Range: 512 to 2G-1 Type: Dynamic

Diagnosis:

Increase when the value of "pending disk I/Os blocked with no pbuf" (as displayed by **vmstat -v**) is increasing rapidly. This indicates that the LVM had to block I/O requests waiting for pbufs to become available.

Tuning:

Useful to increase if there is a substantial number of simultaneous I/Os and the value of "pending disk I/Os blocked with no pbuf" (as displayed by **vmstat -v**), increases over time. The **Ivmo** command can also be used to set a different value for a particular VG. In this case, the larger of the two values is used for this particular VG. Using a value close to 2G will pin a great deal of memory and might result in overall poor system performance. This value should be increased incrementally, and overall system performance should be monitored at each increase.

Refer To:

LVM performance tuning with the lvmo command

Purpose:

If set, will cause a **sync()** to flush all I/O to a file without holding the i-node lock, and then use the i-node lock to do the commit.

Values:

Default: 0 (off) Range 0 or 1 Type: Dynamic

Diagnosis:

I/O to a file is blocked when the **syncd** daemon is running.

Tuning:

Default value of 0 means that the i-node lock is held while all dirty pages of a file are flushed.

Refer To:

File synchronization performance tuning

Examples

sync_release_ilock

1. To list the current and reboot value, range, unit, type, and dependencies of all tunables parameters that are managed by the **ioo** command, enter the following command:

ioo -l

2. To display help on j2_nPagesPerWriteBehindCluster, enter the following command:

ioo -h j2_nPagesPerWriteBehindCluster

3. To set maxrandwrt to 4 after the next reboot, enter the following command:

ioo -r -o maxrandwrt=4

4. To permanently reset all ioo tunable parameters to default, enter the following command:

```
ioo -p -D
```

5. To list the reboot value of all ioo parameters, enter the following command:

6. To list (spreadsheet format) the current and reboot value, range, unit, type and dependencies of all tunables parameters managed by the ioo command, enter the following command:

```
ioo -x
```

Related Information

The nfso command, no command, raso command, schedo command, tuncheck command, tunchange command, tundefault command, tunrestore command, tunsave command, and vmo command.

Kernel Tuning in AIX 5L Version 5.3 Performance Tools Guide and Reference.

Performance tuning enhancements for AIX 5.2 in *Performance management*.

iostat Command

Purpose

Reports Central Processing Unit (CPU) statistics, asynchronous input/output (AIO) and input/output statistics for the entire system, adapters, TTY devices, disks and CD-ROMs.

Syntax

iostat [-a] [-l] [-s] [-t] [-z] [{ -A [-P] [-q | -Q] } | { [-d | -p] -D [-R] } [-m] [Drives ...] [Interval | Count |

Description

The iostat command is used to monitor system input/output (I/O) device loading by observing the time the physical disks are active in relation to their average transfer rates. The iostat command also generates reports that can be used to change system configuration to better balance the I/O load between physical disks and adapters.

All statistics are reported each time the iostat command is run. The report consists of a TTY and CPU header row followed by a row of TTY or asynchronous I/O and CPU statistics. On multiprocessor systems, CPU statistics are calculated system-wide as averages among all processors.

A header row with Number of CPUs and the Number of disks that are currently active in the system are printed at the beginning of the output. If the -s flag is specified, a system header row is displayed followed by a line of statistics for the entire system. The hostname of the system is printed in the system header row.

If you specify the -a flag, the information is displayed in a report in the following order:

- · An adapter-header row.
- · A line of statistics for the adapter.
- · A disk or tape-header row and the statistics of all the disks, CD-ROMs, or tapes connected to the adapter.

Such reports are generated for all disk or tape adapters that are connected to the system. But if the metrics values of the xfer attributes for the adapter are 0, the read, write, and queue attributes correspond to that of the disk that the path is associated with.

A disks header row is displayed followed by a line of statistics for each disk that is configured. If the PhysicalVolume parameter is specified, only those names specified are displayed.

If the *PhysicalVolume* parameter is specified, one or more alphabetic or alphanumeric physical volumes can be specified. If the *PhysicalVolume* parameter is specified, the TTY and CPU reports are displayed and the disk report contains statistics for the specified drives. If a specified logical drive name is not found, the report lists the specified name and displays the message Drive Not Found. If no Logical Drive Names are specified, the report contains statistics for all configured disks and CD-ROMs. If no drives are configured on the system, no disk report is generated. The first character in the *PhysicalVolume* parameter cannot be numeric.

The Interval parameter specifies the amount of time in seconds between each report. If the Interval parameter is not specified, the **iostat** command generates a single report containing statistics for the time since system startup (boot). The Count parameter can be specified in conjunction with the Interval parameter. If the Count parameter is specified, the value of count determines the number of reports generated at Interval seconds apart. If the Interval parameter is specified without the Count parameter, the iostat command generates reports continuously.

The iostat command is useful in determining whether a physical volume is becoming a performance bottleneck and if there is potential to improve the situation. The % utilization field for the physical volumes indicates how evenly the file activity is spread across the drives. A high % utilization on a physical volume is a good indication that there may be contention for this resource. Since the CPU utilization statistics are also available with the iostat report, the percentage of time the CPU is in I/O wait can be determined at the same time. Consider distributing data across drives if the I/O wait time is significant and the disk utilization is not evenly distributed across volumes.

Beginning with AIX 5.3, the iostat command reports number of physical processors consumed (physc) and the percentage of entitlement consumed (% entc) in Micro-Partitioning environments. These metrics will only be displayed on Micro-Partitioning environments.

Note: Some system resource is consumed in maintaining disk I/O history for the iostat command. Use the sysconfig subroutine, or the SMIT to stop history accounting. While the iostat command is running for Count of iterations and if there is a change in system configuration that affects the output of iostat command, it prints a warning message about the configuration change. It then continues the output after printing the updated system configuration information and the header.

Reports

The iostat command generates four types of reports, the TTY and CPU Utilization report, the Disk Utilization report, the System throughput report and the Adapter throughput report.

TTY and CPU Utilization Report: The first report generated by the iostat command is the TTY and CPU Utilization Report. For multiprocessor systems, the CPU values are global averages among all processors. Also, the I/O wait state is defined system-wide and not per processor. The report has the following format:

Column	Description
tin	Shows the total number of characters read by the system for all TTYs.
tout	Shows the total number of characters written by the system to all TTYs.
% user	Shows the percentage of CPU utilization that occurred while executing at the user level (application).
% sys	Shows the percentage of CPU utilization that occurred while executing at the system level (kernel).
% idle	Shows the percentage of time that the CPU or CPUs were idle and the system did not have an outstanding disk I/O request.
% iowait	Shows the percentage of time that the CPU or CPUs were idle during which the system had an outstanding disk I/O request.
physc	Number of physical processors consumed, displayed only if the partition is running with shared processor.
% entc	The percentage of entitled capacity consumed, displayed only if the partition is running with shared processor. Because the time base over which this data is computed can vary, the entitled capacity percentage can sometimes exceed 100%. This excess is noticeable only with small sampling intervals.

This information is updated at regular intervals by the kernel (typically sixty times per second). The TTY report provides a collective account of characters per second received from all terminals on the system as well as the collective count of characters output per second to all terminals on the system.

Methods Used to Compute CPU Disk I/O Wait Time: Operating system version 4.3.3 and later contain enhancements to the method used to compute the percentage of CPU time spent waiting on disk I/O (wio time). The method used in AIX 4.3.2 and earlier versions of the operating system can, under certain circumstances, give an inflated view of wio time on SMPs. The wio time is reported by the commands sar (%wio), vmstat (wa) and iostat (% iowait).

The method used in AIX 4.3.2 and earlier versions is as follows: At each clock interrupt on each processor (100 times a second per processor), a determination is made as to which of the four categories (usr/sys/wio/idle) to place the last 10 ms of time. If the CPU was busy in usr mode at the time of the clock interrupt, then usr gets the clock tick added into its category. If the CPU was busy in kernel mode at the time of the clock interrupt, then the sys category gets the tick. If the CPU was not busy, a check is made to see if any I/O to disk is in progress. If any disk I/O is in progress, the wio category is incremented. If no disk I/O is in progress and the CPU is not busy, the idle category gets the tick. The inflated view of wio time results from all idle CPUs being categorized as wio regardless of the number of threads waiting on I/O. For example, systems with just one thread doing I/O could report over 90 percent wio time regardless of the number of CPUs it has.

The method used in AIX 4.3.3 and later is as follows: The change in operating system version 4.3.3 is to only mark an idle CPU as wio if an outstanding I/O was started on that CPU. This method can report much lower wio times when just a few threads are doing I/O and the system is otherwise idle. For example, a system with four CPUs and one thread doing I/O will report a maximum of 25 percent wio time. A system with 12 CPUs and one thread doing I/O will report a maximum of 8 percent wio time. NFS client reads/writes go through the VMM, and the time that biods spend in the VMM waiting for an I/O to complete is now reported as I/O wait time.

Disk or Tape Utilization Report: The second report generated by the iostat command is the Diskor Tape Utilization Report. By default, the disk Utilization report is displayed, and you must specify the -p flag to display the Tape Utilization Report. The disk report provides statistics on a per-physical-disk basis, and tape utilization report provides statistics on a per-tape basis. The default report has a format similar to the following one:

% tm act Indicates the percentage of time the physical disk/tape was active (bandwidth utilization for the drive). Indicates the amount of data transferred (read or written) to the drive in KB per second. Kbps

Indicates the number of transfers per second that were issued to the physical disk/tape. A transfer is tps

an I/O request to the physical disk/tape. Multiple logical requests can be combined into a single I/O

request to the disk. A transfer is of indeterminate size.

The total number of KB read. Kb read Kb wrtn The total number of KB written.

If you specify the -D flag, the report has the following metrics for disk or tape. Extended metrics for disk are displayed by default and users need to specify the -p option for tape utilization report:

Metrics related to transfers (xfer):

Indicates the percentage of time the physical disk or tape was active (bandwidth % tm act utilization for the drive).

bps Indicates the amount of data transferred (read or written) per second to the drive. Different suffixes are used to represent the unit of transfer. Default is in

bytes per second.

Indicates the number of transfers per second that were issued to the physical tps

disk or tape. A transfer is an I/O request to the physical disk or tape. Multiple logical requests can be combined into a single I/O request to the disk. A transfer

is of indeterminate size.

Metrics related to transfers (xfer):

Indicates the amount of data read per second, from the drive. Different suffixes bread

are used to represent the unit of transfer. Default is in bytes per second.

bwrtn Indicates the amount of data written per second, to the drive. Different suffixes

are used to represent the unit of transfer. Default is in bytes per second.

Read Service Metrics (read):

Indicates the number of read transfers per second.

Indicates the average service time per read transfer. Different suffixes are used avgserv

to represent the unit of time. Default is in milliseconds.

minserv Indicates the minimum read service time. Different suffixes are used to represent

the unit of time. Default is in milliseconds.

maxserv Indicates the maximum read service time. Different suffixes are used to

represent the unit of time. Default is in milliseconds.

Indicates the number of read timeouts per second. timeouts fails Indicates the number of failed read requests per second.

Write Service Metrics (write):

Indicates the number of write transfers per second. wps

Indicates the average service time per write transfer. Different suffixes are used avgserv

to represent the unit of time. Default is in milliseconds.

Indicates the minimum write service time. Different suffixes are used to represent minserv

the unit of time. Default is in milliseconds.

Indicates the maximum write service time. Different suffixes are used to maxserv

represent the unit of time. Default is in milliseconds.

timeouts Indicates the number of write timeouts per second. fails Indicates the number of failed write requests per second.

Wait Queue Service Metrics

(queue): avgtime

Restriction: These metrics are not applicable for tapes.

Indicates the average time spent by a transfer request in the wait queue.

Different suffixes are used to represent the unit of time. Default is in

milliseconds.

mintime Indicates the minimum time spent by a transfer request in the wait queue.

Different suffixes are used to represent the unit of time. Default is in

Indicates the maximum time spent by a transfer request in the wait queue. maxtime

Different suffixes are used to represent the unit of time. Default is in

milliseconds.

Indicates the average wait queue size. avgwqsz avgsqsz Indicates the average service queue size.

sqfull Indicates the number of times the service queue becomes full (that is, the disk is

not accepting any more service requests) per second.

Legend of suffixes representing different units of representation		
Suffix	Description	
K	1000 bytes	
М	1 000 000 bytes if displayed in xfer metrics. Minutes, if displayed in read/write/wait service metrics.	
G	1 000 000 000 bytes.	
Т	1 000 000 000 000 bytes.	
S	Seconds.	
Н	Hour.	

Note: For drives that do not support service time metrics, read, write and wait queue service metrics will not be displayed.

Statistics for CD-ROM devices are also reported.

System Throughput Report: This report is generated if the **-s** flag is specified. This report provides statistics for the entire system. This report has the following format:

Indicates the amount of data transferred (read or written) in the entire system in KB per second. Kbps

tps Indicates the number of transfers per second issued to the entire system.

Kb read The total number of KB read from the entire system. The total number of KB written to the entire system. Kb wrtn

Adapter Throughput Report: This report is generated if the -a flag is specified. This report provides statistics on an adapter-by-adapter basis (for both physical and virtual adapters). This report has the following format for a physical adapter report:

Kbps Indicates the amount of data transferred (read or written) in the adapter in KB per second.

tps Indicates the number of transfers per second issued to the adapter.

Kb read The total number of KB read from the adapter. Kb wrtn The total number of KB written to the adapter.

The virtual adapter's default throughput report has the following format:

Kbps Indicates the amount of data transferred (read or written) in the adapter in KB per second.

tps Indicates the number of transfers per second issued to the adapter.

bkread Number of blocks received per second from the hosting server to this adapter. bkwrtn Number of blocks per second sent from this adapter to the hosting server.

partition-id The partition ID of the hosting server, which serves the requests sent by this adapter.

The virtual adapter's extended throughput report (-D option) has the following format:

Metrics related to transfers (xfer:)

Kbps Indicates the amount of data transferred (read or written) in the adapter in KB per

second.

Indicates the number of transfers per second issued to the adapter. tps

bkread Number of blocks received per second from the hosting server to this adapter. bkwrtn Number of blocks per second sent from this adapter to the hosting server.

partition-id The partition ID of the hosting server, which serves the requests sent by this adapter.

Adapter Read Service Metrics (read:)

Indicates the number of read requests per second. rps

Indicates the average time to receive a response from the hosting server for the read avgserv

request sent. Different suffixes are used to represent the unit of time. Default is in

milliseconds.

Indicates the minimum time to receive a response from the hosting server for the read minserv

request sent. Different suffixes are used to represent the unit of time. Default is in

milliseconds.

Indicates the maximum time to receive a response from the hosting server for the read maxserv

request sent. Different suffixes are used to represent the unit of time. Default is in

milliseconds.

Adapter Write Service Metrics (write:)

wps Indicates the number of write requests per second.

Indicates the average time to receive a response from the hosting server for the write avgserv

request sent. Different suffixes are used to represent the unit of time. Default is in

Indicates the minimum time to receive a response from the hosting server for the write minserv

request sent. Different suffixes are used to represent the unit of time. Default is in

milliseconds.

Indicates the maximum time to receive a response from the hosting server for the write maxserv

request sent. Different suffixes are used to represent the unit of time. Default is in

milliseconds.

Adapter Wait Queue Metrics (queue:)

avgtime Indicates the average time spent by a transfer request in the wait queue. Different

suffixes are used to represent the unit of time. Default is in milliseconds.

mintime Indicates the minimum time spent by a transfer request in the wait queue. Different

suffixes are used to represent the unit of time. Default is in milliseconds.

Indicates the maximum time spent by a transfer request in the wait queue. Different maxtime

suffixes are used to represent the unit of time. Default is in milliseconds.

Indicates the average wait queue size. avgwqsz avgsqsz Indicates the average service queue size.

sqfull Indicates the number of times the service queue becomes full (that is, the hosting server

is not accepting any more service requests) per second.

Legend of suffixes representing different units of representation		
Suffix	Description	
K	1000 bytes.	
М	1 000 000 bytes if displayed in xfer metrics. Minutes, if displayed in read/write/wait service metrics.	
G	1 000 000 000 bytes.	
Т	1 000 000 000 bytes.	
S	Seconds.	
Н	Hours.	

Asynchronous I/O report: The asynchronous I/O report has the following column headers:

Average global AIO request count per second for the specified interval. avgc

Average fastpath request count per second for the specified interval. avfc

Maximum global AIO request count since the last time this value was fetched. maxgc Maximum fastpath request count since the last time this value was fetched. maxfc

maxreqs Maximum AIO requests allowed.

Disk Input/Output History: To improve performance, the collection of disk input/output statistics has been disabled. To enable the collection of this data, type:

chdev -1 sys0 -a iostat=true

To display the current settings, type:

lsattr -E -l sys0 -a iostat

If the collection of disk input/output history is disabled and **iostat** is called without an interval, the **iostat** output displays the message Disk History Since Boot Not Available instead of disk statistics.

Flags

-a	Specifies the Adapter Throughput Report. The read, write, and queue attributes correspond to that of
	the disk. The xfer attributes correspond to the path. The -a flag can be specified with the -A flag, but
	not when -q or -Q flags are specified.

- -A Displays the AIO statistics for the specified interval and count.
- -d Specifies drive report only.
- -D Specifies the extended disk or tape report. If neither the -p flag nor the -d flag is specified along with the -D flag, then the default is disk only.
- -I Displays the output in long listing mode. The default column width is 80.
- **-m** Specifies the statistics for paths.
- **-p** Displays the tape statistics.
 - **Note:** Only the Atape device statistics are reported.
- **-P** Displays the Adapter Throughput report, using the POSIX AIO calls.
- -q Specifies AIO queues and their request counts. The -q flag can be specified only with the -A flag.
- **-Q** Displays a list of all the mounted filesystems and the associated queue numbers with their request counts. The **-Q** flag can be specified only with the **-A** flag.
- -R Specifies that the reset of *min** and *max** values should happen at each interval. The default is to reset the values once when **iostat** is started. The **-R** flag can be specified only with the **-D** flag.
- -s Specifies the system throughput report. The -s flag can be specified with the -A flag, but not when -q or -Q flags are specified.
- -t Specifies TTY/CPU report only. The -t flag is mutually exclusive with the -d or -D flags.
- **-T** Specifies the time stamp.
- -z Resets the disk input/output statistics. Only root users can use this option.

Examples

1. To display a single history since boot report for all TTY, CPU, and Disks, type:

iostat

To display a continuous disk report at two second intervals for the disk with the logical name disk1, type:

iostat -d disk1 2

3. To display six reports at two second intervals for the disk with the logical name disk1, type:

iostat disk1 2 6

4. To display six reports at two second intervals for all disks, type:

iostat -d 2 6

5. To display six reports at two second intervals for three disks named disk1, disk2, disk3, type:

iostat disk1 disk2 disk3 2 6

6. To print the System throughput report since boot, type:

iostat -s

7. To print the Adapter throughput reports at 5-second intervals, type:

iostat -a 5

8. To print 10 System and Adapter throughput reports at 20-second intervals, with only the TTY and CPU report (no disk reports), type:

iostat -sat 20 10

9. To print the System and Adapter throughput reports with the Disk Utilization reports of hdisk0 and hdisk7 every 30 seconds, type:

iostat -sad hdisk0 hdisk7 30

10. To display time stamp next to each line of output of **iostat**, type:

```
iostat -T 60
```

11. To display 6 reports at 2-second intervals on AIO, type:

```
iostat -A 2 6
```

12. To display AIO statistics since boot for queues associated with all mounted filesystems, type:

```
iostat -A -Q
```

13. To display extended drive report for all disks, type:

```
iostat -D
```

14. To display extended drive report for all tapes, type:

```
iostat -Dp
```

15. To display extended drive report for a specific disk, type:

```
iostat -D hdisk0
```

16. To reset the disk input/output statistics, type:

```
iostat -z
```

File

/usr/bin/iostat

Contains the iostat command.

Related Information

The vmstat command.

The iostadd Kernel Service.

Monitoring disk I/O in Performance management

The Input and Output Handling Programmer's Overview in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs describes the files, commands, and subroutines used for low-level, stream, terminal, and asynchronous I/O interfaces.

ipcrm Command

Purpose

Removes message queue, semaphore set, or shared memory identifiers.

Syntax

ipcrm [-m SharedMemoryID][-M SharedMemoryKey][-q MessageID][-Q MessageKey][-s SemaphoreID] [-S SemaphoreKey]

```
ipcrm -r {-q|-m|-s} Name
```

ipcrm -r -u [-o Owner] [-g Group]

Description

The ipcrm command removes one or more message queues, semaphore sets, or shared memory identifiers.

Flags

-g Group	Restricts the removal to unnamed semaphores matching the group specified.
-m SharedMemory ID	Removes the shared memory identifier <i>SharedMemoryID</i> . The shared memory segment and data structure associated with <i>SharedMemoryID</i> are also removed after the last detach operation.
-M SharedMemoryKey	Removes the shared memory identifier, created with the key <i>SharedMemoryKey</i> . The shared memory segment and data structure associated with it are also removed after the last detach operation.
-o Owner	Restricts the removal to unnamed semaphores matching the owner specified.
-q MessageID	Removes the message queue identifier <i>MessageID</i> and the message queue and data structure associated with it.
-Q MessageKey	Removes the message queue identifier, created with the key <i>MessageKey</i> , and the message queue and data structure associated with it.
-r	Removes named or unnamed real-time interprocess communication objects. The named real-time object is either a real-time message queue (-q), a real-time shared memory (-m), or a real-time semaphore (-s) and is identified by its <i>Name</i> .
-s SemaphoreID	Removes the semaphore identifier <i>SemaphoreID</i> and the set of semaphores and data structure associated with it.
-S SemaphoreKey	Removes the semaphore identifier, created with the key <i>SemaphoreKey</i> , and the set of semaphores and data structure associated with it.
-u	Removes all real-time unnamed semaphores. Using a descriptor on a destroyed unnamed semaphore can result in unspecified behavior.

The msgctl, shmctl, and semctl subroutines provide details of the remove operations. The identifiers and keys can be found by using the ipcs command.

Examples

To remove the shared memory segment associated with SharedMemoryID 18602, enter:

ipcrm -m 18602

Related Information

The ipcs command.

The msgget subroutine, semctl subroutine, semget subroutine, shmctl subroutine, shmget subroutine.

The Commands in Operating system and device management.

ipcs Command

Purpose

Reports interprocess communication facility status.

Syntax

ipcs [-m] [-q] [-s] [-S] [-P] [-l] [-a | -b -c -o -p -r -t] [-T] [-C CoreFile] [-N Kernel] [-X]

Description

The ipcs command writes to the standard output information about active interprocess communication facilities. If you do not specify any flags, the ipcs command writes information in a short form about currently active message queues, shared memory segments, semaphores, remote queues, and local queue headers.

The column headings and the meaning of the columns in an **ipcs** command listing follow. The letters in parentheses indicate the flags that cause the corresponding heading to appear. The designator **all** means the heading is always displayed. These flags only determine what information is provided for each facility. They do not determine which facilities are listed.

Т

(all) the type of facility. There are three facility types:

q message queue

m shared memory segment

s semaphore

ID

(all) the identifier for the facility entry.

KEY

(all) the key used as a parameter to the **msgget** subroutine, the **semget** subroutine, or the **shmget** subroutine to make the facility entry.

Note: The key of a shared memory segment is changed to IPC_PRIVATE when the segment is removed until all processes attached to the segment detach from it.

(all) the facility access modes and flags. The mode consists of 11 characters that are interpreted as follows:

MODE

The first two characters can be the following:

- R If a process is waiting on a msgrcv system call.
- **S** If a process is waiting on a **msgsnd** system call.
- D If the associated shared memory segment has been removed. It disappears when the last process attached to the segment detaches it.
- **C** If the associated shared memory segment is to be cleared when the first attach is run.
- If the corresponding special flag is not set.

The next nine characters are interpreted as three sets of 3 bits each. The first set refers to the owner's permissions; the next to permissions of others in the user group of the facility entry; and the last to all others. Within each set, the first character indicates permission to read, the second character indicates permission to write or alter the facility entry, and the last character is currently unused.

The permissions are indicated as follows:

- r If read permission is granted.
- w If write permission is granted.
- **a** If alter permission is granted.
- If the indicated permission is not granted.
- (all) The login name of the owner of the facility entry.
- (all) The name of the group that owns the facility entry.
- $(\boldsymbol{a}, \boldsymbol{c})$ The login name of the creator of the facility entry.
- (a,c) The group name of the creator of the facility entry.

Note: For the **OWNER**, **GROUP**, **CREATOR**, and **CGROUP**, the user and group IDs display instead of the login names.

CBYTES

OWNER

GROUP

CREATOR

CGROUP

(a,o) The number of bytes in messages currently outstanding on the associated message

QNUM QBYTES (a,o) The number of messages currently outstanding on the associated message queue. (a,b) The maximum number of bytes allowed in messages outstanding on the associated message queue.

115

LSPID (a,p) The ID of the last process that sent a message to the associated queue. If the last

> message sent was from a process in a node other than the node that holds the queue, LSPID is the PID of the kernel process that actually placed the message on the queue, not

the PID of the sending process.

LRPID (a,p) The ID of the last process that received a message from the associated queue. If the

last message received was from a process in a node other than the node that holds the queue, LRPID is the PID of the kernel process that actually received the message on the

queue, not the PID of the receiving process.

STIME (a.t) The time when the last message was sent to the associated queue. For remote queues,

this is the server time. No attempt is made to compensate for time-zone differences between

the local clock and the server clock.

RTIME (a.t) The time when the last message was received from the associated queue. For remote

queues, this is the server time. No attempt is made to compensate for any time-zone

differences between the local clock and the server clock.

CTIME (a,t) The time when the associated entry was created or changed. For remote queues, this is

the server time. No attempt is made to compensate for any time-zone differences between

the local clock and the server clock.

NATTCH (a,o) The number of processes attached to the associated shared memory segment.

SEGSZ (a,b) The size of the associated shared memory segment. **CPID** (a,p) The process ID of the creator of the shared memory entry.

LPID (a,p) The process ID of the last process to attach or detach the shared memory segment.

ATIME (a,t) The time when the last attach was completed to the associated shared memory

segment.

DTIME (a,t) The time the last detach was completed on the associated shared memory segment.

NSEMS (a,b) The number of semaphores in the set associated with the semaphore entry.

OTIME (a,t) The time the last semaphore operation was completed on the set associated with the

semaphore entry.

SID (S) The shared memory segment id. SIDs can be used as input to the symon -S command.

RTFLAGS (r) Filled with UNLINK when the real-time interprocess communication object has been

unlinked. Otherwise, a hyphen (-) is displayed.

NAME (r) The name of the real-time interprocess communication object. A hyphen (-) is displayed

for the unnamed semaphores.

This command supports multibyte character sets.

Flags

-a Uses the -b, -c, -o, -p and -t flags.

-b Writes the maximum number of bytes in messages on queue for message queues, the size of

segments for shared memory, and the number of semaphores in each semaphores set.

Writes the login name and group name of the user that made the facility. -C

-CCoreFile Uses the file specified by the CoreFile parameter in place of the Idev/mem file. The CoreFile

parameter is a memory image file produced by the Ctrl-(left)Alt-Pad1 key sequence.

-1 When used with the -S flag, this flag writes the list of SIDs unwrapped.

Writes information about active shared memory segments.

-NKernel Uses the specified Kernel (the /usr/lib/boot/unix file is the default).

Writes the following usage information: -0

· Number of messages on queue

· Total number of bytes in messages in queue for message queues

Number of processes attached to shared memory segments

Writes process number information: -р

· Process number of the last process to receive a message on message gueues

· Process number of last process to send a message on message queues

· Process number of the creating process

· Process number of last process to attach or detach on shared memory segments

-P	Writes the list of SIDs (segment IDs) associated with the shared memory ID, along with the
	number of bytes pinned to that segment and an indication of whether the segment is large-page
	enabled or not. If the segment is large-page enabled, a 'Y' is displayed, otherwise a '-' is
	displayed.
-a	Writes information about active message queues.

Writes information about real-time interprocess communication objects. -r

Writes information about active semaphore set. -s

Writes the list of SID attached to shared memory id.

-t Writes time information:

- · Time of the last control operation that changed the access permissions for all facilities
- · Time of the last msgsnd and msgrcv on message queues
- · Time of the last shmat and shmdt on shared memory
- · Time of the last semop on semaphore sets
- -T Writes the output of the -t flag with the date.
- -X Prints all available characters of each user name, group name of owner, creator, owner group, creator group instead of truncating to the first 8 characters.

Notes:

-S

- 1. If the user specifies either the -C or -N flag, the real and effective UID/GID is set to the real UID/GID of the user invoking ipcs.
- 2. Values can change while ipcs is running; the information it gives is guaranteed to be accurate only when it was retrieved.

Example

Example output from entering ipcs without flags:

ΙP	C status	from /dev/mer	n as of Mon	Aug 14 15:03	3:46 1989
Τ	ID	KEY	MODE	OWNER	GROUP
Me	ssage Que	eues:			
q	0	0x00010381	-Rrw-rw-rw-	- root	system
q	65537	0x00010307	-Rrw-rw-rw-	- root	system
q	65538	0x00010311	-Rrw-rw-rw-	- root	system
q	65539	0x0001032f	-Rrw-rw-rw-	- root	system
q	65540	0x0001031b	-Rrw-rw-rw-	- root	system
q	65541	0x00010339	rw-rw-rw-	root	system
q	6	0x0002fe03	-Rrw-rw-rw-	- root	system
Sh	ared Memo	ory:			
m	65537	0x00000000	DCrw	- root	system
m	720898	0x00010300	-Crw-rw-rw-	- root	system
m	65539	0x00000000	DCrw	- root	system
Se	maphores:	:			
S	131072	0x4d02086a	ra-ra	- root	system
S	65537	0x00000000	ra	- root	system
S	1310722	0x000133d0	ra	- 7003	30720

Files

/usr/lib/boot/unix Specifies the system kernel image.

/dev/mem Specifies memory. /etc/passwd Specifies user names. /etc/group Specifies group names. /usr/include/sys/ipc.h Contains the header file.

Related Information

The **ipcrm** command.

The **symon** command.

The msgrcv subroutine, msgsnd subroutine, semop subroutine, shmat subroutine, shmdt subroutine.

Commands in Operating system and device management.

ipfilter Command

Purpose

Extracts different operation headers from an ipreport output file and displays them in a table. Some customized nfs information regarding requests and replies is also provided.

Syntax

ipfilter [-f [untxca]][-s [untxca]][-n [-d milliseconds]] ipreport output file

Description

The **ipfilter** command extracts specific information from an ipreport output file and displays it to a table. The operation headers currently recognized are: udp, nfs, tcp, ipx, icmp, atm. The ipfilter command has three different types of reports:

- A single file (ipfilter.all) that displays a list of all the selected operations. The table displays packet number, Time, Source and Destination, Length, Sequence #, Ack #, Source Port, Destination Port, Network Interface, and Operation Type.
- Individual files for each selected header (ipfilter.udp, ipfilter.nfs, ipfilter.tcp, ipfilter.ipx, ipfilter.icmp, ipfilter.atm). The information is the same as ipfilter.all.
- A file **nfs.rpt** that reports on nfs requests and replies. The table contains: Transaction ID #, Type of Request, Status of Request, Call Packet Number, Time of Call, Size of Call, Reply Packet Number, Time of Reply, Size of Reply, and Elapsed millisecond between call and reply.

Flags

untxca Specifies operation headers (udp, nfs, tcp, ipx, and icmp and atm respectively). Only Call/Reply pairs whose elapsed time is greater than milliseconds are to be shown. -d milliseconds Selected operations are to be shown in ipfilter.all. -f[untxca]

Generates an nfs.rpt.

-s [untxc] Separate files are to be produced for each of the selected operations.

Related Information

The iptrace daemon, ipreport command.

ipreport Command

Purpose

Generates a packet trace report from the specified packet trace file.

Syntax

/usr/sbin/ipreport [-e] [-r] [-n] [-s] LogFile

Description

The /usr/sbin/ipreport command generates a trace report from the specified trace file created by the iptrace command. The LogFile parameter specifies the name of the file containing the results of the Internet Protocol trace. This file is created by the **iptrace** command.

Flags

- Generates the trace report in EBCDIC format. The default format is ASCII. -e
- -r Decodes remote procedure call (RPC) packets.
- Includes a packet number to facilitate easy comparison of different output formats. -n
- Prepends the protocol specification to every line in a packet.

Related Information

The **iptrace** command, **trpt** command.

ipsec_convert Command

Purpose

Converts IP Security tunnel export files to a format that can be imported by the IBM Secure Network Gateway.

Syntax

ipsec convert SNG22 | FW31 [-f export directory]

Description

IP Security allows the importing of IBM Secure Network Gateway 2.2 and IBM Firewall 3.1 tunnels using the imptun command. However, these firewall products do not allow the reverse capability. The ipsec convert command allows for this capability by translating exported IP Security tunnels to IBM Firewall tunnels. The translated files will be placed in the current directory.

Flags

SNG22 | FW31 Specifies whether the format of the resulting files will be in the format of IBM Secure Network

Gateway 2.2 or IBM Firewall 3.1 format.

Specifies the directory where the exported IPSec files are located. -f

Related Information

The imptun command.

ipsecstat Command

Purpose

Lists status of IP Security devices, IP Security crypto algorithms, and statistics of IP Security packets.

Syntax

ipsecstat [-c] [-d] [-A] [-E]

Description

The **ipsecstat** command, used without flags, displays the status of the IP Security devices, the crypto algorithms installed for IP Security, and the statistics of IP Security packets.

The command can be used with flags to only list the status of IP Security devices, to only list the installed algorithms, or to reset statistic counters (to zero).

Flags

- **-c** Resets statistics counters (after displaying current value). The **-c** flag cannot be used with any other flags.
- -d Lists only the status of the IP Security devices. The -d flag cannot be used with any other flags.
 -A Lists only the installed authentication algorithms. The -A flag cannot be used with any other flags.
- -E Lists only the installed encryption algorithms. The -E flag cannot be used with any other flags.

ipsectrcbuf Command

Purpose

Lists the contents of tracing buffers in the IP Security subsystem.

Syntax

ipsectrcbuf [-I {0|1|2}]

Description

The IP Security subsystem maintains a memory resident trace buffer to help debug if there is a problem. The content of the buffer, a fixed number of the most recent trace messages, will be in a system dump or can be listed by running this command with no arguments.

Flags

- -I Sets the IP Security trace level. By default, of the nine IP Security trace hooks, only IPSEC_ERROR trace messages are put into the buffer. To enable or disable the other trace hooks, use the -I flag with one of the following values:
 - Only IPSEC_ERROR trace messages are written to the buffer. This is the default.
 - 1 IPSEC_FILTER, IPSEC_CAPSUL, IPSEC_CRYPTO, IPSEC_TUNNEL, as well as IPSEC_ERROR trace messages are written to the buffer.
 - All IP Security trace messages are put into the buffer (that includes IPSEC_FILTER_INFO, IPSEC_CAPSUL_INFO, IPSEC_CRYPTO_INFO, and IPSEC_TUNNEL_INFO as well as those in level 1).

iptrace Daemon

Purpose

Provides interface-level packet tracing for Internet protocols.

Syntax

/usr/sbin/iptrace [-a] [-b][-e] [-u] [-PProtocol_list] [-iInterface] [-pPort_list] [-sHost [-b]] [-dHost] [-L Log_size] [-B] [-T] [-S snap_length] LogFile

Description

The /usr/sbin/iptrace daemon records Internet packets received from configured interfaces. Command flags provide a filter so that the daemon traces only packets meeting specific criteria. Packets are traced only between the local host on which the iptrace daemon is invoked and the remote host.

If the **iptrace** process was started from a command line without the System Resource Controller (SRC), it must be stopped with the kill -15 command. The kernel extension loaded by the iptrace daemon remains active in memory if iptrace is stopped any other way.

The LogFile parameter specifies the name of a file to which the results of the **iptrace** command are sent. To format this file, run the **ipreport** command. The **ipreport** command may display the message TRACING DROPPED xxxx PACKETS. This count of dropped packets indicates only the number of packets that the iptrace command was unable to grab because of a large packet, the size of which exceeded the socket-receive buffer size. This message does NOT mean that the packets are being dropped by the system.

Notes:

- 1. The file specified by the LogFile parameter should not reside on an NFS-mounted file system. Specifying an output file on an NFS-mounted file system can cause the **iptrace** daemon to hang. In this case, you might not be able to kill the **iptrace** daemon, thus, requiring that you restart the system.
- 2. If iptrace is killed with kill -9, it is required that you issue iptrace -u to unload the bpf kernel extensions or simply reboot. Sometimes, on a busy system, it is required that you issue iptrace -u multiple times due to a possibility that the kernel extension used by iptrace is busy processing packets.
- 3. The **iptrace** command supports **srcmstr** as well and can be started and stopped from the command line. If started from the command line, it can be stopped using the kill -9 command.

Flage

riags	
-a	Suppresses ARP packets.
-b	Changes the -d or -s flags to bidirectional mode.
-B	Uses bpf for packet capture.
-d Host	Records packets headed for the destination host specified by the <i>Host</i> variable. The <i>Host</i> variable can be a host name or an Internet address in dotted-decimal format.
	If used with the -b flag, the -d flag records packets both going to and coming from the host specified by the <i>Host</i> variable.
-e	Enables promiscuous mode on network adapters that support this function.
-i Interface	Records packets received on the interface specified by the Interface variable.
-L Log_size	This option causes iptrace to log data in such that the LogFile is copied to LogFile.old at the start and also every time it becomes approximately <i>Log_size</i> bytes long.
-P Protocol_list	Records packets that use the protocol specified by the <i>Protocol_list</i> variable which is a comma separated list of protocols. The Protocols can be a decimal number or name from the <i>/etc/protocols</i> file.
-p Port_list	Records packets that use the port number specified by the <i>Port_list</i> variable which is a comma separated list of ports. The <i>Port_list</i> variable can be a decimal number or name from the <i>/etc/services</i> file.
-s Host	Records packets coming from the source host specified by the <i>Host</i> variable. The <i>Host</i> variable can be a host name or an Internet address in dotted-decimal format.
	If used with the -b flag, the -s flag records packets both going to and coming from the host specified by the <i>Host</i> variable.
-S snap_length	Specifies the snap size (how much of each packet is actually captured from the wire) when you run the iptrace daemon with the -B flag (the bpf support). The command iptrace -S 1500 /tmp/iptrace.dump will limit captured packet size to 1500 bytes. The default is 80 bytes.

- Creates a tcpdump compatible dump file. To read the output, use ipreport -T or tcpdump -r. -T iptrace -T in AIX 5.3.0 is not compatible with release 5.2 and earlier, due to different versions of packet capture library (libpcap). Captured files created with iptrace -T in AIX 5.3 cannot be read with standard AIX tcpdump or ipreport on AIX 5.2 and earlier.
- Unloads the kernel extension that was loaded by the iptrace daemon at startup. -u

Exit Status

The command returns the following exit values:

- 0 The daemon has run successfully.
- 1 · No interfaces were found.
 - The pcap_open_live subroutine failed.
 - The pcap_datalink subroutine failed.
 - The pcap_lookupnet subroutine failed.
 - The pcap_loop subroutine failed.
 - · The hostname was not found.
 - · The address was formed incorrectly.
 - · The WPAR did not permit the operation.
 - · The **setpri** subroutine failed.
 - The fopen subroutine failed.
 - · The fstat subroutine failed.
 - The interface is unknown when the daemon looks up the link type.
- The fread subroutine on a trace file failed. 2
- 5 · Socket creation failed.
 - The specified file already exists, but the file is not a trace file.
 - The protocol is not in the /etc/protocols file.
 - The service is not in the /etc/services file.
 - · The daemon failed to load trace extension (netintf).
 - · The daemon failed to unload trace extension.

Examples

9

1. To start the **iptrace** daemon with the System Resource Controller (SRC), enter:

```
startsrc -s iptrace -a "/tmp/nettrace"
```

To stop the iptrace daemon with SRC enter the following:

```
stopsrc -s iptrace
```

2. To record packets coming in and going out to any host on every interface, enter the command in the following format:

```
iptrace /tmp/nettrace
```

The recorded packets are received on and sent from the local host. All packet flow between the local host and all other hosts on any interface is recorded. The trace information is placed into the /tmp/nettrace file.

3. To record packets received on an interface from a specific remote host, enter the command in the following format:

```
iptrace -i en0 -p telnet -s airmail /tmp/telnet.trace
```

The packets to be recorded are received on the en0 interface, from remote host airmail, over the telnet port. The trace information is placed into the /tmp/telnet.trace file.

4. To record packets coming in and going out from a specific remote host, enter the command in the following format:

```
iptrace -i en0 -s airmail -b /tmp/telnet.trace
```

The packets to be recorded are received on the en0 interface, from remote host airmail. The trace information is placed into the /tmp/telnet.trace file.

Related Information

The **ipreport** command, the **tcpdump** command.

The /etc/protocols file format, /etc/services file format.

isC2host Command

Purpose

Determine the C2 status of a system.

Syntax

isC2host [-i | -s]

Description

The isC2host command returns the configuration status of the host machine. If the host has been configured to operate in C2 mode, the command exits with a zero (true) code. If the host has not been configured to operate in C2 mode, the command exits with a non-zero (false) code.

This command may be used in shell scripts where the security status of the host must be known.

The -i option is used to determine the installation status of the system. The C2 status of the system is determined by examining the ODM database, and the exit status indicates whether or not the system was installed in C2 mode.

The -s option is used to initialize AIX in C2 mode and may only be issued by the root user. The C2 status of the system is determined by examining the ODM database. On a system that has not been installed with C2, as indicated by the ODM, this option performs no operation.

Flags

- Determine the C2 installation status of the system.
- Set the C2 status of the system from the ODM.

Subcommands

Exit Status

- When used with no options, the system has been initialized to operate in C2 mode. When used with the -s flag, the system was successfully initialized according to the C2 mode setting defined in the ODM database. When used with the -i flag, the system was installed with C2 enabled.
- 1 When used with no options, the system has not been initialized to operate in C2 mode. When used with the -s flag, the system could not be initialized to operate in the security mode that was defined in the ODM. When used with the -i flag, the system was installed with C2 enabled but is not currently operating in C2 mode.

- When used with the **-s** option, the **isC2host** command was executed by a non-root user. When used with the **-i** option, the system was not installed with C2 enabled.
- The **isC2host** command was executed with an invalid command line option.

Files

/usr/sbin/isC2host

Contains the isC2host command.

Related Information

The chC2admin command, IsC2admin command, mkC2admin command, rmC2admin command.

The sysconfig() subroutine.

The Object Data Manager subsystem.

isCChost Command

Purpose

Determine the Common Criteria enabled status of a system.

Syntax

isCChost [-i | -s]

Description

The **isCChost** command returns the configuration status of the host machine. If the host has been configured to operate in Common Criteria enabled mode, the command exits with a zero (true) code. If the host has not been configured to operate in Common Criteria enabled mode, the command exits with a non-zero (false) code.

This command may be used in shell scripts where the security status of the host must be known.

The -i option is used to determine the installation status of the system. The Common Criteria enabled status of the system is determined by examining the ODM database, and the exit status indicates whether or not the system was installed in Common Criteria enabled mode.

The **-s** option is used to initialize AIX in Common Criteria enabled mode and may only be issued by the root user. The Common Criteria enabled status of the system is determined by examining the ODM database. On a system that has not been installed with Common Criteria enabled, as indicated by the ODM, this option performs no operation.

Flags

- -i Determine the Common Criteria enabled installation status of the system.
- -s Set the Common Criteria enabled status of the system from the ODM.

Subcommands

Exit Status

When used with no options, the system has been initialized to operate in Common Criteria enabled mode. When used with the **-s** flag, the system was successfully initialized according to

- the Common Criteria enabled mode setting defined in the ODM database. When used with the -i flag, the system was installed with Common Criteria enabled enabled.
- 1 When used with no options, the system has not been initialized to operate in Common Criteria enabled mode. When used with the -s flag, the system could not be initialized to operate in the security mode that was defined in the ODM. When used with the -i flag, the system was installed with Common Criteria enabled but is not currently operating in Common Criteria enabled mode.
- When used with the -s option, the isCChost command was executed by a non-root user. When used with the -i option, the system was not installed with Common Criteria enabled.
- 3 The **isCChost** command was executed with an invalid command line option.

Files

/usr/sbin/isCChost

Contains the isCChost command.

Related Information

The chCCadmin command, IsCCadmin command, mkCCadmin command, rmCCadmin command.

The **sysconfig()** subroutine.

The Object Data Manager subsystem.

istat Command

Purpose

Examines i-nodes.

Syntax

istat {FileName | i-nodeNumber Device}

Description

The istat command displays the i-node information for a particular file. You can specify the file either by providing a file or directory name with the FileName parameter or by providing an i-node number with the i-nodeNumber parameter and a device name with the Device parameter. You can specify the Device parameter as either a device name or as a mounted file system name.

If you specify the FileName parameter, the istat command writes the following information about the file:

- · Device where the file resides
- · i-node number of the file, on that device
- · File type, such as normal, directory, and block device
- · File access permissions
- · Name and identification number of the owner and group

Note: The owner and group names for remote files are taken from the local /etc/passwd file.

- · Number of links to the file
- If the i-node is for a normal file, length of the file
- If the i-node is for a device, major and minor device designations
- Date of the last i-node update
- · Date of the last file modification

Date of the last reference to the file

If you specify the *i-nodeNumber* and *Device* parameters, the **istat** command also displays, in hexadecimal values, the block numbers recorded in the i-node.

Note: The *Device* parameter cannot refer to a remote device.

Examples

1. To display the information in the i-node corresponding to the /usr/bin/ksh file, enter:

```
istat /usr/bin/ksh
```

This command displays the i-node information for the /usr/bin/ksh file. The information looks similar to the following:

```
Inode 10360 on device 10/6
                             File
Protection: r-xr-xr-x
Owner: 2(bin) Group: 2(bin)
Link count: 2
              Length 372298 bytes
Last updated: Wed May 13 14:08:13 1992
Last modified: Wed May 13 13:57:00 1992
Last accessed: Sun Jan 31 15:49:23 1993
```

2. To display i-node information by specifying a file i-node number, enter:

```
istat 10360 /dev/hd2
```

This command displays the information contained in the i-node identified by the number 10360 on the /dev/hd2 device. In addition to the information shown in Example 1, this displays:

```
Block pointers (hexadecimal):
                               2a9f
                                     2aa0
     2a9b
          2a9c 2a9d
                        2a9e
```

These numbers are addresses of the disk blocks that make up the /usr/bin/ksh file.

Files

/usr/bin/istat Contains the istat command.

Related Information

The **fsdb** command.

The filesystems file, jfs/filsys.h file.

File systems in Operating system and device management explains file system types, management, structure, and maintenance.

Files in Operating system and device management provides information on working with files.

Directories in Operating system and device management provides an introduction on i-nodes and how they are used by the file system.

j2edlimit Command

Purpose

Manages quota Limits Classes for JFS2 file systems.

Syntax

To edit Quota Limits Classes:

j2edlimit [-e] [-u | -g] Filesystem

To list Quota Limits Classes:

j2edlimit -l [-u | -g] Filesystem

To Set an Existing Limits Class as the Default Limits Class:

j2edlimit -d LimitsClassID [-u | -g] Filesystem

To Assign a User or Group to a Limits Class:

j2edlimit -a LimitsClassID [-u UserName | -g GroupName] Filesystem

Description

Quotas are managed in JFS2 file systems through the use of Limits Classes. Each Limits Class has hard and soft limits for disk space and file, and grace periods for exceeding the soft limits. Individual users and groups may be assigned to a Limits Class and are then subject to the guotas defined by that class. Any user or group not assigned to a class is subject to the quotas defined by the default class (Class ID 0). Quota limits for all users or groups in a particular class can be changed by using i2edlimit to modify the Limits Class, without having to change or duplicate quotas for each user or group. By default, or when used with the -e flag, the j2edlimit command edits the User Limits Classes for the file system specified on the command line. When used with the -q flag, the j2edlimit command edits the Group Limits Classes for the specified file system. The command creates a temporary file that contains the file system's current limits classes, then invokes the vi editor (or the editor specified by the EDITOR environment variable) on the temporary file so that the limits classes can be added and modified. When the editor is exited, the command reads the temporary file and modifies the binary quota files to reflect any changes.

Note: If you specify an editor in the EDITOR environment variable, you must use the full pathname of the editor.

Fields displayed in the temporary file are:

Block Hard Limit

The total amount of 1KB blocks the user or group will be allowed to use, including temporary storage during a quota grace period.

Block Soft Limit

The number of 1KB blocks the user or group will be allowed to use during normal operations.

File Hard Limit

The total number of files the user or group will be allowed to create, including temporary files created during a quota grace period.

File Soft Limit

The number of files the user or group will be allowed to create during normal operations.

Amount of time a user can exceed the Block Soft Limit before it becomes enforced as a hard limit.

File Grace Period

Amount of time a user can exceed the File Soft Limit before it becomes enforced as a hard limit.

Notes:

- 1. A hard limit with a value of 1 indicates that no allocations are permitted. A soft limit with a value of 1, in conjunction with a hard limit with a value of 0, indicates that allocations are permitted only on a temporary basis. Hard or soft limits can be specified in kilobytes (the default), megabytes, or gigabytes.
- 2. A user can exceed established soft limits for the length of the corresponding grace period. Upon expiration of the grace period, the soft limit is enforced as a hard limit. The grace period can be specified in days, hours, mnutes, or seconds. A value of 0 indicates that the default grace period is imposed; a value of 1 second indicates that no grace period is granted.
- 3. After changing a grace period using the **i2edlimit** command, users who have already reached their old grace period must reduce their file system usage to a level below their soft limits in order to use the new grace period. In the future, when these users exceed their soft limits, the new grace period will be in effect.

Flags

- Assigns the User or Group specified by the -u or -g flag to the indicated Limits Class in the file system -a specified on the command line.
- -d Sets the indicated Limits Class as the default for the file system specified on the command line. By default, or with the -u flag, the default is set for User quotas. With the -g flag, the default is set for Group quotas.
- Edits the Limits Classes for the file system specified on the command line (this is the default operation for -е the j2edlimit command). By default, or with the -u flag, the default is set for User quotas. With the -g flag, the default is set for Group quotas.
- When used with the -d. -I or optional -e flag, performs the peration on the Group Limits Classes for the file -g system specified on the command line. When used with the -a flag, assigns the associated Group to the specified Limits Class.
 - Note: If the parameter contains all numbers then it will be treated as a Group ID, and the Group ID will be assigned to the Limits Class.
- Lists the Limits Classes for the file system specified on the command line. By default, or with the -u flag, -1 User limits classes are listed. With the -g flag, Group limits classes are listed. The format of the listing is the same as found in the temporary file when editing Limits Classes.
- When used with the -d, -I or optional -e flag, performs the operation on the User Limits Classes for the file -u system specified on the command line. When used with the -a flag, assigns the associated User to the specified Limits Class.
 - Note: If the parameter contains all numbers then it will be treated as a User ID, and the User ID will be assigned to the Limits Class.

Security

Access Control:

Only the root user can execute this command.

Examples

1. To edit User Limits Classes for the /home file system:

.i2edlimit /home

2. To list Group Limits Classes for the /home file system:

j2edlimit -l -g /home

3. To set User Limits Class ID 2 as the default for the **/foo** file system:

j2edlimit -d2 /foo

4. To assign user markg to Limits Class ID 1 in the /home file system:

j2edlimit -a 1 -u markg /home

Files

Contains usage and Limits information for users. quota.user quota.group Contains usage and Limits information for groups.

/etc/filesystems Contains file system names and locations.

Related Information

The quota command, quotacheck command quotaon, quotaoff command, and repquota command.

The Disk quota system overview and Setting up the disk quota system in the Security.

jobs Command

Purpose

Displays status of jobs in the current session.

Syntax

jobs [-I | -n | -p] [JobID ...]

Description

The jobs command displays the status of jobs started in the current shell environment. If no specific job is specified with the JobID parameter, status information for all active jobs is displayed. If a job termination is reported, the shell removes that job's process ID from the list of those known by the current shell environment.

The /usr/bin/jobs command does not work when operating in its own command execution environment, because that environment does not have applicable jobs to manipulate. For this reason, the jobs command is implemented as a Korn shell or POSIX shell regular built-in command.

If the -p flag is specified, output consists of one line for each process ID. If no flags are specified, standard output is a series of lines with the following fields:

iob-number

Indicates the process group number to use with the wait, fg, bg, and kill commands. When used with these commands, prefix the job number with a % (percent sign).

current

A + (plus sign) identifies the job that will be used as a default for the fq or bq commands. This job ID can also be specified using the %+ (percent sign, plus) or %% (double percent sign).

A - (minus sign) identifies the job that becomes the default if the current default job exits. This job ID can also be specified using %- (percent sign, minus).

For other jobs, the current field is a space character. Only one job can be identified with a +, and only one job can be identified with a -. If there is a single suspended job, that will be the current job. If there are at least two suspended jobs, then the previous job is also suspended.

Displays one of the following values (in the POSIX locale): state

Running

Indicates that the job has not been suspended by a signal and has not exited.

Indicates that the job completed and returned exit status 0.

Done (code)

Indicates that the job completed normally and that it exited with the specified non-zero exit status code. This code is expressed as a decimal number.

Stopped

Indicates that the job was suspended.

Stopped (SIGTSTP)

Indicates that the **SIGTSTP** signal suspended the job.

Stopped (SIGSTOP)

Indicates that the **SIGSTOP** signal suspended the job.

Stopped (SIGTTIN)

Indicates that the **SIGTTIN** signal suspended the job.

Stopped (SIGTTOU)

Indicates that the **SIGTTOU** signal suspended the job.

command The associated command that was given to the shell.

If the -I flag is specified, a field containing the process group ID is inserted before the state field. Also, more processes in a process group may be output on separate lines, using only the job-number and command fields.

Flags

- (lowercase L) Provides more information about each job listed. This information includes the job number, -1 current job, process group ID, state, and the command that initiated the job.
- Displays only jobs that have stopped or exited since last notified. -n
- -p Displays the process IDs for the process group leaders for the selected jobs.

By default the jobs command displays the status of all stopped jobs, all running background jobs, and all jobs whose status has changed but not been reported by the shell.

Exit Status

The following exit values are returned:

Successful completion. >0 An error occurred.

Examples

1. To display the status of jobs in the current environment, enter:

```
jobs -1
```

The screen displays a report similar to the following output:

```
+[4] 139 Running
                       CC - C foo c&
-[3] 465 Stopped
                        mail morris
[2] 687 Done(1)
                        foo.bar&
```

2. To display the process ID for the job whose name begins with "m," enter:

```
jobs -p %m
```

Using the jobs reported in Example 1, the screen displays the following process ID: 465

Files

/usr/bin/ksh Contains the Korn shell jobs built-in command.

/usr/bin/jobs Contains the jobs command.

Related Information

The **bg** command, **csh** command, **fg** command, **kill** command, **ksh** command, **wait** command.

join Command

Purpose

Joins the data fields of two files.

Syntax

```
join [ -a FileNumber | -v FileNumber ] [ -e String ] [ -o List ] [ -t Character ] [ -1 Field ] [
-2 Field ] File1 File2
```

Description

The join command reads the files specified by the File1 and File2 parameters, joins lines in the files according to the flags, and writes the results to standard output. The File1 and File2 parameters must be text files. Both File1 and File2 must be sorted in the collating sequence of sort -b on the field that they are being joined by before invoking the join command.

One line appears in the output for each identical join field appearing in both files. The join field is the field in the input files examined by the join command to determine what will be included in the output. The output line consists of the join field, the rest of the line from the file specified by the File1 parameter, and the rest of the line from the file specified by the File2 parameter. Specify standard input in place of either the File1 or File2 parameter by substituting a - (dash) as the file name. Both input files cannot be specified with a - (dash).

Fields are usually separated by a space, a tab character, or a new-line character. In this case, the join command treats consecutive separators as one and discards leading separators.

Flags

-1 Field	Joins the two files using the field specified by the Field variable in the File1 input file. The
	value of the Field variable must be a positive decimal integer.
-2 Field	Joins the two files using the field specified by the Field variable in the File2 input file. The
	value of the Field variable must be a positive decimal integer.
-a FileNumber	Produces an output line for each line in the file specified by the FileNumber variable whose
	join fields do not match any line in the other input file. The output lines are produced in
	addition to the default output. The value of the FileNumber variable must be either 1 or 2,
	corresponding to the files specified by the File1 and File2 parameters, respectively. If this
	flag is specified with the -v flag, this flag is ignored.
-e String	Replaces empty output fields with the string specified by the String variable.

-o List

Constructs an output line to comprise the fields specified in the List variable. One of the following forms applies to the List variable:

FileNumber.Field

Where FileNumber is a file number and Field is a decimal-integer field number. Separate multiple fields with a, (comma) or space characters with quotation marks around the multiple fields.

0 (zero)

Represents the join field. The -o 0 flag essentially selects the union of the join

-t Character

Uses the character specified by the Character parameter as the field separator character in the input and the output. Every appearance of the character in a line is significant. The default separator is a space. With default field separation, the collating sequence is that of the sort -b command. If you specify -t, the sequence is that of a plain sort. To specify a tab character, enclose it in single quotation marks.

-v FileNumber

Produces an output line for each line in the file specified by the FileNumber variable whose join fields do not match any line in the other input file. Default output is not produced. The value of the FileNumber variable must be either 1 or 2, corresponding to the files specified by File1 and File2 parameters, respectively. If this flag is specified with the -a flag, the -a flag is ignored.

Exit Status

This command returns the following exit values:

- 0 Successful completion.
- >0 An error occurred.

Examples

Note: The vertical alignment shown in the following examples might not be consistent with your output.

1. To perform a simple join operation on two files where the first fields are the same, type:

join phonedir names

If the phonedir file contains the following names:

Adams A. 555-6235 Dickerson B. 555-1842 Erwin G. 555-1234 Jackson J. 555-0256 Lewis B. 555-3237 Norwood M. 555-5341 Smartt D. 555-1540 Wright M. 555-1234 Xandy G. 555-5015

and the names file contains these names and department numbers:

Erwin Dept. 389 Frost Dept. 217 Nicholson Dept. 311 Norwood Dept. 454 Wright Dept. 520 Dept. 999 Xandy

the **join** command displays:

Erwin G.	555-1234	Dept. 389
Norwood M.	555-5341	Dept. 454
Wright M.	555-1234	Dept. 520
Xandy G.	555-5015	Dent. 999

Each line consists of the join field (the last name), followed by the rest of the line found in the phonedir file and the rest of the line in the names file.

2. To display unmatched lines with the **join** command, type:

```
join -a2 phonedir names
```

If the phonedir and names files are the same as in Example 1, the join command displays:

Erwin G.	555-1234	Dept. 389
Frost		Dept. 217
Nicholson		Dept. 311
Norwood M.	555-5341	Dept. 454
Wright M.	555-1234	Dept. 520
Xandy G.	555-5015	Dept. 999

This command performs the same join operation as in Example 1, and also lists the lines of names that have no match in the phonedir file. The names Frost and Nicholson are included in the listing, even though they do not have entries in the phonedir file.

3. To display selected fields with the **join** command, type:

```
join -o 2.3,2.1,1.2,1.3 phonedir names
```

This displays the following fields in the order given:

Field 3 of names	Department number
Field 1 of names	Last name
Field 2 of phonedir	First initial
Field 3 of phonedir	Telephone number

If the phonedir file and names files are the same as in Example 1, the join command displays:

389	Erwin G.	555-1234
454	Norwood M.	555-5341
520	Wright M.	555-1234
999	Xandy G.	555-5015

4. To perform the join operation on a field other than the first, type:

```
sort -b +2 -3 phonedir | join -1 3 - numbers
```

This command combines the lines in the phonedir and numbers files, comparing the third field of the phonedir file to the first field of the numbers file.

First, this command sorts the phonedin file by the third field, because both files must be sorted by their join fields. The output of the sort command is then piped to the join command. The - (dash) by itself causes the join command to use this output as its first file. The -1 3 flag defines the third field of the sorted phonedir file as the join field. This is compared to the first field of numbers because its join field is not specified with a -2 flag.

If the numbers file contains:

```
555-0256
555-1234
555-5555
555-7358
```

then this command displays the names listed in the phonedir file or each telephone number:

```
555-0256
                Jackson J.
555-1234
                Erwin G.
555-1234
                Wright M.
```

Note that the join command lists all the matches for a given field. In this case, the join command lists both Erwin G. and Wright M. as having the telephone number 555-1234. The number 555-5555 is not listed because it does not appear in the phonedir file.

Files

/usr/bin/join Contains the join command. /usr/lib/nls/loc/*.src Contains collation information.

Related Information

The awk command, comm command, cut command, paste command, sort command.

Files in Operating system and device management.

Input and output redirection in *Operating system and device management*.

National Language Support Overview for Programming in AIX 5L Version 5.3 National Language Support Guide and Reference.

joinvg Command

Purpose

Joins a snapshot volume group back into its original volume group.

Syntax

joinvg [-f] vgname

Description

Joins a snapshot volume group that was created with the **splitvg** command back into its original volume group. The snapshot volume group is deleted and the disks reactivated in the original volume group. Any stale partitions will be resynchronized by a background process.

Flags

-f vgname Forces the join when disks in the snapshot volume group are missing or removed. The

mirror copy on the missing or removed disks will be removed from the original volume group. The vgname parameter specifies the original volume group name with the splitvg

command.

Security

Access Control: You must have root authority to run this command.

Examples

To join the original volume group, **testvg**, with the snapshot volume group **snapvg**, enter the following command:

joinvg testvg

Files

/usr/sbin Directory where the joinvg command resides.

Related Information

The splitvg and recreatevg commands.

kdb Command

Purpose

Allows for the examining of a system dump or a running kernel.

Syntax

kdb -h

```
kdb [ -c CommandFile ] [ -cp ] [ -i HeaderFile ] [ -l ] [ -script ] -w -u KernelFile
```

kdb [-c CommandFile] [-cp] [-i HeaderFile] [-l] [-script] [-v] [SystemImageFile [KernelFile [KernelModule ...]]]

kdb [-c CommandFile] [-cp] [-i HeaderFile] [-l] [-script] [-v] [-m SystemImageFile] [-u KernelFile] [-k KernelModule]

Description

The kdb command is an interactive utility for examining an operating system image or the running kernel. The kdb command interprets and formats control structures in the system and provides miscellaneous functions for examining a dump.

Root permissions are required to use the kdb command on the active system because the /dev/pmem special file is used. To run the kdb command on the active system, type the following: kdb

Note: Stack tracing of the current process on a running system does not work.

To invoke the kdb command on a system image file, type the following: kdb *SystemImageFile*

When kdb starts, it looks for a .kdbinit file in the user's home directory and in the current working directory. If a .kdbinit file exists in either of these locations, kdb will execute all of the commands inside the file as if they were entered at the interactive kdb prompt. If a .kdbinit file exists in both of these locations, the file in the home directory will be processed first, followed by the file in the current working directory (unless the current directory is the home directory, in which case the file is processed only once).

Flags

-c CommandFile	Specifies a different name for the startup script file. If this option is used, then kdb searches for the <i>CommandFile</i> parameter in the home and current directories instead of the .kdbinit file.
-ср	Causes kdb to print out each command in the startup script files as the command is run. This can be used to help debug the .kdbinit files, or any other file specified with the -c flag. Each command is printed with a plus (+) sign in front of it.
-h	Displays a short help message in regard to command line usage and a brief listing of the available command line options.
-i HeaderFile	Makes all of the C structures defined in the <i>HeaderFile</i> parameter available for use with the kdb print subcommand. This option requires a C compiler to be installed on the system. If the <i>HeaderFile</i> variable needs additional .h files to compile, these might have to be specified with separate -i options as well.

-k Module Instructs kdb to use the specified Module parameter as an additional kernel module for

resolving symbol definitions not found in the kernel itself. Using this option is equivalent to

specifying the kernel module with the KernelModule parameter.

-1 Disables the inline pager (that is, the more (^C to quit) ? prompt) in kdb. In this case, the

set scroll subcommand in kdb has no effect, and the inline pager is always disabled

regardless of the scroll setting.

Instructs kdb to use the specified Image parameter as the system image file. Using this -m Image

option is equivalent to specifying the system image file with the SystemImageFile

Disables the inline pager (that is, the more (^C to quit) ? prompt) and disables printing of -script

most status information when kdb starts. This option facilitates parsing of the output from

the kdb command by scripts and other programs that act as a front end for kdb.

Instructs kdb to use the specified Kernel as the kernel file for resolving symbol definitions. -u Kernel

Using this option is equivalent to specifying the kernel with the KernelFile parameter.

Displays a list of all Component Dump Tables (CDTs) in the system dump file when kdb

starts. CDTs list the memory regions that are actually included in the system dump. If kdb is

used on a live system, this option is ignored.

Examines a kernel file directly instead of a system image. All kdb subcommands which -w

normally display memory locations from the system image file will instead read data directly

from KernelFile. Subcommands which write memory are not available.

Parameters

Specifies the AIX kernel that kdb will use to resolve kernel symbol definitions. A KernelFile

> kernel file must be available. When examining a system dump, it is imperative that the kernel file be the same as the kernel that was used to take the system dump.

The default value is /unix.

KernelModule Specifies the file names of any additional kernel modules that kdb uses to resolve

symbol definitions not found in the kernel file itself.

SystemImageFile Specifies the file that contains the system image. The value can indicate a system

dump, the name of a dump device, or the /dev/pmem special file. The default value

is /dev/pmem.

Examples

The following examples demonstrate invocation options for the **kdb** command:

1. To invoke the **kdb** command with the default system image and kernel image files, type the following: kdb

The **kdb** program returns a (0)> prompt and waits for the entry of a subcommand.

2. To invoke the **kdb** command using a dump file named /var/adm/ras/vmcore.0 and the UNIX® kernel file named /unix, type the following:

kdb /var/adm/ras/vmcore.0 /unix

The **kdb** program returns a (0)> prompt and waits for the entry of a subcommand.

Files

/usr/sbin/kdb Contains the kdb command. /dev/pmem Default system image file. /unix Default kernel file.

Related Information

AIX 5L Version 5.3 KDB Kernel Debugger and kdb command

kdestroy Command

Purpose

Destroys a Kerberos credentials cache.

Syntax

kdestroy [-q] [-c cache_name | -e expired_time]

Description

The kdestroy command deletes a Kerberos credentials cache file.

If you specify the **-e** flag, the command checks all of the credentials cache files in the default cache directory (/var/krb5/security/creds) and deletes any file which contains only expired tickets, provided the tickets have been expired for the specified *expired time*.

Flags

-c cache_name

Specifies the name of the credentials cache you want to destroy. The default credentials cache is destroyed if you do not specify a command flag.

If the KRB5CCNAME environment variable is set, its value is used to name the default credentials (ticket) cache.

This flag is mutually exclusive with the -e flag.

-e expired_time

Specifies that all credentials cache files containing expired tickets be deleted if the tickets have been expired at least as long as the *expired_time* value.

The expired_time is expressed as nwndnhnmns, where:

n represents a numberw represents weeks

d represents days

h represents hours

m represents minutes

s represents seconds

You must specify the *expired_time* components in this order but you can omit any component. For example, 4h5m represents four hours and 5 minutes and 1w2h represents 1 week and 2 hours. If you only specify a number, the default is hours.

Suppress the beep when **kdestroy** fails to destroy the ticket.

Security

-q

To delete a credentials cache, the user must be the owner of the file or must be a root (uid 0) user.

Examples

- To delete the default credentials cache for the user, type:
 Ideather
- 2. To delete all credentials cache with expired tickets older than one day, type: kdestroy -e 1d

Files

/usr/krb5/bin/kdestroy /var/krb5/security/creds/krb5cc_[uid]

default credentials cache ([uid] is the UID of the user.)

Related Information

The kinit command, klist command, and env command.

keyadd Command

Purpose

keyadd retrieves objects from the source keystore and adds them to the destination keystore.

Syntax

keyadd [-S servicename] -I label -s source keystore [-d destination keystore] [username]

Description

The keyadd command retrieves the objects named by label from the source keystore and adds them to the destination keystore. In a keystore, a user may have the private key, public key and the certificate stored using the same label. All objects matching a label are copied regardless of the object type. If an object with the same label already exists in the destination keystore, the command returns an error. This forces the user to explicitly remove an existing object instead of blindly destroying it.

Attention: Generally, there is no way to recover a destroyed object.

The -S option specifies which end-entity services and libraries to use while adding the objects from the keystore. Available services are defined in /usr/lib/security/pki/ca.cfg. When invoked without -S, keydelete will use the default service, which is local. It is an error to specify a servicename which does not have an entry in the /usr/lib/security/ pki/ca.cfg file.

The -I option must be specified. This label uniquely identifies an object in the keystore to be copied. The -s option must also be specified.

If the -d option is not given, the username's default keystore file will be used as the destination keystore The user's default keystore location is /var/pki/security/keys/<username>.

If no username is given, the currend user's username will be used. The user will be prompted for the password of the destination keystore and the source keystore. If the destination keystore does not exist, one will be created and the user will be asked to enter the destination keystore password again for confirmation.

Flags

-S servicename Specifies which service module to use.

-I label Specifies the label associated with the key to be added.

-s source_keystore Species the location of the source keystore.

-d destination_keystore Specifies the location of the destination keystore.

Exit Status

0 The command completed successfully.

>0 An error occurred.

Security

This is a setuid command. In order to list the contents of a keystore the user must know the password of the private keystore.

Root and invokers belonging to group security are allowed to list anybody's keystore. However, they can only successfully complete this operation if they know the password to the keystore. A non-privileged user is only allowed to list the keystore that he owns.

Audit

This command records the following event information:

KEY Add <username>

Examples

To copy a keystore object labeled as label from /var/pki/security/keys/src.keystore to /var/pki/security/keys/dst.keystore, enter:

\$ keyadd -s /var/pki/security/keys/src.keystore -d /var/pki/ security/keys/dst.keystore -1 label pkitest

Files

/usr/lib/security/pki/policy.cfg

/usr/lib/security/pki/ca.cfg

Related Information

The certadd, certcreate, certdelete, certget, certlink, certlist, certrevoke, certverify, keydelete, keylist, keypasswd and mksecpki commands.

keycomp Command

Purpose

Compiles a keyboard mapping file into an input method keymap file.

Syntax

keycomp < Infile > Outfile

Description

The **keycomp** command reads a textual description of the keyboard from standard input and produces a binary file that maps the keys to standard output. The binary file is used by the Input Method to translate key strokes into character strings.

You can bind characters and strings to keys on a keyboard with specified combinations of modifier keys called keyboard states, or you can specify particular key and state combinations as unbound (return nothing). All input keys are represented by keysyms, which stand for the key symbols that are usually used in the AlXwindows environment to represent keyboard input.

Any combination of modifier keys is possible when you press a key on the keyboard, but usually the keys are mapped into a smaller set of states. This state mapping can be specified.

Keycomp Source File

The input file used by the keycomp command consists of one or more lines. The items on the line are separated by a space. Each line begins with a keysym or a hexadecimal value for a keysym. The hexadecimal value represents keyboard input in the AlXwindows environment. Items following the keysym represent the binding for a particular combination of the Ctrl, Alt, Shift, Lock, and Alt Graphic keys.

An item can be one of the following:

- Character surrounded by single quotation marks
- · String surrounded by double quotation marks
- Keysym allowing mapping to other keysyms
- · U indicating that the entry is unbound

Hexadecimal (\xXX), octal (\oOOO), and decimal (\dDDD) notations of a byte can be contained in character and string items.

Keyboard States

Modifier keys (Shift, Lock, Ctrl, Alt, and Alt Graphics keys) change the state of the keyboard. They are used to select one item from a line corresponding to the input keysym. A value that is a combination of bits, each bit corresponding to a modifier key, indicates the state of a keyboard. The modifier keys increase in significance in the following order: Shift, Lock, Ctrl, Alt, and Alt Graphic modifier keys.

The bit combination or state value of a keyboard is mapped to one item of a line. The mapping is defined by the line beginning with the %M control, which can contain only numbers. The first number after the %M control is the item number. The numbers that follow the first number represent keyboard states, and they are all mapped to the item. See "Examples."

Flags

<InFile Specifies a source file to be compiled by the **keycomp** command.

>OutFile Specifies the name of the keymap file to be created.

Examples

1. The following is an example of a line for XK a keysym input:

```
XK a'a' XK A XK A XK a '\x01' U "hello"
```

A, (comma) can, but need not, follow each item. Regardless of whether a comma follows an item, a space or tab must separate the items.

Blank lines and lines beginning with the # character, except control statements, are ignored. All text between the # and the following line is ignored unless the # is part of a string enclosed in single or double quotation marks. Therefore, you can place comments at the end of a line that contains only a single item.

2. The following line shows that the keyboard states Ctrl, Ctrl+Shift, and Ctrl+Shift+Lock are all mapped to the third item:

%M 3 4 5 7

Files

/usr/include/x11/keysymdef.h /usr/include/x11/aix_keysym.h /usr/bin/keycomp

Contains standard keysym definitions. Contains unique keysym definitions. Contains the keycomp command.

Contains imkeymap source information. Maps a keysym/modifier to a string.

Related Information

The IMInitializeKeymap subroutine.

The Input Method Overview in AIX 5L Version 5.3 National Language Support Guide and Reference.

The National Language Support Overview in AIX 5L Version 5.3 National Language Support Guide and Reference.

keydelete Command

Purpose

Deletes an object (key, certificate, etc) identified by the label from a keystore. If the label is ALL, all objects are deleted.

Syntax

keydelete [-S ServiceName] -I Label [-p PrivateKeystore] [UserName]

Description

The **keydelete** command deletes an object (key, certificate, etc) identified by the *Label*. If the *Label* is ALL, all objects are deleted. The **-S** flag specifies which end-entity services and libraries to use while deleting the objects from the keystore. Available services are defined in **/usr/lib/security/pki/ca.cfg**. When invoked without **-S**, **keydelete** uses the default service, which is **local**. An error is returned if a *ServiceName* is specified which does not have an entry in the **/usr/ lib/security/pki/ca.cfg** file.

The -I flag must be specified. The *Label* is a variable length text string that is used to map a key in the keystore to the certificate which contains the matching public key. If the *Label* is ALL, all the objects in the keystore are deleted.

If the **-p** flag is not given, the username's default keystore file is used. The user's default keystore location is **/var/pki/security/keys/**<*UserName*>.

If no *UserName* is given, the current user's user name is used. The user is prompted for the password of the keystore.

Flags

-S ServiceName Specifies which service module to use.

-I Label Specifies the label associated with the key to be added.
 -p PrivateKeystore Species the location of the source destination keystore.

Arguments

username - Specifies the user whose key is going to be deleted.

Security

This is a privileged (set-UID root) command.

In order to list the contents of a keystore, the user must know the password of the private keystore.

root and invokers belonging to group security are allowed to list anybody's keystore. However, they can only successfully complete this operation if they know the password to the keystore. A non-privileged user is only allowed to list the keystore that he owns.

Audit

This command records the following event information:

KEY Delete < UserName>

Examples

1. To delete a keystore object with a label **signcert** from the invoker's default keystore, type:

```
keydelete -l signcert
```

2. To delete all the objects from the invoker's default keystore, type:

```
kevdelete -1 ALL
```

3. To delete a keystore object with a label signcert from the keystore /home/bob/ bob.keystore, type: keydelete -p /home/bob/bob.keystore -l signcert

Files

/usr/lib/security/pki/ca.cfg

Related Information

The keyadd, keylist, and keypasswd commands.

keyenvoy Command

Purpose

Acts as an intermediary between user processes and the keyserv daemon.

Syntax

/usr/sbin/keyenvoy

Description

The **keyenvoy** command acts as an intermediary by some Remote Procedure Call (RPC) programs between their user processes and the keyserv daemon. An intermediary is necessary because the keyserv daemon talks only to root processes. This program cannot be run interactively.

Files

/usr/sbin/keyenvoy

Contains the keyenvoy command.

Related Information

The keyserv daemon.

Network File System (NFS) Overview for System Management in Networks and communication management.

Network Information Services (NIS) Overview for System Management in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide.

NIS Reference.

keylist Command

Purpose

keylist lists the keystore labels in a private keystore.

Syntax

keylist [-S servicename] [-v | -c] [-p privatekeystore] [username]

Description

The **keylist** command lists the keystore labels in a private keystore. The **-S** option specifies which end-entity services and libraries to use while listing the labels in the keystore. Available services are defined in <code>/usr/lib/security/pki/ca.cfg</code>. When invoked without **-S**, <code>keylist</code> will use the default service, which is <code>local</code>. It is an error to specify a servicename which does not have an entry in the <code>/usr/lib/security/pki/ca.cfg</code> file. The user optionally may provide the location of the private keystore. If not given, the default location will be used. If the **-c** option is given, the type of the keystore object corresponding to the label will be specified by one letter symbol. The following are the symbols denoting the keystore object types:

P = Public Key

p = Private Key

T = Trusted Key

S = Secret Key

C = Certificate

t = Trusted Certificate

U = Useful Certificate

If the **-v** option is used, the type of the object for a label will be given in non-abbreviated version (for example, Public Key, Secret Key).

If required, the user will be prompted for the password of the underlying service keystore.

Flags

-S servicename Specifies which service module to use.-p privatekeystore Specifies the location of the keystore.

-v Specifies that the output is in verbose mode.

-c Specifies a concise output.

Arguments

username Specifies the AIX user whose key labels is going to be gueried.

Exit Status

Successful completion.

>0 An error occured.

Security

This is a privileged (set-UID root) command.

In order to list the contents of a keystore the user must know the password of the private keystore.

Root and invokers belonging to group security are allowed to list anybody's keystore. However, they can only successfully complete this operation if they have the knowledge of the password to the keystore.

A non-privileged user is only allowed to list the keystore that he owns.

Audit

This command records the following event information:

KEY_List <username>

Examples

1. To list the labels in keystore /var/security/pki/keys/bob, enter:

```
$ keylist -c -p /var/pki/security/keys/bob bob
PpC label1
PpC label2
```

2. To list labels/objects in verbose mode, enter:

```
$ keylist -v -p /var/pki/security/keys/bob bob
```

Files

/usr/lib/security/pki/policy.cfg

/usr/lib/security/pki/ca.cfg

Related Information

The certadd, certcreate, certdelete, certget, certlink, certlist, certrevoke, certverify, keyadd, keydelete, keypasswd and mksecpki commands.

keylogin Command

Purpose

Decrypts and stores the user's secret key.

Syntax

keylogin [-r]

Description

The **keylogin** command prompts users for their passwords. Then, the **keylogin** program decrypts the user's secret key, which is stored in the **/etc/publickey** file. The decrypted key is then stored by the local **keyserv** daemon to be used by any secure Remote Procedure Call (RPC) service, such as the Network File System (NFS).

The decrypted key given to the local **keyserv** daemon may eventually reach a time out and become invalid for that particular login session. The user can use the **keylogin** command again to refresh the key held by the **keyserv** daemon.

Flags

Writes unencrpted secret key into key file. The -r flag is used with the keylogin command for the root user principal and to store the root user's key in /etc/.rootkey on a host. This allows processes running as superuser to issue authenticated requests without explicitly executing the keylogin command as superuser at system startup time.

Files

/etc/publickey

Contains public or secret keys for NIS maps.

Related Information

The **chkey** command, **newkey** command.

The keyserv daemon.

How to Export a File System Using Secure NFS, How to Mount a File System Using Secure NFS in Security.

List of NIS Commands.

Network File System (NFS) Overview for System Management in Operating system and device management.

Network Information Services (NIS) Overview for System Management in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide.

keylogout Command

Purpose

Deletes stored secret key.

Syntax

keylogout [-f]

Description

The **keylogout** command deletes the key stored by the key server process **keyserv**. Further access to the key is revoked; however, current session keys may remain valid until they expire or are refreshed.

Deleting the keys stored by keyserv will cause any background jobs or scheduled jobs that need secure RPC services to fail. Since only one copy of the key is kept on a machine, do not place a call to this command in your logout file since it will affect other sessions on the same machine.

Flags

Forces keylogout to delete the secret key for the superuser. By default, keylogout by the superuser is disallowed because it would break all RPC services, such as NFS, that are started by the superuser.

Related Information

The at command, chkey command, login command, keylogin command, newkey command.

The keyserv daemon.

keypasswd Command

Purpose

keypasswd manages the passwords which are used to access a user's private keystore.

Syntax

keypasswd [-S servicename] [-p privatekeystore | -k username]

Description

The **keypasswd** command allows a user to change the password of a private keystore. The user will be asked to enter the old and new password of the keystore. The **-S** option specifies which end-entity services and libraries to use while changing the password. Available services are defined in the **/usr/lib/security/pki/ca.cfg** file. When invoked without **-S**, **keypasswd** will use the **local** service. You will get an error if you specify a servicename which does not have an entry in the **/usr/lib/security/pki/ca.cfg** file. The **-p** option specifies the private keystore for which the password is going to be changed. The **-k** option specifies the user's default private keystore. You will get an error if you specify both the **-k** and **-p** options.

Flags

-S servicename Specifies which service module to use.

-p privatekeystore Specifies the private keystore whose password is going to be changed.

-k Specifies that the keystore to be used is that of username.

Security

This is a privileged (set-UID root) command.

To change the password of a keystore one must know the password of the keystore.

Root and invokers belonging to group security are allowed to change the password of any keystore as long as they know the password of the keystore. A non-privileged user is allowed to change only the keystore file that they own.

Audit

This command records the following event information:

KEY_Password < username>

Examples

- 1. To change the password of the default private keystore that is owned by Bob, enter:
 - \$ keypasswd

where the invoker is Bob.

- 2. To change the password of any other private keystore, enter:
 - \$ keypasswd -p bob.keystore

Files

/usr/lib/security/ca.cfg

/usr/lib/security/policy.cfg

Related Information

The certadd, certcreate, certdelete, certget, certlink, certlist, certrevoke, certverify, keyadd, keydelete, keylist, and mksecpki commands.

keyserv Daemon

Purpose

Stores public and private keys.

Syntax

/usr/sbin/keyserv [-n]

Description

The **keyserv** daemon stores the private encryption keys of each user logged into the system. When a user types in a password during a keylogin, the secret key is decrypted. The decrypted key is then stored by the keyserv daemon. These decrypted keys enable the user to access secure network services such as secure Network File System (NFS).

When the **keyserv** daemon starts, it reads the key for the root directory from the **/etc/.rootkey** file. This daemon keeps the secure network services operating normally. For instance, after a power failure, when the system restarts itself, it gets the key for the root directory from the /etc/.rootkey file.

Flags

Prevents the keyserv daemon from reading the key for the root directory from the /etc/.rootkey file. Instead, the keyserv daemon prompts the user for the password to decrypt the root directory's key stored in the network information service map and then stores the decrypted key in the /etc/.rootkey file for future use. This option is useful if the /etc/.rootkey file ever goes out of date or is corrupted.

Examples

1. To start the **keyserv** daemon enabling the system to get the key for the root directory from the /etc/.rootkey file, enter:

/usr/sbin/keyserv

2. A System Resource Controller (SRC) command can also enable the system to get the key for the root directory from the /etc/.rootkey file as follows:

```
startsrc -s keyserv
```

This command sequence starts a script that contains the keyserv daemon.

3. To prevent the **keyserv** daemon from reading the key for the root directory from the **/etc/rootkey** file, enter:

```
chssys -s keyserv -a '-n'
```

This command passes the **-n** argument to the **keyserv** daemon if SRC is used to start the daemon.

Files

/etc/.rootkey

Stores the encrypted key for the root directory.

Related Information

The chssys command, keyenvoy command, startsrc command.

How to Export a File System Using Secure NFS, How to Mount a File System Using Secure NFS in Security.

Network File System in Networks and communication management.

Network Information Services (NIS) Overview for System Management in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide.

NIS Reference.

System Resource Controller in Operating system and device management.

kill Command

Purpose

Sends a signal to running processes.

Syntax

To Send Signal to Processes

```
kill [ -s { SignalName | SignalNumber } ] ProcessID ...
kill [ - SignalName | - SignalNumber ] ProcessID ...
```

To List Signal Names

kill -I [ExitStatus]

Description

The kill command sends a signal (by default, the SIGTERM signal) to a running process. This default action normally stops processes. If you want to stop a process, specify the process ID (PID) in the ProcessID variable. The shell reports the PID of each process that is running in the background (unless you start more than one process in a pipeline, in which case the shell reports the number of the last process). You can also use the **ps** command to find the process ID number of commands.

A root user can stop any process with the kill command. If you are not a root user, you must have initiated the process you want to stop.

SignalName is recognized in a case-independent fashion, without the SIG prefix.

If the specified SignalNumber is 0, the kill command checks the validity of the specified PID.

Flags

-s{SignalName | SignalNumber}

Specifies the signal as a signal number or a signal name, such as -9 or KILL for the SIGKILL signal.

-SignalName -SignalNumber Specifies a signal name, such as SIGHUP. Specifies a signal number.

ProcessID

Note: To specify the negative PID with the default signal in this syntax, you must specify - - as a signal. Otherwise the first operand is interpreted as a SignalNumber.

Specifies a decimal integer representing a process or process group to be signaled. If PID is a positive value, the kill command sends the process whose process ID is equal to the PID. If the PID value is 0, the kill command sends the signal to all processes having a process group ID equal to the process group ID of the sender. The signal is not sent to processes with a PID of 0 or 1. If the PID is -1, the kill command sends the signal to all processes owned by the effective user of the sender. The signal is not sent to processes with a PID of 0 or 1. If it is a negative number but not -1, the kill command sends the signal to all processes that have a process group ID equal to the absolute value of

-1 -IExitStatus Lists all signal names supported by the implementation

Lists signal names stripped of the common SIG prefix. If ExitStatus is an decimal integer value, the signal name corresponding to that signal is displayed. If ExitStatus is a value of the exit status corresponding to a process that was terminated by a signal, the signal name corresponding to the signal that terminated the process is displayed.

Exit Status

This command returns the following exit values:

At least one matching process was found for each ProcessID operand, and the specified signal was successfully processed for at least one matching process.

An error occurred. >0

Examples

1. To stop a given process, enter:

kill 1095

This stops process 1095 by sending it the default SIGTERM signal. Note that process 1095 might not actually stop if it has made special arrangements to ignore or override the SIGTERM signal.

2. To stop several processes that ignore the default signal, enter:

kill -kill 2098 1569

This sends signal 9, the SIGKILL signal, to processes 2098 and 1569. The SIGKILL signal is a special signal that normally cannot be ignored or overridden.

3. To stop all of your processes and log yourself off, enter:

kill -kill 0

This sends signal 9, the SIGKILL signal, to all processes having a process group ID equal to the senders process group ID. Because the shell cannot ignore the SIGKILL signal, this also stops the login shell and logs you off.

4. To stop all processes that you own, enter:

kill -9 -1

This sends signal 9, the **SIGKILL** signal, to all processes owned by the effective user, even those started at other work stations and that belong to other process groups. If a listing that you requested is being printed, it is also stopped.

5. To send a different signal code to a process, enter:

```
kill -USR1 1103
```

The name of the kill command is misleading because many signals, including SIGUSR1, do not stop processes. The action taken on **SIGUSR1** is defined by the particular application you are running.

Note: To send signal 15, the SIGTERM signal with this form of the kill command, you must explicitly specify -15 or TERM.

Files

/usr/include/sys/signal.h

Specifies signal names.

Related Information

The **csh** command, **ksh** command, **ps** command, **sh** command.

The kill subroutine, sigaction subroutine.

killall Command

Purpose

Cancels all processes except the calling process.

Syntax

killall [-] [-Signal]

Description

The killall command cancels all processes that you started, except those producing the killall process. This command provides a convenient means of canceling all processes created by the shell that you control. When started by a root user, the killall command cancels all cancellable processes except those processes that started it. If several Signals are specified, only the last one is effective.

If no signal is specified, the killall command sends a SIGKILL signal.

Flags

Sends a SIGTERM signal initially and then sends a SIGKILL signal to all processes that survive for 30 seconds after receipt of the signal first sent. This gives processes that catch the SIGTERM signal an opportunity to clean up. If both - and -Signal are set, the killall command sends the specified signal initially and then sends a SIGKILL signal to all processes that survive for 30 seconds after receipt of the signal first sent.

-Signal Sends the specified Signal number or SignalName.

Examples

1. To stop all background processes that have started, enter:

This sends all background processes the kill signal 9 (also called the SIGKILL signal).

2. To stop all background processes, giving them a chance to clean up, enter:

```
killall -
```

This sends signal 15, the SIGTERM signal; waits 30 seconds, and then sends signal 9, the SIGKILL

3. To send a specific signal to the background processes, enter:

```
killall -2
```

This sends signal 2, the **SIGINT** signal, to the background processes.

Related Information

The kill command.

The **signal** subroutine.

kinit Command

Purpose

Obtains or renews the Kerberos ticket-granting ticket.

Syntax

```
kinit [ -l lifetime ] [ -r renewable_life ] [ -f ] [ -p ] [ -A ] [ -s start_time ] [ -S target_service ] [ -k [ -t
keytab_file ] [ -R ] [ -v ] [ -c cachename ] [ principal ]
```

Description

The kinit command obtains or renews a Kerberos ticket-granting ticket. The Key Distribution Center (KDC) options specified by the [kdcdefault] and [realms] in the Kerberos configuration file (kdc.conf) are used if you do not specify a ticket flag on the command line.

If you are not renewing an existing ticket, the command reinitializes the credentials cache and will contain the new ticket-granting ticket received from the KDC. If you do not specify the Principal name on the command line and you do specify the -s flag, the Principal name is obtained from the credentials cache. The new credentials cache becomes the default cache unless you specify the cache name using the -c flag.

The ticket *Time* value for the **-I**, **-r** and **-s** flags is expressed as *ndnhnmns* where:

- n represents a number
- d represents days
- h represents hours
- m represents minutes
- s represents seconds

You must specify the components in this order but you can omit any component, for example 4h5m represents four hours and 5 minutes and 1d2s represents 1 day and 2 seconds.

Note: The Kerberos ticket life time is calculated taking the DST changes into consideration, as per design. Hence Kerberos tickets issued during DST disabled time, if has validity that spans to reach the DST enabled time or vice versa can have a difference of 1 hour displayed in klist.

Flags

-A Specifies that the ticket contain a list of client addresses. The ticket will contain the local host

address list if this option is not specified. When an initial ticket contains an address list, it can

be used only from one of the addresses in the the address list.

Specifies the name of the credentials cache to use. The default credentials cache is used if -c cachename

> this flag is not specified. If the KRB5CCNAME environment variable is set, its value is used to name the default ticket cache. Any existing contents of the cache i are destroyed by kinit.

-f Specifies that the ticket is to be forwardable. To forward the ticket, this flag must be specified. -k Specifies to obtain the key for the ticket principal from a key table. If you do not specify this

flag, you are prompted to enter the password for the ticket principal.

-I lifetime Specifies the ticket end time interval. The ticket cannot be used after the interval expires

unless the ticket is renewed. The interval default time is 10 hours.

Specifies that the ticket is to be proxiable. To make the ticket proxiable, this flag must be -р

specified.

principal Specifies the ticket principal. The principal is obtained from the credentials cache if the

principal is not specified on the command line.

Specifies the renew time interval for a renewable ticket. The ticket cannot be renewed after -r renewable_life

> the interval expires. The renew time must be greater than the end time. If this flag is not specified, the ticket is not renewable, although you can still generate a renewable ticket if the

requested ticket lifetime exceeds the maximum ticket lifetime.

-R Specifies to renew an existing ticket. No other flags may be specified when renewing an

existing ticket.

-s start time Specifies a request for a postdated ticket, valid starting at start_time. Specifies an alternate service name to use when getting initial tickets. **-S** target_service

Specifies the key table name. The default key table is used if this flag is not specified and the -t keytab_file

-k flag is specified. The -t flag implies the -k flag.

Specifies that the ticket granting ticket in the cache be passed to the kdc for validation. If the

ticket is within its requested time range, the cache is replaced with the validated ticket.

Examples

1. To obtain a ticket-granting ticket with a lifetime of 10 hours, which is renewable for five days, type:

kinit -l 10h -r 5d my principal

2. To renew an existing ticket, type:

kinit -R

Files

/usr/krb5/bin/kinit

/var/krb5/security/creds/krb5cc_[uid] default credentials cache ([uid] is the UID of the user.) /etc/krb5/krb5.keytab default location for the local host's keytab file.

/var/krb5/krb5kdc/kdc.conf Kerberos KDC configuration file.

Related Information

The klist command, kdestroy command, and env command.

klist Command

Purpose

Displays the contents of a Kerberos credentials cache or key table.

Syntax

klist [[-c] [-f] [-e] [-s] [-a] [-n]] [-k [-t] [-K]] [name]

Description

The klist command displays the contents of a Kerberos credentials cache or key table.

Flags

- -a Displays all tickets in the credentials cache, including expired tickets. Expired tickets are not listed if this flag is not specified. This flag is valid only when listing a credentials cache.
- -c Lists the tickets in a credentials cache. This is the default if neither the -c nor the -k flag is specified. This flag is mutually exclusive with the -k flag.
- **-e** Displays the encryption type for the session key and the ticket.
- **-f** Displays the ticket flags using the following abbreviations:
 - **F** Forwardable ticket
 - f Forwarded ticket
 - P Proxiable ticket
 - p Proxy ticket
 - D Postdateable ticket
 - d Postdated ticket
 - R Renewable ticket
 - I Initial ticket
 - i Invalid ticket
 - H Hardware preauthentication used
 - A Preauthentication used
 - O Server can be a delegate

name Specifies the name of the credentials cache or key table. The default credentials cache or key table is used if you do not specify a filename.

If you do not specify a name indicating a cache name or keytab name, klist displays the credentials in the default credentials cache or keytab file as appropriate. If the KRB5CCNAME environment variable is set, its value is used to name the default credentials (ticket) cache.

- **-k** Lists the entries in a key table. This flag is mutually exclusive with the **-c** flag.
- -K Displays the encryption key value for each key table entry. This flag is valid only when listing a key table.
- -n Displays the numerical internet address instead of the host name. The default without the -n is host name. This command is used in conjunction with the -a flag.
- -s Suppresses command output but sets the exit status to 0 if a valid ticket-granting ticket is found in the credentials cache. This flag is valid only when listing a credentials cache.
- -t Displays timestamps for key table entries. This flag is valid only when listing a key table.

Examples

- 1. To list all of the entries in the default credentials cache, type:
- 2. To list all of the entries in the etc/krb5/my_keytab key table with timestamps, type:

```
klist -t -k etc/krb5/my_keytab
```

Files

/usr/krb5/bin/klist /var/krb5/security/creds/krb5cc_[uid]

/etc/krb5/krb5.keytab

default credentials cache ([uid] is the UID of the user.)

default location for the local host's keytab file.

Related Information

The kinit command, kdestroy command, and env command.

kmodctrl Command

Purpose

Loads or unloads the kernel extension /usr/lib/drivers/kmobip6.

Syntax

kmodctrl [-k kextname] [-luq]

Description

The kernel extension /usr/lib/drivers/kmobip6 contains support for the Mobile IPv6 functionality. This kernel extension must be loaded in order to configure the system as a mobile IPv6 home agent or correspondent node. Normally this command will be run automatically by the /etc/rc.mobip6 script if mobile IPv6 has been enabled using system management.

Flags

-k Specifies an alternate path for the mobility kernel extension.

-1 Loads the mobility kernel extension.

Checks whether the kernel extension is loaded. -q

Unloads the mobility kernel extension.

Exit Status

- 0 The command completed successfully.
- >0 An error occurred.

Security

You must be the root user or a member of the system group to execute this command.

Examples

1. The following example loads the kmobip6 kernel extension:

2. The following example unloads the kmobip6 kernel extension. This will disable all mobile IPv6 functionality on the system:

```
kmodctrl -u
```

3. The following example queries whether the kmobip6 kernel extension is loaded:

```
kmodctrl -q
```

Related Information

The mobip6ctrl command, mobip6reqd daemon, ndpd-router command, rc.mobip6 command.

The Mobile IPv6 in Networks and communication management.

kpasswd Command

Purpose

Changes the password for a Kerberos principal.

Syntax

kpasswd [Principal]

Description

The kpasswd command changes the password for a specified Kerberos principal. It prompts for the current principals password, which is used to obtain a changepw ticket from the KDC for the user's Kerberos realm. If kpasswd successfully obtains the changepw ticket, the user is prompted twice for the new password and the password is changed.

If the principal is governed by a policy that specifies for example length and/or number of character classes required in the new password, the new password must conform to the policy.

You may not change the password for a ticket-granting service principal (krbtgt/domain) using the kpasswd command.

Parameters

Principal

Specifies the principal for which password you want to change. If you do not specify the principal on the command line, the principal is obtained from the default credentials cache.

Security

When requesting a password change, you must supply both the current password and the new password.

Files

/usr/krb5/bin/kpasswd /var/krb5/security/creds/krb5cc_[uid]

default credentials cache ([uid] is the UID of the user.)

krlogind Daemon

Purpose

Provides the server function for the rlogin command.

Syntax

/usr/sbin/krlogind [-n] [-s]

Note: The krlogind daemon is normally started by the inetd daemon. It can also be controlled from the command line, using SRC commands.

Description

The /usr/sbin/krlogind daemon is the server for the rlogin remote login command. The server provides a remote login facility.

Changes to the krlogind daemon can be made by using Web-based System Manager, the System Management Interface Tool (SMIT) or System Resource Controller (SRC), by editing the /etc/inetd.conf or /etc/services file. Entering krlogind at the command line is not recommended. The krlogind daemon is started by default when it is uncommented in the /etc/inetd.conf file.

The inetd daemon get its information from the /etc/inetd.conf file and the /etc/services file.

After changing the /etc/inetd.conf or /etc/services file, run the refresh -s inetd or kill -1 InetdPID command to inform the **inetd** daemon of the changes to its configuration file.

Service Request Protocol

When the **krlogind** daemon receives a service request, the daemon initiates the following protocol:

- 1. The krlogind daemon checks the source port number for the request. If the port number is not in the range 512 through 1023, the krlogind daemon terminates the connection.
- 2. The krlogind daemon uses the source address of the initial connection request to determine the name of the client host. If the name cannot be determined, the krlogind daemon uses the dotted-decimal representation of the client host address.
- 3. The **krshd** daemon attempts to validate the user using the following steps:
 - makes sure that Kerberos 5 is a valid authentication method if the incoming ticket is a Kerberos 5 ticket. If the incoming ticket is a Kerberos 4 ticket, the connection fails. Kerberos 4 is not supported for **rlogin**.
 - calls kvalid user with the local account name as well as the DCE principal.

Error Messages

The following error messages are associated with the **krlogind** daemon:

Try again A fork command made by the server has failed.

/usr/bin/shell: No shell. The shell specified for the shell variable cannot be started. The shell variable

may also be a program.

Flags

- Disables transport-level keep-alive messages. The messages are enabled by default.
- Turns on socket level debugging. -S

Manipulating the krshd Daemon

The **krshd** daemon is a subserver of the **inetd** daemon, which is a subsystem of the System Resource Controller (SRC). The krshd daemon is a member of the tcpip SRC subsystem group. Using the chauthent command will comment/uncomment the kshell line in the /etc/inetd.conf file and restart the inetd daemon depending on whether Kerberos 5 or Kerberos 4 is configured/unconfigured. This daemon should be manipulated using the chauthent/Isauthent commands. Direct modification of the inetd.conf file's kshell entry in not recommended.

Related Information

The **rlogin** command.

The inetd daemon, rshd daemon, syslogd daemon.

The **pty** special file.

The kvalid_user subroutine.

The /etc/inetd.conf file format.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

Communications and networks in Networks and communication management.

Authentication and the secure rcmds in Networks and communication management.

krshd Daemon

Purpose

Provides the server function for remote command execution.

Syntax

/usr/sbin/krshd

Note: The rshd daemon is normally started by the inetd daemon. It can also be controlled from the command line, using SRC commands.

Description

The /usr/sbin/krshd daemon is the server for the rcp and rsh commands using Kerberos authentication. The krshd daemon provides remote execution of shell commands. These commands are based on requests from privileged sockets on trusted hosts. The shell commands must have user authentication. The **krshd** daemon listens at the kshell socket defined in the **/etc/services** file.

Changes to the krshd daemon can be made using the System Management Interface Tool (SMIT) or System Resource Controller (SRC), by editing the /etc/inetd.conf or /etc/services file. Entering krshd at the command line is not recommended. The krshd daemon is started by default when it is uncommented in the /etc/inetd.conf file.

The inetd daemon gets its information from the /etc/inetd.conf file and the /etc/services file.

After changing the /etc/inetd.conf or /etc/services file, run the refresh -s inetd or kill 1 InetdPID command to inform the inetd daemon of the changes to its configuration file.

Service Request Protocol

When the krshd daemon receives a service request, it initiates the following protocol:

- 1. The **krshd** daemon checks the source port number for the request. If the port number is not in the range 0 through 1023, the krshd daemon terminates the connection.
- 2. The **krshd** daemon reads characters from the socket up to a null byte. The string read is interpreted as an ASCII number (base 10). If this number is nonzero, the krshd daemon interprets it as the port number of a secondary stream to be used as standard error. A second connection is created to the specified port on the client host. The source port on the local host is also in the range 0 through 1023.
- 3. The **krshd** daemon uses the source address of the initial connection request to determine the name of the client host. If the name cannot be determined, the krshd daemon uses the dotted decimal representation of the client host's address.
- 4. The **krshd** daemon retrieves the following information from the initial socket:

- A Kerberos service ticket.
- A null-terminated string of at most 16 bytes interpreted as the user name of the user on the client
- Another null-terminated string interpreted as a command line to be passed to a shell on the local server host.
- · A null-terminated string of at most 16 bytes interpreted as the user name to be used on the local server host.
- If the service ticket was a Kerberos 5 ticket, the daemon will expect either a Kerberos 5 TGT or a null string.
- 5. The krshd daemon attempts to validate the user using the following steps:
 - makes sure that Kerberos 5 is a valid authentication method if the incoming ticket is a Kerberos 5 ticket. Likewise, if the incoming ticket is a Kerberos 4 ticket, the Kerberos 4 authentication method must be configured.
 - calls kvalid_user with the local account name as well as the DCE Principal.
- 6. Once krshd validates the user, the krshd daemon returns a null byte on the initial connection. If the connection is a Kerberos 5 ticket and the TGT is sent, the command line passes to the k5dcelogin command, (which upgrades it to full DCE credentials). If the TGT is not sent or if the connection is a Kerberos 4 ticket, the command line passes to the user's local login shell. The shell then inherits the network connections established by the krshd daemon.

The krshd daemon is controlled by using the System Management Interface Tool (SMIT) or by changing the /etc/inetd.conf file. Entering krshd at the command line is not recommended.

Manipulating the krshd Daemon

The **krshd** daemon is a subserver of the **inetd** daemon, which is a subsystem of the System Resource Controller (SRC). The krshd daemon is a member of the tcpip SRC subsystem group. Using the chauthent command will comment/uncomment the kshell line in the /etc/inetd.conf file and restart the inetd daemon depending on whether Kerberos 5 or Kerberos 4 is configured/unconfigured. This daemon should be manipulated using the chauthent/Isauthent commands. Direct modification of the inetd.conf file's kshell entry in not recommended.

Related Information

The rsh command.

The inetd daemon.

The kvalid_user function.

The /etc/hosts.equiv file format, /etc/inetd.conf file format, and /etc/services file format.

Communications and networks in *Networks and communication management*.

Authentication and the secure rcmds in *Networks and communication management*.

ksh Command

Purpose

Invokes the Korn shell.

Syntax

ksh [-i] [{ + | - } { a e f h k m n p t u v x }] [-o Option ...] [-c String | -s | -r | File [Parameter]]

Note: Preceding a flag with + (plus) rather than - (minus) turns off the flag.

Description

The **ksh** command invokes the Korn shell, which is an interactive command interpreter and a command programming language. The shell carries out commands either interactively from a terminal keyboard or from a file.

The Korn shell is backwardly compatible with the Bourne shell (invoked with the bsh command) and contains most of the Bourne shell features as well as several of the best features of the C shell.

For more information about the Korn shell, refer to Korn shell or POSIX shell commands in Operating system and device management.

Note: The ksh wait built in behaves in a manner similar to the parent wait() API.

An enhanced version of the Korn shell, called ksh93, is also available. The enhanced Korn shell has additional features that are not available in the default Korn shell. For information regarding these additional features, refer to Enhanced Korn shell (ksh93) in Operating system and device management.

Additionally, a restricted version of the Korn shell, called rksh, is available. The restricted Korn shell allows administrators to provide a controlled execution environment for the users. For more information regarding restricted Korn shell, refer to Restricted Korn shell in Operating system and device management.

Flags

i lago	
-a -c String	Exports automatically all subsequent parameters that are defined. Causes the Korn shell to read commands from the <i>String</i> variable. This flag cannot be used with the -s flag or with the <i>File</i> [<i>Parameter</i>] parameter.
-е	Executes the ERR trap, if set, and exits if a command has a nonzero exit status, unless in the following conditions:
	The simple command is contained in a "&&" or "II" list.
	The simple command immediately follows "if", "while" or "until".
	The simple command is contained in a pipeline following "!".
-f	This mode is disabled when profiles are read. Disables file name substitution.
-h	Designates each command as a tracked alias when first encountered.
i	Indicates that the shell is interactive. An interactive shell is also indicated if shell input and output are attached to a terminal (as determined by the ioctl subroutine). In this case, the TERM environment variable is ignored (so that the kill 0 command does not kill an interactive shell) and the INTR signal is caught and ignored (so that a wait state can be interrupted). In all cases, the QUIT signal is ignored by the shell.
-k	Places all parameter assignment arguments in the environment for a command, not just those arguments that precede the command name.
-m	Runs background jobs in a separate process and prints a line upon completion. The exit status of background jobs is reported in a completion message. On systems with job control, this flag is turned on automatically for interactive shells.
-n	Reads commands and checks them for syntax errors, but does not execute them. This flag is ignored for interactive shells.

-o Option

Prints the current option settings and an error message if you do not specify an argument. You can use this flag to enable any of the following options:

allexport

Same as the -a flag.

errexit Same as the -e flag.

bgnice Runs all background jobs at a lower priority. This is the default mode.

emacs Enters an emacs-style inline editor for command entry.

gmacs Enters a gmacs-style inline editor for command entry.

ignoreeof

Does not exit the shell when it encounters an end-of-file character. You must use the **exit** command, or override the flag and exit the shell by pressing the Ctrl-D key sequence more than 11 times.

keyword

Same as the -k flag.

markdirs

Appends a / (slash) to all directory names that are a result of filename substitution.

monitor

Same as the -m flag.

noclobber

Prevents redirection from truncating existing files. When you specify this option, use the redirection symbol >I (right caret, pipe symbol) to truncate a file.

noexec

Same as the -n flag.

noglob Same as the **-f** flag.

nolog Prevents function definitions from being saved in the history file.

nounset

Same as the -u flag.

privileged

Same as the **-p** flag.

verbose

Same as the -v flag.

trackall

Same as the -h flag.

vi Enters the insert mode of a vi-style inline editor for command entry. Entering escape character 033 puts the editor into the move mode. A return sends the line.

viraw Processes each character as it is typed in vi mode.

xtrace Same as the -x flag.

You can set more than one option on a single ksh command line.

Disables the processing of the \$HOME/.profile file when you use the shell as a login shell.

Runs a restricted shell. With a restricted shell you cannot:

- · Change the current working directory.
- · Set the value of the SHELL, ENV, or PATH variable.
- Specify the pathname of a command that contains a / (slash).
- Redirect output of a command with > (right caret), >I (right caret, pipe symbol), <> (left caret, right caret), or >> (two right carets).

Using this flag is the same as issuing the **rksh** command.

-р

Causes the ksh command to read commands from the standard input. Shell output, except for -S the output of the special commands, is written to file descriptor 2. This parameter cannot be used with the -c flag or with the File[Parameter] parameter.

Exits after reading and executing one command. -t Treats unset parameters as errors when substituting. -u

Prints shell input lines as they are read. -v

Prints executed commands and their arguments.

Files

/usr/bin/ksh Contains the path name to the Korn shell.

/tmp/sh* Contains temporary files that are created when a shell is opened.

Related Information

The env command.

The **rksh** command.

The **profile** file format.

Korn shell or POSIX shell commands and Enhanced Korn shell (ksh93) in Operating system and device management.

The Restricted Korn shell section in Operating system and device management.

ksh93 Command

Purpose

Invokes the Enhanced Korn shell.

Syntax

ksh93 [+ | - a b c C e f h i k m n p r s t u v x] [+-R file] [+-o Option] [arg...].

Note: Preceding a flag with + (plus) rather than - (minus) turns off the flag.

Description

The ksh93 command invokes the Enhanced Korn shell, which is an interactive command interpreter and a command programming language. The shell carries out commands either interactively from a terminal keyboard or from a file.

The Enhanced Korn shell has additional features that are not available in the default Korn shell. For information regarding these additional features, refer to Enhanced Korn shell (ksh93) in Operating system and device management.

For more information about the Korn shell, refer to Korn shell or POSIX shell commands in Operating system and device management.

Note: The ksh93 built-in wait behaves in a manner similar to the parent wait subroutine.

Flags

-C

-i

-m

-n

Exports automatically all subsequent parameters that are defined. -a

-b Job completion messages are printed as soon as a background job changes state rather than

waiting for the next prompt.

-c String Causes the Korn shell to read commands from the String variable. This flag cannot be used with

the -s flag or with the File[Parameter] parameter.

Prevents existing files from getting truncated when redirection > is used. O EXCL mode is used to create files. Requires > to truncate a file when -C option is used.

Executes the **ERR** trap, if set, and exits if a command has a nonzero exit status. This mode is -е

disabled while reading profiles.

-f Disables file name substitution.

-h Designates each command as a tracked alias when first encountered.

> Indicates that the shell is interactive. An interactive shell is also indicated if shell input and output are attached to a terminal (as determined by the ioctl subroutine). In this case, the TERM environment variable is ignored (so that the kill 0 command does not kill an interactive shell) and the INTR signal is caught and ignored (so that a wait state can be interrupted). In all cases, the

QUIT signal is ignored by the shell.

-k Places all parameter assignment arguments in the environment for a command, not just those arguments that precede the command name.

> Runs background jobs in a separate process and prints a line upon completion. The exit status of background jobs is reported in a completion message. On systems with job control, this flag is turned on automatically for interactive shells.

Reads commands and checks them for syntax errors, but does not execute them. This flag is ignored for interactive shells.

Note: ksh93 -n outputs a warning message for certain syntax. These messages are warnings. Even though these warnings are issued, the execution of the scripts is unaltered. The following are known warning messages:

```
`...` obsolete, use $(...).
-a obsolete, use -e.
'=' obsolete, use '=='.
%s within [[...]] obsolete, use ((...)).
set %s obsolete.
`{' instead of `in' is obsolete.
"obsolete -j must be 1 or 2.
```

-o Option

Prints the current option settings and an error message if you do not specify an argument. You can use this flag to enable any of the following options:

allexport

Same as the -a flag.

errexit Same as the -e flag.

bgnice

Runs all background jobs at a lower priority. This is the default mode.

emacs

Enters an emacs-style inline editor for command entry.

qmacs

Enters a gmacs-style inline editor for command entry.

ignoreeof

Does not exit the shell when it encounters an end-of-file character. You must use the **exit** command, or override the flag and exit the shell by pressing the Ctrl-D key sequence more than 11 times.

interactive

Same as the -i flag.

keyword

Same as the -k flag.

markdirs

Appends a / (slash) to all directory names that are a result of filename substitution.

monitor

Same as the -m flag.

noclobber

Same as the -C flag.

noexec

Same as the -n flag.

noglob

Same as the -f flag.

nolog Prevents function definitions from being saved in the history file.

notify Same as the -b flag.

nounset

Same as the -u flag.

privileged

Same as the -p flag.

restricted

Same as the -r flag.

verbose

Same as the -v flag.

trackall

Same as the -h flag.

vi Enters the insert mode of a vi-style inline editor for command entry. Entering escape character 033 puts the editor into the move mode. A return sends the line.

viraw Processes each character as it is typed in vi mode.

xtrace Same as the **-x** flag.

You can set more than one option on a single ksh93 command line.

-p Disables processing of the **\$HOME/.profile** file and uses the **/etc/suid_profile** file instead of the **ENV** file. This mode is on whenever the effective uid (gid) is not equal to the real uid (gid). Turning this off causes the effective uid and gid to be set to the real uid and gid.

Runs a restricted shell. With a restricted shell you cannot:

- · Change the current working directory.
- · Set the value of the SHELL, ENV, or PATH variable.
- Specify the path name of a command that contains a / (slash).
- Redirect output of a command with > (right caret), > | (right caret, pipe symbol), <> (left caret, right caret), or >> (two right carets).

-R File A cross reference database is generated when the -R File option is used. This can be used to find

definitions and references for variables and commands by a separate utility.

Causes the **ksh93** command to read commands from the standard input. Shell output, except for the output of the special commands, is written to file descriptor 2. This parameter cannot be used with the **-c** flag or with the *File*[*Parameter*] parameter.

Exits after reading and executing one command.

Treats unset parameters as errors when substituting.

-v Prints shell input lines as they are read.

-x Prints executed commands and their arguments.

Exit Status

-r

-s

-t

0 Successful completion.>0 An error occurred.

Location

/usr/bin/ksh93

Related Information

The env command, the "ksh Command" on page 158.

The wait subroutine.

The **profile** file format.

Korn shell or POSIX shell commands and Enhanced Korn shell (ksh93) in *Operating system and device management*.

kvno Command

Purpose

Displays the current key version number for a principal.

Syntax

kvno [-e etype] service 1 service2....

Description

The **kvno** command displays the current key version number for a principal (*service 1 service2...*). The security policy must allow a service ticket to be obtained for the principal. The current network identity is used when requesting the service ticket.

Flags

Specifies which encryption type to get the current key version. -e etype

service 1 service2... Specifies the principal for which you want to display the current key version number.

Security

The security policy must allow a service ticket to be obtained for the principal.

Files

/usr/krb5/bin/kvno

Related Information

The klist command.

last Command

Purpose

Displays information about previous logins.

Syntax

last [-X][-f FileName][-t Time][-n Number|-Number][Name ...][Terminal ...]

Description

The last command displays, in reverse chronological order, all previous logins and logoffs still recorded in the /var/adm/wtmp file. The /var/adm/wtmp file collects login and logout records as these events occur and holds them until the records are processed by the acctcon1 and acctcon2 commands as part of the daily reporting procedures. When the time daemon, timed, changes the system time, it logs entries in wtmp under the pseudo-user "date". An entry starting with "date I" is logged before the change, and one starting with "date {" is logged after the change. This allows for accurate accounting of logins that span a time change.

The list can be restricted to:

- The number of lines specified either with the -Number parameter or with the -n flag.
- Logins or logoffs by the users specified by the Name parameter.
- Logins or logoffs from the terminals specified by the *Terminal* parameter.
- A terminal can be named fully or abbreviated as a tty. For example, you can specify either the tty0 terminal or the 0 terminal.

Note: If you specify both a Name and Terminal parameter, the last command displays all logins and logoffs meeting either criterion.

For each process, the last command displays the:

- · Time the session began
- Duration
- · Terminal (tty) used

If applicable, the following information is included:

- · Terminations due to rebooting
- Sessions that are still continuing

If the **last** command is interrupted, it indicates how far the search has progressed in the **/var/adm/wtmp** file. If interrupted with a quit signal, the command indicates how far the search has progressed and then continues the search. The quit signal can be any one of the following:

```
#define SIGQUIT 3 /* (*) quit,
generated from terminal special char */
#define SIGKILL 9 /* kill (cannot be caught or ignored) */
#define SIGTERM 15 /* software termination signal */
```

The kill command sends the default SIGTERM signal when it is invoked without any option. If you want to send the SIGQUIT signal, enter the following:

```
kill -3 (Process ID)
```

See the kill command for more information.

Flags

-f FileName Specifies an alternate file from which to read logins and logoffs.

Specifies the number of lines to be displayed on the list. -n

-t Time Displays users logged in at the given Time value. The Time variable is specified in the decimal

form [[CC]YY]MMDDhhmm[.SS] where:

CC Specifies the first two digits of the year.

ΥY Specifies the last two digits of the year.

MM Specifies the month of the year (01 to 12).

DD Specifies the day of the month (01 to 31).

hh Specifies the hour of the day (00 to 23).

Specifies the minute of the hour (00 to 59). mm

SS Specifies the second of the minute (00 to 59).

-X Prints all available characters of each user name instead of truncating to the first 8 characters.

Examples

1. To display all the recorded logins and logoffs by user root or from the console terminal, type:

```
last root console
```

2. To display the time between reboots of the system, type:

last reboot

The reboot pseudo-user logs in when the system starts again.

3. To display all the users still logged in at 10.30 am on April 15th, enter:

```
last -t 04151030
```

4. To display 10 lines in the list, type:

```
last -n 10
```

5. To display all the recorded logins and logoffs without truncating the user name, type:

```
last -X
```

Files

/usr/bin/last Contains the last command.

/var/adm/wtmp Contains connect-time accounting data, including login, logoff, and shutdown records.

Related Information

The acctcon1, accton2 command, lastlogin command.

For more information about the Accounting System, the preparation of daily and monthly reports, and the accounting files, see the System accounting in Operating system and device management.

Setting up an accounting subsystem in Operating system and device management describes the steps you must take to establish an accounting system.

lastcomm Command

Purpose

Displays information about the last commands executed.

Syntax

lastcomm [-X][Command] [Name] [Terminal]

Description

The **lastcomm** command displays information, in reverse chronological order, about all previously executed commands that are still recorded in the summary files in the /var/adm/pacct directory. You need to run the /usr/sbin/acct/startup command before you can execute the lastcomm command.

The list the **lastcomm** command displays can be restricted to:

- · Commands specified by the Command parameter.
- Commands executed by the user specified by the Name parameter.
- Commands from the terminal specified by the *Terminal* parameter.

A terminal can be named fully or abbreviated as a tty. For example, you can specify either the tty0 terminal or the 0 terminal.

For each process, the following information is displayed:

- · The name of the user who ran the process.
- Any flags the accounting facilities collected when the command executed. The following are valid flags:
- S The root user executed the command.
- F The command ran after a fork, but without a following subroutine.
- С The command ran in PDP-11 compatibility mode.
- D The command terminated with the generation of a core file.
- X The command was terminated with a signal.
- The name of the command under which the process was called.
- · The seconds of CPU time used by the process.
- · The time the process was started.

Flags

-X Prints all available characters of each user name instead of truncating to the first 8 characters.

Examples

1. To display information about all previously executed commands recorded in the /var/adm/pacct file, enter:

lastcomm

2. To display information about commands named a out executed by the root user on the ttyd0 terminal,

lastcomm a.out root ttyd0

3. To display information about all previously executed commands recorded in the /var/adm/pacct file without truncating the user name, enter:

lastcomm -X

Files

/usr/bin/lastcomm Contains the lastcomm command.

/var/adm/pacct The directory that contains the current accounting summary files.

Related Information

The **acctcms** command.

For more information about the Accounting System, the preparation of daily and monthly reports, and the accounting files, see the System accounting in Operating system and device management.

Setting up an accounting subsystem in Operating system and device management describes the steps you must take to establish an accounting system.

lastlogin Command

Purpose

Reports the last login date for each user on the system.

Syntax

/usr/sbin/acct/lastlogin [-X]

Description

The lastlogin command updates the /var/adm/acct/sum/loginlog file to show the last date each user logged in. Normally, the runacct command, running under the cron daemon, calls this command and adds the information to the daily report. However, the lastlogin command can also be entered by a user who is a member of the ADM group.

Note: You should not share accounting files among nodes in a distributed environment. Each node should have its own copy of the various accounting files.

Flags

-X Processes all available characters for each user name instead of truncating to the first 8 characters. This flag will also cause the lastlogin command to write to the /var/adm/acct/sumx/loginlog file instead of the /var/adm/acct/sum/loginlog file.

Security

Access Control: This command should grant execute (x) access only to members of the ADM group.

Files

/usr/sbin/acct The path to the accounting commands. /var/adm/wtmp The login and logout history file.

/var/adm/acct/sum Cumulative directory for daily accounting records.

Related Information

The runacct command.

The **cron** daemon.

For more information about the Accounting System, the preparation of daily and monthly reports, and the accounting files, see the System accounting in Operating system and device management.

Setting up an accounting subsystem in Operating system and device management explains the steps you must take to establish an accounting system.

Ib_admin Command

Purpose

Administers the registration of NCS-based servers in location broker databases.

Syntax

Ib_admin [-nq] [-version]

Description

The Ib_admin tool administers the registrations of NCS-based servers in global location broker (GLB) or local location broker (LLB) databases. A server registers universal unique identifiers (UUIDs) specifying an object, a type, and an interface, along with a socket address specifying its location. A client can locate servers by issuing lookup requests to GLBs and LLBs. The **Ib** admin tool can be used to look up information, add new entries, and delete existing entries in a specified database.

The Ib_admin tool is useful for inspecting the contents of location broker databases and for correcting database errors. For example, if a server terminates abnormally without unregistering itself, use Ib admin to manually remove its entry from the GLB database.

When accepting input or displaying output, **Ib admin** uses either character strings or descriptive textual names to identify objects, types, and interfaces. A character string directly represents the data in a UUID in the format

XX.XX.XX.XX.XX.XX.XX.XX.XX.XX.XX

where each x is a hexadecimal digit. Descriptive textual names are associated with UUIDs in the uuidname.txt file.

The **Ib_admin** command examines or modifies only one database at a time. This is referred to as the current database. The use broker command selects the type of location broker database, GLB or LLB. The set_broker command selects the host whose GLB or LLB database is to be accessed. If one replica of a replicated GLB database is modified, the modifications are propagated to the other replicas of that database.

Flags

Do not query for verification of wildcard expansions in unregister operations. -nq

-version Display the version of NCS that this **Ib_admin** belongs to, but do not start the tool.

Subcommands

In the lookup, register, and unregister commands, the object, type, and interface arguments can be either character strings representing UUIDs or textual names corresponding to UUIDs, as described earlier.

a[dd] c[lean] Synonym for register.

Finds and deletes obsolete entries in the current database. When issuing this command, Ib_admin attempts to contact each server registered in the database. If the server responds, the entry for its registration is left intact in the database. If the server does not respond, **Ib_admin** tries to look up its registration in the LLB database at the host where the server is located, tells the result of this lookup, and asks if the entry is to be deleted. If a server responds, but its UUIDs do not match the entry in the database, **lb_admin** tells this result and asks if the entry is to be deleted.

There are two situations in which it is likely that a database entry should be deleted:

- The server does not respond. Ib_admin succeeds in contacting the LLB at the host where the server is located, but the server is not registered with that LLB. The server is probably no longer running.
- · Server responds, but its UUIDs do not match the entry in the database. The server that responded is not the one that registered the entry.

Entries that meet either of these conditions are probably safe to delete.

In other situations, it is best not to delete the entry unless it can be verified directly that the server is not running (for example, by listing the processes running on its host).

When **lb_admin** asks to delete an entry, there are four ways to respond. A y[es] response deletes the entry. A n[o] response leaves the entry intact in the database. After a yes or a no, **lb_admin** proceeds to check the next entry in the current database. A **g[o]** response invokes automatic deletion, in which all eligible entries are deleted and all ineligible entries are left intact, without the user being queried, until all entries have been checked. A q[uit] response terminates the clean operation.

Synonym for unregister.

Displays a description of the specified Command or, if none is specified, list all of the Ib_admin commands.

Looks up and displays all entries with matching Object, Type, and Interface fields in the current database. An asterisk can be used as a wildcard for any of the arguments. If all the arguments are wildcards, lookup displays the entire database.

Exits the Ib_admin session.

d[elete]

h[elp] [Command] or ? [Command]

I[ookup] Object Type Interface

q[uit]

r[egister] Object Type Interface Location Annotation [Flag]

Adds the specified entry to the current database. Use an asterisk to represent the nil UUID in the Object, Type, and Interface fields.

The location is a string in the format Family:Host Port, where Family is an address family, *Host* is a host name, and *Port* is a port number. Possible values for Family include ip. A leading # can be used to indicate that a host name is in the standard numeric form. For example, ip:vienna[1756] and ip:#192.5.5.5[1791] are acceptable location specifiers.

The Annotation is a string of up to 64 characters annotating the entry. Use double quotation marks to delimit a string that contains a space or contains no characters. To embed a double quotation mark in the string, precede it with a backslash.

The Flag is either local (the default) or global, indicating whether the entry should be marked for local registration only or for registration in both the LLB and GLB databases. The Flag is a field that is stored with the entry but does not affect where the entry is registered. The set_broker and use_broker commands select the particular LLB or GLB database for registration. Sets the host for the current LLB or GLB. If specifing global as the BrokerSwitch, set_broker sets the current GLB; otherwise, it sets the current LLB. The host is a string in the format Family: Host, where Family is an address family and Host is a host name. Possible values for Family include ip. A leading # can be used to indicate that a host name is in the standard numeric form. For example, ip:prague and ip:#192.5.5.5 are acceptable host specifiers.

Issue use_broker, not this command, to determine if subsequent operations will access the LLB or the GLB.

Sets the timeout period used by **Ib_admin** for all of its operations. With an argument of short or long, set_timeout sets the timeout accordingly. With no argument, it displays the current timeout value.

Deletes the specified entry from the current database.

The location is a string in the format Family:Host Port, where Family is an address family, *Host* is a host name, and *Port* is a port number. Possible values for Family include ip. A leading # can be used to indicate that a host name is in the standard numeric form. For example, ip:vienna[1756] and ip:#192.5.5.5[1791] are acceptable location specifiers.

An asterisk can be used as a wildcard in the Object, Type, And Interface fields to match any value for the field. Unless queries have been suppressed by invoking **Ib_admin** with the **-nq** option, **unregister** allows deletion of each matching entry. A v[es] response deletes the entry. A n[o] response leaves the entry in the database. A **g[o]** response deletes all remaining database entries that match, without querying. A q[uit] response terminates the unregister operation, without deleting any additional entries.

Selects the type of database that subsequent operations will access, GLB or LLB. The *BrokerSwitch* is either global or local. If a *BrokerSwitch* is not supplied, use broker determines if the current database is global or local.

Use set_broker to select the host whose GLB or LLB is to be accessed.

s[et_broker] [BrokerSwitch] Host

set_t[imeout] [short | long]

u[nregister] Object Type Interface Location

us[e_broker] [BrokerSwitch]

Related Information

The drm admin (NCS) command

The glbd (NCS) daemon, llbd (NCS) daemon, nrglbd (NCS) daemon.

Ib_find Command

Purpose

Gets a list of global location broker (GLB) server daemons and their attributes.

Syntax

lb_find [-q] [-v] [-dl]

Description

The **Ib** find command sends out inquiries to the NCS location broker daemons and gathers the responses. The results are analyzed to determine whether the global location broker is replicatable, and which cell each daemon serves. After ten seconds, the results are summarized, showing the GLB broker type, the server host's network address, a cell name of either default or alternate N, and the cell's UUID.

Flags

- Queries for a GLB server, using the standard RPC mechanism. At most, one GLB server is printed, and only servers in the current machine's cell are searched. The program exits with a status of 0 if a GLB server is found; otherwise the status is nonzero.
- -v Prints out the NCS version string.
- -dl Turns on RPC debugging while searching for GLB servers.

Examples

A network contains one **glbd** in each of two NCS cells and one **nrglbd** in a third cell.

```
/etc/ncs/lb_find
sent to broadcast address 192.92.110.255
waiting for replies
received response from glb daemon at ip:stimpy(192.92.110.43)
port 1072.
received response from glb daemon at ip:oscar(192.92.110.16) port
received response from glb daemon at ip:vmess(192.92.110.21) port
1114.
. . . . .
replicatable
                   ip:stimpy
                                   default
                                                 333b91c50000.0d.0
0.00.87.84.00.00.00
replicatable
                                   alternate 1
                                                 54bdad9a4000.0d.0
                   ip:oscar
0.01.83.0f.00.00.00
non replicatable
                    ip:vmess
                                   alternate 2
                                                 5c0e4acb8fa7.02.c
0.5c.6e.15.00.00.00
```

Related Information

The **lb** admin command.

The glbd (NCS) daemon, llbd (NCS) daemon, nrglbd (NCS) daemon.

Ibxproxy Command

Purpose

Low BandWidth X proxy.

Syntax

```
| Ibxproxy | :<display> | | -help | | -display | Display | | -motion Number | | -terminate | -reset | |
-reconnect | [ -I ] [ -nolbx | [ -nocomp | [ -nodelta | [ -notags | [ -nogfx | [ -noimage | [ -nosquish | [
-nointernsc | [ -noatomsfile | [ -atomsfiles File | [ -nowinattr | [ -nograbcmap | [ -norgbfile | [ -rgbfile
Path ] [-tagcachesize ] [-zlevel Level ] [-compstats ] [-nozeropad ] [-cheaterrors ] [-cheatevents ]
```

Description

The **Ibxproxy** command accepts client connections, multiplexes them over a single connection to the X server, and performs various optimizations on the X protocol to make it faster over low bandwidth and/or high latency connections. Applications that would like to take advantage of the Low Bandwidth extension to X (LBX) must make their connections to an **lbxproxy**. These applications need to know nothing about LBX, they simply connect to the **Ibxproxy** as if were a regular server.

For authentication/authorization, **Ibxproxy** passes the credentials presented by the client along to the server. Since X clients connect to **Ibxproxy**, it is important that the user's **.Xauthority** file contain entries with valid keys associated with the network ID of the proxy. Ibxproxy does not get involved with how these entries are added to the .Xauthority file. The user is responsible for setting it up.

The **Ibxproxy** program has various flags, all of which are optional.

If :<Display> is specified, the proxy uses the Display port when listening for connections. The display port is an offset from port 6000, identical to the way in which regular X display connections are specified. If no port is specified on the command line, **Ibxproxy** defaults to port 63. If the port that the proxy tries to listen on is in use, the proxy exits with an error message.

At startup, **Ibxproxy** pre-interns a configurable list of atoms. This allows **Ibxproxy** to intern a group of atoms in a single round trip and immediately store the results in its cache. While running, **Ibxproxy** uses heuristics to decide when to delay sending window property data to the server. The heuristics depend on the size of the data, the name of the property, and whether a window manager is running through the same **Ibxproxy**. Atom control is specified in the **AtomControl** file, set up during installation of **Ibxproxy**. with command line overrides.

The file is a simple text file. There are three forms of lines: comments, length control, and name control. Lines starting with a ! (exclamation point) are treated as comments. A line of the form z length specifies the minimum length in bytes before property data is delayed. A line of the form options atomname controls the given atom, where options is any combination of the following characters: i means the atom should be pre-interned; and w means data for properties with this name should be delayed only if a window manager is also running through the same **Ibxproxy**.

Flags

-atomsfile File	Overrides the default AtomControl file.
-cheaterrors	Allows cheating on X protocol for the sake of improved performance. The X protocol
	guarantees that any replies, events or errors generated by a previous request are sent before
	those of a later request. This puts substantial restrictions on when Ibxproxy can short circuit
	a request. The -cheaterrors flag allows lbxproxy to violate X protocol rules with respect to

errors. Use at your own risk.

The -cheatevents flag allows Ibxproxy to violate X protocol rules with respect to events as -cheatevents

well as errors. Use at your own risk.

Reports stream compression statistics every time the proxy resets or receives a SIGHUP -compstats

-display Display Specifies the address of the X server supporting the LBX extension. If this flag is not

specified, the display is obtained by the DISPLAY environment variable.

Prints a brief help message about the command line flags. -help

Causes all remaining arguments to be ignored. -1

-motion Number Specifies the maximimum Number of events that can be in flight. A limited number of pointer

motion events are allowed to be in flight between the server and the proxy at any given time.

The default is 8.

-noatomsfile Disables reading of the AtomControl file.

Disables stream compression. -nocomp -nodelta Disables delta request substitutions.

-nogfx Disables reencoding of graphics requests (not including image related requests).

-nograbcmap Disables colormap grabbing. -noimage Disables image compression.

-nointernsc Disables short circuiting of **InternAtom** requests.

-nolbx Disables all LBX optimizations.

-norgbfile Disables color name to RGB resolution in proxy.

-nosquish Disables squishing of X events. -notags Disables usage of tags.

-nowinattr Disables GetWindowAttributes/GetGeometry grouping into one round trip. -nozeropad Indicates to not zero out unused pad bytes in X requests, replies, and events.

-reconnect Causes Ibxproxy to reset (see -reset) and attempts to reconnect to the server when its

connection to the server is broken. The default behavior of **lbxproxy** is to exit.

-rqbfile Path Specifies an alternate RGB database Path for color name to RGB resolution.

-tagcachesize Sets the size of the proxy's tag cache (in bytes).

-[terminatelreset] The default behavior of **Ibxproxy** is to continue running as usual when it's last client exits.

> The -terminate option will cause Ibxproxy to exit when the last client exits. The -reset option will cause **Ibxproxy** to reset itself when the last client exits. Resetting causes **Ibxproxy** to

clean up it's state and reconnect to the server.

-zlevel Level Set the Zlib compression level (used for stream compression). The default is 9.

> 1 = worst compression, fastest. 9 = best compression, slowest.

Id Command

Purpose

Links object files.

Syntax

```
Id [ -DNumber ] [ -eLabel ] [ -G ] [ -HNumber ] [ -K ] [ -m ] [ -M ] [ -oName ] [ -r ] [ -s ] [ -SNumber ] [
-TNumber] [ -u Name ] ... [ -v ] [ -v ] [ -z ] [ -ZString ] ... [ -bOption ] ... [ -LDirectory ] ... { -fFileID ...
-IName ... InputFile ... }
```

or

Id -bsvr4 [-d[y | n]] [-D Number] [-e Label] [-G] [-HNumber] [-K] [-m] [-M] [-oName] [-r] [-R Path] [-s] [-SNumber] [-TNumber] [-u Name] ... [-v] [-v] [-z [defs | nodefs]] [-z multidefs] [-z [text | nowarntext | warntext]]] [-ZString] ... [-bOption] ... [-LDirectory] ... { -fFileID ... -IName ... InputFile ... }

Description

The Id command, also called the linkage editor or binder, combines object files, archives, and import files into one output object file, resolving external references. It produces an executable object file that can be

run. In addition, if you specify the Id command without the -s flag, you can use the output file as an InputFile parameter in another call to the Id command. By default, the Id command creates and places its output in the a.out file.

The Id command can relink a program without requiring that you list all input object files again. For example, if one object file from a large program has changed, you can relink the program by listing the new object file and the old program on the command line, along with any shared libraries required by the program. See "Examples" on page 195.

The Id command links input files in the order you specify on the command line. If you specify a file more than once, only the first occurrence of the file is processed. You must specify at least one input file, either with the -bl (uppercase letter i), -bimport, -bkeepfile, -f, or -l (lowercase letter L) flag or as an InputFile parameter. (The -bl, -bimport, or -bkeepfile flag is the -b flag used with the I, import, or keepfile option.)

Use the **cc** command to link files when you are producing programs that run under the operating system. Because the cc command calls the ld command with common options and necessary support libraries. you do not need to specify them on the command line. (This information is read from the /etc/xIC.cfg or /etc/vac.cfg configuration file.)

Linking Mode

The Id command can link 32-bit objects and programs as well as 64-bit objects and programs, but 32-bit and 64-bit objects may not be linked together. To specify the mode for linking, you can use the **OBJECT MODE** environment variable or the **-b32** or **-b64** options.

Archive Files

Archive files are composite objects, which usually contain import files and object files, including shared objects. If an archive file contains another archive file or a member whose type is not recognized, the Id command issues a warning and ignores the unrecognized member. If an object file contained in an archive file has the F LOADONLY bit set in the XCOFF header, the Id command ignores the member. This bit is usually used to designate old versions of shared objects that remain in the archive file to allow existing applications to load and run. New applications link with the new version of the shared object, that is, another member of the archive.

Shared Objects

A shared object, usually created by another call to the Id command, is an object file with the F_SHROBJ bit set in the XCOFF header. A shared object defines external symbols that are resolved at run time. If you specify the -bnso or -bnoautoimp option, the Id command processes a shared object as an ordinary object file, and if the file is stripped, the link fails.

Ordinarily, a shared object used as input is only listed in the loader section of the output file if a symbol in the shared object is actually referenced. When the run-time linker is used, however, you might want shared objects to be listed even if there are no symbols referenced. When the -brtl option is used, all shared objects listed on the command-line that are not archive members are listed in the output file. The system loader loads all such shared objects when the program runs, and the symbols exported by these shared objects may be used by the run-time linker. Shared objects that are archive members are not loaded automatically unless automatic loading is enabled by an import file in the archive. To enable automatic loading, see "Import and Export File Format (-bl: and -bE: Flags)" on page 191.

Import and Export Files

Import files are ASCII files that identify the external symbols to resolve at run time. An import file identifies the shared object defining the imported symbols. The system loader finds and resolves those symbols at run time. If the first line of an import file begins with #! (#, exclamation point), you can specify the file on the command line as an ordinary InputFile. Otherwise, you must use the -bl or -bimport option to specify the import file.

Export files are ASCII files that identify external symbols that are made available for another executable object file to import. The file format of an export file is the same as the file format of an import file.

Libraries

Libraries are files whose names end in .a, or possibly .so. To designate a library, you can specify an absolute or relative path name or use the -I (lowercase letter L) flag in the form -IName. The last form designates a **lib**Name.a file, or in dynamic mode, a **lib**Name.so file, to be searched for in several directories. These search directories include any directories specified by -L flags and the standard library directories /usr/lib and /lib.

Note: If you specify a shared object, or an archive file containing a shared object, with an absolute or relative path name, instead of with the -IName flag, the path name is included in the import file ID string in the loader section of the output file. You can override this behavior with the -bnoipath option.

Processing

The Id command processes all input files in the same manner, whether they are archives or not. It includes the symbol tables of all objects, discarding only symbol definitions that duplicate existing symbols. Unlike some other versions of the Id command, you do not need to order archive files so references precede definitions. Furthermore, you do not need to list an archive file more than once on the command

The order of the Id command flags does not affect how they are processed, except for the flags used with input object files, libraries, and import files. These flags are: -L. -f, -I (lowercase letter L), -bkeepfile, and **-bl** (uppercase letter i). The flags are processed in the following order:

- 1. The -L flag adds a directory to the list of search directories to locate libraries specified by the -I (lowercase letter L) flag. The directories are searched in the order specified. All -L flags are processed before any -I flags are processed.
- 2. The **Id** command processes the *InputFile* parameters, the files specified by the **-f** flag and libraries specified by the -I (lowercase letter L) flag in the order specified.
- 3. The Id command processes import files specified by the -bI (uppercase letter i) flag in the order specified after processing all other object files and libraries. You can specify an import file as an input file without the **-bl** flag if it is necessary to process the file before processing some object files. In this case, the first line of the import file must begin with the #! (#, exclamation point) symbols, and the import file is processed with other input files as described in step 2.
- 4. The **-bkeepfile** option names an input file on which the **Id** command does not perform garbage collection. If the specified input file is also specified as an InputFile parameter or listed in a file specified by the -f flag, the -bkeepfile option does not affect the order in which the file is processed. Otherwise, the file is processed in order along with other input files, as described in step 2.

An output file produced by the Id command has execute permission set, unless you specify the -r flag or **-bnox** option or errors were reported while linking. An existing output file is not overwritten if any severe errors occurred, or if the output file was specified as an input file and any errors occurred.

Symbols

The Id command uses the following predefined symbols to provide special address locations and can be declared in C syntax as **extern char** *name*[]. The symbol names are:

Specifies the first location of the program. _text _etext Specifies the first location after the program. data Specifies the first location of the data.

Specifies the first location after the initialized data edata

end or end Specifies the first location after all data. The only way to use these symbols is to take their addresses. If an input file redefines any of these symbols, there may be unpredictable results. An additional predefined symbol, ptrgl, is used by compilers to implement calls using function pointers.

Garbage Collection

By default, the Id command performs garbage collection, deleting control sections (CSECTs) that are not referenced when generating the output file.

A CSECT is an indivisible unit of coding or data. A CSECT references another CSECT if it contains a relocation entry (RLD) referring to a symbol contained in the other CSECT. A referenced CSECT causes all CSECTs it references to be referenced as well. In addition, a CSECT is referenced if it contains exported symbols, symbols specified with the -u flag, or the symbol designated as the entry point with the **-e** flag.

If a symbol is not referenced but is needed in the output file, you can export the symbol, specify the symbol with the -u flag, or suppress garbage collection. To suppress garbage collection, use the -r flag or -bnogc option. To suppress garbage collection for individual object files, use the -bkeepfile option or the -bgcbypass option. Even when garbage collection is suppressed, unreferenced internal symbols are deleted.

Ignored and Unsupported Flags

For compatibility with other versions of the Id command, some flags are recognized but ignored. These flags produce a message stating that the flag and its operand were ignored. An ignored flag does not cause the **Id** command to stop without further processing. The following flags are ignored:

- A Number	-bnostrcmpct	-n
-bfilelist	-bstrcmpct	-N
-bfl	-BNumber	-Q
-bforceimp	-d	-RNumber
-bi	-i	-V Number
-binsert	<pre>-j[Key:]Number</pre>	-x
-bnoforceimp	-k Key:Path	-Y Number

Note: When the -bsvr4 option is present on the Id command line, the -R and -z options are redefined.

Flags that the **Id** command does not support result in an error message. After all unsupported flags are diagnosed, the **Id** command stops without further processing.

Flags

The Id command conforms to the XPG Utility Syntax Guidelines, except that the argument - only applies to the next operand, not to the remaining operands on the command line. For example, in the command line:

```
1d -- -s -v
```

The -s is treated as a filename and the -v is treated as a flag. To have -v treated as a filename, specify: 1d -- -s -- -v

Note: Enter a flag with an operand with or without a space between the flag and the operand. You can specify numeric values in decimal, octal (with a leading 0), or hexadecimal (with a leading 0x or 0X) format. If you specify conflicting flags on the command line, the Id command accepts the latest flag and ignores earlier ones.

-bOption Sets special processing options. This flag can be repeated. For more information on these options, see "Options (-bOptions)" on page 180.

-d [y | n]

When -dy is specified, Id uses dynamic linking; this option is equivalent to the -b so option. When -dn is specified, Id uses static linking; this option is equivalent to the -b nso option. The default is -dy. This option is valid only when the -bsvr4 option is specified.

-DNumber

Sets the starting address for the initialized data (the data section) of the output file to Number. If the specified number is -1, the data section starts immediately after the text section. By default, the data section begins at location 0.

Note: The system loader relocates the data section at run time, so the specified number only affects addresses listed in address maps or printed by utilities such as the dump or

-eLabel

Sets the entry point of the executable output file to Label. The default entry point is start (double underscore start).

-fFileID

Specifies a file containing a list of input files to process. FileID must contain a list of input file names. Each line in FileID is treated as if it were listed separately on the Id command line. Lines in the file can contain shell pattern characters * (asterisk), [(left bracket),] (right bracket), and ? (question mark), which are expanded using the glob subroutine and can designate multiple object files.

-G

Produces a shared object enabled for use with the run-time linker. The -G flag is equivalent to specifying the erok, rtl, nortllib, nosymbolic, noautoexp, and M:SRE options with the **-b** flag. Subsequent options can override these options.

-HNumber

Alians the text, data, and loader sections of the output file so that each section begins on a file offset that is a multiple of Number. If the specified number is 1, no alignment occurs. If the specified number is 0, the loader section is aligned on a word boundary, and the text and data sections are aligned on a boundary so as to satisfy the alignment of all CSECTs in the sections. The default value is 0.

-K

If the specified Number causes any CSECTS to be unaligned within the output file, the Id command issues a warning and the output executable file may not load or run.

Aligns the header, text, data, and loader sections of the output file so that each section begins on a page boundary. This flag is equivalent to specifying -HNumber, where Number is the page size of the machine on which Id is running.

-IName

In dynamic mode, processes the libName.so or libName.a file. In all cases, directories specified by the -L flag or in the standard library directories (/usr/lib and /lib) are searched to find the file. In dynamic mode, the first directory containing either libName.so or libName.a satisfies the search. If both files are found in the same directory, libName.a is used. To preference to libName.so, you must specify the rtl option as well. You can repeat this flag. For more information about dynamic mode, see "Run-time Linking" on page 191.

Note: The first definition of a symbol is kept, even if no reference to the symbol has been seen when the archive is read. In other versions of the Id command, a symbol defined in an archive is ignored if no reference to the symbol has been seen when the archive is read.

-LDirectory

Adds Directory to the list of search directories used for finding libraries designated by the -I (lowercase letter L) flag. The list of directories, including the standard library directories, is also recorded in the output object file loader section for use by the system loader unless you use the -blibpath, -bnolibpath, or -bsvr4 option. You can repeat this

-m or -M

Lists to standard output the names of all files and archive members processed to create the output file. Shared objects and import files are not listed.

-oName

Names the output file Name. By default, the name of the output file is a.out.

-r

Produces a nonexecutable output file to use as an input file in another Id command call. This file may also contain unresolved symbols. The -r flag is equivalent to specifying the erok, noglink, nox, and nogc options with the -b flag. (Subsequent options can override these options.)

-R Path

Valid only when the -bsvr4 option is present on the Id command line. It defines a colon-separated list of directories used to specify library search directories to the runtime linker. Path, if present and not NULL, is recorded in the output file's loader section. Then it is used when linking an executable with shared libraries at runtime. Multiple instances of this option are concatenated together with each *Path* separated by a colon.

Strips the symbol table, line number information, and relocation information when -S

> creating the output file. Stripping saves space but impairs the usefulness of the debuggers. You can also strip an existing executable by using the strip command. Note: Non-shared objects cannot be linked if they are stripped. A shared object can be

stripped, but a stripped, shared object cannot be used when linking statically.

-SNumber Sets the maximum size (in bytes) allowed for the user stack when the output executable

program is run. This value is saved in the auxiliary header and used by the system

loader to set the soft ulimit. The default value is 0.

For more information on large user stacks and 32-bit programs, see "Large Program Support Overview" in AIX 5L Version 5.3 General Programming Concepts: Writing and

Debugging Programs.

-TNumber Sets the starting address of the text section of the output file to Number. The default

value is 0.

Note: The system loader relocates the text section at run time, so the specified number affects only addresses listed in address maps or printed by utilities such as the nm or

the dump command.

-uName Prevents garbage collection of the external symbol Name. If the specified symbol does

not exist, a warning is reported. You can repeat this flag.

Writes additional information about binder command execution to the loadmap file.

-V Writes the version string of Id to standard error (stderr).

-z In the absence of the **-b svr4** option, functions the same as the **-K** flag.

-z defs Forces a fatal error if any undefined symbols remain at the end of the link. This is the

default when an executable is built. It is also useful when building a shared library to assure that the object is self-contained, that is, that all its symbolic references are resolved internally. This option is valid only when the -b svr4 option is specified. It is

equivalent to -b ernotok option.

-z nodefs Allows undefined symbols. This is the default when a shared library is built. When used

> with executables, the behavior of references to such undefined symbols is unspecified. This option is valid only when the -b svr4 option is specified. It is equivalent to -b erok

option.

-z multidefs Allows multiple symbol definitions. By default, multiple symbol definitions occurring

> between relocatable objects (.o files) will result in a fatal error condition. This option suppresses the error condition and allows the first symbol definition to be taken. This

option is valid only when the -b svr4 option is specified.

In dynamic mode only, forces a fatal error if any relocations against the .text section -z text

remain. This option is valid only when the -b svr4 option is specified.

-z nowarntext In dynamic mode only, allows relocations against all mappable sections, including the

.text section. This is the default when building a shared library. This option is valid only

when the -b svr4 option is specified.

-z warntext In dynamic mode only, warns if any relocations against the .text section remain. This is

the default when building an executable. This option is valid only when the -b svr4

option is specified.

-ZString Prefixes the names of the standard library directories with String when searching for

> libraries specified by the -I (lowercase letter L) flag. For example, with the -Z/test and -lxyz flags, the Id command looks for the /test/usr/lib/libxyz.a and /test/lib/libxyz.a files. When the -ZString flag is used, the standard library directories are not searched. This flag has no effect on the library path information saved in the loader section of the output file. This flag is useful when developing a new version of a library. You can repeat

this flag.

The Binder

The **Id** command verifies the command-line arguments and calls the binder (by default the /usr/ccs/bin/bind file), passing a generated list of binder subcommands. The binder program actually links the files. Although the binder is usually called by the Id command, you can start the binder directly. In this case, the binder reads commands from standard input.

Two options affect the calling of the binder. The binder option specifies which binder to call, and the nobind option prevents the Id command from calling a binder. Other binder options affect the binder subcommands that are generated.

If the Id command does not detect any errors in the options or command-line arguments, it calls the binder. The binder is called with a command line of the form:

bind [quiet_opt] [loadmap_opt]

The default value for quiet opt is quiet and the default value for the loadmap opt is the null string, so the default command line is:

/usr/ccs/bin/bind quiet

Options (-bOptions)

The following values are possible for the Options variable of the -b flag. You can list more than one option after the **-b** flag, separating them with a single blank.

Notes:

- 1. In the following list of binder options, two option names separated by the word *or* are synonymous.
- 2. The FileID indicates a path name. You can use either a relative or a full path name.
- 3. For a non-repeatable option that is followed by an argument, you can negate the option using a null argument. That is, specify only the option and the colon.
- 4. If you specify conflicting options, the last one takes precedence.

32	Specifies 32-bit linking mode. In this mode, all input object files must be XCOFF32 files, or an error is reported. XCOFF64 archive members are ignored. For import or export files specifying the mode of certain symbols, 64-bit symbols are ignored. If both -b32 and -b64 options are specified, the last specified option is used. If neither option is specified, the mode is determined from the value of environment variable OBJECT_MODE .
64	Specifies 64-bit linking mode. In this mode, all input object files must be XCOFF64 files, or an error will be reported. XCOFF32 archive members are ignored. For import or export files specifying the mode of certain symbols, 32-bit symbols are ignored. If both -b32 and -b64 options are specified, the last specified option is used. If neither option is specified, the mode is determined from the value of environment variable OBJECT_MODE .
asis	Processes all external symbols in mixed case. This is the default. To process all external symbols in uppercase, see the caps option that follows.

autoexp

Automatically exports some symbols from the output module without having to list them in an export file. (This option does not export all symbols from the output module. Use the -bexpall option to export all symbols.) This is the default. Use this option when linking a main program. The linker assumes that you are linking a main program when you do not specify a module type (with the M or modtype option) beginning with S and you do not use the noentry option.

When you use the autoexp option, if any shared object listed on the command-line imports a symbol from the special file. (dot), and the module being linked contains a local definition of the symbol, the symbol is exported automatically.

Other symbols are also exported automatically when you link with the rtl option. If a symbol defined in the module being linked has one or more additional definitions exported from a shared object listed on the command-line, and if any of the definitions is a BSS symbol, the symbol is exported automatically. If the definition in the module being linked is a BSS symbol, the symbol is exported with the nosymbolic attribute. Otherwise, the symbol is exported with the symbolic attribute. If the symbol is listed in an export file with another export attribute, the explicit attribute is used.

If the autoexp option would automatically export a symbol, but the symbol is listed in an export file with the list attribute, the symbol is not exported. Imports symbols from any shared objects specified as input files. The shared objects are referenced but not included as part of the output object file. This is the default.

Automatically load archive member when the **-brtl** option is used.

Generates extra code if the size of thread-local storage in the output object or program is larger than 64 KB and a compiler was used that generates direct references to local-exec or local-dynamic thread-local variables. Extra code is needed for every direct reference to a thread-local variable that cannot be addressed with a 16-bit offset. Because a program containing extra code might have poor performance, it is better to reduce the number of thread-local variables using direct references than to use the option. The default option is the nobigtls option.

Generates extra code if the size of the table of contents (TOC) is greater than 64KB. Extra code is needed for every reference to a TOC symbol that cannot be addressed with a 16-bit offset. Because a program containing generated code may have poor performance, reduce the number of TOC entries needed by the program before using this option. The default is the **nobigtoc** option.

Writes a copy of the binder commands generated by the **Id** command to *FileID*. You can redirect the resultant file as standard input to the binder program when the binder program is called as a standalone program. By default, no file is produced.

Uses FileID as the binder called by the Id command. The default binder is the /usr/ccs/bin/bind file.

Writes a copy of the binder program arguments to FileID. You can use the resultant file to start the binder program as a standalone program. By default, no file is produced.

Writes an address map of the output object file to FileID. Symbols are sorted by section and then by address. For each symbol listed in the map, references from the symbol to other symbols are listed. By default, no file is produced. To learn more about the calls option, see "Address Maps" on page 194.

Processes all external symbols in uppercase. The default is the **asis** option.

autoimp or so

autoload: path/file(member) bigtls

bigtoc

bindcmds:FileID

binder: FileID

bindopts:FileID

C:FileID or calls:FileID

caps

cdtors[:[incl][:[nnn][:order]]]

The linker gathers information about C++ static constructor or destructor functions and saves this information in the output file. The incl suboption tells the linker which archive members to search when creating the saved information. The possible values are:

Searches all members of all archives for constructor or destructor functions. This is the default.

Searches for constructor or destructor functions only if the member is mbr included in the output file. Using the mbr value is equivalent to using the -qtwolink and -bsvr4 options.

Searches for the constructor or destructor functions only in csects csect included from the archive. Using the csect value is equivalent to using the -qtwolink option without the -bsvr4 option.

The nnn suboption specifies the priority of the output module. This priority is used to control the order in which modules are initialized, in case a program loads multiple modules at the same time. (The priority is ignored if the output file is a program and not a shared object.) The priority can be in the range from -2³¹ to 2³¹-1. The default priority is 0. Values in the range from -2³¹ to -2³¹+1023 are reserved for C++ runtime initialization.

The *order* suboption specifies the order in which individual constructor or destructor functions are called, for all functions with the same priority. The possible values are:

- s Sorts in an arbitrary order based on function names. This is the default, and is compatible with the order that the XL C++ compiler uses.
- С Sorts in link order. Constructor or destructor functions in the first input file are initialized first. In archives, functions in the first member are initialized first.
- Sorts in reverse link order. Constructor or destructor functions in the last r input file are initialized first. In archives, functions in the last member are initialized first.

You can specify this option multiple times, but the last suboption that you specify is used. An unspecified suboption does not affect the current or default value. For example, -bcdtors:csect:20:s -bcdtors:::r is the same as -bcdtors:csect::20:r. The default is **-bnocdtors**. If **-bcdtors** is specified, this is equivalent to -bcdtors:all:0:s.

Notes:

- 1. If necessary, the XL C++ compiler produces this option automatically.
- 2. Functions specified with the **-binitfini** option are invoked independently of static constructor or destructor functions. For more information about the order of initialization, see the **dlopen** subroutine.

Combines multiple relocation entries (RLDs) at the same address into a single RLD when possible. This is the default.

Uses the cror 15,15,15 (0x4def7b82) instruction as the special no-op instruction following a call instruction. The default value is ori 0, 0, 0 (0x60000000). See the **nop** option.

Use this option when linking object files on the current level of the system that you intend to relink on AIX 3.1.

Uses the cror 31,31,31 (0x4ffffb82) instruction as the special no-op instruction following a call instruction. The default value is ori 0, 0, 0 (0x60000000). See the **nop** option.

Use this option when linking object files on the current level of the system that you intend to relink on AIX 3.2.

comprid or crid

cror15

cror31

D: Number [/dsa] or maxdata: Number[/dsa]

datapsize:psize

Sets the maximum size (in bytes) allowed for the user data area (or user heap) when the executable program is run. This value is saved in the auxiliary header and used by the system loader to set the soft data ulimit. The default value is 0. When this option is used, the specified number of bytes are reserved for the user data area. The program may not explicitly map objects, using shmat or mmap functions, to virtual addresses that are reserved for the user data area.

For 32-bit programs, the maximum value allowed by the system is 0x80000000 for programs running under Large Program Support and 0xD0000000 for programs running under Very Large Program Support. See "Large Program Support Overview" in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs. When a non-zero value is specified, the user data area begins in segment 3, and the program uses as many segments as neccessary to satisfy the maxdata value specified.

For 64-bit programs the maxdata option provides a guaranteed maximum size for the programs data heap. Any value can be specified but the data area cannot extend past 0x06FFFFFFFFFFF regardless of the maxdata value specified. Requests psize page sizes in bytes for data. The value can be specified as a decimal, hexadecimal, or octal number. The number specifications are the same as in C programming language. Additionally, the page sizes can be specified as a number followed by a one-character suffix:

- · k or K for kilo or 0x400 bytes
- m or M for mega or 0x100000 bytes
- · g or G for giga or 0x40000000 bytes
- t or T for tera or 0x1000000000 bytes
- p or P for peta or 0x400000000000 bytes
- x or X for exo or 0x100000000000000 bytes

For example, either -b datapsize:16k or -b datapsize:0x4000 will request 0x4000 for data and set the F VARPG bit in the XCOFF header.

dbg:Option or debugopt:Option

Sets a special debugging or control option. By default, no debug option is set.

The dbg:loadabs or debugopt:loadabs option is used to indicate that the output program is loaded at the same address as the address specified by the -T and -D flags. In this case, a branch-absolute instruction is never changed to a (relative) branch instruction even if its target is a relocatable symbol. Similarly, a branch instruction is never changed to a branch-absolute instruction.

Deletes all symbols in a CSECT if any symbol in the CSECT was defined by a previously read object file. This option prevents more than one instance of the same function from existing in the same program. For example, if **a.o** defines function a() and b.o defines functions a() and b(), linking a.o and b.o with the -bdelcsect option deletes symbols a() and b() from b.o. Thus, two instances of a() do not exist. The default is the nodelcsect option.

Cause the linker to process subsequent shared objects in dynamic mode. This is the default. In dynamic mode, shared objects are not statically included in the output file. Instead, the shared objects are listed in the loader section of the output file. When you specify the rtl option and dynamic mode is in effect, files ending in .so as well as .a satisfy searches for libraries specified with the -I (lowercase L) flag. When both are in effect, preference is given to .so instead of .a when present in same directory. Otherwise, if only dynamic is set and not rtl; preference is given to .a instead of .so.s

Exports the external symbols listed in the file FileID. Exported symbols are listed in the loader section of the output file. There is no default export file. When the svr4 option is used, the E:FileID option cancels any expall or expfull options. Reports an error if there are any unresolved external references. This is the default.

Produces the output object file without errors even if there are unresolved external references. The default is the ernotok option.

delcsect

dynamic or shared

E:FileID or export:FileID

ernotok or f

erok

errmsg

Writes error messages to standard error if the error level of the message is greater than or equal to the value of the halt option and the quiet option is used or standard output is redirected. This is the default.

ex1:FileID, ex2:FileID, ex3:FileID, ex4:FileID, and ex5:FileID

Provide user exits in the typical binder subcommand sequence. Each file specified by FileID must contain a list of binder subcommands, which will be run as follows:

ex1:FileID

Before reading any InputFiles

ex2:FileID

Immediately before symbol resolution

ex3:FileID

Immediately after symbol resolution

ex4:FileID

Immediately before writing the output file

ex5:FileID

Immediately after writing the output file

Exports all global symbols, except imported symbols, unreferenced symbols defined in archive members, and symbols beginning with an underscore (_). You can export additional symbols by listing them in an export file or using the expfull option. This option does not affect symbols exported by the autoexp option.

When you use this option, you might be able to avoid using an export file. On the other hand, using an export file provides explicit control over which symbols are exported, and allows you to use other global symbols within your shared object without worrying about conflicting with names exported from other shared objects. The default is **noexpall**.

Exports all global symbols other than imported symbols. Exported global symbols include unreferenced symbols defined in archive members, symbols beginning with an underscore (_), and the module's entry point. This option does not affect symbols exported by the autoexp option. The default is noexpfull unless the svr4 option is used.

Functions the same as the **E**:*FileID* option. Functions the same as the ernotok option.

Forces read-only CSECTs that contain references to imported symbols to become read-write. The default is noforceimprw.

Performs garbage collection. Use the nogc, gcbypass, or keepfile option to prevent garbage collection for some or all object files. This is the default.

Specifies the number of files to bypass when garbage collecting if the gc option is specified. This option is ignored if the **nogc** option is used. If *Number* is 0, this option is equivalent to the gc option and garbage collection is performed for all files. The default value is 0.

Uses the global linkage prototype code specified by FileID. Global-linkage interface code is generated for each imported or undefined function. In 32-bit mode, the default is the /usr/lib/glink.o file. In 64-bit mode, the default is the /usr/lib/glink64.o file.

Specifies the maximum error level for binder command processing to continue. The default value is **4**. If any binder subcommand has a return value greater than Number, no additional binder subcommands are processed. If the halt level value is 8 or greater, the output file may not be executable if it is produced at all. Return values are:

n No error

4 Warning

8 Error

12 Severe error

16 Internal program error

expall

expfull

export: FileID

forceimprw

gcbypass:Number

glink:FileID

h: Number or halt: Number

I:FileID or import:FileID initfini:[Initial] [:Termination] [:Priority]

(Uppercase i) Imports the symbols listed in *FileID*. There is no default import file. Specifies a module initialization and termination function for a module, where *Initial* is an initialization routine, *Termination* is a termination routine, and *Priority* is a signed integer, with values from -2,147,483,648 to 2,147,483,647. You must specify at least one of *Initial* and *Termination*, and if you omit both *Termination* and *Priority*, you must omit the colon after *Initial* as well. If you do not specify *Priority*, 0 is the default. This option can be repeated.

This option sorts routines by priority, starting with the routine with the smallest (most negative) priority. It invokes initialization routines in order, and termination routines in reverse order.

This option invokes routines with the same priority in an unspecified order, but if multiple **initfini** options specify the same priority and both an initialization and termination routine, it preserves the relative order of the routines. For example, if you specify the options **initfini:i1:f1** and **initfini:i2:f2**, then function **i1** and **i2** are invoked in an unspecified order, but if **i1** is invoked before **i2** when the module is loaded, **f2** will be invoked before **f1** when the module is unloaded.

Notes

1. The priorities in the following inclusive ranges are reserved:

```
-2,147,483,640 to -2,147,000,000

-1,999,999,999 to -1,000,000,000

-99,999,999 to -50,000,000

0

50,000,000 to 99,999,999

1,000,000,000 to 1,999,999,999

2,147,000,000 to 2,147,483,640
```

Functions specified with the -binitfini option are invoked independently of static constructor or destructor functions. For more information about the order of initialization, see the dlopen subroutine.

For shared objects listed on the command-line, rather than specified with the -I flag, use the path component when listing the shared object in the loader section of the output file. This is the default.

Prevents garbage collection of *FileID*. By default, the binder deletes unreferenced CSECTS in all files. You can repeat this option.

Enables lazy loading of a module's dependent modules. This option adds a **-Irtl** option following other flags and options. If the **-brtl** option is specified, the **-blazy** option is ignored and lazy loading is not enabled.

When a module is linked, a list of its dependent modules is saved in the module's loader section. The system loader automatically loads the dependent modules after the module is loaded. When lazy loading is enabled, loading is deferred for some dependents until a function is called in the module for the first time.

A module is lazy loaded when all references to the module are function calls. If variables in the module are referenced, the module is loaded in the typical way. **Note:** Be careful while comparing function pointers if you are using lazy loading. Usually a function has a unique address to compare two function pointers to determine whether they refer to the same function. When using lazy loading to link a module, the address of a function in a lazy loaded module is not the same address computed by other modules. Programs that depend upon the comparison of function pointers should not use lazy loading.

For more information about lazy loading, refer to "Shared Libraries and Lazy Loading" in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs.

(Lowercase L)Writes each binder subcommand and its results to *FileID*. By default, no file is produced.

ipath

keepfile:FileID

lazy

I:FileID or loadmap:FileID

libpath:Path Uses Path as the library path when writing the loader section of the output file.

> Path is neither checked for validity nor used when searching for libraries specified by the -I flag. Path overrides any library paths generated when the -L flag is used.

If you do not specify any -L flags, or if you specify the nolibpath option, the default library path information is written in the loader section of the output file. The default library path information is the value of the **LIBPATH** environment

variable if it is defined, and /usr/lib:/lib, otherwise.

Functions the same as the **!:** FileID option.

Sets the F LPDATA bit in the XCOFF header of the executable file. When this bit is

set, the process is going to request large pages for its data.

M:ModuleType or modtype: Module Type

map:FileID or R:FileID

loadmap: FileID

Ipdata

Sets the two-character module-type field and the shared object flag in the object file. The module type is not checked by the binder, but it should be set to one of the following values:

1L Single use. Module requires a private copy of the data section for each load.

RE Reusable. Module requires a private copy of the data area for each process dependent on the module.

RO Read only. Module is read-only, and can be used by several processes at one

If an **S** prefix is used on any of the preceding options, the shared flag in the object file is set. The system loader attempts to share a single instance of the data section of an RO module. Otherwise, the module type is ignored by the system loader. The default value is 1L.

UR Sets the SGETUREGS flag for the linker. When the SGETUREGS flag is set, the contents of the registers are stored in a buffer. This option is used by coredump

Writes an address map of the output object file to FileID. Symbols are sorted by section and then by address. By default, no file is produced. To learn more about the map option,

see "Address Maps" on page 194.

Functions the same as the **D**: Number[/dsa] option. maxdata: Number[/dsa] maxstack: Number or Functions the same as the -S flag.

S:Number

modtype: Module Type Functions the same as the **M**:ModuleType option. nl or noloadmap

Does not write the binder subcommands and their results to a load map file. This is the

noautoexp Prevents automatic exportation of any symbols. The default is the **autoexp** option. Links any unstripped, shared objects as ordinary object files. When you use this option, noautoimp or nso

> the loader section of shared objects is not used. The default is the **autoimp** or **so** option. Note: By using either of these flags, you statically link a shared object file into an application. Any application that is statically linked is not binary portable from any fix or

release level to any other fix or release level.

Generates a severe error message if the compiler generates direct references to nobigtls

thread-local variables and the relocation to one of the variables overflows because the size of the thread-local storage is greater than 64 KB. If an output file is produced, it will not

run correctly. The **nobigtls** option is the default option.

Generates a severe error message if the size of the TOC is greater than 64 KB. If an nobigtoc

output file is produced, it will not execute correctly. This is the default.

nobind Omits calling the binder. Instead, the Id command writes the generated list of binder

subcommands to standard output. By default, the Id command calls the binder.

nocdtors Does not gather static constructor or destructor functions. This is the default.

nocomprid or nocrid Does not combine multiple relocation entries (RLDs) at the same address into a single

RLD. The default is the **comprid** or **crid** option.

Allows all symbols in the CSECT to be considered during symbol resolution, even if some nodelcsect

symbol in the CSECT is defined in a previously read object file. For more information, see the **delcsect** option. The **nodelcsect** option is the default.

noexpall

Does not export symbols unless you list them in an export file or you export them with the autoexp option. This is the default.

noexpfull

Does not export symbols unless you list them in an export file or you export them with the autoexp option. This is the default, unless the svr4 option is used.

noentry

Indicates that the output file has no entry point. To retain any needed symbols, specify them with the -u flag or with an export file. You can also use the -r flag or the nogc or gcbtpass options to keep all external symbols in some or all object files. If neither the **noentry** nor the **nox** option is used and the entry point is not found, a warning is issued. This warning is suppressed when the **svr4** option is used.

noerrmsq

Does not write error messages to standard error. Use this option if you specify the noquiet option and you pipe standard output to a command such as tee or pg.

noforceimprw

Allows read-only CSECTs to reference imported symbols. This is the default.

nogc

Prevents garbage collection. CSECTs in all object files that contain global symbols are kept, whether they are referenced or not. The default is the gc option.

noglink

Prevents the Id command from inserting global linkage code. By default, the binder inserts the global linkage code.

noipath

For shared objects listed on the command-line, rather than specified with the -I flag, use a null path component when listing the shared object in the loader section of the output file. A null path component is always used for shared objects specified with the -I flag. This option does not affect the specification of a path component by using a line beginning with #! in an import file. The default is the **ipath** option.

nolibpath

Overrides any previous library path generated by the -L flag or specified by the libpath option. Instead, the default library path information is written in the loader section of the output file. The default library path information is the value of the LIBPATH environment variable if it is defined, and /usr/lib:/lib otherwise.

noloadmap

Functions the same as the nl option.

nolpdata

Clears the F LPDATA bit in the XCOFF header of the executable file. When this bit is not set, the process is going to use small (regular) pages for its data.

nom

Does not list the object files used to create the output file. This option overrides the -m flag. This is the default.

noobjreorder

Does not use the depth-first CSECT reordering logic. The CSECTs in the output file are arranged in the same order that the object files and library files were specified on the command line, except as follows:

- CSECTs are placed in their correct text, data, or BSS section of the object file, based on the storage-mapping class field of each CSECT.
- All CSECTs with a storage-mapping class of XMC_TC (TOC address constant) or XMC_TD (TOC variable) are grouped together.

nop:Nop

If both the noobjreorder and noreorder options are specified, the noreorder option takes precedence. The default is the reorder option.

Specifies the no-op instruction used after branches to local routines. Nop can be one of the special values cror15, cror31, ori, or an eight-digit hexadecimal number. The ori instruction is the default. Specifying the -bnop:cror15 option is equivalent to specifying the -bcror15 option; specifying the -bnop:cror31 option is equivalent to specifying the -bcror31 option. If you specify one of the special nop options, all previous nop options are overridden

If Nop is an eight-digit hexadecimal number, it specifies an arbitrary machine instruction. This machine instruction overrides any previously specified special value for Nop instruction. When you use this form, you can repeat this option.

The last machine instruction specified is the instruction generated by the binder after intramodule branches. Other specified machine instructions are recognized as no-op instructions, but are converted to the preferred no-op instruction.

Writes each binder subcommand and its results to standard output. The default is the quiet option.

noquiet

noreorder Does not reorder CSECTs, except to combine all XMC_TC (TOC address constant) and

XMC_TD (TOC variable) CSECTs and place them in the data section, and combine all BSS symbols and place them in the bss section. All other CSECTs are placed in the text section, so text and data are mixed in the output file. When the **noreorder** option is used, the text section of the output file may no longer be position-independent and the system loader will not load a module if the text section is not position-independent. Therefore, avoid using this option for programs and kernel extensions. If both **noobjreorder** and **noreorder** options are specified, the **noreorder** option takes precedence. The default is

the reorder option.

nortl Disables run-time linking for the output file. This option implies the **nortllib** and

nosymbolic- options. Furthermore, additional actions described under the rtl option are

not taken. This is the default unless the svr4 option is used.

nortllib Does not include a reference to the run-time linker. If a main program is linked with this

option, no run-time linking will take place in the program, regardless of the way any shared modules were linked that are used by the program. This is the default unless the ${\bf svr4}$

option is used.

norwexec Specifies that if the system's **sed_config** setting is not off, the process' private data areas

will have non-execute permission.

nostabsplit Prevents the debug section to be written to an alternate output file with the extension

.stab. This is the default setting.

nostrip Does not generate a stripped output file. Thus, the symbol table and relocation information

is written in the output file. This option overrides the -s flag. This is the default.

nosymbolic Assigns the **nosymbolic** attribute to most symbols exported without an explicit attribute.

For more information, see "Attributes of Exported Symbols" on page 193. The default is

the **nosymbolic-** option.

nosymbolic- Assigns the **nosymbolic-** attribute to most symbols exported without an explicit attribute.

For more information, see "Attributes of Exported Symbols." This is the default.

notextro or **nro**Does not check to ensure that there are no load time relocation entries for the text section

of the output object file. This is the default.

notmprelname The binder does not check for general instantiations.

Note: This option is only needed for 32-bit mode. This option is ignored when building

64-bit objects.

notypchk Does not check function-parameter types between external functional calls. The default is

the typchk option.

nov Does not write additional information to the load map file. This option is the default and

overrides the -v flag.

noweaklocal Resolves weak symbols using normal search order. This option overrides the weaklocal

option. It is the default option.

nox Does not make the output file executable. Neither the auxiliary header nor the loader

section is written. Flags and options that specify values written in the auxiliary header or loader section have no effect when this option is used. The default is the \mathbf{x} option.

nro Functions the same as the notextro option.nso Functions the same as the noautoimp option.

pD:Origin Specifies Origin as the address of the first byte of the file page containing the beginning of

the data section. For example, if the data section begins at offset 0x22A0 in the object file, and pD:0x20000000 is specified, the first byte of the data section is assigned address

0x200002A0. This assumes a page size of 4096 (0x1000) bytes.

pT: Origin Specifies Origin as the address of the first byte of the file page containing the beginning of

the text section. For example, if the text section begins at offset 0x264 in the object file, and pT:0x10000000 is specified, the first byte of the text section is assigned address

0x10000264.

quiet Does not write binder subcommands and their results to standard output. This is the

default.

R: FileID Functions the same as the **map:** FileID option.

r or reorder Reorders CSECTs as part of the save command processing. The reorder process

arranges CSECTs of the same storage-mapping class by proximity of reference. This is the

default.

rename: Symbol, NewName Renames the external symbol *Symbol* to *NewName*. In effect, it is as if all definitions and references to *Symbol* in all object files were renamed to *NewName* before the files were processed. By default, symbols are not renamed.

reorder ro or textro

rtl

Functions the same as the r option.

Ensures that there are no load time relocation entries for the text section of the resultant object file. The default is the **nro** option.

Enables run-time linking for the output file. This option implies the **rtllib** and **symbolic** options.

When dynamic mode is in effect (see the **dynamic** and **static** options), the **rtl** option allows input files specified with the **-l** flag to end in **.so** as well as in **.a**.

All input files that are shared objects are listed as dependents of your program in the output files loader section. The shared objects are listed in the same order as they were specified on the command line.

A shared object contained in an archive is only listed if the archive specifies automatic loading for the shared object member. You specify automatic loading for an archive member **foo.o** by creating an import file with the following lines:

autoload
#! (foo.o)

and adding the import file as a member to the archive. You may also specify automatic loading for an archive member foo.o by using the **-bautoload** option:

-bautoload:<archive name>(foo.o)

You may specify additional archive members with additional -bautoloads.

If the first line of an import file begins with #! (number sign, exclamation point), you can specify the file on the command line as an ordinary *InputFile*. Otherwise, you must use the **-bl** or **-bimport** option to specify the import file.

Includes a reference to the run-time linker. The run-time linker is defined in **librtl.a**, and an implicit **-Irtl** flag is added automatically to the command line. This option (implied by the **rtl** option) must be used when linking a main program or no run-time linking will occur. Shared objects do not have to be linked with this option. The default is the **nortllib** option unless the **svr4** option is used.

Specifies that the execute permissions of the process' private data areas will be determined according to the system's **sed_config** setting. This is the default.

Specifies that the process' private data areas will have execute permission, regardless of the system's **sed_config** setting.

Functions the same as the **-S** flag.

Writes an address map of the object file to *FileID*. Symbols are listed alphabetically. For each symbol listed in the map, references from the symbol to the other symbols are listed. By default, no file is produced. To learn more about the **scalls** option, see "Address Maps"

on page 194.

Functions the same as the **dynamic** option.

Writes an address map of the object file to *FileID*. Symbols are listed alphabetically. By default, no file is produced. To learn more about the **smap** option, see "Address Maps"

that follows.

Functions the same as the autoimp option.

rtllib

rwexec

rwexec_must

S:Number scalls:FileID

shared smap:FileID

so

stabcmpct:Level

Specifies the level of compaction for stabstrings in the debug section. Stabstrings are strings that are longer than eight characters. Each substring in the symbol table has its own offset in the debug section. The following values are valid for *Level*:

- Does not compact. Separate copies of duplicate stabstrings are written to the debug section.
- Deletes duplicates. Each stabstring is written once to the .debug section. Duplicate stabstrings in the symbol table specifies the same offset into the debug section.
- 2 Renumbers the stabstrings and deletes most duplicates. (In some instances, multiple stabstrings can exist. They describe the same type but use different type numbers.) The scope of a type number is the entire output file, rather than a single input file as indicated by a C_FILE symbol table entry.

If the binder does not recognize a stabstring, it returns an error message and the resulting executable file does not have valid stabstrings. The rest of the file is unaffected by the error.

stabsplit stackpsize:psize Causes the debug section to be written to an alternate output file with the extension .stab. Requests psize page sizes in bytes for process main thread stack. The value can be specified as a decimal, hexadecimal, or octal number. The number specifications are the same as in C programming language. Additionally, the page sizes can be specified as a number followed by a one-character suffix:

- · k or K for kilo or 0x400 bytes
- m or M for mega or 0x100000 bytes
- g or G for giga or 0x40000000 bytes
- t or T for tera or 0x1000000000 bytes
- p or P for peta or 0x400000000000 bytes
- x or X for exo or 0x100000000000000 bytes

For example, either -b stackpsize:16k or -b stackpsize:0x4000 will request 0x4000 for process main thread stack and set the F_VARPG bit in the **XCOFF** header.

Causes the linker to process subsequent shared objects in static mode. In static mode, shared objects are statically linked in the output file. Furthermore, files ending in .so are not found when searching for libraries specified with the -I flag.

This option changes the meaning of some other options on the command line and the standard behavior of the linker. It has the following effect on the linker:

- · -b rtl is set
- -b rtllib is set only when building an executable or if not set explicitly to -b nortllib
- -b symbolic is set only when building an executable or if not set explicitly by one of -b symbolic, -b nosymbolic, or -b nosymbolic-
- -b expfull is set only when neither -b E nor -b export are present
- · -b noexpall is set
- · -d, instead of being ignored, is redefined and can assume two values: -dy or -dn
- -R, instead of being ignored, takes one suboption that defines the runtime library search path
- -z, instead of being a synonym of the -K option, takes either defs, nodefs, multidefs, text, nowarntext, or warntext, as a suboption
- directories specified with the -L option are not included in the runtime libraries search path

Writes an address map of the object file to *FileID*. Symbols are listed alphabetically. For each symbol listed in the map, references to the symbol from other symbols are listed. By default, no file is produced. To learn more about the **sxref** option, see "Address Maps." that follows.

symbolic

sxref:FileID

Assigns the **symbolic** attribute to most symbols exported without an explicit attribute. For more information, see "Attributes of Exported Symbols" that follows. This is the default when the **svr4** option is used; otherwise, the default is the **symbolic**- option.

static

svr4

190

textro textpsize:psize

Same as the **ro** option.

Requests psize page sizes in bytes for text. The value can be specified as a decimal, hexadecimal, or octal number. The number specifications are the same as in C

programming language. Additionally, the page sizes can be specified as a number followed by a one-character suffix:

- · k or K for kilo or 0x400 bytes
- m or M for mega or 0x100000 bytes
- · g or G for giga or 0x40000000 bytes
- t or T for tera or 0x10000000000 bytes
- p or P for peta or 0x400000000000 bytes
- x or X for exo or 0x100000000000000 bytes

For example, either -b textpsize:16k or -b textpsize:0x4000 will request 0x4000 for text

and set the F VARPG bit in the XCOFF header.

tmplrename Specifies that the binder should check for general instantiations. The binder checks for any

symbol of the form __tfNNxxx_name and renames the symbol to name. The default is

-bnotmplrename.

Note: This option is only needed for 32-bit mode. This option is ignored when building

64-bit objects.

typchk Performs function-parameter type checking between external functional calls.

Parameter-type checking information can be included in object files by compilers and

assemblers. This is the default.

For more information on type checking, see the "XCOFF (a.out) File Format" in AIX 5L

Version 5.3 Files Reference.

weaklocal Specifies that weak symbols are searched for first in the object files where they are

referenced. If the symbols are not found there, the normal search order is resumed.

Makes the output file executable, if no errors exist. This is the default option. Y

X or xref:FileID Writes an address map of the object file to FileID. Symbols are sorted by section and then

> by address. For each symbol listed in the map, references to the symbol from other symbols are listed. By default, no file is produced. To learn more about the xref option,

see "Address Maps" that follows.

Run-time Linking

By default, references to symbols in shared objects are bound at link time. That is, the output module associates an imported symbol with a definition in a specific shared object. At load time, the definition in the specified shared object is used even if other shared objects export the same symbol.

You can cause your program to use the run-time linker, allowing some symbols to be rebound at load time. To create a program that uses the run-time linker, link the program with the -brtl option. The way that shared modules are linked affects the rebinding of symbols.

You can build shared objects enabled for run-time linking by using the -G flag. You can fully enable run-time linking for existing shared objects by relinking them with the rtl_enable command, as long as they have not been stripped.

Import and Export File Format (-bl: and -bE: Flags)

Each line within an import or export file must list a single symbol, followed by optional keywords or an optional address. Keywords are svc, svc32, svc3264, svc64, syscall, syscall32, syscall3264, syscall64, symbolic, nosymbolic, nosymbolic-, list, cm, bss, and weak. Only the keyword weak may be used in conjunction with another keyword.

In an import file, you can specify an address after the symbol to map data CSECTs to a shared memory segment and eliminate the need to use the assembler. You can also use one of the keywords cm, bss, or weak to specify the storage class of an imported symbol. When the autoexp option is used, the storage class of an imported symbol affects which symbols are automatically exported. If any other keyword is specified in an import file, the keyword is ignored.

In an export file, you can use the **svc** or **syscall** keyword after a name to indicate that it is a system call. This is needed when linking kernel extensions. You can use the symbolic, nosymbolic, or nosymbolickeyword to associate an attribute with an exported symbol. For more information, see "Attributes of Exported Symbols" on page 193. You can use the list keyword to cause a symbol to be listed in the loader section of the output file, although it will not be marked as an exported symbol. This can be used for applications that want to process some symbols at run time. Listed symbols are not processed by the system loader or the run-time linker. A symbol address and the keywords cm and bss are ignored in an export file. The weak keyword can be used to specify weak symbol binding, and may be used with another attribute.

The Id command treats import and export files according to the following guidelines:

- A blank line is ignored.
- A line beginning with an * (asterisk) is a comment and is ignored.
- A line beginning with a # (#, blank space) provides operands to the **setopt** binder subcommand (-bdbg: Option). For example, a line containing # verbose causes the binder to list each symbol as it is read from the file. These option settings are active only while processing the file. The # 32, # 64, # no32, and # no64 options can be used to specify whether the listed symbols should be used for 32-bit links, 64-bit links, or both.

32-bit and 64-bit Import File Options

This option is used in an import or export file to specify that subsequent symbols should be 32 processed when linking in 32-bit mode, but ignored when linking in 64-bit mode. If no 32 or 64 option is specified, all symbols are processed in both 32- and 64-bit modes. 64 This option is used in an import or export file to specify that subsequent symbols should be processed when linking in 64-bit mode, but ignored when linking in 32-bit mode. If no 32 or 64 option is specified, all symbols are processed in both 32- and 64-bit modes. Override a previous 32 or 64. Subsequent symbols are processed in both 32- and 64-bit modes. **no32** or **no64**

 When processing an import file, a line beginning with a #! (#, exclamation point) provides the shared library name to be associated with subsequent import symbols. The line can occur more than once and applies to subsequent symbols until the next line beginning with #! is read. This file name information is placed in the loader section of the XCOFF object file. It is used by the system loader to locate the appropriate object file at execution time. If the import file name is ipath/ifile (imember), the file name placed in the loader section is determined based on the import file name and the contents of the #! line of the import file, as follows:

#! (Nothing after the #!) Use null path, null file, and null number. This is treated as a deferred import by the system loader. #! () Use ipath, ifile, and imember. This line can be used if the import file is specified as an InputFile parameter on the command line. The file must begin with #! in this case. This line can also be used to restore the default name if it was changed by another #! line.

#! path/file (member) Use the specified path, file, and member.

#! path/file Use the specified path and file, and a null member.

#! file Use a null path, the specified file, and a null member. At run time, a list of directories is

searched to find the shared object.

#! (member) Use ipath, ifile, and the specified member. At run time, a list of directories is searched to

find the shared object.

Use a null path and specified file and member. At run time, a list of directories is searched to #! file (member)

find the shared object.

(A single dot) This name refers to the main executable. Use this file name when you are #!. creating a shared object that imports symbols from multiple main programs with different names. The main program must export symbols imported by other modules, or loading will fail.

This import file name can be used with or without the run-time linker.

#! .. (Two dots) Use this name to list symbols that will be resolved by the run-time linker. Use this file name to create shared objects that will be used by programs making use of the run-time linker. If you use a module that imports symbols from .. in a program that was not linked with the rtllib option, symbols will be unresolved, and references to such symbols will result in undefined behavior.

To automatically load archive members when the **-brtl** option is used, you can create an import file as follows. If **shr.so** is a shared object in an archive, create an import file:

autoload #! (shr.so)

You can list additional member names on additional lines, if appropriate. You do not need to list symbol names in the import file because the symbols imported from shr.so will be read from shr.so itself.

For more information on creating a shared library, see "How to Create a Shared Library" in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs. For more information on loading and binding, see the load subroutine in AIX 5L Version 5.3 Technical Reference: Base Operating System and Extensions Volume 1.

Attributes of Exported Symbols

When you use run-time linking, a reference to a symbol in the same module can only be rebound if the symbol is exported with the proper attribute. References to symbols with the symbolic attribute cannot be rebound. References to symbols with the nosymbolic attribute can be rebound. References to symbols with the nosymbolic- attribute can be rebound if the symbols are variables. For function symbols, calls using a function pointer can be rebound, while direct function calls cannot be rebound. The **nosymbolic**attribute is the default and is provided for compatibility with previous versions of the operating system, but its use is not recommended.

If you are not using the run-time linker, avoid using the nosymbolic attribute because intra-module function calls will be made indirectly through a function descriptor using global-linkage code. Otherwise, the attribute of exported symbols has no effect for modules used with programs that do not use the run-time linker.

You can specify an explicit export attribute for symbols listed in an export file. Most symbols without an explicit attribute are exported with the default export attribute, as specified with the symbolic, nosymbolic, or nosymbolic- options.

The weak export attribute will mark the associated symbol's mapping type with L WEAK in the loader section.

Imported symbols may only have the weak export attribute. If a symbol is imported from another module, all references to the symbol can be rebound. However, if a symbol is imported at a fixed address, all references are bound to this fixed address and cannot be rebound by the run-time linker. The system loader must resolve deferred imports. The run-time linker never resolves or rebinds references to deferred imports.

For exports of non-imported symbols, the following rules are used.

- If a symbol has the list attribute, it is listed in the loader section symbol table, but the L_EXPORT flag is not set in the symbol table entry. The run-time linker ignores such symbols.
- If a symbol was exported with an explicit attribute, the explicit attribute is used.
- If the symbol is a BSS symbol, it is exported with the nosymbolic attribute.

 Otherwise, the symbol is exported with the global attribute, as specified by the symbolic, nosymbolic, or **nosymbolic-** option. The default global attribute is **nosymbolic-**.

Address Maps

The Id command generates address maps, listing the layout of symbols in the output object file. If you use the map (or R) option, unresolved symbols and imported symbols are listed first, followed by the symbols in each section in address order. If you use the calls (or C) option, each symbol that is listed is followed by a list of references from that symbol to other symbols. If you use the xref (or X) option, each symbol that is listed is followed by a list of references to that symbol from other symbols. If you use the **smap**, scalls, or sxref option, the address map contains the same information as listed by the map, calls, or **xref** option, respectively, but symbols are listed in alphabetical order.

Internal symbols, with a storage class C HIDEXT, are printed with the characters < and > (angle brackets) surrounding the symbol name. Names of external symbols, with a storage class C_EXT, are printed without the angle brackets, and those with a storage class of C_WEAKEXT, are printed with the characters { and } surrounding the symbol name.

Information listed about each symbol includes:

- An indication of whether the symbol is imported, exported, or the entry point. An * (asterisk) is used to mark the entry point, I is used to mark imported symbols, and E is used to mark exported symbols.
- Its address (except for imported symbols)
- Length and alignment (for CSECTs and BSS symbols)
- Storage-mapping class
- · Symbol type
- Symbol number (used to differentiate between symbols of the same name)
- Symbol name
- Input file information

Storage-mapping classes and symbol types are defined in the /usr/include/syms.h file. In the address maps, only the last two characters are shown, except that storage-mapping class XMC_TC0 is shown as T0.

The input file information depends on the type of input file. For object files, source files names obtained from C_FILE symbols table entries are listed. If the object is from an archive file, the object file name is listed in the following format:

ArchiveFileName[ObjectName]

A shared object name is listed between { } (braces). If a shared object is defined by an import file, the name of the import file is listed before the shared object name.

Import symbols have a symbol type of ER, but they have associated file input information. Undefined symbols are also listed with a symbol type of ER, but all other columns, except the symbol number, are left blank.

The -T and -D flags (or pT or pD options) affect the addresses printed in these address maps. For machine-level debugging, it is helpful to choose address so that symbols are listed with the same addresses that they have at run time. For a 32-bit program that does not use privately loaded shared objects, you can choose the proper addresses by specifying the -bpT:0x10000000 and -bpD:0x200000000 options. These options are defined by default in the /etc/xIC.cfg or /etc/vac.cfg file.

Environment Variables

The following environment variables affect the execution of the **Id** command:

LIBPATH If LIBPATH is defined, its value is used as the default library path information. Otherwise, the

> default library path information is /usr/lib:/lib. If no -L flags are specified and no -blibpath option is specified, the default library path information is written in the loader section of the output file. Regardless of any options specified, LIBPATH is not used when searching for

libraries that are specified from the command line.

TMPDIR If the output file already exists or it is on a remote file system, the Id command generates a

temporary output file. The temporary output file is created in the directory specified by TMPDIR. If TMPDIR is not defined, the temporary output file is created in the /tmp directory if the output

file is remote, or in the same directory as the existing output file.

If neither the -b32 nor -b64 option is used, the OBJECT_MODE environment variable is OBJECT_MODE

> examined to determine the linking mode. If the value of OBJECT MODE is 32 or 64, 32-bit or 64-bit mode is used, respectively. If the value is 32_64 or any other value, the linker prints an error message and exits with a non-zero return code. Otherwise, 32-bit mode is used.

Examples

1. To link several object files and produce an **a.out** file to run under the operating system, type:

```
ld /usr/lib/crt0.o pgm.o subs1.o subs2.o -lc
```

The -1c (lowercase letter L) links the **libc.a** library. A simpler way to accomplish this is to use the cc command (the compiler) to link the files as follows:

```
cc pgm.o subs1.o subs2.o
```

2. To specify the name of the output file, type:

```
cc -o pgm pgm.o subs1.o subs2.o
```

This creates the output in the file pgm.

3. To relink pgm if only the object file **subs1.0** has changed, type:

```
cc -o pgm subsl.o pgm
```

The CSECTs that originally came from object files **pqm.o** and **subs2.o** are read from the file **pqm**. This technique can speed the linking process if a program consists of many input files, but only a few files change at a time.

4. To link with library subroutines, type:

```
cc pgm.o subs1.o subs2.o mylib.a -ltools
```

This links the object modules pam.o. subs1.o. and subs2.o. the subroutines from the mylib.a archive. and the subroutine from the library specified by -I (lowercase letter L) flag. (This means the /usr/lib/libtools.a file).

5. To generate a shared object, type:

```
ld -o shrsub.o subs1.o subs2.o -bE:shrsub.exp -bM:SRE -lc
```

This links the object files **subs1.o**, **subs2.o**, and the subroutines from the library **libc.a** specified by **-lc** flag. It exports the symbols specified in the file shrsub.exp and stores the linked shared object in file shrsub.o. The -bM: SRE sets the shared object flag in the linked object file.

6. To link with the shared object shrsub.o generated previously, type:

```
cc -o pgm pgm.o shrsub.o -L '.'
```

This links the object file pgm.o with the exported symbols of shrsub.o. The linked output is stored in the object file pgm. The -L'.' adds the current directory to the library search path that the system loader uses to locate the shrsub.o shared object. At run time, this program is loaded only if it is run

from a directory containing an instance of the shrsub.o file or if the shrsub.o file is found in the /usr/lib standard library directory. To allow the program to be run from anywhere, use the option -L `pwd`. The list of directories searched by the system loader can be seen using the **dump** command.

7. To link a program using the **libc.a** library as a non-shared library, type:

```
cc -o pgm pgm.o -bnso -bI:/lib/syscalls.exp
```

This links pgm.o with the necessary support libraries and names the output file pgm. For the cc command, the libc.a library is a necessary support library and is usually link-edited to the user's program as a shared library. In this example, the -bnso option directs the Id command to link with the libc.a library as a non-shared library, and the -bI:/lib/syscalls.exp directs the Id command to import the system call functions that are actually contained in the kernel or /usr/lib/boot/unix file. Whenever linking with the -bnso option, any symbols that were both imported and exported (that is, passed through) in a shared object must be explicitly imported, as is done by the -bI:/lib/syscalls.exp option in this example.

Note: Any time that /usr/lib/libc.a is linked non-shared, the flag -bl:/lib/syscalls.exp must be used. The application can also have to be linked again whenever an updated release of the operating system is installed. Any application that is statically linked is not binary portable from any fix or release level to any other fix or release level.

Files

/usr/bin/ld Contains the Id command.

/usr/lib/lib*.a Specifies libraries used for linking programs. Specifies the default output file name. a.out

Related Information

The ar command, as command, nm command, dump command, rtl enable command, strip command.

The **a.out** file format.

The **glob** subroutine, **load** subroutine, **loadbind** subroutine, **loadquery** subroutine, **unload** subroutine.

"How to Create a Shared Library" in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs.

"Large Program Support Overview" in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs.

"Shared Libraries and Lazy Loading" in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs.

"Shared Library Overview" in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs.

"XCOFF (a.out) File Format" in AIX 5L Version 5.3 Files Reference.

Idd Command

Purpose

Lists dynamic dependencies.

Syntax

Idd FileName

Description

The Idd command lists the path names of all dependencies. The command will report dependencies on only valid XCOFF files.

Parameters

FileName

Specifies the file whose dependencies will be listed.

Exit Status

The command completed successfully.

>0 An error occurred.

Examples

1. To display dependencies on /usr/bin/dbx, enter:

```
1dd /usr/bin/dbx
```

```
The output looks like the following:
```

```
/usr/bin/dbx needs:
        /usr/lib/libc.a(shr.o)
        /usr/lib/libdbx.a(shr.o)
        /unix
        /usr/lib/libcrypt.a(shr.o)
        /usr/lib/libpthdebug.a(shr.o)
```

Files

/usr/bin/ldd

Contains the Idd command.

Related Information

The **dump** command.

Idedit Command

Purpose

Modifies an XCOFF executable file header.

Syntax

Idedit -b Option [-V] File

Description

You can use the Idedit command to modify various fields in an XCOFF header or the auxiliary header of an executable file. The Idedit command makes it possible to mark or unmark an application as a 'large page data' program. The Idedit command also makes it possible to add or modify the values of MAXDATA and MAXSTACK without relinking.

The format of the -b flag is similar to the format used by the link editor, the Id command. The -b flag can be used multiple times on the command line.

If no flags are specified, the Idedit command displays a usage message using the standard error output.

Flags

-b Option Modifies an executable as specified by Option. The possible values for Option are:

datapsize:psize

Requests psize page sizes in bytes for data. The value can be specified as a decimal, hexadecimal, or octal number. The number specifications are the same as in C programming language. Additionally, the page sizes can be specified as a number followed by a one-character suffix:

- k or K for kilo or 0x400 bytes
- m or M for mega or 0x100000 bytes
- g or G for giga or 0x40000000 bytes
- t or T for tera or 0x10000000000 bytes
- p or P for peta or 0x400000000000 bytes
- x or X for exo or 0x100000000000000 bytes

For example, either -b datapsize:16k or -b datapsize:0x4000 will request 0x4000 for data and set the F VARPG bit in the XCOFF header. It is accomplished by setting the corresponding member of the auxiliary header to the logarithm base 2 of the given value psize. If the value is different from 0, the F VARPG bit of the XCOFF header's f_flags member is also set. Otherwise, this bit is cleared.

Ipdata Marks a file as a 'large page data' executable.

nolpdata

Unmarks a file as a 'large page data' executable.

maxdata: value

Sets the MAXDATA value. value is an octal number when it starts with 0, a hexadecimal number when it starts with 0x, and a decimal number in all other cases.

maxdata: value/dsa

Sets the MAXDATA value and the DSA bit. value is an octal number when it starts with 0, a hexadecimal number when it starts with 0x, and a decimal number in all other cases.

maxstack: value

Sets the MAXSTACK value. value is an octal number when it starts with 0, a hexadecimal number when it starts with 0x, and a decimal number in all other cases.

rwexec

Marks a file's writable and mappable sections and stack as executable.

norwexec

Marks a file's writable and mappable sections and stack as non-executable.

stackpsize:psize

Requests *psize* page sizes in bytes for process main thread stack. The value can be specified as a decimal, hexadecimal, or octal number. The number specifications are the same as in C programming language. Additionally, the page sizes can be specified as a number followed by a one-character suffix:

- · k or K for kilo or 0x400 bytes
- · m or M for mega or 0x100000 bytes
- · g or G for giga or 0x40000000 bytes
- t or T for tera or 0x1000000000 bytes
- p or P for peta or 0x400000000000 bytes
- x or X for exo or 0x10000000000000 bytes

For example, either -b stackpsize:16k or -b stackpsize:0x4000 will request 0x4000 for process main thread stack and set the F_VARPG bit in the **XCOFF** header. It is accomplished by setting the corresponding member of the auxiliary header to the logarithm base 2 of the given value *psize*. If the value is different from 0, the F_VARPG bit of the **XCOFF** header's f_flags member is also set. Otherwise, this bit is cleared.

textpsize:psize

Requests *psize* page sizes in bytes for text. The value can be specified as a decimal, hexadecimal, or octal number. The number specifications are the same as in C programming language. Additionally, the page sizes can be specified as a number followed by a one-character suffix:

- · k or K for kilo or 0x400 bytes
- · m or M for mega or 0x100000 bytes
- · g or G for giga or 0x40000000 bytes
- t or T for tera or 0x1000000000 bytes
- p or P for peta or 0x400000000000 bytes
- x or X for exo or 0x100000000000000 bytes

For example, either -b textpsize:16k or -b textpsize:0x4000 will request 0x4000 for text and set the F_VARPG bit in the **XCOFF** header. It is accomplished by setting the corresponding member of the auxiliary header to the logarithm base 2 of the given value *psize*. If the value is different from 0, the F_VARPG bit of the **XCOFF** header's **f_flags** member is also set. Otherwise, this bit is cleared.

Prints the version of the Idedit command on the standard error output.

Example

1. To request system-selected page sizes for text, data, and stacks, enter:

ldedit -b textpsize:0 -b datapsize:0 -b stackpsize:0

This clears the F_VARPG bit in the **XCOFF** header.

Related Information

The **Id** command, **dump** command.

learn Command

Purpose

Provides computer-aided instruction for using files, editors, macros, and other features.

Syntax

learn[- Directory] [Subject[LessonNumber]]

Description

The **learn** command provides computer-aided instruction for using files, editors, macros, and other features. The first time you invoke the command, the system provides introductory information about the learn command. Otherwise, the learn command begins at the point where you left the last learn command session.

You can bypass the default action of the learn command by specifying the Subject parameter. The learn command starts with the first lesson of the subject you specify. You can specify any of the following subjects:

- Files
- Editors
- · More files
- Macros
- · EQN (the enquiry character)
- · C (the language)

Note: You can only run the EQN lesson on a hardcopy terminal that is capable of 1/2 line motion. The /usr/share/lib/learn/eqn/lnit file contains a detailed list of the supported terminals.

When you enter the learn command, the system searches the /usr/share/lib/learn directory for the appropriate lesson file. Use the -Directory flag to identify a different search directory.

Subcommands

- The **bye** subcommand terminates a **learn** command session.
- The where subcommand tells you of your progress; the where m subcommand provides more detail.
- The **again** subcommand re-displays the text of the lesson.
- The **again** LessonNumber subcommand lets you review the lesson.
- The hint subcommand prints the last part of the lesson script used to evaluate a response; the hint m subcommand prints the entire lesson script.

Parameters

-Directory Allows you to specify a different search directory. By default, the system searches for lesson

files in the /usr/share/lib/learn directory.

LessonNumber Identifies the number of the lesson.

Subject Specifies the subject you want instruction on.

Examples

To take the online lesson about files, enter:

learn files

The system starts the **learn** program and displays instructions for how to use the program.

Files

Contains the file tree for all dependent directories and files. /usr/share/lib/learn

/tmp/pl* Contains the practice directories.

Related Information

The **ex** command.

Shells in Operating system and device management.

leave Command

Purpose

Reminds you when you have to leave.

Syntax

leave [[+] hhmm]

Description

The leave command waits until the specified time and then reminds you that you have to leave. You are reminded at 5 minutes and at 1 minute before the actual time, again at that time, and at every minute thereafter. When you log off, the leave command exits just before it would have displayed the next message.

If you do not specify a time, the leave command prompts with When do you have to leave? A reply of newline causes the leave command to exit; otherwise, the reply is assumed to be a time. This form is suitable for inclusion in a .login or .profile file.

The leave command ignores interrupt, guit, and terminate operations. To clear the leave command, you should either log off or use the kill-9 command and provide the process ID.

Flags

Specifies to set the alarm to go off in the indicated number of hours and minutes from the current time. Specifies a time of day in hours and minutes (based on a 12- or 24-hour clock) or, if preceded by the +, a set number of hours and minutes from the current time for the alarm to go off. All times are converted to a 12-hour clock and assumed to relate to the next 12 hours.

Examples

To remind yourself to leave at 3:45, enter:

leave 345

Related Information

The calendar command.

lecstat Command

Purpose

Displays operational information about an Asynchronous Transfer Mode network protocol (ATM) Local Area Network (LAN) Emulation Client.

Syntax

lecstat [-a -c -q -r -s -t -v] Device_Name

Description

This command displays ATM LAN Emulation Client (LEC) operational information gathered by a specified LEC device. If a LEC device name is not entered, statistics for all available LEC's appear. Select a flag to narrow down your search results. You can display specific categories of information such as Configuration, LE_ARP Cache Entries, Virtual Connections, and Statistics, or you can choose to display all of the information categories.

You can also toggle debug tracing on or off and reset statistics counters.

Parameters

Device Name The name of the LE Client device, for example, ent1.

Flags

Requests all the LE Client information. This flag does not reset statistics counters or toggle trace. -a

Requests the configuration. -C Requests the LE_ARP cache. -q

-r Resets the statistics counters after reading.

Requests the statistics counters. -S Toggles full debug trace on or off. -t Requests the list of virtual connections. -v

The following information appears for all valid calls and contains the following fields:

Device Type

Displays a description of the LAN Emulation Client (example: Ethernet or Token Ring)

LAN MAC Address

Displays the LAN Emulation Client's 6-byte Ethernet or Token Ring MAC address.

ATM Address

Displays the LAN Emulation Client's 20-byte Asynchronous Transfer Mode (ATM) address.

Elapsed Time

Displays the real time period which has elapsed since statistics were last reset.

Driver Flags

The current LAN Emulation Client(LEC) device driver NDD status flags. Example status flags:

Broadcast Allowing broadcast packets.

Dead Requires re-open.

Debug Internal debug tracing enabled. Limbo Attempting ELAN recovery. Running Fully operational on the ELAN. Up Device has been opened.

Configuration Information

Selected with the -a or -c flags. Displays the network administrator's pre-configured attributes, as well as the current ELAN configuration values as defined by the LANE Servers.

Lane LE_ARP Table Entries

Selected with the -a or -q flags. Displays the current LE Client ARP cache. Included are the type of entry, it's state, the remote LAN MAC address or route descriptor, the remote ATM address and some descriptive values.

Example Types

```
BUS-PP
                   Broadcast and Unknown Server (point-to-point).
BUS-MP
                   Broadcast and Unknown Server (multi-point).
                   Data (point-to-point).
Data
LES-PP
                   LE Server (point-to-point).
LES-MP
                   LE Server (multi-point).
```

Example States

```
Arping
               Attempting to locate remote client/server via LE ARP.
               Fully connected to the remote client/server.
Connected
Flushing
               Flushing the data path to the client/server.
Known
               Remote address is known but no connection yet.
Unknown
               Remote address in unknown and not able to LE ARP yet.
```

Lane Servers and Statistics

Selected with the -a or -s flags. Displays the current Transmit, Receive, and General statistics for this LE Client, as well as the ATM addresses of the current and available LANE Servers.

Lane connections

Selected with the -a or -v flags. Displays the current list of virtual connections in use by this LE Client. Included are virtual path and channel values, remote ATM address, and some descriptive values such as whether this connection was started by the remote, whether it is a duplicate connection, or whether the remote station is proxied by another LE Client.

Exit Status

If you specify an invalid *Device Name*, this command produces error messages stating that it could not connect to the device. Examples of an invalid device error message might be:

```
LECSTAT: No LANE device configured.
LECSTAT: Device is not a LANE device.
LECSTAT: Device is not available.
```

Related Information

The atmstat command, entstat command, mpcstat command, and tokstat command.

lex Command

Purpose

Generates a C or C++ language program that matches patterns for simple lexical analysis of an input stream.

Syntax

```
lex [ -C ] [ -t ] [ -v| -n ] [ File... ]
```

Description

The **lex** command reads *File* or standard input, generates a C language program, and writes it to a file named lex.yy.c. This file, lex.yy.c, is a compilable C language program. A C++ compiler also can compile the output of the lex command. The -C flag renames the output file to lex.yy.C for the C++ compiler.

The C++ program generated by the lex command can use either STDIO or IOSTREAMS. If the cpp define CPP IOSTREAMS is true during a C++ compilation, the program uses IOSTREAMS for all I/O. Otherwise, STDIO is used.

The lex command uses rules and actions contained in File to generate a program, lex.yy.c, which can be compiled with the cc command. The compiled lex.yy.c can then receive input, break the input into the logical pieces defined by the rules in File, and run program fragments contained in the actions in File.

The generated program is a C language function called yylex. The lex command stores the yylex function in a file named lex.yy.c. You can use the yylex function alone to recognize simple one-word input, or you can use it with other C language programs to perform more difficult input analysis functions. For example, you can use the lex command to generate a program that simplifies an input stream before sending it to a parser program generated by the **vacc** command.

The **yylex** function analyzes the input stream using a program structure called a finite state machine. This structure allows the program to exist in only one state (or condition) at a time. There is a finite number of states allowed. The rules in File determine how the program moves from one state to another.

If you do not specify a File, the lex command reads standard input. It treats multiple files as a single file.

Note: Since the lex command uses fixed names for intermediate and output files, you can have only one program generated by lex in a given directory.

lex Specification File

The input file can contain three sections: definitions, rules, and user subroutines. Each section must be separated from the others by a line containing only the delimiter, % (double percent signs). The format is:

```
definitions
rules
%%
user subroutines
```

The purpose and format of each are described in the following sections.

Definitions

If you want to use variables in your rules, you must define them in this section. The variables make up the left column, and their definitions make up the right column. For example, if you want to define D as a numerical digit, you would write the following:

```
[0-9]
D
```

You can use a defined variable in the rules section by enclosing the variable name in {} (braces), for example:

{D}

Lines in the definitions section beginning with a blank or enclosed in \(\{ \, *\} \) delimiter lines are copied to the **lex.yy.c** file. You can use this construct to declare C language variables to be used in the **lex** actions or to include header files, for example:

```
#include <math.h>
int count;
%}
```

Such lines can also appear at the beginning of the rules section, immediately after the first % delimiter, but they should not be used anywhere else in the rules section. If the line is in the definitions section of File, the lex command copies it to the external declarations section of the lex.yy.c file. If the line appears in the rules section, before the first rule, the lex command copies it to the local declaration section of the vylex subroutine in lex.yy.c. Such lines should not occur after the first rule.

The type of the lex external, yytext, can be set to either a null-terminated character array (default) or a pointer to a null-terminated character string by specifying one of the following in the definitions section:

```
(default)
%array
%pointer
```

In the definitions section, you can set table sizes for the resulting finite state machine. The default sizes are large enough for small programs. You may want to set larger sizes for more complex programs.

- **%a***n* Number of transitions is *n* (default 5000)
- **%e***n* Number of parse tree nodes is *n* (default 2000)
- **%h**n Number of multibyte character output slots (default is 0)
- %kn Number of packed character classes (default 1000)
- **%m**n Number of multibyte "character class" character output slots (default is 0)
- **%n***n* Number of states is *n* (default 2500)
- %on Number of output slots (default 5000, minimum 257)
- **%p***n* Number of positions is *n* (default 5000)
- %vp Percentage of slots vacant in the hash tables controlled by %h and %m (default 20, range 0 <= P < 100)
- **%z***n* Number of multibyte character class output slots (default 0)

If multibyte characters appear in extended regular expression strings, you may need to reset the output array size with the %o argument (possibly to array sizes in the range 10,000 to 20,000). This reset reflects the much larger number of characters relative to the number of single-byte characters.

If multibyte characters appear in extended regular expressions, you must set the multibyte hash table sizes with the %h and %m arguments to sizes greater than the total number of multibyte characters contained in the lex file.

If no multibyte characters appear in extended regular expressions but you want '.' to match multibyte characters, you must set %z greater than zero. Similarly, for inverse character classes (for example, [^abc]) to match multibyte characters, you must set both %h and %m greater than zero.

When using multibyte characters, the **lex.yy.c** file must be compiled with the **-qmbcs** compiler option.

Rules

Once you have defined your terms, you can write the rules section. It contains strings and expressions to be matched by the yylex subroutine, and C commands to execute when a match is made. This section is required, and it must be preceded by the delimiter %% (double percent signs), whether or not you have a definitions section. The lex command does not recognize your rules without this delimiter.

In this section, the left column contains the pattern in the form of an extended regular expression, which will be recognized in an input file to the **yylex** subroutine. The right column contains the C program fragment executed when that pattern is recognized, called an action.

When the lexical analyzer finds a match for the extended regular expression, the lexical analyzer executes the action associated with that extended regular expression.

Patterns can include extended characters. If multibyte locales are installed on your system, patterns can also include multibyte characters that are part of the installed code set.

The columns are separated by a tab or blanks. For example, if you want to search files for the keyword **KEY**, you can write the following:

```
(KEY) printf ("found KEY");
```

If you include this rule in File, the yylex lexical analyzer matches the pattern KEY and runs the printf subroutine.

Each pattern can have a corresponding action, that is, a C command to execute when the pattern is matched. Each statement must end with a; (semicolon). If you use more than one statement in an action, you must enclose all of them in { } (braces). A second delimiter, %%, must follow the rules section if you have a user subroutine section. Without a specified action for a pattern match, the lexical analyzer copies the input pattern to the output without changing it.

When the yylex lexical analyzer matches a string in the input stream, it copies the matched string to an external character array (or a pointer to a character string), vytext, before it executes any commands in the rules section. Similarly, the external int, yyleng, is set to the length of the matched string in bytes (therefore, multibyte characters will have a size greater than 1).

For information on how to form extended regular expressions, see "Extended Regular Expressions in the lex Command" in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs.

User Subroutines

The **lex** library defines the following subroutines as macros that you can use in the rules section of the **lex** specification file:

input Reads a byte from yyin.

unput Replaces a byte after it has been read.

output Writes an output byte to yyout.

winput Reads a multibyte character from yyin.

Replaces a multibyte character after it has been read. wunput

woutput Writes a multibyte output character to yyout.

Calls the **setlocale** (LC_ALL, " "); subroutine to determine the current locale. yysetlocale

The winput, wunput, and woutput macros are defined to use the yywinput, yywunput, and yywoutput subroutines coded in the lex.yy.c file. For compatibility, these yy subroutines subsequently use the input, unput, and output subroutines to read, replace, and write the necessary number of bytes in a complete multibyte character.

You can override these macros by writing your own code for these routines in the user subroutines section. But if you write your own, you must undefine these macros in the definition section as follows:

```
%{
#undef input
#undef unput
#undef output
#undef winput
#undef wunput
#undef woutput
#undef yysetlocale
%}
```

There is no main subroutine in lex.yy.c, because the lex library contains the main subroutine that calls the yylex lexical analyzer, as well as the yywrap subroutine called by yylex() at the end of File. Therefore, if you do not include main(), yywrap(), or both in the user subroutines section, when you compile **lex.yy.c**, you must enter cclex.yy.c-11, where 11 calls the **lex** library.

External names generated by the **lex** command all begin with the preface vv, as in vvin, vvout, vvlex, and yytext.

Finite State Machine

The default skeleton for the finite state machine is defined in /usr/ccs/lib/lex/ncform. The user can use a personally configured finite state machine by setting an environment variable LEXER=PATH. The PATH variable designates the user-defined finite state machine path and file name. The lex command checks the environment for this variable and, if it is set, uses the supplied path.

Putting Blanks in an Expression

Normally, blanks or tabs end a rule and therefore, the expression that defines a rule. However, you can enclose the blanks or tab characters in " " (quotation marks) to include them in the expression. Use quotes around all blanks in expressions that are not already within sets of [] (brackets).

Other Special Characters

The lex program recognizes many of the normal C language special characters. These character sequences are:

Sequence	Meaning
\a	Alert
\b	Backspace
\f	Form Feed
\n	Newline character (Do not use the actual newline character in an expression.)
\r	Return
\t	Tab
\v	Vertical Tab
//	Backslash
\digits	The character with encoding represented by the one-, two-, or three-digit octal integer specified by digits .
\xdigits	The character with encoding represented by the sequence of hexadecimal characters specified by digits.
\c	Where c is none of the characters listed above, represents the character c unchanged.

Note: Do not use \0 or \x0 in lex rules.

When using these special characters in an expression, you do not need to enclose them in quotes. Every character, except these special characters and the operator symbols described in "Extended Regular Expressions in the lex Command" in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs, is always a text character.

Matching Rules

When more than one expression can match the current input, the lex command chooses the longest match first. When several rules match the same number of characters, the lex command chooses the rule that occurs first. For example, if the rules

```
integer keyword action...;
[a-z]+
          identifier action...;
```

are given in that order, and integers is the input word, lex matches the input as an identifier, because [a-z]+ matches eight characters while integer matches only seven. However, if the input is integer, both rules match seven characters. lex selects the keyword rule because it occurs first. A shorter input, such as int, does not match the expression integer, and so lex selects the identifier rule.

Matching a String Using Wildcard Characters

Because lex chooses the longest match first, do not use rules containing expressions like .*. For example:

```
1.*1
```

might seem like a good way to recognize a string in single quotes. However, the lexical analyzer reads far ahead, looking for a distant single quote to complete the long match. If a lexical analyzer with such a rule gets the following input:

```
'first' quoted string here, 'second' here
```

it matches:

'first' quoted string here, 'second'

To find the smaller strings, first and second, use the following rule:

```
'[^'\n]*'
```

This rule stops after 'first'.

Errors of this type are not far reaching, because the . (period) operator does not match a new-line character. Therefore, expressions like .* (period asterisk) stop on the current line. Do not try to defeat this with expressions like [.\n]+. The lexical analyzer tries to read the entire input file and an internal buffer overflow occurs.

Finding Strings within Strings

The lex program partitions the input stream and does not search for all possible matches of each expression. Each character is accounted for once and only once. For example, to count occurrences of both she and he in an input text, try the following rules:

```
she
              s++
             h++
he
\n
              ١.
                             ;
```

where the last two rules ignore everything besides he and she. However, because she includes he, lex does not recognize the instances of he that are included in she.

To override this choice, use the action **REJECT**. This directive tells **lex** to go to the next rule. **lex** then adjusts the position of the input pointer to where it was before the first rule was executed and executes the second choice rule. For example, to count the included instances of he, use the following rules:

```
she
                      {s++;REJECT;}
he
                      {h++;REJECT;}
\n
```

After counting the occurrences of she, lex rejects the input stream and then counts the occurrences of he. Because in this case she includes he but not vice versa, you can omit the **REJECT** action on he. In other cases, it may be difficult to determine which input characters are in both classes.

In general, **REJECT** is useful whenever the purpose of **lex** is not to partition the input stream but to detect all examples of some items in the input, and the instances of these items may overlap or include each other.

Flags

- -C Produces the lex.yy.C file instead of lex.yy.c for use with a C++ compiler. To get the I/O Stream Library, use the macro, _CPP_IOSTREAMS, as well.
- Suppresses the statistics summary. When you set your own table sizes for the finite state machine, the lex -n command automatically produces this summary if you do not select this flag.
- Writes lex.yy.c to standard output instead of to a file. -t
- Provides a one-line summary of the generated finite-state-machine statistics.

Exit Status

This command returns the following exit values:

- Successful completion. n
- >0 An error occurred.

Examples

1. To draw **lex** instructions from the file lexcommands and place the output in **lex.yy.c**, use the following command:

lex lexcommands

2. To create a lex program that converts uppercase to lowercase, removes blanks at the end of a line, and replaces multiple blanks by single blanks, including the following in a lex command file:

```
[A-Z]
       putchar(yytext[0]+ 'a'-'A');
[]+$;
       putchar(' ');
```

Files

/usr/ccs/lib/libl.a /usr/ccs/lib/lex/ncform Contains the run-time library. Defines a finite state machine.

Related Information

The **yacc** command.

Generating a Lexical Analyzer with the lex Command in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs.

Using the lex Program with the yacc Program in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs.

Example Program for the lex and yacc Programs in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs.

National Language Support Overview for Programming AIX 5L Version 5.3 National Language Support Guide and Reference.

line Command

Purpose

Reads one line from the standard input.

Syntax

line

Description

The line command copies one line from standard input and writes it to standard output. It returns an exit value of 1 on an end-of-file and always writes at least a new-line character. Use this command within a shell command file to read from the work station.

Exit Status

This command returns the following exit values:

- 0 Successful completion.
- >0 End-of-file occurred on input.

Examples

To read a line from the keyboard and append it to a file, create a script file as follows:

```
echo 'Enter comments for the log:'
echo ': \c'
line >>log
```

This shell procedure displays the message:

```
Enter comments for the log:
```

and then reads a line of text from the workstation keyboard and adds it to the end of the log. The echo': \c' command displays a colon prompt. See the **echo** command for information about the \c escape sequence.

Related Information

The **echo** command, **ksh** command, **sh** command.

The **read** subroutine.

The Input and Output Handling Programmer's Overview in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs describes the files, commands, and subroutines used for low-level, stream, terminal, and asynchronous I/O interfaces.

link Command

Purpose

Performs a link subroutine.

Syntax

link File1 File2

Description

The link command performs the link subroutine on a specified file. The link command does not issue error messages when the associated subroutine is unsuccessful; you must check the exit value to determine if the command completed normally. It returns a value of 0 if it succeeds, a value of 1 if too few or too many parameters are specified, and a value of 2 if its system call is unsuccessful.

Attention: The link command allows a user with root user authority to deal with unusual problems, such as moving an entire directory to a different part of the directory tree. It also permits you to create directories that cannot be reached or escaped from. Be careful to preserve the directory structure by observing the following rules:

- · Be certain every directory has a . (dot) link to itself.
- · Be certain every directory has a .. (dot dot) link to its parent directory.
- Be certain every directory has no more than one link to itself or its parent directory.
- Be certain every directory is accessible from the root of its file system.

Note: If the . (dot) entry has been destroyed and the fsck command is unable to repair it (a rare occurrence), you can use the link command to restore the . (dot) entry of the damaged directory. Use the **link** Dir Dir/. command where the Dir parameter is the name of the damaged directory. However, use this only as a last resort when the directory is destroyed and the fsck command is unable to fix it.

Although the linked files and directories can be removed by the **unlink** command, it's safer to use the **rm** or **rmdir** command.

Examples

To create an additional link for an existing file1, enter:

link file1 file2

Files

/usr/sbin/link

Contains the link command.

Related Information

The **fsck** command, **unlink** command, **In** command.

The link subroutine, unlink subroutine.

The File systems in Operating system and device management explains file system types, management, structure, and maintenance.

The Files in Operating system and device management provides information on working with files.

The Directories in Operating system and device management explains working with directories and path names.

lint Command

Purpose

Checks C and C++ language programs for potential problems.

Syntax

```
lint [-a ] [-b ] [-c ] [-C ] [-h ] [-lKey ] [-n ] [-oLibrary ] [-qDBCS ] [-p ] [-t ] [-u ] [-v ] [-w Class
[Class ... ] ] [ -X ] [ -MA ] [ -NdNumber ] [ -NINumber ] [ -NnNumber ] [ -NtNumber ] [ -IDirectory ] [
-DName [=Definition ] ] [ -UName ] File ...
```

Description

The **lint** command checks C and C++ language source code for coding and syntax errors and for inefficient or non-portable code. You can use this program to:

- Identify source code and library incompatibility.
- Enforce type-checking rules more strictly than does the compiler.
- · Identify potential problems with variables.
- Identify potential problems with functions.
- · Identify problems with flow control.
- · Identify legal constructions that may produce errors or be inefficient.
- Identify unused variable and function declarations.
- · Identify possibly non-portable code.

Note: Checking of C++ language files by the lint command requires the presence of the C Set++ Compiler package.

The inter-file usage of functions is checked to find functions that return values in some instances and not in others, functions called with varying numbers or types of arguments, and functions whose values are not used or whose values are used but not returned.

The **lint** command interprets file name extensions as follows:

- File names ending in .c are C language source files.
- File names ending in .C are C++ language source files.
- File names ending in .In are non-ASCII files that the lint command produces when either the -c or the **-o** flag is used.

The **lint** command warns you about files with other suffixes and ignores them.

The lint command takes all the .c, .C, and .In files and the libraries specified by -I flags and processes them in the order that they appear on the command line. By default, it adds the standard Ilib-Ic.In lint library to the end of the list of files. However, when you select the -p flag, the lint command uses the Ilib-port.In portable library. By default, the second pass of lint checks this list of files for mutual compatibility; however, if you specify the -c flag, the .In and Ilib-lx.In files are ignored.

The -c and -o flags allow for incremental use of the lint command on a set of C and C++ language source files. Generally, use the lint command once for each source file with the -c flag. Each of these runs produces a .In file that corresponds to the .c file and writes all messages concerning that source file. After you have run all source files separately through the lint command, run it once more, without the -c flag, listing all the .In files with the needed -I flags. This writes all inter-file inconsistencies. This procedure works well with the make command, allowing it to run the lint command on only those source files modified since the last time that set of source files was checked.

The lint and LINT preprocessor symbols are defined to allow certain questionable code to be altered or removed for the lint command. Therefore, the lint and LINT symbols should be thought of as a reserved word for all code that is planned to be checked by lint.

The following comments in a C and C++ language source program change the way the lint command operates when checking the source program:

/*NOTREACHED*/	Suppresses	comments	about	unreachable code.

Suppresses checking the following old style function declaration for varying /*VARARGSNumber*/

> numbers of arguments, but does check the data type of the first Number arguments. If you do not include a value for Number, the lint command checks no arguments (Number=0). The ANSI function prototypes should use the ellipsis to indicate unspecified parameters rather than this comment

mechanism.

/*ARGSUSED*/ Suppresses warnings about function parameters not used within the function

definition.

/*LINTLIBRARY*/ If you place this comment at the beginning of a file, the lint command does not

identify unused functions and function parameters in the file. This is used when

running the lint command on libraries.

/*NOTUSED*/ Suppresses warnings about unused external symbols, functions and function

> parameters in the file beginning at its point of occurrence. This is a superset of the /*LINTLIBRARY*/ comment directive, but applies also to external symbols. It is useful for suppressing warnings about unused function prototypes and

other external object declarations.

Suppresses warnings about used, but undefined external symbols and /*NOTDEFINED*/

functions in the file beginning at its point of occurrence.

Permits a standard prototype-checking library to be formed from header files by /*LINTSTDLIB*/

making function prototype declarations appear as function definitions. This directive implicitly activates both the /*NOTUSED*/ and /*LINTLIBRARY*/

comment directives to reduce warning noise levels.

The lint command warning messages give file name and line number. As each file goes through the first pass, warnings for each file and each line number are reported.

If you have not specified the -c flag, the lint command collects information gathered from all input files and checks it for consistency. At this point, if it is not clear whether a message stems from a given source file or from one of its included files, the lint command displays the source file name followed by a question mark.

ANSI programs that include many standard header files may wish to set the -wD flag to reduce the quantity of warnings about prototypes not used, and the -n flag to disable checking against the ANSI standard library. For non-ANSI programs, it is advisable to specify the -wk flag to reduce the amount of warnings concerning the absence of function prototypes.

Flags

-u

-v

-a	Suppresses messages about assignments of long values to variables that are not long.
-b	Suppresses messages about unreachable break statements.
-c	Causes the lint command to produce an .In file for every .c file on the command line. These .In files are the product of the first pass of the lint command only and are not checked for inter-function compatibility.
-C	Specifies to use the C++ libraries (in the /usr/lpp//xlC/lib directory).
-h	Does not try to detect bugs, improper style, or reduce waste.
-lKey	Includes the additional Ilib-I Key. In lint library. You can include a lint version of the Ilib-Im.In math library by specifying -Im on the command line or Ilib-Idos.In library by specifying the -Idos flag on the command line. Use this flag to include local lint libraries when checking files that are part of a project having a large number of files. This flag does not prevent the lint command from using the Ilib-Ic.In library. The lint library must be in the /usr/ccs/lib directory.
-n	Suppresses the check for compatibility with either the standard or the portable lint libraries. This applies for both the ANSI and extended mode libraries.
-o Library	Causes the lint command to create the llib-l Library. In lint library. The -c flag nullifies any use of the -o flag. The lint library produced is the input that is given to the second pass of the lint command. The -o flag simply causes this file to be saved in the named lint library. To produce a llib-l Library. In without extraneous messages, use the -x flag. The -v flag is useful if the source files for the lint library are just external interfaces (for example, the way the llib-lc file is written). These flag settings are also available through the use of lint command comment lines.
-p	Checks for portability to other C language dialects.
-t	Checks for problematic assignments when porting from 32 to 64 bit. Only the following cases are checked:
	 all shift / mask operations are flagged because some operations that work well in 32-bit may cause problems in 64-bit.
	 warnings are given for the following type of assignments.
	<pre>int = long int = ptr</pre>

Suppresses messages about functions and external variables that are either used and not defined or defined and not used. Use this flag to run the lint command on a subset of files of a

Suppresses messages about function parameters that are not used.

-w Class [Class...]

Controls the reporting of warning classes. All warning classes are active by default, but can be individually deactivated by including the appropriate option as part of the Class argument. The individual options are listed as:

- а Non-ANSI features.
- Comparisons with unsigned values. C
- d Declaration consistency.
- h Heuristic complaints.
- k Use for K+R type source code.
- Assignment of long values to variables that are not long.
- n Null-effect code.
- Unknown order of evaluation.
- Various portability concerns.
- Return statement consistency.
- Storage capacity checks. S
- Proper usage of variables and functions. u
- Deactivate all warnings.
- C Constants occurring in conditionals.
- D External declarations are never used.
- 0 Obsolescent features.
- Function prototype presence.
- Detection of unreachable code.

Suppresses messages about variables that have external declarations but are never used. -x -MA

Enforces the ANSI C language standard rules. The default mode is equal to the extended C mode. The ANSI mode prepends the standard ANSI library function prototypes in place of the default extended mode C lint library. The ANSI mode enforces a stricter inter-file object

reference and provides definition linkage checks.

-NdNumber Changes the dimension table size to *Number*. The default value of *Number* is 2000. -NINumber Changes the number of type nodes to Number. The default value of Number is 8000. -NnNumber Increases the size of the symbol table to Number. The default value of Number is 1500. -NtNumber Changes the number of tree nodes to *Number*. The default value of *Number* is 1000.

In addition, the **lint** command recognizes the following flags of the **cpp** command (macro preprocessor):

Adds the Directory to the list of directories in which the lint command searches for the #include -IDirectory

files.

-DName[=Definition] Defines the Name, as if by the #define file. The default of the Definition is the value of 1.

-qDBCS Sets multibyte mode specified by the current locale.

Removes any initial definition of the Name, where the Name is a reserved symbol that is -UName

predefined by the particular preprocessor.

Exit Status

This command returns the following exit values:

Successful completion.

>0 An error occurred.

Examples

1. To check a C program for errors, enter:

lint command.c

2. To suppress some of the messages, enter:

lint -v -x program.c

This checks program.c, but does not display error messages about unused function parameters (-v) or unused externals (-x).

3. To check the program against an additional lint library, enter:

lint -lsubs program.c

This checks program.c against both the /usr/ccs/lib/llib-lc.ln standard lint library and /usr/lib/llib-lsubs.ln lint library.

4. To check against the portable library and an additional library, enter:

lint -lsubs -p program.c

This checks program.c against both the /usr/ccs/lib/llib-port.In portable lint library and /usr/lib/llib-lsubs.In lint library.

5. To check against a nonstandard library only, enter:

lint -lsubs -n program.c

This checks program.c against only /usr/lib/llib-lsubs.ln.

Files

/usr/lib/lint[12] /usr/ccs/lib/llib-lansi /usr/ccs/lib/llib-lansi.ln /usr/ccs/lib/llib-lc /usr/ccs/lib/llib-lc.ln /usr/ccs/lib/llib-lcrses /usr/ccs/lib/llib-lcrses.ln /usr/ccs/lib/llib-lm /usr/ccs/lib/llib-lm.ln /usr/ccs/lib/llib-port /usr/ccs/lib/llib-port.ln /usr/lpp//xIC/lib /var/tmp/*lint*

Programs

Declarations for standard ANSI functions (source) Declarations for standard ANSI functions (binary format) Declarations for standard functions (source) Declarations for standard functions (binary format)

Declarations for curses functions (source) Declarations for curses functions (binary format) Declarations for standard math functions (source) Declarations for standard math functions (binary format)

Declarations for portable functions (source) Declarations for portable functions (binary format)

Directory containing C++ libraries

Temporary files

Related Information

The cpp command, make command.

listdgrp Command

Purpose

Displays devices of a device class.

Syntax

listdgrp DeviceClass

Description

Lists information about devices where the DeviceClass parameter referes to a object class of Customized Devices in the Device Configuration database.

Parameters

DeviceClass

Specifies the device class whose members will be displayed.

Exit Status

- 0 The command completed successfully.
- >0 An error occurred.

Examples

1. To list the devices in the adapter class, enter:

```
listdgrp adapter
```

The output looks similar to the following:

a0 sa1 siokma0 fda0 scsi0 scsi1 b10 sioka0 siota0

Files

/usr/bin/listdgrp

Contains the System V listdgrp command.

Related Information

The chdev command, Isattr command, Isdev command, mkdev command, rmdev command.

listvgbackup Command

Purpose

Lists or restores the contents of a volume group backup on a specified media.

Syntax

```
listvgbackup [ -b blocks ] [ -f device ] [ -a ] [ -c ] [ -l ] [ -n ] [ -r ] [ -s ] [ -d path ] [ -B ] [ -D ] [ -L ] [ -V ] [
file_list]
```

Description

The listvgbackup command lists the contents of a volume group backup from tape, file, CD-ROM, or other source and can be used to restore files from a valid backup source. The listvgbackup command also works for multi-volume backups such as multiple CDs, DVDs, USB disks, or tapes.

The listvgbackup -r and restorevgfiles commands perform identical operations and should be considered interchangeable.

Flags

-d path

-n

-r

-s

Verifies the physical block size of the tape backup, as specified by the -b block flag. You may -a

need to alter the block size if necessary to read the backup. The -a flag is valid only when a

tape backup is used.

-b blocks Specifies the number of 512-byte blocks to read in a single input operation, as defined by the

blocks parameter. If the blocks parameter is not specified, the number of blocks read will

default to 100.

-B Prints the volume group backup log to **stdout**.

> This flag will display the past 256 backups (roughly). The log is in alog format and is kept in /var/adm/ras/vgbackuplog. Each line of the log is a semicolon-separated list of the file or device name, the command used to make backup, date, shrink size, full size of the backup, and recommended maintenance or technology level (if any).

> Note: The shrink size is the size of the data on all filesystems. The full size is total size of

each filesystem (unused + data).

Produces colon-separated output. This flag only works with the -I and -L flags. -C

Specifies the directory path to which the files will be restored, as defined by the path

parameter. If the -d parameter is not used, the current working directory is used. This can be a problem if the current working directory is root. We recommend writing to a temporary folder

instead of to root.

-D Produces debug output.

Displays useful information about a volume group backup. -1

> This flag requires the -f device flag. This flag causes listvgbackup to display information such as volume group, date and time backup was made, uname output from backed up system, oslevel, recommended maintenance or technology level, backup size in megabytes, and backup shrink size in megabytes. The shrink size is the size of the data on all filesystems. The full size is the total size of each filesystem (unused + data). The -I flag also displays the logical volume and filesystem information of the backed up volume group, equivalent to

running "Isvg -I vgname".

-L Displays lpp fileset information about a **mksysb** backup only.

> This flag requires the -f device flag and displays the equivalent information to that produced by invoking "Islpp -I" on the running backed up system. This flag does not produce output about

any volume group backup other than that produced by mksysb.

-f device Specifies the type of device containing the backup (file, tape, CD-ROM, or other source) as

defined by the device parameter. When -f is not specified, device will default to /dev/rmt0.

Does not restore ACLs, PCLs, or extended attributes.

Specifies to restore the backup files, as defined by the file-list parameter. If the file-list

parameter is not specified, then all files in the backup will be restored. If the -r flag is not used, then executing the **listvgbackup** command only lists the files in the specified backup.

Specifies that the backup source is a user volume group and not rootvg.

-V Verifies a tape backup.

> This flag requires the -f device flag and works for tape devices only. The -V flag causes listvgbackup to verify the readability of the header of each file on the volume group backup and print any errors that occur to stderr.

Parameters

file_list Identifies the list of files to be restored. This parameter is used only when the -r flag is specified.

The full path of the files relative to the current directory should be specified in the space-separated list. All files in the specified directory will be restored unless otherwise directed.

If you are restoring all files in a directory, we recommend writing to a temporary folder instead of

to root.

Examples

1. To list the contents of the system backup located on the default device /dev/rmt0, enter:

2. To list the contents of the system backup located on device /dev/cd1, enter:

listvgbackup -f /dev/cd1

3. To list the contents of the system backup located on device /dev/cd1, which is a user volume group that is not rootyg, enter:

listvgbackup -f /dev/cd1 -s

4. To restore /etc/filesystems from the system backup located on device /dev/cd1, enter:

listvgbackup -f /dev/cdl -r ./etc/filesystems

5. To restore all files in the /myfs/test directory of the non-rootyg backup, which is located on device /dev/cd1, and write the restored files to /data/myfiles, enter:

listvgbackup -f /dev/cdl -r -s -d /data/myfiles ./myfs/test

6. To display colon separated lpp information about a mksysb backup tape located on /dev/rmt0, enter the following:

1smksysb -Lc -f /dev/rmt0

7. To display the volume group backup log to **stdout**, enter:

1ssavevg -B

8. To list volume group and general backup data about a backup located at /tmp/mybackup, enter:

listvgbackup -1 -f /tmp/mybackup

9. To verify the readability of each header on a volume group backup tape in /dev/rmt0, enter:

lsmksysb -V -f /dev/rmt0

10. To list the contents of the system backup located on device /dev/usbms0, use the following command:

listvgbackup -f /dev/usbms0

Files

/usr/bin/listvgbackup

Contains the listvgbackup command

Related Information

The restorevgfiles command.

listX11input Command

Purpose

Lists X11 input extension records entered into the Object Data Manager (ODM) database.

Syntax

listX11input

Description

The **listX11input** command lists all X11 input extension records entered in the ODM database.

Error Codes

ODM could not open class

The ODM database is not stored in the /usr/lib/objrepos directory.

Related Information

The addX11input command, deleteX11input command.

Ilbd Daemon

Purpose

Manages the information in the local location broker database.

Syntax

IIbd [-family FamilyName] [-version]

Description

The **IIbd** daemon is part of the Network Computing System (NCS). It manages the local location broker (LLB) database, which stores information about NCS-based server programs running on the local host.

A host must run the IIbd daemon to support the location broker forwarding function or to allow remote access (for example, by the Ib admin tool) to the LLB database. In general, any host that runs an NCS-based server program should run an **IIbd** daemon, and **IIbd** should be running before any such servers are started. Additionally, any network or internet supporting NCS activity should have at least one host running a global location broker daemon (glbd).

The **IIbd** daemon is started in one of two ways:

- Through the System Resource Controller (the recommended method), by entering on the command line: startsrc -s 11bd
- By a person with root user authority entering on the command line: /etc/ncs/11bd &

TCP/IP must be configured and running on your system before you start the IIbd daemon. (You should start the **IIbd** daemon before starting the **glbd** or **nrglbd** daemon.)

Flags

-listen FamilyList Restricts the address families on which an LLB listens. Use it only if you are

creating a special configuration where access to an LLB is restricted to a subset

of hosts in the network or internet.

The FamilyList is a list of the address families on which the LLB will listen. Names in this list are separated by spaces. Possible family names include ip.

If **IIbd** is started without the **-listen** option, the LLB will listen on all address

families that are supported both by NCS and by the local host.

Displays the version of NCS that this Ilbd belongs to, but does not start the

daemon.

Files

-version

/etc/rc.ncs Contains commands to start the NCS daemons.

Related Information

The **lb admin** command, **startsrc** command...

The **glbd** (NCS) daemon, **nrglbd** (NCS) daemon.

In Command

Purpose

Links files.

Syntax

To Link a File to a File

In [-f | -n] [-s] SourceFile [TargetFile]

To Link a File or Files to a Directory

In [-f | -n] [-s] SourceFile ... TargetDirectory

Description

The In command links the file designated in the SourceFile parameter to the file designated by the TargetFile parameter or to the same file name in another directory specified by the TargetDirectory parameter. By default, the In command creates hard links. To use the In command to create symbolic links, designate the -s flag.

A symbolic link is an indirect pointer to a file; its directory entry contains the name of the file to which it is linked. Symbolic links may span file systems and may refer to directories.

If you are linking a file to a new name, you can list only one file. If you are linking to a directory, you can list more than one file.

The TargetFile parameter is optional. If you do not designate a target file, the In command creates a new file in your current directory. The new file inherits the name of the file designated in the SourceFile parameter. See example 5.

Notes:

- 1. You cannot link files across file systems without using the **-s** flag.
- 2. If TargetDirectory is already a symbolic link to a directory, then the In command treats the existing target as a file. This means that a command such as In -fs somepath/Iname symdir will not follow the existing symbolic link of symdir, instead it will create a new symbolic link from somepath/Iname to symdir.

Flags

- -f Causes the In command to replace any destination paths that already exist. If a destination path already exists and the -f flag is not specified, the In command writes a diagnostic message to standard error without creating a new link and continues to link the remaining SourceFiles.
- Specifies that if the link is an existing file, do not overwrite the contents of the file. The -f flag overrides this -n flag. This is the default behavior.

Causes the In command to create symbolic links. A symbolic link contains the name of the file to which it is -S linked. The referenced file is used when an open operation is performed on the link. A stat call on a symbolic link returns the linked-to file; an Istat call must be done to obtain information about the link. The readlink call may be used to read the contents of a symbolic link. Symbolic links can span file systems and refer to directories.

> Note: Absolute path names must be used when specifying the SourceFile parameter for the -s flag. If the absolute path name is not designated, unexpected results may occur when the SourceFile and the TargetFile parameters are located in different directories. The source file does not need to exist before creating the symbolic link.

Exit Status

This command returns the following exit values:

- All specified files were successfully linked.
- >0 An error occurred.

Examples

1. To create another link (alias) to a file, enter:

```
ln -f chap1 intro
```

This links chap1 to the new name, intro. If intro does not already exist, the file name is created. If intro does exist, the file is replaced by a link to chap1. Then both the chap1 and intro file names will refer to the same file. Any changes made to one also appear in the other. If one file name is deleted with the **rm** command, the file is not completely deleted since it remains under the other name.

2. To link a file to the same name in another directory, enter:

```
ln index manual
```

This links index to the new name, manual/index.

Note: intro in example 1 is the name of a file; manual in example 2 is a directory that already exists.

3. To link several files to names in another directory, enter:

```
1n chap2 jim/chap3 /home/manual
```

This links chap2 to the new name /home/manual/chap2 and jim/chap3 to /home/manual/chap3.

4. To use the In command with pattern-matching characters, enter:

```
1n manual/* .
```

This links all files in the manual directory into the current directory, . (dot), giving them the same names they have in the manual directory.

Note: You must type a space between the asterisk and the period.

5. To create a symbolic link, enter:

```
ln -s /tmp/toc toc
```

This creates the symbolic link, toc, in the current directory. The toc file points to the /tmp/toc file. If the /tmp/toc file exists, the **cat** toc command lists its contents.

To achieve identical results without designating the *TargetFile* parameter, enter:

```
1n -s /tmp/toc
```

Files

/usr/bin/ln

Contains the **In** command.

Related Information

The **cp** command, **mv** command, **rm** command.

The link subroutine, readlink subroutine, stat subroutine, symlink subroutine.

Directories in Operating system and device management describes the structure and characteristics of directories in the file system.

Files in Operating system and device management describes files, file types, and how to name files.

File and directory links in *Operating system and device management* explains the concept of file linking.

Linking for Programmers in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging *Programs* discusses links from a programming viewpoint.

locale Command

Purpose

Writes information to standard output about either the current locale or all public locales.

Syntax

locale [-O 64][-a | -m] | [[-c] [-k] Name ...]

Description

The locale command writes information to standard output about either the current locale or all public locales. A public locale is a locale available to any application.

To write the name and value of each current locale category, do not specify any flags or variables. To write the names of all available public locales, specify the -a flag. To write a list of the names of all available character-mapping (charmap) files, specify the -m flag. These charmap filenames are suitable values for the -f flag specified with the localedef command.

To write information about specified locale categories and keywords in the current locale, specify the Name parameter. The Name parameter can be one of the following:

- A locale category, such as LC_CTYPE or LC_MESSAGES
- A keyword, such as yesexpr or decimal_point
- The **charmap** reserved word to determine the current character mapping

You can specify more than one *Name* parameter with the **locale** command.

If you specify the locale command with a locale category name and no flags, the locale command writes the values of all keywords in the locale category specified by the Name parameter. If you specify the locale command with a locale keyword and no flags, the locale command writes the value of the keyword specified by the Name parameter.

If the Name parameter is a locale category name or keyword, the -c and -k flags can determine the information displayed by the locale command.

Flags

- -a Writes the names of all available public locales.
- -c Writes the names of selected locale categories. If the *Name* parameter is a keyword, the **locale** command writes the name of the locale category that contains the specified keyword, and the value of the specified keyword. If the *Name* parameter is a locale category, the **locale** command writes the name of the specified locale category and the values of all keywords in the specified locale category.
- -k Writes the names and values of selected keywords. If the *Name* parameter is a keyword, the **locale** command writes the name and value of the specified keyword. If the *Name* parameter is a locale category, the **locale** command writes the names and values of all keywords in the specified locale category.
- -m Writes the names of all available character-mapping (charmap) files.
- Writes the name of the locale category, followed by the names and values of selected keywords. If the Name parameter is a keyword, the locale command writes the name of the locale category that contains the specified keyword, and the name and value of the specified keyword. If the Name parameter is a locale category, the locale command writes the name of the specified locale category and the names and values of all keywords in the specified locale category.
- **-O** 64 Displays locale information as seen by a 64 bit executable. This should be identical to information as seen by a 32 bit executable.

Exit Status

This command returns the following exit values:

- O All the requested information was found and output successfully.
- >0 An error occurred.

Examples

1. To retrieve the names and values of all the current locale environment variables, enter:

locale

If locale_x and locale_y are valid locales on the system, as determined with locale -a, and if the locale environment variables are set as follows:

```
LANG=locale_x
LC COLLATE=locale y
```

The locale command produces the following output:

```
LANG=locale_x
LC_CTYPE="locale_x"
LC_COLLATE=locale_y
LC_TIME="locale_x"
LC_NUMERIC="locale_x"
LC_MONETARY="locale_x"
LC_MESSAGES="locale_x"
LC_ALL=
```

Note: When setting the locale variables, some values imply values for other locale variables. For example, if the **LC_ALL** locale variable is set to the **En_US** locale, all locale environment variables are set to the **En_US** locale. In addition, implicit values are enclosed in double quotes ("). Explicitly set values are not enclosed in double quotes ("). See "Understanding Locale Environment Variables" in *AIX 5L Version 5.3 National Language Support Guide and Reference* for more information.

2. To determine the current character mapping, enter:

locale charmap

If the **LC_ALL** locale variable is set to the C locale, the **locale** command produces the following output:

IS08859-1

3. To retrieve the value of the decimal point delimiter for the current locale, enter:

```
locale -ck decimal point
```

If the LC ALL locale variable is set to the C locale, the locale command produces the following output:

```
LC NUMERIC
decimal_point="."
```

Related Information

The localedef command.

Character Set Description (charmap) Source File Format and Locale Definition Source File Format in AIX 5L Version 5.3 Files Reference.

For specific information about the locale definition source file format, categories, and their locale variables, see the LC_COLLATE category, LC_CTYPE category, LC_MESSAGES category, LC_MONETARY category, LC_NUMERIC category, and LC_TIME category in AIX 5L Version 5.3 Files Reference.

National Language Support Overview, and Understanding Locale Environment Variables in AIX 5L Version 5.3 National Language Support Guide and Reference.

localedef Command

Purpose

Converts locale and character set description (charmap) source files to produce a locale database.

Syntax

localedef [-c] [-f Charmap] [-i SourceFile] [-L LinkOptions] [-m MethodFile] LocaleName

Description

The localedef command converts source files that contain definitions of locale-dependent information (such as collation, date and time formats, and character properties) into a locale object file used at run-time. The locale object file created by the localedef command is then used by commands and subroutines that set the locale with the setlocale subroutine.

The -i SourceFile flag and variable specify the file that contains the source category definitions. If the -i flag is not specified, the file is read from standard input.

The -f CharMap flag and variable specify a file that maps character symbols to actual character encodings. Using the -f flag allows one locale source definition to be applicable to more than one code set. If the -f flag is not specified, the default value for the CharMap variable is ISO8859-1.

The LocaleName parameter specifies the locale name for the locale database generated by the localedef command from the specified source files. The LocaleName parameter can be either an absolute path name for the file location or a relative path name.

If a locale category source definition contains a copy statement and the statement names an existing locale installed in the system, the localedef command proceeds as though the source definition contained the valid category source definition for the named locale.

Notes:

- 1. The localedef command uses the C compiler to generate the locale database. Therefore, to use this command you must have the C compiler installed.
- 2. When replacing systemwide databases, it is advisable to do a soft reboot to ensure that the new locale is used throughout the system.

If an error is detected, no permanent output is created.

If warnings occur, permanent output is created when the -c flag is specified. The following conditions cause warning messages to be issued:

- · A symbolic name not found in the file pointed to by the Charmap variable is used for the descriptions of the LC_TYPE or LC_COLLATE categories. This is an error condition for other categories.
- The number of operands to the order_start keyword exceeds the COLL_WEIGHTS_MAX limit.
- · Optional keywords not supported by the implementation are present in the source file.

Flags

-c	Forces the creation of locale tables even if warning messages have been issued.
-f CharMap	Specifies the name of a file containing a mapping of character symbols and collating element symbols to actual character encodings. A locale is associated with one and only one code set. If this flag is not specified, the ISO 8859-1 code set is assumed. Note: The use of certain system-provided <i>CharMap</i> files is fully supported. However, while correctly defined user-provided <i>CharMap</i> files may work properly, the result of such use is not guaranteed.
-i SourceFile	Specifies the path name of a file containing the locale category source definitions. If this flag is not present, source definitions are read from standard input.
-L LinkOptions	Passes the specified link options to the Id command used to build the locale.
-m MethodFile	Specifies the name of a method file that describes the methods to override when constructing a locale. The method file specifies user-supplied subroutines that override existing definitions, as well as a path name for the library containing the specified subroutines. The localedef command reads the method file and uses entry points when constructing the locale objects. The code set methods specified are also used in parsing the file pointed to by the <i>CharMap</i> variable. Note: To create a 64-bit locale, the method file must specify the path of the library as a single archive that has two shared objects, one 32-bit and the other 64-bit, that contain the specified subroutines. Specifying separate paths to the 32-bit and 64-bit shared objects causes the localedef command to fail due to incompatible XCOFF format.
LocaleName	Specifies the name of the locale to be created. This is the name that can subsequently be used to access this locale information.
	be used to access this locate information.

Exit Status

The localedef command returns the following exit values:

- No errors occurred and the locales were successfully created.
- 1 Warnings occurred and the locales were successfully created.
- 2 The locale specification exceeded limits or the code set or sets used were not supported by the implementation, and no locale was created.
- The capability to create new locales is not supported.
- >3 Warnings or errors occurred and no locales were created.

Examples

- 1. To create a locale called Austin from standard input and disregard warnings, enter: localedef -c Austin
- 2. To create a locale called Austin with Austin.src as source input, enter:

Related Information

The Id command, locale command.

The **setlocale** subroutine.

Character Set Description (charmap) Source File Format, Locale Definition Source File Format and Method Source File Format in AIX 5L Version 5.3 Files Reference.

For specific information about the locale categories and their keywords, see the LC COLLATE category, LC CTYPE category, LC MESSAGES category, LC MONETARY category, LC NUMERIC category, and LC TIME category for the locale definition source file format in AIX 5L Version 5.3 Files Reference.

National Language Support Overview for System Management in AIX 5L Version 5.3 National Language Support Guide and Reference.

lock Command

Purpose

Reserves a terminal.

Syntax

lock [-Timeout]

Description

The lock command requests a password from the user, reads it, and requests the password a second time to verify it. In the interim, the command locks the terminal and does not relinquish it until the password is received the second time or one of the following occurs:

- · The timeout interval is exceeded.
- The command is killed by a user with appropriate permission.

The timeout default value is 15 minutes, but this can be changed with the -Timeout flag.

Flags

-Timeout

Indicates the timeout interval in minutes, as specified by the Timeout parameter. The default value is 15 minutes.

Examples

1. To reserve a terminal under password control, enter:

1ock

You are prompted for the password twice so the system can verify it. If the password is not repeated within 15 minutes, the command times out.

2. To reserve a terminal under password control, with a timeout interval of 10 minutes, enter:

lock -10

Files

/usr/bin/lock

Contains the lock command.

Related Information

The **passwd** command.

For more information about the identification and authentication of users, discretionary access control, the trusted computing base, and auditing, refer to the Security.

lockd Daemon

Purpose

Processes lock requests.

Syntax

/usr/sbin/rpc.lockd [-t TimeOut] [-g GracePeriod] [-d debug] [-x xnfs] [-T RetransmissionsTimeout] [number of server]

Description

The lockd daemon processes lock requests that are either sent locally by the kernel or remotely by another lock daemon. The lockd daemon forwards lock requests for remote data to the server site lock daemon through the RPC package. The lockd daemon then asks the statd (status monitor) daemon for monitor service. The reply to the lock request is not sent to the kernel until both the statd daemon and the server site lockd daemon reply. The statd daemon should always be started before the lockd daemon.

If either the status monitor or the server site lock daemon is unavailable, the reply to a lock request for remote data is delayed until all daemons become available.

When a server recovers, it waits for a grace period for all client site **lockd** daemons to submit reclaim requests. The client site lockd daemons, on the other hand, are notified of the server recovery by the statd daemon. These daemons promptly resubmit previously granted lock requests. If a lockd daemon fails to secure a previously granted lock at the server site, the lockd daemon sends a SIGLOST signal to the process.

The lockd daemon is started and stopped with the following System Resource Controller (SRC) commands:

```
startsrc -s rpc.lockd
stopsrc -s rpc.lockd
```

To modify the arguments passed to the **lockd** daemon when it is started, use the following command: chssys -s rpc.lockd Parameters...

The status monitor maintains information on the location of connections as well as the status in the /etc/sm directory, the /etc/sm.bak file, and the /etc/state file. When restarted, the statd daemon gueries these files and tries to reestablish the connection it had prior to termination. To restart the statd daemon, and subsequently the lockd daemon, without prior knowledge of existing locks or status, delete these files before restarting the **statd** daemon.

By default rpc.lockd establishes a dynamic socket port number for receiving requests. Entries may be added to the /etc/services file specifying the port that rpc.lock will listen for requests on. The service

name is lockd and a unique port number should be specified. The following entries in /etc/services file would specify that port 16001 be used for both tcp and udp.

lockd 16001/tcp lockd 16001/udp

Flags

-d debug Specifies the debug level of the rpc.statd daemon. By default, the debug level is

disabled.

-g GracePeriod Uses the GracePeriod variable to specify the amount of time, in seconds, that the

lockd daemon should wait for reclaim requests for previously granted locks. The default

value of the GracePeriod variable is 45 seconds.

-T RetransmissionsTimeout Specifies the timeout for one-way RPC connections. One-way RPC connections stay

valid for RetransmissionsTimeout number of seconds. If this variable is set to 0, then

there is no client cache for one-way RPC calls. The default value for the

RetransmissionsTimeout variable is 300 seconds.

-t TimeOut Uses the TimeOut variable to specify the interval between retransmitting lock requests

to the remote server. The default value for the TimeOut variable is 15 seconds.

-x xnfs Specifies if the rpc.lockd daemon needs to follow the xnfs specification. By default, this

flag is turned off.

Parameters

number of server Specifies the number of daemons to start.

Examples

1. To specify a grace period, enter:

/usr/sbin/rpc.lockd -g 60

In this example, the grace period is set for 60 seconds.

2. To specify the amount of time the **lockd** daemon should wait before retransmitting a lock request, enter:

/usr/sbin/rpc.lockd -t 30

In this example, the retransmissions occur after 30 seconds.

Files

/etc/services Contains lockd parameter information entries.

Related Information

The chssys command, nfso command, no command.

The statd daemon.

The **fcntl** subroutine, **lockf** subroutine, **signal** subroutine.

List of NFS commands.

Network File System (NFS) Overview for System Management in Networks and communication management.

locktrace Command

Purpose

Controls kernel lock tracing.

Syntax

locktrace [-r classname | -s classname | -S | -R | -I]

Description

The **locktrace** command controls which kernel locks are being traced by the **trace** subsystem. The default is to trace none. If the machine has been rebooted after running the bosboot -L command, kernel lock tracing can be turned on or off for one or more individual lock classes, or for all lock classes. If bosboot -L was not run, lock tracing can only be turned on for all locks or none. The trace events collected in this case when locks are taken or missed (hook id 112), and released (hook id 113) do not have the lock class name available.

Flags

-r classname	Turns off lock tracing for all kernel locks belonging to the specified class. This option always fails if you did not run the bosboot -L command.
-s classname	Turns on lock tracing for all kernel locks belonging to the specified class. This option always fails if you did not run the bosboot -L command. To trace several specific classes at the same time, run the locktrace command multiple times, with a specific lock class each time. You can enter up to 32 class names.
-R	Turn off all lock tracing.
-S	Turn on lock tracing for all locks regardless of their class membership.
-1	List kernel lock tracing current status.

Examples

1. To start tracing the SEM LOCK CLASS, enter the following command:

```
locktrace -s SEM LOCK CLASS
```

2. To stop all lock tracing, enter the following command:

```
locktrace -R
```

3. To reset previous lock trace entries and then trace the SEM_LOCK_CLASS and SHM_LOCK_CLASS lock classes, enter the following commands:

```
locktrace -R
locktrace -s SEM LOCK CLASS
locktrace -s SHM LOCK CLASS
```

You can view current lock classes using the -I flag:

```
locktrace -1
```

The following output will be displayed:

```
lock tracing enabled for classes:
  SHM_LOCK_CLASS
  SEM LOCK CLASS
```

File

/usr/bin/locktrace

Contains the locktrace command.

Related Information

The **bosboot** command, and the **trace** command.

logevent Command

Purpose

Logs event information generated by the event response resource manager (ERRM) to a specified log file.

Syntax

logevent [-h] log_file

Description

The **logevent** captures event information that is posted by the event response resource manager (ERRM) in environment variables the ERRM generates when an event occurs. This script can be used as an action that is run by an event response resource. It can also be used as a template to create other user-defined actions. The language in which the messages of the logevent script are returned depend on the locale settings.

Event information that is returned about the ERRM environment variables includes the following:

Local Time

Time when the event or rearm event is observed. The actual environment variable supplied by ERRM is ERRM TIME. This value is localized and converted to readable form before being displayed.

This script uses the alog command to write event information to and read event information from the specified log file.

Flags

Writes the script's usage statement to standard output.

Parameters

log file

Specifies the name of the file where event information is logged. An absolute path for the log file parameter should be specified.

The log_file is treated as a circular log and has a fixed size of 64KB. When log_file is full, new entries are written over the oldest existing entries.

If log file already exists, event information is appended to it. If log file does not exist, it is created so that event information can be written to it.

Exit Status

- 0 The script has run successfully.
- 1 A required log file is not specified.
- 2 The log file path is not valid.

Restrictions

- · This script must be run on the node where the ERRM is running.
- The user who runs this script must have write permission for the log file where the event information is logged.

Standard Output

When the -h flag is specified, the script's usage statement is written to standard output.

Examples

1. To log information, specify /tmp/event.log in the Web-based System Manager interface. ERRM runs this command:

/usr/sbin/rsct/bin/logevent/tmp/event.log

The /tmp/event.log file does not need to exist when the command is run.

2. To see the contents of the /tmp/event.log file, run this command:

```
alog -f /tmp/event.log -o
```

The following sample output shows a warning event for the /var file system (a file system resource):

Event reported at Mon Mar 27 16:38:03 2007

Condition Name: /var space used Severity: Warning Event Type: Event

Expression: PercentTotUsed>90

Resource Name: /var

Resource Class Name: IBM.FileSystem Data Type: CT UINT32 Data Value: 91

Location

/usr/sbin/rsct/bin/logevent

Related Information

Commands: alog, elogevent

logform Command

Purpose

Initializes a logical volume for use as a Journaled File System (JFS) log. Initializes an Enhanced Journaled File System (JFS2) outline log. Reformats an inline log for an existing JFS2 file system using an inline log.

Syntax

logform [-V vfstype] LogName

Description

The logform command initializes a logical volume for use as a JFS or JFS2 log device. Running the logform command on any JFS log device or JFS2 outline or inline log device will destroy all log records on the log device. This may cause the file system to lose its recovery capability and therefore to lose the file system data.

When you run the **logform** command on an outline log for a JFS2 file system that is already using an outline log, the device type for the outline log must be ifs2log. Otherwise, the logform command will exit with an error.

To reuse an existing logical volume as an outline log device for a JFS2 file system, you must delete the logical volume and then recreate it as device type ifs2log.

For the outline log device of a JFS file system, the same rules are applied. That is, for a new logical volume, the type should be jfslog. For a reuse logical volume, you should delete the logical volume and recreate it as Iv type jfslog. However, logform does not do type check for the log device of a JFS file system. The logform command does not report any error when input log device has a wrong ly type. The user should pay attention to the ly type.

When you run the logform command on a device with logical volume type jfs2, if the device has a file system with an inline log, then the inline log will be reformatted. If the device has a file system with an outline log, then an error will be reported.

When the logform command is used to format an inline log for an existing JFS2 file system, the file system data will not be affected; only the log records are destroyed. The logical volume type for an inline log is the same as for the file system. For a JFS2 file system, the inline log logical volume type is jfs2.

For a JFS2 file system, **logform** formats a maximum of 2047 MBytes of log. If the log size is greater than 2047 MBytes, only 2047 MBytes will be formatted and the rest will left untouched and will not be used.

Flags

-V vfstype [jfs | jfs2]

If specified, vfstype indicates what type of file system the log should be formatted for. If this option is not specified, then the type is obtained from the logical volume's type. Note that for jfs2 log device this flag is always ignored. The logform command is unable to change the lv type according to the value of the -V flag. Therefore the user should create an Iv with the correct Iv type (jfslog or jfs2log) before calling the logform command. Use of this flag is strongly discouraged.

Parameters

LogName

The LogName parameter specifies the absolute path to the logical volume to be initialized (for example, /dev/jfslog1). When the logform command is run on an inline log, LogName is the device name of the file system.

Examples

1. To create a JFS logging device on a newly created volume group, first create a logical volume of type jfslog:

```
mklv -t jfslog -y jfslog1 newvg 1
```

This command creates a jfslog logical volume named jfslog1 in the volume group newvg. The size of the logical volume is 1 logical partition.

2. To format the jfslog1 logical volume once it has been created, enter:

```
logform /dev/jfslog1
```

The jfslog1 logical volume is now ready to be used as a JFS log device.

3. To format the inline log for an existing file system called /j2 which is on the file system device /dev/fs1v00, type:

```
logform /dev/fslv00
```

This formats the inline log for file system /j2, but does not touch the data in the file system.

Files

/etc/filesystems

Lists the known file systems and defines their characteristics, including the log device.

Related Information

The **crfs** command, **mkfs** command, **mklv** command.

The File systems in Operating system and device management explains file system types, management, structure, and maintenance.

The Mounting in Operating system and device management explains mounting files and directories, mount points, and automatic mounts.

The JFS and JFS2 in *Operating system and device management*.

logger Command

Purpose

Makes entries in the system log.

Syntax

logger [-f File] [-i] [-p Priority] [-t Tag] [Message]

Description

The logger command provides an interface to the syslog subroutine, which writes entries to the system log. A *Message* variable can be specified on the command line, which is logged immediately, or a *File* variable is read and each line of the File variable is logged. If you specify no flags or variables, the logger command will wait for you to enter a message from standard input. The messages returned by the LOG KERN facility cannot be logged by this command.

Flags

-f File Logs the specified *File* variable. If the *Message* variable is specified, this flag is ignored.

-i Logs the process ID of the logger process with each line.

-p Priority Enters the message with the specified priority. The Priority parameter may be a number or a

facility.level priority specifier.

-t Tag Marks every line in the log with the specified *Tag* parameter.

Indicates the message to log. If this variable is not specified, the logger command logs either Message

standard input or the file specified with the -f File flag.

Examples

1. To log a message indicating a system reboot, enter:

logger System rebooted

2. To log a message contained in the /tmp/msg1 file, enter:

logger -f /tmp/msg1

3. To log the daemon facility critical level messages, enter:

logger -pdaemon.crit

Exit Status

This command returns the following exit values:

0 Successful completion.

>0 An error occurred.

Files

/usr/bin/logger

Contains the logger command.

Related Information

The syslogd daemon.

The **syslog** subroutine.

login Command

Purpose

Initiates a user session.

Syntax

login [-h HostName] [-p] [-f User | -k] [User [Environment]]

Description

The login command (part of the tsm command) initiates sessions on the system for the user specified by the User parameter. You can also specify environment variables to be added to the user's environment. These are strings of the form Variable=Value. The login command is not normally entered on the command line.

You can configure the login command to create your home directory at your login if you do not have a home directory already. The login command calls the mkuser.sys command to create the home directory and customize the account. To enable this capability, set the mkhomeatlogin attribute of the usw stanza in the /etc/security/login.cfg file to true.

Notes:

- 1. The PATH, IFS, HOME, and SHELL environment variables may not be initialized from the command line.
- 2. The login command supports multibyte user names. It is recommended that the system administrator restrict the user names to characters within the portable character set to remove any ambiguity.
- 3. If the /etc/nologin file exists, the system prevents the user from logging in and displays the contents of the /etc/nologin file. The system does allow the root user to log in if this file exists. The /etc/nologin file is removed when you reboot the system.

The login command can handle Distributed Computing Environment (DCE) user names of up to 1024 characters. DCE user names are stored in the LOGIN environment variable. Because DCE user names do not conform to standard operating system requirements, the first 8 characters of the DCE user name are stored in all standard operating system files and environments.

The **login** command performs the following functions:

Checks accounts The **login** command validates the user's account, ensuring

authentication, logins enabled properly, and correct capacity for the port

used for the login.

The **login** command verifies the user's identity by using the system **Authenticates users**

defined authentication methods for each user. If a password has expired, the user must supply a new password. If secondary authentication methods are defined, these methods are invoked but

need not be successful in order to log in to the system.

Establishes credentials The **login** command establishes the initial credentials for the user from

the user database. These credentials define the user's access rights

and accountability on the system.

The login command initializes the user environment from the user Initiates a session

database, from the command line, and from the /etc/environment configuration file; changes the current directory to the user's home

directory (normally); and runs the user's initial program.

These functions are performed in the order given; if one fails, the functions that follow are not performed.

When a user logs in successfully, the login command makes entries in the /etc/utmp file that tracks current user logins and the /var/adm/wtmp file that is used for accounting purposes. The login command also sets the **LOGIN** and **LOGNAME** environment variables.

Information pertaining to each unsuccessful login is recorded in the /etc/security/failedlogin file. The information stored is the same as that in the /etc/utmp file, except that unrecognizable user names are logged as UNKNOWN USER. This ensures that a password accidentally entered as a user name, for example, is not allowed into the system unencrypted.

After a successful login, the login command displays the message of the day, the date and time of the last successful and unsuccessful login attempts for this account, and the total number of unsuccessful login attempts for this account since the last successful login. These messages are suppressed if there is a .hushlogin file in your home directory.

The **login** command also changes the ownership of the login port to the user. This includes any ports noted as synonyms in the /etc/security/login.cfg file.

In order to preserve the integrity of the system, only one session at a time is allowed to be logged in to a port. This means that the login command entered from the shell prompt cannot succeed, as both the original session and the new login session would be on the same port. However, the exec login command succeeds because a new shell replaces the current one. The login command is typically a built-in shell command, causing the shell to replace itself.

Note: Unless your terminal displays only uppercase letters, your user name should not consist of uppercase letters exclusively.

To log in with multibyte user names, you must first open a Japanese window (aixterm) and initiate a new login from the Japanese window.

Flags

-f User Identifies a user who has already been authenticated. If the real ID of the login process is root

(0), then the user is not authenticated.

Identifies the login as a remote login and specifies with the HostName variable the name of the -h HostName machine requesting the login. This form of the login is used only by the telnetd and rlogind

daemons.

-k Identifies the login as using Kerberos authentication and causes login to pass control to

/usr/bin/k5dcelogin to handle authentication. This form of login is only used by the krshd

daemon.

Preserves the current terminal type by setting it the value of the \$TERM environment variable -p

instead of the type contained in the CuAt/PdAt object classes database.

Security

The **login** command is a PAM-enabled application with a service name of login. System-wide configuration to use PAM for authentication is set by modifying the value of the auth type attribute, in the usw stanza of /etc/security/login.cfg, to PAM AUTH as the root user.

The authentication mechanisms used when PAM is enabled depend on the configuration for the login service in /etc/pam.conf. The login command requires /etc/pam.conf entries for the auth, account, password, and session module types. Listed below is a recommended configuration in /etc/pam.conf for the login service:

```
# AIX login configuration
login auth required /usr/lib/security/pam_aix
login account required /usr/lib/security/pam aix
login session required /usr/lib/security/pam aix
login password required /usr/lib/security/pam_aix
```

Examples

To log in to the system as user jamesd, enter the following at the login prompt:

login: jamesd

If a password is defined, the password prompt appears. Enter your password at this prompt.

Files

/usr/sbin/login Contains the login command. /etc/utmp Contains accounting information. /var/adm/wtmp Contains accounting information. /etc/motd Contains the message of the day.

/etc/passwd Contains passwords.

\$HOME/.hushlogin Suppresses login messages.

/etc/environment Contains user environment configuration information.

/etc/security/login.cfg Contains port synonyms.

/etc/security/lastlog Contains information pertaining to the most recent successful and

unsuccessful login attempts.

/etc/security/failedlogin Contains information pertaining to each unsuccessful login.

Related Information

The getty command, setgroups command, setsenv command, su command tsm command.

The utmp, wtmp, failedlogin file format, lastlog file format.

The authenticate subroutine, setuid subroutine.

Login message suppression in *Operating system and device management*.

Shells in Operating system and device management describes what shells are, the different types of shells, and how shells affect the way commands are interpreted.

logins Command

Purpose

Displays user and system login information.

Syntax

logins [-a] [-m] [-o] [-p] [-s] [-t] [-u] [-x] [-g Groups] [-l Logins]

Description

The logins command displays information about user and system logins. By default, the logins command prints the following:

- Userr ID
- · primary group name
- · primary group ID
- the /etc/passwd account field on user information.

The output is sorted by user ID, displaying system logins followed by user logins.

Depending on the options chosen, the following fields can also be displayed:

- · user or system login
- user ID number
- · multiple group names
- · multiple group IDs
- · home directory
- · login shell
- four password aging parameters
- /etc/passwd account field value (user name or other information)
- · primary group name
- · primary group ID

Flags

-a	In addition to the default output, the -a flag adds two password expiration fields to the
	display. These fields show how many days a password can remain unused before it
	automatically becomes inactive and the date that the password will expire.
-g Groups	Displays all users belonging to group, sorted by user ID. Multiple groups can be specified as
	a comma separated list. Groups must specify valid group names on the system. Comma
	separate names when specifying more than one group.
-I Logins	Displays the requested login. Multiple logins can be specified as a comma-separated list.
	Logins must specify valid user names on the system.
-m	Displays multiple group membership information.
-0	Formats output into one line of colon separated fields.
-p	Displays users without passwords.
-s	Displays all system logins.
-t	Sorts output by user name instead of by user ID.
-u	Displays all user logins.

-x

Prints an extended set of information about each selected user. Information for each user is printed on a separate line containing the home directory, login shell, and password aging information. The extended information includes the following:

- The password status
- · The date on which the password was last changed
- · The number of days required between changes
- · The number of days allowed before a change is needed
- The number of days that the user will receive a password expiration warning message before the password expires

The password status is displayed in an abbreviated form as PS for logins with password, NP for no password or LK for locked.

Exit Status

- 0 The command completed successfully.
- >0 An error occurred.

Examples

1. To list all the logins with no passwords, enter:

```
logins -p
```

The output looks similar to the following:

pwdless	204	staff	1
nopwd	208	staff	1

The **-p** option ensures that only logins with no passwords are listed.

2. To list all the system logins sorted by alphabetical order enter:

```
logins -st
```

The output looks similar to the following:

adm	4	adm	4
bin	2	bin	2
daemon	1	staff	1
1p	11	1p	11
1pd	9	nobody	-2
root	0	system	0
sys	3	sys	3
uucp	5	uucp	5

The -t option prints out the logins sorted alphabetically and not by uid.

3. To list the login details of users "root' and "admin", enter:

```
logins -1 root,adm
```

The output looks similar to the following:

```
root
                 0
                         system
                                          0
adm
                 4
```

4. To list the password aging details of users "root" and "admin" enter:

```
logins -xl root,adm
```

The output looks similar to the following:

```
PS 021102 0 0 0 adm 4 adm /var/adm /sbin/sh PS 000000 0 0 0
```

The **-x** option ensures that extended password information for these logins are retrieved and printed in the output.

5. To display the multiple group information of a particular user in a colon separated format enter:

```
logins -mol root,adm
```

The output looks similar to the following:

```
root:0:system:0::bin:2:sys:3:security:7:cron:8:audit:10:lp:11
adm:4:adm:4:
```

The **-m** option is used here to retrieve the multiple group information of a particular login (user). The **-o** option ensures that the output is displayed in colon separated format.

6. To display the users of the "staff" and "sys" groups in a colon separated format, sorted by user name, enter:

```
logins -tsog staff, sys
```

The output looks similar to the following:

```
bin:2:bin:2:
daemon:1:staff:1:
invscout:200:staff:1:
root:0:system:0:
sys:3:sys:3:
```

Files

/usr/bin/loginsContains the logins command./etc/passwdContains the password file./etc/groupContains the group file.

Related Information

The Isuser command, the Isgroup command.

logname Command

Purpose

Displays login name.

Syntax

logname

Description

The **logname** command displays the login name of the current process. This is the name that the user logged in with and corresponds to the **LOGNAME** variable in the system-state environment. This variable is only set when the user logs into the system.

The **logname** command invokes the **getlogin** subroutine to get the information about the login name.

Security

Access Control: This program is installed as a normal user program in the Trusted Computing Base.

Exit Status

This command returns the following exit values:

Successful completion.

>0 An error occurred.

Examples

To display your login name to standard output, enter:

logname

Files

/usr/bin/logname

Contains the logname command.

Related Information

The **getty** command, the **login** command, the **setgroups** command, the **setsenv** command, the **su** command, the **tsm** command.

The **getlogin** subroutine in AIX 5L Version 5.3 Technical Reference: Base Operating System and Extensions Volume 1.

logout Command

Purpose

Stops all processes on a port.

Syntax

logout

Description

The **logout** command terminates all processes either with the same controlling terminal as the present process or with all processes which have this terminal open. Processes that are not children of the present process are terminated upon access to the terminal. The present process is also terminated. If the **login** command user and the **logout** command user do not match, the **logout** command permission is denied, and the command stops.

Examples

From a shell started by the ksh or bsh command, enter:

logout

Files

/usr/bin/logoutContains the logout command./etc/utmpContains a record of logged-in users.

Related Information

The bsh command, getty command, init command, ksh command, login command, setgroups command, shell command, su command, tsh command tsm command.

The **setuid** subroutine.

Shells in Operating system and device management describes what shells are, the different types of shells, and how shells affect the way commands are interpreted.

look Command

Purpose

Finds lines in a sorted file.

Syntax

look [-d] [-f] String [File ...]

Description

The **look** command searches sorted files specified by the *File* parameter and prints all lines that begin with the string specified by the String parameter. The look command uses a binary search, therefore files specified by the File parameter must be sorted in the C locale collating sequence.

The -d and -f flags affect comparisons as in the sort command. This means a file must be sorted using the -f flag in the sort command before using the look command with the -f flag.

If the File parameter is not specified, the /usr/share/dict/words file is assumed with the collating sequence specified by the -df flags. The sort is completed using the current collating sequence. This should match the collating sequence used to produce the dictionary file. The look command limits the length of a word search to 256 characters.

Flags

- -d Specifies dictionary order. Only letters, digits, tabs, and spaces are considered in comparisons.
- Compares uppercase and lowercase letters as equivalent values. Case is not considered in the sorting so that initial-capital and all-capital words are not grouped together at the beginning of the output.

Note: To use the look -f command, the input file must be sorted with the sort -f command.

Example

To search for all lines in the sortfile file that begin with the letter a, enter:

look a sortfile

File

/usr/share/dict/words

Contains the default dictionary.

Related Information

The grep command, sort command.

Input and output redirection in *Operating system and device management*.

lookbib Command

Purpose

Finds references in a bibliography.

Syntax

lookbib [-n] [Database ...]

Description

The **lookbib** command uses an inverted index made by the **indxbib** command to find sets of bibliographic references. The lookbib command reads keywords typed after the > prompt on the terminal, and retrieves records containing all these keywords. If nothing matches, nothing is returned except another > prompt.

The lookbib command asks if you need instructions and prints some brief information if you type a user-defined affirmative answer.

The Database parameter specifies files that contain bibliographic references, indexes, or similar types of information. It is possible to search multiple databases as long as they have a common index made by the indxbib command. In that case, only the first database name given to the indxbib command is specified to the lookbib command.

If the lookbib command does not find the index files (the .i[abc] files), it looks for a reference file with the same name as the first database, but without the suffixes. It creates a file with a .iq suffix, suitable for use with the fgrep command. It then uses this fgrep command file to find references. Using the .ig file is simpler but slower than using the .i[abc] files, and does not allow the use of multiple reference files.

Flags

Turns off the prompt for instructions.

Files

Database.ia Contains the entry file. Database.ib Contains the posting file. Database.ic Contains the tag file. Database.ig Contains the output file.

Related Information

The addbib command, indxbib command, refer command, roffbib command, sortbib command.

lorder Command

Purpose

Finds the best order for member files in an object library.

Syntax

lorder [-X {32|64|32_64}] File ...

Description

The lorder command reads one or more object or library archive files, looking for external references and writing a list of paired file names to standard output. The first pair of files contains references to identifiers that are defined in the second file.

If object files do not end with .o, the lorder command overlooks them and attributes their global symbols and references to some other file.

Flags

-X mode Specifies the type of object file lorder should examine. The mode must be one of the following:

> 32 Processes only 32-bit object files

> 64 Processes only 64-bit object files

32_64 Processes both 32-bit and 64-bit object files

The default is to process 32-bit object files (ignore 64-bit objects). The mode can also be set with the OBJECT MODE environment variable. For example, OBJECT MODE=64 causes lorder to process any 64-bit objects and ignore 32-bit objects. The -X flag overrides the **OBJECT MODE** variable.

Files

/tmp/sym* Contains temporary files.

Related Information

The ar command, Id command, tsort command, xargs command.

The ar file.

Subroutines Overview in AIX 5L Version 5.3 General Programming Concepts.

Ip Command

The **Ip** command includes information for the AIX Print Subsystem **Ip** and the System V Print Subsystem

AIX Print Subsystem Ip Command

Purpose

Sends requests to a line printer.

Syntax

Ip [-c] [-dQueue] [-m] [-nNumber] [-oOption] [-s] [-tTitle] [-w] [Files]

Description

The Ip command arranges for the files specified by the Files parameter and their associated information (called a request) to be printed by a line printer. If you do not specify a value for the Files parameter, the Ip command accepts standard input. The file name - (dash) represents standard input and can be

specified on the command line in addition to files. The **Ip** command sends the requests in the order specified. If the job is submitted to a local print queue, the **Ip** command displays the following to standard output:

Job number is: nnn

where nnn is the assigned job number. To suppress the job number use the -s flag.

Flags

-c Copies the files to be printed immediately when the **Ip** command is run. The **Ip** command copies files only when requested. No links are created. If you specify the **-c** flag, be careful not to remove any of the files before they are printed. If you do not specify the **-c** flag, changes made to the files after the request is made appear in the printed output.

-d Queue Specifies the print queue to which a job is sent.

-m Sends mail (see the mail command) after the files are printed. By default, no mail is sent

upon normal completion of the print request.

-nNumber Prints the number of copies of printed output. The default number of copies is 1.

-oOptions Specifies that flags specific to the backend be passed to the backend. Thus, for each queue,

other flags not described in this article can be included with the **Ip** command. See the **piobe** command for a list of these flags. Specifying this flag is the same as specifying the **-o** flag for

the **enq** command.

-s Suppresses the automatic return of job numbers. The **Ip** command reports the job number as

the default, the **-s** flag overrides the default.

-tTitle Specifies printing the title of the file on the banner page of the output.

-w Writes a message on the print requesters terminal after the files are printed. If the requester

is not logged in, the **mail** command sends the message. If the user is logged in on multiple windows or terminals, the message may not be sent to the LFT where the command was issued. The message is sent to the first terminal on which the **writesrv** daemon sees the

user to be logged in.

Note: If the **-w** flag is used in conjunction with the **-m** flag, the print requester will only receive mail and will not get a message on the terminal.

Examples

- 1. To print the /etc/motd file on printer 1p0 attached to device d1p0, enter:
 - lp /etc/motd
- 2. To print 30 copies of the **/etc/motd** file using a copy of the file, and to notify the user that the job is completed using mail, enter:

```
lp -c -m -n30 -dlp0:lpd0 /etc/motd
```

3. To print the /etc/motd file using backend flags -f and -a, with a job title of blah, enter:

4. To gueue the MyFile file and return the job number, enter:

lp myfile

5. To queue the MyFile file and suppress the job number, enter:

lp -s myfile

Exit Status

This command returns the following exit values:

- O All input files processed successfully.
- >0 No output device is available, or an error occurred.

Files

/usr/sbin/qdaemon Contains the queuing daemon. /var/spool/lpd/qdir/* Contains the queue requests.

/var/spool/lpd/stat/* Contains information on the status of the devices. /var/spool/qdaemon/* Contains temporary copies of enqueued files.

Contains the queue configuration file. /etc/qconfig

/etc/qconfig.bin Contains digested, binary version of the /etc/qconfig file.

Related Information

The cancel command, enable command, lpr command, lpstat command, mail command.

The writesrv daemon.

The /etc/qconfiq file.

Command for starting a print job (qprt command) in Operating system and device management.

Printing administration in the Printers and printing.

Printers, print jobs, and queues in *Operating system and device management*.

Print spooler in *Printers and printing*.

System V Print Subsystem Ip Command

Purpose

Sends print requests

Syntax

Ip [print-options] [files]

Ip -i request-ID print-options

Description

The first form of the **Ip** command arranges for the named *files* and associated information (collectively called a request) to be printed. If filenames are not specified on the command line, the standard input is assumed. The standard input may be specified along with named files on the command line by listing the filenames and specifying - for the standard input. The files will be printed in the order in which they appear on the command line.

The LP print service associates a unique request-ID with each request and displays it on the standard output. This request-ID can be used later when canceling or changing a request, or when determining its status. See the cancel command for details about canceling a request, and Ipstat for information about checking the status of a print request.

The second form of **Ip** is used to change the options for a request submitted previously. The print request identified by the request-ID is changed according to the print-options specified with this command. The print-options available are the same as those with the first form of the Ip command. If the request has finished printing, the change is rejected. If the request is already printing, it will be stopped and restarted from the beginning (unless the -P flag has been given).

If you enter 1p -?, the system displays the command usage message and returns 0.

Sending a print request

The first form of the **Ip** command is used to send a print request either to a particular printer or to any printer capable of meeting all requirements of the print request.

Flags must always precede filenames, but may be specified in any order.

Printers for which requests are not being accepted will not be considered when the destination is any. (Use the **Ipstat -a** command to see which printers are accepting requests.) However, if a request is destined for a class of printers and the class itself is accepting requests, then all printers in the class will be considered, regardless of their acceptance status.

For printers that take mountable print wheels or font cartridges, if you do not specify a particular print wheel or font with the -S flag, whichever one happens to be mounted at the time your request is printed will be used. The Ipstat -p printer -I command is used to see which print wheels are available on a particular printer. The **Ipstat -S -I** command is used to see what print wheels are available and on which printers. Without the -S flag, the standard character set is used for printers that have selectable character sets.

If you experience problems with jobs that usually print but on occasion do not print, check the physical connections between the printer and your computer. If you are using an automatic data switch or an A/B switch, try removing it and see if the problem clears.

Flags

Make copies of the files to be printed immediately when Ip is invoked. Normally files will not be copied, but will be linked whenever possible. If the -c flag is not specified, the user should be careful not to remove any of the files before the request has been printed in its entirety. It should also be noted that if the -c flag is not specified, any changes made to the named files after the request is made but before it is printed will be reflected in the printed output.

-d dest

Choose dest as the printer or class of printers that is to do the printing. If dest is a printer, then the request will be printed only on that specific printer. If dest is a class of printers, then the request will be printed on the first available printer that is a member of the class. If dest is any, then the request will be printed on any printer that can handle it. Under certain conditions (unavailability of printers, file space limitations, and so on) requests for specific destinations may not be accepted (see **Ipstat**). By default, dest is taken from the environment variable **LPDEST**. If **LPDEST** is not set, then dest is taken from the environment variable PRINTER. If PRINTER is not set, a default destination (if one exists) for the computer system is used. If no system default is set and -T is used, dest will be selected on the basis of content-type specified with the -T flag [see the description of -T]. Destination names vary between systems (see **lpstat**).

-f form-name [-d any]

Print the request on the form form-name. The LP print service ensures that the form is mounted on the printer. If form-name is requested with a printer destination that cannot support the form, the request is rejected. If form-name has not been defined for the system, or if the user is not allowed to use the form, the request is rejected. (see **lpforms**). When the **-d any** flag is given, the request is printed on any printer that has the requested form mounted and can handle all other needs of the print request.

-H special-handling

Print the request according to the value of special-handling. Acceptable values for special-handling are defined below:

hold Do not print the request until notified. If printing has already begun, stop it. Other print requests will go ahead of a held request until it is resumed.

resume

Resume a held request. If it had been printing when held, it will be the next request printed, unless subsequently bumped by an immediate request. The -i flag (followed by a request-ID) must be used whenever this argument is specified.

immediate

(Available only to LP administrators) Print the request next. If more than one request is assigned immediate, the most recent request will be printed first. If another request is currently printing, it must be put on hold to allow this immediate request to print.

-L locale-name

Specify locale-name as the locale to use with this print request. By default, locale-name is set to the value of LC CTYPE. If LC CTYPE is not set, locale-name defaults to the C locale.

Send mail after the files have been printed. By default, mail is not sent upon normal completion of -m the print request.

-n number

Print *number* copies of the output. The default is one copy.

-o options

Specify printer-dependent options. Several such options may be collected by specifying the -o keyletter more than once (that is, -o option[1] -o option[2] ... -o option[n]), or by specifying a list of options with one -o keyletter enclosed in double quotes and separated by spaces (that is, -o "**option[1]** *option[2]* . . . *option[n]*").

nobanner

Do not print a banner page with this request. The administrator can disallow this option at any time.

nofilebreak

Do not insert a form feed between the files given, if submitting a job to print more than one file. This option is not supported by printers configured to use the PS (PostScript®) interface.

length=*scaled-decimal-number*

Print this request with pages scaled-decimal-number long. A scaled-decimal-number is an optionally scaled decimal number that gives a size in lines, characters, inches, or centimeters, as appropriate. The scale is indicated by appending the letter i for inches, or the letter c for centimeters. For length or width settings, an unscaled number indicates lines or characters; for line pitch or character pitch settings, an unscaled number indicates lines per inch or characters per inch (the same as a number scaled with i). For example, length=66 indicates a page length of 66 lines, length=11i indicates a page length of 11 inches, and length=27.94c indicates a page length of 27.94 centimeters. This option may not be used with the -f option and is not supported by the PS (PostScript).

width=scaled-decimal-number

Print this request with pages scaled-decimal-number wide. (See the explanation of scaled-decimal-numbers in the discussion of length, above.) This option may not be used with the -f option and is not supported by the PS (PostScript).

lpi=scaled-decimal-number

Print this request with the line pitch set to scaled-decimal-number. (See the explanation of scaled-decimal-numbers in the discussion of length, above.) This option may not be used with the -f flag and is not supported by the PS (PostScript).

cpi=picalelitelcompressed

Print this request with the character pitch set to pica (representing 10 characters per inch), elite (representing 12 characters per inch), or compressed (representing as many characters per inch as a printer can handle). There is not a standard number of characters

per inch for all printers; see the terminfo database for the default character pitch for your printer. This option may not be used with the -f flag and is not supported by the PS (PostScript).

stty=stty-option-list

A list of options valid for the stty command; enclose the list with single quotes if it contains

-P page-list

Print the pages specified in page-list. This flag can be used only if there is a filter available to handle it; otherwise, the print request will be rejected. The page-list may consist of ranges of numbers, single page numbers, or a combination of both. The pages will be printed in ascending order.

-q priority-level

Assign this request priority-level in the printing queue. The values of priority-level range from 0 (highest priority) to 39 (lowest priority). If a priority is not specified, the default for the print service is used, as assigned by the system administrator. A priority limit may be assigned to individual users by the system administrator.

- -R Remove file(s) after submitting the print request. Use this flag with caution.
- See -T content-type [-r] below. -r
- Suppress the ``request id is ..." message. -S
- -S character-set [-d any]

-S print-wheel [-d any]

Print this request using the specified character-set or print-wheel. If a form was requested and it requires a character set or print wheel other than the one specified with the -S flag, the request is rejected.

For printers that take print wheels: if the print wheel specified is not one listed by the administrator as acceptable for the printer specified in this request, the request is rejected unless the print wheel is already mounted on the printer.

For printers that use selectable or programmable character sets: if the character-set specified is not one defined in the Terminfo database for the printer (see terminfo), or is not an alias defined by the administrator, the request is rejected.

When the -d any flag is used, the request is printed on any printer that has the print wheel mounted or any printer that can select the character set, and that can handle all other needs of the request.

-t title Print title on the banner page of the output. The default is no title. Enclose title in quotes if it contains blanks.

-T content-type [-r]

Print the request on a printer that can support the specified *content-type*. If no printer accepts this type directly, a filter will be used to convert the content into an acceptable type. If the -r flag is specified, a filter will not be used. If -r is specified but no printer accepts the content-type directly, the request is rejected. If the content-type is not acceptable to any printer, either directly or with a filter, the request is rejected.

In addition to ensuring that no filters will be used, the -r flag will force the equivalent of the -o 'stty=-opost' flag.

Write a message on the user's terminal after the files have been printed. If the user is not logged -w in, or if the printer resides on a remote system, then mail will be sent instead. Be aware that messages may be sent to a window other than the one in which the command was originally entered.

-y mode-list

Print this request according to the printing modes listed in mode-list. The allowed values for mode-list are locally defined. This option may be used only if there is a filter available to handle it; otherwise, the print request will be rejected.

The following list describes the *mode-list* options:

-v reverse

Reverse the order in which pages are printed. This filter option is not supported by the LP Print Service.

-y landscape

Change the orientation of a physical page from portrait to landscape.

-y x=number,y=number

Change the default position of a logical page on a physical page by moving the origin.

-y group=number

Group multiple logical pages on a single physical page.

-y magnify=number

Change the logical size of each page in a document.

-o length=number

Select the number of lines in each page of the document.

-P number

Select, by page numbers, a subset of a document to be printed.

-n number

Print multiple copies of a document.

Files

/var/spool/lp/*

Related Information

The **Ipstat** command, and **mail** command.

Ip.cat, Ip.set, Ip.tell Command

Note: This is a System V Print Subsystem command.

Purpose

Default printer filter used by interface programs.

Syntax

/usr/lib/lp/bin/lp.cat [-r] [Rate]

/usr/lib/lp/bin/lp.set H_pitch V_pitch Width Length Charset

/usr/lib/lp/bin/lp.tell Printer

Description

The Ip.cat command is the default printer filter called by the interface programs. Ip.cat reads the file to be printed on its standard input and writes it to the device to be printed on.

Ip.cat handles the following signals:

- normal termination (SIGTERM)
- serial line hangup (SIGHUP due to DCD, Data Carrier Detect, dropping)
- interrupts (SIGINT and SIGQUIT)
- early pipe termination (SIGPIPE)

The **Ip.cat** command aborts a printing job if it has to wait too long on output. The default maximum time to wait is calculated as twice the output buffer size (2 * 1024 bytes) divided by the smallest of the values of the transmission rate, print rate, or the specified Rate (all rates are in characters per second, CPS). A new maximum delay time may be defined by the Rate parameter provided that this increases the delay time. If Rate is 0 then the delay allowed is effectively infinite.

When the -r flag is specified, Ip.cat reports the effective throughput in characters per second. This statistic is printed on the standard error after the transmission of every 1024 bytes.

Interface programs may call the **Ip.set** command to set the character pitch (*H pitch*), line pitch (*V pitch*), page Width, page Length, and character set (Charset) on the printer.

The default units are characters per inch for the character and line pitch, number of columns for width, and number of lines for length. Units may be stated explicitly by appending the values with c for centimeters, and i for inches.

If it cannot set a particular characteristic, **Ip.set** exits with a value of 1 and prints a one letter character code followed by a newline character to the standard error. The character codes are shown in the following table:

Character code	Printer characteristic not set
Н	character pitch
L	page length
S	character set
V	line pitch
W	page width

Interface scripts use Ip.tell to forward descriptions of printer faults to the print service. Ip.tell sends everything that it reads on its standard input to the print service. The print service forwards the message as an alert to the print administrator.

Flags

Specifies reports the effective throughput in characters per second for the Ip.cat command. This -r statistic is printed on the standard error after the transmission of every 1024 bytes.

Exit Status

The following table shows the possible exit values for **lp.cat**:

0	Normal exit; no error
1	Standard input not defined
2	Standard output not defined
3	Printer type (TERM) not defined or not in terminfo database
4	Standard input and output are identical
5	Write failed; printer may be off-line
6	Excessive delay caused timeout; printer may be off-line
7	Hangup (SIGHUP) detected: loss of carrier

Ip.set returns 0 if successful; otherwise it returns 1 on error.

Ip.tell returns:

0	Normal exit; no error
1	Cannot open message queue to the print service
90	Cannot get printer name or key from print service
91	Cannot send message to print service
92	Cannot receive acknowledgment from print service
93	Corrupted acknowledgment received from print service
94	Print service reports message corrupted in transmission

Files

/usr/lib/lp/bin/lp.cat	Full pathname of Ip.cat
/usr/lib/lp/bin/lp.set	Full pathname of Ip.set
/usr/lib/lp/bin/lp.tell	Full pathname of Ip.tell

/etc/lp/model Printer interface programs directory /etc/lp/interfaces Printer interface programs directory

References

The **Ip** command.

The **signal** subroutine.

The **terminfo** file.

Ipadmin Command

Note: This is a System V Print Subsystem command.

Purpose

Configures the LP print service.

Syntax

Adding or Changing the Configuration of a Local Printer

```
Ipadmin -p Printer -v Device [ -D Comment ] [ -A AlertType ] [ -W Minutes ] [ -c Class ] [ -e Printer 1 ] [ -F
FaultRecovery ] [ -f allow: FormList | -f denyFormList ] [ -h ] [ -l Content-Type-List ] [ -i Interface ] [ -l ] [
-M -f Form-Name [ -o File-break ] ] [ -M -S Print-Wheel ] [ -m Model ] [ -O Copy-Options ] [ -o
Print-Options ] [ -o nobanner | -o banner ] [ -r Class ] [ -S List ] [ -s Server-Name [!ServerPrinterName ] ]
[ -T Printer-Type-List ] [ -u allow:Login-Id-List | -u deny:Login-Id-List ] ]
```

Adding or Changing the Configuration of a Remote Printer

```
Ipadmin -p Printer -s ServerName [!ServerPrinterName] -v Device [ -D Comment ] [ -A AlertType ] [ -W
Minutes | [ -c Class | [ -e Printer1 | [ -F FaultRecovery | [ -f allow:FormList | -f denyFormList | [ -h ] [ -l
Content-Type-List | [ -i Interface | [ -i | [ -M -f Form-Name [ -o Filebreak ] ] [ -M -S Print-Wheel ] [ -m
Model | [ -O CopyOptions | [ -o PrintOptions | [ -o nobanner | -o banner | [ -r Class | [ -S List | [ -T
PrinterTypeList ] [ -u allow:LoginIdList | -u deny:LoginIdList ] ] [ -v Device ]
```

Removing a Printer Destination

Ipadmin -x Destination

Setting or Changing the System Default Destination

Ipadmin -d [Destination]

Setting an Alert for a Print Wheel

Ipadmin -S Print-Wheel **-A** AlertType [**-W** Minutes] [**-Q** Requests]

Description

The Ipadmin command configures the LP print service by defining printers and devices. It is used to:

- · Add and change printers
- · Remove printers from the service
- · Set or change the system default destination
- · Define alerts for printer faults
- Mount print wheels
- · Define printers for remote printing services

Printer and class names may be no longer than the maximum length filename allowed for the filesystem type you are using, and may consist of all printable characters except the space, slash, backslash, colon, semicolon, comma, asterisk, question mark, and tilde. The dash can be used in any position except the first position in a printer name.

If you enter lpadmin -?, the system displays the command usage message and returns 0.

For additional information about network printers, see the **lpsystem** command.

Adding or changing a printer

The -p Printer flag is used to configure a new printer or to change the configuration of an existing printer. When you use this form of the **lpadmin** command, you must select one of the following:

- -v Device, required to configure a local printer
- -s ServerNname [!ServerPrinterName], required to configure a remote printer

Removing a printer destination

The -x dest flag removes the destination dest (a printer or a class), from the LP print service. If dest is a printer and is the only member of a class, then the class is deleted. If dest is all, all printers and classes are removed. No other parameters are allowed with -x.

Setting/changing the system default destination

The -d [dest] flag makes dest, an existing printer or class, the new system default destination. If dest is not supplied, then there is no system default destination. No other parameters are allowed with -d. To unset the system default printer, the user can enter the keyword **none**.

Setting an alert for a print wheel

The -S Print-Wheel flag is used with the -A Alert-Type flag to define an alert to mount the print wheel when there are jobs gueued for it. If this command is not used to arrange alerting for a print wheel, no alert will be sent for the print wheel. See the other use of -A flag, with the -p.

The Alert-Types are the same as those available with the -A flag: mail, write, quiet, none, shell-command, and list. See the description of -A, for details about each.

The message sent appears as follows:

The print wheel Print-Wheel needs to be mounted on the printer(s): printer (integer1 requests) integer2 print requests await this print wheel.

The printers listed are those that the administrator had earlier specified were candidates for this print wheel. The number integer1 listed next to each printer is the number of requests eligible for the printer. The number integer2 shown after the printer list is the total number of requests awaiting the print wheel. It will be less than the sum of the other numbers if some requests can be handled by more than one printer.

If the Print-Wheel is all, the alerting defined in this command applies to all print wheels already defined to have an alert.

If the -W flag is not given, the default procedure is that only one message will be sent per need to mount the print wheel. Not specifying the -W flag is equivalent to specifying -W once or -W 0. If Minutes is a number greater than zero, an alert is sent at intervals specified by *minutes*.

If the -Q flag is also given, the alert is sent when a certain number (specified by the argument requests) of print requests that need the print wheel are waiting. If the -Q flag is not given, or requests is 1 or the word any (which are both the default), a message is sent as soon as anyone submits a print request for the print wheel when it is not mounted.

Flags

Notes:

- When creating a new printer, you must specify the -v, or -s flag. In addition, only one of the following may be supplied: -e, -i, or -m; if none of these three flags is supplied, the model standard is used.
- If -s and/or -R flags are specified, the following flags are not valid: -A, -e, -F, -h, -i, -I, -M, -m, -o, **-v**, and **-W**.

-A AlertType [-W minutes]

The -A flag defines an alert to inform the administrator when a printer fault is detected, and periodically thereafter, until the printer fault is cleared by the administrator. If an alert is not defined for a particular printer, mail is sent to user Ip by default. The AlertTypes are:

mail Send the alert message via mail (see mail) to the administrator.

write Write the message to the terminal on which the administrator is logged in. If the administrator is logged in on several terminals, one is chosen arbitrarily.

quiet Do not send messages for the current condition. An administrator can use this option to temporarily stop receiving further messages about a known problem. Once the fault has been cleared and printing resumes, messages will again be sent when another fault occurs with the printer.

none Do not send messages; any existing alert definition for the printer is removed. No alert is sent when the printer faults until a different alert-type (except quiet) is used.

shell-command

Run the shell-command each time the alert needs to be sent. The shell command should expect the message in standard input. If there are blanks embedded in the command, enclose the command in quotes. The mail and write values for this option are equivalent to the values mail login-ID and write login-ID respectively, where login-ID is the current name for the administrator. This will be the login ID of the person submitting this command unless he or she has used the su command to change to another login ID. If the su command has been used to change the login ID, then the login-ID for the new login is used.

list Display the type of the alert for the printer fault. No change is made to the alert. The message sent appears as follows:

The printer *Printer* has stopped printing for the reason given below. Fix the problem and bring the printer back on line. Printing has stopped, but will be restarted in a few minutes; issue an enable command if you want to restart sooner. Unless someone issues a change request

lp -i request-id -P . . .

to change the page list to print, the current request will be reprinted from the beginning.

The reason(s) it stopped (multiple reasons indicate reprinted attempts):

reason

The LP print service can detect printer faults only through an adequate fast filter and only when the standard interface program or a suitable customized interface program is used. Furthermore, the level of recovery after a fault depends on the capabilities of the filter. If the *Printer* is all, the alerting defined in this command applies to all existing printers. If the -W flag is not used to arrange fault alerting for *Printer*, the default procedure is to mail one message to the administrator of Printer per fault. This is equivalent to specifying -W once or -W 0. If minutes is a number greater than zero, an alert is sent at intervals specified by minutes.

-c Class

-d [*Dest*]

-D Comment

-e Printer1

Note: Do not specify the -i and -m flags may not be specified with the -e flag. Specifies the recovery to be used for any print request that is stopped because of a printer fault, according to the value of FaultRecovery:

Saves the Comment for display whenever a user asks for a full description of Printer (see

Copies the interface program of an existing Printer1 to be the interface program for Printer.

Insert Printer into the specified Class. Class is created if it does not already exist.

Makes *dest*, an existing printer or class, the new system default destination.

Ipstat). The LP print service does not interpret this comment.

-F FaultRecovery

continue

Continue printing on the top of the page where printing stopped. This requires a filter to wait for the fault to clear before automatically continuing.

beginning

Start printing the request again from the beginning.

wait Disable printing on *Printer* and wait for the administrator or a user to enable printing again.

During the wait the administrator or the user who submitted the stopped print request can issue a change request that specifies where printing should resume. (See the -i flag of the Ip command.) If no change request is made before printing is enabled, printing will resume at the top of the page where stopped, if the filter allows; otherwise, the request will be printed from the beginning.

The default value of *FaultRecovery* is **beginning**.

deny:FormList

-f allow: FormList | -f Allows or denies the forms in FormLlist to be printed on Printer. By default no forms are allowed on a new printer.

> For each printer, the LP print service keeps two lists of forms: an allow-list of forms that may be used with the printer, and a deny-list of forms that may not be used with the printer. With the -f allow flag, the forms listed are added to the allow-list and removed from the deny-list. With the -f deny flag, the forms listed are added to the deny-list and removed from the allow-list.

If the allow-list is not empty, only the forms in the list may be used on the printer, regardless of the contents of the deny-list. If the allow-list is empty, but the deny-list is not, the forms in the deny-list may not be used with the printer. All forms can be excluded from a printer by specifying -f deny:all. All forms can be used on a printer (provided the printer can handle all the characteristics of each form) by specifying -f allow:all.

The LP print service uses this information as a set of guidelines for determining where a form can be mounted. Administrators, however, are not restricted from mounting a form on any printer. If mounting a form on a particular printer is in disagreement with the information in the allow-list or deny-list, the administrator is warned but the mount is accepted. Nonetheless, if a user attempts to issue a print or change request for a form and printer combination that is in disagreement with the information, the request is accepted only if the form is currently mounted on the printer. If the form is later unmounted before the request can print, the request is canceled and the user is notified by mail.

If the administrator tries to specify a form as acceptable for use on a printer that doesn't have the capabilities needed by the form, the command is rejected.

The Ipadmin command issues a warning when an invalid (nonexistent) form name is submitted with the -f deny: flag.

See the other use of -f, with the -M flag.

Indicates that the device associated with the printer is hardwired. If neither of the mutually exclusive flags, -h and -l, is specified, this flag is assumed.

Allow Printer to handle print requests with the content types listed in a Content-Type-List. If the -I Content-Type-List

list includes names of more than one type, the names must be separated by commas or blank spaces. If they are separated by blank spaces, the entire list must be enclosed in double quotes.

The type **simple** is recognized as the default content type. A **simple** type of file is a data stream containing only printable ASCII characters and the following control characters.

Control Character	Octal Value	Meaning
backspace	10	move back one character, except at beginning of line
tab	11	move to next tab stop
linefeed (newline)	12	move to beginning of next line
form feed	14	move to beginning of next page
carriage return	15	move to beginning of current line

To prevent the print service from considering **simple** a valid type for the printer, specify either an explicit value (such as the printer type) in the content-type-list, or an empty list. If you do want **simple** included along with other types, you must include **simple** in the *content-type-list*.

Except for simple, each content-type name is freely determined by the administrator. If the printer type is specified by the -T option, then the printer type is implicitly considered to be also a valid content type.

Establish a new interface program for Printer. The Interface is the pathname of the new program. Do not specify the -e and -m flags with this flag.

Indicates that the device associated with Printer is a login terminal. The LP scheduler (Ipsched) disables all login terminals automatically each time it is started. The -h flag may not be specified with this flag.

Mounts the form Form-Name on Printer. Print requests that need the pre-printed form Form-Name are printed on Printer. If more than one printer has the form mounted and the user has specified any with the -d flag of the lp command as the printer destination, then the print request is printed on the one printer that also meets the other needs of the request.

The page length and width, and character and line pitches needed by the form are compared with those allowed for the printer, by checking the capabilities in the terminfo database for the type of printer. If the form requires attributes that are not available with the printer, the administrator is warned but the mount is accepted. If the form lists a print wheel as mandatory, but the print wheel mounted on the printer is different, the administrator is also warned but the mount is accepted.

-h

-i Interface

-1

-M -f Form-Name [-a [-o filebreak]]

If the -a flag is given, an alignment pattern is printed, preceded by the same initialization of the physical printer that precedes a normal print request. Printing is assumed to start at the top of the first page of the form. After the pattern is printed, the administrator can adjust the mounted form in the printer and press return for another alignment pattern (no initialization this time), and can continue printing as many alignment patterns as desired. The administrator can quit the printing of alignment patterns by typing q.

If the -o filebreak flag is given, a form feed is inserted between each copy of the alignment pattern. By default, the alignment pattern is assumed to correctly fill a form, so no form feed is added.

A form is unmounted either by mounting a new form in its place or by using the -f none flag. By default, a new printer has no form mounted.

See the other use of -f without the -M.

-M -S Print-Wheel

Mount the Print-Wheel on Printer. Print requests that need the Print-Wheel will be printed on Printer. If more than one printer has Print-Wheel mounted and the user has specified any with the -d flag of the Ip command as the printer destination, then the print request is printed on the one printer that also meets the other needs of the request.

If the Print-Wheel is not listed as acceptable for the printer, the administrator is warned but the mount is accepted. If the printer does not take print wheels, the command is rejected.

A print wheel is unmounted either by mounting a new print wheel in its place or by using the -S none flag. By default, a new printer has no print wheel mounted.

See the other uses of the -S flag without the -M.

-m Model

Select Model interface program, provided with the LP print service, for the printer. DO not use the **-e** and **-i** flags with this flag. The following interface programs are available:

standard

generic printer interface

PS interface for PostScript printers only

By default, the **standard** interface is used.

-O Copy-Option

The -O controls whether or not Ip makes a copy of the user's file(s) when a print job is submitted. The copy-option can be either copy or nocopy. If -O copy is specified, the LP system always copies the user's source files to the spool area when a print job is submitted. If -O nocopy is specified, the files are copied only if the user specifies the -c flag of Ip when submitting the job.

This flag sets the value of the copy-files parameter in the /etc/default/lp file. The value, which can be either on or off, is checked every time a print job is submitted.

-o Printing-Option

Specifies the, in the list below the default given to an interface program if the option is not taken from a preprinted form description or is not explicitly given by the user submitting a request (see Ip). The only -o options that can have defaults defined are listed below.

length=scaled-decimal-number width=scaled-decimal-number cpi=scaled-decimal-number **lpi**=scaled-decimal-number stty='stty-option-list'

scaled-decimal-number refers to a non-negative number used to indicate a unit of size. The type of unit is shown by a trailing letter attached to the number. Three types of scaled decimal numbers can be used with the LP print service:

- numbers that show sizes in centimeters, marked with a trailing c
- numbers that show sizes in inches, marked with a trailing i
- · numbers that show sizes in units appropriate to use, without a trailing letter that is, lines, characters, lines per inch, or characters per inch.

The first four default option values must agree with the capabilities of the type of physical printer, as defined in the terminfo database for the printer type. If they do not, the command is rejected.

The stty-option-list is not checked for allowed values, but is passed directly to the stty program by the standard interface program. Any error messages produced by stty when a request is processed (by the standard interface program) are mailed to the user submitting the request. For each printing option not specified, the defaults for the following attributes are defined in the terminfo entry for the specified printer type.

```
length
width
cpi
1pi
```

The default for stty is

```
stty='9600 cs8 -cstopb -parenb ixon
-ixany opost -olcuc onlcr -ocrnl -onocr
-onlret -ofill nl0 cr0 tab0 bs0 vt0 ff0'
```

You can set any of the **-o** flags to the default values (which vary for different types of printers), by typing them without assigned values, as follows:

```
length=
width=
cpi=
lpi=
stty=
```

-o nobanner

-o banner

-p Printer

-Q Requests

-r Class

-S List

Allows a user to submit a print request specifying that no banner page be printed.

Forces a banner page to be printed with every print request, even when a user asks for no banner page. This is the default; you must specify -o nobanner if you want to allow users to be able to specify **-o nobanner** with the **Ip** command.

Configures a new printer changes the configuration of an existing printer.

Specifies that an alert be sent when a certain number of print Requests that need the print wheel are waiting.

Remove Printer from the specified Class. If Printer is the last member of Class, then Class is removed.

Allows either the print wheels or aliases for character sets named in List to be used on the printer. The -S flag does not let you add items to a List specified with an earlier invocation of -S; instead, it replaces an existing List with a new one. Thus -S differs from the -f, -u, allow, and deny options, which allow you to modify existing lists of available forms and authorized users. Once you've run the -S flag, the print wheels and character sets specified, in List, on the current command line are the only ones available.

If the printer is a type that takes print wheels, then List is a comma or space separated list of print wheel names. Enclose the list with quotes if it contains blanks. These are the only print wheels considered mountable on the printer. You can always force a different print wheel to be mounted, however. Until the flag is used to specify a list, no print wheels is considered mountable on the printer, and print requests that ask for a particular print wheel with this printer is rejected.

If the printer is a type that has selectable character sets, then List is a comma or blank separated list of character set name mappings or aliases. Enclose the list with quotes if it contains blanks. Each mapping is of the form:

known-name=alias

The known-name is a character set number preceded by cs, such as cs3 for character set three, or a character set name from the Terminfo database entry csnm. See terminfo. If this flag is not used to specify a list, only the names already known from the Terminfo database or numbers with a prefix of cs are acceptable for the printer.

If List is the word none, any existing print wheel lists or character set aliases is removed. See the other uses of the -S with the -M flag.

-s Server-Name [!Server-Printer-Name Specifies that you are configuring a remote printer. It makes a server printer accessible to users on your system. *Server-Name* is the name of the system on which the printer is located. It must be listed in the LP systems table. See **Ipsystem**. *Server-Printer-Name* is the name used on the server system for that printer. For example, if you want to access *Printer1* on *Server1* and you want it called *Printer2* on your system, enter **-p** *Printer2* **-s** *Server1!Printer1*.

If Server-Name is a Netware server, defined as -t nuc using the **Ipsystem** command, then Server-Printer-Name can be the name of a Netware queue or Netware printer.

-T Printer-Type-List

Identify the printer as being of one or more *Printer-Type*s. Each *Printer-Type* is used to extract data from the **terminfo** database; this information is used to initialize the printer before printing each user's request. Some filters may also use a *Printer-Type* to convert content for the printer. If this flag is not used, the default *Printer-Type* is unknown; no information will be extracted from **terminfo** so each user request is printed without first initializing the printer. Also, this flag must be used if the following are to work: **-o cpi**, **-o lpi**, **-o width**, and **-o length** flags of the **lpadmin** and **lp** commands, and the **-S** and **-f** flags of the **lpadmin** command.

If the *Printer-Type-List* contains more than one type, then the *content-type-list* of the **-I** option must either be specified as **simple**, as empty (**-I** ""), or not specified at all.

-u allow:Login-ID-List-u deny:Login-ID-List

Allows or denies the users in *Login-ID-List* access to the printer. By default all users on the local system are allowed on a new printer. The *Login-ID-List* parameter may include any or all of the following constructs:

login-ID

a user on the local system

system-name!login-ID

a user on system system-name

system-name!all

all users on system system-name

all!login-ID

a user on all systems

all users on the local system

all!all all users on all systems

For each printer the LP print service keeps two lists of users:

- · An allow-list of people allowed to use the printer
- · A deny-list of people denied access to the printer.

With the **-u allow** flag, the users listed are added to the allow-list and removed from the deny-list. With the **-u deny** flag, the users listed are added to the deny-list and removed from the allow-list.

If the allow-list is not empty, only the users in the list may use the printer, regardless of the contents of the deny-list. If the allow-list is empty, but the deny-list is not, the users in the deny-list may not use the printer. All users can be denied access to the printer by specifying **-u deny:all**. All users may use the printer by specifying **-u allow:all**.

-v Device

Specifies you are configuring a local printer. It associates a *Device* with *Printer*. *Device* is the pathname of a file that is writable by **Ip**. The same *Device* can be associated with more than one printer.

-x Dest

Removes the destination dest (a printer or a class), from the LP print service.

Files

/etc/lp

/var/spool/lp/*

Related Information

The accept command, enable command, lpsched, command, lpsystem command.

Ipar netboot Command

Purpose

Retrieves MAC address and physical location code from network adapters for a partition, or instructs a partition to network boot.

Syntax

To Retrieve MAC Address:

Ipar_netboot -M -n [-v] [-x] [-f] [-i] [-A] -t ent [-D -s Speed -d Duplex -S Server -G Gateway -C Client -K subnetmask | partition name partition profile manage system

To Preform Network Boot:

lpar_netboot [-v] [-x] [-f] [-i] [-g args] [-A -D | [-D] -I phys_loc | [-D] -m maddress] -t ent -s Speed -d Duplex -S Server -G Gateway -C Client -K subnetmask partition_name partition_profile manage_system

Description

The **lpar netboot** command instructs a logical partition to network boot by having the partition send out a bootp request to a server specified with the -S flag. The server can be a NIM server serving SPOT resources or any server serving network boot images.

If the -M and -n flags are specified, the Ipar_netboot command returns the Media Access Control address and the physical location code for a particular type of network adapter specified with the -t flag. When the -m flag is specified, Ipar_netboot boots a partition using a specific network adapter that matches the specified MAC address. When the -I flag is specified, Ipar netboot boots a partition using a specific physical location code for the network adapter that matches the specified physical location code. The matching MAC address or physical location code is dependent upon the hardware resource allocation in the profile the partition was booted in. The Ipar_netboot command also requires arguments for partition name, partition profile (which contains the allocated hardware resources), and the name of the managed system that the partition was defined in.

Flags

-A -C Client	Returns all adapters of the given type. Specifies the IP address of the machine to network boot.
-D	Performs a ping test so the adapter can successfully ping the server specified with the -S flag.
-d Duplex	Specifies the duplex setting of the machine specified with the -C flag.
-f	Forces a close virtual terminal session for the partition.
-G Gateway	Specifies the gateway IP address of the machine specified with the -C flag.
-g args	Specifies generic arguments for booting.
-i	Forces an immediate shutdown of the partition.

-K subnetmask

-I phys_loc

-M

-m maddress

-S Server

-s Speed

-t ent

-X

Specifies the mask that the gateway should use in determining the appropriate subnetwork for routing. The subnet mask is a set of 4 bytes, as in the Internet address. The subnet mask consists of high bits (1s) corresponding to the bit positions of the network and subnetwork address, and low bits (0s) corresponding to the bit positions of the host address.

Specifies the physical location code of the network adapter to network boot.

Displays the network adapter MAC address and physical location code.

Specifies the MAC address of the network adapter to network boot.

Instructs the partition to not network boot.

Specifies the IP address of the machine to retrieve the network boot image during network boot.

Specifies the speed setting of the machine specified with the -C flag.

Specifies the type of adapter for MAC address or physical location code discovery, or for network boot.

Displays additional information while the command is

Displays debug output while the command is running.

Parameters

partition_name partition_profile managed_system Specifies the name of the partition.

Specifies the name of the partition profile to use.

Specifies the name of the managed system on which the partition is defined.

Exit Status

Successful completion

Security

Access Control: You must have root authority to run the <code>lpar_netboot</code> command.

Examples

To retrieve MAC address and physical location code for partition mach with a partition profile machA_prof on a managed system test_sys, type:

```
lpar netboot -M -n -t ent "machA" "machA prof" "test sys"
```

To network boot partition machA with a partition profile machA prof on a managed system test sys, type:

```
lpar netboot -t ent -s auto -d auto -S 9.3.6.49 -G 9.3.6.1 -C 9.3.6.234
           "machA" "machA_prof" "test_sys"
```

3. To network boot partition machA with a specific MAC address of 00:09:6b:dd:02:e8 and a partition profile machA prof on a managed system test sys, type:

```
lpar netboot -t ent -m 00096bdd02e8 -s auto -d auto -S 9.3.6.49 -G 9.3.6.1
            -C 9.3.6.234 "machA" "machA_prof" "test_sys"
```

To network boot partition machA with a specific physical location code of U1234.121.A123456-P1-T6 and a partition profile machA prof on a managed system test sys, type:

```
lpar netboot -t ent -1 U1234.121.A123456-P1-T6 -s auto -d auto -S 9.3.6.49
             -G 9.3.6.1 -C 9.3.6.234 "machA" "machA prof" "test sys"
```

5. To perform a ping test and a network boot of partition machA with a partition profile machA prof on a managed system test sys, type:

```
lpar netboot -t ent -D -s auto -d auto -S 9.3.6.49 -G 9.3.6.1 -C 9.3.6.234
             "machA" "machA prof" "test sys"
```

Location

/usr/sbin/lpar netboot

Files

/usr/sbin/installios /etc/niminfo

Contains the installios command. Contains variables used by NIM.

Related Information

The **nim** command, **nim master setup** command, **nimconfig** command.

Iparstat Command

Purpose

Reports logical partition (LPAR) related information and statistics.

Syntax

Iparstat { [-i | -d | -H | [-h] [*Interval* [*Count*]] }

Description

The Iparstat command provides a report of LPAR related information and utilization statistics. This command provides a display of current LPAR related parameters and Hypervisor information, as well as utilization statistics for the LPAR. An interval mechanism retrieves numbers of reports at a certain interval.

The various options of **Iparstat** command are exclusive of each other. The **Iparstat** command with no options will generate a single report containing utilization statistics related to the LPAR since boot time. If the -h option is specified, the report will include summary statistics related to the Hypervisor. If an Interval and Count are specified, the above report display repeats for every Interval seconds and for Count iterations. Interval and Count cannot be used with the -i option. Only root users can run the -h and -H options.

When the Iparstat command is invoked without the -i option, two rows of statistics are displayed. The first row displays the System Configuration, which is displayed once when the command starts and again whenever there is a change in the system configuration. The second row contains the Utilization Statistics which will be displayed in intervals and again any time the values of these statistics are deltas from the previous interval.

The following information is displayed in the system configuration row:

Partition Type. Can be either dedicated or shared. type

mode Indicates whether the partition processor capacity is capped or uncapped allowing it to consume idle cycles from the shared pool. Dedicated LPAR is capped or donating.

smt Indicates whether simultaneous multi-threading is enabled or disabled in the partition. If there are two SMT threads, the row is displayed as "on." However, if there are more than two SMT threads, the number of SMT threads is displayed.

lcpu Number of online logical processors.

mem Online Memory Capacity.

Number of online physical processors in the pool. psize

ent Entitled processing capacity in processor units. This information is displayed only if the partition type is shared.

The following information is displayed in the utilization row:

%user Shows the percentage of the entitled processing capacity used while executing at the user level (application).

For dedicated partitions, the entitled processing capacity is the number of physical processors.

For uncapped partitions with a current physical processor consumption above their entitled capacity, the percentage becomes relative to the number of physical processor consumed (physc).

%sys Shows the percentage of the entitled processing capacity used while executing at the system level (kernel).

For dedicated partitions, the entitled processing capacity is the number of physical processors.

For uncapped partitions with a current physical processor consumption above their entitled capacity, the percentage becomes relative to the number of physical processor consumed (physc).

Shows the percentage of the entitled processing capacity unused while the partition was idle and did not have any outstanding disk I/O request.

For dedicated partitions, the entitled processing capacity is the number of physical processors.

For uncapped partitions with a current physical processor consumption above their entitled capacity, the percentage becomes relative to the number of physical processor consumed (physc).

%wait

Shows the percentage of the entitled processing capacity unused while the partition was idle and had outstanding disk I/O requests.

For dedicated partitions, the entitled processing capacity is the number of physical processors.

For uncapped partitions with a current physical processor consumption above their entitled capacity, the percentage becomes relative to the number of physical processor consumed (physc).

The following statistics are displayed when the partition type is shared or dedicated-donating:

physc

Shows the number of physical processors consumed.

Shows the number of virtual context switches that are virtual processor hardware preemptions.

The following statistics are displayed only when the partition type is shared:

%entc Shows the percentage of the entitled capacity consumed. Because the time base over which this data is computed can vary, the entitled capacity percentage can sometimes exceed 100%. This excess is noticeable only with small sampling intervals.

lbusy Shows the percentage of logical processor(s) utilization that occurred while executing at the user and system level.

Shows the available physical processors in the shared pool. app

phint Shows the number of phantom (targeted to another shared partition in this pool) interruptions received.

The following statistics are displayed only when the **-h** flag is specified:

%hypv

Shows the percentage of physical processor consumption spent making hypervisor calls.

hcalls Shows the average number of hypervisor calls that were started.

The following statistic is displayed only if the hardware can use the SPURR, and the processor is not running at nominal speed:

%nsp Shows the current average processor speed as a percentage of nominal speed.

The following statistic is displayed only if the turbo-mode accounting is disabled:

%utcvc

Shows the total percentage of unaccounted turbo cycles.

The following statistics are displayed only when the -d flag is specified.

%utuser

Shows the percentage of unaccounted turbo cycles in the user mode execution (application).

%utsys

Shows the percentage of unaccounted turbo cycles in the kernel mode execution (kernel).

%utidle

Shows the percentage of the unaccounted turbo cycles when the partition is idle and does not have any outstanding disk I/O requests.

%utwait

Shows the percentage of the unaccounted turbo cycles when the partition is idle and has outstanding disk I/O request(s).

Flags

-i

Lists details on the LPAR configuration. The various details displayed by the -i option are listed below:

Name Description

Partition Name

Logical partition name as assigned at the HMC.

Partition Number

Number of this Logical Partition.

Online Virtual CPUs

Number of CPUs (virtual engines) currently online.

Maximum Virtual CPUs

Maximum possible number of CPUs (virtual engines).

Online Memory

Amount of memory currently online.

Maximum Memory

Maximum possible amount of Memory.

Type Indicates whether the LPAR is using dedicated or shared CPU resource and if the SMT is turned ON. The Type is displayed in the format [Shared | Dedicated] [-SMT] [-#]

The following list explains the different Type formats:

- · Shared Indicates that the LPAR is running in the Shared processor mode.
- · Dedicated Indicates that the LPAR is running in the dedicated processor mode.
- SMT[-#] Indicates that the LPAR has SMT mode turned ON and the number of SMT threads is 2. If the number of threads is greater than 2, then the number of threads is also displayed.

Mode Indicates whether the LPAR processor capacity is capped, or if it is uncapped and allowed to consume idle cycles from the shared pool. Dedicated LPAR is capped or donating.

Entitled Capacity

The number of processing units this LPAR is entitled to receive.

Variable Capacity Weight

The priority weight assigned to this LPAR which controls how extra (idle) capacity is allocated to it. A weight of -1 indicates a soft cap is in place.

Minimum Capacity

The minimum number of processing units this LPAR was defined to ever have. Entitled capacity can be reduced down to this value.

Maximum Capacity

The maximum number of processing units this LPAR was defined to ever have. Entitled capacity can be increased up to this value.

Capacity Increment

The granule at which changes to Entitled Capacity can be made. A value in whole multiples indicates a Dedicated LPAR.

Maximum Physical CPUs in System

The maximum possible number of physical CPUs in the system containing this LPAR.

-i (continued)

Active Physical CPUs in System

The current number of active physical CPUs in the system containing this LPAR.

Active CPUs in Pool

The maximum number of CPUs available to this LPAR's shared processor pool.

Shared Physical CPUs in system

The number of physical CPUs available for use by shared processor LPARs.

Maximum Capacity of Pool

The maximum number of processing units available to this LPAR's shared processor pool.

Entitled Capacity of Pool

The number of processing units that this LPAR's shared processor pool is entitled to receive

Unallocated Capacity

The sum of the number of processor units unallocated from shared LPARs in an LPAR group. This sum does not include the processor units unallocated from a dedicated LPAR, which can also belong to the group. The unallocated processor units can be allocated to any dedicated LPAR (if it is greater than or equal to 1.0) or shared LPAR of the group.

Physical CPU Percentage

Fractional representation relative to whole physical CPUs that these LPARs virtual CPUs equate to. This is a function of Entitled Capacity / Online CPUs. Dedicated LPARs would have 100% Physical CPU Percentage. A 4-way virtual with Entitled Capacity of 2 processor units would have a 50% physical CPU Percentage.

Minimum Memory

Minimum memory this LPAR was defined to ever have.

Minimum Virtual CPUs

Minimum number of virtual CPUs this LPAR was defined to ever have.

Unallocated Weight

Number of variable processor capacity weight units currently unallocated within the LPAR group.

Partition Group ID

LPAR group that this LPAR is a member of.

Shared Pool ID

Identifier of Shared Pool of Physical processors that this LPAR is a member.

Provides detailed Hypervisor information. This option basically displays the statistics for each of the Hypervisor calls. The various Hypervisor statistics displayed by this option, for each of the Hypervisor calls, are as below:

Statistic

Description

Number of calls

Number of Hypervisor calls made.

Total Time Spent

Percentage of total time spent in this type of call.

Hypervisor Time Spent

Percentage of Hypervisor time spent in this type of call.

Average Call Time

Average call time for this type of call in nano-seconds.

Maximum Call Time

Maximum call time for this type of call in nano-seconds.

Adds summary hypervisor statistics to the default **Iparstat** output.

-H

-d

Shows the detailed CPU utilization statistics. When the turbo-mode accounting is disabled, the Iparstat command shows the breakdown by category of the unaccounted turbo cycles along with the dedicated, donating or shared utilization columns: %user, %sys, %idle, %wait, %entc, %idon, %bdon, %istol and %bstol.

Note: If Pool Utilization Authority (PUA) is not available, the app column is not displayed.

Examples

1. To get the default LPAR statistics, enter:

```
lparstat 1 1
```

2. To get default LPAR statistics with summary statistics on Hypervisor, enter:

```
lparstat -h 1 1
```

3. To get the information about the partition, enter:

```
lparstat -i
```

4. To get detailed Hypervisor statistics, enter:

```
lparstat -H 1 1
```

Files

/usr/bin/lparstat

Contains the **Iparstat** command.

Related Information

The mpstat command, iostat command, vmstat command, sar command.

Ipc Command

Note: This is a System V Print Subsystem command.

Purpose

Provides (BSD) line printer control.

Syntax

/usr/ucb/lpc [Command [Parameter . . .]]

Description

The **lpc** command controls the operation of the printer or of multiple printers. The **lpc** command can be used to start or stop a printer, disable or enable a printer's spooling queue, rearrange the order of jobs in a queue, or display the status of each printer, along with its spooling queue and printer daemon.

If you enter 1pc -?, the system displays the command usage message and returns 0.

With no parameters, the **lpc** command runs interactively, prompting with 1pc>. If parameters are supplied, the **lpc** command interprets the first as a Command to execute; each subsequent parameter is taken as a Parameter for that command. The standard input can be redirected so that the Ipc command reads Commands from a file.

Commands may be abbreviated to an unambiguous substring.

Note: The printer parameter is specified just by the name of the printer (as Iw), not as you would specify it to Ipr or Ipq (not as -PIw).

```
? [ Command. . . ]
help [ Command . . . ]
abort [ all | [ Printer . . . ] ]
clean [ all | [ Printer . . . ] ]
disable [ all | [ Printer . . . ] ]
down [ all | [ Printer. . . ] ] [ Message ]
enable [ all | [ Printer. . . ] ]
exit
quit
restart [ all | [ Printer.... ] ]
start [ all | [ Printer... ] ]
status [ all | [ Printer...].]
stop [ all | [ Printer... ] ]
topq Printer [ Job#...] [ User... ]
up [ all | [ Printer...] ]
```

Files

/var/spool/lp/*
/var/spool/lp/system/pstatus

Error Codes

?Ambiguous command ?Invalid command

Displays a short description of each command specified in the parameter list or, if no parameters are given, a list of the recognized commands.

Terminates an active spooling daemon on the local host immediately and then disables printing (preventing new daemons from being started by **lpr**) for the specified printers. The **abort** command can only be used by a privileged user.

Removes all files created in the spool directory by the daemon from the specified printer queues on the local machine. The **clean** command can only be used by a privileged user.

Turns the specified printer queues off. This prevents new printer jobs from being entered into the queue by **lpr**. The **disable** command can only be used by a privileged user.

Turns the specified printer queue off, disables printing, and puts *Message* in the printer status file. The message does not need to be quoted. The remaining parameters are treated like **echo**. This is normally used to take a printer down and let others know why (**Ipq** indicates that the printer is down, as does the **status** command).

Enables spooling on the local queue for the listed printers so that **lpr** can put new jobs in the spool queue. The **enable** command can only be used by a privileged user.

Exits from **Ipc**.

Quits from Ipc.

Attempts to start a new printer daemon. This is useful when some abnormal condition causes the daemon to die unexpectedly leaving jobs in the queue. This command can be run by any user.

Enables printing and starts a spooling daemon for the listed printers. The **start** command can only be used by a privileged user.

Displays the status of daemons and queues on the local machine. This command can be run by any user.

Stops a spooling daemon after the current job completes and disable printing. The **stop** command can only be used by a privileged user.

Moves the print jobs specified by *Job#* or those jobs belonging to *User* to the top (head) of the printer queue. The **topq** command can only be used by a privileged user.

Enables everything and starts a new printer daemon. Undoes the effects of **down**.

The abbreviation matches more than one command. A command or abbreviation is not recognized.

?Privileged command

Ipc: printer: unknown printer to the print service

lpc: error on opening queue to spooler

lpc: Can't send message to LP print service lpc: Can't receive message from LP print service

lpc: Received unexpected message from LP print service

The command can be executed only by the privileged

The *printer* was not found in the System V LP database. Usually this is a typing mistake; however, it may indicate that the printer does not exist on the system. Use Iptstat **-p** to find the reason.

The connection to **Ipsched** on the local machine failed. This usually means the printer server started at boot time has died or is hung. Check if the printer spooler daemon /usr/lib/lp/lpsched is running.

Indicates that the LP print service has been stopped. Get help from the system administrator.

It is likely there is an error in this software. Get help from system administrator.

Related Information

The **lpq** command, **lpr** command, **lprm** command, **lpsched** command.

Ipd Command

Purpose

Provides the remote print server on a network.

Syntax

lpd [-d] [-l] [-D DebugOutputFile]

Description

The Ipd daemon is the remote print server. It monitors port 515 for print requests. Each request is placed in a directory named /var/spool/lpd.

A computer on a network (host) that can create a Transmission Control Protocol/Internet Protocol (TCP/IP) data stream and use the **lpd** protocol can print remotely or act as a print server. As a security feature, the Ipd daemon accepts print requests only from remote hosts that are listed in the local /etc/hosts.equiv or /etc/hosts.lpd file.

The **lpd** daemon can run on any host in the network; its function is to accept print requests from foreign hosts (on port 515). The **lpd** daemon handles each request by forking a child process. Remote requests are first checked against the /etc/hosts.equiv and /etc/hosts.lpd files for permission to print on the local host.

Changes can be made to the /etc/hosts.equiv and /etc/hosts.lpd files without restarting the system. To put changes to these files into effect without restarting the system, use the System Resource Controller (SRC) refresh command. This command causes the /etc/hosts.equiv and /etc/hosts.lpd database files to be reloaded and the changes implemented.

Note: The queuing system does not support multibyte host names.

The /etc/locks/lpd file contains the process ID of the currently running instance of the lpd daemon. If the current machine becomes inoperable, you may need to remove the ID for the Ipd daemon when the system starts up again. The error message displayed is 1pd: lock file or duplicate daemon.

Manipulating the Ipd Daemon with the System Resource Controller

The Ipd daemon is a subsystem controlled by the System Resource Controller (SRC). The Ipd daemon is a member of the TCP/IP system group.

Use the following SRC commands to manipulate the **lpd** daemon:

Starts a subsystem, group of subsystems, or a subserver. startsrc stopsrc Stops a subsystem, group of subsystems, or a subserver.

refresh Causes the subsystem or group of subsystems to reread the appropriate configuration file.

traceson Enables tracing of a subsystem, group of subsystems, or a subserver. tracesoff Disables tracing of a subsystem, group of subsystems, or a subserver. Gets the status of a subsystem, group of subsystems, or a subserver. Issrc

Flags

-d Sends a status of Inactive to be logged with the SRC controller and sends error

messages during socket communication setup failures to the user display.

-1 Sends a status of Active to be logged with the SRC controller and sends valid or

invalid job request messages to the user display.

-D DebugOutputFile Sends extensive debugging output used for problem determination to the file

specified by *DebugOuputFile*. This should only be used during problem determination as the DebugOuputFile can grow large rapidly. If the output file specified already exists, new debugging output is appended to the end of it. If there are any problems creating or writing to the output file, the debugging option

is ignored.

Examples

1. To start the **lpd** server daemon, enter:

startsrc -s 1pd

2. To start the **lpd** server daemon while enabling the display of certain error messages, enter:

startsrc -s lpd -a " -d"

3. To send logging information to the **stderr** daemon, enter:

startsrc -s lpd -a " -l"

4. To start the **lpd** server daemon in debugging mode with output going to /tmp/dbglpd.out, enter:

startsrc -s lpd -a " -D /tmp/dbglpd.out"

Files

/usr/sbin/lpd Specifies the path to the **lpd** daemon. /dev/lp* Contains the names of print devices.

/etc/hosts.equiv Contains the names of hosts allowed to execute commands and print.

/etc/hosts.lpd Contains the names of hosts allowed to print only.

/var/spool/lpd Contains the spool directory for control, status, and data files.

/etc/locks/lpd Contains the PID of the currently running **lpd** daemon. After a system crash, this PID

may need to be deleted. The following error message indicates the problem:

lpd: lock file or duplicate daemon

Related Information

Remote Printing Overview in the *Printers and printing*.

Ipfilter Command

Note: This is a System V Print Subsystem command.

Purpose

Administers filters used with the LP print service.

Syntax

Ipfilter -f FilterName -F PathName

Ipfilter -f FilterName -

Ipfilter -f FilterName -i

Ipfilter -f FilterName -x

Ipfilter -f FilterName -I

Description

The **Ipfilter** command is used to add, change, delete, and list a filter used with the LP print service. These filters are used to convert the content type of a file to a content type acceptable to a printer.

If you enter lpfilter -?, the system displays the command usage message and returns 0.

Flags

- (hyphen) Adds or changes a filter as specified from standard input.

-f FilterName
 -F PathName
 Specifies the name of the filter to be added, changed, deleted, or listed.
 Add or changes a filter as specified by the contents of the file pathname.

-i Resets an original filter to its original settings.

-I Lists a filter description.

-x Deletes a filter.

The parameter **all** can be used instead of a *FilterName* with any of these flags. When **all** is specified with the **-F** or **-** flag, the requested change is made to all filters. Using **all** with the **-i** flag has the effect of restoring to their original settings all filters for which predefined settings were initially available. Using the **all** parameter with the **-x** flag results in all filters being deleted, and using it with the **-I** flag produces a list of all filters.

Adding or changing a filter

The filter named in the **-f** flag is added to the filter table. If the filter already exists, its description is changed to reflect the new information in the input.

The filter description is taken from the *PathName* if the **-F** flag is given or from the standard input if the **-** flag is specified. One of the two must be given to define or change a filter. If the filter named is one originally delivered with the LPprint service, the **-i** flag restores the original filter description.

When an existing filter is changed with the **-F** flag or the **-** flag, items that are not specified in the new information are left as they were. When a new filter is added with this command, unspecified items are given default values.

Filters are used to convert the content of a request into a data stream acceptable to a printer. For a given print request, the LP print service knows the following:

- Content in the request
- · Name of the printer
- Type of the printer
- Types of content acceptable to the printer
- Modes of printing asked for by the originator of the request

It uses this information to find a filter or a pipeline of filters that converts the content into a type acceptable to the printer.

A list of items that provide input to this command and a description of each item follows. All lists are comma or space separated.

• Input types: content-type-list · Output types: content-type-list · Printer types: printer-type-list

· Printers: printer-list · Filter type: filter-type

· Command: shell-command

Flags: template-list

Input types Gives the types of content that can be accepted by the filter. (The default is any.)

Output types Gives the types of content that the filter can produce from any of the input content types. (The

default is any.)

Printer types Gives the type of printers for which the filter can be used. The LP print service restricts the use

of the filter to these types of printers. (The default is any.)

Printers Gives the names of the printers for which the filter can be used. The LP print service restricts the

use of the filter to just the printers named. (The default is any.)

Marks the filter as a slow filter or a fast filter. Slow filters are generally those that take a long Filter type

time to convert their input. They are run unconnected to a printer to keep the printers from being tied up while the filter is running. If a listed printer is on a remote system, the filter type for it must have the value slow. Fast filters are generally those that convert their input quickly or those that must be connected to the printer when run. These are given to the interface program IP to

run connected to the physical printer.

Command Specifies the program to run to invoke the filter. The full program pathname as well as fixed flags

must be included in the shell-command; additional flags are constructed, based on the

characteristics of each print request and on the "flags" field. A command must be given for each

filter.

The command must accept a data stream as standard input and produce the converted data stream on its standard output. This allows filter pipelines to be constructed to convert data not

handled by a single filter.

Specifies the comma-separated list of templates used by the LP print service to construct flags to **Flags**

the filter from the characteristics of each print request listed in the table later.

In general, each template is of the following form:

keyword-pattern=replacement

The keyword names the characteristic that the template attempts to map into a filter-specific flag; each valid keyword is listed in the table below. A pattern is one of the following: a literal pattern of one of the forms listed in the table, a single asterisk (*), or a regular expression. If pattern matches the value of the characteristic, the template fits and is used to generate a filter-specific

flag. The replacement is what is used as the flag.

Regular expressions are the same as those found in the **ed** or vi commands. This includes the $\setminus (\ldots \setminus)$ and \n constructions, which can be used to extract portions of the pattern for copying into the replacement, and the ``&", which can be used to copy the entire pattern into the replacement.

The replacement can also contain a ``*". It too, is replaced with the entire pattern, just like the ``&" of ed command.

Ip flag	Properties	
-Т	Characteristic Content type (input)	
	Keyword INPUT	
	Possible patterns content-type	
N/A	Characteristic Content type (output)	
	Keyword OUTPUT	
	Possible patterns content-type	
N/A	Characteristic Printer type	
	Keyword TERM	
	Possible patterns printer-type	
-d	Characteristic Printer name	
	Keyword PRINTER	
	Possible patterns printer-name	
-f, -o cpi=	Characteristic Character pitch	
	Keyword CPI	
	Possible patterns integer	
-f, -o lpi=	Characteristic Line pitch	
	Keyword LPI	
	Possible patterns integer	

Ip flag	Properties
-f, -o length=	Characteristic Page length
	Keyword LENGTH
	Possible patterns integer
-f, -o width=	Characteristic Page width
	Keyword WIDTH
	Possible patterns integer
-P	Characteristic Pages to print
	Keyword PAGES
	Possible patterns page-list
-S	Characteristic Character set Print wheel
	Keyword CHARSET CHARSET
	Possible patterns character-set-name print-wheel-name
-f	Characteristic Form name
	Keyword FORM
	Possible patterns form-name
-у	Characteristic Modes
	Keyword MODES
	Possible patterns mode
-n	Characteristic Number of copies
	Keyword COPIES
	Possible patterns integer

For example, the template MODES landscape = -1 shows that if a print request is submitted with the -y landscape flag, the filter is given the flag -I. As another example, the template TERM * = -T * shows that the filter is given the flag -T printer-type for whichever printer-type is associated with a print request using the filter.

As a last example, consider the template MODES prwidth = (.*) = -w1. Suppose a user gives the command Ip -y prwidth=10

From the table above, the LP print service determines that the -y flag is handled by a **MODES** template. The MODES template here works because the pattern ``prwidth\=\(.*\)" matches the prwidth=10 given by the user. The replacement -w\1 causes the LP print service to generate the filter flag -w10.

If necessary, the LP print service constructs a filter pipeline by concatenating several filters to handle the user's file and all the print flags. If the print service constructs a filter pipeline, the INPUT and OUTPUT values used for each filter in the pipeline are the types of the input and output for that filter, not for the entire pipeline.

Deleting a filter

The -x flag is used to delete the filter specified in *FilterName* from the LP filter table.

Listing a filter description

The -I flag is used to list the description of the filter named in FilterName. If the command is successful, the following message is sent to standard output:

Input types: content-type-list Output types: content-type-list Printer types: printer-type-list Printers: printer-list Filter type: filter-type Command: *shell-command* flags: template-list

If the command fails, an error message is sent to standard error.

Related Information

The **Ipadmin** command.

Ipforms Command

Note: This is a System V Print Subsystem command.

Purpose

Administer forms used with the LP print service.

Syntax

Ipforms -f FormName Options

Ipforms -f FormName -A AlertType [-Q minutes] [-W requests]

Description

The **lpforms** command is used to administer the use of preprinted forms, such as company letterhead paper, with the LP print service. A form is specified by its FormName. Users may specify a form when submitting a print request (see the **Ip** command). The parameter **all** can be used instead of FormName with either of the command lines shown above. The first command line allows the administrator to add.

change, and delete forms, to list the attributes of an existing form, and to allow and deny users access to particular forms. The second command line is used to establish the method by which the administrator is alerted that the form FormName must be mounted on a printer.

If you enter 1pforms -?, the system displays the command usage message and returns 0.

With the first **lpforms** command line, one of the following flags must be used:

Flags

- (hyphen) Adds or changes form FormName, as specified by the information from standard input. Adds or changes form FormName, as specified by the -F pathname information in pathname. -1 Lists the attributes of form FormName. Deletes form FormName (this flag must be used -x separately; it may not be used with any other flag).

Adding or changing a form

The -F pathname flag is used to add a new form, FormName, to the LP print service, or to change the attributes of an existing form. The form description is taken from pathname if the -F flag is given, or from the standard input if the - flag is used. One of these two flags must be used to define or change a form. pathname is the pathname of a file that contains all or any subset of the following information about the form:

Page length: scaled-decimal-number1 Page width: scaled-decimal-number2 Number of pages: integer Line pitch: scaled-decimal-number3 Character pitch: scaled-decimal-number4 Character set choice: character-set/print-wheel [mandatory] Ribbon color: *ribbon-color* Comment: comment Alignment pattern: [content-type] content

The term "scaled-decimal-number" refers to a non-negative number used to indicate a unit of size. The type of unit is shown by a "trailing" letter attached to the number. Three types of scaled decimal numbers can be used with the LP print service: numbers that show sizes in centimeters (marked with a trailing "c"); numbers that show sizes in inches (marked with a trailing "i"); and numbers that show sizes in units appropriate to use (without a trailing letter), that is, lines, characters, lines per inch, or characters per inch.

Except for the last two lines, the above lines may appear in any order. The Comment and comment items must appear in consecutive order but may appear before the other items, and the "Alignment pattern" and the content items must appear in consecutive order at the end of the file. Also, the comment item may not contain a line that begins with any of the key phrases above, unless the key phrase is preceded with a ">". Any leading ">" sign found in the comment are removed when the comment is displayed. Case distinctions in the key phrases are ignored.

When this command is issued, the form specified by FormName is added to the list of forms. If the form already exists, its description is changed to reflect the new information. Once added, a form is available for use in a print request, except where access to the form has been restricted, as described under the -u flag. A form may also be allowed to be used on certain printers only.

A description of each form attribute is below: Page length and Page width Before printing the content of a print request needing this form, the generic interface program provided with the LP print service initializes the physical printer to handle pages scaled-decimal-number1 long, and scaled-decimalnumber2 wide using the printer type as a key into the terminfo database. The page length and page width are also passed, if possible, to each filter used in a request needing this Number of pages Each time the alignment pattern is printed, the LP print service attempts to truncate the content to a single form by, if possible, passing to each filter the page subset of 1-integer. Line pitch and Character pitch Before printing the content of a print request needing this form, the interface programs provided with the LP print service initializes the physical printer to handle these pitches, using the printer type as a key into the terminfo database. Also, the pitches are passed, if possible, to each filter used in a request needing this form. scaled-decimal-number3 is in lines per centimeter if a "c" is appended, and lines per inch otherwise; similarly, scaled-decimal-number4 is in characters per centimeter if a "c" is appended, and characters per inch otherwise. The character pitch can also be given as elite (12 characters per inch), pica (10 characters per inch), or compressed (as many characters per inch as possible). Character set choice When the LP print service alerts an administrator to mount this form, it also mentions that the print wheel print-wheel should be used on those printers that take print wheels. If printing with this form is to be done on a printer that has selectable or loadable character sets instead of print wheels, the interface programs provided with the LP print service automatically selects or loads the correct character set. If mandatory is appended, a user is not allowed to select a different character set for use with the form; otherwise, the character set or print wheel named is a suggestion and a default only. When the LP print service alerts an administrator to mount Ribbon color this form, it also mentions that the color of the ribbon should be ribbon-color.

The LP print service displays the *comment* unaltered when a user asks about this form (see the Ipstat command).

When mounting this form, an administrator can ask for the content to be printed repeatedly, as an aid in correctly positioning the preprinted form. The optional *content-type* defines the type of printer for which *content* had been generated. If content-type is not given, simple is assumed.

> Note: The content is stored as given and is readable only by the user Ip.

When an existing form is changed with this command, items missing in the new information are left as they were. When a new form is added with this command, missing items gets the following defaults:

Comment

Alignment pattern

Page Length: 66 Page Width: 80 Number of Pages: 1 Line Pitch: 6 Character Pitch: 10 Character Set Choice: any Ribbon Color: any

Deleting a form

The -x flag is used to delete the form FormName from the LP print service.

Listing form attributes

The -I flag is used to list the attributes of the existing form FormName. Because of the potentially sensitive nature of the alignment pattern, only the administrator can examine the form with this command. Other people may use the **Ipstat** command to examine the non-sensitive part of the form description.

Allowing and denying access to a form

The -u flag, followed by the parameter allow:login-ID-list or -u deny:login-ID-list lets you determine which users are allowed to specify a particular form with a print request. This flag can be used with the -F or flag.

The login-ID-list parameter may include any or all of the following constructs:

login-ID A user on the local system system-name!login-ID A user on system system-name system-name!all All users on system system-name

all!login-ID A user on all systems all All users on the local system all!all All users on all systems

The default value of *login-ID-list* is **all**.

The LP print service keeps two lists of users for each form: an "allow-list" of people allowed to use the form, and a "deny-list" of people that may not use the form.

- If allow-list is present and *login-ID* is in it, access is allowed.
- If only deny-list is present and *login-ID* is not in it, access is allowed.
- If *login-ID* is in deny-list, access is denied.
- If neither allow-list or deny-list are present, access is denied.
- If both lists are present, and *login-ID* is in neither, access is denied.
- If only allow-list is present and *login-ID* is not in it, access is denied.

If the allow-list is not empty, only the users in the list are allowed access to the form, regardless of the contents of the deny-list. If the allow-list is empty but the deny-list is not, the users in the deny-list may not use the form (but all others may use it).

All users can be denied access to a form by specifying -f deny:all. All users can be allowed access to a form by specifying -f allow:all. (This is the default.)

Setting an alert to mount a form

The -f FormName flag is used with the -A AlertType flag to define an alert to mount the form when there are queued jobs which need it. If this flag is not used to arrange alerting for a form, no alert is sent for that form.

The method by which the alert is sent depends on the value of the AlertType parameter specified with the -A flag. The alert types are the same as those available with the -A flag to Ipadmin: mail, write, quiet, none, shell-command, and list. See the description of -A on Ipadmin for details about each.

The message sent appears as follows:

```
The form FormName needs to be mounted
on the printer(s):
printer (integer1 requests).
integer2 print requests await this form.
Use the ribbon-color ribbon.
Use the print-wheel print wheel, if appropriate.
```

The printers listed are those that the administrator had earlier specified were candidates for this form. The number integer1 listed next to each printer is the number of requests eligible for the printer. The number integer2 shown after the list of printers is the total number of requests awaiting the form. It is less than the sum of the other numbers if some requests can be handled by more than one printer. The ribbon-color and print-wheel are those specified in the form description. The last line in the message is always sent, even if none of the printers listed use print wheels, because the administrator may choose to mount the form on a printer that does use a print wheel.

Where any color ribbon or any print wheel can be used, the statements above read:

```
Use any ribbon.
  Use any print-wheel.
```

If FormName is any, the alerting defined in this command applies to any form for which an alert has not yet been defined. If FormName is all, the alerting defined in this command applies to all forms.

If the -W flag is not given, the default procedure is that only one message is sent per need to mount the form. Not specifying the -W flag is equivalent to specifying -W once or -W 0. If minutes is a number greater than 0, an alert is sent at intervals specified by minutes.

If the -Q flag is also given, the alert is sent when a certain number (specified by the parameter requests) of print requests that need the form are waiting. If the -Q flag is not given, or the value of requests is 1 or any (which are both the default), a message is sent as soon as anyone submits a print request for the form when it is not mounted.

Listing the current alert

The -f flag, followed by the -A flag and the parameter list is used to list the type of alert that has been defined for the specified form FormName. No change is made to the alert. If FormName is recognized by the LP print service, one of the following lines is sent to the standard output, depending on the type of alert for the form.

```
When requests requests are queued:
alert with shell-command every minutes minutes
When requests requests are queued:
write to user-name every minutes minutes
When requests requests are queued:
mail to user-name every minutes minutes
No alert
```

The phrase "every minutes minutes" is replaced with "once" if minutes (-W minutes) is 0.

Terminating an active alert

The -A quiet flag is used to stop messages for the current condition. An administrator can use this flag to temporarily stop receiving further messages about a known problem. Once the form has been mounted and then unmounted, messages are again sent when the number of print requests reaches the threshold requests.

Removing an alert definition

No messages are sent after the -A none flag is used until the -Aflag is given again with a different AlertType. This can be used to permanently stop further messages from being sent as any existing alert definition for the form is removed.

Related Information

The **Ipadmin** command.

The terminfo file.

Iphistory Command

Purpose

Lists or clears a certain number of least-privilege (LP) commands that were previously issued during the current resource monitoring and control (RMC) session.

Syntax

- To list a particular number of previously-issued commands:
 - On the local node:

```
Iphistory [-h] [-TV] [number of commands]
```

- On all nodes in a domain:

```
Iphistory –a [-h] [-TV] [number of commands]
```

- On a subset of nodes in a domain:

```
lphistory -n host1[,host2...] [-h] [-TV] [number_of_commands]
```

- · To clear the history list:
 - On the local node:

```
Iphistory -c [-h] [-TV]
```

- On all nodes in a domain:

```
Iphistory -c -a [-h] [-TV]
```

- On a subset of nodes in a domain:

```
Iphistory -c -n host1[,host2,...] [-h] [-TV]
```

Description

The **Iphistory** command either lists or clears a certain number of LP commands that were previously issued during the current RMC session, for all nodes or a subset of nodes within a cluster. By default, the Iphistory command returns the 10 previous LP commands in their entirety, including all parameters and flags. You can use the *number_of_commands* parameter to list up to 1000 commands.

The **Iphistory** –c command clears the LP history list for all nodes or a subset of nodes within a cluster.

This command runs on any node. If you want this command to run on all of the nodes in a domain, use the -a flag. If you want this command to run on a subset of nodes in a domain, use the -n flag. Otherwise, this command runs on the local node.

Flags

- Clears the LP history list. You cannot specify this flag with the *number of commands* parameter. -с
- Displays previously-issued LP commands for all nodes in the domain. The _a CT MANAGEMENT SCOPE environment variable's setting determines the cluster scope. If CT MANAGEMENT SCOPE is not set, the LP resource manager uses scope settings in this order:
 - 1. The management domain, if it exists
 - 2. The peer domain, if it exists
 - 3. Local scope

The **Iphistory** command runs once for the first valid scope that the LP resource manager finds. For example, suppose a management domain and a peer domain exist and the CT_MANAGEMENT_SCOPE environment variable is not set. In this case, Iphistory -a runs in the management domain. To run **lphistory -a** in the peer domain, you must set CT_MANAGEMENT_SCOPE to 2.

-n *host1*[,*host2*,...]

Specifies the node or nodes in the domain on which the LP command history list is to be retrieved or cleared. By default, the LP history list for the local node is retrieved or cleared. The -n flag is valid only in a management or peer domain. If the CT_MANAGEMENT_SCOPE environment variable is not set, the LP resource manager uses scope settings in this order:

- 1. The management domain, if it exists
- 2. The peer domain, if it exists
- 3. Local scope

The **Iphistory** command runs once for the first valid scope that the LP resource manager finds.

- -h Writes the command's usage statement to standard output.
- -T Writes the command's trace messages to standard error.
- -V Writes the command's verbose messages to standard output.

Parameters

number of commands

Specifies the number of LP commands that you want to list, You can list a minimum of 1 command and a maximum of 1000 commands. The default value is 10. You cannot specify this parameter with the -c flag.

Security

To run the **Iphistory** command, you need write permission in the Class ACL of the **IBM.LPCommands** resource class. Permissions are specified in the LP ACLs on the contacted system. See the Ipacl file for general information about LP ACLs and the RSCT Administration Guide for information about modifying them.

Exit Status

- 0 The command has run successfully.
- 1 An error occurred with RMC.
- 2 An error occurred with the command-line interface (CLI) script.
- 3 An incorrect flag was specified on the command line.
- 4 An incorrect parameter was specified on the command line.
- 5 An error occurred with RMC that was based on incorrect command-line input.

6 The resource was not found.

Environment Variables

CT CONTACT

Determines the system that is used for the session with the RMC daemon. When CT_CONTACT is set to a host name or IP address, the command contacts the RMC daemon on the specified host. If CT CONTACT is not set, the command contacts the RMC daemon on the local system where the command is being run. The target of the RMC daemon session and the management scope determine the LP resources that are processed.

CT MANAGEMENT SCOPE

Determines the management scope that is used for the session with the RMC daemon to process the LP resources. The management scope determines the set of possible target nodes where the resources can be processed. The valid values are:

- 0 Specifies local scope.
- 1 Specifies local scope.
- 2 Specifies *peer domain* scope.
- 3 Specifies management domain scope.

If this environment variable is not set, *local* scope is used.

Implementation Specifics

This command is part of the Reliable Scalable Cluster Technology (RSCT) fileset for AIX.

Standard Output

When the -h flag is specified, this command's usage statement is written to standard output. When the -V flag is specified, this command's verbose messages are written to standard output.

Standard Error

All trace messages are written to standard error.

Examples

- 1. To list 20 LP commands that were previously issued on the local node, enter: 1phistory 20
- 2. Suppose nodeA is in a management domain and CT_MANAGEMENT_SCOPE is set to 3. To list the LP command history on **nodeA**, enter:

lphistory -c -n nodeA

Location

/usr/sbin/rsct/bin/lphistory Contains the **Iphistory** command

Related Information

Books: RSCT Administration Guide, for information about modifying LP ACLs.

Commands: chipcmd, isipcmd, mkipcmd, rmipcmd, runipcmd

Information Files: Ipacl, for general information about LP ACLs

Ipmove Command

Note: This is a System V Print Subsystem command.

Purpose

Moves print requests.

Syntax

Ipmove Requests Destination

Ipmove Destination1 Destination2

Description

The **Ipmove** command moves requests that were queued by **Ip** between LP destinations. This command moves a specific Request to the specified Destination. Requests are request-IDs returned by Ip. You can also attempt to move all requests for Destination1 to Destination2. This form of the Ipmove command causes **Ip** to reject any new requests for *Destination1*.

Note: When moving requests, Ipmove never checks the acceptance status (see accept) of the new destination. Also, the request-IDs of the moved requests are not changed, so you can still find their requests. The **Ipmove** command does not move requests that have options (such as content type and form required) that cannot be handled by the new destination.

If a request was originally queued for a class or the special destination any and the first form of Ipmove was used, the destination of the request is changed to New-Ddestination. A request thus affected is printable only on New-Destination and not on other members of the class or other acceptable printers if the original destination was any.

If you enter 1 pmove -?, the system displays the command usage message and returns 0.

Files

/var/spool/lp/*

Related Information

The accept command, enable command, Ip command, Ipadmin command, Ipstat command.

Ippchk Command

Purpose

Verifies files of an installable software product.

Syntax

```
Ippchk [-R { Path | ALL } ] { -c[u] | -f | -l[u] | -v } [-m [1 | 2 | 3]] [-O { [r] [s] [u] } ] [
ProductName [ FileList ... ] ]
```

Description

The **Ippchk** command verifies that files for an installable software product (fileset) match the Software Vital Product Data (SWVPD) database information for file sizes, checksum values, or symbolic links. A fileset is a separately installable option of a software package.

Flags

-O {[r][s][u]}

-f

-1

-v

Performs a checksum operation on the FileList items and verifies that the checksum and -C the file size are consistent with the SWVPD database.

Checks that the FileList items are present and the file size matches the SWVPD database.

Verifies symbolic links for files as specified in the SWVPD database.

-m [1|2|3] Displays three levels of information. The levels are as follows:

Error messages only (default).

2 Error messages and warnings.

Error messages, warnings and informational messages.

Verifies the specified parts of the program. This flag is not needed with standalone systems because without this option all parts are verified by default. The flags specify the following parts:

Indicates the / (root) part is to be verified.

Indicates the /usr/share part is to be verified. s

Indicates the /usr part is to be verified.

-R { Path | ALL } Indicates a user-specified installation location.

> Updates the SWVPD with new checksum or size information from the system when the system information does not match the SWVPD database. This flag sets symbolic links that are found to be missing. This flag is valid with only the -c or -I flag.

Verifies that the / (root), /usr and /usr/share parts of the system are valid with each other. In other words, this flag verifies that all software products installed on the / (root) file system are also installed on the /usr file system and, conversely, all the software products installed in the /usr file system are also installed on the / (root) file system. You cannot specify FileList items with this flag. This flag also verifies requisites.

Note: Only one of the -c, -f, -I, and -v flags can be specified with each use of the Ippchk command.

Parameters

FileList Specifies the file or files to check. This parameter is a list of file names separated by spaces.

The file names can be a single name or a pair of names separated by a colon. The first form specifies a simple file and the second form specifies a member of an archive file, where the first name specifies the member and the second name specifies the archive file that contains the member. The full path name of the file or files must be specified. To specify multiple files you can use the pattern-matching characters * (asterisk) and ? (question mark), but they should be enclosed in a pair of 's (single quotes). Single quotes are recommended to prevent the korn

shell wildcard expansion.

If this parameter is omitted, all files of a software product are checked. If this parameter is specified, it must be preceded by a software product name.

ProductName Specifies the name of the software product whose files are to be checked. If this parameter is omitted, all software products in the SWVPD are checked. To specify multiple software products you can use the pattern-matching characters * (asterisk) and ? (question mark), but they must

be enclosed in a pair of 's (single quotes) to prevent the shell from expanding them.

Exit Status

0 (zero) The command completed successfully.

nonzero An error was found.

The **Ippchk** command returns zero if no errors were found. Any other return value indicates an error was found.

Examples

1. To verify all files that comprise the X11.fnt package, type:

```
lppchk -c X11.fnt
```

2. To verify the symbolic links of all software products whose names begin with X11, type:

```
lppchk -l 'X11*'
```

3. To verify that all filesets have all required requisites and are completely installed, type:

```
1ppchk -v
```

Files

/etc/objrepos/lpp Specifies installation information of all software products on the root.
/usr/lib/objrepos/lpp Specifies installation information of all software products on the /usr file

system

/usr/share/lib/objrepos/lpp Specifies installation information of all software products on the /usr/share

file system.

/etc/objrepos/product Specifies installation and update information of all software products on the

root.

/usr/lib/objrepos/product Specifies installation and update information of all software products on the

/usr file system.

/usr/share/lib/objrepos/product Specifies installation and update information of all the software products on

the /usr/share file system.

/etc/objrepos/inventory Specifies names and locations of files in a software product on the root.

/usr/lib/objrepos/inventory Specifies names and locations of files in a software product on the /usr file

system.

/usr/share/lib/objrepos/inventory Specifies names and locations of files in a software product on the

/usr/share file system.

Related Information

The installp command, sum command, tcbck command.

Ippmgr Command

Purpose

Manages an existing installp image source.

Syntax

Ippmgr -d DirectoryOrDevice [-r | -m MoveDirectory] { [-x] [-X] [-I] [-u] [-b] [-k LANG] } [-p] [-t] [-s] [-V] [-D]

Description

Ippmgr is designed to perform the following functions on an existing installp image source (also known as an **Ipp_source** in the NIM environment):

- Remove duplicate updates (-u Flag).
- 2. Remove duplicate base levels (-b Flag).
- 3. Eliminating updates which are the same level as bases of the same fileset. Such updates can create conflicts that lead to installation failure (-u Flag).
- 4. Remove message and locale filesets other than the language you specify (-k Flag).
- 5. Remove superseded filesets (-x Flag).
- 6. Remove non-system images from a NIM lpp_source resource (-X Flag).

By default, Ippmgr will list all images filtered by the above routines. The "-r" flag can be used to remove the filtered images and the "-m" flag can be used to move the images to another location.

Note: Ippmgr is not intended to replace bffcreate, install anything, or work with installed filesets. It is also not intended to address any issues other than those aforementioned. Before using the "-X" flag, you should have a good understanding of NIM, system images (known as SIMAGES in NIM), and the workings of a NIM lpp_source resource.

Flags

-b -D	Causees Ippmgr to filter for base level duplicates. Specifies debug mode. This flag is for debugging the Ippmgr script. Note: Debug. This produces a large quantity of output and greatly reduces Ippmgr performance. It is not useful for normal operations.
-d DeviceOrDirectory	Specifies the device or directory where the installp images reside. Currently this can be any directory, NFS mount point, or cdrom device. If the directory is not writable, you should use the -t flag. If the target of your operation is a NIM Ipp_source resource, you should specify the Ipp_source location (see the Isnim command). This flag is required for all operations.
-k LANG	Keeps only the message and locale images for the language specified by <i>LANG</i> . All other languages are filtered.
-1	Lists filtered images only. By default, lppmgr will only list all filtered image files unless the "-r" or "-m" flag is specified. The "-l" flag will override the "-r" or "-m" flag.
-m Directory	Moves filtered files to <i>Directory</i> . The location specified by <i>Directory</i> can be any writable directory path. This flag cannot be used with the "-r" flag.
-p	Specifies prompt mode. Prompt when moving or removing files.
-r	Removes files that have been filtered by Ippmgr .
	Note: If the prompt flag is not specified (-p), Ippmgr will remove all filtered files without further user interaction. This flag cannot be used with the "-m" flag.
-S	Prints space usage info. This will print the amount of space a particular fileset is using and the total amount of space in question. Some buffer space is added for file metadata.
-t	Specifies that Ippmgr will <i>not</i> rebuild the .toc file. This can be useful for having a quick look without having to rebuild the entire .toc file, which can take some time. Also, this is required for read-only devices.
-u	Causes Ippmgr to filter for duplicate updates and conflicting updates which are the same level as bases of the same fileset.
-V	Specifies verbose mode. Ippmgr will give more output in certain situations.
-x	Causes Ippmgr to filter for superseded updates.
-X	Filters non-system images from a NIM Ipp_source resource.

Exit Status

- 0 All **Ippmgr** related operations completed successfully.
- >0 An error occurred.

Security

Only the root user can execute Ippmgr.

Examples

- 1. To list all duplicate and conflicting updates in image source directory /myimages, enter: lppmgr -d /myimages -u
- 2. To remove all duplicate and conflicting updates in image source directory /myimages, enter:

```
lppmgr -d /myimages -u -r
```

3. To remove all duplicate and conflicting updates, duplicate base levels, and all message/locale filesets other than "en US" in prompted mode, enter:

```
1ppmgr -d /myimages -purb -k en US
```

4. To move all superseded update images and non SIMAGES from NIM Ipp source location /lpps/433 to directory /backups, enter:

```
lppmgr - d / lpps / 433 - x - X - m / backups
```

Files

/usr/lib/instl/lppmgr

Contains the **Ippmgr** command.

Related Information

The installp command, Islpp command, Isnim command.

Ipq Command

The **lpq** command includes information for the AIX Print Subsystem **lpq** and the System V Print Subsystem Ipq.

AIX Print Subsystem Ipg Command

Purpose

Examines the spool queue.

Syntax

lpq [+ [Number]] [-I | -W] [-P Printer] [JobNumber] [UserName]

Description

The Ipq command reports the status of the specified job or all jobs associated with the specified UserName and JobNumber variables. JobNumber variable specifies the number of the job in the spool queue that you want to view. A *UserName* variable specifies viewing the jobs for the name of the person who submitted the job to that queue.

The **lpq** command reports on any jobs currently in the default queue when invoked without any options. Parameters supplied that are not recognized as parameters are interpreted as user names or job numbers to filter out only those jobs of interest.

For each job submitted (each job called by the **lpr** command), the **lpq** command reports the user's name, current rank in the queue, the name of the job, the job identifier (a number that can be supplied to the Iprm command for removing a specific job), and the total size in blocks. Normally, only as much information as will fit on one line is displayed. Job ordering depends on the algorithm used to scan the spooling directory and is supposed to be FIFO (first-in-first-out). File names making up a job may be unavailable (when the **lpr** command is used as a sink in a pipeline). In this case, the file is indicated as -(standard input).

The display generated by the **lpg** command contains two entries for remote gueues. The first entry contains the client's local queue and local device name and its status information. The second entry follows immediately; it contains the client's local queue name (again), followed by the remote queue name. Any jobs submitted to a remote queue are displayed first on the local side and are moved to the remote device as the job is processed on the remote machine.

Since the status commands communicate with remote machines, the status display may occasionally appear to hang while waiting for a response from the remote machine. The command will eventually time out if a connection cannot be established between the two machines.

Flags

-I Generates the long output format.

+ [Number] Displays the spool queue until it empties. A Number variable is the time in seconds

before the display regenerates.

-P *Printer* Displays the spool queue for the printer specified by the *Printer* variable.

Note: Any destination command line options override both the LPDEST and the

PRINTER environment variables.

-W Displays a wide version of status information with longer queue names, device names,

and job numbers. Longer job number information is available on AIX 4.3.2 and later. This flag cannot be used with the -I flag. If the -I flag and the -W flag are used simultaneously,

the first one specified takes precedence.

Examples

1. To display a job number in the print queue 1p0, enter:

1pq -P 1p0

This command displays a list similar to the following:

0ueue Dev Status Job Files PΡ B1ks CP Rnk User d1p0 1p0 39 83 running motd guest 10 12 1 1

2. To display the status of the default queue in wide format for AIX 4.3.2 or later, enter:

lpq -W

Files

/usr/bin/lpqContains the lpq command./usr/sbin/qdaemonContains the queuing daemon./etc/qconfigContains the queue configuration file.

/etc/qconfig.bin Contains the digested, binary version of the /etc/qconfig file.

/var/spool/lpd/qdir/* Contains queue requests.

/var/spool/lpd/stat/* Contains information on the status of the devices. /var/spool/qdaemon/* Contains temporary copies of enqueued files.

Related Information

The **lpr** command, **lprm** command, **lpstat** command, **qchk** command.

The qconfig file.

Checking print job status (qchk command) in Operating system and device management.

Printers, print jobs, and queues in Operating system and device management.

Print spooler in the Printers and printing.

System V Print Subsystem Ipq Command

Purpose

(BSD) Displays the queue of printer jobs

Syntax

/usr/bin/lpq [-Pprinter] [-I] [+ [interval]] [job# ...] [username ...]

Description

The **lpq** command displays the contents of a printer queue. It reports the status of jobs specified by *job#*, or all jobs owned by the user specified by username. **Ipg** reports on all jobs in the default printer queue when invoked with no arguments.

For each print job in the queue, **Ipq** reports the user's name, current position, the names of input files comprising the job, the job number (by which it is referred to when using Iprm) and the total size in bytes. Normally, only as much information as will fit on one line is displayed. Jobs are normally queued on a first-in-first-out basis. Filenames comprising a job may be unavailable, such as when Ipr is used at the end of a pipeline; in such cases the filename field indicates the standard input.

If **Ipq** warns that there is no daemon present (that is, due to some malfunction), the **Ipc** command can be used to restart a printer daemon.

Output formatting is sensitive to the line length of the terminal; this can result in widely-spaced columns.

Flags

-P printer

Display information about the queue for the specified printer. In the absence of the -P flag, the queue to the printer specified by the PRINTER variable in the environment is used. If the **PRINTER** variable is not set, the queue for the default printer is used.

-1 Display queue information in long format; includes the name of the host from which the job originated.

+[interval]

Display the spool queue periodically until it empties. This option clears the terminal screen before reporting on the queue. If an interval is supplied, Ipq sleeps that number of seconds in between reports.

Files

/var/spool/lp

spooling directory.

/var/spool/lp/tmp/system name/*-0 request files specifying jobs

Error Codes

lpq: printer is printing

The **Ipq** program queries the spooler **LPSCHED** about the status of the printer. If the printer is disabled, the system administrator can restart the spooler using **lpc**.

lpq: printer waiting for auto-retry (offline ?)

The daemon could not open the printer device. The printer may be turned off-line. This message can also occur if a printer is out of paper, the paper is jammed, and so on. Another possible cause is that a process, such as an output filter, has exclusive use of the device. The only recourse in this case is to kill the offending process and restart the printer with **lpc**.

lpq: waiting for host to come up

A daemon is trying to connect to the remote machine named host, in order to send the files in the local gueue. If the remote machine is up, Ipd on the remote machine is probably dead or hung and should be restarted using Ipc.

lpg: sending to host

The files are being transferred to the remote host, or else the local daemon has hung while trying to transfer the files.

lpq: printer disabled reason:

The printer has been marked as being unavailable with **lpc**.

lpg: The LP print service isn't running or can't be reached.

The **Ipsched** process overseeing the spooling queue does not exist. You can restart the printer daemon with Ipc.

lpq: printer: unknown printer

The printer was not found in the System V LP database. Usually this is a typing mistake; however, it may indicate that the printer does not exist on the system. Use **Ipstat -p** to find the reason.

lpq: error on opening queue to spooler

The connection to **Ipsched** on the local machine failed. This usually means the printer server started at boot time has died or is hung. Check if the printer spooler daemon /usr/lib/lp/lpsched is running.

1pq: Can't send message to LP print service

lpg: Can't establish contact with LP print service

These indicate that the LP print service has been stopped. Get help from the system administrator.

lpg: Received unexpected message from LP print service

It is likely there is an error in this software. Get help from system administrator.

Related Information

The **lpc** command, **lpr** command, and **lprm** command.

Ipr Command

The Ipr command includes information for the AIX Print Subsystem Ipr and the System V Print Subsystem lpr.

AIX Print Subsystem Ipr Command

Purpose

Enqueues print jobs.

Syntax

```
lpr [ -f ] [ -g ] [ -h ] [ -j ] [ -l ] [ -m ] [ -n ] [ -p ] [ -r ] [ -s ] [ -P Printer ] [ -# NumberCopies ] [ -C Class ] [ -J
Job ] [ -T Title ] [ -i [ NumberColumns ] ] [ -w Width ] [ File ... ]
```

Description

The **Ipr** command uses a spooling daemon to print the named *File* parameter when facilities become available. If no files are specified, the Ipr command reads from standard input.

Flags

-# Number	Produces multiple copies of output, using the <i>Number</i> variable as the number of copies for
	and file named

-C Class Specifies the print Class as the job classification on the burst page.

Uses a filter that interprets the first character of each line as a standard FORTRAN carriage -f

control character.

The files are assumed to contain standard plot data. -g

-h Suppresses printing of the burst page.

Note: The default is to print a header page and not a trailer page.

-i [Number] Indents output Number spaces. If the Number variable is not given, eight spaces are used as

the default.

-j Specifies that the message Job number is: nnn, where nnn is the assigned job number, be

displayed to standard output. This occurs only if the job is submitted to a local print queue.

-J Job Prints the Job variable as the job name on the burst page. Usually, the **lpr** command uses the

name of the first file.

(Lowercase L) Uses a filter that allows control characters to be printed. -1

-m Sends mail upon completion of spooling.

Uses a filter that formats files containing ditroff (device-independent troff) data. -n

-P Printer Forces output to the Printer variable. If this flag is not specified, the following conditions occur:

• If a default exists, the **lpr** command uses the default printer.

 If the LPDEST environment variable is set, then lpr uses the value specified by the LPDEST variable. If set, this value is always used, even if the PRINTER variable is also set.

• If the PRINTER variable is set and no LPDEST variable is set, then Ipr uses the value specified by the **PRINTER** environment variable.

Note: Any destination command line options override both the LPDEST and the PRINTER environment variables.

Uses the **pr** command to format the file (1pr -p is very much like pr | 1pr). -р

Removes the file upon completion of spooling. -r

Prints from the files specified on the command line rather than trying to copy them (so large -S

files can be printed). This means the data files should not be modified or removed until they have been printed. Note that this flag only works on the local host (files sent to remote printer hosts are copied anyway), and only with named data files. It does not work if the Ipr command

is at the end of a pipeline.

-T Title Uses the Title variable instead of the file name for the title used by the pr command.

-w Number Uses the *Number* variable as the page width for the **pr** command.

Examples

1. To print three copies of the files new.index.c, print.index.c, and more.c, enter:

lpr -#3 new.index.c print.index.c more.c

Prints three copies of the new.index.c file, three copies of the print.index.c file, and three copies of the more.c file.

2. To print three copies of the concatenation of three files new.index.c, print.index.c, and more.c,

cat new.index.c print.index.c more.c | lpr -#3

3. To print Operations on the burst page, followed by file new.index.c, enter:

lpr -C Operations new.index.c

This replaces the system name (the name returned by host name) with Operations on the burst page.

4. To gueue the MyFile file and return the job number, enter:

```
lpr -j MyFile
```

Files

/usr/sbin/qdaemon Queuing daemon. /etc/qconfig Queue configuration file.

/etc/gconfig.bin Digested, binary version of the /etc/qconfig file.

/var/spool/lpd/qdir/* Queue requests.

/var/spool/lpd/stat/* Information on the status of the queues. /var/spool/qdaemon Temporary copies of enqueued files.

Related Information

The **lpd** command, **lpq** command, **lprm** command, **pr** command, **qdaemon** command.

The qconfig file.

Command for starting a print job (gprt command) in Operating system and device management.

Printers, print jobs, and queues in *Operating system and device management*.

Printing administration in the Printers and printing.

Print spooler in the Printers and printing.

System V Print Subsystem Ipr Command

Purpose

(BSD) Sends a job to the printer.

Syntax

/usr/bin/lpr [-P printer] [-# copies] [-C class] [-J job] [-T title] [-i [indent]] [-w cols] [-r] [-m] [-h] [-s] [-filter option] [file ...]

Description

The Ipr command forwards printer jobs to a spooling area for subsequent printing as facilities become available. Each printer job consists of copies of each file you specify. The spool area is managed by the line printer spooler, Ipsched. Ipr reads from the standard input if no files are specified.

Ip is the preferred interface.

Command-line options cannot be combined into a single argument as with some other commands. The command:

```
lpr -fs
```

is not equivalent to

Placing the -s flag first, or writing each option as a separate argument, makes a link as expected.

Ipr -p is not precisely equivalent to pr I Ipr. Ipr -p puts the current date at the top of each page, rather than the date last modified.

Fonts for troff and T[E]X reside on the printer host. It is not possible to use local font libraries.

Ipr objects to printing binary files.

If userA uses **su** to become userB and uses /usr/bin/lpr, then the printer request will be entered as userB, not userA

Flags

-P printer

Send output to the named *printer*. Otherwise send output to the printer named in the **PRINTER** environment variable, or to the default printer, Ip.

-# copies

Produce the number of *copies* indicated for each named file. For example:

```
lpr -#3 index.c lookup.c
```

produces three copies of index.c, followed by three copies of lookup.c. On the other hand,

```
cat index.c lookup.c | lpr -#3
```

generates three copies of the concatenation of the files.

-C class

Print *class* as the job classification on the burst page. For example,

```
lpr -C Operations new.index.c
```

replaces the system name (the name returned by ``hostname") with Operations on the burst page, and prints the file new.index.c.

- -J job Print job as the job name on the burst page. Usually, **Ipr** uses the first file's name.
- -T title Use title instead of the file name for the title used by pr.

-i[indent]

Indent output indent <Space> characters. Eight <Space> characters is the default.

-w cols

Use *cols* as the page width for **pr**.

- -r Remove the file upon completion of spooling, or upon completion of printing with the -s flag.
- Send mail upon completion. -m
- -h Suppress printing the burst page.
- -s Use the full pathnames (not symbolic links) of the files to be printed rather than trying to copy them. This means the data files should not be modified or removed until they have been printed. This flag only prevents copies of local files from being made. Jobs from remote hosts are copied anyway. The -s flag only works with named data files; if the lpr command is at the end of a pipeline, the data is copied to the spool.

filter_option

The following single letter options notify the line printer spooler that the files are not standard text files. The spooling daemon will use the appropriate filters to print the data accordingly.

- -p Use **pr** to format the files (**lpr** -**p** is very much like **pr l lpr**).
- -1 Print control characters and suppress page breaks.
- -t The files contain **troff** (cat phototypesetter) binary data.
- The files contain data from *ditroff* (device independent **troff**). -n
- -d The files contain data from tex (DVI format from Stanford).
- -g The files contain standard plot data as produced by the routine **plot** for the filters used by the printer spooler.

- The files contain a raster image. The printer must support an appropriate imaging model -V such as PostScript in order to print the image.
- -C The files contain data produced by cifplot.
- -f Interpret the first character of each line as a standard FORTRAN carriage control character.

If no filter_option is given (and the printer can interpret PostScript), the string `%!' as the first two characters of a file indicates that it contains PostScript commands.

These filter options offer a standard user interface, and all options may not be available for, nor applicable to, all printers.

Files

/usr/lib/lp/lpsched

System V line printer spooler

/var/spool/lp/tmp/*

directories used for spooling

/var/spool/lp/tmp/system/*-0

spooler control files

/var/spool/lp/tmp/system/*-N

(N is an integer and > 0) data files specified in `*-0' files

Error Codes

lpr: printer: unknown printer

The printer was not found in the LP database. Usually this is a typing mistake; however, it may indicate that the printer does not exist on the system. Use **Ipstat -p** to find the reason.

lpr: error on opening queue to spooler

The connection to **Ipsched** on the local machine failed. This usually means the printer server started at boot time has died or is hung. Check if the printer spooler daemon /usr/lib/lpsched is running.

lpr: printer: printer queue is disabled

This means the gueue was turned off with

/usr/etc/lpc disable printer

to prevent Ipr from putting files in the queue. This is usually done by the system manager when a printer is going to be down for a long time. The printer can be turned back on by a privileged user with Ipc.

1pr: Can't send message to the LP print service

lpr: Can't establish contact with the LP print service

These indicate that the LP print service has been stopped. Get help from the system administrator.

1pr: Received unexpected message from LP print service

It is likely there is an error in this software. Get help from system administrator.

lpr: There is no filter to convert the file content

Use the Ipstat -p -I command to find a printer that can handle the file type directly, or consult with your system administrator.

lpr: cannot access the file

Make sure file names are valid.

Related Information

The **lpc** command, **lpq** command, **lprm** command, and **troff** command.

Iprm Command

The **lprm** command includes information for the AIX Print Subsystem **lprm** and the System V Print Subsystem **lprm**.

AIX Print Subsystem Iprm Command

Purpose

Removes jobs from the line printer spooling queue.

Syntax

lprm [-P Printer] [JobNumber] [UserName ...] [-]

Description

The **lprm** command removes one or more jobs from the spool queue of a printer.

You cannot run the **Iprm** command without specifying a job number, the - (minus sign) flag, or at least one user name.

Specifying a *UserName* parameter, or list of names, causes the **lprm** command to attempt to remove any jobs queued belonging to that user (or users).

You can remove an individual job from a queue by specifying its *JobNumber*. This job number is obtained by using the **Ipq** command.

Flags

Removes all jobs a user owns. Someone with root user authority can use this flag to remove all jobs from a queue. This flag is not valid for remote print.

-P Printer

Specifies the queue associated with a specific *Printer* variable. If this flag is not specified, the following conditions occur:

- If the LPDEST environment variable is set, then Iprm uses the value specified by the LPDEST variable. If set, this value is always used, even if the PRINTER variable is also set.
- If the PRINTER variable is set and no LPDEST variable is set, then Iprm uses the value specified by the PRINTER environment variable.

If neither the **LPDEST** nor the **PRINTER** variable is set, the **lprm** command removes jobs from the default queue.

Note: Any destination command line options override both the **LPDEST** and the **PRINTER** environment variables.

Examples

- 1. To remove job number 13 from the default printer queue, enter:

 | prm 13
- 2. To remove job number 13 from printer queue 1p0, enter:

```
lprm -P lp0 13
```

3. To remove a job from the printer queue for a certain user, enter:

1prm guest

Files

/usr/bin/lprm Contains the lprm command.
/etc/qconfig Contains the configuration file.

Related Information

The **lpq** command, **lpr** command, **qcan** command.

Canceling a print job (gcan command) in Operating system and device management.

System V Print Subsystem Iprm Command

Purpose

(BSD) Remove jobs from the printer queue

Syntax

/usr/bin/lprm [-Pprinter] [-] [job # ...] [username...]

Description

The **lprm** command removes a job or jobs from a printer's spooling queue. Since the spool directory is protected from users, using **lprm** is normally the only method by which a user can remove a job.

Without any arguments, **Iprm** deletes the job that is currently active, provided that the user who invoked **Iprm** owns that job.

When the privileged user specifies a username, **lprm** removes all jobs belonging to that user.

You can remove a specific job by supplying its job number as an argument, which you can obtain using **lpq**. For example:

Iprm reports the names of any files it removes, and is silent if there are no applicable jobs to remove.

Iprm Sends the request to cancel a job to the print spooler, **LPSCHED**.

An active job may be incorrectly identified for removal by an **lprm** command issued with no arguments. During the interval between an **lpq** command and the execution of **lprm**, the next job in queue may have become active; that job may be removed unintentionally if it is owned by you. To avoid this, supply **lprm** with the job number to remove when a critical job that you own is next in line.

Only the privileged user can remove print jobs submitted from another host.

Flags

-Pprinter

Specify the queue associated with a specific printer. Otherwise the value of the **PRINTER** variable in the environment is used. If this variable is unset, the queue for the default printer is used.

Remove all jobs owned by you. If invoked by the privileged user, all jobs in the spool are removed. Job ownership is determined by the user's login name and host name on the machine where the lpr command was executed.

Files

/var/spool/lp/*

spooling directories

Error Codes

lprm: printer: unknown printer

The printer was not found in the System V LP database. Usually this is a typing mistake; however, it may indicate that the printer does not exist on the system. Use Ipstat -p to get the status of printers.

lprm: error on opening queue to spooler

The connection to **Ipsched** on the local machine failed. This usually means the printer server started at boot time has died or is hung. Check if the printer spooler daemon /usr/lib/lp/lpsched is running.

1prm: Can't send message to the LP print service

1prm: Can't receive message from the LP print service

These indicate that the LP print service has been stopped. Get help from the system administrator.

1prm: Received unexpected message from the LP print service

It is likely there is an error in this software. Get help from system administrator.

lprm: Can't cancel request

You are not allowed to remove another user's print request.

Related Information

The **Ip** command, **Ipq** command, **Ipr** command, and **Ipsched** command.

Ipsched Command

Note: This is a System V Print Subsystem command.

Purpose

Starts/stops the print service.

Syntax

/usr/lib/lp/lpsched

Ipshut

Description

The **Ipsched** command starts the LP print service.

The Ipshut command shuts down the print service. All printers that are printing at the time the Ipshut command is invoked stop printing. When Ipsched is started again, requests that were printing at the time a printer was shut down are reprinted from the beginning.

You must have the appropriate privilege to run these commands.

If the scheduler fails to run, check the **Ipsched** log file, which contains all failed attempts to load print requests, printer descriptions, forms, filters, classes, alerts, and systems. The log files are located in /var/lp/logs. Useful information on the networked print service can also be found in the /var/lp/logs/lpNet log file.

If you enter 1psched -?, the system displays the command usage message and returns 0.

Files

/var/spool/lp/*

Related Information

The accept command, enable command, lpadmin command.

Ipstat Command

The Ipstat command includes information for the AIX Print Subsystem Ipstat and the System V Print Subsystem **Ipstat**.

AIX Print Subsystem Ipstat Command

Purpose

Displays line printer status information.

Syntax

lpstat [-aList] [-cList] [-d] [-oList] [-pList] [-r] [-s] [-t] [-uList] [-vList] [-W]

Description

The **Ipstat** command displays information about the current status of the line printer.

If no flags are given, **Ipstat** prints the status of all requests made by the **Ip** command.

Flags can appear in any order and can be repeated. Some flags take an optional list as a parameter. Enter the list as either a list of items separated by commas, as in 1pstat -aQueue1, Queue2, or as a list of items enclosed in single or double quotes and separated either by commas or one or more spaces, as in, for example, lpstat -a"Queue1 Queue2" or lpstat -a"Queue1, Queue2" or lpstat -a'Queue1 Queue2' or lpstat -a'Queue1,Queue2'.

If you specify a flag with no parameters, all information pertaining to that flag is printed.

The display generated by the **Ipstat** command contains two entries for remote gueues. The first entry contains the client's local queue and local device name and its status information. The second entry contains the client's local queue name followed by the remote queue name. The spooling subsystem first displays remote print requests on the local queue. When the remote machine begins to process the remote print job, the status display for the print job moves to the remote queue.

When a status command communicates with a remote host, the display occasionally appears to hang while the command waits for a response from the remote machine. The command eventually times out if no connection is established between the two machines.

Flags

-a List	Provides status and job information on queues. Specifying the Ipstat command with this flag is the same
	as specifying the enq -q -PQueue1 -PQueue2 command (where Queue1, Queue2, etc., are items in
	List).

-cList Provides status and job information on queues. Specifying the **Ipstat** command with this flag is the same as specifying the **enq -q -P**Queue1 **-P**Queue2 ... command (where Queue1, Queue2, etc., are items in List).

-d Prints the status information for the system default destination for the **Ip** command. Specifying the **Ipstat** command with this flag is the same as specifying the **enq** -**q** command.

 -oList Prints the status of print requests or print queues. List is a list of intermixed printer names and job numbers.

-pList Prints the status of printers.

-r Provides status and job information on queues. Specifying the **Ipstat** command with this flag is the same as specifying the **enq** -A command.

-s Displays a status summary, including a list of printers and their associated devices. Specifying the **Ipstat** command with this flag is the same as specifying the **enq** -A command.

-t Displays all status information, including a list of printers and their associated devices. Specifying the **lpstat** command with this flag is the same as specifying the **enq -AL** command.

-uList Prints the status of all print requests for users specified in List. List is a list of login names. Specifying the **lpstat** command with this flag is the same as specifying the **enq -u** UserName command.

-vList Prints the status of printers. The List variable is a list of printer names.

-W Displays a wide version of status information with longer queue names, device names, and job numbers. Longer job number information is available on AIX 4.3.2 and later. This flag cannot be used with the **-t** flag. If the **-t** flag and the **-W** flag are used simultaneously, the first one specified takes precedence.

Exit Status

This command returns the following exit values:

0 Successful completion.

>0 An error occurred.

Examples

1. To display the status for all print queues, enter:

2. To display the long status for all printers, enter:

lpstat -t

3. To display a job number in the print gueue 1p0, enter:

lpstat -plp0

This command displays a list similar to the following:

PΡ Queue Dev Status Job Files User B1ks CP Rnk 39 83 0a1 dlp0 motd 12 running guest 1

4. To display the status for users root, ghandi, and king, enter:

lpstat -u"root,ghandi,king"

5. To display the status of all print queues in wide format for AIX 4.3.2 or later, enter:

lpstat -W

Files

/var/spool/lpd/*

Contains temporary copies of remote enqueued files.

Related Information

The disable command, enable command, enq command, lp command, lpr command, qchk command.

Command for checking print job status (qchk command) in Operating system and device management.

Printers, print jobs, and queues in Operating system and device management.

Print spooler in Operating system and device management.

System V Print Subsystem Ipstat Command

Purpose

Prints information about the status of the LP print service.

Syntax

lpstat [flags] [request-ID-list]

Description

The Ipstat command displays information about the current status of the LP print service. If no flags are given, **Ipstat** displays the status of all print requests made by you. (See **Ip** for more information.)

The command **Ipstat -o** printername is used to list all the requests gueued on the specified printer. If printername points to a remote printer (see **Ipadmin**), then **Ipstat -o** printername lists all the requests on the remote printer, not just those submitted locally.

Any arguments that are not flags are assumed to be request-IDs as returned by Ip. The Ipstat command displays the status of such requests. The flags may appear in any order and may be repeated and intermixed with other arguments. Some of the keyletters below may be followed by an optional list that can be in one of two forms:

- a list of items separated by commas, for example, -p printer1, printer2
- a list of items separated by spaces and enclosed in quotes, for example, -u "user1 user2 user3"

Specifying all after any keyletter that takes list as an argument causes all information relevant to the keyletter to be displayed. For example, the command Ipstat -a all lists the accepting status of all print destinations.

The omission of a list following such keyletters causes all information relevant to the keyletter to be displayed. For example, the command **lpstat -a** is equivalent to **lpstat -a all**.

There are two exceptions to the behavior of the all keyword. The first is when it is used in conjunction with the -o flag: Ipstat -o all only lists requests submitted locally to remote printers. The second is when it is used with directory-enabled print queues. Use of the all keyword will only return non-directory-enabled print queues. Ipstat -a list will report whether the both directory-enabled and non-directory-enabled print queues in list are accepting requests. For the -a and -b flags, lpsched will remember the directory-enabled print gueues specified until it is restarted. Subsequent calls to Ipstat -a and Ipstat -p will report the status of all non-directory-enabled print queues as well as the directory-enabled print queues previously specified. Once Ipsched has been restarted, the use of the all keyword with the Ipstat command will once again only display non-directory-enabled print queues. The dslpsearch command should be used to search for defined directory-enabled print gueues.

If you enter 1pstat -?, the system displays the command usage message and returns 0.

Flags

-a [list]

Report whether print destinations are accepting requests. list is a list of intermixed printer names and class names.

-c [list]

Report names of all classes and their members. *list* is a list of class names.

-d Report what the system default destination is (if any).

-f [list] [-I]

Verify that the forms in list are recognized by the LP print service. list is a list of forms; the default is all. The -I option will list the form parameters.

-o [list] [-l]

Report the status of print requests. list is a list of intermixed printer names, class names, and request-IDs. The keyletter -o may be omitted. The -I option lists for each request whether it is queued for, assigned to, or being printed on a local printer, the form required (if any), and the character set or print wheel required (if any). Note that required forms (if any) are not listed for remote printers.

-p [list] [-D] [-I]

If the -D flag is given, a brief description is printed for each printer in list. If the -I flag is given, a full description of each printer's configuration is given, including the form mounted, the acceptable content and printer types, a printer description, the interface used, and so on.

In order to maintain system security access information, the information needed to produce the printer status given by **Ipstat -p** is available only if the LP scheduler is running.

- Report the status of the LP request scheduler (whether it is running). -r
- -R Report a number showing the rank order of jobs in the print queue for each printer.
- -s [-l] Display a status summary, including the status of the LP scheduler, the system default destination, a list of class names and their members, a list of printers and their associated devices, a list of the systems sharing print services, a list of all forms and their availability, and a list of all recognized character sets and print wheels. The -I flag displays all parameters for each form and the printer name where each character set or print wheel is available.
- -S [/ist] [-I]

Verify that the character sets or the print wheels specified in *list* are recognized by the LP print service. Items in list can be character sets or print wheels; the default for list is all. If the -I flag is given, each line is appended by a list of printers that can handle the print wheel or character set. The list also shows whether the print wheel or character set is mounted or specifies the built-in character set into which it maps.

-t [-l] Display all status information: all the information obtained with the -s flag, plus the acceptance and idle/busy status of all printers and status of all requests. The -I flag displays more detail as described for the -f, -o, -p, and -s flag.

-u [login-ID-list]

Display the status of output requests for users. The login-ID-list argument may include any or all of the following constructs:

login-ID

a user on the local system

system-name!login-ID

a user on system system-name

```
system-name!all
       all users on system system-name
all!login-ID
       a user on all systems
all
       all users on the local system
all!all all users on all systems
```

The default value of *login-ID-list* is all.

Ipsystem Command

Note: This is a System V Print Subsystem command.

Purpose

Registers remote systems with the print service.

Syntax

```
Ipsystem [-T Timeout] [-R Retry] [-y Comment] SystemName [SystemName . . . ]
Ipsystem -I [ SystemName . . . ]
Ipsystem -r SystemName [SystemName . . . ]
lpsystem -A
```

Description

The **Ipsystem** command defines parameters for the LP print service, with respect to communication (via a high-speed network such as TCP/IP) with remote systems.

Specifically, the **Ipsystem** command defines remote systems with which the local LP print service can exchange print requests. These remote systems are described to the local LP print service in terms of several parameters that control communication: type, retry, and timeout. These parameters are defined in /etc/lp/Systems. You can edit this file with a text editor (such as vi), but editing is not recommended. By using **Ipsystem**, you can ensure that **Ipsched** is notified of any changes to the *Systems* file.

The Timeout parameter specifies the length of time (in minutes) that the print service should allow a network connection to be idle. If the connection to the remote system is idle (that is, there is no network traffic) for N minutes, then drop the connection. (When there is more work, the connection is re-established.) Legal values are **n**, **0**, and *N*, where *N* is an integer greater than 0. If a decimal number is used for N, it is truncated to the whole number. The value n means never time out; 0 means as soon as the connection is idle, drop it. The default is **n**.

The Retry parameter specifies the length of time (in minutes) to wait before trying to re-establish a connection to the remote system, when the connection was dropped abnormally (that is, a network error). Legal values are **n**, **0**, and *N*, where *N* is an integer greater than 0. It means wait *N* minutes before trying to reconnect. If a decimal number is used for N, it is truncated to the whole number. (The default is 10 minutes.) The value n means do not retry dropped connections until there is more work; 0 means try to reconnect immediately.

The Comment parameter allows you to associate a free form comment with the system entry. This is visible when **Ipsystem -I** is used.

The SystemName is the name of the remote system from which you want to be able to receive jobs and to which you want to be able to send jobs. A special entry is provided with the /etc/lp/Systems file by default, which allows all connections to **bsd** systems. That entry uses the asterisk (*) as the SystemName.

The command Ipsystem -I [SystemName] prints out a description of the parameters associated with SystemName (if a system has been specified) or with all the systems in its database (if SystemName has not been specified).

The command Ipsystem -r SystemName removes the entry associated with SystemName. The print service no longer accepts jobs from that system or send jobs to it, even if the remote printer is still defined on the local system. The scheduler must be running when the removal of a systems file entry occurs, because the scheduler checks whether the system entry is currently used by a printer destination. If currently used, the system entry cannot be removed.

If you use Ipsystem -r SystemName to remove a system and you have active printers for that system, you will not be allowed to remove the system from the system file. **Ipsystem -r** SystemName only works if no printers for that system exist.

With respect to the semantics of the *Timeout* and *Retry* values, the print service uses one process for each remote system with which it communicates, and it communicates with a remote system only when there is work to be done on that system or work is being sent from that system.

The system initiating the connection is the master process, and the system accepting the connection is the secondary process. This designation serves only to determine which process dies (the secondary) when a connection is dropped. This helps prevent more than one process communicating with a remote system. All connections are bi-directional, regardless of the master/secondary designation. You cannot control a system's master/secondary designation. Typically, a client machine has the master child, and the server machine has the secondary child. If a master process times out, then both the secondary and master exit. If a secondary process times out, then it is possible that the master may still live and retry the connection after the retry interval. Therefore, one system's resource management strategy can affect another system's strategy.

All forms of the **Ipsystem** command accept * (asterisk enclosed in double quotes) for *SystemName*.

Depending upon the configuration of the name server, you may need to change the entry in the SystemName field in /etc/lp/Systems to a full domain name.

If you enter lpsystem -?, the system displays the command usage message and returns 0.

Flags

-I [SystemName]

-r SystemName

-R Retry

-T Timeout

-y Comment

Prints out the TCP/IP address in a format.

Prints out a description of the parameters associated with SystemName or with all the systems in its database. Removes the entry associated with SystemName. Specifies time to wait before trying to reestablish a connection for a remote system.

Specifies the time allowed for a network connection to be idle. Timeout is in minutes. Default is to never time out. The Comment parameter allows you to associate a free-form comment with the system entry.

Security

Only a user with appropriate privileges may execute the **lpsystem** command.

Files

/etc/lp/* /var/spool/lp/*

Related Information

The **Ipsched** command.

Iptest Command

Purpose

Generates the line printer ripple pattern.

Syntax

Iptest [;Length Count]

Description

The Iptest command writes the traditional "ripple" test pattern on a standard output device such as a terminal or a printer. In 96 lines, this pattern will print all 96 printable ASCII characters in each position. While originally created to test printers, the ripple pattern is quite useful for testing terminals, driving terminal ports for debug purposes, or any other task where a quick supply of random data is needed.

Using the **Iptest** command, you can specify the output line length if the default length of 79 is not appropriate. You can also specify the number of output lines to be generated if the default Count parameter of 200 is not appropriate. Note that if Count parameter is specified, Length must also be specified.

Examples

To display or print 100 lines of 80-column test output to standard output, enter: 1ptest 80 100

Related Information

The cancel command, disable command, enable command, Ip command, Ipstat command.

Ipusers Command

Note: This is a System V Print Subsystem command.

Purpose

Set printing queue priorities.

Syntax

Ipusers -d *PriorityLevel*

Ipusers -q PriorityLimit -u LoginIDList

Ipusers -u LoginIDList

Ipusers -q PriorityLimit

lpusers -l

Description

The **Ipusers** command sets limits to the queue priority level that can be assigned to jobs submitted by users of the LP print service.

The first form of the command (with -d) sets the system-wide priority default to PriorityLevel, where PriorityLevel is a value of 0 to 39, with 0 being the highest priority. If a user does not specify a priority level with a print request (see the **Ip** command), the default priority is used. Initially, the default priority level is 20.

The second form of the command (with -q and -u) sets the default *PriorityLimit* (from 0 to 39) that the users in the LoginIDList can request when submitting a print request. The LoginIDList parameter may include any or all of the following constructs:

Users that have been given a limit cannot submit a print request with a higher priority level than the one assigned, nor can they change a request already submitted to have a higher priority. Any print requests submitted with priority levels higher than allowed will be given the highest priority allowed.

The third form of the command (with -u) removes any explicit priority limit for the specified users.

The fourth form of the command (with -q) sets the default priority limit for all users not explicitly covered by the use of the second form of this command.

The last form of the command (with -I) lists the default priority level and the priority limits assigned to users.

If you enter 1 pusers -?, the system displays the command usage message and returns 0.

Parameters

LoginID system_name!login-ID system_name!all all!login-ID all

Specifies a a user on the local system. User on the system system_name Users on system system_name User on all systems Users on the local system

Flags

-d PriorityLevel

-1

-q PriorityLimit

-q PriorityLimit -u LoginIDList

-u LoginIDList

Sets the system-wide priority default to PriorityLevel. Lists the default priority level and the priority limits assigned to users.

Sets the default highest priority level for all users not explicitly covered.

Sets the default highest priority level users in LoginIDList can request when submitting a print request.

Removes any explicit priority level for the specified users.

Related Information

The **Ip** command.

Is Command

Purpose

Displays the contents of a directory.

Syntax

To Display Contents of Directory or Name of File

To Display Contents of Directory

```
Is -f [ -C ] [ -d ] [ -i ] [ -m ] [ -s ] [ -X] [ -x ] [ -1 ] [ -U ] [ Directory ... ]
```

Description

The **Is** command writes to standard output the contents of each specified *Directory* parameter or the name of each specified *File* parameter, along with any other information you ask for with the flags. If you do not specify a *File* or *Directory* parameter, the **Is** command displays the contents of the current directory.

Specifying more than one of the options in the mutually exclusive pairs is not considered an error. The last option specified in each pair determines the output format.

By default, the **Is** command displays all information in alphabetic order by file name. The collating sequence is determined by the **LANG** or **LC_COLLATE** environment variable. The "National Language Support Overview for Programming" in *AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs* contains more details.

When the **Is** command displays the contents of a directory, it does not show entries for files whose names begin with a . (dot) unless you use the **-a** or **-A** flag. If the command is executed by root, it uses the **-A** flag by default.

There are three main ways to format the output:

- · List one entry per line.
- List entries in multiple columns by specifying either the -C or -x flag. The -C flag is the default format when output is to a tty. The **Is** command displays single column output if file or directory names are too long.
- List entries in a comma-separated series by specifying the -m flag.

To determine the number of character positions in the output line, the **Is** command uses the **COLUMNS** environment variable. If this variable is not set, the command gets the current column value of the display. If the **Is** command cannot determine the number of character positions by either of these methods, it uses a default value of 80.

The mode displayed with the **-U** flag is the same as with the **-I** flag, except for the addition of an 11th character interpreted as follows:

- E Indicates a file has extended attributes (EA) information. The EA of a file is displayed by using the **getea** command.
- Indicates a file does not have extended attributes information.

The mode displayed with the **-e** and **-I** flags is interpreted as follows:

If the first character is:

- d The entry is a directory.
- b The entry is a block special file.
- С The entry is a character special file.
- The entry is a symbolic link, and either the -N flag was specified or the symbolic link did not point to an I existing file.
- The entry is a first-in, first-out (FIFO) special file. р
- s The entry is a local socket.
- The entry is an ordinary file.

The next nine characters are divided into three sets of three characters each. The first set of three characters show the owner's permission. The next set of three characters show the permission of the other users in the group. The last set of three characters shows the permission of anyone else with access to the file. The three characters in each set indicate, respectively, read, write, and execute permission of the file. Execute permission of a directory lets you search a directory for a specified file.

Permissions are indicated as follows:

- r Read
- Write (edit) w
- Execute (search) X
- Corresponding permission not granted

The group-execute permission character is **s** if the file has set-group-ID mode. The user-execute permission character is s if the file has set-user-ID mode. The last character of the mode (usually x or -) is T if the 01000 (octal) bit of the mode is set (see the **chmod** command for the meaning of this mode). The indications of set-ID and 01000 bit of the mode are capitalized (S and T, respectively) if the corresponding execute permission is not set. The mode t indicates that the sticky bit is on for the file or the directory.

The mode displayed with the -e flag is the same as with the -I flag, except for the addition of an 11th character interpreted as follows:

Indicates a file has extended security information. For example, the file may have extended ACL, TCB, or TP attributes in the mode.

The access control information (ACL) of a file is displayed by using the aclget command. The value of the TCB and TP attributes are displayed by using the chtcb command.

Indicates a file does not have extended security information.

When the size of the files in a directory are listed, the **Is** command displays a total count of blocks, including indirect blocks.

Flags

-A	Lists all entries except.	(dot) and	(dot-dot).

- Lists all entries in the directory, including the entries that begin with a . (dot). -a
- Displays nonprintable characters in an octal (\nnn) notation. -b
- -C Uses the time of last modification of the i-node for either sorting (when used with the -t flag) or for displaying (when used with the -I flag). This flag has no effect if it is not used with either the -t or
 - -I flag, or both.
- Sorts output vertically in a multicolumn format. This is the default method when output is to a -C
 - terminal.
- -d Displays only the information for the directory named. Directories are treated like files, which is
 - helpful when using the -I flag to get the status of a directory.

- Displays the mode (including security information), number of links, owner, group, size (in bytes), time of last modification, and name of each file. If the file is a special file, the size field contains the major and minor device numbers. If the file is a symbolic link, the path name of the linked-to file is printed preceded by a -> (minus, greater than) sign. The attributes of the symbolic link are displayed.
- -E Lists extent attributes of a file that exists in Vxfs file systems, such as space reservation, fixed extent size, and extent allocation flag information. You must specify the -I flag with this flag; otherwise, the Is command ignores the -E flag and completes the execution.
- -f Lists the name in each slot for each directory specified in the *Directory* parameter. This flag turns off the -I, -t, -s, and -r flags, and turns on the -a flag. The order of the listing is the order in which entries appear in the directory.
 - Puts a / (slash) after each file name if the file is a directory, an * (asterisk) if the file can be executed, an = (equal sign) if the file is a socket, a I (pipe) sign if the file is a FIFO, and an @ for a symbolic link. Symbolic links that are named as operands are not followed unless you have specified the -H or -L flag.
- **-g** Displays the same information as the **-l** flag, except the **-g** flag suppresses display of the owner and symbolic link information.
 - If a symbolic link referencing a file of type directory is specified on the command line, the **Is** command shall evaluate the file information and file type to be those of the file referenced by the link, and not the link itself; however, the **Is** command shall write the name of the link itself and not the file referenced by the link.
- -i Displays the i-node number in the first column of the report for each file.
- -k Sets the block size for -s option and the per-directory block count written for -l, -n, -s, -g, and -o options to 1024 bytes.
 - Lists the file or directory contents that the link references. This is the default action. Symbolic links are followed. If the -I option is used, the -N option becomes the default, and no symbolic links are followed. When the -I option is used, only the -L option can override the -N default.
 - (Lower case L) Displays the mode, number of links, owner, group, size (in bytes), and time of last modification for each file. If the file is a special file, the size field contains the major and minor device numbers. If the time of last modification is greater than six months ago, the time field is shown in the format **month date year** where as files modified within six months the time field is shown as **month date time** format.

If the file is a symbolic link, the path name of the linked-to file is printed preceded by a ->. The attributes of the symbolic link are displayed. The -n, -g, and -o flag overrides the -I flag.

Notes:

-F

-H

-1

-0

- 1. A symbolically linked file is followed by an arrow and the contents of the symbolic link.
- 2. The performance of the **Is** command when used with the **-I** option can be improved by executing the **mkpasswd** command. This is helpful when a directory contains files owned by different users, such as the **/tmp** directory.
- **-m** Uses stream output format (a comma-separated series).
- **-n** Displays the same information as the **-I** flag, except that the **-n** flag displays the user and the group IDs instead of the user and group names.
- **-N** Does not follow symbolic links when determining the status of a file.

Note: If both the **-L** and **-N** options are used, the last one will dominate. Also, any time a symbolic link is given that includes a / (slash) as the final character, the link will automatically be followed regardless of any options used.

- Displays the same information as the -I flag, except the -o flag suppresses display of the group and symbolic link information.
- -p Puts a slash after each file name if that file is a directory. This is useful when you pipe the output of the **Is** command to the **pr** command, as follows:

- **-q** Displays nonprintable characters in file names as a ? (question mark).
- **-r** Reverses the order of the sort, giving reverse alphabetic or the oldest first, as appropriate.

-R Lists all subdirectories recursively.

-s Gives size in kilobytes (including indirect blocks) for each entry.

-t Sorts by time of last modification (latest first) instead of by name.

Displays similar information as the -I flag. Displays the mode (including security information and named extended attribute information), number of links, owner, group, size (in bytes), time of last modification, and name of each file. If the file is a special file, the size field contains the major and minor device numbers. If the file is a symbolic link, the path name of the linked-to file is printed preceded by a -> (minus, greater than) sign. The attributes of the symbolic link are displayed.

Uses the time of the last access, instead of the time of the last modification, for either sorting (when used with the -t flag) or for displaying (when used with the -l flag). This flag has no effect if

it is not used with either the -t or -I flag, or both.

-x Sorts output horizontally in a multi-column format.

-X Prints long user names when used with other flags that display user names. The upper limit is determined by the **max_logname** ODM attribute in the PdAt and CuAt object classes. If a user name is greater than the **max_logname** attribute, it will be truncated to the number of characters as specified by the **max_logname** attribute, less one character.

-1 Forces output into one-entry-per-line format. This is the default when the output is not directed to a terminal.

Exit Status

-u

This command returns the following exit values:

O All files were written successfully.

>0 An error occurred.

Examples

1. To list all files in the current directory, type:

1s -a

This lists all files, including . (dot), .. (dot-dot), and other files with names beginning with a dot.

2. To display detailed information, type:

```
ls -1 chap1 .profile
```

This displays a long listing with detailed information about chap1 and .profile.

3. To display detailed information about a directory, type:

```
ls -d -l . manual manual/chap1
```

This displays a long listing for the directories . and manual, and for the file manual/chap1. Without the -d flag, this would list the files in the . and manual directories instead of the detailed information about the directories themselves.

4. To list the files in order of modification time, type:

```
ls -1 -t
```

This displays a long listing of the files that were modified most recently, followed by the older files.

5. To display detailed information with expanded user and group name, type:

```
ls -lX .profile
```

This displays a long listing with detailed information about .profile.

6. To display about whether extended attributes are set on the files in current directory, type:

Example output:

-rwSr-x+	1 root	system	28 Apr 29 03:23 only_aixc
-rwSr-xE	1 root	system	4 Apr 29 03:23 only_aixc_ea
-rw-rrE	1 root	system	4 Apr 29 03:23 only_ea
+	1 root	system	265 Apr 29 03:23 only_nfs4
E	1 root	system	64 Apr 29 03:23 only_nfs4_ea
-rw-rr	1 root	system	4 Apr 29 03:23 only regular

Files

/usr/bin/ls Contains the Is command.

/etc/passwd Contains user IDs. /etc/group Contains group IDs.

/usr/share/lib/terminfo/* Contains terminal information.

Related Information

The aciget command, chmod command, chtcb command, find command, mkpasswd command, qprt command.

Directories in Operating system and device management describes the structure and characteristics of directories in the file system.

Files in Operating system and device management describes files, file types, and how to name files.

File and directory links in *Operating system and device management* explains the concept of file linking.

Shells in *Operating system and device management* describes shells, the different types, and how they affect the way commands are interpreted.

File and directory access modes in Operating system and device management introduces file ownership and permissions to access files and directories.

National Language Support Overview for Programming in AIX 5L Version 5.3 National Language Support Guide and Reference explains collating sequences, equivalence classes, and locale.

Is-secidapcintd Command

Purpose

The Is-secIdapcIntd command lists the status of the secIdapcIntd daemon process.

Syntax

/usr/sbin/ls-secIdapcIntd

Description

The Is-secIdapcIntd command lists the secIdapcIntd daemon status. The information returned includes the following:

- The LDAP server the secidapcintd daemon is talking to
- The LDAP server port number
- The version of the LDAP protocol used
- · User base DN

- · Group base DN
- · System (id) base DN
- · User cache size
- · User cache size used
- · Group cache size
- · Group cache size used
- · Cache time out (time to live) value
- secIdapcIntd to LDAP server heart beat interval
- · Number of thread used by **secidapcintd** daemon
- · Authentication mechanism in use
- · Attribute search mode
- · Default user attribute entry location
- · Timeout period (seconds) for LDAP client requests to the server
- · User objectclass used in the LDAP server
- · Group objectclass used in the LDAP server

Example

 1. To list the status of the secidapcintd daemon, type: /usr/sbin/ls-secidapcintd

Files

/etc/security/ldap/ldap.cfg

Contains information needed by the **secidapcintd** daemon to connect to the server.

Related Information

The secidapcintd daemon

The mksecidap, stop-secidapcintd, start-secidapcintd, restart-secidapcintd, and flush-secidapcintd commands.

The /etc/security/ldap/ldap.cfg file.

Isactdef Command

Purpose

Displays the action definitions of a resource or a resource class.

Syntax

To display the action definitions of a *resource*:

```
Isactdef [-p property] [-s i | o] [-e] [-I | -i | -t | -d | -D delimiter] [-x] [-h] [-TV] resource_class [ action1 [ action2 ... ] ]
```

To display the action definitions of a resource class:

```
Isactdef −c [−p property] [−s i | o] [−e] [−l | −i | −t | −d | −D delimiter] [−x] [−h] [−TV] resource_class [ action1 [ action2 ... ] ]
```

To display all resource class names:

Isactdef

Description

The Isactdef command displays a list of the action definitions of a resource or a resource class. By default, this command displays the action definitions of a resource. To see the action definitions of a resource class, specify the -c flag.

If you do not specify any actions on the command line, this command only displays actions that are defined as public. To override this default, use the -p flag or specify on the command line the names of the actions that have definitions you want to display.

To see the structured data definition that is required as input when this action is invoked, specify the -s i flag. To see the structured data definition linked with the output that results from invoking this action, specify the -s o flag.

By default, this command does not display action descriptions. To display action definitions and descriptions, specify the -e flag.

Flags

- -с Displays the action definitions for resource_class.
- -d Specifies delimiter-formatted output. The default delimiter is a colon (:). Use the -D flag if you want to change the default delimiter.

-D delimiter

Specifies delimiter-formatted output that uses the specified delimiter. Use this flag to specify a delimiter other than the default colon (:). An example is when the data to be displayed contains colons. Use this flag to specify a delimiter of one or more characters.

- Specifies expanded format. Displays descriptions along with the action definitions. -е
- −i Specifies input format. Generates a template of resource data input file. The output is displayed in long (stanza) format. The attribute's SD element data types are displayed as the value in the attr=value pairs. It is suggested that when you use this flag, the output of the **Isactdef** command be directed to a file. This flag overrides the -s o flag.
- -ISpecifies "long" format — one entry per line. This is the default display format. If the Isactdef command is issued with the -I flag, but without a resource class name, the -I flag is ignored when the command returns the list of defined resource class names.

-p property

Displays actions with the specified property. By default, only the definitions for public actions are displayed. To display all action definitions regardless of the action property, use the -p 0 flag.

Action properties:

0x0001 long_running

0x0002 public

A decimal or hexadecimal value can be specified for the property. To request the action definitions for all actions that have one or more properties, "OR" the properties of interest together and then specify the "OR"ed value with the -p flag. For example, to request the action definitions for all actions that are long_running or public, enter:

-p 0x03

-silo

Displays the structured data definition for the action input or action response.

i Displays the action input structured data definitions. This is the default.

- Displays the action response (output) structured data definitions. 0
- -t Specifies table format. Each attribute is displayed in a separate column, with one resource per
- Suppresses header printing. **-X**
- Writes the command's usage statement to standard output. -h
- -T Writes the command's trace messages to standard error. For your software-service organization's use only.
- -V Writes the command's verbose messages to standard output.

Parameters

resource class

Specifies the name of the resource class with the action definitions that you want to display. If resource_class is not specified, a list of all of the resource class names is displayed.

action1 [action2...]

Specifies one or more actions. If resource_class is specified, zero or more action names can be specified. If no actions are specified, all of the action definitions for resource_class are displayed. Enter specific action names to control which actions are displayed and in what order. Use blank spaces to separate action names.

Security

The user needs read permission for the resource class specified in **Isactdef** to run **Isactdef**. Permissions are specified in the access control list (ACL) file on the contacted system. See the RSCT: Administration Guide for information about the ACL file and how to modify it.

Exit Status

- 0 The command has run successfully.
- 1 An error occurred with RMC.
- 2 An error occurred with the command-line interface (CLI) script.
- 3 An incorrect flag was specified on the command line.
- 4 An incorrect parameter was specified on the command line.
- 5 An error occurred with RMC that was based on incorrect command-line input.

Environment Variables

CT_CONTACT

When the CT CONTACT environment variable is set to a host name or IP address, the command contacts the Resource Monitoring and Control (RMC) daemon on the specified host. If the environment variable is not set, the command contacts the RMC daemon on the local system where the command is being run. The resource class or resources that are displayed or modified by the command are located on the system to which the connection is established.

CT IP AUTHENT

When the CT_IP_AUTHENT environment variable exists, the RMC daemon uses IP-based network authentication to contact the RMC daemon on the system that is specified by the IP address to which the CT CONTACT environment variable is set. CT IP AUTHENT only has meaning if CT_CONTACT is set to an IP address; it does not rely on the domain name system (DNS) service.

CT_MANAGEMENT_SCOPE

Determines the management scope that is used for the session with the RMC daemon to monitor and control the resources and resource classes. The management scope determines the set of possible target nodes where the resources and resource classes can be monitored and controlled. The valid values are:

- **0** Specifies *local* scope.
- 1 Specifies *local* scope.
- 2 Specifies *peer domain* scope.
- 3 Specifies management domain scope.

If this environment variable is not set, local scope is used.

Implementation Specifics

This command is part of the Reliable Scalable Cluster Technology (RSCT) fileset for AIX.

Standard Output

When the **-h** flag is specified, this command's usage statement is written to standard output. All verbose messages are written to standard output.

Standard Error

All trace messages are written to standard error.

Examples

1. To list the names of all of the resource classes, enter:

lsactdef

The output will look like this:

```
class_name
"IBM.Association"
"IBM.AuditLog"
"IBM.AuditLogTemplate"
"IBM.Condition"
"IBM.EventResponse"
"IBM.Host"
"IBM.Program"
"IBM.Sensor"
"IBM.ManagedNode"
```

2. To list the public resource action definitions for resource class IBM.AuditLog, enter:

lsactdef IBM.AuditLog

The output will look like this:

```
Resource Action Definitions for
class name: IBM.AuditLog
action 1:
                    = "GetRecords"
       action name
       display_name = ""
       description = ""
       properties
                   = {"public"}
       confirm prompt = ""
       action_id
                     = 0
       variety_list = \{\{1..1\}\}
       variety_count = 1
       timeout
                      = 0
action 2:
```

```
description = ""
properties = {"public"}
confirm_prompt = ""
action id = 1
variety list = \{\{1..1\}\}
variety count = 1
timeout
```

3. To list the structured data definition required for invoking the action on resources in resource class IBM.AuditLog, action GetRecords, enter:

```
lsactdef -s i IBM.AuditLog GetRecords
```

The output will look like this:

```
Resource Action Input for: IBM.AuditLog
action name GetRecords:
sd element 1:
       element_name
                        = "MatchCriteria"
display_name = ""
description = ""
description
       element_data_type = "char_ptr"
element_index = 0
sd element 2:
                       = "IncludeDetail"
       element_name
display_name = ""
description
description
       element_data_type = "uint32"
        element_index = 1
```

Location

/usr/sbin/rsct/bin/lsactdef

Related Information

Books: RSCT: Administration Guide, for information about RMC operations

Commands: Isrsrcdef

Information Files: rmccli, for general information about RMC commands

Isaliq Command

Purpose

Lists the names of all configured queues.

Syntax

Isaliq [-c]

Description

The Isaliq command lists the names of all configured queues contained in the /etc/qconfig file. By specifying the -c flag, this listing is displayed in colon format. This flag is used mainly by SMIT.

You can use the Printer Queues application in Web-based System Manager (wsm) to change print queue characteristics. You could also use the System Management Interface Tool (SMIT) smit Isaliq fast path to run this command.

Flag

Causes colon format output for use by SMIT.

Examples

1. To list all of the queue names in the /etc/qconfig file, enter:

A listing similar to the following is displayed:

1p1 1p2

2. To list all configured queues in colon format, enter:

```
lsallq -c
```

A listing similar to the following is displayed:

0a1 1p0:queue1 1p0:queue2 1p1

Files

/usr/bin/lsallq Contains the Isallq command.

Configuration file. /etc/qconfig

Related Information

The chaue command, Isque command, Isaliquev command, mkque command, rmque command.

The qconfig file.

Listing print gueues and print gueue devices in the Printers and printing.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

Isalique Command

Purpose

Lists all configured printer and plotter queue device names within a specified queue.

Syntax

Isaliqdev [-c] -qName

Description

The Isallqdev command lists all configured device names within a specified queue in the /etc/qconfig file.

You can use the Printer Queues application in Web-based System Manager (wsm) to change print queue characteristics. You could also use the System Management Interface Tool (SMIT) smit IsalIqdev fast path to run this command.

Flags

-q Name Specifies the queue name.

Causes colon format output for use by SMIT. -C

Examples

1. To list the names all of the configured queue devices within the 1p0 queue in the /etc/qconfig file, enter:

```
lsallqdev -q lp0
```

A listing similar to the following is displayed:

1pd0 1pd1

1pd2 2. To list the names of all of the configured queue device within the 1p0 queue in the /etc/qconfig file in

```
lsallqdev -q lp0 -c
```

colon format, enter:

A listing similar to the following is displayed:

1p0:1pd1 1p0:1pd2

Files

/usr/bin/Isallqdev Contains the Isallqdev command.

/etc/qconfig Configuration file.

Related Information

The chquedev command, Isquedev command, Isaliq command, mkquedev command, rmquedev command.

The qconfig file.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

Listing print queues and print queue devices in the Printers and printing.

Isarm command

Purpose

Displays Application Response Measurement (ARM) application and process usage information.

Syntax

```
lsarm -a [ -g ] [ -t ] [ -u ] [ ApplicationName ... ]
```

or

```
Isarm -p [ -a [ -g ] [ -t ] [ ProcessID ... ]]
```

Description

The Isarm command displays information about applications registered with the operating system using the Application Response Measurement (ARM) APIs. The -a flag displays information about applications by application name. The -p option displays information about the applications used by a process.

Flags

Displays application names. -a Displays group names associated with the application. -g -p

Displays transaction names associated with the

application.

Displays process numbers using the application. -11 -t Displays the applications used by a process.

Parameters

ApplicationName Specifies a list of one or more applications for which the

Isarm command should display information.

ProcessID Specifies a list of one or more process IDs for which the

Isarm command should display information.

Exit Status

The command completed successfully.

>0 An error occurred.

Examples

1. To display all application names, type:

lsarm -a

2. To display group names, transaction class names, and process numbers using the 'database' application, type:

```
lsarm -a -q -t -u database
```

3. To display the process IDs for all processes using ARM applications, type:

4. To display the application names, group names, and transaction names used by process 25038, type:

1 sarm - p - a - g - t 25038

Location

/usr/ewlm/sbin/lsarm

Related Information

Isattr Command

Purpose

Displays attribute characteristics and possible values of attributes for devices in the system.

Syntax

```
Isattr { -D [ -O ] | -E [ -O ] | -F Format [ -Z Character ] } -I Name [ -a Attribute ] ... [ -f File ] [ -h ] [ -H ]
Isattr { -D [ -O ] | -F Format [ -Z Character ] } { [ -c Class ] [ -s Subclass ] [ -t Type ] } [ -a Attribute ] ... [ -f
File ] [ -h ] [ -H ]
Isattr -R { -I Name | [ -c Class ] [ -s Subclass ] [ -t Type ] } -a Attribute [ -f File ] [ -h ] [ -H ]
Isattr -I Name { -o operation [ ... ] } -F Format [ -Z Character ] [ -f File ] [ -h ] [ -H ]
| Isattr { [ -c Class ] [ -s Subclass ] [ -t Type ] } { -o operation [ ... ] } -F Format [ -Z Character ] [ -f File ] [
-h ] [ -H ]
```

Description

The **Isattr** command displays information about the attributes of a given device or type of device. If you do not specify the device logical name with the -I Nameflag, you must use a combination of one or all of the -c Class, -s Subclass, and -t Type flags to uniquely identify the predefined device.

You must specify one of the following flags with the Isattr command:

-D Displays default values.

-E Displays effective values (valid only for customized devices specified with the -I flag).

-F Format Specifies the user-defined format. Displays the range of legal values. -R

When you display the effective values of the attributes for a customized device, the information is obtained from the Configuration database, not the device. The database values reflect how the device is configured unless it is reconfigured with the **chdev** command using the **-P** or **-T** flag. If this occurs, the information displayed by the Isattr command might not correctly indicate the current device configuration until after the next system boot.

If you use the **-D** or **-E** flag, the output defaults to the values for the attribute's name, value, description. and user-settable strings, unless it is also used with the -O flag. The -O flag displays the names of all the attributes specified, separated by colons. On the next line, the -O flag displays all of the corresponding attribute values, separated by colons. The -H flag can be used with either the -D, -E, or -F flag to display headers above the column names. You can define the format of the output with a user-specified format using the -F Format flag, where the Format parameter is a quoted list of column names separated by non-alphanumeric characters or white space. If the **-F** Format flag is specified, the **-Z** Character flag may also be specified to change the default record separator from a newline character to the indicated Character.

The Isattr command can display "operation" information from the Extended Predefined Attribute (PdAtXtd) object class. This information is used by the Web-based System Manager. The operation information is accessed through the -o operation flag. The -o operation flag and the -a attribute flag cannot be specified in the same invocation of the **Isattr** command. The **-o** operation flag is also not valid with the **-R** flag. When the -o operation flag is specified, only fields from the PdAtXtd object class can be specified with the -F Format flag.

You can supply the flags either on the command line or using the specified -f File flag.

Flags

-a Attribute

Displays information for the specified attributes of a specific device or type of device. You can use one -a flag for each attribute name or multiple attribute names. If you use one -a flag for multiple attribute names, the list of attribute names must be enclosed in quotes with spaces between the names. If you use the -R flag, you must specify only one -a flag with only one attribute name. If you do not specify either the -a or -R flag, the Isattr command displays all information for all attributes of the specified device. The -a Attribute flag cannot be used in conjunction with the -o Operation flag. This combination of flags causes the Isattr command to exit with an error message.

-c Class

Specifies a device class name. This flag can be used to restrict the output to devices of a specified class. This flag cannot be used with the **-E** or **-I** flag.

-D

Displays the attribute names, default values, descriptions, and user-settable flag values for a specific device when it is not used with the **-O** flag. The **-D** flag displays only the attribute name and default value in colon format when it is used with the **-O** flag. This flag can be used with any combination of the **-c**, **-s**, and **-t** flags that uniquely identifies a device from the Predefined Devices object class, or with the **-I** flag. This flag cannot be used with the **-E**, **-F**, or **-R** flags.

-E

Displays the attribute names, current values, descriptions, and user-settable flag values for a specific device when it is not used with the **-O** flag. The **-E** flag displays only the attribute name and current value in colon format when it is used with the **-O** flag. This flag cannot be used with the **-c**, **-D**, **-F**, **-R**, **-s**, or **-t** flags.

-f File

Reads the necessary flags from the File parameter.

-F Format

Displays the output in a user-specified format, where the *Format* parameter is a quoted list of column names separated by nonalphanumeric characters or white space. If white space is used as the separator, the <code>Isattr</code> command displays the output in aligned columns. Only column names from the Predefined Attributes (<code>PdAt</code>), Customized Attributes (<code>CuAt</code>), and the Extended Predefined Attributes (<code>PdAtXtd</code>) object classes can be specified. In addition to the column names, there are two special purpose names that can be used: the name *description* can be used to obtain a display of attribute descriptions and *user-settable* can be used to determine whether or not an attribute can be changed. This flag cannot be used with the <code>-E</code>, <code>-D</code>, <code>-O</code> or <code>-R</code> flags.

-H

Displays headers above the column output. The **-O** and **-R** flag take precedence over the **-H** flag.

-h

Displays the command usage message.

-I Name

Specifies the device logical name in the Customized Devices object class whose attribute names or values you want displayed.

-o Operation

Displays information for the specified operations of a specific device or type of device. You can use one -o flag for each operation name or multiple operation names. If you use one -o flag for multiple operation names, the list of attribute names must be enclosed in quotes with spaces between the names. Wildcard characters can also be used for the operation name. The valid set of wildcard characters are the same set used by the odmget command. All operations associated with a specific device, or type of device, can be displayed by using an operation value of "?*". The -o Operation flag cannot be used in conjunction with the -a attribute flag or the -R flag. Any combination of these flags causes the Isattr command to exit with an error message.

-0

Displays all attribute names separated by colons and, on the second line, displays all the corresponding attribute values separated by colons. The attribute values are current values when the **-E** flag is specified and default values when the **-D** flag is specified. This flag cannot be used with the **-F** and **-R** flags.

-R Displays the legal values for an attribute name. The -R flag cannot be used with the -D, -E, -F and -O flags, but can be used with any combination of the -c, -s, and -t flags that uniquely identifies a device from the Predefined Devices object class, or with the -I flag. The -R flag

displays the list attribute values in a vertical column as follows:

Value1 Value2 · · · ValueN

The -R flag displays the range attribute values as x...n(+i) where x is the start of the range,

n is the end of the range, and i is the increment.

-s Subclass Specifies a device subclass name. This flag can be used to restrict the output to that for

devices of a specified subclass. This flag cannot be used with the -E or -I flag.

-t Type Specifies a device type name. This flag can be used to restrict the output to that for devices

of a specified class. This flag cannot be used with the -E or -I flag.

-Z Character

The **-Z** Character flag is used with programs that must deal with ODM fields that might have embedded new line characters. An example of such a program is the Web-based System Manager. The **-Z** Character flag is used to change the record separator character for each

record, or line, of output generated. The new record separator is specified using the *Character* argument to this flag. The **-Z** *Character* flag is only relevant when the **-F** *Format* flag is specified. The **-Z** *Character* flag cannot be used with the **-D**, **-E**, **-O**, or the **-R** flags.

Examples

1. To list the current attribute values for the rmt0 tape device, type the following:

lsattr -1 rmt0 -E

The system displays a message similar to the following:

mode y	'es	Use DEVICE BUFFERS during writes	True
block_size 1	.024	BLOCK size (0=variable length)	True
extfm y	'es	Use EXTENDED file marks	True
ret n	10	RETENSION on tape change or reset	True
density_set_1 3		DENSITY setting #1	True
density_set_2 3	6	DENSITY setting #2	True
compress y	'es	Use data COMPRESSION	True
size_in_mb 1	2000	Size in Megabytes	False
ret_error n	10	RETURN error on tape change or reset	True

2. To list the default attribute values for the rmt0 tape device, type the following:

lsattr -1 rmt0 -D

The system displays a message similar to the following:

mode	yes	Use DEVICE BUFFERS during writes	True
block size	1024	BLOCK size (0=variable length)	True
extfm	yes	Use EXTENDED file marks	True
ret	no	RETENSION on tape change or reset	True
density set 1	37	DENSITY setting #1	True
density_set_2	36	DENSITY setting #2	True
compress	yes	Use data COMPRESSION	True
size in mb	12000	Size in Megabytes	False
ret error	no	RETURN error on tape change or reset	True

3. To list the current value of the **bus_intr_lvl** attribute for the scsi0 SCSI adapter, type the following:

```
lsattr -l scsi0 -a bus intr lvl -E
```

The system displays a message similar to the following:

```
bus intr lvl 1 Bus interrupt level False
```

4. To list the possible values of the login attribute for the tty0 tty device, type the following:

```
lsattr -l tty0 -a login -R
```

The system displays a message similar to the following:

enable disable share delay

5. To list the default attribute values for an IBM 4340 parallel printer, type the following:

lsattr -c printer -s parallel -t ibm4340 -D

The system displays a message similar to the following:

•		9	
ptop	600	Printer TIME OUT period	True
line	60	Number of LINES per page	True
col	80	Number of COLUMNS per page	True
ind	0	Number of columns to INDENT	True
plot	no	Send all characters to printer UNMODIFIED	True
backspace	yes	Send BACKSPACES	True
cr	yes	Send CARRIAGE RETURNS	True
form	yes	Send FORM FEEDS	True
lf	yes	Send LINE FEEDS	True
addcr	yes	Add CARRIAGE RETURNS to LINE FEEDS	True
case	no	Convert lowercase to UPPERCASE	True
tabs	yes	EXPAND TABS on eight position boundaries	True
wrap	no	WRAP CHARACTERS beyond the specified width	True
mode	no	Return on ERROR	True
interface		31	True
-		STATE to be configured at boot time	True
busy_delay	0	Microseconds to delay between characters	True

6. To list the possible values of the **ptop** attribute for an IBM 4340 parallel printer, type the following:

lsattr -c printer -s parallel -t ibm4340 -a ptop -R

The system displays a message similar to the following:

1...1000 (+1)

7. To list the current attribute values for the rmt0 tape device in colon-separated format, type the following:

lsattr -l rmt0 -E -0

The system displays a message similar to the following:

#mode:block size:extfm:ret:density set 1:density set 2:compress:size in mb:ret error yes:1024:yes:no:37:36:yes:12000:no

8. To display system attributes, type the following:

lsattr -E -l sys0

The system displays output similar to the following:

keylock	normal	State of system keylock at boot time	False
maxbuf	20	Maximum number of pages in block I/O BUFFER CACHE	True
maxmbuf	0	Maximum Kbytes of real memory allowed for MBUFS	True
maxuproc	128	Maximum number of PROCESSES allowed per user	True
autorestart	false	Automatically REBOOT system after a crash	True
iostat	false	Continuously maintain DISK I/O history	True
realmem	4194304	Amount of usable physical memory in Kbytes	False
conslogin	enable	System Console Login	False
fwversion	IBM, SPH00221	Firmware version and revision levels	False
maxpout	0	HIGH water mark for pending write I/Os per file	True
minpout	0	LOW water mark for pending write I/Os per file	True
fullcore	false	Enable full CORE dump	True
pre430core	false	Use pre-430 style CORE dump	True
ncargs	6	ARG/ENV list size in 4K byte blocks	True
rtasversion	1	Open Firmware RTAS version	False
modelname	IBM,7044-270	Machine name	False

systemid	IBM,011037D1F	Hardware system identifier	False
boottype	disk	N/A	False
SW_dist_intr	false	Enable SW distribution of interrupts	True
cpuguard	disable	CPU Guard	True
frequency	93750000	System Bus Frequency	False

Note: The same information is available in a more readable format using SMIT. Select the System Environments -> Change / Show Characteristics of Operating Systems options to view this information.

Files

Contains the Isattr command. /usr/sbin/lsattr

Related Information

The chdev command, Isconn command, Isdev command, Isparent command, mkdev command, rmdev command.

Tunable parameters in Performance management.

Isaudrec Command

Purpose

Lists records from the audit log.

Syntax

```
Isaudrec [-I] [-a | -n node_name1[,node_name2]...] [-S subsystem_name]
[-s selection_string] [-x] [-h] [ field_name1 [field_name2...] ]
```

Description

The Isaudrec command is used to list records in the audit log. The audit log is a facility for recording information about the system's operation. It can include information about the normal operation of the system as well as failures and other errors. It augments the error log functionality by conveying the relationship of the error relative to other system activities. All detailed information about failures is still written to the AIX error log.

Records are created in the audit log by subsystems that have been instrumented to do that. For example, the event response subsystem runs in the background to monitor administrator-defined conditions and then invokes one or more actions when a condition becomes true. Because this subsystem runs in the background, it is difficult for the operator or administrator to understand the total set of events that occurred and the results of any actions that were taken in response to an event. Because the event response subsystem records its activity in the audit log, the administrator can easily view its activity as well as that of other subsystems using this command.

Each record in the audit log contains named fields. Each field contains a value that provides information about the situation corresponding to the record. For example, the field named Time indicates the time at which the situation occurred. Each record has a set of common fields and a set of subsystem-specific fields. The common fields are present in every record in the audit log. The subsystem-specific fields vary from record to record. Their names are only significant when used with a subsystem name because they may not be unique across all subsystems. Each record is derived from a template that defines which subsystem-specific fields are present in the record and defines a format string that is used to generate a message describing the situation. The format string may use record fields as inserts. A subsystem typically has many templates.

The field names can be used as variables in a selection string to choose which records are displayed. A selection string is an expression that is made up of field names, constants, and operators. The syntax of a selection string is similar to an expression in the C programming language or the SQL "where" clause. The selection string is matched against each record using the referenced fields of each record to perform the match. Any records that match are displayed. The selection string is specified with the -s flag. For information on how to specify selection strings, see the RSCT: Administration Guide.

You can also specify field names as parameters to this command to choose which fields are displayed and the order in which they are displayed. The common field names are:

<u>Field</u>	Description
Time	The time when the situation occurred that the record corresponds to. The value is a 64-bit integer and represents the number of microseconds since Unix Epoch (00:00:00 GMT January 1, 1970). See the constants below for specifying the time in more user-friendly formats.
Subsystem	The subsystem that generated the record. This is a string.
Category	Indicates the importance of the situation corresponding to the audit record, as determined by the subsystem that generated the record. The valid values are: 0 (informational) and 1

SequenceNumber

(error).

The unique 64-bit integer that is assigned to the record. No other record in the audit log will have the same sequence number.

TemplateId The subsystem-dependent identifier that is assigned to records that have the same content and format string. This value is a 32-bit unsigned integer.

NodeName The name of the node from which the record was obtained. This field name cannot be used in a selection string.

In addition to the constants in expressions that are described in the RSCT: Administration Guide, you can use the following syntax for dates and times with this command:

#mmddhhmmyyyy

This format consists of a sequence of decimal characters that are interpreted according to the pattern shown. The fields in the pattern are, from left to right: mm = month, dd = day, hh = hour, mm = minutes, yyyy = year. For example, #010523042004 corresponds to January 5, 11:04 PM, 2004. The fields can be omitted from right to left. If not present, the following defaults are used: year = the current year, minutes = 0, hour = 0, day = 1, and month = the current month.

#-mmddhhmmyyyy

This format is similar to the previous one, but is relative to the current time and date. For example, the value #-0001 corresponds to one day ago and the value #-010001 corresponds to one month and one hour ago. Fields can be omitted starting from the right and are replaced by 0.

The audit records considered for display and matched against the selection string can be restricted to a specific subsystem by using the -S flag. If this flag is specified, the subsystem-specific field names can be used in the selection string in addition to the common field names.

The nodes from which audit log records are considered for display and matched against the selection string can be restricted to a set of specific nodes by using the -n flag. If this flag is specified, the search is limited to the set of nodes listed. Otherwise, the search is performed for all nodes defined within the current management scope, as determined by the CT MANAGEMENT SCOPE environment variable.

The audit records are displayed in a table. Field names specified as parameters control which fields are displayed and the order in which they appear on each line. By default, the columns displayed are: the date and time, the subsystem name that generated the record, the severity of the situation, and the subsystem-specific message that describes the situation. If the management scope is not local, the node name is displayed in the first column.

Flags

- -1 Indicates that long output should be produced. Long output includes subsystem-specific fields that are not included in the formatted message text.
- Specifies that records from all nodes in the domain are to be displayed. If both the -n and the -a flags are omitted, records from the local node only are displayed.
- -n node_name1[,node_name2]...

Specifies the list of nodes containing audit log records that will be examined and displayed if they meet the other criteria, such as matching the specified selection string. Node group names can also be specified, which are expanded into a list of node names. If both the -n and the -a flags are omitted, records from the local node only are displayed.

-S subsystem_name

Specifies a subsystem name. If this flag is present, only records identified by subsystem name are considered for display. The records displayed can be further restricted by the -s flag. If the subsystem name contains any spaces, it must be enclosed in single or double quotation marks.

For backward compatibility, the subsystem name can be specified using the -n flag only if the -a and the -S flags are not specified.

-s selection string

Specifies a selection string. This string is evaluated against each record in the audit log. All records that match the selection string will be displayed. If the selection string contains any spaces, it must be enclosed in single or double quotation marks. For information on how to specify selection strings, see the RSCT: Administration Guide.

The names of fields in the record can be used in the expression. If the -S flag is not specified. only the names of common fields can be used. See the **Description** for a list of the common field names and their data types. If the -S flag is specified, the name of any field for the specified subsystem as well as the common field names can be used.

If this flag is omitted, the records that are displayed will depend on the -S flag. If the -S flag is omitted, all records from the audit log are displayed. Otherwise, all records for the subsystem identified by the -S flag are displayed.

- -x Excludes the header (suppresses header printing).
- -h Writes the command's usage statement to standard output.

Parameters

field name1 [field name2...]

Specifies one or more fields in the audit log records to be displayed. The order of the field names on the command line corresponds to the order in which they are displayed. If no field names are specified, Time, Subsystem, Severity, and Message are displayed by default. If the management scope is not local, NodeName is displayed as the first column by default. See the Description for information about these and other fields.

Security

In order to list records from an audit log when the -S flag is omitted, you must have read access to the target resource class on each node from which records are to be listed. When the -S flag is specified, you must have read access to the audit log resource corresponding to the subsystem identified by the -S flag on each node from which records are to be listed.

Authorization is controlled by the RMC access control list (ACL) file that exists on each node.

Exit Status

- The command ran successfully.
- An error occurred with RMC.
- An error occurred with a command-line interface script. 2
- An incorrect flag was entered on the command line.
- An incorrect parameter was entered on the command line.
- 5 An error occurred that was based on incorrect command-line input.

Environment Variables

CT CONTACT

Determines the system where the session with the resource monitoring and control (RMC) daemon is established. When CT CONTACT is set to a host name or IP address, the command contacts the RMC daemon on the specified host. If CT CONTACT is not set, the command contacts the RMC daemon on the local system where the command is being run. The target of the RMC daemon session and the management scope determine the resource classes or resources that can be affected by this command.

CT IP AUTHENT

When the CT_IP_AUTHENT environment variable exists, the RMC daemon uses IP-based network authentication to contact the RMC daemon on the system that is specified by the IP address to which the CT_CONTACT environment variable is set. CT_IP_AUTHENT only has meaning if CT_CONTACT is set to an IP address; it does not rely on the domain name system (DNS) service.

CT_MANAGEMENT_SCOPE

Determines (in conjunction with the -a and -n flags) the management scope that is used for the session with the RMC daemon. The management scope determines the set of possible target nodes where audit log records can be listed. If the -a and -n flags are not specified, local scope is used. When either of these flags is specified, CT_MANAGEMENT_SCOPE is used to determine the management scope directly. The valid values are:

- 0 Specifies local scope.
- 1 Specifies *local* scope.
- 2 Specifies *peer domain* scope.
- Specifies management domain scope.

If this environment variable is *not* set, *local* scope is used.

Implementation Specifics

This command is part of the Reliable Scalable Cluster Technology (RSCT) fileset for AIX.

Standard Output

When the -h flag is specified, this command's usage statement is written to standard output.

Examples

1. To list all records in the audit log on every node in the current management scope as determined by the CT MANAGMENT SCOPE environment variable, enter:

1saudrec

2. To list all records that were logged in the last hour on every node in the current management scope as determined by the CT_MANAGMENT_SCOPE environment variable, enter:

```
lsaudrec -s "Time > #-000001"
```

3. To list the time and sequence number of every record in the audit log for the subsystem abc on nodes mynode and yournode, enter:

```
1saudrec -n mynode,yournode -S abc Time SequenceNumber
```

4. To list the records that are generated by the event-response resource manager (ERRM), enter:

```
1saudrec - SERRM
```

5. To list the records that are related to a condition called **Condition1**, enter:

```
lsaudrec -SERRM -s"ConditionName=='Condition1'"
```

6. To list the records that are related to an event from **Condition1**, enter:

```
lsaudrec -SERRM -s"ConditionName=='Condition1' && Etype==91"
```

7. To list the records that are related to a rearm event from **Condition1**, enter:

```
lsaudrec -s"ConditionName=='Condition1' && Etype==92"
```

8. To list error records only, enter:

```
lsaudrec -s"Category=1"
```

9. To list the sensor resource manager records in the audit log on the local node, enter:

```
1saudrec -SSSRM
```

The output will look like this:

Time	Subsystem	Category	Description
11/10/05 21:52:32	SSRM	Error	The Command /SENSOR/sensor.ksh 1 in Sensor
			<pre>SENSOR_NOUSER_1 execution fails.</pre>
11/10/05 21:52:36	SSRM	Error	The Command /SENSOR/sensor.nocmd 1 in Sensor
			SENSOR NOCMD 1 exits with error 127.

10. To list, in long format, the sensor resource manager records in the audit log on the local node, enter:

```
1saudrec -1 -SSSRM
```

The output will look like this:

```
= 11/10/05 21:52:32 243097
Time
Subsystem = SSRM
           = Error
Description = The Command /SENSOR/sensor.ksh 1 in Sensor SENSOR_NOUSER_1 execution fails.
ErrorMsg = 2645-202 The user name "guest" that was specified for running the command does not exist.
           = 11/10/05 21:52:36 361726
Time
Subsystem = SSRM
Category = Error
Description = The Command /SENSOR/sensor.nocmd 1 in Sensor SENSOR_NOCMD_1 exits with error 127.
StandardOut =
StandardErr = ksh: /u/diane/drmc/scripts/SENSOR/sensor.nocmd: not found
```

Location

/usr/sbin/rsct/bin/lsaudrec

Related Information

Books: RSCT: Administration Guide, for information about:

- · how to specify selection strings
- · using constants in expressions

Isauthent Command

Purpose

Lists the authentication methods currently configured on the system.

Syntax

Isauthent

Description

The **Isauthent** command calls the **get auth method** subroutine in the **Iibauthm.a** library, translates a list of authentication methods returned, and prints the authentication methods configured to stdout. Each authentication method is outputted on a separate line.

The authentication methods are listed in the order in which they are configured. If none of the authentication methods are configured, **Isauthent** returns without printing anything.

The Isauthent command writes an error message to stderr and returns a -1 if get_auth_method fails.

Examples

If all of the authentication methods are configured as:

1sauthent

the output would consist of:

Kerberos 5 Kerberos 4 Standard AIX

Related Information

The chauthent command, ftp command, rcp command, rlogin command, rsh command, telnet, tn, or tn3270 command.

The get auth method and set auth method subroutines.

Communications and networks in Networks and communication management.

Authentication and the secure rcmds in Networks and communication management.

IsC2admin Command

Purpose

Display the name of the current C2 System Administrative Host.

Syntax

IsC2admin

Description

The IsC2admin command displays the name of the administrative host. An administrative host must have been defined, and the system must have been installed in C2 mode for this command to operate successfully.

Exit Status

- The administrative host information has been successfully displayed.
- 1 This system was not installed with C2 security.
- 2 This system has not been initialized to operate in C2 mode.
- 3 An error occurred while displaying the name of the administrative host.

Files

/usr/sbin/lsC2admin

Contains the IsC2admin command.

Related Information

The chC2admin command, isC2host command, mkC2admin command, rmC2admin command.

IsCCadmin Command

Purpose

Display the name of the current Common Criteria enabled System Administrative Host.

Syntax

IsCCadmin

Description

The **IsCCadmin** command displays the name of the administrative host. An administrative host must have been defined, and the system must have been installed in Common Criteria enabled mode for this command to operate successfully.

Exit Status

- **0** The administrative host information has been successfully displayed.
- 1 This system was not installed with Common Criteria enabled security.
- 2 This system has not been initialized to operate in Common Criteria enabled mode.
- 3 An error occurred while displaying the name of the administrative host.

Files

/usr/sbin/IsCCadmin

Contains the IsCCadmin command.

Related Information

The chCcadmin command, isCChost command, mkCCadmin command, rmCCadmin command.

Iscfg Command

Purpose

Displays configuration, diagnostic, and vital product data (VPD) information about the system.

Syntax

To Display Specific Data on all Systems

Iscfg [-v] [-p] [-s] [-l Name]

Description

If you run the **Iscfg** command without any flags, it displays the name, location and description of each device found in the current Customized VPD object class that is a child device of the **sys0** object. It will not display any device that has been marked missing in the Customized Device Object Class. The list is sorted by parent, child, and device location. Information on a specific device can be displayed with the **-I** flag.

Use the **Iscfg** command to display vital product data (VPD) such as part numbers, serial numbers, and engineering change levels from either the Customized VPD object class or platform specific areas. Not all devices contain VPD data.

VPD data that is preceded by ME signifies that the VPD data was entered manually using a diagnostic service aid. For some devices, the vital product data is collected automatically from the devices through methods and added to the Customized VPD object class.

If you run the **Iscfg** command with the **-p** flag, it displays device information stored in the platform specific data areas. When used with the **-v** flag, VPD data stored for these devices is also displayed. This information is obtained on a Common Hardware Reference Platform (CHRP) system from the open firmware device tree.

-I Name	Displays device information for the named device.
-p	Displays the platform-specific device information. This flag only applies to AIX 4.2.1 or later.
-v	Displays the VPD found in the Customized VPD object class. Also, on AIX 4.2.1 or later, displays
	platform specific VPD when used with the -n flag

-s Displays the device description on a separate line from the name and location.

Examples

1. To display the system configuration, enter:

lscfg

The system displays a message similar to the following:

INSTALLED RESOURCE LIST

The following resources are installed on the machine:

```
+/- = Added or deleted from Resource List.
* = Diagnostic support not available.
```

- + indicates the resource has been added to the Diagnostic Resource List. The resource is added to the Diagnostic Resource list by default when the diagnostic fileset is installed. A resource must be in the Diagnostic Resource List before diagnostics tasks can be performed on the resource.
- indicates the resource was deleted from the Diagnostic Resource List.

The resource can be added or deleted from the Resource List by running the **diag** command, and using the Task Selection menu to select either Add Resource to Resource List, or Delete Resource from Resource List.

Diagnostic support for a resource, indicated by the + character is not necessarily inclusive of all diagnostic tasks. Some resources are only supported with a subset of diagnostic task, and that subset might or might not include the Run Diagnostics Task.

```
Model Architecture: chrp
  Model Implementation: Multiple Processor, PCI bus
+ sys0
                                   System Object
                                   System Planar
+ sysplanar0
+ mem0
                                   Memory
+ L2cache0
                                   L2 Cache
                  U1.1-P1-C1
                                   Processor
+ proc0
                  U0.2-P1
                                   PCI Bus
* pci3
+ scsi0
                   U0.1-P1/Z1
                                   Wide/Ultra-2 SCSI I/O Controller
+ rmt0
                   U1.1-P1/Z1-A3
                                   SCSI 4mm Tape Drive (12000 MB)
+ cd0
                  U1.1-P1/Z1-A5
                                   SCSI Multimedia CD-ROM Drive (650 MB)
+ hdisk0
                  U1.1-P1/Z1-A9
                                  16 Bit LVD SCSI Disk Drive (4500 MB)
+ fd0
                  U0.1-P1-D1
                                   Diskette Drive
```

2. To display the system configuration with the device description on a separate line, enter:

The system displays a message similar to the following:

INSTALLED RESOURCE LIST

The following resources are installed on the machine:

```
+/- = Added or deleted from Resource List.
* = Diagnostic support not available.
  Model Architecture: chrp
 Model Implementation: Multiple Processor, PCI bus
```

- + indicates the resource has been added to the Diagnostic Resource List. The resource is added to the Diagnostic Resource list by default when the diagnostic fileset is installed. A resource must be in the Diagnostic Resource List before diagnostics tasks can be performed on the resource.
- indicates the resource was deleted from the Diagnostic Resource List.

The resource can be added or deleted from the Resource List by running the diag command, and using the Task Selection menu to select either Add Resource to Resource List, or Delete Resource from Resource List.

Diagnostic support for a resource, indicated by the + character is not necessarily inclusive of all diagnostic tasks. Some resources are only supported with a subset of diagnostic task, and that subset might or might not include the Run Diagnostics Task.

```
+ sys0
        System Object
+ sysplanar0
        System Planar
+ mem0
        Memory
+ L2cache0
        L2 Cache
+ proc0
                   U5734.100.1234567-P1-C1
        Processor
+ proc1
                   U5734.100.1234567-P1-C2
        Processor
                   U5734.100.1234567-P1-D9
+hdisk0
      16 Bit LVD SCSI Disk Drive (4500 MB)
+fd0
                   U5734.100.1234567-P1-D1
      Diskette Drive
```

3. To display the name, location, and description for devices specified by the logical name proc without VPD, enter:

```
lscfg -lproc\*
```

The system displays information for all devices with logical names beginning with proc, as follows:

```
        proc0
        U1.1-P1-C1
        Processor

        proc1
        U1.1-P1-C1
        Processor

        proc2
        U1.1-P1-C1
        Processor

        proc3
        U1.1-P1-C1
        Processor

        proc4
        U1.1-P1-C2
        Processor

        proc5
        U1.1-P1-C2
        Processor

        proc6
        U1.1-P1-C2
        Processor

        proc7
        U1.1-P1-C2
        Processor
```

4. To display the VPD for a specific device specified by the logical name ent0, enter:

```
1scfg -v -1 ent0
```

The system displays the following:

5. To display the VPD in the open firmware device tree for the corresponding node to the ent0 device, enter:

```
1scfg -vp -lent0
```

The following is displayed:

Files

/usr/sbin/lscfg Contains the lscfg command.

Physical Location: U0.1-P1-I2/E1

Related Information

The Isattr command, Isconn command, Isdev command, Isparent command.

Iscifscred Command

Purpose

Lists the server or user entries stored in the /etc/cifs_fs/cifscred file.

Syntax

Iscifscred [-h RemoteHost] [-u user]

Description

The Iscifscred command lists all of the server or user entries that have passwords stored in the /etc/cifs_fs/cifscred file.

Flags

-h RemoteHost Lists credentials matching the given remote host (CIFS

server) only.

-u user Lists credentials matching the given user name only.

Exit Status

0 The command completed successfully.

>0 An error occurred.

Examples

1. To list all server and user entries on a server named server1, enter:

lscifscred -h server1

Location

/usr/sbin/lscifscred

Related Information

The chcifscred command, chcifsmnt command, "Iscifsmnt Command," "mkcifscred Command" on page 549, "mkcifsmnt Command" on page 550, rmcifscred command, rmcifsmnt command.

Iscifsmnt Command

Purpose

Lists the CIFS mounts defined in the /etc/filesystems file.

Syntax

Iscifsmnt [-c | -l | -p] [FileSystem]

Description

The Iscifsmnt command lists the specified CIFS mounts that are defined in the /etc/filesystems file.

Flags

Specifies that the CIFS mount be listed in colon delimited -C

-1 Specifies that the CIFS mount be listed in standard format

with each field separated by whitespace. This is the

Specifies that the CIFS mount be listed in pipe delimited -p

format.

Parameters

FileSystem

Specifies which file system to list the characteristics of. The default is to list all CIFS file systems.

Exit Status

>0

The command completed successfully.

An error occurred.

Examples

1. To list all CIFS mounts defined in /etc/filesystems, enter:

lscifsmnt

Location

/usr/sbin/lscifsmnt

Related Information

The chaifscred command, chaifsmnt command, "Isaifscred Command" on page 331, "mkaifscred Command" on page 549, "mkcifsmnt Command" on page 550, rmcifscred command, rmcifsmnt command.

Isclass Command

Purpose

List Workload Management classes and their limits.

Syntax

Isclass [-C | -D | -f] [-r] [-d Config_Dir] [-S SuperClass] [Class]

Description

The Isclass command, with no argument, returns the list of superclasses, one per line. With a class name as argument, it prints the class. The subclasses can be displayed with the -r (recursive) flag, or with the -S Superclass flag.

When WLM is started, if an empty string is passed as the name of the configuration with the -d flag, Isclass lists the classes defined in the in-core WLM data structures.

The **Isclass** command does not require any special level of privilege and is accessible for all users.

Note: If this command is given a set of time-based configurations (either specified with the -d flag, or because the current configuration is a set), the Isclass command returns the classes of the regular configuration which applies (or would apply) at the time the command is issued.

Flags

-C Displays the class attributes and limits in colon-separated records, as follows:

1sclass -C myclass

#name:description:tier:inheritance:authuser:authgroup:adminuser:admingroup:rset:CPUshares:CPUmin: CPUsoftmax:CPUhardmax:memoryshares:memorymin:memorysoftmax:memoryhardmax:diskIOshares:diskIOmin: diskIOsoftmax:diskIOhardmax:totalCPUhardmax:totalCPUunit:totalDiskIOhardmax:totalDiskIOunit: total Connect time hard max: total Connect time unit: total Processes hard max: total Thread shard max: total Logins hard max: total Connect time unit: total Processes hard max: total Thread shard max: total Logins hard max: total Connect time unit: total Processes hard max: total Thread shard max: total Logins hard m $\verb|classRealMem: classRealMem: classVirtMem: classVirtMem: classLargePages: classLargePagesunit: \\$

procVirtMem:procVirtMemunit:localshm:vmenforce:delshm

-d Config_Dir

Use /etc/wlm/Config_Dir as alternate directory for the definition files. If an empty string is passed (for example, -d ""), Isclass lists the classes defined in the in-core WLM data structures. If this flag is not present, the current configuration files in the directory pointed to by /etc/wlm/current are used.

-D

Displays the default values for the class attributes and limits in colon-separated records. Any other flag or argument used in conjunction with **-D** is ignored. For example:

#name:description:tier:inheritance:authuser:authgroup:adminuser:admingroup:rset:CPUshares:CPUmin: CPUs of t max: CPU hard max: memory shares: memory min: memory soft max: memory hard max: diskIO shares: diskIO min: memory shadiskIOsoftmax:diskIOhardmax:totalCPUhardmax:totalCPUunit:totalDiskIOhardmax:totalDiskIOunit: total Connect time hard max: total Connect time unit: total Processes hard max: total Thread shard max: total Loginshard max: total Connect time unit: total Processes hard max: total Thread shard max: total Connect time unit: total Processes hard max: total Thread shard max: total Thread sha ${\tt classRealMem:classRealMemunit:classVirtMem:classVirtMemunit:classLargePages:classLargePagesunit:}$ procVirtMem:procVirtMemunit:localshm:vmenforce:delshm

Displays the output in stanzas, with each stanza identified by a class name. Each

Attribute=Value pair is listed on a separate line:

Class:

attribute1=value attribute2=value attribute3=value

-r

-f

Displays, recursively, the superclasses with all their subclasses. When specifying -r:

- If Class is not specified, Isclass shows all the superclasses with all their subclasses.
- If the name of a superclass is specified, Isclass displays the superclass with all its subclasses.
- If the name of a subclass is specified, -r is ineffective (displays only the subclass). Restricts the scope of the command to the subclasses of the specified superclass. Only

-S SuperClass

subclasses are shown with the -S flag.

Files

classes Contains the names and definitions of the classes.

limits Contains the limits enforced on the classes.

shares Contains the resource shares attributes for each class.

Related Information

The wimcntrl command, chclass command, mkclass command, and rmclass command.

Iscomg Command

Purpose

Displays information about the communication groups of a peer domain.

Syntax

Iscomg [-I | -t | -d | -D delimiter] [-x] [-i] [-h] [-TV] [communication_group]

Description

The **Iscomg** command displays information about the communication groups that are defined to the online peer domain on which the command runs. If you specify the name of a communication group, the **Iscomg** command displays information about that communication group only.

Some of the communication group information that is displayed follows:

Field Description

Name The name of the communication group

Sensitivity The number of missed heartbeats that constitute a failure

Period The number of seconds between heartbeats

Priority The relative priority of the communication group

Broadcast Indicates whether broadcast should be used if it is supported by the

underlying media

SourceRouting Indicates whether source routing should be used if it is supported by the

underlying media

NIMPath The path to the Network Interface Module (NIM) that supports the adapter

types in the communication group

NIMParameters The NIM start parameters

Interface resources

Use the **-i** flag to display information about the interface resources that refer to *communication_group*. If you specify the **-i** flag, **Iscomg** displays the following information:

<u>Field</u> <u>Description</u>

Name The name of the interface resource that refers to *communication_group*

NodeName The host name of the interface resource that refers to

communication_group

IPAddress The IP address of the interface resource that refers to

communication_group

SubnetMask The subnet mask of the interface resource that refers to

communication_group

SubnetThe subnet of the interface resource that refers to *communication_group*

Flags

- **-I** Displays the information on separate lines (long format).
- -t Displays the information in separate columns (table format). This is the default format.
- -d Displays the information using delimiters. The default delimiter is a colon (:). Use the -D flag if you want to change the default delimiter.

-D delimiter

Displays the information using the specified delimiter. Use this flag to specify a delimiter other than the default colon (:) — when the information you want to display contains colons, for example. You can use this flag to specify a delimiter of one or more characters.

- **-x** Excludes the header (suppresses header printing).
- -i Displays information about the interface resource that refers to *communication_group*.
- Writes the command's usage statement to standard output.

- -T Writes the command's trace messages to standard error. For your software service organization's
- -V Writes the command's verbose messages to standard output.

Parameters

communication_group

Specifies the name of the communication group about which you want to display information. You can specify a communication group name or a substring of a communication group name for this parameter. If you specify a substring, the command displays information about any defined communication group with a name that contains the substring.

Security

The user of the **Iscomg** command needs read permission for the **IBM.CommunicationGroup** resource class. Read permission for the IBM.NetworkInterface resource class is required to display the network interface information. By default, root on any node in the peer domain has read and write access to these resource classes through the configuration resource manager.

Exit Status

- 0 The command ran successfully.
- 1 An error occurred with RMC.
- 2 An error occurred with a command-line interface script.
- 3 An incorrect flag was entered on the command line.
- 4 An incorrect parameter was entered on the command line.
- 5 An error occurred that was based on incorrect command-line input.
- 6 The communication group definition does not exist.

Environment Variables

CT CONTACT

Determines the system where the session with the resource monitoring and control (RMC) daemon occurs. When CT CONTACT is set to a host name or IP address, the command contacts the RMC daemon on the specified host. If CT_CONTACT is not set, the command contacts the RMC daemon on the local system where the command is being run. The target of the RMC daemon session and the management scope determine the resource classes or resources that are processed.

CT IP AUTHENT

When the CT_IP_AUTHENT environment variable exists, the RMC daemon uses IP-based network authentication to contact the RMC daemon on the system that is specified by the IP address to which the CT CONTACT environment variable is set. CT IP AUTHENT only has meaning if CT_CONTACT is set to an IP address; it does not rely on the domain name system (DNS) service.

Restrictions

This command must be run on a node that is defined and online to the peer domain on which the communication group exists.

Implementation Specifics

This command is part of the Reliable Scalable Cluster Technology (RSCT) fileset for AIX.

Standard Input

When the -f "-" or -F "-" flag is specified, this command reads one or more node names from standard input.

Standard Output

When the -h flag is specified, this command's usage statement is written to standard output. All verbose messages are written to standard output.

Standard Error

All trace messages are written to standard error.

Examples

In these examples, **nodeA** is defined and online to peer domain **ApplDomain**.

1. To display general information about the communication groups for ApplDomain, run this command on nodeA:

1scomg

The output will look like this:

```
Name Sensitivity Period Priority Broadcast SourceRouting NIMPath
                                                                 NIMParameters
             2 1 no yes /usr/sbin/rsct/bin/hats_nim
ComG1 2
```

2. To display information about the interface resources that refer to the communication group ComGrp1 for the peer domain ApplDomain, run this command on nodeA:

```
lscomg -i ComGrp1
```

The output will look like this:

Name	NodeName	IPAddr	SubnetMask	Subnet
eth0	n24	9.234.32.45	255.255.255.2	9.235.345.34
eth0	n25	9.234.32.46	255.255.255.2	9.235.345.34

Location

/usr/sbin/rsct/bin/lscomg

Related Information

Books: RSCT: Administration Guide, for information about peer domain operations

Commands: chcomg, Isrpdomain, Isrpnode, mkcomg, preprpnode, rmcomg

Information Files: rmccli, for general information about RMC-related commands

Iscondition Command

Purpose

Lists information about one or more conditions.

Syntax

Field

Iscondition [-a][-m]-n]-e[-C]-I]-t[-d]-D delimiter [-A][-q][-U][-x][-h][-TV][condition1 [,condition2,...]:node_name]

Description

The Iscondition command lists the following information about defined conditions:

Description

<u> 2000 i piron</u>
The name of the condition
The location of the condition (for management domain scope or peer domain scope)

MonitorStatus The status of the condition

ResourceClassThe resource class that is monitored by this condition **EventExpression**The expression that is used in monitoring this condition

EventDescription A description of the **EventExpression** field

RearmExpression The expression used in determining when monitoring should restart for

this condition after an event has occurred

RearmDescription A description of the RearmExpression field

SelectionString The selection string that is applied to the attributes of ResourceClass to

determine which resources are included in the monitoring of this condition

Severity The severity of the condition: critical, warning, or informational.

NodeNames The host names of the nodes where the condition is registered

MgtScope The RMC scope in which the condition is monitored

Toggle Specifies whether the condition toggles between the event and the rearm

event

Locked Specifies whether the resource is locked or unlocked

For a list of all conditions, enter the **Iscondition** command without any condition names specified. A list of all the condition names is returned with the monitoring status for each condition. The default format in this case is tabular. Specifying a node name following the condition names limits the display to the conditions defined on that node. You can list all of the conditions on a node by specifying a colon (:) followed by the node name. The node name is a node within the management scope, which is determined by the CT_MANAGEMENT_SCOPE environment variable. The management scope determines the list of nodes from which the conditions are listed. For local scope, only conditions on the local node are listed. Otherwise, the conditions from all nodes within the domain are listed.

For all of the information about all condition names, specify the **-A** flag with the **Iscondition** command. The **-A** flag causes all information about a condition to be listed when no condition names are specified. When all the information about all conditions is listed, the default format is long. If a monitoring-status flag (**-e**, **-m**, or **-n**) is specified, the conditions with that status are listed.

When more than one condition is specified, the condition information is listed in the order in which the condition names are entered.

By default, when a condition name is specified with the **Iscondition** command, all of the condition's attributes are displayed.

Flags

- -a Specifies that this command applies to all nodes in the cluster. The cluster scope is determined by the CT_MANAGEMENT_SCOPE environment variable. If it is not set, first the management domain scope is chosen if it exists, then the peer domain scope is chosen if it exists, and then local scope is chosen, until the scope is valid for the command. The command will run once for the first valid scope found. For example, if both a management and peer domain exist, Iscondition -a with CT_MANAGEMENT_SCOPE not set will list the management domain. In this case, to list the peer domain, set CT_MANAGEMENT_SCOPE to 2.
- **-m** Lists only those conditions that are being monitored without error.
- **-n** Lists only those conditions that are not being monitored.
- **-e** Lists only those conditions that are monitored in error.
- **-C** Displays a **mkcondition** command template based on the condition. By modifying this template,

you can create new conditions. If more than one condition is specified, the template for each **mkcondition** command appears on a separate line. This flag is ignored when no conditions are specified. This flag overrides the **–I** flag.

- Produces long-formatted output. Displays the condition information on separate lines.
- -t Displays the condition information in separate columns (table format).
- -d Produces delimiter-formatted output. The default delimiter is a colon (:). Use the -D flag if you want to change the default delimiter.

-D delimiter

Produces delimiter-formatted output that uses the specified delimiter. Use this flag to specify something other than the default, colon (:). An example is when the data to be displayed contains colons. Use this flag to specify a delimiter of one or more characters.

- **-A** Displays all of the attributes of the condition.
- -q Does not return an error when the condition does not exist.
- **-U** Indicates whether the resource is locked.
- Suppresses header printing.
- **-h** Writes the command's usage statement to standard output.
- **-T** Writes the command's trace messages to standard error. For your software service organization's use only.
- **-V** Writes the command's verbose messages to standard output.

Parameters

condition1 [,condition2,...]

Specifies the name of an existing condition that is defined on the host name *node_name*. You can specify more than one condition name. This parameter can be a condition name or a substring of a condition name. When it is a substring, any defined condition name that contains the substring will be listed.

node_name

Specifies the node where the condition is defined. If *node_name* is not specified, the local node is used. *node_name* is a node within the scope determined by the CT_MANAGEMENT_SCOPE environment variable.

Security

The user needs read permission for the **IBM.Condition** resource class to run **Iscondition**. Permissions are specified in the access control list (ACL) file on the contacted system. See the *RSCT: Administration Guide* for details on the ACL file and how to modify it.

Exit Status

- **0** The command ran successfully.
- 1 An error occurred with RMC.
- 2 An error occurred with a command-line interface script.
- 3 An incorrect flag was entered on the command line.
- 4 An incorrect parameter was entered on the command line.
- 5 An error occurred that was based on incorrect command-line input.

Environment Variables

CT CONTACT

Determines the system where the session with the resource monitoring and control (RMC) daemon occurs. When CT_CONTACT is set to a host name or IP address, the command contacts the RMC daemon on the specified host. If CT_CONTACT is not set, the command contacts the RMC daemon on the local system where the command is being run. The target of the RMC daemon session and the management scope determine the resource classes or resources that are processed.

CT IP AUTHENT

When the CT IP AUTHENT environment variable exists, the RMC daemon uses IP-based network authentication to contact the RMC daemon on the system that is specified by the IP address to which the CT_CONTACT environment variable is set. CT_IP_AUTHENT only has meaning if CT_CONTACT is set to an IP address; it does not rely on the domain name system (DNS) service.

CT_MANAGEMENT_SCOPE

Determines the management scope that is used for the session with the RMC daemon in processing the resources of the event-response resource manager (ERRM). The management scope determines the set of possible target nodes where the resources can be processed. The valid values are:

- 0 Specifies local scope.
- 1 Specifies local scope.
- 2 Specifies peer domain scope.
- 3 Specifies management domain scope.

If this environment variable is *not* set, *local* scope is used.

Implementation Specifics

This command is part of the Reliable Scalable Cluster Technology (RSCT) fileset for AIX.

Standard Output

When the -h flag is specified, this command's usage statement is written to standard output. All verbose messages are written to standard output.

Standard Error

All trace messages are written to standard error.

Examples

These examples apply to standalone systems:

1. To list all conditions and their monitoring status, run this command:

1scondition

The output will look like this:

```
MonitorStatus
                          "nodeA"
"FileSystem space used"
                                         "Monitored"
"tmp space used"
                          "nodeA"
                                        "Not monitored"
"var space used"
                          "nodeA"
```

2. To list general information about the condition "FileSystem space used" in long form, run this command:

```
lscondition "FileSystem space used"
```

The output will look like this:

```
= "FileSystem space used"
Name
                = "nodeA"
Node
MonitorStatus = "Monitored"
ResourceClass = "IBM.FileSystem"
EventExpression = "PercentTotUsed > 99"
EventDescription = "Generate event when space used is
                   greater than 99 percent full"
RearmExpression = "PercentTotUsed < 85"
RearmDescription = "Start monitoring again after it is
                    less than 85 percent"
SelectionString = ""
                = "w"
Severity
               = "{}"
NodeNames
              = "1"
MgtScope
                = "Yes"
Toggle
                 = "No"
Locked
```

3. To list the command that would create the condition "FileSystem space used", run this command:

lscondition -C "FileSystem space used"

The output will look like this:

```
mkcondition -r IBM.FileSystem -a PercentTotUsed \
-e "PercentTotUsed > 99" -E "PercentTotUsed < 85" \
-d "Generate event when space used is greater than 99 percent full" \
-D "Start monitoring after it is less than 85 percent" \
-S w "FileSystem space used"</pre>
```

4. To list all conditions that have the string **space** in their names, run this command:

1scondition space

The output will look like this:

5. To list the conditions that are in error, run this command:

1scondition -e

The output will look like this:

```
Name MonitorStatus
"var space used" "Error"
```

This example applies to clustered systems:

1. To list all conditions and their monitoring status, run this command:

1scondition -a

The output will look like this:

Name	Node	MonitorStatus
"FileSystem space used"	"nodeA"	"Monitored"
"tmp space used"	"nodeB"	"Not monitored"
"var space used"	"nodeC"	"Error"

Location

/usr/sbin/rsct/bin/lscondition

Related Information

Books: RSCT: Administration Guide, for more information about ERRM operations

Commands: chcondition, Iscondresp, mkcondition, rmcondition

Information Files: rmccli

Iscondresp Command

Purpose

Lists information about a condition and any of its condition/response associations.

Syntax

To list the link between a condition and one or more responses:

Iscondresp [-a | -n] [-I | -t | -d | -D delimiter] [-q] [-U] [-x] [-z] [-h] [-TV] [condition[:node_name] [response1 [response2...]]]

To list all of the links to one or more responses:

Iscondresp $[-a \mid -n]$ $[-I \mid -t \mid -d \mid -D$ delimiter[-q] [-x] [-z] -r [-U] [-h] [-TV]response1[:node name] [response2...]

Description

The Iscondresp command lists information about a condition and its linked responses. A link between a condition and a response is called a condition/response association. The information shows which responses are linked with a condition and whether monitoring is active for a condition and its linked response. The following information is listed:

<u>Field</u>	Description
Condition	The name of the condition linked with a response.
Response	The name of the response linked with the condition.
State	The state of the response for the condition. The state indicates whether a specified response is active or not.
Node	The location of the condition and the response.
Locked	Indicates whether the resource is locked or unlocked.

To list a particular condition and response, specify both the condition and the response. To list all responses to a condition, specify the condition only. To list all conditions to which a response is linked, specify the response and the -r flag. To list all conditions and their linked responses, do not specify any condition or response parameters.

Specifying a node name limits the display to the condition/response associations that are defined on that node. List all of the condition/response associations on a node by specifying a colon (:) followed by the node name. The node name is a node within the management scope determined by the CT MANAGEMENT SCOPE environment variable. The management scope determines the list of nodes from which the condition/response associations are listed. For local scope, only condition/response

associations on the local node are listed. For management domain scope and peer domain scope, the condition/response associations from all nodes within the domain are listed.

When neither the -a flag nor the -n flag is specified, all selected conditions for the responses are listed. Tabular format is the default.

Flags

- -a Lists only those responses that are active for the condition.
- Lists only those responses that are not active for the condition. -n
- -1 Displays the condition information and response information on separate lines (long format).
- –t Displays the condition information and response information in separate columns (table format).
- Specifies delimiter-formatted output. The default delimiter is a colon (:). Use the -D flag if you want -d to change the default delimiter.

-D delimiter

Specifies delimiter-formatted output that uses delimiter. Use this flag to specify something other than the default colon (:). For example, when the data to be displayed contains colons, use this flag to specify another delimiter of one or more characters.

- Does not return an error if either the condition or the response does not exist. -q
- -U Indicates whether the resource is locked.
- Suppresses header printing. -x
- -z Specifies that this command applies to all nodes in the cluster. The cluster scope is determined by the CT MANAGEMENT SCOPE environment variable. If it is not set, first the management domain scope is chosen if it exists, then the peer domain scope is chosen if it exists, and then local scope is chosen, until the scope is valid for the command. The command will run once for the first valid scope found. For example, if both a management and peer domain exist, Iscondresp -z with CT MANAGEMENT SCOPE not set will list the management domain. In this case, to list the peer domain, set CT MANAGEMENT SCOPE to 2.
- Lists information about all of the condition/response associations for the specified responses. Use -r this flag to indicate that all command parameters specified are responses, not conditions.
- -h Writes the command's usage statement to standard output.
- -T Writes the command's trace messages to standard error. For your software service organization's
- -V Writes the command's verbose messages to standard output.

Parameters

condition

The *condition* can be a condition name or a substring of a condition name. When it is a substring, any defined condition name that contains the substring and is linked to the response will be listed.

response1 [response2...]

This parameter can be a response name or a substring of a response name. You can specify more than one response name. When it is a substring, any defined response name that contains the substring and is linked to the condition will be listed.

node_name

Specifies the node where the condition or response is defined. If node_name is not specified, the local node is used. node_name is a node within the scope determined by the CT_MANAGEMENT_SCOPE environment variable.

Security

The user needs read permission for the IBM.Association resource class to run Iscondresp. Permissions are specified in the access control list (ACL) file on the contacted system. See the RSCT: Administration Guide for details on the ACL file and how to modify it.

Exit Status

- 0 The command ran successfully.
- 1 An error occurred with RMC.
- 2 An error occurred with a command-line interface script.
- 3 An incorrect flag was entered on the command line.
- 4 An incorrect parameter was entered on the command line.
- 5 An error occurred that was based on incorrect command-line input.

Environment Variables

CT CONTACT

Determines the system where the session with the resource monitoring and control (RMC) daemon occurs. When CT CONTACT is set to a host name or IP address, the command contacts the RMC daemon on the specified host. If CT_CONTACT is not set, the command contacts the RMC daemon on the local system where the command is being run. The target of the RMC daemon session and the management scope determine the resource classes or resources that are processed.

CT IP AUTHENT

When the CT_IP_AUTHENT environment variable exists, the RMC daemon uses IP-based network authentication to contact the RMC daemon on the system that is specified by the IP address to which the CT_CONTACT environment variable is set. CT_IP_AUTHENT only has meaning if CT CONTACT is set to an IP address; it does not rely on the domain name system (DNS) service.

CT MANAGEMENT SCOPE

Determines the management scope that is used for the session with the RMC daemon in processing the resources of the event-response resource manager (ERRM). The management scope determines the set of possible target nodes where the resources can be processed. The valid values are:

- Specifies *local* scope.
- Specifies local scope.
- 2 Specifies *peer domain* scope.
- 3 Specifies management domain scope.

If this environment variable is *not* set, *local* scope is used.

Implementation Specifics

This command is part of the Reliable Scalable Cluster Technology (RSCT) fileset for AIX.

Standard Output

When the -h flag is specified, this command's usage statement is written to standard output. All verbose messages are written to standard output.

Standard Error

All trace messages are written to standard error.

Examples

To see which resources are locked, run this command:

1scondresp -U

The output will look like this:

```
Condition
                                           Node
                                                                 Locked
"/tmp space used"
                    "E-mail root off-shift" "nodeA" "Not active"
"Page space in rate" "E-mail root anytime"
                                            "nodeA" "Not active"
```

These examples apply to standalone systems:

1. To list all conditions with their linked responses, run this command:

1scondresp

The output will look like this:

Condition	Response	Node	State
"FileSystem space used"	"Broadcast event on-shift"	"nodeA"	"Active"
"FileSystem space used	"E-mail root anytime"	"nodeA"	"Not Active"
"Page in Rate"	"Log event anvtime"	"nodeA"	"Active"

2. To list information about the condition "FileSystem space used", run this command:

lscondresp "FileSystem space used"

The output will look like this:

Condition	Response	Node	State
"FileSystem space used"	"Broadcast event on-shift"	"nodeA"	"Active"
"FileSystem space used	"E-mail root anytime"	"nodeA"	"Not Active"

3. To list information about the condition "FileSystem space used" for responses that are active, run this command:

lscondresp -a "FileSystem space used"

The output will look like this:

```
Condition
                        Response
                                                     Node
                                                               State
                                                     "nodeA"
                                                               "Active"
"FileSystem space used" "Broadcast event on-shift"
```

4. To list information about the condition "FileSystem space used" with the linked response "Broadcast event on-shift", run this command:

lscondresp "FileSystem space used" "Broadcast event on-shift"

The output will look like this:

Condition	Response	Node	State
"FileSystem space used"	"Broadcast event on-shift"	"nodeA"	"Active"

5. To list all conditions that have the string space in their names with their linked responses, run this command:

1scondresp space

The output will look like this:

Condition	Response	Node	State
"FileSystem space used"	"Broadcast event on-shift"	"nodeA"	"Active"
"FileSystem space used	"E-mail root anytime"	"nodeA"	"Not Active"

These examples apply to management domains:

1. In this example, the condition "FileSystem space used" is defined on the management server. To list information about "FileSystem space used", run this command on the management server:

```
lscondresp "FileSystem space used"
```

The output will look like this:

Condition	Response	Node	State
"FileSystem space used"	"Broadcast event on-shift"	"nodeB"	"Active"
"FileSystem space used"	"E-mail root anytime"	"nodeB"	"Not Active"

2. In this example, the condition "FileSystem space used" is defined on the managed node nodeC. To list information about "FileSystem space used", run this command on the management server:

```
lscondresp "FileSystem space used":nodeC
```

The output will look like this:

Condition	Response	Node	State
"FileSystem space used"	"Broadcast event on-shift"	"nodeC"	"Active"
"FileSystem space used"	"E-mail root anytime"	"nodeC"	"Not Active"

This example applies to a peer domain:

1. In this example, the condition "FileSystem space used" is defined in the domain. To list information about "FileSystem space used", run this command on one of the nodes in the domain:

```
lscondresp "FileSystem space used"
```

The output will look like this:

Condition	Response	Node	State
"FileSystem space used"	"Broadcast event on-shift"	"nodeD"	"Active"
"FileSystem space used"	"E-mail root anytime"	"nodeD"	"Not Active"
"FileSystem space used"	"Broadcast event on-shift"	"nodeE"	"Active"
"FileSystem space used"	"E-mail root anytime"	"nodeE"	"Not Active"

Location

/usr/sbin/rsct/bin/lscondresp

Related Information

Books: RSCT: Administration Guide, for more information about ERRM operations

Commands: mkcondition, mkcondresp, mkresponse, rmcondresp, startcondresp, stopcondresp

Information Files: rmccli

Isconn Command

Purpose

Displays the connections a given device, or kind of device, can accept.

Syntax

```
Isconn { -p ParentName | [ -c ParentClass ] [ -s ParentSubclass ] [ -t ParentType ] } { -l ChildName | -k
ChildConnectionKey \ [ -f File \ ] [ -F Format \ ] [ -h \ ] [ -H \ ]
```

Description

The Isconn command, when used with the -p ParentName flag, displays the connection locations on the parent device to which the device specified by the -I ChildName flag can be connected, or to which devices of the connection type specified by the -k ChildConnectionKey flag can be connected. If the -k and -I flags are not used, the Isconn command displays information about where a child device can be connected on the specified parent.

If the -p ParentName flag is not used, you must use a combination of one or all of the -c ParentClass, -s ParentSubclass, and -t ParentType flags to uniquely identify the predefined parent device.

You can display the default output, which is the connection location (or connection location and connection key if no child is specified), from the Predefined Connection object class. If you do not display the default, you can display the output in a user-specified format where the Format parameter is a quoted list of column names separated by nonalphanumeric characters or white space using the -F Format flag. You can insert headers above the columns using the -H flag.

Use the flags either on the command line or in the specified -f File flag.

Flags

-c ParentClass -f File -F Format	Specifies the class name of a possible parent device in the Predefined Devices object class. This flag cannot be used with the -p flag. Reads the necessary flags from the <i>File</i> parameter. Formats the output in a user-specified format, where the <i>Format</i> parameter is a quoted list of column names from the Predefined Connection object class separated, and possibly terminated, by non-alphanumeric characters or white space. If white space id used as the separator, the Isconn command displays the output in aligned columns.
-H	Displays headers above the column output.
-h	Displays the command usage message.
-k ChildConnectionKey	Specifies the connection key that identifies the subclass of the child device. This flag cannot be used with the -I flag.
-I ChildName	Specifies the logical name of a possible child device. This flag cannot be used with the -k flag.
-p ParentName	Specifies the parent device's logical name from the Customized Devices object class. This flag cannot be used with the -c , -s , or -t flag.
-s ParentSubclass	Specifies the subclass of a possible parent device in the Predefined Devices object class. This flag cannot be used with the -p flag.
-t ParentType	Specifies the device type of a possible parent device from the Predefined Devices object class. This flag cannot be used with the -p flag.

Examples

1. To list all of the possible connection locations on the sa2 IBM 8-Port EIA-232/RS-422A (PCI) Adapter that will accept an RS-232 device connection, type the following:

```
1sconn -p sa2 -k rs232
```

The system displays a possible connections similar to the following:

```
0
1
2
3
4
5
6
7
```

2. To list all of the possible connection locations and connection types on the sa2 IBM 8-Port EIA-232/RS-422A (PCI) Adapter, type the following:

1sconn -p sa2

The system displays a message similar to the following:

- 0 rs232
- 1 rs232
- 2 rs232
- 3 rs232
- 4 rs232
- 5 rs232
- 6 rs232
- 7 rs232
- 0 rs422
- 1 rs422
- 2 rs422
- 3 rs422 4 rs422
- 5 rs422
- 6 rs422
- 7 rs422

Files

/usr/sbin/lsconn

Specifies the command file.

Related Information

The chdev command, Isattr command, Isdev command, Isparent command, mkdev command, rmdev command.

Iscons Command

Purpose

Writes the name of the current console device to standard output.

Syntax

Iscons [-s] [-a | -O]

Iscons -b [-s] [-a | -O]

Iscons -d [-s]

Description

The Iscons command writes the name of the current console device to standard output. This command is also used to write the name of the device that is to be the console on the next start of the system to standard output. You can change the current console device using the swcons command. You can change the device to be the system console on the next start of the system using the chcons command.

Flags

- Displays a list of attribute name = attribute value pairs for the console device and console logging and tagging attributes. When used with the -b flag, the values are retrieved from the ODM. Without the -b flag, the values are retrieved from the console device driver. For additional information about console output logging and tagging, see the console Special File in the AIX 5L Version 5.3 Files Reference book.

 Note: This flag is not valid with the -O flag or the -d flag.
- **-b** Displays the full path name of the system console selected for the next startup of the system.
- Displays the full path name of the system console selected on the current startup of the system.
 Note: This flag is not valid with the -O flag or the -a flag.
- -O Similar to the -a flag but outputs the attribute names and values in a format suitable for use by SMIT. This flag is NOT valid with the -d flag.
 - Note: This flag is not valid with the -d flag or the -a flag.
- -s Suppresses reporting of the path name.

Exit Status

This command returns the following exit values:

- The device you are using is the current system console.
- **1** The device you are using is not the current system console.
- The device you are using is the console device selected at system start but is not currently the device supporting console message output.
- 3 Flags specified are not valid.
- 4 System error occurred.

Examples

1. To display the full path name of the current system console, type:

1scons

2. To display the full path name of the system console effective on the next startup of the system, type:

```
1scons -b
```

3. To display the full path name of the system console selected on the current startup of the system, type:

```
1scons -d
```

4. To test whether or not the current system console is directed to your display, type:

```
if lscons -s
then
echo "System messages are directed to my display" >/dev/tty
fi
```

Files

/usr/sbin/lscons

Contains the Iscons command.

Related Information

The **chcons** command, **swcons** command.

The **console** special file.

Iscore Command

Purpose

Views the current core settings.

Syntax

Iscore [-R registry] [username | -d]

Description

The **Iscore** command will be the user interface to view the current core settings. It will have the following usage:

```
lscore [-R registry] [username|-d]
```

As with **chcore**, the **-d** flag will show the default values. Viewing settings for another user is a privileged operation; however, any user may view the default values.

Flags

-d Changes the default setting for the system.

-R registry Specifies the loadable I&A module.

Security

May only be run by root or another user with system authority.

Examples

1. To list the current settings for root, type:

1score root

The output will look like:

```
compression: on
path specification: default
corefile location: default
naming specification: off
```

2. To list the default settings for the system, type:

```
1score -d
```

The output will look like:

```
compression: off
path specification: on
corefile location: /corefiles
naming specification: off
```

Related Information

The chcore command.

Iscosi Command

Purpose

Lists information related to a Common Operating System Image (COSI).

Syntax

Iscosi [[-I{1|2|3}] . . .] [-v] [COSI]

Description

The **Iscosi** command lists the status and detailed information related to a Common Operating System Image (COSI). The level of information to be listed depends on the numeric value specified by the **-I** flag, with a level ranging from 1 - 3 (3 being the most detailed). If a level is not specified, a default of level 1 information is displayed. If no argument is specified, the **Iscosi** command lists any common images that exist in the environment. The **bos.sysmgt.nim.master** fileset must be present on the system in order for the **Iscosi** command to be successful. This command can also be executed on a thin server.

Flags

-I{1|2|3}

Specifies the level of information to display.

- This level displays very limited information related to a COSI. The information listed shows only a brief summary of the COSI and the thin servers that might be using it.
- This level displays more than just basic information related to a COSI. The level includes information pertaining to the software content of the COSI.
- This level displays more in-depth information related to a COSI. The level includes information pertaining to the installation log of the COSI.

Enables verbose debug output when the **Iscosi** command runs.

-v

Exit Status

>0

The command completed successfully. An error occurred.

Security

Access Control: You must have root authority to run the Iscosi command.

Examples

1. To check if any common images exist in an environment, enter:

lscosi

When this command is entered without an argument, it merely lists common images in the environment. The output might be similar to the following list:

```
52H_0442A_cosi

52I_0444B2_GOLD_cosi

52L_0534A_cosi

53E_0545A_cosi

53D_GOLD_cosi

53A_GOLD_cosi

52M_0544A_cosi
```

2. To list brief status information for a common image named cosil, enter:

1scosi cosi1

Information similar to the following is displayed:

```
53H 0538A spot:
 class = resources
type = spot
 plat_defined = chrp
 Rstate = ready for use
 prev state = verification is being performed
  location = /export/nimvg/spot/53H_0538A spot/usr
 version = 5
release = 2
mod = 0
              = 0
 mod
 oslevel r = 5300-05
 alloc count = 2
              = master
  server
  if supported = chrp.mp ent
 Rstate result = success
Thin Server:
Client1
Client2
```

3. To list software content for a common image named cosi1, enter:

```
lscosi -12 cosi1
```

Software content similar to the following is displayed from the common image:

```
Fileset
                                      Level State Type Description
(Uninstaller)
bos.64bit 5.2.0.75 C F Base Operating System 64 bit Runtime bos.diag.com 5.2.0.75 C F Common Hardware Diagnostics bos.diag.rte 5.2.0.75 C F Hardware Diagnostics
```

4. To list both software content and status information for a common image named cosi1, enter:

```
lscosi -l1 -l2 cosi1
```

Location

/usr/sbin/lscosi

Files

/etc/niminfo

Contains variables used by NIM.

Related Information

The chcosi command, cpcosi command, "mkcosi Command" on page 571, "mkts Command" on page 692, nim command, nim_clients_setup command, nim_master_setup command, nimconfig command, rmcosi command.

Isdev Command

Purpose

Displays devices in the system and their characteristics.

Syntax

```
Isdev [ -C ][ -c Class ] [ -s Subclass ] [ -t Type ] [ -f File ] [ -F Format / -r ColumnName ] [ -h ] [ -H ] [ -I {
Name | - } ] [ -p Parent ] [ -S State ]
```

Description

The Isdev command displays information about devices in the Device Configuration database. You can display information about all devices in the Customized Devices object class using the -C flag. Any combination of the -c Class, -s Subclass, -t Type, -I Name, -p Parent, and -S State flags selects a subset of the customized devices. You can display information about all devices in the Predefined Devices object class using the -P flag. Any combination of the -c Class, -s Subclass, and -t Type flags selects a subset of the predefined devices.

You can display the default output one of the following ways:

- From the Customized Devices object class using the -C flag
- · From the Predefined Devices object class using the -P flag

To override these two default outputs, use the -F Format flag to display the output in a format that you specify using the Format parameter. The Format parameter is a quoted list of column names separated and possibly ended by non-alphanumeric characters or white space.

The Isdev command only shows information about devices based upon information in the Customized Devices (Cudv) object class or the Predefined Devices (PdDv) object class. Other object classes (such as the Customized Path (CuPath) object class) are not examined. This situation means that there may be conditions where a device might not be displayed. For example, if the -p Parent flag is used, but the parent identified in the Customized Devices object for a device does not match the Parent specified through the -p flag, the device is not displayed. However, the device may have a path to the given Parent that is defined in the Customized Paths object class. Use the Ispath command to show all MPIO-capable child devices of the given parent.

You can also use the Devices application in Web-based System Manager, or the System Management Interface Tool (SMIT) **smit Isdev** fast path to change device characteristics.

Flags

-C Lists information about a device that is in the Customized Devices object class. The default information displayed is name, status, location, and description. The -C flag is not required, but is maintained for compatibility reasons. The -C flag cannot be specified with the -P flag. If neither are specified, the Isdev command behaves as if the -C flag was specified. -c Class Specifies a device class name. This flag can be used to restrict output to devices in a specified class. -f File Reads the necessaary flags from the File parameter. -F Format Displays the output in a user-specified format, where the Format parameter is a quoted list

of column names from the Predefined or Customized Devices object class, separated and possibly ended by nonalphanumeric characters or white space. If white space is used as the separator, the **Isdev** command displays the output in aligned columns.

If you specify the -F Format flag with the -C flag, you can specify column names from both the Customized and Predefined Devices object classes. If you specify the -F Format flag with the -P flag, you can only specify column names from the Predefined Devices object class. In addition to the column names, the special purpose name description can be used to obtain a display of device descriptions. This flag cannot be used with the -r ColumnName flag. Also, the physic special purpose name can be used to display a device's physical location code.

Displays headers above the column output. -H -h Displays the command usage message.

-I Name Specifies the device logical name from the Customized Devices object class of the device

> for which information is listed. The Name argument to the -I flag can contain the same wildcard characters that can be used with the odmget command. If the Name argument is a dash, names will be read from STDIN. Names on STDIN must be separated by a comma, a tab, a space, or a "newline" character. Names cannot contain wildcard

characters. This flag cannot be used with the -P flag.

-p Parent Specifies the device logical name from the Customized Devices object class for the parent

> of devices to be displayed. The -p Parent flag can be used to show the child devices of the given Parent. The Parent argument to the -p flag may contain the same wildcard charcters that can be used with the **odmget** command. This flag cannot be used with the **-P** flag. Lists information about a device that is in the Predefined Devices object class. The default

information displayed is class, type, subclass, and description. This flag cannot be used

with the -C, -I, or -S flags.

-r ColumnName Displays the set of values in a column. For example, the ColumnName parameter takes the

> value of the Class parameter to list all of the classes. If you specify the -r ColumnName flag with the -C flag, you can specify column names from both the Customized and Predefined Devices object classes. If you specify the -r ColumnName flag with the -P flag, you can only specify column names from the Predefined Devices object class. This flag

cannot be used with the -F Format flag.

-S State Lists all devices in a specified state as named by the State parameter. The State parameter

can be a value of one of the following: · d, D, 0 or defined for the Defined state

• a, A, 1, or available for the Available state

• s, S, 2, or stopped for the Stopped state

This flag can be used to restrict output to devices in a specified state. This flag cannot be

used with the -P flag.

Specifies a device subclass name. This flag can be used to restrict output to devices in a -s Subclass

specified subclass.

Specifies a device type name. This flag can be used to restrict output to devices of a -t Type

specified type.

Exit Status

-P

This command returns the following exit values:

Successful completion. >0 An error occurred.

Examples

1. To list all of the devices in the Predefined Devices object class with column headers, type the following:

1sdev -P -H

class	type	subclass	description
logical volume	vgtype	vgsubclass	Volume group
logical volume	lvtype	lvsubclass	Logical volume
1 vm	1 vdd	1 vm	LVM Device Driver
posix aio	posix aio	node	Posix Asynchronous I/O
aio	aio	node	Asynchronous I/O (Legacy)
pty	pty	pty	Asynchronous Pseudo-Terminal
mouse	030102	usbif	USB mouse
keyboard	030101	usbif	USB keyboard
driver	tmssar	node	Target Mode SSA Router
tmssa	tmssa	tmssar	Target Mode SSA Device
disk	hdisk	ssar	SSA Logical Disk Drive
ndisk	1000mbC	ssar	1GB SSA C Physical Disk Drive

ndick	2000mbC	ccan	2CD SSA C Dhysical Disk Dnivo
pdisk	200011100	ssar	2GB SSA C Physical Disk Drive
•			
•			
disk	540mb2	scsi	540 MB SCSI Disk Drive
disk	540mb3	scsi	540 MB SCSI Disk Drive
disk	540mb4		540 MB SCSI Disk Drive
		scsi	
disk	540mb5	scsi	540 MB SCSI Disk Drive
disk	730mb2	SCS1	730 MB SCSI Disk Drive
disk	810mb	scsi	810 MB SCSI Disk Drive
disk	810mb2	scsi	810 MB SCSI Disk Drive
bus	pcic	pci	PCI Bus
bus	isac	pci	ISA Bus
adapter	df1000f9	pci	FC Adapter
adapter	df1000f7	pci	FC Adapter
driver	efscsi	iocb	FC SCSI I/O Controller Protocol Device
adapter	c1110358	pci	USB OHCI Adapter (c1110358)
adapter	ad100501	pci	ATA/IDE Controller Device
adapter	4f111100	pci	IBM 8-Port EIA-232/RS-422A (PCI) Adapter
adapter	ccm	pci	Name of the Common Character Mode device driver
driver	hdlc	331121b9	IBM HDLC Network Device Driver
adapter	331121b9	pci	IBM 2-Port Multiprotocol Adapter (331121b9)
adapter	2b102005	pci	GXT130P Graphics Adapter
adapter	2b101a05	pci	GXT120P Graphics Adapter
adapter	23100020	pci	IBM 10/100 Mbps Ethernet PCI Adapter (23100020)
			, , , , , , , , , , , , , , , , , , , ,
if	tr	TR	Token Ring Network Interface
if	vi	VI	Virtual IP Address Network Interface
if	xt	XT	X.25 Network Interface
tcpip	inet	TCPIP	Internet Network Extension
swap	paging	nfs	NFS Swap DEVICE
drawer	media1	media	SCSI Device Drawer
drawer	scsi1	dasd	SCSI DASD Drawer
adapter	4f111b00	pci	IBM 128-Port Async (PCI) Adapter
concentrator	16c232	•	16-Port RAN EIA-232 for 128-Port Adapter
concentrator	16e232	sync_pci	16-Port Enhanced RAN EIA-232 for 128-Port Adapter
	16e422	sync_pci	
concentrator if		sync_pci	16-Port Enhanced RAN RS-422 for 128-Port Adapter ATM Network Interface
	at 14105200	AT	
adapter	14105300	pci	IBM PCI 25MBPS ATM Adapter (14105300)

2. To list all of the devices in the Customized Devices object class, type the following: 1sdev -C

-		
sys0	Available	System Object
sysplanar0	Available	System Planar
mem0	Available	Memory
L2cache0	Available	L2 Cache
proc0	Available 00-00	Processor
pci0	Available	PCI Bus
pci1	Available	PCI Bus
isa0	Available 10-58	ISA Bus
siota0	Available 01-Q1	Tablet Adapter
ppa0	Available 01-R1	CHRP IEEE1284 (ECP) Parallel Port Adapter
sa0	Available 01-S1	Standard I/O Serial Port
sa1	Available 01-S2	Standard I/O Serial Port
paud0	Available 01-Q2	Ultimedia Integrated Audio
siokma0	Available 01-K1	Keyboard/Mouse Adapter
fda0	Available 01-D1	Standard I/O Diskette Adapter
scsi0	Available 10-60	Wide/Ultra-2 SCSI I/O Controller
scsi1	Available 10-61	Wide/Ultra-2 SCSI I/O Controller
sa2	Available 10-68	IBM 8-Port EIA-232/RS-422A (PCI) Adapter
sa3	Available 10-70	IBM 8-Port EIA-232/RS-422A (PCI) Adapter
sa4	Available 10-78	IBM 8-Port EIA-232/RS-422A (PCI) Adapter

hd3 Defined Logical volume Logical volume Defined hd1 hd10opt Defined Logical volume inet0 Available Internet Network Extension en0 Available 10-80 Standard Ethernet Network Interface Defined 10-80 IEEE 802.3 Ethernet Network Interface et0 100 Available Loopback Network Interface pty0 Available Asynchronous Pseudo-Terminal gxme0 Defined Graphics Data Transfer Assist Subsystem rcm0 Available Rendering Context Manager Subsystem Defined Asynchronous I/O (Legacy) aio0 posix_aio0 Defined Posix Asynchronous I/O Available 01-S1-00-00 Asynchronous Terminal tty0 Available 01-S2-00-00 Asynchronous Terminal tty1

3. To list the adapters that are in the Available state in the Customized Devices object class, type the following:

```
1sdev -C -c adapter -S a
```

The system displays a message similar to the following:

```
sa0
        Available 01-S1
                          Standard I/O Serial Port
       Available 01-S2
                          Standard I/O Serial Port
sa1
siokma0 Available 01-K1
                          Keyboard/Mouse Adapter
fda0
       Available 01-D1
                          Standard I/O Diskette Adapter
scsi0
       Available 10-60
                          Wide/Fast-20 SCSI I/O Controller
fcs0
       Available 10-68
                          FC Adapter
                          Wide/Ultra-2 SCSI I/O Controller
scsil Available 10-88
fcs1
       Available 20-60
                          FC Adapter
sioka0 Available 01-K1-00 Keyboard Adapter
siotaO Available 01-Q1
                          Tablet Adapter
                          CHRP IEEE1284 (ECP) Parallel Port Adapter
       Available 01-R1
ppa0
paud0
      Available 01-Q2
                          Ultimedia Integrated Audio
                          IBM PCI Tokenring Adapter (14101800)
t.ok0
       Available 10-70
ent0
       Available 10-80
                          IBM 10/100 Mbps Ethernet PCI Adapter (23100020)
sioma0 Available 01-K1-01 Mouse Adapter
```

4. To list all of the tape devices in the Predefined Devices object class, type the following:

1sdev -P -c tape

The system displays a message similar to the following:

```
tape ost
             fcp Other FC SCSI Tape Drive
tape scsd
             fcp FC SCSI Tape Drive
          iscsi Other iSCSI Tape Drive
tape ost
            iscsi iSCSI Tape Drive
tape scsd
tape 1200mb-c scsi 1.2 GB 1/4-Inch Tape Drive
tape 150mb scsi
                   150 MB 1/4-Inch Tape Drive
             scsi 3490E Autoloading Tape Drive
tape 3490e
tape 4mm2gb scsi 2.0 GB 4mm Tape Drive
tape 4mm4gb scsi 4.0 GB 4mm Tape Drive
tape 525mb
             scsi 525 MB 1/4-Inch Tape Drive
tape 8mm
             scsi 2.3 GB 8mm Tape Drive
            scsi 5.0 GB 8mm Tape Drive
tape 8mm5gb
             scsi 7.0 GB 8mm Tape Drive
tape 8mm7qb
tape 9trk
             scsi
                   1/2-inch 9-Track Tape Drive
tape ost
             scsi
                   Other SCSI Tape Drive
                   SCSI Tape Drive
tape scsd
             scsi
tape 4mm2gb2 scsi 2.0 GB 4mm Tape Drive
```

5. To list the supported device classes from the Predefined Devices object class, type the following:

lsdev -P -r class

```
PCM
adapter
aio
array
bus
cdrom
concentrator
container
dial
disk
diskette
drawer
driver
gxme
if
keyboard
1ft
logical volume
1pfk
1 vm
memory
mouse
pdisk
planar
port
posix_aio
printer
processor
pseudo
pty
rcm
rwoptical
swap
sys
tablet
tape
tcpip
tmscsi
tmssa
tty
```

6. To list the supported subclasses in the Predefined Devices object class for the **disk** class, type the following:

```
lsdev -P -c disk -r subclass
```

The system displays a message similar to the following:

dar fcp fdar ide iscsi scraid scsi ssar vscsi

7. To list the name, class, subclass, and type of every device in the Available state in the Customized Devices object class with column headers, type the following:

```
lsdev -C -H -S a -F 'name class subclass type'
```

```
L2cache0
           memory
                                L2cache rspc
                      sys
proc0
           processor sys
                                proc rspc
pci0
           bus
                      chrp
                                pci
pci1
           bus
                      chrp
                                pci
isa0
           bus
                      pci
                                isac
siota0
           adapter
                      isa sio isa tablet
ppa0
           adapter
                      isa sio chrp ecp
sa0
           adapter
                      isa sio pnp501
sa1
           adapter
                      isa_sio pnp501
paud0
           adapter
                      isa_sio baud4232
siokma0
           adapter
                      isa sio
                                kma chrp
fda0
           adapter
                      isa sio
                                pnp700
scsi0
           adapter
                      pci
                                sym896
           adapter
                      pci
scsi1
                                s vm896
sa2
           adapter
                      pci
                                4f111100
           adapter
                                4f111100
sa3
                      pci
sa4
           adapter
                      pci
                                4f111100
ent0
           adapter
                                23100020
                      pci
mg20
           adapter
                      pci
                                2b102005
sa5
           adapter
                      pci
                                4f111100
sioka0
           adapter
                      kma chrp keyboard
sioma0
           adapter
                      kma chrp mouse
fd0
           diskette siofd
                                fd
cd0
           cdrom
                      scsi
                                scsd
hdisk0
           disk
                      scsi
                                scsd
kbd0
           keyboard
                      std k
                                ps2
mouse0
                      std m
                                {\sf mse\_3b}
           mouse
1vdd
           1 vm
                      1 vm
                                1vdd
1ft0
           1ft
                      node
                                1ft
inet0
            tcpip
                      TCPIP
                                inet
en0
           i f
                      EN
                                en
100
           if
                      10
                                10
pty0
           pty
                      pty
                                pty
rcm0
           rcm
                      node
                                rcm
tty0
           tty
                      rs232
                                tty
tty1
           tty
                      rs232
                                tty
```

8. To list the name, class, location, and physloc of all adapter devices in the Customized Devices object class with column headers, type the following:

```
lsdev -C -c adapter -F 'name class location physloc'
```

The system displays a message similar to the following:

```
ent0
       adapter 02-08 UTMP0.02F.00004BA-P1-C3-T1
      adapter 01-08 UTMP0.02F.00004BA-P1-C2-T1
scsi0
      adapter 01-09 UTMP0.02F.00004BA-P1-C2-T2
scsi2
      adapter 03-08 UTMP0.02F.00004BA-P1-C4-T1
scsi3
      adapter 03-09 UTMP0.02F.00004BA-P1-C4-T2
vsa0
                     U9111.520.10004BA-V4-C0
      adapter
vscsi0 adapter
                     U9111.520.10004BA-V4-C2
vscsil adapter
                     U9111.520.10004BA-V4-C3
```

9. To list all of the children of the pci0 bus, type the following:

```
lsdev -p pci0
```

The system displays a message similar to the following:

```
ent0 Available 10-80 IBM 10/100 Mbps Ethernet PCI Adapter (23100020) isa0 Available 10-58 ISA Bus scsi0 Available 10-60 Wide/Fast-20 SCSI I/O Controller scsi1 Available 10-88 Wide/Ultra-2 SCSI I/O Controller tok0 Available 10-70 IBM PCI Tokenring Adapter (14103e00)
```

10. To list the devices whose names are contained in the file /tmp/f, type:

```
cat /tmp/f | 1sdev -1 -
```

```
pciO Available PCI Bus
scsiO Available 10-60 Wide/Fast-20 SCSI I/O Controller
hdiskO Available 10-60-00-8,0 16 Bit SCSI Disk Drive
```

Files

/usr/sbin/lsdev

Contains the Isdev command.

Related Information

The **chdev** command, **Isattr** command, **Isconn** command, **Isparent** command, **mkdev** command, **rmdev** command.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

For more information about the SMIT application, see System management interface tool in *Operating* system and device management.

Isdisp Command

Purpose

Lists the displays available on the system.

Syntax

Isdisp [-I]

Description

The **Isdisp** command lists the displays currently available on the system, displaying a logical name of the display, a physical slot number of a display adapter, the type of bus to which a graphics display is attached, a display name and a description of each of the displays. This command also lists the default display.

Flags

-I Specifies the removal of all header information and `Default display' from format.

Examples

To list all available displays, enter:

1sdisp

The following output of the Isdisp command lists three available displays for AIX 5.1 and earlier:

```
DEV_NAME SLOT BUS ADPT_NAME DESCRIPTION

ppr0 00-01 mca POWER_G4 Midrange Graphics Adapter
gda0 00-03 mca colordga Color Graphics Display Adapter
ppr1 00-04 mca POWER_Gt3 Midrange Entry Graphics Adapter

Default display = gda0
```

Files

bin/Isdisp Contains the **Isdisp** command.

Related Information

The **chdisp** command.

Low Function Terminal (LFT) Subsystem Overview in AIX 5L Version 5.3 Kernel Extensions and Device Support Programming Concepts.

Isfilt Command

Purpose

Lists filter rules from either the filter table or the IP Security subsystem.

Syntax

Isfilt -v 4|6 [-n fid_list] [-a] [-d]

Description

Use the Isfilt command to list filter rules and their status.

Note: Filter description fields are not listed in the kernel. No filter description text will be displayed when active or dynamic filter rules are listed.

Flags

-a	List only the active filter rules. The active filter rules are the rules being used by the filter kernel currently. If omitted, all the filter rules in the filter rule table will be listed.
-d	Lists the dynamic filter rules used for Internet Key Exchange (IKE) tunnels. This table is built dynamically as IKE negotiations start creating IP Security tunnels and their corresponding filter rules are added to the dynamic IKE filter table.
-n	Specifies the ID(s) of filter rule(s) that are displayed. The <i>fid_list</i> is a list of filter IDs separated by a space or "," or "-". The -n is not for active filter rules. This flag cannot be used with the -a flag.
-V	IP version of the filter rule you want to list. Valid values for this flag are 4 and 6. If this flag is not used, both IP version 4 and IP version 6 are listed.

Isfont Command

Purpose

Lists the fonts available to the display.

Syntax

Isfont [-I]

Description

The Isfont command displays a list of the fonts available to the display. The font identifier can help you change fonts using the chfont command.

You can use a Web-based System Manager Devices application (wsm devices fast path) to run this command. You could also use the System Management Interface Tool (SMIT) smit Isfont fast path to run this command.

Flags

Specifies the removal of all header information from format of data.

Examples

To list all fonts available to the display, enter:

1sfont

The following example displays the font identifier, font name, glyph size, and font encoding for each available font:

FONT	FILE	GLYPH	FONT
ID	NAME	SIZE	ENCODING
====	===========	=====	=======
0	Erg22.iso1.snf	12x30	IS08859-1
1	Erg11.iso1.snf	8x15	IS08859-1

For further details about the fonts available, see Text Fonts for the AIX System.

Files

/bin/lsfont Contains the Isfont command. /usr/lpp/fonts Contains fonts directory.

Related Information

The chfont command, mkfont command.

Low Function Terminal (LFT) Subsystem Overview in AIX 5L Version 5.3 Kernel Extensions and Device Support Programming Concepts.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

Isfs Command

Purpose

Displays the characteristics of file systems.

Syntax

Isfs [-q] [-c | -l] [-a | -v VfsType | -u MountGroup| [FileSystem...]]

Description

The Isfs command displays characteristics of file systems, such as mount points, automatic mounts, permissions, and file system size. The FileSystem parameter reports on a specific file system. The following subsets can be queried for a listing of characteristics:

- · All file systems
- · All file systems of a certain mount group
- · All file systems of a certain virtual file system type
- · One or more individual file systems

The Isfs command displays additional Journaled File System (JFS) or Enhanced Journaled File System (JFS2) characteristics if the -q flag is specified.

You can use a Web-based System Manager File Systems application (wsm fs fast path) to run this command. You could also use the System Management Interface Tool (SMIT) smit Isfs fast path to run this command.

Flags

Lists all file systems (default). -a

Specifies that the output should be in colon format. -C -1 Specifies that the output should be in list format.

-q Displays additional Journaled File System (JFS) or Enhanced Journaled File System (JFS2)

characteristics specific to the file system type.

This information is not reported for other virtual file system types. It is displayed in addition

to other file system characteristics reported by the Isfs command.

-u MountGroup Reports on all file systems of a specified mount group.

Reports on all file systems of a specified type. -v VfsType

Examples

1. To show all file systems in the **/etc/filesystems** file, enter:

2. To show all file systems of vfs type jfs, enter:

lsfs -v jfs

3. To show the file system size, the fragment size, the compression algorithm (if any), and the number of bytes per i-node as recorded in the superblock of the root file system, enter:

1sfs -q /

Files

/etc/filesystems Lists the known file systems and defines their characteristics.

Related Information

The **chfs** command, **crfs** command, **rmfs** command.

File systems in Operating system and device management explains file system types, management, structure, and maintenance.

Mounting in Operating system and device management explains mounting files and directories, mount points, and automatic mounts.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

System management interface tool in Operating system and device management explains SMIT structure, main menus, and tasks.

Isgroup Command

Purpose

Displays group attributes.

Syntax

```
Isgroup [-R load module] [-c |-f] [-a List] {ALL | Group [,Group]...}
```

Description

The **Isgroup** command displays group attributes. You can use this command to list all the system groups and their attributes or you can list all the attributes of individual groups. Since there is no default parameter, you must enter the ALL keyword to list all the system groups and their attributes. All the attributes described in the charoup command appear. If the Isgroup command cannot read one or more attributes, it lists as much information as possible. To view a selected attribute, use the -a List flag.

Note: If you have a Network Information Service (NIS) database installed on your system, some user information may not appear when you use the **Isgroup** command.

By default, the **Isgroup** command lists each group on one line. It displays attribute information as Attribute=Value definitions, each separated by a blank space. To list the group attributes in stanza format, use the -f flag. To list the information in colon-separated records, use the -c flag.

You can use a Web-based System Manager Users application (wsm users fast path) to run this command. You could also use the System Management Interface Tool (SMIT) smit Isgroup fast path to run this command.

Flags

-a List Specifies the attributes to display. The List parameter can include any attribute defined in the charoup command, and requires a blank space between attributes. If you specify an empty list, only the group names are listed. -C

Displays the attributes for each group in colon-separated records, as follows:

#name: attribute1: attribute2: ... Group: value1: value2:

Displays the group attributes in stanzas. Each stanza is identified by a group name. Each -f Attribute=Value pair is listed on a separate line:

> group: attribute1=value

attribute2=value attribute3=value

Specifies the loadable I&A module used to get the group attribute list.

load module

Exit Status

This command returns the following exit values:

0 The command runs successfully and all requested changes are made.

>0 An error occurred. The printed error message lists further details about the type of

failure.

Security

Access Control: This command should be a general user program with execute (x) access for all users. Attributes are read with the access rights of the invoker, so all users may not be able to access all the information. This depends on the access policy of your system. This command should have the trusted computing base attribute.

Files Accessed:

Mode File

/etc/group

/etc/security/group

/etc/passwd

Limitations

Listing a group may not be supported by all loadable I&A modules. If the loadable I&A module does not support listing a group, then an error is returned.

Examples

1. To display the attributes of the finance group in the default format, type:

1sgroup finance

2. To display the id, members (users), and administrators (adms) of the finance group in stanza format, type:

```
lsgroup -f -a id users adms finance
```

3. To display the attributes of all the groups in colon-separated format, type:

```
1sgroup -c ALL
```

All the attribute information appears, with each attribute separated by a blank space.

4. To display the attributes of the LDAP I&A loadable module group monsters, type:

```
1sgroup -R LDAP monsters
```

Files

/usr/sbin/lsgroup Contains the Isgroup command. /etc/group Contains the basic attributes of groups. Contains the extended attributes of groups. /etc/security/group

/etc/passwd Contains user IDs, user names, home directories, login shell, and finger

information.

Related Information

The **chfn** command, **chgroup** command, **chgrpmem** command, **chsh** command, **chuser** command, Isuser command, mkgroup command, mkuser command, passwd command, pwdadm command, rmgroup command, rmuser command, setgroups command, setsenv command.

For more information about the identification and authentication of users, discretionary access control, the trusted computing base, and auditing, refer to the Security.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

Isiscsi Command

Purpose

Displays information for iSCSI target data.

Syntax

Isiscsi [-I AdapterName] [-g group] [-p] [-F Format]

Description

The **Isiscsi** command displays iSCSI target data from ODM. There are two categories of data stored in ODM. The first is for statically configured iSCSI targets, which require that all the relevant iSCSI target information (such as target name, IP address, and port number) are specified in order for AIX to discover them. The second category of iSCSI target data is for iSCSI target devices that can be configured automatically, but require authentication from the host (such as passwords). These two categories of iSCSI target data are associated with the **static** and **auto** groups, respectively, specified by the **-g** flag.

Flags

-F Format

-g group

-I AdapterName

-р

Displays the output in a user-specified format, where the *Format* parameter is a quoted list of column names, separated and possibly ended by nonalphanumeric characters or white space. If white space is used as the separator, the **Isiscsi** command displays the output in aligned columns.

Specifies which group this iSCSI target is associated with. There two valid groups are **static** and **auto**. The **static** group is for iSCSI targets that cannot be automatically discovered from this host; all relevant iSCSI target information for them (such as target name, IP address, and port number) must be specified. The **auto** group is for iSCSI targets that are automatically discovered, but require authentication information such as passwords. Specifies the adapter name for the iSCSI TCP/IP Offload Engine (TOE) adapter that is attached to this iSCSI target. It can also specify the iSCSI protocol device for the iSCSI software solution device.

Displays the iSCSI target's password used for iSCSI logins from this adapter.

Exit Status

υ >0 The command completed successfully. An error occurred.

Security

The Isiscsi command is executable only by root.

Examples

1. To list all iSCSI target data for the iSCSI TOE adapter ics0, enter:

lsiscsi -l ics0

The system displays output similar to the following:

```
10.1.2.116 3260 ign.sn9216.iscsi-hw1
10.1.2.116 3260 ign.sn2105.iscsi-target
```

2. To list all iSCSI target data for this host, enter:

lsiscsi

The system displays output similar to the following:

```
ics0 1 10.1.2.116 3260 iqn.sn9216.iscsi-hw1
ics0 10.1.2.116 3260 iqn.sn2105.iscsi-target
ics1 11.23.45.67 iqn.mds9216.iscsi hw2.116 3260 iqn.sn2105.iscsi-target
```

Location

/usr/sbin/Isiscsi

Files

src/bos/usr/sbin/iscsia

Contains the common source files from which the iSCSI commands are built.

Related Information

The chiscsi Command, "mkiscsi Command" on page 592, rmiscsi Command.

Isitab Command

Purpose

Lists records in the /etc/inittab file.

Syntax

Isitab { -a | Identifier }

Description

The Isitab command displays a record in the /etc/inittab file. You can display all of the records in the /etc/inittab file, or use the *Identifier* parameter to display a specific record. The *Identifier* parameter is a 14-character field that uniquely identifies an object.

Flags

Specifies that all records in the /etc/inittab file are listed.

Examples

1. To display the record for tty2, enter:

```
lsitab "tty002"
```

The output is similar to: tty002:2:respawn:/usr/sbin/getty/dev/tty2

2. To display all of the records in the /etc/inittab file, enter:

```
lsitab -a
```

All of the records in the /etc/inittab file are displayed.

Files

/etc/inittab Indicates which processes the init command starts.

Related Information

The **chitab** command, **init** command, **mkitab** command, **rmitab** command.

Iskbd Command

Purpose

List the current software keyboard map loaded into the system.

Syntax

Iskbd

Description

The **Iskbd** command displays the absolute pathname of the current software keyboard map loaded into the system.

To list the current software keyboard map enter:

1skbd

You can use the Devices application in Web-based System Manager (wsm) to change device characteristics. You could also use the System Management Interface Tool (SMIT) smit Iskbd fast path to run this command.

Note: This command can be used only on an LFT display.

Example

Following is an example of the listing displayed by the lskbd command:

The current software keyboard map = /usr/lib/nls/loc/C.lftkeymap

Files

/usr/bin/lskbd Contains the Iskbd command. /usr/lib/nls/loc Software keyboard map directory.

Related Information

The **chkbd** command, **smit** command.

Low Function Terminal (LFT) Subsystem Overview in AIX 5L Version 5.3 Kernel Extensions and Device Support Programming Concepts.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

Isldap Command

Purpose

Displays naming service objects from the configured LDAP directory server.

Syntax

Isldap [-a] [entity [entry name | filter]]

Description

The Isldap command displays the naming service objects from the configured LDAP directory server. It queries the LDAP server through the secIdapcIntd daemon. Some or all of the objects of a particular entity can be listed by the Isldap command. By default, the Isldap command displays only the distinguished name (DN) of the returned objects. In addition, the -a flag can be used to view the attributes.

The Isldap command supports the following entities:

Entity	objectClass	Default attribute name
aliases	mailGroup	cn
automount	automountMap nisObject	automountMapName nisMapName
bootparams	bootableDevice	cn
ethers	ieee802Device	cn
group	posixgroup AIXAccessGroup	cn groupname
hosts	ipHost	cn
netgroup	ipNetgroup	cn
networks	ipNetwork	cn
passwd	posixAccount AIXAccount	uid username
protocols	ipProtocol	cn
rpc	oncRpc	cn
services	ipService	cn

The automount entity has two object classes. The Isldap command treats automountMap with higher precedence over nisMap by always returning automountMap objects if it finds any, and returning nisMap objects only in the absence of automountMap objects.

For the passwd and group entities, the Isldap command returns the correct objects according to the LDAP client configuration. However, the correct attribute name corresponding to the object classes must be supplied for 1sldap passwd attribute=value queries.

If an entity name is not specified from the command line, the Isldap command displays container entries of the entities and any other entries that are siblings of these containers. Users must have root permissions to list the container entries.

The entry_name parameter is the name of the object to be queried. For example, if the entity is passwd, the entry_name is the user account name. The entry_name parameter is equivalent to default attribute name = entry name. The **Isldap** command accepts the * wildcard in *entry name* for a substring search. All entries are returned if entry name is not specified.

Instead of *entry_name*, a *filter* can also be supplied to search for entries that match certain criteria. Simple filters can be specified as *attributename=attributevalue*, where *attributename* is the LDAP attribute name.

The **Isldap** command prints the result to **stdout**. If the **-a** flag is not specified, **Isldap** prints entries found in the form of DNs, with each DN separated by a blank line. If the **-a** flag is specified, each entry is printed in Idif format, with a blank line between entries.

Flags

-a

Displays all attributes of returned objects. By default only the DN of the objects are displayed.

Exit Status

Upon success, the **Isldap** command returns 0. Upon failure, a nonzero value is returned, with one of the following error messages written to **stderr**:

EIO Connection error. **EINVAL** Invalid parameters.

EPERM No permission to run the operation.

ENOMEM Not enough memory.

other **errno** Other errors.

Security

The **Isldap** command can be run by any user. It is owned by the root user and security group, and has access permissions of 555.

When listing the passwd entity with the **-a** option by root user, **Isldap** returns all attributes of the found users. However, when the same command is run by a nonprivileged user, **Isldap** returns only the same commonly readable attributes as returned by the **Isuser** command in addition to the object class information. For all other entities, there is no difference in output regardless of which user runs the command.

Examples

1. To list all entries of the host entity, type:

1sldap hosts

Information similar to the following is returned:

dn: cn=myhost+ipHostNumber=192.3.193.46,ou=Hosts,cn=aixdata

dn: cn=starfish+ipHostNumber=192.3.193.47,ou=Hosts,cn=aixdata

dn: cn=loopback+ipHostNumber=127.0.0.1,ou=Hosts,cn=aixdata

2. To list host starfish and all of its attributes, type:

lsldap -a hosts starfish

Information similar to the following is returned:

dn: cn=starfish+ipHostNumber=192.3.193.47,ou=Hosts,cn=aixdata

objectClass: top

```
objectClass: ipHost
   objectClass: device
   ipHostNumber: 192.3.193.47
   cn: loopback
   cn: localhost
3. To list users with names beginning with the letter b, type:
   lsldap passwd "b*"
   Information similar to the following is returned:
   dn: uid=bin,ou=people,cn=aixdata
   dn: uid=bob,ou=people,cn=aixdata
4. To list user foo and its attributes, type:
   lsldap -a passwd foo
   Information similar to the following is returned:
   dn: uid=foo,ou=people,cn=aixdata
   uid: foo
   objectClass: account
   objectClass: posixAccount
   objectClass: shadowAccount
   objectClass: top
   cn: foo
   uidNumber: 259
   gidNumber: 1
   homeDirectory: /home/foo
   loginShell: /usr/bin/ksh
   shadowlastchange: 12740
   userpassword: {crypt}rNnLQ9TAD2u/k
   shadowmin: 5
5. To list users who run /usr/bin/ksh, type:
   lsldap passwd loginshell=/usr/bin/ksh
   Information similar to the following is returned:
   dn: uid=bin,ou=people,cn=aixdata
```

dn: uid=bob,ou=people,cn=aixdata

dn: uid=foo,ou=people,cn=aixdata

Restrictions

The **Isldap** command relies on the **secidapcintd** daemon to work.

Location

/usr/sbin/Isldap

Related Information

The secidapcintd daemon.

Light Directory Access Protocol in the Security.

Islicense Command

Purpose

Displays the number of fixed licenses and the status of the floating licensing.

Syntax

Islicense [-A] [-c]

Description

The Islicense command displays the number of fixed licenses and the status of the floating licensing.

Flags

- The -A flag causes the Islicense command to report the current number of available fixed licenses. When the -A flag is not specified, the maximum number of fixed licenses and license status is reported.
- Displays the output in : (colon) form. -C

Examples

1. To display the number of fixed licenses and the floating license status, enter:

lslicense

Example output would be:

```
Maximum number of fixed licenses is 10.
Floating licensing is enabled.
```

2. To display the number of fixed licenses and the floating license status in a colon format, enter:

```
lslicense -c
```

Example output would be:

```
#fixed:floating
10:on
```

3. To display license information including the number of available fixed licenses, enter:

```
1slicense -A
```

Output similar to the following will display:

Maximum number of fixed licenses is 2. Floating licensing is disabled. Number of available fixed licenses is 2.

Related Information

The **chlicense** command and **monitord** daemon.

Islpcmd Command

Purpose

Lists information about the least-privilege (LP) resources on one or more nodes in a domain.

Syntax

To display LP resource information:

· On the local node:

```
Islpcmd [ -A | resource_name1 [ , resource_name2 , ... ] | -R RunCmdName1 [ , RunCmdName2 , ...
] ] [-h] [-TV]
```

· On all nodes in a domain:

```
Islpcmd -a [ -A | resource_name1 [ , resource_name2 , ... ] | -R RunCmdName1 [ , RunCmdName2 ,
... ] ] [-h] [-TV]
```

On a subset of nodes in a domain:

```
Islpcmd -n host1 [,host2,...] [ -A | resource_name1 [ , resource_name2 , ... ] | -R RunCmdName1 [ ,
RunCmdName2, ... ] ] [-h] [-TV]
```

Description

The Islpcmd command displays information about LP resources on one or more nodes in a domain. LP resources are root commands or scripts to which users are granted access based on permissions in the LP access control lists (ACLs). Use this command to display the attributes of one or more LP commands by specifying the resource name1, resource name2,...] parameter. If you omit this parameter, the Islpcmd command lists the names of all of the LP commands. Use the -A flag to list all of the LP commands and all of their attributes and values. Use the -R flag to list one or more LP resources that have a particular RunCmdName value.

The **Islpcmd** command lists the following information about defined LP resources:

Field Description

Name The name of the LP resource.

CommandPath

The fully-qualified path of the LP resource.

Description A description of the LP resource.

Lock The lock setting. Valid values are: 0 (the lock is not set) and 1 (the lock is set).

CheckSum The CheckSum value of the LP resource to which CommandPath points. The LP

resource manager assigns a value of 0 if the LP resource does not exist or if the user did

not update the **CheckSum** value after the LP resource was made available.

RunCmdName

The LP resource name that is used as a parameter with the **runlpcmd** command.

FilterScript The path to the filter script.

FilterArq The list of arguments to pass to **FilterScript**. This command runs on any node. If you want this command to run on all of the nodes in a domain, use the -a flag. If you want this command to run on a subset of nodes in a domain, use the -n flag. Otherwise, this command runs on the local node.

Flags

- Displays information about one or more LP resources on all nodes in the domain. The CT MANAGEMENT SCOPE environment variable's setting determines the cluster scope. If CT MANAGEMENT SCOPE is not set, the LP resource manager uses scope settings in this order:
 - 1. The management domain, if it exists
 - 2. The peer domain, if it exists
 - 3. Local scope

The Islpcmd command runs once for the first valid scope that the LP resource manager finds. For example, suppose a management domain and a peer domain exist and the

CT_MANAGEMENT_SCOPE environment variable is not set. In this case, Islpcmd -a runs in the management domain. To run Islpcmd -a in the peer domain, you must set CT MANAGEMENT SCOPE to 2.

-**n** host1[,host2,...]

Specifies the node or nodes in the domain on which the LP resource is to be listed. By default, the LP resource is changed on the local node. The -n flag is valid only in a management or peer domain. If the CT_MANAGEMENT_SCOPE variable is not set, the LP resource manager uses scope settings in this order:

- 1. The management domain, if it exists
- 2. The peer domain, if it exists
- 3. Local scope

The **Islpcmd** command runs once for the first valid scope that the LP resource manager finds.

- Displays all of the LP resources with their attributes and values. -A
- -R Display all attributes of the LP resources that have the same **RunCmdName** value.
- -h Writes the command's usage statement to standard output.
- -T Writes the command's trace messages to standard error.
- -V Writes the command's verbose messages to standard output.

Parameters

resource_name1[,resource_name2,...]

Specifies one or more LP resources for which you want to display information.

Security

To run the **Islpcmd** command, you need:

- read permission in the Class ACL of the IBM.LPCommands resource class.
- · read permission in the Resource ACL.

As an alternative, the Resource ACL can direct the use of the Resource Shared ACL if this permission exists in the Resource Shared ACL.

Permissions are specified in the LP ACLs on the contacted system. See the Ipacl file for general information about LP ACLs and the RSCT Administration Guide for information about modifying them.

Exit Status

The command has run successfully.

- 1 An error occurred with RMC.
- 2 An error occurred with the command-line interface (CLI) script.
- 3 An incorrect flag was specified on the command line.
- 4 An incorrect parameter was specified on the command line.
- 5 An error occurred with RMC that was based on incorrect command-line input.
- The resource was not found.

Environment Variables

CT CONTACT

Determines the system that is used for the session with the RMC daemon. When CT CONTACT is set to a host name or IP address, the command contacts the RMC daemon on the specified host. If CT_CONTACT is not set, the command contacts the RMC daemon on the local system where the command is being run. The target of the RMC daemon session and the management scope determine the LP resources that are processed.

CT_MANAGEMENT_SCOPE

Determines the management scope that is used for the session with the RMC daemon to process the LP resources. The management scope determines the set of possible target nodes where the resources can be processed. The valid values are:

- 0 Specifies local scope.
- 1 Specifies local scope.
- 2 Specifies *peer domain* scope.
- 3 Specifies management domain scope.

If this environment variable is not set, *local* scope is used.

Implementation Specifics

This command is part of the Reliable Scalable Cluster Technology (RSCT) fileset for AIX.

Standard Output

When the -h flag is specified, this command's usage statement is written to standard output. When the -V flag is specified, this command's verbose messages are written to standard output.

Standard Error

All trace messages are written to standard error.

Examples

1. To list the names of all LP resources on the local node, enter:

1s1pcmd

The output will look like this:

1pcommand1 1pcommand2

2. To list the names and attributes of all LP resources on the local node, enter:

1s1pcmd -A

The output will look like this:

```
Name=1pcommand1
CommandPath=/tmp/my command
Description=
Lock=1
CheckSum=112
RunCmdName=1pcommand1
FilterScript=
FilterArg=
Name=1pcommand2
CommandPath=/tmp/cmds/this command
Description=
Lock=0
CheckSum=0
RunCmdName=1pcommand2
FilterScript=
FilterArg=
           -----
```

3. To list the attributes of the LP resource **Ipcommand1** on the local node, enter:

1s1pcmd 1pcommand1

The output will look like this:

Name=1pcommand1 CommandPath=/tmp/my command Description= Lock=1 CheckSum=100 RunCmdName=1pcommand1 FilterScript= FilterArg=

4. To list the attributes of LP resources that have a **RunCmdName** value of **rpower** on the local node, enter:

1s1pcmd -R rpower

The output will look like this:

```
Name=1pcommand1
CommandPath=/opt/csm/bin/rpower
Description=
Lock=1
CheckSum=112
RunCmdName=rpower
FilterScript=/tmp/test1
FilterArg=node1, node2, node3
-----
Name=1pcommand2
CommandPath=/opt/csm/bin/rpower
Description=
Lock=0
CheckSum=112
RunCmdName=rpower
FilterScript=/tmp/test1
FilterArg=node4, node5, node6
```

Location

/usr/sbin/rsct/bin/lslpcmd Contains the Islpcmd command

Related Information

Books: RSCT Administration Guide, for information about modifying LP ACLs.

Commands: chlpcmd, lphistory, mklpcmd, rmlpcmd, runlpcmd

Information Files: **IpacI**, for general information about LP ACLs

Islpp Command

Purpose

Lists installed software products.

Syntax

```
Islpp { -d | -E | -f | -h | -i | -l | -L | -p } [ -a] [ -c] [ -J ] [ -q ] [ -l ] [ -O { [ r ] [ s ] [ u ] } ] [ FilesetName ... |
-b File | all ]
Islpp -w [-c][-q][-O {[r][s][u]}][FileName ... | all]
Islpp -L -c [ -v]
Islpp -S [A|O]
Islpp -e
```

Description

The Islpp command displays information about installed filesets or fileset updates. The FilesetName parameter is the name of a software product. The File parameter specifies a bundle file to use as a fileset list.

When only the -I (lowercase L) flag is entered, the Islpp command displays the latest installed level of the fileset specified for formatted filesets. The base level fileset is displayed for formatted filesets. When the -a flag is entered along with the -I flag, the Islpp command displays information about all installed filesets for the FilesetName specified. The -I (uppercase i) flag combined with the -I (lowercase L) flag specifies that the output from the Islpp command should be limited to base level filesets.

The **Islpp** command and the **compare report** command both show information about interim fixes installed on the system. The Islpp -L or Islpp -Lc command and the Islpp -e command must be run by root. Any interim fix information returned is used by the compare report command. The information includes an interim fix label and a level value. The interim fix label is the equivalent of a fileset name, and its level is based on the time (YY.MM.DD.HHMMSS, where YY is the year, MM is the month, DD is the day, HH is the hour, MM is the minute, and SS is the second) in which the interim fix was packaged. If a non-root user runs these commands, only software products and levels are returned, and interim fix information is not included.

The -d, -f, -h, -i, -l (lowercase L), -L, and -p flags request different types of output reports.

The -a, -c, -J, and -q flags specify the amount and format of the information that is displayed in the report.

The -O flag specifies that data is to come from a specified part of the fileset. The part may be the root part, -Or, the share part, -Os, or the usr part, -Ou.

The default value for the FilesetName parameter is all, which displays information about all installed software products. Pattern matching characters, such as * (asterisk) and ? (question mark), are valid in the FilesetName parameter. You don't have to enclose these characters in " (single quotation marks). However, using single quotation marks prevents you from searching the contents of your present directory.

Output Values

Much of the output from the Islpp command is understandable without an explanation. Other fields contain data that needs to be defined. The following sections define terms used in several of the output fields.

State Values

The state field in the Islpp output gives the state of the fileset on your system. It can have the following

State	Definition
APPLIED	The specified fileset is installed on the system. The APPLIED state means that the fileset can be rejected with the installp command and the previous level of the fileset restored. This state is only valid for Version 4 fileset updates and 3.2 migrated filesets.
APPLYING	An attempt was made to apply the specified fileset, but it did not complete successfully, and cleanup was not performed.
BROKEN	The specified fileset or fileset update is broken and should be reinstalled before being used.
COMMITTED	The specified fileset is installed on the system. The COMMITTED state means that a commitment has been made to this level of the software. A committed fileset update cannot be rejected, but a committed fileset base level and its updates (regardless of state) can be removed or deinstalled by the installp command.
EFIXLOCKED	The specified fileset is installed on the system and is locked by the interim fix manager (the emgr command).
OBSOLETE	The specified fileset was installed with an earlier version of the operating system but has been replaced by a repackaged (renamed) newer version. Some of the files that belonged to this fileset have been replaced by versions from the repackaged fileset.
COMMITTING	An attempt was made to commit the specified fileset, but it did not complete successfully, and cleanup was not performed.
REJECTING	An attempt was made to reject the specified fileset, but it did not complete successfully, and cleanup was not performed.

Action Values

The action field in the Islpp output identifies the installation action that was taken for the fileset. The following values may be found in this field:

Action	Definition
APPLY	An attempt was made to apply the specified fileset.
CLEANUP	An attempt was made to perform cleanup for the specified fileset.
COMMIT	An attempt was made to commit the specified fileset.
REJECT	An attempt was made to reject the specified fileset.

Status Values

The **status** field in the **IsIpp** output identifies the resultant status in the history of installation actions. The following values may be found in this field:

Status	Definition
BROKEN	The fileset was left in a broken state after the specified action.
CANCELED	The specified action was canceled before it completed.
COMPLETE	The commitment of the fileset has completed successfully.

Flags

- a	Displays all the information about filesets specified when combined with other flags. This flag shows all updates when combined with the -I flag and all history when combined with the -I flag. This flag cannot be specified with the -I flag.
-b File	Specifies a bundle file to search for fileset names. The filesets listed in the bundle are then listed as if they had been specified explicitly as <i>FilesetName</i> parameters. To mimic installp behavior, the installp image names are automatically wildcarded. For example, a bundle file entry of I:bos.abc will behave as if bos.abc* was specified as a <i>FilesetName</i> parameter. Note: This might also return results for bos.abcdef.If the file does not reside in one of the known bundle locations, the full path and file name, including extension, must be specified.
-c	Displays information as a list separated by colons. This flag cannot be specified with the -J flag.
-d	Displays filesets that are dependents of the specified software. A dependent fileset is one that has the specified software as a prerequisite, corequisite, ifrequisite, or installed requisite.
-е	Displays every interim fix installed on the system.
-E	Lists license agreements.
-f	Displays the names of the files added to the system during installation of the specified fileset. This flag cannot be specified with the -a flag.
-h	Displays the installation and update history information for the specified fileset. You cannot use this flag with the -J flag.
-1	(uppercase i) Limits the inputs to software products.
-i	Displays the product information for the specified fileset.
-J	Generates output in a form suitable for the System Management Interface Tool (SMIT) command to list output. This flag can only be specified with the -I (lowercase L) and -L flags.
-I	(lowercase L) Displays the name, most recent level, state, and description of the specified fileset.
-L	Displays the name, most recent level, state, and description of the specified fileset. The build date, which is specified by the year and the week in the form of <i>yyww</i> (for example, 0852), is also displayed for a fileset, if it has one. Part information (usr , root , and share) is consolidated into the same listing. For formatted filesets, it displays the most recent maintenance or technology level for the specified filesets. In addition, this flag lists any subsystem selective fixes that were installed on top of the maintenance or technology level. RPM and ISMP images are also listed.
- O	Lists information for the specified part of the fileset. When the -O flag is not specified information is listed for all parts. This option is designed for use by the nim command to list software product information for diskless or dataless workstations. You can use the following flags with this flag:

- Indicates to list information for the root part.
- Indicates to list information for the /usr/share part. -s
- Indicates to list information for the /usr part. -u
- -р Displays requisite information for the specified fileset.
- Suppresses the display of column headings.
- -S [A|O] Displays a list of automatically installed filesets and a list of optionally installed filesets. If the -S flag is followed by A, then only the automatically installed filesets are listed. If the -S flag is followed by O, then only the optionally installed filesets are listed.
- Displays only information from the vendor database, which contains ISMP product information. This flag is only valid when used with both the -L and the -c flags.
- Lists fileset that owns this file. -w

You must specify one of the mutually exclusive flags: -d, -e, -E, -f, -h, -i, -l, -L, -p, -S, and -w.

Examples

1. To list the installation state for the most recent level of installed filesets for all of the **bos.rte** filesets, type:

```
lslpp -l "bos.rte.*"
```

2. To list the installation state for the base level and updates for the fileset **bos.rte.filesystem**, type: lslpp -La bos.rte.filesystem

3. To list the installation history information of all the filesets in the **bos.net** software package, type:

lslpp -ha 'bos.net.*'

4. To list the names of all the files of the **bos.rte.lvm** fileset, type:

lslpp -f bos.rte.lvm

5. To list the fileset that owns **installp**, type:

lslpp -w /usr/sbin/installp

Output similar to the following displays:

```
Type
/usr/sbin/installp
                              bos.rte.install
```

6. To list the fileset that owns all file names that contain installp, type:

```
lslpp -w "*installp*"
```

Output similar to the following displays:

```
File
                                Fileset
 Type
                                bos.rte.install
/usr/sbin/installp
/usr/clvm/sbin/linstallpv
                                prpq.clvm
/usr/lpp/bos.sysmgt/nim/methods/c installp
                                bos.sysmgt.nim.client File
```

7. To display all files in the inventory database, type:

lslpp -w

8. To display the installation state for the RPM cdrecord image, type:

1slpp -L cdrecord

9. To display the installation state for all the filesets contained in the Server bundle located at /usr/sys/inst.data/sys bundles/Server.bnd, type:

```
lslpp -L -b Server
or:
lslpp -L -b /usr/sys/inst.data/sys_bundles/Server.bnd
```

Files

/etc/objrepos/history

/usr/lib/objrepos/history

/usr/share/lib/objrepos/history

/etc/objrepos/lpp

/usr/lib/objrepos/lpp

/usr/share/lib/objrepos/lpp

/etc/objrepos/product

/usr/lib/objrepos/product

/usr/share/lib/objrepos/product

Specifies installation and update history information

of all software products on the root.

Specifies installation and update history information of all software products on the /usr file system.

Specifies installation and update history information of all software products on the /usr/share file

system.

Specifies installation information of all software

products on the root.

Specifies installation information of all software

products on the /usr file system.

Specifies installation information of all software

products on the /usr/share file system.

Specifies installation and update information of all

software products on the root.

Specifies installation and update information of all

software products on the /usr file system.

Specifies installation and update information of all the software products on the /usr/share file system. /etc/objrepos/inventory

/usr/lib/objrepos/inventory

/usr/share/lib/objrepos/inventory

/usr/sys/inst.data/sys_bundles/ and /usr/sys/inst.data/ user_bundles/

Specifies names and locations of files in a software product on the root.

Specifies names and locations of files in a software product on the /usr file system.

Specifies names and locations of files in a software product on the /usr/share file system.

Known locations for bundle files. Bundle files should have a .bnd extension.

Related Information

The emgr command, installp command, inulag command, nim command.

Isly Command

Purpose

Displays information about a logical volume.

Syntax

To Display Logical Volume Information

Islv [-L] [-II -m] [-nPhysicalVolume] LogicalVolume

To Display Logical Volume Allocation Map

Islv [-L] [-nPhysicalVolume] -pPhysicalVolume [LogicalVolume]

Description

The Islv command displays the characteristics and status of the Logical Volume or lists the logical volume allocation map for the physical partitions on the PhysicalVolume. The logical volume can be a name or identifier.

Note: If the IsIv command cannot find information for a field in the Device Configuration Database, it will insert a question mark (?) in the value field. As an example, if there is no information for the LABEL field, the following is displayed:

LABEL: ?

The command attempts to obtain as much information as possible from the description area when it is given a logical volume identifier.

You can use the Volumes application in Web-based System Manager to change volume characteristics. You could also use the System Management Interface Tool (SMIT) smit IsIv fast path to run this command.

Flags

-L Specifies no waiting to obtain a lock on the Volume group.

Note: If the volume group is being changed, using the -L flag gives unreliable date.

-1

Lists the following fields for each physical volume in the logical volume:

PV Physical volume name.

Copies The following three fields:

- The number of logical partitions containing at least one physical partition (no copies) on the physical volume
- The number of logical partitions containing at least two physical partitions (one copy) on the physical volume
- The number of logical partitions containing three physical partitions (two copies) on the physical volume

In band

The percentage of physical partitions on the physical volume that belong to the logical volume and were allocated within the physical volume region specified by Intra-physical allocation policy.

Distribution

The number of physical partitions allocated within each section of the physical volume: outer edge, outer middle, center, inner middle, and inner edge of the physical volume.

Lists the following fields for each logical partition:

LPs Logical partition number.

PV1 Physical volume name where the logical partition's first physical partition is located.

PP1 First physical partition number allocated to the logical partition.

PV2 Physical volume name where the logical partition's second physical partition (first copy) is located.

PP2 Second physical partition number allocated to the logical partition.

PV3 Physical volume name where the logical partition's third physical partition (second copy) is located.

PP3 Third physical partition number allocated to the logical partition.

Accesses information from the specific descriptor area of *PhysicalVolume* variable. The information may not be current since the information accessed with the -n flag has not been validated for the logical volumes. If you do not use the -n flag, the descriptor area from the physical volume that holds the validated information is accessed and therefore the information that is displayed is current. The volume group need not be active when you use this flag.

Displays the logical volume allocation map for the *PhysicalVolume* variable. If you use the *LogicalVolume* parameter, any partition allocated to that logical volume is listed by logical partition number. Otherwise, the state of the partition is listed as one of the following:

used Indicates that the partition is allocated to another logical volume.

free Indicates that the specified partition is not being used on the system.

stale Indicates that the specified partition is no longer consistent with other partitions. The computer lists the logical partitions number with a question mark if the partition is stale.

If no flags are specified, the following status is displayed:

Logical volume

Volume group

Name of the logical volume. Logical volume names must be unique systemwide and can range from 1 to 15 characters.

Name of the volume group. Volume group names must be unique

systemwide and can range from 1 to 15 characters.

-m

-n PhysicalVolume

-p PhysicalVolume

Logical volume identifier (LV identifier)

Permission

Volume group state (VG state)

Logical volume state (LV state)

Type

Write verify

Mirror write consistency

Max LPs

PP size Copies

Schedule policy (Sched policy)

I Ps PPs

Stale partitions

BB policy Inter-policy Intra-policy

Upper bound

Relocatable

Mount point

Lahel

Each LP copy on a separate PV?

Serialize IO?

Stripe width Stripe size

Identifier of the logical volume.

Access permission; read-only or read-write.

State of the volume group. If the volume group is activated with the varyonvg command, the state is either active/complete (indicating all physical volumes are active) or active/partial (indicating all physical volumes are not active). If the volume group is not activated with the varyonvg command, the state is inactive. State of the logical volume. The Opened/stale status indicates the

logical volume is open but contains physical partitions that are not current. Opened/syncd indicates the logical volume is open and synchronized. Closed indicates the logical volume has not been

opened.

Logical volume type.

Write verify state of on or off.

Mirror write consistency state of on or off.

Maximum number of logical partitions the logical volume can hold.

Size of each physical partition.

Number of physical partitions created for each logical partition when

allocating.

Sequential or parallel scheduling policy.

Number of logical partitions currently in the logical volume. Number of physical partitions currently in the logical volume. Number of physical partitions in the logical volume that are not

current.

Bad block relocation policy. Inter-physical allocation policy. Intra-physical allocation policy.

If the logical volume is super strict, upper bound is the maximum

number of disks in a mirror copy.

Indicates whether the partitions can be relocated if a reorganization

of partition allocation takes place.

File system mount point for the logical volume, if applicable.

Specifies the label field for the logical volume.

The strictness value. Current state of allocation, strict, nonstrict, or

superstrict. A strict allocation states that no copies for a logical partition are allocated on the same physical volume. If the allocation does not follow the strict criteria, it is called nonstrict. A nonstrict allocation states that at least one occurrence of two physical partitions belong to the same logical partition. A superstrict allocation states that no partition from one mirror copy may reside

the same disk as another mirror copy.

Serialization of overlapping IOs state of yes or no. If serialization is

turned on (yes), then overlapping IOs are not allowed on a block range, and only a single IO in a block range is processed at any one time. Most applications, such as file systems and databases, perform serialization; therefore, serialization should be turned off

(no). The default setting for new logical volumes is no.

The number of physical volumes being striped across.

The number of bytes per stripe.

Examples

1. To display information about logical volume 1v03, enter:

1s1v 1v03

Information about logical volume 1v03, its logical and physical partitions, and the volume group to which it belongs is displayed.

2. To display the logical volume allocation map for hdisk2, enter:

```
lslv -p hdisk2
```

An allocation map for hdisk2 is displayed, showing the state of each partition. Since no LogicalVolume parameter was included, the map does not contain logical partition numbers specific to any logical volume.

3. To display information about logical volume 1v03 by physical volume, enter:

```
1s1v -1 1v03
```

The characteristics and status of 1v03 are displayed, with the output arranged by physical volume.

4. To display information about physical volume hdisk3 gathered from the descriptor area on hdisk2, enter:

```
lslv -n hdisk2 -p hdisk3 lv02
```

An allocation map, using the descriptor area on hdisk2, is displayed. Because the LogicalVolume parameter is included, the number of each logical partition allocated to that logical volume is displayed on the map.

5. To display information about a specific logical volume, using the identifier, enter:

lslv 00000256a81634bc.2

All available characteristics and status of this logical volume are displayed.

File

/usr/sbin Contains the IsIv command.

Related Information

The chiv command, ispv command, isvg command, mkiv command, reorgvg command, varyonvg command.

Monitoring disk I/O in Performance management

The Logical volume storage in Operating system and device management explains the Logical Volume Manager, physical volumes, logical volumes, volume groups, organization, ensuring data integrity, and allocation characteristics.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

System management interface tool in *Operating system and device management* explains the structure, main menus, and tasks that are done with SMIT.

Ismaster Command

Purpose

Displays the characteristics for the configuration of an NIS master server.

Syntax

/usr/sbin/Ismaster [-c | -l]

Description

The **Ismaster** command displays the characteristics of an NIS master server. The host names of the slave servers are listed along with the currently served domains.

You can use the Devices application in Web-based System Manager (wsm) to change device characteristics. You could also use the System Management Interface Tool (SMIT) **smit Ismaster** fast path to run this command.

Flags

- -c Specifies that the output should be in colon format. This flag is the default.
- -I Specifies that the output should be in list format.

Examples

To list the NIS master server characteristics in colon format, enter:

1smaster -c

Files

/var/yp/domainname directory

Contains the NIS maps for the NIS domain.

Related Information

The chmaster command, mkmaster command, rmyp command, smit command.

Network File System (NFS) Overview for System Management in *Networks and communication management*.

Network Information Services (NIS) Overview for System Management in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide.

NIS Reference in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

System management interface tool in Operating system and device management.

Ismcode Command

Purpose

Displays microcode and firmware levels of the system and adapters and devices.

Syntax

Ismcode [-A | -d Name] [-r | -c] [-t [service | system | adapter | adapter-boot | raid-dasd | backplane]]

Description

The **Ismcode** command when run without any flags, displays the platform system firmware microcode level and the service processor microcode levels, if supported. Not all systems contain a service processor, nor do all systems support displaying the system processor level. Information on a specific device is displayed with the **-d** flag.

If you run the **Ismcode** command with the **-r** or **-c** flag, it displays the microcode levels in a **printf** format; that is, not a menu. This method is preferred if running **Ismcode** from a script.

Flags

-A Displays microcode level information for all supported devices. Using this flag assumes the **-r**

flag.

-c Displays the microcode/firmware levels without using menus.
 -d Name Displays microcode level information for the named device.

-r Displays the microcode/firmware levels in a tabular format. The microcode level is preceded

by a Type if supported or required.

Current supported Types are as follows:

system

System Firmware

service

Service Processor

adapter

Adapter Functional microcode

adapter-boot

Adapter Boot Microcode

raid-dasd

DASD Microcode in a RAID array

backplane

Backplane Microcode in a RAID subsystem

Specifies the microcode type. The microcode level information of the specified type is displayed. You can use the **-t** flag only when a device supports multiple types. You can use the **-A** flag to find any devices supporting multiple types.

Examples

-t

1. To display the system firmware level and service processor (if present), type:

1smcode -c

The system displays a message similar to the following:

System Firmware level is TCP99256

2. To display the system firmware level and service processor (if present) in raw mode, type:

1smcode -r

The system displays a message similar to the following:

system:TCP99256

3. To display the adapter microcode levels for a RAID adapter scraid0, type:

1smcode -r -d scraid0

The system displays a message similar to the following:

```
adapter:4.20.18|adapter-boot:4.00.26
raid-dasd:22:FFC #:DDYS-T0.524D3031.53393446
raid-dasd:26:FFC #:DDYS-T0.524D3031.53393446
raid-dasd:2e:FFC #:DDYS-T0.525A3034.53393243
```

4. To display the microcode level for a tape drive **rmt0**, type:

```
1smcode -r -d rmt0
```

The system displays a message similar to the following:

C009

5. To display the microcode level for all supported devices, type:

```
1smcode -A
```

The system displays a message similar to the following:

```
sys0!system:TCP99256
rmt0!C009
scraid0!adapter:4.20.18|adapter-boot:4.00.26
raid-dasd:22:FFC #:DDYS-T0.524D3031.53393446
raid-dasd:26:FFC #:DDYS-T0.524D3031.53393446
raid-dasd:2e:FFC #:DDYS-T0.525A3034.53393243
```

6. To display the microcode level of the adapter microcode type for a RAID adapter scraid0, type:

```
1smcode -rd scraid0 -t adapter
```

The system displays a message similar to the following:

```
adapter:4.50.01
```

Files

/usr/sbin/lsmcode

Contains the Ismcode command.

Related Information

The diag command.

Ismksysb Command

Purpose

Lists or restores the contents of a volume group backup on a specified media.

Syntax

```
Ismksysb [ -b blocks ] [ -f device ] [ -a ] [ -c ] [ -l ] [ -n ] [ -r ] [ -s ] [ -d path ] [ -B ] [ -D ] [ -L ] [ -V ] [
file_list ]
```

Description

The **Ismksysb** command lists the contents of a volume group backup from tape, file, CD-ROM, or other source and can be used to restore files from a valid backup source. The **Ismksysb** command also works for multi-volume backups such as multiple CDs, DVDs, USB disks, or tapes.

The **Ismksysb** -r and **restorevgfiles** commands perform identical operations and should be considered interchangeable.

Flags

-a Verifies the physical block size of the tape backup, as specified by the -b block flag. You may

need to alter the block size if necessary to read the backup. The -a flag is valid only when a

tape backup is used.

-b blocks Specifies the number of 512-byte blocks to read in a single input operation, as defined by the

blocks parameter. If the blocks parameter is not specified, the number of blocks read will

default to 100.

-B Prints the volume group backup log to **stdout**.

> This flag will display the past 256 backups (roughly). The log is in alog format and is kept in /var/adm/ras/vgbackuplog. Each line of the log is a semicolon-separated list of the file or device name, the command used to make backup, date, shrink size, full size of the backup, and recommended maintenance or technology level (if any).

> Note: The shrink size is the size of the data on all filesystems. The full size is total size of each filesystem (unused + data).

Produces colon-separated output. This flag only works with the -I and -L flags.

Specifies the directory path to which the files will be restored, as defined by the path -d path

parameter. If the -d parameter is not used, the current working directory is used. This can be a problem if the current working directory is root. We recommend writing to a temporary folder instead of to root.

-D Produces debug output.

-f device Specifies the type of device containing the backup (file, tape, CD-ROM, or other source) as

defined by the device parameter. When -f is not specified, device will default to /dev/rmt0.

-1 Displays useful information about a volume group backup.

> This flag requires the -f device flag. This flag causes Ismksysb to display information such as volume group, date and time backup was made, uname output from backed up system, oslevel, recommended maintenance or technology level, backup size in megabytes, and backup shrink size in megabytes. The shrink size is the size of the data on all filesystems. The full size is the total size of each filesystem (unused + data). The -I flag also displays the logical volume and filesystem information of the backed up volume group, equivalent to running "Isvg -I vgname".

Displays lpp fileset information about a mksysb backup only. -L

> This flag requires the -f device flag and displays the equivalent information to that produced by invoking "Isipp -I" on the running backed up system. This flag does not produce output about any volume group backup other than that produced by mksysb.

Does not restore ACLs, PCLs, or extended attributes -n

Specifies to restore the backup files, as defined by the file-list parameter. If the file-list -r

> parameter is not specified, then all files in the backup will be restored. If the -r flag is not used, then executing the Ismksysb command only lists the files in the specified backup.

Specifies that the backup source is a user volume group and not rootvg.

-V Verifies a tape backup.

> This flag requires the -f device flag and works for tape devices only. The -V flag causes Ismksysb to verify the readability of the header of each file on the volume group backup and print any errors that occur to stderr.

Parameters

file list

-c

Identifies the list of files to be restored. This parameter is used only when the -r flag is specified. The full path of the files relative to the current directory should be specified in the space-separated list. All files in the specified directory will be restored unless otherwise directed. If you are restoring all files in a directory, we recommend writing to a temporary folder instead of to root.

Examples

- 1. To list the contents of the system backup located on the default device /dev/rmt0, enter: 1smksysb
- 2. To list the contents of the system backup located on device /dev/cd1, enter: 1smksysb -f /dev/cd1
- 3. To list the contents of the system backup located on device /dev/cd1, which is a user volume group that is not rootyg, enter:

```
lsmksvsb -f /dev/cd1 -s
```

To restore /etc/filesystems from the system backup located on device /dev/cd1, enter:

```
lsmksysb -f /dev/cd1 -r ./etc/filesystems
```

5. To restore all files in the /myfs/test directory of the non-rootyg backup, which is located on device /dev/cd1, and write the restored files to /data/myfiles, enter:

```
lsmksysb -f /dev/cd1 -r -s -d /data/myfiles ./myfs/test
```

6. To display colon separated lpp information about a mksysb backup tape located on /dev/rmt0, enter the following:

```
1smksysb -Lc -f /dev/rmt0
```

7. To display the volume group backup log to **stdout**, enter:

8. To list volume group and general backup data about a backup located at /tmp/mybackup, enter:

```
lsmksysb -l -f /tmp/mybackup
```

9. To verify the readability of each header on a volume group backup tape in /dev/rmt0, enter:

```
1smksysb -V -f /dev/rmt0
```

10. To list the contents of the system backup located on device /dev/usbms0, use the following command:

```
1smksysb -f /dev/usbms0
```

Files

/usr/bin/lsmksysb

Contains the Ismksysb command

Related Information

The restorevgfiles command.

Isnamsy Command

Purpose

Shows name service information stored in the database.

Syntax

Isnamsv { -C | -S"AttributeList ..." } [-Z]

Description

The Isnamsv high-level command shows customized, TCP/IP-based name service information from the /etc/resolv.conf file only. No information from the name server database is shown. The command can extract all customized name service information or selected name service attribute information from the configuration database.

You can use the Network application in Web-based System Manager (wsm) to change network characteristics. You could also use the System Management Interface Tool (SMIT) smit IsnamersIv fast path to run this command.

Flags

-C

Extracts all customized name service configuration information.

-S "AttributeList ..." Specifies a selected set of attributes to be extracted from the system

configuration database. Attributes can be the following:

domain Domain name

nameserver

Internet address of name server in dotted decimal format Specifies that the output be in colon format. This flag is used when the

Isnamsv command is invoked from the SMIT usability interface.

Examples

-Z

1. To list all customized name service configuration information in dotted decimal format, enter the following command:

1snamsv -C

2. To list selected attributes, enter the following command:

lsnamsv -S "domain nameserver"

The -S flag indicates that the quoted list that follows contains a list of attributes to display.

Related Information

The namersly command.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

Naming and Understanding the SMIT Interface for TCP/IP in Networks and communication management.

Isnfsexp Command

Purpose

Displays the characteristics of directories that are exported with the Network File System (NFS).

Syntax

/usr/sbin/lsnfsexp [-c | -l] [Directory] [-V Exported Version] [-f Exports_file]

Description

The Isnfsexp command displays the characteristics of NFS-exported directories. The Directory parameter specifies the directory to be displayed. If no directory is specified, all directories exported with NFS will be displayed.

Flags

-c Specifies that the output should be in colon format.

-1 (Lowercase L) Specifies that the output should be in list format. This flag is the default. Specifies the directory to be displayed. If no directory is specified, all directories Directory

exported with NFS will be displayed.

-f Exports_file Specifies the full path name of the export file to use if other than /etc/exports. **-V** Exported Version

Specifies the version of the directory to be displayed. Valid version numbers are 2, 3

and 4.

Examples

1. To list all of the directories currently exported with NFS in the colon format, enter:

2. To list all of the directories currently exported with NFS in the colon format and use a specified path name other than /etc/exports enter:

```
lsnfsexp -c -f /etc/exports.other
```

3. To list the entry for the /common/documents directory that is exported as version 4, enter the following command:

```
lsnfsexp /common/documents -V 4
```

File

/etc/exports Lists the directories the server can export.

Related Information

The **chnfsexp** command, **exportfs** command, **mknfsexp** command, **rmnfsexp** command, **smit** command.

Network File System (NFS) Overview for System Management in Networks and communication management.

Network Information Services (NIS) Overview for System Management in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide.

NIS Reference in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide.

Isnfsmnt Command

Purpose

Displays the characteristics of NFS mountable file systems.

Syntax

/usr/sbin/lsnfsmnt [-c | -l | -p] [FileSystem]

Description

The Isnfsmnt command displays the current characteristics of NFS mountable file systems. The FileSystem parameter specifies the file system to be displayed in the output. If no file system is specified, all of the file systems that are NFS mountable will be displayed.

Flags

-c Specifies that the output should be in colon format.

-1 (Lowercase L) Specifies that the output should be in list format. This flag is the default.

Specifies that the output should be in pipe format. -р

Examples

To list all of the NFS mounted file systems in the colon format, enter:

```
1snfsmnt -c
```

Files

/etc/filesystems

Centralizes file system characteristics.

Related Information

The **chnfsmnt** command, **mknfsmnt** command, **mount** command, **rmnfsmnt** command, **smit** command.

Network File System in Networks and communication management.

Network Information Services (NIS) Overview for System Management in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide.

NIS Reference.

System management interface tool in Operating system and device management.

Isnim Command

Purpose

Displays information about the Network Installation Management (NIM) environment.

Syntax

To Display a List of Supported NIM Classes, Subclasses, or Types

Isnim { -p| -P} [-cClass| -S]

To Display Predefined NIM Information

Isnim { -p| -P} [-c Class| -s Subclass| -t Type] [-I| -O] [-Z]

OR

Isnim { -p| -P}[-a Attribute] . . . [-Z]

To Display Attributes Required for an Operation

Isnim -tType -qOperation

To Display Information about All Customized NIM Objects

Isnim [-cClass| -sSubclass| -tType] [-I| -O] [-Z]

OR

Isnim [-aAttribute] . . . [-Z]

To Display Information about a Specific NIM Object

Isnim[-I | -O| -a Attribute . . .][-Z] ObjectName

OR

Isnim[-qOperation] ObjectName

To Display Information about Resources Available to a Specific NIM Machine

Isnim -L [-sSubclass| -tType]ObjectName

To Display Information about NIM Groups

Isnim -g | -m [-a Attribute | -cClass | -L | -I | -sSubclass | -tType | GroupObjectName

Description

The Isnim command displays information about the NIM environment. This information is divided into two basic categories: predefined and customized.

Predefined information consists of values that are preset by NIM and cannot be modified by the user. Examples of predefined information include:

- The types of objects supported by NIM
- · The classes and subclasses into which NIM organizes objects
- · The operations that can be performed on NIM objects
- The attributes that can be entered by the user

In general, NIM uses this information to make decisions during operations. Predefined information can be displayed by using the -p or -P flag. The -p flag displays default values while the -P flag displays help information.

Customized information consists of values that you enter or modify. This information represents the physical environment in which NIM operates. Related pieces of customized information are grouped together to form objects, which are organized in the NIM database by object type and class. Some examples of object types include diskless, paging, and standalone. Two examples of object classes are machines and network.

For example, a standalone workstation that is part of the NIM environment is represented by a unique object. This object is classified by NIM as a standalonemachines object, where standalone represents the object type and machines represents the object class. Entering the Isnim command on the command line without any flags displays information on all customized objects.

You can also use the **Isnim** command to display relationships between customized objects. Choose an object to anchor on (specified by the Objectname parameter) and then select the desired relationship with the -c, -s, or -t flag. The information displayed then depends upon the type and class of the anchored object. For example, if you select an object of type spot, the type of relationships that can be displayed are:

- Machines that use the Shared Product Object Tree (SPOT) resource.
- Networks that can access the SPOT resource.

When not displaying relationships, the **Isnim** command provides flags that can be used to filter the output that it would normally display. The -a, -c, -0, -s, or -t flag can be used to restrict the amount of information which is displayed.

Flags

-a Attribute Filters displayed information based on the specified attribute name. The possible attributes

are:

Operation

subclass

type

class

-c Class Specifies a NIM object class. When this flag is used without the Objectname parameter, it

filters the displayed information so only information about objects in that class is displayed.

-g Displays long listing of group object with state information for individual members.

-I Displays detailed information.

-L Displays information about resources that can be accessed by a client machine.

-m Applies other flags specified to group members.

-O Lists the operations NIM supports.

-p Displays predefined information using default values.

-P Displays help information for predefined data.

-q *Operation* Lists the attributes required for the specified operation.

-S Displays a list of NIM subclasses.

-s Subclass Specifies a NIM subclass. When this flag is used without the ObjectName parameter, it filters

the displayed information so only information about objects in that subclass is displayed.

-t Type Specifies a NIM object type. When this flag is used without the Objectname parameter, it

filters the displayed information so only information about objects of that type is displayed.

-Z Displays information in colon-separated format.

Security

Access Control: You must have root authority to run the Isnim command.

Examples

1. To display a list of NIM object classes, enter:

lsnim -p

2. To display a list of NIM subclasses, enter:

1snim -p -S

3. To display the list of NIM object types for the machines object class, enter:

lsnim -p -c machines

4. To display help information about NIM object types for the machines object class, enter:

lsnim -P -c machines

5. To display detailed information about the NIM attributes named lpp source and Rstate, enter:

1snim -p -a 1pp source -a Rstate

6. To display the operations which can be performed on the paging object type, enter:

1snim -p -t paging -0

7. To display the information required to perform a bos_inst operation on an object of the standalone object type, enter:

lsnim -t standalone -q bos_inst

8. To display information about all customized objects of the diskless object type, enter:

lsnim -t diskless

9. To display all customized objects in the networks object class, enter:

1snim -c networks

10. To display detailed information about a NIM object named altoid, enter:

lsnim -l altoid

11. To display the relationship between an object named altoid and all NIM resources, enter:

lsnim -c resources altoid

12. To display a list of operations that can be applied to altoid, enter:

lsnim -O altoid

13. To display a list of resources available to altoid, enter:

lsnim -L altoid

14. To display the members of the machine group MacGrp1 with state and group exclusion status, enter:

1snim -g MacGrp1

15. To display basic information about the members of the resource group ResGrp1, enter:

```
1snim -m ResGrp1
```

16. To display a long listing of members of the machine group MacGrp1, with any hidden NIM internal information, enter:

```
lsnim -m -Fl MacGrp1
```

17. To display all members of machine group MacGrp1 which has a spot allocated, enter:

```
lsnim -ma spot MacGrp1
```

Files

/etc/niminfo

Contains variables used by NIM.

Related Information

The nim command, nimclient command, nimconfig command, niminit command.

The .info file.

IsnIspath Command

Purpose

Shows the value of the secure NLSPATH system configuration variable.

Syntax

IsnIspath

Description

The IsnIspath command outputs the current value of the secure NLSPATH variable.

Related Information

The **chnlspath** command.

Isparent Command

Purpose

Displays the possible parent devices that accept a specified connection type or device.

Syntax

Isparent { -C | -P } { -k ChildConnectionKey | -I ChildName } [-f File] [-FFormat] [-h] [-H]

Description

The **Isparent** command lists devices from the Device Configuration database that can accept a given device as a child device, specified by the -I ChildName flag, or a given type of child device connection, specified by the -k ChildConnectionKey flag.

You can display the default output one of the following ways.

· Use the -C flag to display the default output information for a device from the Customized Devices object class, which is name, state, location, and description.

• Use the **-P** flag to display the default output information for a device from the Predefined Devices object class, which is class, type, subclass, and description.

To override these two default outputs, you can use the **-F** Format flag to display the output as designated by a user-formatted string. The Format parameter is a quoted list of column names separated and possibly terminated by nonalphanumeric characters.

You can supply the flags either on the command line or from the specified File parameter using the -f flag.

Flags

-C

	class. The information displayed can be from both the Customized and
	Predefined Devices object classes. This flag cannot be used with the -P
	flag.
-f File	Reads the necessary flags from the File variable.
-F Format	Displays the output in a user-specified format, where the <i>Format</i> variable is a quoted list of column names from the Predefined Devices object class or the Customized Devices object class separated and possibly terminated by non-alphanumeric characters. If white space is used as the separator, the
	Isparent command displays the output in aligned columns. In addition to the column names in the two object classes, the special name <i>description</i> can be used to display a text description of the device.
-H	Displays headers above the column output.

-H Displays headers above the column output-h Displays the command usage message.

-k ChildConnectionKey Specifies the connection key that identifies the device subclass name of the

child device. This flag cannot be used with the -I flag.

-I ChildName Specifies the logical name of a possible child device. This flag cannot be

used with the -k flag.

-P Lists information about a device that is in the Predefined Devices object

class. The information displayed can be from both the Customized and Predefined Devices object classes. This flag cannot be used with the ${f -C}$

Lists information about a device that is in the Customized Devices object

flag.

Examples

1. To list possible parent devices in the Customized Devices object class that accept an RS-232 device, type the following:

```
1sparent -C -k rs232
```

The system displays a message similar to the following:

```
sa0 Available 01-S1 Standard I/O Serial Port
sa1 Available 01-S2 Standard I/O Serial Port
sa2 Available 10-68 IBM 8-Port EIA-232/RS-422A (PCI) Adapter
sa3 Available 10-70 IBM 8-Port EIA-232/RS-422A (PCI) Adapter
sa4 Available 10-78 IBM 8-Port EIA-232/RS-422A (PCI) Adapter
sa5 Available 20-58 IBM 8-Port EIA-232/RS-422A (PCI) Adapter
```

2. To list possible types of parent devices in the Predefined Devices object class that accept an RS-232 device, type the following:

```
1sparent -P -k rs232
```

The system displays a message similar to the following:

```
adapter pnp501 isa_sio Standard I/O Serial Port adapter 4f111100 pci IBM 8-Port EIA-232/RS-422A (PCI) Adapter concentrator 16c232 sync_pci 16-Port RAN EIA-232 for 128-Port Adapter concentrator 16e232 sync_pci 16-Port Enhanced RAN EIA-232 for 128-Port Adapter
```

3. To list possible parent devices in the Customized Devices object class that accept the rmt0 tape device as a child device, type the following:

```
1sparent -C -1 rmt0
```

The system displays a message similar to the following:

```
scsi2 Available 20-60 Wide/Ultra-2 SCSI I/O Controller
scsi3 Available 20-61 Wide/Ultra-2 SCSI I/O Controller
scsil Available 10-88 Wide/Ultra-2 SCSI I/O Controller
scsi0 Available 10-60 Wide/Fast-20 SCSI I/O Controller
```

4. To list possible types of parent devices in the Predefined Devices object class that accept the rmt0 tape device as a child device, type the following:

```
1sparent -P -1 rmt0
```

The system displays a message similar to the following:

```
adapter sym896 pci Wide/Ultra-2 SCSI I/O Controller
adapter sym895 pci Wide/Ultra-2 SCSI I/O Controller
adapter sym875 pci Wide/Fast-20 SCSI I/O Controller
```

Files

/usr/sbin/lsparent

Contains the Isparent command.

Related Information

The chdev command, Isattr command, Isconn command, Isdev command, mkdev command, rmdev command.

Ispath Command

Purpose

Displays information about paths to an MultiPath I/O (MPIO) capable device.

Syntax

```
Ispath [ -F Format ] [ -H ] [ -I Name ] [ -p Parent ] [ -s Status ] [ -w Connection ]
Ispath -A -I Name -p Parent [ -w Connection ] {-D [ -O ] | -E [ -O ] | -F Format [ -Z character ] } [ -a
Attribute ] ...[ -f File ] [ -H ]
Ispath -A -I Name -p Parent [ -w Connection ] -R -a Attribute [ -f File ] [ -H ]
```

Ispath -h

Description

The Ispath command displays one of two types of information about paths to an MPIO capable device. It either displays the operational status for one or more paths to a single device, or it displays one or more attributes for a single path to a single MPIO capable device. The first syntax shown above displays the operational status for one or more paths to a particular MPIO capable device. In this instance, the **Ispath** command is similar to the Isdev command. The second syntax (keyed by the presence of the -A flag) displays one or more attributes for a single path to a particular MPIO capable device. In this instance, the Ispath command is similar to the Isattr command. In fact, all of the flags for the Isattr command are supported on the **Ispath** command when displaying path attributes.

Displaying Path Status with the Ispath Command

When displaying path status, the set of paths to display is obtained by searching the device configuration database for paths that match the following criteria:

- The target device name matches the device specified with the -I flag. If the -I flag is not present, then the target device is not used in the criteria.
- The parent device name matches the device specified with the -p flag. If the -p flag is not present, then parent is not used in the criteria.
- The connection matches the connection specified with the -w flag. If the -w flag is not present, then connection is not used in the criteria.
- The path status matches status specified with the -s flag. If the -s flag is not present, the path status is not used in the criteria.

If none of the -I, -p, -w, -s flags are specified, then all paths known to the system are displayed.

By default, this command will display the information in columnar form. When no flags are specified that qualify the paths to display, the format of the output is:

status device parent

The default display format can be overridden by using the -F Format flag. The -F Format flag displays the output in a user-specified format where the Format parameter is a quoted list of field names separated by, and possibly ended by, non-alphanumeric characters or white space. The field names are the fields defined in the CuPath class or one of the column heading defined above.

Note: The column names above are not translated into other languages (either when output as column headings or when input as part of the *Format* of the **-F** flag).

Possible values that can appear for the status column are:

enabled

Indicates that the path is configured and operational. It will be considered when paths are selected for IO.

disabled

Indicates that the path is configured, but not currently operational. It has been manually disabled and will not be considered when paths are selected for IO.

failed Indicates that the path is configured, but it has had IO failures that have rendered it unusable. It will not be considered when paths are selected for IO.

defined

Indicates that the path has not been configured into the device driver.

missing

Indicates that the path was defined in a previous boot, but it was not detected in the most recent boot of the system.

detected

Indicates that the path was detected in the most recent boot of the system, but for some reason it was not configured. A path should only have this status during boot and so this status should never appear as a result of the Ispath command.

Displaying Path Attributes with the Ispath Command

When displaying attributes for a path, the path must be fully qualified. Multiple attributes for a path can be displayed, but attributes belonging to multiple paths cannot be displayed in a single invocation of the **Ispath** command. Therefore, in addition to the -A flag, the -I, -p, or-w flags are required to uniquely identify a single path. For example:

• if only one path exists to a device, the -I flag is required

- if only one path between a device and a specific parent, the -I and -p flags are required
- if there are multiple paths between a device and a specific parent, the -I, -p, and -w flags are required

Furthermore, the **-s** flag is not allowed.

The same rules used by the Isattr command for displaying device attributes applies to the Ispath command for displaying path attributes.

By default, this command will display the information in columnar form. The format of the output is the same as the **Isattr** command:

attribute value description user settable

All fields are shown by default. The default display format can be overridden by using the -F Format flag. The -F Format flag displays the output in a user-specified format where the Format parameter is a quoted list of column names separated by, and possibly ended by, non-alphanumeric characters or white space. The column names allowed are the field names from the CuPathAt, PdPathAt, and PdAtXtd object classes plus the columns listed above. The PdAtXtd based information is used by the Web-based System Manager.

Note: The column names above are not translated into other languages (either when output as column headings or when input as part of the Format of the -F flag).

Flags

-a Attribute	Identifies the specific attribute to list. The 'Attribute' is the name of a path specific attribute. When this flag is provided, only the identified attribute is displayed. Multiple instances of this flag may be used to list multiple attributes. If this flag is not specified at all, all attributes associated with the identified path will be listed.
-A	Indicates that attributes for a specific path are to be displayed. When the -A flag is present, the -s <i>Status</i> flag is not allowed. However, the -I <i>Name</i> , -p <i>Parent</i> , and -w <i>Connection</i> flags must be present to fully qualify the path.
-D	Displays the attribute names, default values, descriptions, and user-settable flag values for a specific path when not used with the -O flag. The -D flag displays only the attribute name and default value in colon format when used with the -O flag. This flag is only valid when displaying path attributes and it cannot be used with the -E , -F , or -R flag.
-E	Displays the attribute names, current values, descriptions, and user-settable flag values for a specific path when not used with the -O flag. The -E flag displays only the attribute name and current value in colon format when used with the -O flag. This flag is only valid when displaying path attributes and it cannot be used with the -D , -F , or -R flag.
-f File	Reads the needed flags from the File parameter.
-F Format	Displays the output in a user-specified format, where the <i>Format</i> parameter is a quoted list of column names separated by non-alphanumeric characters or white space. Using white space as the separator, the Ispath command displays the output in aligned columns. Valid column names depends upon the type of information requested. For path display, column names from the CuPath object class can be specified. For path attribute display (the -A flag is specified), column names from the PdPathAt and CuPathAt object classes can be specified. In addition to the column names, there are two special purpose names that can be used. The name description can be used to obtain a display of attribute descriptions and user-settable can be used to obtain an indication as to whether or not an attribute can be changed. This flag cannot be used with the -E , -D , -O or -R flag.
-h	Displays the command usage message.
-Н	Displays headers above the column output. To use the -H flag with the -O flag is meaningless, the -O flag prevails. To use the -H flag with the -R flag is meaningless; the -R flag prevails.
-I Name	Specifies the logical device name of the target device whose path information is to be displayed. This flag is optional for displaying path status, but is required for displaying path attributes.

-0

-R

-p Parent

Displays all attribute names separated by colons and, on the second line, displays all the corresponding attribute values separated by colons. The attribute values are current values when the -E flag is also specified and default values when the -D flag is specified. This flag is only valid when displaying path attributes and it cannot be used with the -F and -R flags. Indicates the logical device name of the parent device of the path(s) to be displayed. This flag is optional for displaying path status, but is required for displaying path attributes. Displays the legal values for an attribute name. The -R flag cannot be used with the -D, -E, -F and -O flags. The -R flag displays the list attribute values in a vertical column as follows:

Value1 Value2

.

. ValueN

The **-R** flag displays the range attribute values as x...n(+i) where x is the start of the range, n is the end of the range, and i is the increment.

-s Status

The **-s** *Status* flag indicates the status to use in qualifying the paths to be displayed. When displaying path information, the allowable values for this flag are:

enabled

Display paths that are **enabled** for MPIO path selection.

disabled

Display paths that are **disabled** from MPIO path selection.

failed Display paths that are **failed** due to IO errors.

available

Display paths whose **path_status** is **PATH_AVAILABLE** (that is, paths that are configured in the system, includes **enabled**, **disabled**, and **failed** paths).

defined

Display paths whose path_status is PATH_DEFINED.

missing

Display paths whose path_status is PATH_MISSING.

-w Connection

Indicates the connection information to use in qualifying the paths to be displayed. This flag is optional for displaying path status, but is required for displaying path attributes.

-Z Character

The **-Z** Character flag is meant to be used for programs that need to deal with ODM fields that may have embedded new line characters. An example of such a program is the Web-based System Manager. The **-Z** Character flag is used to change the record separator character for each record (line) of output generated. The new record separator is the 'Character' argument to this flag. The **-Z** Character flag is only relevant when the **-A** and the **-F** Format flags are specified. The **-Z** Character flag cannot be used with the **-D**, **-E**, **-O**, or the **-R** flags.

Security

Privilege Control: All users can execute this command.

Auditing Events: None.

Examples

Examples of displaying path status:

1. To display the status of all paths to hdisk1 with column headers, enter:

lspath -H -l hdisk1

The system will display a message similar to the following:

```
status device parent
enabled hdisk1 scsi0
disabled hdisk1 scsi1
missing hdisk1 scsi2
```

2. To display, without column headers, the set of paths whose operational status is disabled, enter:

```
1spath -s disabled
```

The system will display a message similar to the following:

```
disabled hdisk1 scsi1
disabled hdisk2 scsi1
disabled hdisk23 scsi8
disabled hdisk25 scsi8
```

3. To display the set of paths whose operational status is failed, enter:

```
1spath -s failed
```

The system will display a message similar to the following:

```
failed hdisk1 scsi1
failed hdisk2 scsi1
failed hdisk23 scsi8
failed hdisk25 scsi8
```

4. To display in a user-specified format, without column headers, the set of paths to hdisk1 whose path status is available enter:

```
lspath -l hdisk1 -s available -F"connection:parent:path_status:status"
```

The system will display a message similar to the following:

```
5,0:scsi0:available:enabled 6,0:scsi1:available:disabled
```

Note that this output shows both the path status and the operational status of the device. The path status simply indicates whether the path is configured or not. The operational status indicates how the path is being used with respect to path selection processing in the device driver. Only paths with a path status of available also have an operational status. If a path is not currently configured into the device driver, it does not have an operational status.

Examples of displaying path attributes:

1. If the target device is a SCSI disk, to display all attributes for the path to parent scsi0 at connection 5,0, use the command:

```
lspath -AHE -1 hdisk10 -p scsi0 -w "5,0"
```

The system will display a message similar to the following:

```
attribute value description user_settable weight 1 Order of path failover selection true
```

Related Information

The **chpath** command, **mkpath** command, **rmpath** command.

Isprtsv Command

Purpose

Shows print service information stored in the database.

Syntax

```
Isprtsv { -c | -p } [ -h ] [ -q QEntry ... ] [ -Z ]
```

Description

The Isprtsv high-level command shows predefined and customized TCP/IP-based print service information. Use the Isprtsv command to extract customized or predefined print service information.

The **Isprtsv** command can show the following information:

- · A list of host names that have access rights to the print server
- Logical print queue information only

Flags

-C Extracts customized configuration information.

-h Shows a list of host names that can use the print server.

Extracts predefined configuration information.

Shows the logical print queues specified and their attributes available on a host. The QEntry -qQEntry...

variable specifies the names of the queues to display.

-Z Specifies that the output be produced in colon format. This flag is used if the Isprtsv command

is invoked from the SMIT usability interface.

Examples

1. To show all host names who have access rights to a print server, enter:

```
$ lsprtsv -c -h
```

2. To show which logical printers are available on a given client machine, enter:

```
lsprtsv -c -q sahara
```

Related Information

The chque command, chquedev command, ruser command.

The **lpd** daemon, **qdaemon** daemon.

Understanding the Transmission Control Protocol / Internet Protocol in Networks and communication management.

Isps Command

Purpose

Displays the characteristics of a paging space.

Syntax

Description

The **Isps** command displays the characteristics of a paging space. The **Isps** command displays characteristics such as the paging-space name, physical-volume name, volume-group name, size, percentage of the paging space used, whether the space is active or inactive, and whether the paging space is set to automatic. The PagingSpace parameter specifies the paging space whose characteristics are to be shown.

For NFS paging spaces, the physical-volume name and volume-group name will be replaced by the host name of the NFS server and the path name of the file that is used for paging.

If the -t flag is specified, the argument will be assumed to be a third-party helper executable. If the helper executable is present in the /sbin/helpers/pagespace path then it will be spawned passing all the arguments and with the -I flag to specify the Isps command. The helper executable must take care of displaying the characteristics of the page space. If the helper program doesn't exist in /sbin/helpers/pagespace directory, the Isps command will display the usage error. The helper executable must exit with a 0 if successful and a non-zero if it fails.

You can use the File Systems application in Web-based System Manager (wsm) to change file system characteristics. You could also use the System Management Interface Tool (SMIT) smit Isps fast path to run this command.

Flags

- Specifies that the characteristics of all paging spaces are to be given. The size is given in megabytes. -a
- Specifies that the output should be in colon format. The colon format gives the paging space size in logical -C
- -1 Specifies that the output should be in list format.
- Specifies that the summary characteristics of all paging spaces are to be given. This information consists of the -s total paging space in megabytes and the percentage of paging space currently assigned (used). If the -s flag is specified, all other flags are ignored.

Note: There is a paging space limit of 64 GB per device.

Note: Setting the environment variable PSALLOC=early causes the use of early paging space algorithm. In this case, the value the -s flag specifies is different from the value returned for a single paging space or when using the -a flag for all the paging spaces. The value the -s flag displays is the percentage of paging space allocated (reserved), whether the paging space has been assigned (used) or not. Therefore, the percentage reported by the -s flag is usually larger than that reported by the -a flag when PSALLOC is set to early.

- Specifies the characteristics of the paging space. One of the following variables is required: -t
 - lv Specifies that the characteristics of only logical volume paging spaces are to be given.
 - Specifies that the characteristics of only NFS paging spaces are to be given. The heading of the nfs output will be changed to display the host name of the NFS server and the path name of the file that resides on the server that is being used for NFS paging.

ps_helper

Name of the helper program for a third party device.

Examples

1. To list the characteristics of all paging spaces, enter:

```
lsps -a
```

This displays the characteristics for all paging spaces and provides a listing similar to the following listing:

```
Page Space Physical Volume Volume Group
                                       Size
                                             %Used Active Auto Type Chksum
hd6
                                       512MB
           hdisk0
                          rootvg
                                              1
                                                    yes
                                                           yes
                                                                1 v
```

2. To display the characteristics of paging space myps using the helper program foo enter the following commad:

```
1sps -t foo myps
```

This displays the characteristics for all paging spaces and provides a listing similar to the following listing:

Page Space	Physical Volume	Volume Group	Size %Used	Active	Auto	Туре
myps	mydisk	myvg	512MB	1 ye	s yes	1 v

Files

/etc/swapspaces

Specifies the paging space devices activated by the swapon -a command.

Related Information

The mkps command, chps command, rmps command, swap command, swapon command, swapoff command.

File systems in Operating system and device management explains file system types, management, structure, and maintenance.

Paging space in Operating system and device management explains paging space and its allocation policies.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

System management interface tool in *Operating system and device management* explains the structure, main menus, and tasks that are done with SMIT.

Ispv Command

Purpose

Displays information about a physical volume within a volume group.

Syntax

Ispv

OR

Ispv [-L] [-I | -p | -M] [-n DescriptorPhysicalVolume] [-v VolumeGroupID] PhysicalVolume

Description

The **Ispv** command displays information about the physical volume if the specific physical volume name is specified. If you do not add flags to the Ispv command, the default is to print every known physical volume in the system along with its physical disk name, physical volume identifiers (PVIDs), to which volume group (if any) the physical volume belongs, and the state of the volume group as active if the volume group is varied on or concurrent if it is varied on in concurrent mode.

Note: If the Ispv command cannot find information for a field in the Device Configuration Database, it will insert a question mark (?) in the value field. As an example, if there is no information for the PP RANGE field, the following might be displayed:

PP RANGE: ?

The Ispv command attempts to obtain as much information as possible from the description area when it is given a logical volume identifier.

When the *PhysicalVolume* parameter is used, the following characteristics of the specified physical volume are displayed:

Physical volume Name of the physical volume.

Volume group Name of volume group. Volume group names must be unique systemwide names

and can be from 1 to 15 characters long.

PV Identifier The physical volume identifier for this physical disk.

VG Identifier The volume group identifier of which this physical disk is a member. PVstate State of the physical volume. If the volume group that contains the physical volume

is varied on with the **varyonvg** command, the state is active, missing, or removed. If the physical volume is varied off with the **varyoffvg** command, the state is varied

off.

Allocatable Allocation permission for this physical volume.

Logical volumes Number of logical volumes using the physical volume.

Stale PPs Number of physical partitions on the physical volume that are not current.

VG descriptors Number of volume group descriptors on the physical volume.

PP size Size of physical partitions on the volume.

Total PPs Total number of physical partitions on the physical volume.

Free PPs Number of free physical partitions on the physical volume.

Used PPs Number of used physical partitions on the physical volume.

Max Request Max transfer size of the physical volume.

Free distribution Number of free partitions available in each intra-physical volume section.

Used distribution Number of used partitions in each intra-physical volume section.

You can use the Volumes application in Web-based System Manager (wsm) to change volume characteristics. You could also use the System Management Interface Tool (SMIT) **smit Ispv** fast path to run this command.

Flags

-1

-M

-L Specifies no waiting to obtain a lock on the Volume group.

Note: If the volume group is being changed, using the -L flag gives unreliable date.

Lists the following fields for each logical volume on the physical volume:

LVname Name of the logical volume to which the physical partitions are allocated.

LPs The number of logical partitions within the logical volume that are contained on this physical volume.

PPs The number of physical partitions within the logical volume that are contained on this physical volume.

Distribution

The number of physical partitions, belonging to the logical volume, that are allocated within each of the following sections of the physical volume: outer edge, outer middle, center, inner middle and inner edge of the physical volume.

Mount Point

File system mount point for the logical volume, if applicable.

Lists the following fields for each logical volume on the physical volume:

PVname: PPnum [LVname: LPnum [:Copynum] [PPstate]]

Where:

PVname Name of the physical volume as specified by the system.

PPnum Physical partition number.

LVname Name of the logical volume to which the physical partitions are allocated. Logical

volume names must be system-wide unique names, and can range from 1 to 64 characters.

LPnum Logical partition number. Logical partition numbers can range from 1 to 64,000.

Copynum

Mirror number.

PPstate

Only the physical partitions on the physical volume that are not current are shown as stale.

404

Accesses information from the variable descriptor area specified by the -n

DescriptorPhysicalVolume DescriptorPhysicalVolume variable. The information may not be current, since the

information accessed with the -n flag has not been validated for the logical volumes. If you do not use the -n flag, the descriptor area from the physical volume that holds the validated information is accessed, and therefore the information displayed is current. The volume group need not be active when you use this flag.

Lists the following fields for each physical partition on the physical volume:

A range of consecutive physical partitions contained on a single region of the

physical volume.

The current state of the physical partitions: free, used, stale, or vgda. State

> Note: If a volume group is converted to a big vg format, it may be necessary to use some data partitions for volume group descriptor area. These partitions will

be marked vgda.

Region The intra-physical volume region in which the partitions are located.

LVname The name of the logical volume to which the physical partitions are allocated.

The type of the logical volume to which the partitions are allocated. Type

Mount point

File system mount point for the logical volume, if applicable.

-v VolumeGroupID

Accesses information based on the VolumeGroupID variable. This flag is needed only when the Ispv command does not function due to incorrect information in the Device Configuration Database. The VolumeGroupID variable is the hexadecimal representation

of the volume group identifier, which is generated by the mkvg command.

Examples

-p

1. To display the status and characteristics of physical volume hdisk3, enter: 1spv hdisk3

2. To display the status and characteristics of physical volume hdisk5 by physical partition number, enter:

1spv -p hdisk5

Files

/usr/sbin Contains the Ispv command.

Related Information

The **chpv** command, **Islv** command, **Isvg** command, **mklv** command, **varyonvg** command.

Logical volume storage in Operating system and device management explains the Logical Volume Manager, physical volumes, logical volumes, volume groups, organization, ensuring data integrity, and allocation characteristics.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

System management interface tool in *Operating system and device management* explains the structure, main menus, and tasks that are done with SMIT.

Isque Command

Purpose

Displays the queue stanza name.

Syntax

Isque [-c] -qName

Description

The Isque command uses the printf subroutine to display the name of the queue stanza and associated attributes from the /etc/qconfig file.

Flags

Causes colon output format for use by SMIT.

Specifies the Name of the queue stanza that is sent to standard output. -q Name

Examples

1. To display the name of queue stanza 1p0, enter:

```
lsque -qlp0
```

A list similar to the following is displayed:

```
device = 1pd0
host = neptune
rq = nlp0
```

2. To display the name of queue stanza 1p0 in colon format, enter:

```
lsque -c -q lp0
```

A list similar to the following is displayed:

```
device:discipline:up:acctfile:host:s statfilter:l statfilter:rq
lpd0:fcfs:true:false:neptune:::nlp0
```

Files

/usr/bin/lsque Contains the Isque command. /etc/gconfig Contains the configuration file.

Related Information

The **chque** command, **Isquedev** command, **mkque** command, **rmque** command.

The qconfig file.

The **printf** subroutine.

Printer-specific information, Installing support for additional printers, and Virtual printer definitions and attributes in Printers and printing.

Printing administration in *Printers and printing*.

Isquedev Command

Purpose

Displays the device stanza name.

Syntax

Isquedev [-c] -qName -d Name

Description

The **Isquedev** command displays the name of the queue stanza and associated attributes from the **/etc/qconfig** file.

Flags

Specifies colon output format for use by SMIT.

-d Name Specifies the Name variable of the device stanza that is displayed.

-q Name Specifies the Name variable of the queue containing the device stanza that is displayed.

Examples

1. To display device stanza dlp0 on the lp0 queue, type:

```
lsquedev -q lp0 -d dlp0
```

A listing similar to the following is displayed:

```
dlp0:
FILE = /dev/lp0
BACKEND = /usr/lib/lpd/piobe
```

2. To display device stanza dlp0 on the lp0 queue in colon format, type:

```
lsquedev -c -qlp0 -d dlp0
```

A listing similar to the following is displayed:

```
file:access:feed:header:trailer:backend:align
dlp0:/dev/lp0:read:never:never:never:/usr/lib/lpd/piobe:TRUE
```

Files

/usr/bin/lsquedevContains the Isquedev command./etc/qconfigContains the configuration file.

Related Information

The chquedev command, Isque command, mkquedev command, rmquedev command.

The **qconfig** file.

The **printf** subroutine.

Printing administration in the *Printers and printing*.

Printer-specific information, Installing support for additional printers, and Virtual printer definitions and attributes in the Printers and printing.

Print spooler in the Printers and printing.

Isresource Command

Purpose

Displays bus resources for available devices in the system and recommends attribute values for bus resource resolution.

Syntax

Isresource [-a | -r] [-d] -I Name

Description

The Isresource command writes a list of assigned bus resources to standard out, or determines if the bus resources for devices resolve.

The Isresource command lets you display the currently assigned values for the bus resource attributes for the device specified by the given device logical name (-I Name). Use the -a flag to display the currently assigned values for all bus resource attributes for all devices under the same parent bus as the specified device.

Use the -r flag to determine if the bus resources for the specified device are resolvable. In this case, the Isresource command checks all devices under the same parent bus as the specified device, including defined but not available devices, to see if their bus resource attributes are resolvable. The Isresource command produces no output if all attributes resolve. The Isresource command provides information depending on the type of conflict detected if any device's bus resources are unresolvable. In some cases, the **Isresource** command can provide you with information that leads to the resolution of the conflict.

The **Isresource** command identifies the device name, attribute name, and a suggested value for the attribute if a conflict results from an attribute that only a user can change. Setting the attribute to the suggested value should resolve the conflict. This may aid in the configuration of devices with attributes that can only a user can change. Such devices include adapter cards which use jumpers or switches on the card to select values.

In some cases, a conflict may be due to an attribute which the system can normally adjust at boot time but is prevented from doing so at run time because the device is in the Available state. In these situations, the Isresource command will indicate that the configuration will be resolved by rebooting the system.

It is possible that multiple user changeable attributes will be identified when unresolvable conflicts occur. These may be for the device specified by the given device logical name (-I Name) or for other devices in the system. All of the identified attributes will need to be changed to resolve the conflict. It may even be the case where user changeable attributes are identified and a reboot is indicated. In this case, all of the identified attributes will need to be changed and the system rebooted to resolve the conflicts.

Finally, **Isresource** may determine that the set of devices currently defined in the devices configuration database can not be resolved regardless of attributes being changed or the system rebooted. In this case, a list of the devices which could not be resolved is written to standard out. If the problem has resulted from a new device just being defined, that device should be removed, or the devices listed by Isresource should be removed. If the problem is not resolved by removing devices, there could be additional problems on the next reboot. This is because the order in which devices are resolved at boot time may differ from the order they are resolved by Isresource, resulting in a different set of unresolvable devices at boot time.

If the set of unresolvable devices at boot time should now include a device needed for booting, problems such as no console being configured or the system failing to boot could occur.

The following applies when Isresource is used to list currently assigned bus resource values (the -r flag is not specified).

The **TYPE** field in the output listing contains the following symbols:

- Bus Memory Address Values
- Bus Memory Address Values M
- 0 I/O Address Values
- Bus Interrupt Levels
- Ν Non-sharable Bus Interrupt Levels
- Α **DMA Arbitration Level**

The **S** column denotes shared attributes. These are attributes which are required to be set to the same value. They are grouped by the number specified in the column. All attributes with a 1 by them must be set to the same value, all attributes with a 2 by them must be set to the same value, and so on. In some cases, two or more interrupt attributes may be set to the same value but have no numbers in the S column indicating that they are shared. This is because the values are not required to be the same but just happen to be set to the same value because they could not be assigned their own unique values.

The G column denotes attributes in a group. These are a set of attributes whose values depend on each other. If one is changed to the next possible value, the rest of the attributes in the group must also be changed to the next possible value. Their groupings are indicated by the number specified in the column. All attributes with a 1 by them are in the same group, all attributes with a 2 by them are same group, and so on.

On some models, the interrupt value displayed may be followed by a value enclosed in parenthesis. This is not part of the interrupt value but serves to identify the interrupt controller to which the interrupt is associated. The identifier consists of a letter followed by a number, such as A0. The letter indicates the type of interrupt controller and the number distinguishes between multiple instances of that type of controller. There are two types of interrupt controllers that may be identified:

- Α Indicates an AT interrupt controller.
- В Indicates a non-AT interrupt controller.

Flags

Specifies that all allocated bus resource attributes for all devices connected to the same top parent bus as the device specified with the -I flag are to be displayed. This flag cannot be used with the -r flag.

-d Specifies that the attribute text descriptions are to be included in the output. (Lowercase L) Specifies the logical name of the device attributes to display. -I Name

Specifies to attempt to resolve all bus resources of all devices connected to the same top parent bus as the device specified with the -I flag. This will include all devices that are in the DEFINED state. The Isresource command will display any conflicts and advise the user on changeable values. No changes to the ODM database are made. This flag cannot be used with the -a flag.

Security

Access Control: Any User

Auditing Events: N/A

Examples

1. To list bus attributes for the token ring device, enter:

lsresource -1 tok0

The system displays a message similar to the following:

TYPE	DEVICE	ATTRIBUTE	S G	CURRENT VALUE
M	tok0	dma_bus_mem		0x003b2000 - 0x003f1fff
0	tok0	bus_io_addr		0x000086a0 - 0x000086af
N	tok0	bus_intr_lvl		3
Α	tok0	dma_lvl		7

2. To list bus attributes for all devices, enter:

lsresource -a -1 tok0

The system displays a message similar to the following:

TYPE	DEVICE	ATTRIBUTE	S G	CURRENT VALUE
TYPE M M M M M M M M M M M M M M M M	bus0 gda0 gda0 gda0 gda0 gda0 gda0 scsi0 scsi0 tok0 da0 siokta0 sioma0 ppa0 gda0 tok0 siokta0	bus_iocc_mem vram_start bus_mem_start dma1_start dma2_start dma3_start dma4_start bus_mem_addr dma_bus_mem dma_bus_mem bus_io_addr bus_int_lvl bus_intr_lvl bus_intr_lvl bus_intr_lvl bus_intr_lvl bus_intr_lvl dma_lvl dma_lvl dma_channel	S G 1	0x00fffff0 - 0x00ffffff 0x00400000 - 0x007fffff 0x000c0000 - 0x000c1fff 0x00800000 - 0x009fffff 0x00a00000 - 0x00bfffff 0x00c00000 - 0x00dfffff 0x01000000 - 0x011fffff 0x00000000 - 0x00301fff 0x00100000 - 0x00301fff 0x003b2000 - 0x00301fff 0x00000060 - 0x0000006f 0x00000050 - 0x0000006f 0x00000050 - 0x00000051 0x00000048 - 0x00000049 0x00000078 - 0x0000007a 0x00002110 - 0x0000211f 0x000086a0 - 0x000086af 1 (A0) 1 (A0) 13 (A0) 9 (A0) 14 (A0) 6 (A0) 3 (A0) 0
A A	scsi0 tok0	dma_lvl dma_lvl		4 7

3. To report the outcome of a resolution of device attributes, enter:

lsresource -r - d -l tok0

Depending on the outcome of the resolution, different messages may be displayed. The output below signifies to a user that the resolution can be successful if changes are made, i.e., the attributes are changed to the suggested values.

lsresource: The attribute(s) for some device(s) in the system could not be resolved. To resolve conflicts, attribute(s) need to be modified. A suggested value for each attribute is provided.

DEVICE	ATTRIBUTE	CURRENT	SUGGESTED	DESCRIPTION
ent1	bus_intr_lvl	11	5	Bus interrupt level
ent1	bus_mem_addr	0xc0000	0xc4000	Bus memory address
ent1	bus_io_addr	0x300	0x320	Bus I/O address
ent2	bus_intr_lvl	11	7	Bus interrupt level
ent2	bus mem addr	0xc0000	0xc8000	Bus memory address

Files

/usr/sbin/lsresource

Contains the Isresource command.

Isresponse Command

Purpose

Lists information about one or more responses. I you too

Syntax

Isresponse [-a] [-C | -I | -t | -d | -D delimiter] [-A] [-q] [-U] [-x] [-h] [-TV] [response 1[, response 2,...] : node_name]

Description

The Isresponse command lists the following information about defined responses:

FieldDescriptionResponseNameThe name of the response.NodeThe location of the response.ActionThe name of an action.

DaysOfWeek

The days of the week when the action can be run. **DaysOfWeek** and **TimeOfDay** together define the interval when the action can be run.

The values for the days can be separated by plus signs (+) or displayed as a range of days separated by a hyphen (-). Multiple **DaysOfWeek** values are separated by commas (,). The number of **DaysOfWeek** values must match the number of **TimeOfDay** values. The values for each day follow:

Sunday
 Monday
 Tuesday
 Wednesday
 Thursday
 Friday
 Saturday

TimeOfDay

The time range when **Action** can be run, consisting of the start time followed by the end time separated by a hyphen. **DaysOfWeek** and **TimeOfDay** together define the interval when the action can be run.

The time is in 24-hour format (HHMM), where the first two digits represent the hour and the last two digits represent the minutes. Multiple **TimeOfDay** values are separated by commas (,). The number of **DaysOfWeek** values must match the number of **TimeOfDay** values.

ActionScript The script or command to run for the action.

ReturnCode The expected return code for ActionScript.

CheckReturnCode Indicates whether the actual return code for ActionScript is compared to

its expected return code. The values are: y (yes) and n (no).

EventType The type of event that causes the action to be run: event, rearm event, or

StandardOut Indicates whether standard output is directed to the audit log. The values

are: y (yes) and n (no).

EnvironmentVars Indicates any environment variables that will be set before the action is

run.

UndefRes Indicates whether the action is to be run if a monitored resource becomes

undefined. The values are: **y** (yes) and **n** (no).

Locked Indicates whether the resource is locked or unlocked.

To get a list of all response names, run the Isresponse command alone without any response names specified. A list of all response names is returned. The default format in this case is tabular.

Specifying a node name after the response names limits the display to the responses defined on that node. List all of the responses on a node by specifying a colon (:) followed by the node name. The node name is a node within the management scope determined by the CT MANAGEMENT SCOPE environment variable. The management scope determines the list of nodes from which the responses are listed. For local scope, only responses on the local node are listed. Otherwise, the responses from all nodes within the domain are listed.

To see all the information about all response names, specify the -A flag with the Isresponse command. The -A flag causes all information about a response to be listed when no response names are specified. When all of the information about all responses is listed, the long format is the default.

When more than one response is specified, the response information is listed in the order in which the responses are entered.

Flags

- -a Specifies that this command applies to all nodes in the cluster. The cluster scope is determined by the CT MANAGEMENT SCOPE environment variable. If it is not set, first the management domain scope is chosen if it exists, then the peer domain scope is chosen if it exists, and then local scope is chosen, until the scope is valid for the command. The command will run once for the first valid scope found. For example, if both a management and peer domain exist, Isresponse -a with CT MANAGEMENT SCOPE not set will list the management domain. In this case, to list the peer domain, set CT_MANAGEMENT_SCOPE to 2.
- -C Displays the mkresponse command that can be used to create the response and one of its actions. If more than one response is specified, each mkresponse command appears on a separate line. This flag is ignored when no responses are specified. This flag overrides the -I flag.
- -1 Displays the response information on separate lines (long form).
- -t Displays the response information in separate columns (table form).
- -d Specifies delimiter-formatted output. The default delimiter is a colon (:). Use the -D flag if you wish to change the default delimiter.

-D delimiter

Specifies delimiter-formatted output that uses the specified delimiter. Use this flag to specify something other than the default, colon (:). For example, when the data to be displayed contains colons, use this flag to specify another delimiter of one or more characters.

- -A Displays all of the attributes of the response.
- -q Does not return an error when **response** does not exist.
- -U Indicates whether the resource is locked.

- -x Suppresses headers when printing.
- -h Writes the command's usage statement to standard output.
- **-T** Writes the command's trace messages to standard error. For your software service organization's use only.
- -V Writes the command's verbose messages to standard output.

Parameters

response1[,response2,...]

This parameter can be a response name or a substring of a response name. You can specify more than one response name. When it is a substring, any defined response name that contains the substring is listed.

node name

Specifies the node where the response is defined. If node name is not specified, the local node is used. node_name is a node within the scope determined by the CT_MANAGEMENT_SCOPE environment variable.

Security

The user needs read permission for the **IBM.EventResponse** resource class to run **Isresponse**. Permissions are specified in the access control list (ACL) file on the contacted system. See the RSCT: Administration Guide for details on the ACL file and how to modify it.

Exit Status

- The command ran successfully.
- 1 An error occurred with RMC.
- 2 An error occurred with a command-line interface script.
- 3 An incorrect flag was entered on the command line.
- 4 An incorrect parameter was entered on the command line.
- 5 An error occurred that was based on incorrect command-line input.

Environment Variables

CT_CONTACT

Determines the system where the session with the resource monitoring and control (RMC) daemon occurs. When CT CONTACT is set to a host name or IP address, the command contacts the RMC daemon on the specified host. If CT_CONTACT is not set, the command contacts the RMC daemon on the local system where the command is being run. The target of the RMC daemon session and the management scope determine the resource classes or resources that are processed.

CT IP AUTHENT

When the CT IP AUTHENT environment variable exists, the RMC daemon uses IP-based network authentication to contact the RMC daemon on the system that is specified by the IP address to which the CT CONTACT environment variable is set. CT IP AUTHENT only has meaning if CT_CONTACT is set to an IP address; it does not rely on the domain name system (DNS) service.

CT MANAGEMENT SCOPE

Determines the management scope that is used for the session with the RMC daemon in processing the resources of the event-response resource manager (ERRM). The management scope determines the set of possible target nodes where the resources can be processed. The valid values are:

- 0 Specifies local scope.
- 1 Specifies local scope.
- 2 Specifies peer domain scope.
- 3 Specifies management domain scope.

If this environment variable is not set, local scope is used.

Implementation Specifics

This command is part of the Reliable Scalable Cluster Technology (RSCT) fileset for AIX.

Standard Output

When the -h flag is specified, this command's usage statement is written to standard output. All verbose messages are written to standard output.

Standard Error

All trace messages are written to standard error.

Examples

1. To list all of the responses, run this command:

1sresponse

The output will look like this:

```
ResponseName
"E-mail root anytime"
"E-mail root first shift"
"Critical notifications"
"Generate SNMP trap"
```

2. To see which resources are locked, run this command:

```
1sresponse -U
```

The output will look like this:

```
ResponseName
                                                               Node
                                                                                   Locked
"Broadcast event on-shift" "nodeA"

"E-mail root off-shift" "nodeA"

"E-mail root anytime" "nodeA"

"Log event anytime" "nodeA"
                                                              "nodeA"
                                                                                   "No"
                                                                                   "No"
                                                                                   "No"
                                                                                   "No"
"Informational notifications" "nodeA"
"Warning notifications" "nodeA"
"Critical notifications" "nodeA"
"Generate SNMP trap" "nodeA"
                                                                                   "No"
                                                                                    "No"
                                                                                    "No"
                                                               "nodeA"
                                                                                    "No"
 "Generate SNMP trap"
```

3. To list general information about the response "Critical notifications", run this command:

```
Isresponse "Critical notifications"
```

The output will look like this:

```
ResponseName = "Critical notifications"
Node = "nodeA"
Action = "Log Critical Event"
DaysOfWeek = 1+2+7
= 0000-2400
ActionScript = "/usr/sbin/rsct/bin/logevent /tmp/criticalEvents"
ReturnCode = 0
CheckReturnCode = "y"
EventType = "b"
StandardOut
                 = "y"
EnvironmentVars = '"Env1=5", "Env=10"'
```

```
UndefRes
                = "n"
ResponseName = "Critical notifications"
              = "nodeA"
Node
            = "E-mail root"
Action
DaysOfWeek = 6+2,6+2,6+5
TimeOfDay = 1700-2400,0000-0800,0000-2400
ActionScript = "/usr/sbin/rsct/bin/notifyevent root"
                = 0
ReturnCode
CheckReturnCode = "y"
               = "b"
EventType
               = "y"
StandardOut
EnvironmentVars = ""
                = "n"
UndefRes
```

4. To list the command that would create the response "Critical notifications" along with one of its actions, run this command:

```
lsresponse -C "Critical notifications"
```

The output will look like this:

```
mkresponse -n "Log Critical Event" -d 1+2+7 -t 0000-2400 \
-s "usr/sbin/rsct/bin/logevent /tmp/criticalEvents" \
-e b -r 0 "Critical notifications"
```

5. To list all responses that have the string E-mail in their names, run this command:

```
lsresponse "E-mail"
```

The output will look like this:

```
ResponseName = "E-mail root anytime"
          = "E-mail root"
Action
ResponseName = "E-mail root first shift"
         = "E-mail root"
Action
```

Location

/usr/sbin/rsct/bin/lsresponse

Related Information

Books: RSCT: Administration Guide, for more information about ERRM operations

Commands: chresponse, Iscondresp, mkcondresp, mkresponse, rmresponse

Information Files: rmccli

Isrole Command

Purpose

Displays role attributes. This command applies only to AIX 4.2.1 and later.

Syntax

```
Isrole [ -c | -f ] [ -a List ] { ALL | Name [ ,Name ] ... }
```

Description

The Isrole command displays the role attributes. You can use this command to list all attributes of all the roles or all the attributes of specific roles. Since there is no default parameter, you must enter the ALL

keyword to see the attributes of all the roles. By default, the Isrole command displays all role attributes. To view selected attributes, use the -a List flag. If one or more attributes cannot be read, the Isrole command lists as much information as possible.

By default, the Isrole command lists each role's attributes on one line. It displays attribute information as Attribute=Value definitions, each separated by a blank space. To list the role attributes in stanza format, use the **-f** flag. To list the information as colon-separated records, use the **-c** flag.

You can use the Users application in Web-based System Manager (wsm) to change user characteristics. You could also use the System Management Interface Tool (SMIT) to run this command.

Flags

-a List Lists the attributes to display. The List variable can include any attribute defined in the chrole command and requires a blank space between attributes. If you specify an empty list, only the role names are displayed.

Displays the role attributes in colon-separated records, as follows: -C

```
# role: attribute1: attribute2: ...
 Role: value1:
                    value2:
```

-f Displays the output in stanzas, with each stanza identified by a role name. Each Attribute=Value pair is listed on a separate line:

Role:

attribute1=value attribute2=value attribute3=value

Security

Files Accessed:

Mode

/etc/security/roles

Examples

To display the role rolelist and groups of the role **ManageAllUsers** in colon format, enter:

lsrole -c -a rolelist groups ManageAllUsers

Information similar to the following appears:

```
# role: rolelist:groups
ManageAllUsers: ManagerBasicUser:security
```

Files

/etc/security/roles

Contains the attributes of roles.

Related Information

The chrole command, chuser command, Isuser command, mkrole command, mkuser command, rmrole command.

For more information about the identification and authentication of users, discretionary access control, the trusted computing base, and auditing, refer to the Security.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

Isrpdomain Command

Purpose

Displays peer domain information for the node.

Syntax

Isrpdomain [-o | -O] [-I | -t | -d | -D delimiter] [-x] [-h] [-TV] [peer_domain]

Description

The Isrpdomain command displays information about the peer domains that the node where the command runs belongs to. Use the command's flags and parameters to specify which information you want to display and how you want to display it. When you specify the name of a peer domain, the command displays information about that peer domain only. The -o and -O flags also limit the information this command displays. The -o flag displays information only about the online peer domain. The -O flag displays information only about peer domains that are offline.

By default, the **Isrpdomain** command displays information in table format (-t).

Some of the peer domain information that is displayed follows:

<u>Field</u>	Description
Name	The name of the peer domain
RSCTActiveVersion	The version of RSCT that is active in the peer domain
MixedVersions	Indicates whether more than one version of RSCT is active in the peer domain
TSPort	The topology services port number
GSPort	The group services port number
OpState	The current state of the peer domain

Flags

- -0 Displays information about the node's online peer domain.
- **-O** Displays information about peer domains that are offline for the node.
- -1 Displays the information on separate lines (long format).
- -t Displays the information in separate columns (table format). This is the default.
- Displays the information using delimiters. The default delimiter is a colon (:). Use the -D flag if you -d want to change the default delimiter.

-D delimiter

Displays the information using the specified delimiter. Use this flag to specify a delimiter other than the default colon (:) — when the information you want to display contains colons, for example. You can use this flag to specify a delimiter of one or more characters.

- -x Excludes the header (suppresses header printing).
- -h Writes the command's usage statement to standard output.

- -T Writes the command's trace messages to standard error. For your software service organization's
- -V Writes the command's verbose messages to standard output.

Parameters

peer domain

Specifies the name of the peer domain about which you want to display information. You can specify a peer domain name or a substring of a peer domain name for this parameter. If you specify a substring, the command displays information about any defined peer domain with a name that contains the substring.

Security

The user of the Isrpdomain command needs read permission for the IBM.PeerDomain resource class on the node on which the command runs. By default, root on any node in the peer domain has read and write access to this resource class through the configuration resource manager.

Exit Status

- 0 The command ran successfully.
- 1 An error occurred with RMC.
- An error occurred with a command-line interface script. 2
- 3 An incorrect flag was entered on the command line.
- 4 An incorrect parameter was entered on the command line.
- 5 An error occurred that was based on incorrect command-line input.
- 6 The peer domain definition does not exist.

Environment Variables

CT_CONTACT

Determines the system where the session with the resource monitoring and control (RMC) daemon occurs. When CT CONTACT is set to a host name or IP address, the command contacts the RMC daemon on the specified host. If CT_CONTACT is not set, the command contacts the RMC daemon on the local system where the command is being run. The target of the RMC daemon session and the management scope determine the resource classes or resources that are processed.

CT IP AUTHENT

When the CT_IP_AUTHENT environment variable exists, the RMC daemon uses IP-based network authentication to contact the RMC daemon on the system that is specified by the IP address to which the CT_CONTACT environment variable is set. CT_IP_AUTHENT only has meaning if CT_CONTACT is set to an IP address; it does not rely on the domain name system (DNS) service.

Restrictions

This command must be run on the node for which the peer domain information is requested.

Implementation Specifics

This command is part of the Reliable Scalable Cluster Technology (RSCT) fileset for AIX.

Standard Input

When the -f "-" or -F "-" flag is specified, this command reads one or more node names from standard input.

Standard Output

When the -h flag is specified, this command's usage statement is written to standard output. All verbose messages are written to standard output.

Standard Error

All trace messages are written to standard error.

Examples

1. To display general information about the peer domains to which **nodeA** belongs, run this command on nodeA:

1srpdomain

The output will look like this:

Name	OpState	RSCTActiveVersion	MixedVersions	TSPort	GSPort
App1Domain	0nline	2.4.7.1	No	12347	12348

2. To display general information about the peer domains to which nodeA belongs, with the default delimiter (but without the heading), run this command on **nodeA**:

```
1srpdomain -xd
```

The output will look like this:

ApplDomain:Online:2.4.7.1:No:12347:12348:

3. To display general information about the peer domains to which **nodeA** belongs, in long format, run this command on nodeA:

```
1srpdomain -1
```

The output will look like this:

= ApplDomain = Online OpState RSCTActiveVersion = 2.4.7.1 MixedVersions = No TSPort = 12347 GSPort = 12348

Location

/usr/sbin/rsct/bin/Isrpdomain

Related Information

Books: RSCT: Administration Guide, for information about peer domain operations

Commands: Isrpnode, mkrpdomain, preprpnode, rmrpdomain, startrpdomain, stoprpdomain

Information Files: rmccli, for general information about RMC-related commands

Isrpnode Command

Purpose

Displays information about one or more of the nodes that are defined in the online peer domain.

Syntax

Isrpnode [-o | -O | -L] [-i] [-I | -t | -d | -D delimiter] [-x] [-h] [-TV] [node_name]

Isrpnode -p peer_domain [-I | -t | -d | -D delimiter] [-x] [-h] [-TV]

Description

The **Isrpnode** command displays information about one or more of the nodes that are defined in the online peer domain. Use the command's flags and parameters to specify which information you want to display and how you want to display it. When you specify a node name, the command displays information about that node only. The **-o**, **-O**, and **-L** flags also limit the information this command displays. The **-o** flag displays information about nodes that are online. The **-O** flag displays information about nodes that are offline. The **-L** flag displays information about the local node, which is the node the command runs on.

By default, the **Isrpnode** command displays information in table format (-t).

Some of the node information that is displayed follows:

<u>Field</u> <u>Description</u>

Name The name of the node in the peer domain.

OpState The operational state of the node.

RSCTVersion The version of RSCT that is active in the node.

The following fields are displayed when you specify the -i flag:

NodeNum The node number used by topology services and group services. This

number is unique within the cluster.

NodelD The unique node identifier.

Flags

- **-o** Displays information about the nodes that are online in the peer domain.
- Displays information about the nodes that are offline in the peer domain.
- **-L** Displays information about the local node only, which is the node that the command runs on.
- -p peer_domain

Displays information about nodes defined in an *offline* peer domain that the local node belongs to. (By default, the **Isrpnode** command displays information about the nodes that are defined in the domain where you are currently *online*.) However, this information might not reflect changes that are made to the domain after the local node is taken offline, because an offline node might not have the latest configuration.

The -p flag ignores the CT CONTACT environment variable.

- -i Displays the node number and node ID for the node. The node number is used by topology services and group services and is unique within the cluster. The node ID is the unique node identifier.
- -I Displays the information on separate lines (long format).

- Displays the information in separate columns (table format). This is the default format. -t
- -d Displays the information using delimiters. The default delimiter is a colon (:). Use the -D flag if you want to change the default delimiter.

-D delimiter

Displays the information using the specified delimiter. Use this flag to specify a delimiter other than the default colon (:) — when the information you want to display contains colons, for example. You can use this flag to specify a delimiter of one or more characters.

- Excludes the header (suppresses header printing). -X
- -h Writes the command's usage statement to standard output.
- -T Writes the command's trace messages to standard error. For your software service organization's use only.
- -V Writes the command's verbose messages to standard output.

Parameters

node name

Specifies the name of the node about which you want to display information. You can specify a node name or a substring of a node name for this parameter. If you specify a substring, the command displays information about any defined node with a name that contains the substring.

Security

The user of the Isrpnode command needs read permission for the IBM.PeerNode resource class on the node this command runs on. By default, root on any node in the peer domain has read and write access to this resource class through the configuration resource manager.

Exit Status

- The command ran successfully.
- An error occurred with RMC.
- 2 An error occurred with a command-line interface script.
- 3 An incorrect flag was entered on the command line.
- 4 An incorrect parameter was entered on the command line.
- 5 An error occurred that was based on incorrect command-line input.

Environment Variables

CT_CONTACT

Determines the system where the session with the resource monitoring and control (RMC) daemon occurs. When CT CONTACT is set to a host name or IP address, the command contacts the RMC daemon on the specified host. If CT CONTACT is not set, the command contacts the RMC daemon on the local system where the command is being run. The target of the RMC daemon session and the management scope determine the resource classes or resources that are processed.

CT IP AUTHENT

When the CT IP AUTHENT environment variable exists, the RMC daemon uses IP-based network authentication to contact the RMC daemon on the system that is specified by the IP address to which the CT CONTACT environment variable is set. CT IP AUTHENT only has meaning if CT_CONTACT is set to an IP address; it does not rely on the domain name system (DNS) service.

Restrictions

This command must be run on a node that is online in the peer domain.

Implementation Specifics

This command is part of the Reliable Scalable Cluster Technology (RSCT) fileset for AIX.

Standard Input

When the -f "-" or -F "-" flag is specified, this command reads one or more node names from standard input.

Standard Output

When the -h flag is specified, this command's usage statement is written to standard output. All verbose messages are written to standard output.

Standard Error

All trace messages are written to standard error.

Examples

1. To display general information about the nodes in the online peer domain that **nodeA** belongs to, run this command on nodeA:

1srpnode

The output will look like this:

```
Name
        OpState RSCTVersion
nodeA Online 2.4.7.1 nodeB Online 2.4.7.1
nodeC Offline 2.4.7.1
```

2. To display general information about the nodes in the online peer domain that nodeA belongs to, with the default delimiter (but without the heading), run this command on **nodeA**:

```
1srpnode -xd
```

The output will look like this:

```
nodeA:Online:2.4.7.1:
nodeB:Online:2.4.7.1:
nodeC:Offline:2.4.7.1:
```

3. To display general information about the nodes in the online peer domain that **nodeA** belongs to, in long format, run this command on **nodeA**:

```
1srpnode -1
```

The output will look like this:

```
Name
          = nodeA
OpState = Online
RSCTVersion = 2.4.7.1
          = nodeB
Name
OpState = Online
RSCTVersion = 2.4.7.1
Name
         = nodeC
OpState = Offline
RSCTVersion = 2.4.7.1
```

4. To display general information about the nodes in the online peer domain that **nodeA** belongs to, including the node number and node ID, run this command on nodeA:

1srpnode -i

The output will look like this:

Name	OpState	RSCTVersion	NodeNum	NodeID
nodeA	Online	2.4.7.1	2	40a514bed9d82412
nodeB	Online	2.4.7.1	1	47fe57098f4ec4d9

Location

/usr/sbin/rsct/bin/lsrpnode

Related Information

Books: RSCT: Administration Guide, for information about peer domain operations

Commands: addrpnode, preprpnode, startrpnode, stoprpnode

Information Files: rmccli, for general information about RMC-related commands

Isrset Command

Purpose

Displays system rset contents.

Syntax

or

Isrset [-X] [-P] [-v | -o] -p pid

Description

The Isrset command displays information contained in rsets stored in the system registry or rsets attached to a process.

Flags

-f	Displays rset owner, group, and mode data.
-v	Verbose mode. Displays resources contained in the rset, rset owner, group and mode data.
-0	Displays only the online resources contained in the rset. The default is to display all resources.
-p <i>pid</i>	Displays the effective rset attached to this process.
-r rsetname	Displays the rset with this name in the system registry. The name consists of a namespace and an <i>rsname</i> separated by a "/" (slash). Both the <i>namespace</i> and <i>rsname</i> may contain up to 255 characters. See the rs_registername() service for additional information about character set limits of rset names.
-n namespace	Displays all rsets in this <i>namespace</i> in the system registry.
-a	Displays all rsets in the system registry.
-P	Displays the partition rset attached to the specified process.
-S	Displays the resources contained in this rset if it were to be scheduled with the -S hint with either the execrset or the attachrset command. The rset does not need to be an exclusive rset. This is to be contrasted with the attachrset and execrset commands, which require exclusive rsets to be specified with the -S flag.
-X	Prints all available characters of each user and group name instead of truncating to the first 8 characters.

Examples

1. To display all resources for all rsets in the system registry, type:

```
1srset -v -a
```

2. To display a summary of the effective rset attached to pid 28026, type:

```
1srset -p 28026
```

3. To display the online resources in the effective rset attached to pid 28026, type:

```
1srset -o -p 28026
```

4. To display all the resources in the effective rset attached to pid 28026, type:

```
lsrset -v -p 28026
```

5. To display online resources for all rsets in the system registry, type:

```
lsrset -a -o
```

6. To display all resources for all rsets in the system registry with expanded user and group name, type:

```
1srset -X -v -a
```

Files

/etc/bin/Isrset

Contains the Isrset command

Related Information

The attachrset, detachrset, execrset, mkrset, and rmrset commands.

Isrsrc Command

Purpose

Displays attributes and values for a resource or a resource class.

Syntax

To display the attributes and values for a resource:

Isrsrc [-s "selection_string"] [-a | -N { node_file | "-" }] [-A p | d | b] [-p property] [-I | -I | -t | -d -D delimiter] [-x] [-h] [-TV] [resource_class] [attr...]

[-TV] [resource_class]

To display the attributes and values for a resource class:

Isrsrc -c [-A p | d | b] [-p property] [-I | -i | -t | -d | -D delimiter] [-x] [-a] [-h] [-TV] resource_class [attr...]

Isrsrc -C domain_name... [-A p | d | b] [-p property] [-I | -i | -t | -d | -D delimiter] [-x] [-h] [-TV] resource_class [attr...]

To display a list of all of the resource classes:

Isrsrc

Description

The Isrsrc command displays the persistent and dynamic attributes and their values for a resource or a resource class.

Instead of specifying multiple node names in selection_string, you can use the -N node_file flag to indicate that the node names are in a file. Use -N "-" to read the node names from standard input.

When no attribute names are specified:

- only attributes that are defined as **public** are displayed. Use the **-p** flag to override this default.
- the -A p | d | b flag controls whether persistent attributes or dynamic attributes or both and their values — are displayed.

When one or more attribute names are specified, these names and their values are displayed in the order specified, provided that each of the specified attribute names is valid.

To display a list of the attributes and values for a resource class, specify the -c flag.

For best performance, specify either the -A p flag or only persistent attributes as parameters.

Specify the -r flag to display only the resource handles associated with the resources for the specified resource class.

To display a list of the attributes and values for a resource class, specify the -c flag.

By default, the resource attributes and values are displayed in long format. Use the -t, -d, or -D flag to display the resources in table format or delimiter-formatted output.

If Cluster Systems Management (CSM) is installed on your system, you can use CSM defined node groups as node name values to refer to more than one node. For information about working with CSM node groups and using the CSM nodegrp command, see the CSM: Administration Guide and the CSM: Command and Technical Reference.

The Isrsrc command does not list any attributes that have a datatype defined as ct none (Quantum, for example). RMC does not return attribute values for attributes that are defined as Quantum. To list attribute definitions, use the Isrsrcdef command.

Flags

Specifies that this command applies to all nodes in the cluster. The cluster scope is determined by the CT MANAGEMENT SCOPE environment variable. If it is not set, first the management domain scope is chosen if it exists, then the peer domain scope is chosen if it exists, and then local scope is chosen, until the scope is valid for the command. The command will run once for the first valid scope found. For example, if both a management and peer domain exist, Isrsrc -a with CT_MANAGEMENT_SCOPE not set will list the management domain. In this case, to list the peer domain, set CT MANAGEMENT SCOPE to 2.

-Apldlb

Specifies an attribute type. By default only persistent attributes are displayed. This flag can be used only when no attribute names are specified on the command line.

- Displays only persistent attributes. р
- d Displays only dynamic attributes.
- Displays both persistent and dynamic attributes.

For best performance, specify the -A p flag.

- Displays the attributes for the resource class. This flag overrides the **-r** flag.
- -C domain name...

Displays the class attributes of a globalized resource class on one or more RSCT peer domains that are defined on the management server. Globalized classes are used in peer domains and

management domains for resource classes that contain information about the domain. To display class attributes of a globalized resource class on all peer domains defined on the management server, use the -c flag with the -a flag instead of -C. The command returns the name of the peer domain in the form of an attribute ActivePeerDomain. This is not an actual attribute, but is presented as such to indicate which peer domain is being displayed.

-d Specifies delimiter-formatted output. The default delimiter is a colon (:). Use the -D flag if you want to change the default delimiter.

-D delimiter

Specifies delimiter-formatted output that uses the specified delimiter. Use this flag to specify something other than the default colon (:). An example is when the data to be displayed contains colons. Use this flag to specify a delimiter of one or more characters.

- -i Generates a template of resource_data_input_file that can then, after appropriate editing, be used as input to the mkrsrc command. The output is displayed in long (stanza) format. All required and optional attributes that can be used to define a resource are displayed. The attribute data type is displayed as the value in the attr=value pairs. It is suggested that when you use this flag, the output of the **Isrsrc** command be directed to a file. This flag overrides the -s and -A d flags.
- -1 Specifies long formatted output. Each attribute is displayed on a separate line. This is the default display format. If the Isrsrc command is issued with the -I flag, but without a resource class name, the -I flag is ignored when the command returns the list of defined resource class names.

-p property

Displays attributes with the specified property. By default, only public attributes are displayed. To display all of the attributes regardless of the property, use the -p 0 flag. Use this flag in conjunction with the -A flag when no attributes are specified on the command line.

Persistent attribute properties:

0x0001	read_only
0x0002	<pre>reqd_for_define (required)</pre>
0x0004	<pre>inval_for_define (not valid)</pre>
8000x0	<pre>option_for_define (optional)</pre>
0x0010	selectable
0x0020	public

Dynamic attribute properties:

0x0020 public

A decimal or hexadecimal value can be specified for the property. To display attributes and their values for all attributes that have one or more properties, "OR" the properties of interest together and then specify the "OR"ed value with the -p flag. For example, to display attributes and their values for all persistent attributes that are either reqd_for_define or option_for_define, enter: 1srsrc -p 0x0a

Displays the resource handles for the resources that match the specified selection string or all -r resources when no selection string is specified.

-s "selection string"

Specifies a selection string. All selection strings must be enclosed within either double or single quotation marks. If the selection string contains double quotation marks, enclose the entire selection string in single quotation marks. For example:

```
-s 'Name == "testing"'
-s 'Name ?= "test"'
```

Only persistent attributes may be listed in a selection string. For information on how to specify selection strings, see the RSCT: Administration Guide .

- -t Specifies table format. Each attribute is displayed in a separate column, with one resource per line.
- Suppresses header printing. **-x**
- -h Writes the command's usage statement to standard output.
- -T Writes the command's trace messages to standard error. For your software-service organization's use only.
- -V Writes the command's verbose messages to standard output.

Parameters

resource class

Specifies the name of the resource class with the resources that you want to display.

Specifies one or more attribute names. Both persistent and dynamic attribute names can be attr... specified to control which attributes are displayed and their order. Zero or more attributes can be specified. Attributes must be separated by spaces.

Security

The user needs read permission for the resource_class specified in Isrsrc to run Isrsrc. Permissions are specified in the access control list (ACL) file on the contacted system. See the RSCT: Administration Guide for information about the ACL file and how to modify it.

Exit Status

- The command has run successfully.
- An error occurred with RMC. 1
- 2 An error occurred with the command-line interface (CLI) script.
- 3 An incorrect flag was specified on the command line.
- 4 An incorrect parameter was specified on the command line.
- 5 An error occurred with RMC that was based on incorrect command-line input.

Environment Variables

CT CONTACT

When the CT CONTACT environment variable is set to a host name or IP address, the command contacts the Resource Monitoring and Control (RMC) daemon on the specified host. If the environment variable is not set, the command contacts the RMC daemon on the local system where the command is being run. The resource class or resources that are displayed or modified by the command are located on the system to which the connection is established.

CT IP AUTHENT

When the CT_IP_AUTHENT environment variable exists, the RMC daemon uses IP-based network authentication to contact the RMC daemon on the system that is specified by the IP address to which the CT CONTACT environment variable is set. CT IP AUTHENT only has meaning if CT CONTACT is set to an IP address; it does not rely on the domain name system (DNS) service.

CT MANAGEMENT SCOPE

Determines the management scope that is used for the session with the RMC daemon to monitor

and control the resources and resource classes. The management scope determines the set of possible target nodes where the resources and resource classes can be monitored and controlled. The valid values are:

- Specifies local scope.
- 1 Specifies *local* scope.
- 2 Specifies peer domain scope.
- 3 Specifies management domain scope.

If this environment variable is not set, local scope is used.

Implementation Specifics

This command is part of the Reliable Scalable Cluster Technology (RSCT) fileset for AIX.

Standard Output

When the -h flag is specified, this command's usage statement is written to standard output. All verbose messages are written to standard output.

Standard Error

All trace messages are written to standard error.

Examples

1. To list the names of all of the resource classes, enter:

```
1srsrc
```

The output will look like this:

```
class name
"IBM. Association"
"IBM.Condition"
'IBM.EventResponse"
"IBM.Host"
"IBM.Ethernet"
"IBM. TokenRing"
```

2. To list the persistent attributes for resource IBM. Host that have 4 processors, enter:

```
lsrsrc -s "NumProcessors == 4" -A p -p 0 IBM.Host
```

The output will look like this:

```
Resource Persistent Attributes for: IBM.Host
resource 1:
                     = "c175n05.ppd.pok.ibm.com"
       ResourceHandle = "0x4008 0x0001 0x00000000 0x0069684c 0x0d7f55d5 0x0c32fde3"
       Variety = 1
       NodeList
                     = {1}
       NumProcessors = 4
       RealMemSize
                     = 1073696768
```

3. To list the public dynamic attributes for resource IBM. Host on node 1, enter:

```
lsrsrc -s 'Name == "c175n05.ppd.pok.ibm.com"' -A d IBM.Host
```

The output will look like this:

```
Resource Dynamic Attributes for: IBM.Host
resource 1:
           ProcRunQueue = 1.03347987093142
ProcSwapQueue = 1.00548852941929
TotalPgSpSize = 65536
```

```
TotalPgSpFree = 65131
PctTotalPgSpUsed = 0.61798095703125
PctTotalPgSpFree = 99.3820190429688
PctTotalTimeIdle = 0
PctTotalTimeWait = 51.5244382399734
PctTotalTimeKernel = 12.8246006482343
PctTotalTimeKernel = 35.6509611117922
PctRealMemFree = 66
PctRealMemFramesFree = 173361
VMPgInRate = 0
VMPgGutRate = 0
VMPgFaultRate = 0
```

4. To list the Name, Variety, and ProcessorType attributes for the IBM.Processor resource on all the online nodes, enter:

lsrsrc IBM.Processor Name Variety ProcessorType

The output will look like this:

```
Resource Persistent Attributes for: IBM. Processor
resource 1:
                     = "proc3"
       Name
       Variety = 1
       ProcessorType = "PowerPC 604"
resource 2:
                     = "proc2"
       Name = "p Variety = 1
       Name
       ProcessorType = "PowerPC_604"
resource 3:
       Name = "proc1"
Variety = 1
       ProcessorType = "PowerPC 604"
resource 4:
                     = "proc0"
                  = 1
        Variety
       ProcessorType = "PowerPC 604"
```

5. To list both the persistent and dynamic attributes for the resource class IBM.Condition, enter:

```
lsrsrc -c -A b -p 0 IBM.Condition
```

The output will look like this:

```
Resource Class Persistent and Dynamic Attributes for: IBM.Condition resource 1:

ResourceType = 0

Variety = 0
```

6. To list the nodes in the cluster that have at least four processors, using the /tmp/common/node_file file:

The output will look like this:

```
Resource Persistent Attributes for IBM.Host
Name NumProcessors
"node1.ibm.com" 4
"node2.ibm.com" 4
```

Location

/usr/sbin/rsct/bin/lsrsrc

Related Information

Books:

- · CSM: Administration Guide, for information about node groups
- · CSM: Command and Technical Reference, for information about the nodegrp command
- RSCT: Administration Guide, for information about RMC operations and about how to use expressions and selection strings

Commands: Isrsrcdef, mkrsrc, nodegrp

Information Files: rmccli, for general information about RMC commands

Isrsrcdef Command

Purpose

Displays definition information for a resource or a resource class.

Syntax

For a resource...

To display the definition:

```
| Isrsrcdef [-p property] [-e] [-s] [ -l | -i | -t | -d | -D delimiter ] [-x] [-h] [-TV] resource_class [attr...]
```

To display the persistent attribute definitions:

Isrsrcdef –A p [**–p** property] [**–e**] [**–l** | **–i** | **–t** | **–d** | **–D** delimiter] [**–x**] [**–h**] [**–TV**] resource_class [attr...]

To display the dynamic attribute definitions:

Isrsrcdef -A d [-p property] [-e] [-s] $[-l \mid -i \mid -t \mid -d \mid -D \text{ delimiter}]$ [-x] [-h] [-TV] resource_class [attr...]

For a resource class...

To display the definition:

| Isrsrcdef -c [-p property] [-e] [-s] [-l | -i | -t | -d | -D delimiter] [-x] [-h] [-TV] resource_class [attr...]

To display the persistent attribute definitions:

Isrsrcdef -c -A p [-p property] [-e] [-s] [-I | -I | -I | -D delimiter] [-x] [-h] [-TV] resource_class [attr...]

To display the dynamic attribute definitions:

Isrsrcdef -c -A d [-p property] [-e] [-s] [-I | -i | -t | -d | -D delimiter] [-x] [-h] [-TV] resource_class [attr...]

To display a list of all of the resource class names:

Isrsrcdef

Description

The **Isrsrcdef** command displays the definition of a resource or a resource class or the persistent or dynamic attribute definitions of a resource or a resource class. By default:

- if no attr parameters are specified on the command line, this command displays the definitions for public attributes. To override this default, use the -p flag or specify the name of the attribute you want to display.
- this command does not display attribute descriptions. To display attribute definitions and descriptions, specify the -e flag.

Flags

-Apld

Specifies the attribute type. You can display either persistent or dynamic attribute definitions. Use this flag with the -c flag to display the persistent or dynamic attribute definitions of a resource class.

- р Displays only persistent attributes
- d Displays only dynamic attributes
- Displays the definition of a resource class definition. To display the persistent attribute definitions -c for a resource class, specify this flag with the -A p flag. To display the dynamic attribute definitions for a resource class, specify this flag with the -A d flag.
- -d Specifies delimiter-formatted output. The default delimiter is a colon (:). Use the -D flag to change the default delimiter.

-D delimiter

Specifies delimiter-formatted output that uses the specified delimiter. Use this flag to specify something other than the default colon (:). An example is when the data to be displayed contains colons. Use this flag to specify a delimiter of one or more characters.

- Specifies expanded format. By default, the descriptions of the definitons are not displayed. Specify -e this flag to display the definitions and the descriptions.
- −i Generates a template of resource_data_input_file that can then, after appropriate editing, be used as input to the mkrsrc command. The output is displayed in long (stanza) format. All required and optional attributes that can be used to define a resource are displayed. The attribute data type is displayed as the value in the attr=value pairs. It is suggested that when you use this flag, the output of the **Isrsrcdef** command be directed to a file. This flag overrides the **-s** and **-A d** flags.
- -1 Specifies "long" format — one entry per line. This is the default display format. If the Isrsrcdef -I command is issued without a resource class name, this flag is ignored when the command returns the list of defined resource class names.

-p property

Displays attribute definitions for attributes with the specified property. By default, only the definitions for public attributes are displayed. To display all attribute definitions regardless of the property, use the -p 0 flag.

Persistent attribute properties:

0x0001 read only

0x0002reqd_for_define (required)0x0004inval_for_define (not valid)0x0008option_for_define (optional)

0x0010 selectable 0x0020 public

Dynamic attribute properties:

0x0020 public

A decimal or hexadecimal value can be specified for the property. To request the attribute definitions for all attributes that have one or more properties, "OR" the properties of interest together and then specify the "OR"ed value with the **-p** flag. For example, to request the attribute definitions for all persistent attributes that are either **reqd_for_define** or **option_for_define**, enter: lsrsrcdef -p 0x0a

- **-s** Displays the structured data definition. Specify this flag for the structured data definition to be expanded so that each element definition of the structured data attributes is displayed.
- -t Specifies table format. Each attribute is displayed in a separate column, with one resource per line.
- Suppresses header printing.
- **-h** Writes the command's usage statement to standard output.
- **-T** Writes the command's trace messages to standard error. For your software-service organization's use only.
- **-V** Writes the command's verbose messages to standard output.

Parameters

resource class

Specifies the name of the resource class with the attribute definitions you want to display.

attr If a resource_class parameter is specified, zero or more attribute names can be specified. If no attr parameter is specified, the definition for all of the attributes for the resource are displayed. Specify individual attribute names to control which attributes are displayed and their order. Specify only persistent attribute names when the -A p flag is used. Specify only dynamic attribute names when the -A d flag is used. Attributes must be separated by spaces.

Security

The user needs write permission for the *resource_class* specified in **Isrsrcdef** to run **Isrsrcdef**. Permissions are specified in the access control list (ACL) file on the contacted system. See *RSCT*: *Administration Guide* for information about the ACL file and how to modify it.

Exit Status

- **0** The command has run successfully.
- 1 An error occurred with RMC.
- 2 An error occurred with the command-line interface (CLI) script.
- 3 An incorrect flag was specified on the command line.
- 4 An incorrect parameter was specified on the command line.
- 5 An error occurred with RMC that was based on incorrect command-line input.

Environment Variables

CT CONTACT

When the CT CONTACT environment variable is set to a host name or IP address, the command contacts the Resource Monitoring and Control (RMC) daemon on the specified host. If the environment variable is not set, the command contacts the RMC daemon on the local system where the command is being run. The resource class or resources that are displayed or modified by the command are located on the system to which the connection is established.

CT IP AUTHENT

When the CT_IP_AUTHENT environment variable exists, the RMC daemon uses IP-based network authentication to contact the RMC daemon on the system that is specified by the IP address to which the CT_CONTACT environment variable is set. CT_IP_AUTHENT only has meaning if CT_CONTACT is set to an IP address; it does not rely on the domain name system (DNS) service.

CT_MANAGEMENT_SCOPE

Determines the management scope that is used for the session with the RMC daemon to monitor and control the resources and resource classes. The management scope determines the set of possible target nodes where the resources and resource classes can be monitored and controlled. The valid values are:

- Specifies local scope.
- 1 Specifies local scope.
- Specifies peer domain scope.
- 3 Specifies management domain scope.

If this environment variable is *not* set, *local* scope is used.

Implementation Specifics

This command is part of the Reliable Scalable Cluster Technology (RSCT) fileset for AIX.

Standard Output

When the -h flag is specified, this command's usage statement is written to standard output. All verbose messages are written to standard output.

Standard Error

All trace messages are written to standard error.

Examples

1. To display the names of all of the resource classes defined on the system, enter:

1srsrcdef

The output will look like this:

```
class name
"IBM. ATMDevice"
"IBM. Association"
"IBM.AuditLoa"
"IBM.AuditLogTemplate"
"IBM.Condition"
"IBM.EthernetDevice"
"IBM.EventResponse"
```

2. To display the resource class definitions for resource IBM.Host, enter:

```
lsrsrcdef -c IBM.Host
```

The output will look like this:

```
Resource Class Definition for: IBM.Host
resource class 1:
     = "IBM.Host"
      class name
      class_dattr_count = 3
      class action count = 0
      pattr_count = 6
      dattr count
      action count
                  = 0
      error count
                    = 0
      rsrc_mgr_count = 1
rsrc_mgrs 1:
      mgr name = "IBM.HostRM"
      first key = 1
      last key = 1
```

3. To display the resource class persistent attribute definitions for resource IBM.Host, enter:

```
lsrsrcdef -c -A p -p 0 IBM.Host
```

The output will look like this:

```
Resource Class Persistent Attribute Definitions for: IBM.Host
attribute 1:
                                 = "Variety"
        program name
                                 = ""
        display_name
                                 = ""
       group_name
properties
description
                               = {"read_only","inval_for_define"}
                               = 1111
        attribute_id
                               = 0
       group_id data_type
                               = 255
                                = "uint32"
        variety_list
                               = {{1..1}}
       variety_count
                                 = 1
        default_value
                                 = 0
```

4. To display the resource persistent attribute definitions and descriptions for resource IBM.Host, enter:

```
lsrsrcdef -A p -p 0 -e IBM.Host
```

The output will look like this:

```
Resource Persistent Attribute Definitions for: IBM.Host
attribute 1:
                                      program name
                                                                                                                            = "Name"
                                     as returned by command."
                                   = ""
                                      default value
attribute 2:
                                     program_name
display_name
group_name
properties
= "Resource |
= "Internal" |
= 
                                                                                                                             = "ResourceHandle"
                                      program_name
                                                                                                                             = "Resource Handle"
                                                                                                                             = {"read only", "inval for define", "selectable"}
                                      properties
                                                                                                                              = "A globally unique handle that identifies the host.
                                      description
                                                                                                                                              Every resource is assigned a resource handle,
```

```
which is used internally for identifying and locating each resource. The resource handle
                              is fixed in size and avoids the problems of
                              name space collisions across different types
                              of resources."
       attribute 3:
       program_name = "Variety"
display_name = "Variety"
group_name = "Internal"
```

5. To display the public dynamic attributes for resource IBM. Host, enter:

lsrsrcdef -A d IBM.Host

The output will look like this:

```
Resource Dynamic Attribute Definitions for: IBM.Host
attribute 1:
            program_name = "ProcRunQueue"
display_name = ""
group_name = ""
properties = {"public"}
description = ""
attribute_id = 1
group_id = 1
data_type = "float64"
variable_type = 0
variety_list = {{1..1}}
variety_count = 1
init_value = 0
min_value = 0
max_value = 100
expression_description = ""
                                                       = "ProcRunQueue"
              program name
              expression_description = ""
              rearm_expression = "ProcRunQueue < 50"
rearm_description = ""
PTX name = ""
              PTX name
attribute 2:
```

Location

/usr/sbin/rsct/bin/lsrsrcdef

Related Information

Books: RSCT: Administration Guide, for information about RMC operations

Commands: Isrsrc, mkrsrc

Information Files:

- resource_data_input
- · rmccli, for general information about RMC commands

Issavevg Command

Purpose

Lists or restores the contents of a volume group backup on a specified media.

Syntax

Issavevg [-b blocks] [-f device] [-a] [-c] [-l] [-n] [-r] [-s] [-d path] [-B] [-D] [-L] [-V] [
file list]

Description

The **Issavevg** command lists the contents of a volume group backup from tape, file, CD-ROM, or other source and can be used to restore files from a valid backup source. The **Issavevg** command also works for multi-volume backups such as multiple CDs, DVDs, USB disks, or tapes.

The **Issavevg -r** and **restorevgfiles** commands perform identical operations and should be considered interchangeable.

Flags

-a	Verifies the physical block size of the tape backup, as specified by the -b block flag. You may
	need to alter the block size if necessary to read the backup. The -a flag is valid only when a

tape backup is used.

-b blocks Specifies the number of 512-byte blocks to read in a single input operation, as defined by the

blocks parameter. If the blocks parameter is not specified, the number of blocks read will

default to 100.

-B Prints the volume group backup log to **stdout**.

This flag will display the past 256 backups (roughly). The log is in alog format and is kept in /var/adm/ras/vgbackuplog. Each line of the log is a semicolon-separated list of the file or device name, the command used to make backup, date, shrink size, full size of the backup, and recommended maintenance or technology level (if any).

Note: The shrink size is the size of the data on all filesystems. The full size is total size of

each filesystem (unused + data).

-c Produces colon-separated output. This flag only works with the -I and -L flags.

-d path Specifies the directory path to which the files will be restored, as defined by the path

parameter. If the **-d** parameter is not used, the current working directory is used. This can be a problem if the current working directory is root. We recommend writing to a temporary folder

instead of to root.

-D Produces debug output.

-f device Specifies the type of device containing the backup (file, tape, CD-ROM, or other source) as

defined by the device parameter. When -f is not specified, device will default to /dev/rmt0.

Displays useful information about a volume group backup.

This flag requires the **-f** device flag. This flag causes **Issavevg** to display information such as volume group, date and time backup was made, uname output from backed up system, oslevel, recommended maintenance or technology level, backup size in megabytes, and backup shrink size in megabytes. The shrink size is the size of the data on all filesystems. The full size is the total size of each filesystem (unused + data). The **-I** flag also displays the logical volume and filesystem information of the backed up volume group, equivalent to

running "Isvg -I vgname".

-L Displays lpp fileset information about a **mksysb** backup only.

This flag requires the **-f** device flag and displays the equivalent information to that produced by invoking "**Islpp -I**" on the running backed up system. This flag does not produce output about

any volume group backup other than that produced by **mksysb**.

-n Does not restore ACLs, PCLs, or extended attributes

-1

Specifies to restore the backup files, as defined by the file-list parameter. If the file-list -r parameter is not specified, then all files in the backup will be restored. If the -r flag is not

used, then executing the Issavevg command only lists the files in the specified backup.

Specifies that the backup source is a user volume group and not rootvg.

Verifies a tape backup. -V

> This flag requires the -f device flag and works for tape devices only. The -V flag causes Issavevg to verify the readability of the header of each file on the volume group backup and print any errors that occur to stderr.

Parameters

file_list

Identifies the list of files to be restored. This parameter is used only when the -r flag is specified. The full path of the files relative to the current directory should be specified in the space-separated list. All files in the specified directory will be restored unless otherwise directed. If you are restoring all files in a directory, we recommend writing to a temporary folder instead of to root.

Examples

- 1. To list the contents of the system backup located on the default device /dev/rmt0, enter:
- 2. To list the contents of the system backup located on device /dev/cd1, enter:

lssavevg -f /dev/cd1

3. To list the contents of the system backup located on device /dev/cd1, which is a user volume group that is not rootvg, enter:

lssavevg -f /dev/cd1 -s

4. To restore /etc/filesystems from the system backup located on device /dev/cd1, enter:

lssavevg -f /dev/cd1 -r ./etc/filesystems

5. To restore all files in the /myfs/test directory of the non-rootyg backup, which is located on device /dev/cd1, and write the restored files to /data/myfiles, enter:

```
lssavevg -f /dev/cdl -r -s -d /data/myfiles ./myfs/test
```

6. To display colon separated lpp information about a mksysb backup tape located on /dev/rmt0, enter the following:

```
1smksysb -Lc -f /dev/rmt0
```

7. To display the volume group backup log to **stdout**, enter:

1ssavevg -B

8. To list volume group and general backup data about a backup located at /tmp/mybackup, enter: lssavevg -l -f /tmp/mybackup

9. To verify the readability of each header on a volume group backup tape in /dev/rmt0, enter: lsmksysb -V -f /dev/rmt0

10. To list the contents of the system backup located on device /dev/usbms0, use the following command:

lssavevg -f /dev/usbms0

Files

/usr/bin/Issavevg

Contains the Issavevg command

Related Information

The restorevgfiles command.

Issec Command

Purpose

Lists attributes in the security stanza files.

Syntax

Issec [-c] [-f File] [-s Stanza] [-a Attribute ...]

Description

The Issec command lists attributes stored in the security configuration stanza files. The following security configuration files contain attributes that you can specify with the Attribute parameter:

- /etc/security/environ
- /etc/security/group
- · /etc/security/audit/hosts
- /etc/security/lastlog
- · /etc/security/limits
- /etc/security/login.cfg
- · /usr/lib/security/mkuser.default
- /etc/security/passwd
- /etc/security/portlog
- /etc/security/roles
- /etc/security/smitacl.user
- /etc/security/smitacl.group
- /etc/security/user
- /etc/security/user.roles

When listing attributes in the /etc/security/environ, /etc/security/lastlog, /etc/security/limits, /etc/security/passwd, and /etc/security/user files, the stanza name specified by the Stanza parameter must be either a valid user name or default. When listing attributes in the /etc/security/group file, the stanza name specified by the Stanza parameter must be either a valid group name or default. When listing attributes in the /usr/lib/security/mkuser.default file, the Stanza parameter must be either admin or user. When listing attributes in the /etc/security/portlog file, the Stanza parameter must be a valid port name. When listing attributes in the /etc/security/login.cfg file, the Stanza parameter must be either a valid port name, a method name, or the usw attribute.

You cannot list the password attribute of the /etc/security/passwd file with the Issec command.

Only the root user or a user with PasswdAdmin authorization can list the lastupdate and flags attributes for administrative users.

Flags

-0 Specifies that the output should be in colon-separated format.

-f File Specifies the name of the stanza file to list. -s Stanza Specifies the name of the stanza to list.

-a Attribute Specifies the attribute to list.

Security

Access Control: This command grants execute access only to the root user and the security group. The command has the trusted computing base attribute and runs the setuid subroutine for the root user to access the security databases.

Files Accessed:

Mode	File
r	/etc/security/environ
r	/etc/security/group
r	/etc/security/audit/hosts
r	/etc/security/lastlog
r	/etc/security/limits
r	/etc/security/login.cfg
r	/usr/lib/security/mkuser.default
r	/etc/security/passwd
r	/etc/security/portlog
r	/etc/security/roles
r	/etc/security/smitacl.user
r	/etc/security/smitacl.group
r	/etc/security/user
r	/etc/security/user.roles

Examples

1. To list the number of unsuccessful login attempts by the root user since the last successful login of the root user, enter:

```
lssec -f /etc/security/lastlog -s root -a unsuccessful login count
```

The system displays the result as follows:

```
root unsuccessful login count=15
```

2. To list the times that logins are allowed on the /dev/tty2 port, enter:

```
lssec -f /etc/security/login.cfg -s /dev/tty2 -a logintimes
```

The system displays the result as follows:

```
/dev/tty0 logintimes=!january1,!july4,!december25
```

- 3. To list the default setting for the tpath attribute and the ttys attribute in colon format,
- 4. enter:

```
lssec -c -f /etc/security/user -s default -a tpath -a ttys
```

The system displays the result as follows:

```
#name:tpath:ttys
default:nosak:ALL
```

Files

/usr/bin/lssec	Specifies the path to the Issec command.
/etc/security/environ	Contains the environment attributes of users.
/etc/security/group	Contains extended attributes of groups.
/etc/security/audit/hosts	Contains host and processor IDs.
/etc/security/lastlog	Defines the last login attributes for users.
/etc/security/limits	Defines resource quotas and limits for each user.
/etc/security/login.cfg	Contains port configuration information.

/usr/lib/security/mkuser.default Contains the defaults values for new users.

/etc/security/passwd Contains password information.

/etc/security/portlog Contains unsuccessful login attempt information for each port.

 /etc/security/roles
 Contains a list of valid roles.

 /etc/security/smitacl.user
 Contains user ACL definitions.

 /etc/security/smitacl.group
 Contains group ACL definitions.

/etc/security/user Contains the extended attributes of users.
/etc/security/user.roles Contains a list of roles for each user.

Related Information

The **chgroup** command, **chsec** command, **chuser** command, **grpck** command, **login** command, **lsgroup** command, **lsuser** command, **mkgroup** command, **mkuser** command, **passwd** command, **pwdck** command, **rmgroup** command, **rmuser** command, **su** command, **usrck** command.

The **getgroupattr** subroutine, **getportattr** subroutine, **getuserattr** subroutine, **getuserpw** subroutine, **putgroupattr** subroutine, **putgroupattr** subroutine, **putuserpw** subroutine.

List of Security and Auditing Subroutines in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs.

Issensor Command

Purpose

Displays the sensors that are defined to the resource monitoring and control (RMC) subsystem.

Syntax

Issensor [-a | -n host1[,host2...] | -N { node_file | "-" }] [-h] [-v | -V] [-A | sensor_name1 [sensor_name2...]]

Description

The **Issensor** command displays the attributes of one or more sensors. If you don't specify any *name* parameters, the **Issensor** command lists the names of all of the sensors. Use the **-A** flag to list all of the sensors and all of their attributes and values.

Using **Issensor** sensor_name or **Issensor** -A causes the sensor command to run. The sensor command is the command or script that is defined to set the sensor attribute values. It is specified using the **mksensor** command.

The **Issensor** command lists the following information about defined sensors:

Field	Description
Name	The name of the sensor.
Command	The command that is run to update the sensor attributes
ConfigChanged	Information about changes to access or to persistent attributes
ControlFlags	Indicates whether any special handling is required for this sensor
Description	This field is not used
ErrorExitValue	Indicates how the exit value is interpreted by the sensor resource manager

The exit code from the command that is running

ExitValue

Float32 The type **float32** attribute for this sensor resource Float64 The type **float64** attribute for this sensor resource Int32 The type int32 attribute for this sensor resource Int64 The type int64 attribute for this sensor resource

NodeNameList The name of the node where the sensor resource is defined

RefreshInterval The interval in seconds in which the sensor attribute values are updated

by running the sensor command

SavedData A specific output string from the command

SD Contains all dynamic resource attributes except ConfigChanged,

Quantum, and ExitValue as its elements

String The type string attribute for this sensor resource Uint32 The type **uint32** attribute for this sensor resource Uint64 The type **uint64** attribute for this sensor resource

UserName The user ID that is used when run the sensor command is run

The **Issensor** command runs on any node. If you want **Issensor** to run on all of the nodes in a domain, use the -a flag. If you want Issensor to run on a subset of nodes in a domain, use the -n flag.

Flags

- Lists sensors that match the specified name on all nodes in the domain. The CT MANAGEMENT SCOPE environment variable determines the cluster scope. If CT MANAGEMENT SCOPE is not set, first the management domain scope is chosen if it exists, then the peer domain scope is chosen if it exists, and then local scope is chosen, until the scope is valid for the command. The command will run once for the first valid scope found. For example, if both a management domain and a peer domain exist, Issensor -a with CT_MANAGEMENT_SCOPE not set will run in the management domain. In this case, to run in the peer domain, set CT MANAGEMENT SCOPE to 2.
- -A Displays all of the sensors with their attributes and values.
- **-n** host1[,host2...]

Specifies the node from which the sensor should be listed. By default, the sensor is listed from the local node. This flag is only appropriate in a management domain or a peer domain.

-N {node file | "-"}

Specifies a file or standard input listing the nodes on which the sensor must be removed. This flag is only appropriate in a Cluster Systems Management (CSM) or a peer domain cluster.

- -h Writes the command's usage statement to standard output.
- -v | -V

Writes the command's verbose messages to standard output.

Parameters

sensor name1 [sensor name2...]

Specifies the names of one or more sensors to display.

Security

The user needs read permission for the IBM.Sensor resource class in order to run Issensor. Permissions are specified in the access control list (ACL) file on the contacted system. See the RSCT: Administration Guide for details on the ACL file and how to modify it.

Exit Status

- 0 The command has run successfully.
- 1 An incorrect combination of flags and parameters has been entered.
- 6 No sensor resources were found.
- n Based on other errors that can be returned by the RMC subsystem.

Environment Variables

CT CONTACT

When the CT CONTACT environment variable is set to a host name or IP address, the command contacts the resource monitoring and control (RMC) daemon on the specified host. If this environment variable is not set, the command contacts the RMC daemon on the local system where the command is being run. The resource class or resources that are displayed or modified by the command are located on the system to which the connection is established.

CT IP AUTHENT

When the CT_IP_AUTHENT environment variable exists, the RMC daemon uses IP-based network authentication to contact the RMC daemon on the system that is specified by the IP address to which the CT CONTACT environment variable is set. CT IP AUTHENT only has meaning if CT_CONTACT is set to an IP address; it does not rely on the domain name system (DNS) service.

CT_MANAGEMENT_SCOPE

Determines the management scope that is used for the session with the RMC daemon to monitor and control the resources and resource classes. The management scope determines the set of possible target nodes where the resources and resource classes can be monitored and controlled.

The valid values are:

- **0** Specifies *local* scope.
- 1 Specifies *local* scope.
- 2 Specifies peer domain scope.
- 3 Specifies management domain scope.

If this environment variable is *not* set, *local* scope is used.

Implementation Specifics

This command is part of the Reliable Scalable Cluster Technology (RSCT) fileset for AIX.

Examples

1. To list the names of all of the sensors, enter:

1ssensor

The output will look like this:

sensor1 sensor2

sensor3

2. To list the names and attributes of all sensors, enter:

1ssensor -A

The output will look like this:

```
Name = sensor1
ActivePeerDomain =
Command = /usr/local/bin/sensorcmd1
ConfigChanged = 0
ControlFlags = 1
Description =
ErrorExitValue = 1
ExitValue = 0
Float32 = 1.06381e+06
Float64 = 1.06381e+06
Int32 = 1063814
Int64 = 1063814
NodeNameList = {somenode.pok.ibm.com}
RefreshInterval = 60
SavedData = Last SavedData
SD = [string from sensor1,1063814,1063814,1063814,1.06381e+06,1.06381e+06]
String = string from sensor1
Uint32 = 1063814
Uint64 = 1063814
UserName = root
_____
Name = CFMRootModTime
ActivePeerDomain =
Command = /opt/csm/csmbin/mtime/cfmroot
ConfigChanged = 0
ControlFlags = 0
Description =
ErrorExitValue = 1
ExitValue = 0
Float32 = 0
Float64 = 0
Int32 = 0
Int64 = 0
NodeNameList = {somenode.pok.ibm.com}
RefreshInterval = 60
SavedData =
SD = [,0,0,0,0,0,0]
String =
Uint32 = 0
Uint64 = 0
UserName = root
Name = ErrorLogSensor
ActivePeerDomain =
Command = /opt/csm/csmbin/monerrorlog
ConfigChanged = 0
ControlFlags = 0
Description =
ErrorExitValue = 1
ExitValue = 0
Float32 = 0
Float64 = 0
Int32 = 0
Int64 = 0
NodeNameList = {somenode.pok.ibm.com}
RefreshInterval = 60
SavedData =
SD = [,0,0,0,0,0,0]
String =
Uint32 = 0
Uint64 = 0
UserName = root
```

3. To list the attributes of sensor2, enter:

The output will look like this:

```
Name = sensor2
Command = /usr/local/bin/sensorcmd2
ConfigChanged = 0
ControlFlags = 0
Description =
ErrorExitValue = 1
ExitValue = 127
Float32 = 0
Float64 = 0
Int32 = 0
Int64 = 0
NodeNameList = {somenode.pok.ibm.com}
RefreshInterval = 60
SavedData =
SD = [,0,0,0,0,0,0]
String =
Uint32 = 0
Uint64 = 0
UserName = root
```

Location

/usr/sbin/rsct/bin/lssensor

Related Information

Books: RSCT: Administration Guide, for information about the ACL authorization file

Commands: chsensor, mksensor, refsensor, rmsensor

Isslot Command

Purpose

Displays dynamically reconfigurable slots, such as hot plug slots, and their characteristics.

Syntax

Isslot -c ConnectorType [-a | -o | -I DeviceName | -s Slot] [-F Delimiter]

Description

The **Isslot** command displays all the specified hot plug slots and their characteristics. Hot plug slots are the plug-in points for connecting entities that can be added and removed from the system without turning the system power off or rebooting the operating system. The **-c** flag is required. It specifies the type of hot plug connector, for example, pci for hot pluggable PCI adapters. You can display only the empty, that is, available, hot plug slots with the **-a** flag, the occupied slots with the **-o** flag, or a specific slot by using the **-s** flag. The **-I** flag can be used to locate the slot associated with specified *DeviceName*, as listed by the **Isdev** command.

The **Isslot** command is used to list the connectors which are connection points for either physical entities like PCI adapters or logical entities like Logical slots or logical host-Ethernet adapter ports. The connector has the following types:

- pci, a physical connector
- · slot, a logical connector
- · phb, a logical connector

port, a logical connector

The -a and the -o flags will be ignored for the logical connectors. The Isslot command in the case of the logical connectors displays the logical entities that are currently assigned to the partition, depending upon the connector type specified. You may need to run Isslot -c slot and Isslot -c phb to view all logical connections.

The output of the **Isslot** command is dependent on the *ConnectorType* and the platform on which the command is executed. The characteristics of a slot may include the following:

- · Slot name or identification
- Connector type or slot description, for example, a PCI hot plug slot
- · Connected device name(s), for example, scsi0, ent0

When the PHBs are listed using the Isslot command, the Device(s) Connected column will display the ODM name of the PHB followed by the ODM names of the devices corresponding to the logical slots underneath the PHB, with all the ODM devices associated with each logical slot displayed on each separate line under the ODM name of the PHB. In case there is no ODM name for the PHB, a blank line will be displayed.

Flags

-a	Displays available hot plug slots and their characteristics. Available slots are those slots that do not have a hot plug device connected. This flag is ignored for connector types of slot and phb.
-c ConnectorType	Displays the slots of the specified <i>ConnectorType</i> . <i>ConnectorType</i> identifies the type of connector. For example, the <i>ConnectorType</i> for a hot plug PCI slot is pci, for logical slots, it is slot and for PHBs, it is phb. This flag is required.
-F Delimiter	Specifies a single character to delimit the output. The heading is not displayed and the columns are delimited by the <i>Delimiter</i> character.
-I DeviceName	Displays the characteristics of the slot to which <i>DeviceName</i> is associated. The <i>DeviceName</i> is the logical device name of the device connected to the slot, as listed by the Isdev command.
-0	Displays the characteristics of the occupied slots. Occupied slots have a hot plug device connected. This flag is ignored for connector types of slot and phb.
-s Slot	Displays characteristics for the specified <i>Slot</i> . The format of <i>Slot</i> is platform/connector_type dependent.

Examples

1. To list the available PCI hot plug slots, enter:

lsslot -c pci -a

The system displays a message similar to the following:

Slot name	Description	Device(s) Connected
U0.4-P1-I1	PCI 64 bit, 66MHz, 3.3 volt slot	empty
U0.4-P1-I2	PCI 64 bit, 66MHz, 3.3 volt slot	empty
U0.4-P1-I3	PCI 64 bit, 66MHz, 3.3 volt slot	empty

2. To list the PCI hot plug slot associated with a scsi adapter named scsi1, enter:

lsslot -c pci -l scsi1

The system displays a message similar to the following:

Slot name	Description	Device(s) Connected
U0.4-P1-I1	PCI 64 bit, 33MHz, 5 volt slot	scsi1

3. To list all the PCI hot plug slots, enter:

lsslot -c pci

The system displays a message similar to the following:

Slot name	Description	Device(s) Connected
U0.4-P1-I1	PCI 64 bit, 33MHz, 3.3 volt slot	empty
U0.4-P1-I2	PCI 64 bit, 33MHz, 3.3 volt slot	scsi0
U0.4-P1-I3	PCI 64 bit, 33MHz, 3.3 volt slot	unknown
U0.4-P1-I5	PCI 64 bit, 33MHz, 3.3 volt slot	empty

Slots that have unknown in the Device(s) Connected column have a device connected to the slot, but the device isn't in the ODM customized device (CuDv) database. This can be due to the device having been newly added but not configured yet, deleted with the rmdev -d command, or the system may not be installed with the software packages associated with the device.

4. To list all the PCI Host Bridges that are assigned to the partition, enter:

lsslot -c phb

This displays output similar to the following:

PHB	Name	Descript	tion		Device(s)	Connected
PHB	1	Logical	PCI Host	Bridge	pci0 pci2 scsi	1
PHB	2	Logical	PCI Host	Bridge	pci1 pci3	
					pci4 scsi	<u> </u>

5. In case the PCI Host Bridge is assigned to the partition but has no ODM data, column will show blank as shown in this example. For example, when you enter:

lsslot -c phb

The output will look similar to the following:

PHB	Name	Description	Device(s)	Connected
PHB	4	Logical PCI Host Bridge		
PHB	5	Logical PCI Host Bridge		

6. To list all the logical host-Ethernet adapter-port devices that are assigned to the partition, enter:

lsslot -c port

LHEA port name	Description	Device(s) Connected
Port 1	Logical HEA Port	ent4
Port 2	Logical HEA Port	ent7

When the logical host-Ethernet adapter port is assigned to the partition but has no ODM data, the column shows Unknown as shown in the example:

lsslot -c port

LHEA port name	Description	Device(s) Connected
Port 4	Logical HEA Port	Unknown
Port 5	Logical HEA Port	Unknown

Files

/usr/sbin/lsslot

Related Information

The drslot command, the Isdev command.

For information about Hot Plug Management and PCI Hot Plug Support for PCI Adapters, see PCI hot plug management in Operating system and device management.

Issrc Command

Purpose

Gets the status of a subsystem, a group of subsystems, or a subserver.

Syntax

To Get All Status

Issrc [-h Host] -a

To Get Group Status

Issrc [-h Host] -g GroupName

To Get Subsystem Status

Issrc [-h Host] [-l] -s Subsystem

To Get Status by PID

Issrc [-h Host] [-l] -p SubsystemPID

To Get Subserver Status

Issrc [-h Host] [-l] -t Type [-p SubsystemPID] [-o Object] [-P SubserverPID]

To Get Subsystem Status in SMIT Format

Issrc -S [-s Subsystem | -d]

To Get Subserver Status in SMIT Format

Issrc -T [-t Type]

To Get Notify in SMIT Format

Issrc -N [-n NotifyName]

Description

The **Issrc** command sends a request to the System Resource Controller to get status on a subsystem, a group of subsystems, or all subsystems. The Issrc command sends a subsystem request packet to the daemon to be forwarded to the subsystem for a subserver status or a long subsystem status.

You can choose whether to request a short or long status for a subserver. When the -I flag is absent, the status request is assumed to be a short status. A short status of a subsystem, group of subsystems, or all subsystems is handled by the System Resource Controller.

When the -I flag is present for a subsystem, a status request is taken to the subsystem and the subsystem sends the status back. The -I flag is supported only for those subsystems not using signals as their communication method. For either a long or short status of a subserver, the subsystem is sent a status request packet, and the subsystem sends the status back.

The Issrc command output can sometimes show two entries for a particular daemon. One instance will be active and another instance will be inoperative. This can happen if the subsystem is modified (using the mkssys command or chssys command) without stopping the subsystem. The original subsystem will remain active and the modified instance will be inoperative until the subsystem is stopped and started again.

Flags

Lists the current status of all defined subsystem. -a Specifies that the default record is printed.

Specifies a group of subsystems to get status for. The command is unsuccessful if the -g GroupName

GroupName variable is not contained in the subsystem object class.

Specifies the foreign host on which this status action is requested. The local user must -h Host

> be running as "root". The remote system must be configured to accept remote System Resource Controller requests. That is, the srcmstr daemon (see /etc/inittab) must be started with the -r flag and the /etc/hosts.equiv or .rhosts file must be configured to

allow remote requests.

-1 Requests that a subsystem send its current status in long form. Long status requires

that a status request be sent to the subsystem; it is the responsibility of the subsystem

to return the status.

Specifies the name of a notify method. -n NotifyName

Specifies that the Object Data Manager (ODM) records are output in SMIT format for -N

the notify object class.

-o Object Specifies that a subserver Object variable is passed to the subsystem as a character

-p SubsystemPID Specifies a particular instance of the SubsystemPID variable to get status for, or a

particular instance of the subsystem to which the status subserver request is to be

-P SubserverPID Specifies that a SubserverPID variable is to be passed to the subsystem as a character

string.

-s Subsystem Specifies a subsystem to get status for. The Subsystem variable can be the actual

subsystem name or the synonym name for the subsystem. The command is

unsuccessful if the Subsystem variable is not contained in the subsystem object class.

Specifies that the ODM records are output in SMIT format for the subsystem object

class.

-t Type Requests that a subsystem send the current status of a subserver. The command is

unsuccessful if the subserver *Type* variable is not contained in the subserver object

-T Specifies that the ODM records are output in SMIT format for the subserver object

class.

Examples

-S

1. To get the status of all subsystems on the local machine, enter:

lssrc -a

This gets the status of all subsystems known on the local machine.

2. To get the status of all subsystems on a foreign host, enter:

1ssrc -h zork -a

This gets the status of all subsystems known on the zork machine.

3. To get the status of the srctest subsystem, enter:

lssrc -s srctest

This gets the status of all instances of the srctest subsystem on the local machine.

4. To get the status of the subsystem by PID, enter:

lssrc -p 1234

This gets the status of the subsystem with the subsystem PID of 1234 on the local machine.

5. To get the status of the tcpip subsystem group, enter:

```
lssrc -g tcpip
```

This gets the status of all instances of subsystems in the tcpip group on the local machine.

6. To get the status of the tester subserver, enter:

```
lssrc -t tester -p 1234
```

This gets the status of tester subserver that belongs to the srctest subsystem with the subsystem PID of 1234 on the local machine.

7. To get the status of the subsystem by PID, enter:

```
lssrc -1 -p 1234
```

This gets the long status of the subsystem with the PID of 1234.

Files

/etc/objrepos/SRCsubsys Specifies the SRC Subsystem Configuration Object Class. /etc/objrepos/SRCsubsvr Specifies the SRC Subserver Configuration Object Class. /etc/objrepos/SRCnotify Specifies the SRC Notify Configuration Object Class. Defines the sockets and protocols used for Internet services. /etc/services /dev/SRC Specifies the AF_UNIX socket file.

/dev/.SRC-unix Specifies the location for temporary socket files.

Related Information

The **mkssys** command, **rmssys** command.

System Resource Controller in Operating system and device management gives an explanation of subsystems, subservers, and the System Resource Controller.

Ists Command

Purpose

Lists information pertaining to a thin server.

Syntax

Ists [[-I{1|2|3}] . . .] [-v] [ThinServer]

Description

The Ists command lists information pertaining to a thin server. The level of information to be listed depends on the numeric value specified by the -I flag, with a level ranging from 1 - 3 (3 being the most detailed). If a level is not specified, a default of level 1 information is displayed. This command can be run on both a NIM master or a thin server. When run on a NIM master and no argument is provided, the Ists command lists all thin servers in the environment controlled by the caller of the Ists command.

Flags

-I{1|2|3}

Specifies the level of information to display.

- This level displays very limited information related to a thin server. The information listed shows only a brief summary of the thin server, such as the common image it is using.
- 2 This level displays more than just basic information related to a thin server. The level includes information pertaining to the software content of the thin server.
- This level displays more in-depth information related to a thin server. The level includes information pertaining to the installation log of the thin server.

Enables verbose debug output when the **Ists** command runs.

-V

Exit Status

∪ >0 The command completed successfully. An error occurred.

Security

Access Control: You must have root authority to run the Ists command.

Examples

1. To list brief status information for a thin server named lobo, enter:

```
1sts lobo
```

Information similar to the following is displayed:

```
Lobo:

class = machines
type = diskless
platform = chrp
netboot_kernel = 64
if1 = master_net jsblade04 0 ent1
cable_type1 = bnc
Cstate = diskless or dataless boot is enabled
prev_state = in the process of booting
Mstate = currently running
boot = boot
dump = dump_res
paging = paging_res
root = root_res
spot = 530spot_res
cpuid = 00012A80D000
control = master
Cstate_result = success
```

2. To list software content for a thin server named lobo, enter:

```
1sts -12 lobo
```

Software content similar to the following is displayed from the common image:

Fileset (Uninstaller)	Level State	Type	Description
bos.64bit	5.2.0.75 C	F	Base Operating System 64 bit Runtime
bos.diag.com	5.2.0.75 C	F	Common Hardware Diagnostics
bos.diag.rte	5.2.0.75 C	F	Hardware Diagnostics
•			
•			
•			

3. To list both software content and status information for a thin server named lobo, enter:

```
lsts -11 -12 lobo
```

Location

/usr/sbin/lsts

Files

/etc/niminfo

Contains variables used by NIM.

Related Information

The dbts command, "mkcosi Command" on page 571, "mkts Command" on page 692, nim command, nim_clients_setup command, nim_master_setup command, nimconfig command, rmcosi command, rmts command, swts command.

Istun Command

Purpose

Lists tunnel definition(s).

Syntax

Istun [-v 4|6] [-t tid_list] [-p manual] [-a]

Description

Use the Istun command to list the tunnel definition(s) and their current status. This command can either list the tunnels in the tunnel database or in the active system.

Flags

-v	This flag specifies the IP version. For listing IP version 4 tunnel only, use the value of 4. For listing IP
	version 6 tunnel only, use the value of 6 . If this flag is not used, both the version 4 and version 6 tunnels will be listed.
-t	Only list the tunnel definition and its current status for the tunnel whose tunnel ID is in tid_list. If this

flag is not used, all the tunnel definitions and their current status will be listed. Selects the type of the tunnel to be listed. Using the -p flag with the value of manual lists manual

-p tunnels only. The -p flag is for listing tunnel definitions in the tunnel database only and thus is mutually exclusive with the -a flag.

Lists the tunnels active in the IP Security subsystem. -a

Related Information

The gentun command, chtun command, imptun command, exptun command, mktun command, and rmtun command.

Isuser Command

Purpose

Displays user account attributes.

Syntax

```
Isuser [-R load module] [-c |-f] [-a List] { ALL | Name [,Name] ... }
```

Description

The Isuser command displays the user account attributes. You can use this command to list all attributes of all the system users or all the attributes of specific users. Since there is no default parameter, you must enter the ALL keyword to see the attributes of all the users. By default, the Isuser command displays all user attributes. To view selected attributes, use the -a List flag. If one or more attributes cannot be read, the **Isuser** command lists as much information as possible.

Note: If you have a Network Information Service (NIS) database installed on your system, some user information may not appear when you use the **Isuser** command.

By default, the Isuser command lists each user's attributes on one line. It displays attribute information as Attribute=Value definitions, each separated by a blank space. To list the user attributes in stanza format, use the -f flag. To list the information as colon-separated records, use the -c flag.

You can use the Users application in Web-based System Manager (wsm) to change user characteristics. You could also use the System Management Interface Tool (SMIT) smit Isusers fast path to run this command.

Flags

-a List Lists the attributes to display. The List variable can include any attribute defined in the chuser command and requires a blank space between attributes. If you specify an empty list, only the user names are displayed.

Displays the user attributes in colon-separated records, as follows: -C

```
# name: attribute1: attribute2: ...
 User: value1:
                    value2:
```

Displays the output in stanzas, with each stanza identified by a user name. Each Attribute=Value pair is -f listed on a separate line:

user:

attribute1=value attribute2=value attribute3=value

Specifies the loadable I&A module used to display the user account attributes.

load module

Exit Status

This command returns the following exit values:

0 The command runs successfully and all requested changes are made.

>0 An error occurred. The printed error message lists further details about the type of failure.

Security

Access Control: This command should be a general user program with execute (x) access for all users. Since the attributes are read with the access rights of the user who invokes the command, some users may not be able to access all the information. This command should have the trusted computing base attribute.

Files Accessed:

Mode	File
r	/etc/passwd
r	/etc/security/user
r	/etc/security/user.roles
r	/etc/security/limits
r	/etc/security/environ
r	/etc/group
r	/etc/security/audit/config

Examples

1. To display the user id and group-related information about the smith account in stanza form, enter:

```
lsuser -f -a id pgrp groups admgroups smith
```

Information similar to the following appears:

```
smith:
  ID=2457
  pgrp=system
   groups=system, finance, staff, accounting
   admgroups=finance,accounting
```

2. To display the user id, groups, and home directory of smith in colon format, enter:

```
lsuser -c -a id home groups smith
```

Information like the following appears:

```
# name: ID:home:groups
smith: 2457:/home/smith:system,finance,staff,accounting
```

3. To display all the attributes of user smith in the default format, enter:

```
lsuser smith
```

All the attribute information appears, with each attribute separated by a blank space.

4. To display all the attributes of all the users, enter:

```
1suser ALL
```

All the attribute information appears, with each attribute separated by a blank space.

Files

/usr/sbin/Isuser Contains the Isuser command. /etc/passwd Contains basic user information. /etc/security/limits Defines resource quotas and limits for each user. /etc/security/user Contains the extended attributes of users. /etc/security/user.roles Contains the administrative role attributes of users. /etc/security/environ Contains the environment attributes of users. /etc/group Contains basic group attributes. /etc/security/audit/config Contains the audit configuration files.

Related Information

The **chfn** command, **chgroup** command, **chgrpmem** command, **chsh** command, **chuser** command, **lsgroup** command, **mkgroup** command, **mkuser** command, **passwd** command, **pwdadm** command, **rmgroup** command, **rmuser** command, **setgroups** command, **setsenv** command.

For more information about the identification and authentication of users, discretionary access control, the trusted computing base, and auditing, refer to the *Security*.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

For more information about administrative roles, refer to Administrative roles in Security.

Isvfs Command

Purpose

Lists entries in the /etc/vfs file.

Syntax

Isvfs { -a | VfsName }

Description

The **Isvfs** command lists entries in the **/etc/vfs** file. You can display information about a specific Virtual File System (VFS) type or all known VFS types.

Flag

-a Lists all stanzas in the /etc/vfs file, including the default stanza.

Parameter

VfsName Specifies the name of a virtual file system.

Examples

1. To list the vfs entry named newvfs, enter:

1svfs newvfs

2. To list all vfs types, enter:

lsvfs -a

Files

/etc/vfs Contains descriptions of virtual file system types.

Related Information

The **chvfs** command, **crvfs** command, **rmvfs** command, **mount** command.

File systems in *Operating system and device management* explains file system types, management, structure, and maintenance.

Mounting in Operating system and device management explains mounting files and directories, mount points, and automatic mounts.

Isvg Command

Purpose

Displays information about volume groups.

Syntax

| Isvg [-L] [-o] | [-n DescriptorPhysicalVolume] | [-i] [-I | -M | -p] VolumeGroup ...

Description

The **Isvg** command displays information about volume groups. If you use the *VolumeGroup* parameter, only the information for that volume group is displayed. If you do not use the *VolumeGroup* parameter, a list of the names of all defined volume groups is displayed.

When information from the Device Configuration database is unavailable, some of the fields will contain a question mark (?) in place of the missing data. The **Isvg** command attempts to obtain as much information as possible from the description area when the command is given a logical volume identifier.

Note: To determine a volume group's major number, use the Is -al /dev/VGName command. This command lists the special device file that represents the volume group. The volume group major number is the same as the major device number of the special device file. For example, for a volume group named halvg, enter the following command:

```
ls -al /dev/halvg
```

This command returns the following:

```
crw-rw---- 1 root system 52, 0 Aug 27 19:57 /dev/ha1vg
```

In this example, the volume group major number is 52.

You can use the Volumes application in Web-based System Manager (wsm) to change volume characteristics. You could also use the System Management Interface Tool (SMIT) smit Isvg fast path to run this command.

Flags

-L Specifies no waiting to obtain a lock on the Volume group.

> Note: If the volume group is being changed, using the -L flag gives unreliable data.

-p

Lists the following information for each physical volume within the group specified by the *VolumeGroup* parameter:

Physical volume

A physical volume within the group.

PVstate

State of the physical volume.

Total PPs

Total number of physical partitions on the physical volume.

Free PPs

Number of free physical partitions on the physical volume.

Distribution

The number of physical partitions allocated within each section of the physical volume: outer edge, outer middle, center, inner middle, and inner edge of the physical volume.

Lists the following information for each logical volume within the group specified by the *VolumeGroup* parameter:

LV A logical volume within the volume group.

Type Logical volume type.

LPs Number of logical partitions in the logical volume.

PPs Number of physical partitions used by the logical volume.

PVs Number of physical volumes used by the logical volume.

Logical volume state

State of the logical volume. Opened/stale indicates the logical volume is open but contains partitions that are not current. Opened/syncd indicates the logical volume is open and synchronized. Closed indicates the logical volume has not been opened.

Mount point

File system mount point for the logical volume, if applicable.

Reads volume group names from standard input.

Lists the following fields for each logical volume on the physical volume:

PVname: PPnum [LVname: LPnum [:Copynum] [PPstate]]

PVname Name of the physical volume as specified by the system.

PPnum Physical partition number. Physical partition numbers can range from 1 to

LVname Name of the logical volume to which the physical partitions are allocated. Logical volume names must be system-wide unique names, and can range from 1 to 64 characters.

LPnum Logical partition number. Logical partition numbers can range from 1 to 64,000.

Copynum

Mirror number.

PPstate

Only the physical partitions on the physical volume that are not current are shown as stale.

-n DescriptorPhysicalVolume

Accesses information from the descriptor area specified by the *DescriptorPhysicalVolume* variable. The information may not be current, since the information accessed with the -n flag has not been validated for the logical volumes. If you do not use the -n flag, the descriptor area from the physical volume that holds the most validated information is accessed, and therefore the information displayed is current. The volume group need not be active when you use this flag.

-1

-i

-M

Lists only the active volume groups (those that are varied on). An active volume

group is one that is available for use.

Information displayed if you do not specify any flags:

-0

Name of the volume group. Volume group names must be unique systemwide Volume group

and can range from 1 to 15 characters.

Volume group state State of the volume group. If the volume group is activated with the varyonvg

> command, the state is either active/complete (indicating all physical volumes are active) or active/partial (indicating some physical volumes are not active).

Permission Access permission: read-only or read-write.

Max LVs Maximum number of logical volumes allowed in the volume group.

LVs Number of logical volumes currently in the volume group.

Open LVs Number of logical volumes within the volume group that are currently open.

Total PVs Total number of physical volumes within the volume group. Active PVs Number of physical volumes that are currently active.

The volume group identifier. VG identifier PP size Size of each physical partition.

Total PPs Total number of physical partitions within the volume group.

Number of physical partitions not allocated. Free PPs

Alloc PPs Number of physical partitions currently allocated to logical volumes.

Number of physical volumes needed for a majority. Quorum

Number of volume group descriptor areas within the volume group. **VGDS**

Automatic activation at IPL (yes or no). Auto-on

States whether the volume group is Concurrent Capable or Non-Concurrent Concurrent

States whether you should autovary the Concurrent Capable volume group in Auto-Concurrent

concurrent or non-concurrent mode. For volume groups that are Non-Concurrent

Capable, this value defaults to Disabled.

VG Mode The vary on mode of the volume group: Concurrent or Non-Concurrent. Node ID Node id of this node if volume group is varied on in concurrent node. Node ids of other concurrent nodes that have this volume group varied on. Active Nodes Max PPs Per PV Maximum number of physical partitions per physical volume allowed for this

volume group.

Max PVs Maximum number of physical volumes allowed in this volume group. This

information is displayed only for 32 and 128 PV volume groups.

Logical track group size of the volume group. The maximum amount of data that LTG size

can be transferred in one I/O request to the disks of the volume group. The LTG size will be displayed in kilobytes unless the LTG size is greater than 1 MB, in which case megabytes will be used. If the volume group was created on AIX 5.3, then it is capable of dynamically determining the LTG size based-on the disk topology and it is listed as Dynamic. If that capability is disabled by the user with the varyonvg -M option, then it will be listed as Static. If the capability does not exist because the volume group was created prior to AIX 5.3, then the VG will not

be listed as Static or Dynamic.

BB POLICY Bad block relocation policy of the volume group.

SNAPSHOT VG Snapshot volume group name if the snapshot volume group is active, else

snapshot volume group identifier.

Original volume group name of a snapshot volume group if the original volume PRIMARY VG

group is active, else original volume group identifier.

Examples

1. To display the names of all active volume groups, enter:

lsvg -o

2. To display the names of all volume groups within the system, enter:

3. To display information about volume group vg02, enter:

1svg vg02

The characteristics and status of both the logical and physical partitions of volume group vg02 are displayed.

4. To display the names, characteristics, and status of all the logical volumes in volume group vg02, enter:

1svg -1 vg02

Files

/usr/sbin

Contains the directory where the Isvg command resides.

Related Information

The chvg command, Ispv command, Islv command, varyonvg command.

Logical volume storage in Operating system and device management explains the Logical Volume Manager, physical volumes, logical volumes, volume groups, organization, ensuring data integrity, and allocation characteristics.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

System management interface tool in Operating system and device management explains the structure, main menus, and tasks that are done with SMIT.

Isvgfs Command

Purpose

Displays a list of file systems belonging to a volume group.

Syntax

Isvgfs volumegroup

Description

The **Isvgfs** command displays a list of file systems that belong to the specified volume group.

Parameters

volumegroup

Specifies a volume group.

Examples

1. To display a list of file systems in the volume group vg02, enter the following command: 1svqfs vq02

Exit Status

The **Isvgfs** command returns the following exit values:

0 Successful completion. >0 An error occurred.

Files

/usr/sbin Contains the directory where the **Isvgfs** command resides.

Related Information

The Isvg, Islv, and Isfs commands.

File systems in Operating system and device management explains file system types, management, structure, and maintenance.

Logical volume storage in Operating system and device management explains the Logical Volume Manager, physical volumes, logical volumes, volume groups, organization, ensuring data integrity, and allocation characteristics.

Isvirprt Command

Purpose

Displays the attribute values of a virtual printer.

Syntax

Isvirprt [-q QueueName -d DeviceName { [-f Format] [-n] [-a AttributeName | -s SectionName] ... | -i | **-D** }]

Description

The Isvirprt command displays the attribute values for the virtual printer assigned to the PrintQueueName and QueueDeviceName variables.

The **Isvirprt** command becomes interactive if no flags are specified with the command. A list of print queue names is displayed, and a prompt appears requesting that the desired print queue name be selected. After a valid print queue name is selected, a prompt appears requesting that attribute names be entered. If an attribute name of * (asterisk) is entered, a list of all attributes is displayed.

Note: Attribute names for default values of the **qprt** command line flags can be specified by entering the flag letters. For example, to view the default value for the -w flag (page width), enter the w attribute name. All other attribute names must be 2 characters long.

You can use the Printer Queues application in Web-based System Manager (wsm) to change printer characteristics. You could also use the System Management Interface Tool (SMIT) smit Isvirprt fast path to run this command.

Flags

-a AttributeName

Specifies the name of an attribute for which information is to be displayed. The flag cannot be used with the -s flag. The -a flag can be specified many times to list multiple attributes. The AttributeName value can be a single-character name (for example, i), a simple two-character name (for example, ci), or a regular expression that specifies multiple attributes (for example, ^i.*.)

-d QueueDeviceName

Specifies the name of the queue device to which the virtual printer is assigned.

This flag is optional, but can be specified only if the -q flag is specified.

Displays data streams supported by a given queue and queue device name variable values. The **-D** flag displays the default data stream first and all other

supported data streams in alphabetical order.

-f Format

-D

-i

Specifies the display format for attribute information. Attribute information includes the attribute value, limits field, and attribute description. The Format value is specified in printf format. The -f Format option also supports the following predefined set of position arguments:

Note: [*.*] is not a required element for the following format values.

%1\$[*.*]s

Message catalog name

%2\$[**.**]d

Message number

%3\$[*.*]s

Attribute name

%4\$[*.*]s

Limits field

%5\$[**.**]s

Attribute value

%6\$[**.**]s

Attribute description

%7\$c Second character of attribute name.

Sets the command to interactive mode. The -q and -d flags must be specified

with the -i flag. If values have been assigned to the QueueName and

DeviceName variables, the command does not prompt for the queue and device

names and accepts attribute names interactively.

Displays only the specified attributes that have nonnull values. -n

-s SectionName Specifies a section name in the virtual printer attribute database of the specified

queue and queue device. The SectionName values begin with two underscores and contain three characters that identify a section. For example, the name of a section that contains all the flag attributes is __FLG. The -s flag can not be used with the -a flag. This option can be repeated to list multiple attributes. The

SectionName variable value can be a regular expression.

-q PrintQueueName Specifies the name of the print queue to which the virtual printer is assigned. This

flag is optional, but can be specified only if the -d flag is specified.

Examples

1. To show the attribute values for the w (default page width) and si (user to receive the "Intervention Required" messages) attributes for the virtual printer assigned to the mypro queue device on the prog print queue, enter:

```
lsvirprt -dmypro -qproq -a w -a si
```

The output from this command is:

Name	Description	Value
_W	COLUMNS per page	136
si	USERS to get intervention messag	es

2. To show the same attributes in Example 1, but the be prompted for the flag values, enter:

lsvirpt

The output from this command is:

```
e4039c
1
                         0piobe
                                            ibm4039 (PCL Emulation)
2
        e4039s
                         @piobe
                                           ibm4039 (PostScript)
3
        fjzhp4s
                         jzfile
                                           hplj-4 (PostScript)
                                           hplj-4 (PCL)
4
        hpc14
                         hp@pc15
```

3. To list attributes in a section for header and trailer pipelines for the que queue and the dev device,

```
1svirpt -qque -ddev -s HTP
```

The output from this command is:

```
Name
        Description
                                          Value
sh
        Pipeline for Header Page
                                          %Ide/pioburst %F[H]
                                          %Idb/H.ascii |
                                          %Ide/pioformat
                                          -0%Idd/%Imm
                                          -!%Idf/piof5202 -L! -J!
                                          %IsH
st
        Pipeline for Trailer Page
                                          %Ide/pioburst %F[H]
                                          %Idb/T.ascii |
                                          %Ide/pioformat
                                          -0%Idd/%Imm
                                          -!%Idf/piof5202-L!
                                          -t%0%G 1%r%{14}%-%d
                                          %IsT
```

4. To list all the data streams supported for the que queue and the dev device, enter:

```
lsvirpt -qque -ddev -D
```

The output from this command is:

```
a ASCII
p pass-through
s PostScript
```

5. To list names and descriptions of all attributes in a printer attribute database for the que queue and the dev device in a specific format, enter:

```
lsvirpt -qque -ddev -a'.*' -f' %3$5.5s: %6$s\\n'
```

The output from this command is:

```
__FLG: Values That May Be Overridden With Flags
_A: stderr returned?
_E: Double spacing flag
_F: (not used) Font file name
_H: Name to Replace Host Name of Burst Page
```

6. To list all the sections in a printer attribute data base for the que queue and the dev device in a specific format, enter:

```
lsvirpt -qque -ddev -a'__.*' -f'%3$s: %6$s\\n'
```

The output from this command is:

```
__FLG: Values That May Be Overridden With Flags On the Command Line
__SYS: Other Values Of Interest To the Streams Administrator
__IDS: Pipelines For Input Data Streams (2 char,1st="i",2nd=data stream name)
__PFL: Flags Prohibited For Input Data Streams (2 char,1st="I", 2nd=data stream name)
```

```
__FIL: Command Strings For Filter Flags (2 char, 1st="f",
__DIR: Directories
```

Files

/etc/qconfig /usr/sbin/lsvirprt /var/spool/lpd/pio/@local/custom/* /var/spool/lpd/pio/@local/ddi/*

Contains the configuration file. Contains the Isvirprt command. Contains virtual printer attribute files. Contains the digested virtual printer attribute files.

Related Information

The **chvirprt** command, **mkvirprt** command, **rmvirprt** command.

The qconfig file.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

Configuring a printer without adding a queue in Printers and printing.

Printing administration in *Printers and printing*.

Print spooler in *Printers and printing*.

Virtual printer definitions and attributes in Printers and printing.

Adding a printer using the printer colon file in Printers and printing.

Isymode Command

Purpose

Display the current video mode of the X server.

Note: This command is usable only while the X server is running.

Syntax

Isvmode

Description

The **Isymode** command displays the current output device and viewport size used by the X server.

Security

Access Control: Any User

Auditing Events: None

Exit Status

The following exit values are returned:

0 Successful completion.

Examples

To display the current video mode of the X server.

1svmode

Something similar to the following displays:

```
Current video mode information
Logical screen size [1024x768]
Viewport size [640x480]
Vertical sync. (Hz) [60]
Active output device [LCD][CRT]
```

Files

/usr/bin/X11/Isvmode

Contains the Isvnode command.

Related Information

The chymode command.

Isvpd Command

Purpose

Lists the vital product data (VPD) associated with the field replaceable units (FRUs) configured on a system.

Syntax

Isvpd [-m] [-s serial_number] [-t type_model] [-v]

Description

The **Isvpd** command collects vital product data (VPD) for field replaceable units (FRUs). It reads the appropriate device configuration object classes in the Object Data Manager (ODM) and gathers VPD and general system information. The **Isvpd** command can extract additional VPD by reading data structures that are specific to the platform on which it is running. Data is provided in a format that aids service personnel in monitoring device quality and performance.

Note: Output from the **Isvpd** command is informational only and subject to change as hardware definitions change. Portable applications should not parse this data.

Flags

-m

Distinguishes between a FRU with global VPD and a FRU with partition private VPD. FRUs with global VPD begin with a line in the format of *FC *********. FRUs with partition private VPD begin with a line in the format of *FC =======. If this flag is not specified, the output begins with a line in the format of *FC ????????. For LPARs, this option distinguishes between FRUs associated with the overall system and FRUs assigned to a specific partition.

-s serial_number

-t type_model

-v

Specifies the serial number for the system. The optional serial_number parameter is obsolete and should not be used on AIX 5.2 and later systems. If the serial number is entered, that value will be used in the output of the command. In some cases, Isvpd is unable to automatically determine the serial number. In these cases, the user must supply the value in order for it to be displayed in the command output.

Specifies the type model for the system. The optional type_model parameter is obsolete and should not be used on AIX 5.2 and later systems. If the type model is entered, that value will be used in the output of the command. In some cases, Isvpd is unable to automatically determine the type model. In these cases, the user must supply the value in order for it to be displayed in the command output.

Produces verbose output for debugging purposes only.

Exit Status

1

The command completed successfully. An error occurred.

Examples

1. Output for the **Isvpd** command is similar to the following.

Note: Portable applications should not parse this data.

*VC 5.0

*TM IBM,7029-6E3

*SE IBM,0110B721E

*PI 000B721E

*OS AIX 5.3.0.0

*FC ???????

*DS Platform Firmware

*YL U0.1-P1-X1/Y1

*RM 3F041029

*VK RS6K

*FC ???????

*DS System Firmware

*YL U0.1-P1-X1/Y2

*RM RG041029_d79e00_regatta

*VK RS6K

*FC ???????

*DS System VPD

*YL U0.1

*SE 10B721E

*TM 7029-6E3

*MN IBM980

*VK RS6K

*PA Y

*BR I0

*FC ????????

*DS PS CEC OP PANEL

*YL U0.1-L1

*SN YL1124350190

*EC H64013

*CC 28D3

*FN 97P3352

*DC BD 200210290851

*VK RS6K

*FC ???????

*DS 2 WAY BACKPLANE

*YL U0.1-P1

*SN YL1123354433

*PN 80P3099

*CC 26F5

*CE 1

*FN 80P3099

*VK RS6K

*FC ???????

*DS CSP

*YL U0.1-P1-X1

*SN YL1024360048

*PN 80P5573

*CC 28D0

*CE 1

*FN 80P5573

*RM 3F041029

*VK RS6K

*FC ???????

*DS IBM 1.8V VRM

*YL U0.1-P1-V1

*FN 24P6892

*VK RS6K

*FC ???????

*DS IBM 2.5V VRM

*YL U0.1-P1-V2

*FN 53P5623

*VK RS6K

*FC ???????

*DS IBM 1.2V VRM

*YL U0.1-P1-V3

*FN 53P5621

*VK RS6K

*FC ????????

*DS A IBM AC PS

*YL U0.1-V2

*SN YL1023C90045

*EC H85582

*CC 51B5

*FN 97P5101

*VK RS6K

*FC ????????

*DS IBM Air Mover

*YL U0.1-F1

*FN 53P4612

*VK RS6K

*FC ???????

*DS IBM Air Mover

*YL U0.1-F2

*FN 53P4612

*VK RS6K

*FC ????????

*DS IBM Air Mover

*YL U0.1-F3

*FN 53P4612

*VK RS6K

*FC ???????

*DS VSBPD4E1 U4SCSI

*YL U0.1-P2

*SN YL11243550F4

*PN 80P4611

*EC H85823

*CC 28D2

*FN 80P4610

*FS

*VK RS6K

```
*FC ???????
*DS MEDIA BACKPLANE
*YL U0.1-P4
*SN YL1124341459
*PN 80P3510
*EC H85610
*CC 28D1
*FN 80P3516
*VK RS6K
*FC ???????
*DS PCI-X Dual Channel Ultra320 SCSI Adapter
*AX sisscsia1
*PL 1Z-08
*CD 10140266
*PN 97P6513
*FN 97P6513
*SN YL11A5013461
*MN 001A
*EC 1
*RM 05080064
*Z0 5702
*YL U0.1-P1-I1
*FC ???????
*DS IDE DVD-ROM Drive
*AX cd0
*PL 1G-19-00
*MF IBM
*TM DROM00205
*RL NR38
*Z0 058002028F000010
*YL U0.1-P1-X1/Q6-A0
*FC ???????
*DS 16 Bit LVD SCSI Disk Drive
*AX hdisk0
*PL 1S-08-00-5,0
*MF IBM
*TM ST336607LC
*FN 00P3068
*RL 4335304A
*SN 000D7D3B
*EC H12094
*PN 00P2676
*Z0 000003129F00013E
*Z1 0812C512
*Z2 0002
*Z3 04341
*Z4 0001
*Z5 22
*Z6 H12094
*YL U0.1-P1/Z1-A5
*FC ???????
*DS 16 Bit LVD SCSI Disk Drive
*AX hdisk1
*PL 1S-08-00-8,0
*MF IBM
*TM ST336607LC
*FN 00P3068
*RL 4335304A
*SN 000D7996
*EC H12094
*PN 00P2676
*Z0 000003129F00013E
*Z1 0812C512
*Z2 0002
*Z3 04340
*Z4 0001
*Z5 22
```

```
*Z6 H12094
*YL U0.1-P1/Z1-A8
*FC ???????
*DS Diskette Drive
*AX fd0
*PL 01-D1-00-00
*YL U0.1-P1-X1-D1
*FC ???????
*DS Asynchronous Terminal
*AX tty0
*PL 01-S1-00-00
*YL U0.1-P1-X1/S1-L0
*FC ???????
*DS SCSI Enclosure Services Device
*AX ses0
*PL 1S-08-00-15,0
*MF IBM
*TM VSBPD4E1 U4SCSI
*RL 4610
*SN 243550F4
*Z0 0D0002022F004000
*FN 80P4610
*FL DB1
*FS
*YL U0.1-P1/Z1-Af
*FC ???????
*DS IBM MS 512 MB
*YL U0.1-P1-M5
*SN YL10243591YT
*PN 00P5767
*CC 30D2
*FN 00P5767
*SZ 512
*VK RS6K
*FC ???????
*DS IBM MS 512 MB
*YL U0.1-P1-M7
*SN YL10243591YP
*PN 00P5767
*CC 30D2
*FN 00P5767
*SZ 512
*VK RS6K
*FC ???????
*DS IBM MS 512 MB
*YL U0.1-P1-M4
*SN YL1024359208
*PN 00P5767
*CC 30D2
*FN 00P5767
*SZ 512
*VK RS6K
*FC ???????
*DS IBM MS 512 MB
*YL U0.1-P1-M2
*SN YL1024359204
*PN 00P5767
*CC 30D2
*FN 00P5767
*SZ 512
*VK RS6K
```

Location

/usr/sbin/lsvpd

Related Information

The "lscfg Command" on page 328, uname command.

Isvsd Command

Purpose

Displays configured virtual shared disks and their characteristics.

Syntax

Isvsd [-I | -s[vsd_name...]] | [-i]

Description

The **Isvsd** command displays information about virtual shared disks currently configured on the node on which the command is run. If a list of virtual shared disks follows the flags, information about those virtual shared disks is displayed. **Isvsd** with no arguments or flags lists the names of all the virtual shared disks currently configured on the node.

The **Isvsd** command displays information about both the configuration and the usage of a virtual shared disk.

You can use the System Management Interface Tool (SMIT) to run the **Isvsd** command. To use SMIT, enter:

smit vsd mgmt

and select the Show All Managed Virtual Shared Disk Characteristics option.

Flags

-I

Lists the name of the virtual shared disk, the minor number, the state, the current server node number, and, at the server only, the major and minor number of the logical volume. (This flag is lowercase I, as in Iist.)

The state field can have one of the following values:

STP Stopped

SUS Suspended

ACT Active

An asterisk (*) in front of any of these values indicates that the virtual shared disk has been fenced from this node.

This flag is not compatible with the -s flag.

The server_list of the virtual shared disk is listed.

-s

Lists usage statistics about the virtual shared disks. It lists the number of local logical read and write operations, the number of remote logical read and write operations, the number of client logical read and write operations, the number of physical reads and writes, and the number of 512-byte blocks read and written. The number of blocks read and written is cumulative, so issue **ctlvsd** –**V** to reset this count before measuring it.

The local logical operations are requests which were made by a process executing at the local node, whereas the remote logical operations were made by a process executing on a remote node. *Client operations* are those local logical requests that cannot be satisfied locally, and have to be sent to a remote node. *Physical* operations are those server operations which must be passed to the underlying disk device.

This flag is not compatible with the -I flag.

-i Lists the "node to IP address" map that is currently used by the virtual shared disk driver.

Parameters

vsd_name Specifies a virtual shared disk. This parameter is valid only with the -I and -s flags.

Security

You must be in the AIX bin group to run this command.

Restrictions

You must issue this command from a node that is online in the peer domain. To bring a peer domain online, use the **startrpdomain** command. To bring a particular node online in an existing peer domain, use the **startrpnode** command. For more information on creating and administering an RSCT peer domain, refer to *RSCT Administration Guide*.

Examples

1. To list all virtual shared disks in the system, enter:

1svsd

The system displays a message similar to the following:

vsd00

vsd01

.

2. To list virtual shared disks and their characteristics, enter:

```
1svsd -1
```

The system displays a message similar to the following:

```
minor state server lv_major lv_minor vsd_name
                                                 size (MB)
                                       vsdn08v3
83
      STP
              -1
                       0
                                0
                                                   20
84
      STP
                                       vsdn08v4
               -1
                        0
                                 0
                                                   16
```

3. To list statistics about virtual shared disks and precede the column output with a header, enter:

```
1svsd -s
```

The system displays a message similar to the following:

1c-rd	1c-wt	rm-rd	rm-wt	c-rd	c-wt	p-rd	p-wt	br	bw	vsd name
84	84	2858	169	0	0	348	253	164	184	vsd.vsd1
0	0	0	0	0	0	0	0	0	0	vsd.rl01
0	0	0	0	0	0	0	0	0	0	vsd.r102

The following table spells out the names of the headers used in the displays for the -I and -s options:

Header

Meaning

minor Virtual shared disk minor number

state State of this virtual shared disk: active, stopped, suspended

server Primary node for this virtual shared disk

Iv major

Logical volume major number

ly minor

Logical volume minor number

vsd name

Name of this virtual shared disk

lc-rd Local logical readslc-wt Local logical writesrm-rd Remote logical readsrm-wt Remote logical writesc-rd Client logical reads

c-wt Client logical writes

p-rd Physical readsp-wt Physical writesbr Blocks readbw Blocks written

Location

/opt/rsct/vsd/bin/lsvsd

Related Information

Commands: cfgvsd, preparevsd, resumevsd, startvsd, stopvsd, suspendvsd, ucfgvsd

IswImconf Command

Purpose

Lists Workload Manager (WLM) configurations.

Syntax

IswImconf [-r | -s | -c | -d Config] [-l] [-t TimeSpec]

Description

The **IswImconf** command lists by default all WLM configurations and, using its flags, it is able to do the following:

- Tell which is the current configuration or set name.
- · Give the list of all existing regular WLM configurations.
- · Give the list of all existing WLM configuration sets.
- Tell which configuration of a set is (or would be) applicable currently (or at some time of the week).
- · Tell the type of a configuration.

Flags

-c Restricts the displayed configurations to the current configuration or set.
 -d Config Restricts the displayed configurations to the Config configuration or set.

Modifies the way dates are displayed for configuration sets (ineffective for regular

configurations). Sets are displayed with their currently applicable regular configuration, in the

form confset/config.

-r Restricts the displayed configurations to regular configurations only.

-1

-S -t TimeSpec Restricts the displayed configurations to configuration sets only.

Uses TimeSpec instead of the current time to display applicable regular configuration of sets. TimeSpec consists in the day of the week (0 for Sunday to 6 for Saturday) and the time of the day in 24 hours format separated with a comma, in a form similar to time ranges as described in the confsetcntrl command. For example, to know which configuration would apply on Mondays at noon, use -t 1,12:00.

Note: The -t flag is only effective with -I flag.

Examples

The following examples demonstrate how to display, change, and use WLM configurations using the **Iswimconf** command, the **confsetcntrl** command, the **wimcheck** command, and the **wimcntrl** command.

1. To find the WLM configurations, type:

1sw1mconf

The output to this command might look similar to the following:

standard template fytrules fvtlimits fvtregul fvtdfct fvtsynt fvtthreads

2. To show the current WLM configuration, type:

lswlmconf -c

The output might look similar to the following:

fvtlimits

3. To show configuration sets, use the **Iswimconf** with the **-s** flag as follows:

lswlmconf -s

Since this example configuration contains no configuration sets, this command produces a message indicating that no matching configuration was found.

4. In order to create a configuration set using standard as the default configuration, type:

```
confsetcntrl -C confset1 standard
```

5. Now, use the **IswImconf** command to show the new configuration set, as follows:

1sw1mconf -s

The command now produces the following output:

6. In order to use the fvtlimits configuration for confset1 on week days (Monday through Friday) by specifying a time range, type:

```
confsetcntrl -d confset1 -a fvtlimits 1-5
```

7. You might want this configuration only in the morning. You cannot change a time range. Instead you must remove the time range and then create a new time range.

First, remove the old time range, as follows (confsetcntrl accepts day names, as reported by locale day or locale abday commands):

```
confsetcntrl -d confset1 -r fvtlimits monday-friday
```

Then create the new time range, as follows:

```
confsetcntrl -d confset1 -a fvtlimits 1-5,8:00-12:00
```

8. In order to add another time range for using the fvtregul configuration on Sundays, type:

```
confsetcntrl -d confset1 -a fvtregul 0
```

9. In order to display configuration set confset1, type:

```
confsetcntrl -d confset1
```

In this example, this command produces the following output:

```
fvtlimits:
       time = "1-5.8:00-12:00"
fvtregul:
       time = "0"
standard:
       time = "-"
```

10. In order to create a configuration set called confset2 using template as the default configuration,

```
confsetcntrl -C confset2 template
```

In order change confset2 so it will use the configuration fvtsynt every nigh, type:

```
confsetcntrl -d confset2 -a fvtsynt 18:00-10:00
```

11. In order to display the list of regular configurations, type:

```
lswlmconf -r
```

In this example, this produces the following output, (which demonstrates that in this example the list of regular configurations has not changed):

standard template fvtrules fvtlimits fvtregul fytdfct fvtsvnt fvtthreads

However, as expected, the list of configurations sets in this example has changed, as shown by the following command:

```
lswlmconf -s
```

This command produces the following output in this example:

```
confset1
confset2
```

12. In order to show which configuration would be currently active when that the date command reports the current time as Tue Jul 16 18:55:10 EET 2002 with configuration set confset2, type:

```
lswlmconf -d confset2 -l
```

In this example, this command produces the following output:

```
confset2/fvtsynt
```

You can also show which configurations would be active at another time. To show which configurations would be active on Sunday at 9:00am, type:

```
lswlmconf -1 -t 0,9:00
```

This command produces the following output in this example:

```
standard
template
fvtrules
fvtlimits
```

```
fvtregul
fvtdfct
fvtsynt
fvtthreads
confset1/fvtregul
confset2/fvtsynt
```

In order to display this information only for configuration sets, type:

```
lswlmconf -s -1 -t 0.9:00
```

This produces the following output in this example:

```
confset1/fvtregul
confset2/fvtsynt
```

13. In order to remove configuration set confset2, type:

```
confsetcntrl -D confset2
```

IswImconf -s now produces the following output in this example:

14. In order to check configuration set confset1, use the wimcheck command as follows:

```
wlmcheck -d confset1
```

In this example, this produces the following output:

```
WLM is not running.
Checking classes and rules for 'confset1' configuration...
fvtlimits/System
fvtlimits/Default
fvtlimits/Shared
fvtlimits/login
fvtregul/System
fvtregul/Default
fvtregul/Shared
standard/System
standard/Default
standard/Shared
```

15. In order to start using configuration set confset1 used in this example, type:

```
wlmcntrl -a -d confset1
```

The command **IswImconf -c** now produces the following output:

confset1

The command IswImconf -cl, which shows the active regular configuration, now produces the following output:

confset1/standard

Files

The configurations or sets files are subdirectories of /etc/wlm.

Related Information

The wimcntrl command, confsetcntrl command.

Ivmo Command

Purpose

Manages lym pbuf tunable parameters.

Syntax

Ivmo -v Name -o Tunable [=NewValue]

lvmo -a [-v vgname]

Description

The Ivmo command sets or displays pbuf tuning parameters. The equal sign can be used to set a particular tunable to a given value. Otherwise, if no equal sign is used, the value of the tunable will be displayed.

Attention: Misuse of the Ivmo command can cause performance degradation or operating-system failure.

The Ivmo -a command generates pbuf and blocked I/O statistics. The pbuf and blocked I/O report has the following label:

Label	Description
vgname	Volume group name specified with the -v option.
pv_pbuf_count	The number of pbufs that are added when a physical volume is added to the volume group.
total_vg_pbufs	Current total number of pbufs available for the volume group.
max_vg_pbuf_count	The maximum number of pbufs that can be allocated for the volume group.
pervg_blocked_io_count	Number of I/O's that were blocked due to lack of free pbufs for the volume group.
pv_min_pbuf	The minimum number of pbufs that are added when a physical volume is added to any volume group.
global_blocked_io_count	Number of I/O's that were blocked due to lack of free pbufs for all volume groups.

Flags

Displays value for all tunable parameters, one per line in pairs *tunable* = *value*.

-o Tunable [=NewValue] Displays the value or sets Tunable to NewValue.

Tunable Parameters

pv_pbuf_count The number of pbufs that will be added when a physical volume is added to the volume group. The maximum number of pbufs that can be allocated for the volume max_vg_pbuf_count group. Note: The volume group must be varied off and varied on again for this value to take effect. This value will not affect rootvg. pv_min_pbuf The minimum number of pbufs that will be added when a physical volume is added to any volume group. Note: Use the ioo command to change this value.

Exit Status

This command returns zero for successful completion; otherwise it returns nonzero.

Security

You must have root authority to run this command.

Examples

- 1. To display the value for the pv pbuf count, type the following: lvmo -v rootvg -o pv pbuf count
- 2. To set the pv pbuf count value to 2048, type the following: 1vmo -v rootvg -o pv pbuf count=2048
- 3. To generate pbuf and blocked I/O statistics, type the following: lvmo -a

Location

/usr/sbin/lvmo

Related Information

The "ioo Command" on page 90, "Ivmstat Command," vmo command.

Ivmstat Command

Purpose

Reports input/output statistics for logical partitions, logical volumes and volume groups. Also reports pbuf and blocked I/O statistics and allows pbuf allocation changes to volume groups.

Syntax

lvmstat { -I | -v } Name [-e | -d] [-F] [-C] [-c Count] [-s] [Interval [Iterations]]

Description

The **Ivmstat** command generates reports that can be used to change logical volume configuration to better balance the input/output load between physical disks.

By default, the statistics collection is not enabled in the system. You must use the -e flag to enable this feature for the logical volume or volume group in question. Enabling the statistics collection for a volume group enables for all the logical volume in that volume group.

The first report generated by **lvmstat** provides statistics concerning the time since the system was booted. Each subsequent report covers the time since the previous report. All statistics are reported each time lvmstat runs. The report consists of a header row followed by a line of statistics for each logical partition or logical volume depending on the flags specified.

If the -I flag is specified, Name is the logical volume name, and the statistics are for the physical partitions of this logical volume. The mirror copies of the logical partitions are considered individually for the statistics reporting. They are listed in descending order of number of i/os (iocnt) to the partition.

The Interval parameter specifies the amount of time, in seconds, between each report. The first report contains statistics for the time since the volume group startup, varyonvg. Each subsequent report contains statistics collected during the interval since the previous report. If the Count parameter is specified, only the top Count lines of the report are generated. For a logical volume if Count is 10, only the 10 busiest partitions are identified. If the *Iterations* parameter is specified in conjunction with the *Interval* parameter, then only that many iterations are run. If no Iterations parameter is specified, Ivmstat generates reports continuously. If Interval is used to run lymstat more than once, no reports are printed if the statistics did not change since the last run. A single period. (period) is printed instead.

The **Ivmstat** command is useful in determining whether a physical volume is becoming a hindrance to performance by identifying the busiest physical partitions for a logical volume.

Note: The Ivmstat commands reports I/O statistics of the local node only.

Input/Output Reports

The Ivmstat command generates two types of reports, per partition statistics in a logical volume and per logical volume statistics in a volume group. The reports have the following format:

Description Log_part Logical partition number mirror#Log_part Mirror copy number of the logical partition iocntLog_part Number of read and write requests The total number of kilobytes read Kb_readLog_part Kb_wrtnLog_part The total number of kilobytes written KbpsLog_part The amount of data transferred in kilobytes per second

Flags

Column

-c Count	Prints only the specified number of lines of statistics.
-C	Causes the counters that keep track of the iocnt, Kb_read and Kb_wrtn be cleared for the specified logical volume/volume group.
-d	Specifies that statistics collection should be disabled for the logical volume/volume group in question.
-е	Specifies that statistics collection should be enabled for the logical volume/volume group in question.
-F	Causes the statistics to be printed colon-separated.
-I	Specifies the name of the stanza to list.
-s	Suppresses the header from the subsequent reports when <i>Interval</i> is used.
-v	Specifies that the <i>Name</i> specified is the name of the volume group.

Security

To use **lvmstat**, you must have root user authority.

Examples

1. To enable the statistics collection for volume group datavg (all the LVs in datavg are enabled), type:

lvmstat -v datavg -e

2. To display the history of all the partitions of logical volume hd2, type:

lvmstat -1 hd2

3. To display the history of top five logical volumes of volume group uservg, type:

lvmstat -v uservg -c 5

4. To display a continuous report at two second intervals for the logical volume ramly, type:

lvmstat -1 ramlv 2

5. To display six reports at two second intervals for the volume group rootyg, type:

lvmstat -v rootvg 2 6

6. To reset the counters for statistics for all the logical volumes in the volume group uservg, type:

lvmstat -v uservg -C

7. To disable statistics collection for dataly, type:

lvmstat -1 datalv -d

Files

/usr/sbin/lvmstat Contains the Ivmstat command.

Related Information

The knlist subroutine.

The /dev/kmem special file.

m4 Command

Purpose

Preprocesses files, expanding macro definitions.

Syntax

```
m4 [-e] [-I] [-s] [-B Number] [-D Name [= Value]] ... [-H Number] [-I Directory] [-S Number] [-T
Number ] [ -U Name ] ... [ File ... ]
```

Description

The m4 command is a macro processor used as a preprocessor for C and other languages. You can use it to process built-in macros or user-defined macros.

Each File parameter is processed in order. If you do not specify a File parameter or if you specify the -(dash) as a file name, the m4 command reads standard input. It writes the processed macros to standard output. Macro calls follow the form:

```
macroname(argument . . . )
```

The left parenthesis must immediately follow macroname. If the left parenthesis does not follow the name of a defined macro, the m4 command reads it as a macro call with no arguments. Macro names consist of ASCII alphabetic letters, digits, and the (underscore) character. Extended characters are not allowed in macro names. The first character cannot be a digit.

While collecting arguments, the m4 command ignores unquoted leading blanks, tabs, and new-line characters. Use single quotation marks to quote strings. The value of a quoted string is the string with the quotation marks stripped off.

When the **m4** command recognizes a macro, it collects arguments by searching for a matching right parenthesis. If you supply fewer arguments than appear in the macro definition, the m4 command considers the trailing arguments in the definition to be null. Macro evaluation proceeds normally during the collection of the arguments. All commas or right parentheses within the value of a nested call are translated literally; they do not need an escape character or quotation marks. After collecting arguments, the **m4** command pushes the value of the macro back onto the input stream and scans again.

Built-in Macros

The m4 command makes available the following built-in macros. You may redefine them, but you will lose the original meaning. The values of these macros are null unless otherwise stated:

define(Name,NewName)

Replaces the macro Name with the value of NewName. The NewName string can take the form n... (where n is a digit). In this case, each occurrence of n in the replacement text is replaced by the nth argument of Name. \$0 is the name of the macro. The null string replaces missing arguments. The number of arguments replaces \$#. A comma-separated list of all arguments replaces \$*. \$@ acts like \$*, but each argument is quoted with the current quotation character (see changequote).

undefine(Name) defn(Name . . .)

Removes the definition of Name. Returns the quoted definition of Name. pushdef(Name, NewName) Redefines Name with NewName as in define, but saves any previous definition Removes the current definition of Name and returns to the previous popdef(Name . . .) definition, if one existed. ifdef(Name,True,[False]) Returns the value of *True* only if *Name* is defined and is not defined to be 0, otherwise returns False. If you do not supply False, its value is null. Returns all but the first argument. The other arguments are guoted and **shift**(Argument . . .) pushed back with commas in between. The quoting nullifies the effect of the extra scan that is subsequently performed. changequote(L,R) Changes quote symbols to L and R. The symbols can be up to 5 bytes long. changequote without arguments restores the original values (`'). Changes left and right comment markers from the default # and new-line changecom(L,R)character to L and R. With no arguments, the comment mechanism is disabled. With one argument, the left marker becomes the parameter and the right marker becomes a new-line character. With two arguments, both markers are affected. Comment markers can be up to 5 bytes long. divert(Number) Changes the current output stream to stream Number. There are 10 output streams, numbered 0-9. The final output is the concatenation of the streams in numerical order. Initially, stream 0 is the current stream. The **m4** command discards output diverted to a stream other than 0-9. undivert(Number . . .) Causes immediate output of text from the specified diversions (or all diversions if there is no argument). Text may be undiverted into another diversion. Undiverting discards the diverted text. Returns the value of the current output stream. divnum dnl Reads and discards characters up to and including the next new-line character. **ifelse**([String1,String2,True,[False]] . . .) If String1 and String2 are the same then the value is True. If they are not and if there are more than four arguments, the m4 command repeats the process with the additional arguments (4, 5, 6, and 7). Otherwise, the value is either False or null if you provide no value for False. incr(Number) Returns the value of its argument incremented by 1. decr(Number) Returns the value of its argument decreased by 1. Evaluates its first argument as an arithmetic expression, using 32-bit eval(Expression[,Number1[,Number2]]) arithmetic. The operators you can use are +, -, *, /,%, ^ (exponentiation), bitwise &, I, ~, and ^ relationals, and parentheses. Octal and hex numbers can be specified as in C. Number1 specifies the radix for the result of the expression. The default radix is 10. The optional *Number2* specifies the minimum number of digits in the result. len(String) Returns the number of bytes in String. dlen(String) Returns the number of displayable characters in *String*; that is, two-byte extended characters are counted as one displayable character. index(String1,String2) Returns the position in the *String1* string where the *String2* string begins (zero origin), or -1 if the second parameter does not occur. substr(String,Position, [Number]) Returns a substring of *String*. The beginning of the substring is selected with Position, and Number indicates the length of the substring. Without Number, the substring includes everything to the end of the first string. Transliterates the characters in String from the set given by From to the translit(String,From,To) set given by To. No abbreviations are permitted. Two-byte extended characters are correctly mapped into the corresponding replacement characters. include(File) Returns the contents of *File* or displays an error message if it cannot access the file. sinclude(File) Returns the contents of *File*, but it gives no error message if *File* is inaccessible. syscmd(Command) Runs the Command. No value is returned. sysval Returns the return code from the last call to syscmd. maketemp(. . . nnnn . . .) Replaces *nnnn* in its argument with the current process ID number.

m4exit(Value) Exits from m4 immediately, returning the specified exit Value (the default

is 0).

m4wrap(LastMacro) Runs LastMacro after reading the end-of-file character. For example,

m4wrap (`cleanup ()') runs the cleanup macro at the end of **m4**.

errprint(Message) Includes Message on the diagnostic output file.

dumpdef([Name . . .]) Writes to standard output the current names and definitions for the

named items or for all if no arguments are provided.

traceon(Macro) Turns on tracing for Macro. If none is named, tracing is turned on for all

macros.

traceoff(Macro . . .) Turns off trace globally and for any Macro specified. Macros specifically

traced by traceon can be untraced only by specific calls to traceoff.

Flags

-B Number Makes the Number variable the size of the push-back and parameter collection buffers (the

default is 4096).

Operates interactively. Interrupts are ignored and the output is not buffered.

-H *Number* Makes the *Number* variable the size of the symbol table hash array (the default is 199). The

size must be a prime number.

-I Directory (Uppercase i) Searches the Directory variable first, then searches the directories on the

standard list for include (built-in macro) files with names that do not begin with a / (slash).

-I (Lowercase L) Enables line-numbering output for the assembler (.xline . . .).

-s Enables the line-sync output for the C preprocessor (#line . . .).

-S Number Makes the Number variable the size of the call stack (the default is 100 slots). Macros take

three slots, and non-macro arguments take one.

-T *Number* Makes the *Number* variable the size of the token buffer (the default is 512 bytes).

The preceding flags must appear before any file names and before any -D or -U flags.

-D Name[=Value] Defines the Name variable as the Value variable. If the Value variable is not specified,

the Name variable becomes null.

-U Name Undefines a the Name variable previously defined with the **-D** flag.

Exit Status

This command returns the following exit values:

Successful completion.

>0 An error occurred.

If the **m4exit** macro is used, the exit value can be specified by the input file.

Examples

To preprocess a C language program with the **m4** command and compile it, enter:

m4 prog.m4 > prog.c
cc prog.c

Files

/usr/ccs/bin/m4 Contains the m4 command.

Related Information

The m4 Macro Processor Overview in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs.

The Commands in Operating system and device management.

The **as** command, **cc** command, **cpp** command.

mach Command

Purpose

Displays the processor type of the current host .

Syntax

mach

Description

The mach command displays the architecture of the system processor.

Exit Status

- 0 The command completed successfully.
- >0 An error occurred.

Examples

1. To display the processor type of the current host use the mach command in the following way: mach

Files

/usr/bin/mach

Contains the System V mach command.

Related Information

The uname command.

machstat Command

Purpose

Reports the value of the first 4 bits of the power status register.

Syntax

machstat { -p | -f }

Description

The machstat command returns the value of a status register. There is no standard output or error except when using the -f flag on CHRP hardware.

Flags

- On non-CHRP machines, returns Power Status Register bits 10-13. On CHRP machines, displays the EPOW status, EPOW modifier, and, if present, EPOW version.
- Returns the first 4 bits of the power status register. -p

Exit Status

The machstat command returns a value of 255 if an error occurs. Otherwise it returns the value of the register.

Security

Access Control: root only

Examples

To see the current value of the power status register, enter:

```
machstat -p
echo $?
```

Files

/etc/rc.powerfail

Shuts down a system when a power failure is detected

Related Information

The rc.powerfail command.

macref Command

Purpose

Produces a cross-reference listing of macro files.

Syntax

```
macref [ -n ] [ -s ] [ -t ] [ — ] [ File ... ]
```

Description

The macref command reads the named English-language files (which are assumed to be nroff or troff command input) and produces a cross-referenced listing of the symbols in the input.

The default output is a list of the symbols found in the input, each accompanied by a list of all references to that symbol. The macref command lists the symbols alphabetically in the left column, with references following to the right. Each reference is given in the following form:

```
[ [( NMName ) ]
MName- ]
Type LNumber
Γ # ]
```

Generated names are listed under the artificial symbol name ~sym.

Input Parameters

File

Specifies the nroff or troff file from which the macref command produces output containing a list cross-referencing macros.

Output Parameters

NMName The name of the macro within which MName is defined.

MName The name of the macro within which the reference occurs. This field is not present if the reference

occurs outside a macro.

Туре The type associated, by context, with this occurrence of the symbol. The types can be the following:

Request

Macro m

Diversion d

String S

Number register n

Parameter. For instance, $\$ is a parameter reference to x.

Note: Parameters are never modified, and the only valid parameter symbol names are 1, 2, . . .

LNumber

The line number on which the reference occurred.

This reference modifies the value of the symbol.

Flags

-n Causes one line to be printed for each reference to a symbol.

Causes symbol-use statistics to be printed. -S

-t Causes a macro table of contents to be printed.

The flags can be grouped behind one - (minus sign). Use a — (dash) to delimit the end of flags.

Note: The macref command does not accept - as standard input.

Files

/tmp/macref.tXXXXXX Contains a temporary file. /tmp/macref.sXXXXXX Contains a temporary file. /tmp/macref.cXXXXXX Contains a temporary file.

Related Information

The mm command, mmt command, mvt command, nroff command, troff command.

The **man** macro package, **mm** macro package, **mv** macro package.

mail, Mail, or mailx Command

Purpose

Sends and receives mail.

Syntax

To Read Incoming Mail mail -e

```
mail -f [ -dlHNn ] [ -F ] [ FileName ]

mail [ -dlHNn ] [ -F ] [ -u UserID ]

To Send Mail
mail [ -s Subject ] [ -c Address(es) ] [ -dinNv ] Address
```

Description

The mail command invokes the mail utility, enabling you to:

- · Read incoming mail.
- · Send mail.

In addition, you can use the available options and subcommands to customize the way you send and receive mail.

The mail command operates on two types of mailboxes, the system mailbox and the personal mailbox.

Incoming mail is stored in the system mailbox. By default, a user's system mailbox is a file located in the /var/spool/mail directory. The mailbox file is named after the userID. For example, if your user ID is *jeanne*, then your system mailbox is /var/spool/mail/jeanne.

By default, when a user has read, deleted, or saved all the mail in their system mailbox, the mailbox is deleted. To prevent the mailbox from being deleted, use the **set** subcommand to set the **keep** option.

In addition to the system mailbox, there is the user's personal mailbox. As messages are read, if they are not deleted or saved to a file, they will be marked to be moved to the personal mailbox. The personal mailbox, by default, is **\$HOME/mbox**. For example, if your home directory is **/home/lance**, then **/home/lance/mbox** is your personal mailbox. The messages remain in your personal mailbox until you move them to a folder or delete them.

Folders provide a way to save messages in an organized fashion. You can create as many folders as you need. Name each folder with a name that pertains to the subject matter of the messages it contains.

Note: Results can be unpredictable when running multiple instances of the **mail** command on one mailbox.

Examining the Contents of Your Mailbox

To process your mail, type mail at the system prompt. The Mail program displays a one-line entry for each piece of mail in your system mailbox:

```
Mail [5.2 UCB] [AIX 4.1] Type ? for help.
"/var/spool/mail/lance": 2 messages 2 new
>N 1 karen Thu Sep 17 14:36 13/359 "Dept Meeting"
N 2 lance@zeus Thu Sep 17 15:06 10/350 "Delay"
N 3 karen Thu Sep 17 14:36 13/359 "Meeting Cancel"
```

The current message is marked by a > at the beginning of a line in the header summary.

Each one-line entry displays the following fields:

status Indicates the current class of a piece of mail. The status can be any of the following:

N A new message

P A message to be preserved in system mailbox.

U An unread message. An unread message is a message that was listed in the mailbox last time you invoked the Mail program, but whose contents you did not examine.

* A message that was saved or written to a file or folder.

A message without a status indicates that the message has been read but has not been deleted or

saved.

number Identifies the numerical order of the message.

sender Identifies the address of the person who sent the mail.

date Specifies the date the message was received.

size Defines the number of lines and characters contained in the letter (this includes the header).

subject Identifies the subject of the message.

Finally, following the list of mail, the Mail program displays the mailbox prompt, which by default is ?, to indicate that it is waiting for input.

Flags

-c Address(es)	Specifies the list of users to which	a copy of the message is sent.	You can specify one or
0 / 100/000(00)	opodinos trio not or aboro to writer	a copy of the moodage is cont.	rod odii opooliy olio ol

more addresses. When specifying more than one address, the list of addresses must be

in (" ") quotes.

-e Tests for the presence of mail in the system mailbox. The **mail** utility will write nothing

and exit with a successful return code if there is mail to read.

-f FileName Reads messages from the named file. If a file operand is not specified, then reads

messages from mbox. When you quit from reading the messages, undeleted messages

are written back to this file.

-F Records the message in a file named after the recipient. The name is the portion of the

address found first on the To: line in the mail header. Overrides the record variable if set.

-H Writes a header summary only.

-i Causes tty interrupt signals to be ignored.
 -n Inhibits reading the /usr/share/lib/Mail.rc file.

Expands the From User field to 256 characters to handle the long user names.

-N Suppresses the initial printing of headers.

-s Subject Specifies a subject for a message to be created.

-u UserID Specifies an abbreviated equivalent of doing mail -f /var/spool/mail/UserID. Starts the

Mail program for a specified user's mailbox. You must have access permission to the

specified mailbox.

-v Puts the Mail program into verbose mode. Displays the details of delivery on the user's

terminal.

Environmental Variables

The following environment variables affect the execution of mail:

DEAD Pathname of the file in which to save partial messages in case of interrupts or delivery errors.

EDITOR Pathname of the editor to use when the **edit** or **~e** command is used.

HOME Pathname of the user's home directory.

LISTER String representing the command for writing the contents of the folder directory to standard output

when the **folders** command is given. Any string acceptable as a command_string operand to the **sh** -c command is valid. If this variable is null or not set, the output command will be *ls*. The default value is

unset.

MAILBOX Specifies the location of the system mailbox for the mail command. The MAILBOX value is where the

mail command searches for mail messages. The system default value if the MAILBOX environment

variable is not specified is the /var/spool/mail directory.

MAILRC Pathname of your personal startup file. The default is \$HOME/.mailrc.

MBOX Pathname of your personal mailbox where messages are saved from the system mailbox that have

been read. The exit command overrides this function, as will saving the message explicitly in another

file. The default is \$HOME/mbox.

PAGER String representing an output filtering or pagination command for writing the output to the terminal. Any

string acceptable as a command_string operand to the **sh-c** command is valid. When standard output is a terminal device, the message output will be piped through the command if the mail internal variable **crt** is set to a value less the number of lines in the message. If the **PAGER** variable is null or not set,

the paginator is the pg shell command.

SHELL Pathname of a preferred command interpreter.

VISUAL Pathname of a utility to invoke when the visual command or ~v command-escape is used. If this

variable is not set, the full screen editor will be vi.

Internal Variables in Mail

dot

allnet Treats all network names, whose login name components match,

identically. Causes the msglist message specifications to behave

similarly. The default is **noallnet**.

append Adds the message saved in your mailbox to the end, rather than the

beginning, of the **\$HOME/mbox** file. The default is **noappend**.

ask, asksub Prompts for the subject of each message if not specified on the command

line with the **-s** option. If you do not wish to create a subject field, press Enter at the prompt. It is not possible to set both **ask** and **noasksub**, or

noask and asksub. The default is asksub.

askbcc Prompts for the addresses of people to add to the blind copy list. If you

do not wish to send blind copies, press Enter at the prompt.

askcc Prompts for the addresses of people who should receive copies of the

message. If you do not wish to send copies, press Enter at the prompt.

autoprint Sets the delete subcommand to delete the current message and display

the next message.

crt Specifies the minimum number of lines that a message must contain

before any output filtering or pagination is used when the message is

displayed.

debug Displays debugging information. Messages are not sent while in debug

mode. This is the same as specifying the -d flag on the command line. Interprets a period entered on a line by itself as the end of a message

you are sending.

escape=c Sets the command escape character to be the character c. By default the

command escape character is ~ (tilde).

Replyall, flipr Reverses the meanings of the Respond and respond or Reply and

reply commands. The default is noflipr.

folder=*directory*The directory name in which to store mail folders. After the directory is

defined, you can use the + (plus sign) notation to refer to it when using

the FileName parameter with mailbox subcommands.

header Enables writing of the header summary when entering mail in receive

mode. The default is header.

hold Holds messages that you have read but have not deleted or saved in the

system mailbox instead of in your personal mailbox. The default is

nohold.

ignore Ignores interrupts while entering messages. Echoes interrupts as @ (at)

characters.

ignoreeof Sets the mail command to refuse the Ctrl+D key sequence as the end of

a message. Input can be terminated only by entering a period . (period)

on a line by itself or by the ~. command escape. The default is

noignoreeof.

indentprefix=string A string that will be prefixed to each line that is inserted into the message

by the ~m command escape. This variable defaults to one tab character.

keep When a system mailbox, secondary mailbox, or mbox is empty, truncate it

to zero length instead of removing it. The default is nokeep.

keepsave Keep messages that have been saved with the (s)ave or (w)rite

subcommands in the system mailbox instead of deleting them. The

default is nokeepsave.

metoo Includes the sender in the alias expansion if sender's name is part of the

alias. By default, expanding the alias removes the sender.

onehop When responding to a message that was originally sent to several

recipients, the other recipient addresses are usually forced to be relative to the originating author's machine for the response. This flag disables alteration of the recipient's addresses, improving efficiency in a network where all machines can send directly to all other machines (that is, one

hop away). The default is noonehop.

outfolder Causes the files used to record outgoing messages to be located in the

directory specified by the folder variable unless the pathname is absolute.

The default is **nooutfolder**. See the **record** and **folder** variables.

page Insert a form-feed after each message sent through the pipe created by

the pipe command. The default is nopage.

prompt=string Set the command-mode prompt to string. If string is null or if **noprompt** is

set, no prompting will occur. The default is to prompt with the "?" string. Refrain from writing the opening message and version when entering

mail. The default is noquiet.

record=file Defines a file in which to record all outgoing mail. The default is

norecord.

save Enables saving of messages in the dead.letter file on interrupt or delivery

error. The default is save.

screen=number Sets the number of lines in a screenful of headers for the headers and z

commands.

sendmail=shell_command Alternative command for delivering messages.

sendwait Wait for the background mailer to finish before returning. The default is

nosendwait.

showto When the sender of the message was the user who is invoking mail, write

the information from the To: line instead of the From: line in the header

summary. The default is noshowto.

sign=string Inserts string into the text of a message when the ~a command escape is

given. The default is **nosign**. The character sequences /t and /n are recognized in the string as tab and newline characters, respectively.

Sign=string Inserts string into the text of a message when the ~A command escape is

given. The default is noSign.

toplines=number Number of lines displayed by the top subcommand.

verbose Displays the actual delivery of messages on the terminal. This is the

same as specifying the -v flag on the command line.

Setting Environment Variables

The Bourne shell (**bsh** command) uses and checks the following variables. These variables can be set in **\$HOME/.profile**.

MAIL Specifies the location and name of the user's system mailbox that is checked by the Bourne shell

to determine whether or not you have mail. If the system mailbox is not empty, the Bourne shell sends a message that you have new mail. The Bourne shell checks the system mailbox periodically

based on the value of the MAILCHECK environment variable.

MAILCHECK Specifies the interval at which the Bourne shell checks the system mailbox for mail.

MAILMSG Specifies the message sent to your console shell by the system when you have mail. The default

processes in climitary to the following:

message is similar to the following:

YOU HAVE NEW MAIL

quiet

Examples

1. To start the Mail program and list the messages in your mailbox, type the following at the command line prompt:

mail

The mail command lists every messages in your system mailbox. The mail system then displays the mailbox prompt (?) to indicate waiting for input. When you see this prompt, enter any mailbox subcommand. To see a list of subcommands, type:

?

This entry lists the Mail subcommands.

2. To send the message letter to the recipient user1@host1 and copies to user2@host2 and user3@host3, type:

```
mail -c "user2@host2 user3@host3" user1@host1<letter
```

3. To look at the contents of your personal mailbox, type:

mail -f

This command displays a list of the messages in your personal mailbox, \$HOME/mbox.

4. To look at the contents of a specific mail folder, type:

```
mail -f +dept
```

This command displays a listing of the messages in the dept folder.

5. To send a message to a user on your local system, type:

mail ron

When you finish typing the message to user ron, press Enter and press either . (period) or Ctrl+D to exit the editor and send the message. To determine if a user is on your local system, check for the user's name in your /etc/passwd file.

If your message is delivered successfully, you receive no notification. If your message could not be delivered, an error message is sent to you.

6. To mail a file to another user on your local system, type:

```
mail karen < letter1
```

This command sends the contents of the file letter1 to user karen on your local system. After the command sends the file, the Mail program displays the command line prompt.

7. To send a message to a user on a remote system, type:

```
mail dale@zeus
```

You now can create a message to dale. In this example, you are sending a message to user dale on remote system zeus. To send a message to a user on another system connected to your system through a network, you must know that person's login ID and the name of the other system.

Mailbox Subcommands for the mail, Mail, and mailx Command

From the mail prompt, ? (question mark), you can enter subcommands to manipulate mail in your mailbox. Subcommands that work on more than one message at a time use the MessageList parameter. Subcommands that work with files or folders use the FileName parameter. These parameters are discussed in Mail command and subcommands in Networks and communication management.

The following list describes the Mailbox subcommands and their functions:

Echoes the number of the current message.

#

!Command alias

alternates AlternatesList

chdir Directory

copy [MessageList] File

Copy [MessageList]

delete [MessageList]

discard [FieldList]

dp

dt

echo String edit [MessageList]

exit

file [Name]

Comment character for writing comments in mail script files.

Displays the previous message.

Displays a brief summary of mailbox subcommands. Identical to the help subcommand.

Executes the workstation shell command specified by Command.

- (a) With no arguments, displays all currently defined aliases and their corresponding addresses. With one argument, displays one alias. With more than one argument, creates a new alias or changes an old alias. Identical to the group subcommand.
- (alt) The alternates subcommand is useful if you have accounts on several machines. Use the subcommand to inform the Mail program that the addresses listed in AlternatesList all refer to you. When you use the reply subcommand to reply to messages, the Mail program does not send a copy of the message to any of the addresses given in AlternatesList. If you enter the alternates subcommand with no argument, the Mail program displays the current set of alternate names.
- (cd) Changes your working directory to the indicated *Directory*. If no directory is given, it changes to your login directory.
- (c, co) Appends each message in MessageList to the end of File. Displays the file name in quotes, followed by the line count and character count, on the user's terminal. Does not delete any messages when you quit.
- (C) Saves the specified message in a file whose name is derived from the author of the message to be saved, without marking the messages as saved. Otherwise, it is equivalent to the **Save** subcommand.
- (d) Marks the messages in MessageList to be deleted when you guit the Mail program. Entering the d subcommand without a message list deletes the current message. Deleted messages are not saved in your \$HOME/mbox file nor are they available for most other commands. However, you can use the undelete subcommand to restore messages you have deleted while in the same mailbox session. If you delete a message and either change to another mailbox or quit the mailbox with the quit subcommand, the deleted message cannot be recalled.
- (di) Identical to the ignore subcommand.

Note: The **retain** subcommand overrides the **discard** subcommand. Deletes the current message and displays the next message. If there is no

next message, the Mail program displays E0F. Identical to the dt

Deletes the current message and displays the next message. If there is no next message, the Mail program displays E0F. Identical to the dp subcommand.

Displays the character string String on the command line.

- (e) Starts the alternate editor using the *MessageList* as input files. To define an alternate editor, use the set EDITOR= statement or place an entry in your **\$HOME/.mailrc** file. Any message specified by the *MessageList* parameter retains the changes made during the editor session.
- (ex or x) Leaves the mailbox and returns to the operating system without changing the original contents of the mailbox. The mailbox returns to the condition that it was when the Mail program was started. Messages marked to be deleted are not deleted. Identical to the xit subcommand.
- (fi) Identical to the folder subcommand.

folder [Name]

folders

group

followup [message]

from [MessageList]

headers [Message]

Followup [MessageList]

(fo) Switches to a new mail file or folder. With no arguments, the subcommand displays the name of the current mailbox. If an argument is included, it stores the current mailbox with changes (such as messages deleted) and reads in the new mailbox specified by the *Name* parameter. Identical to the **file** subcommand.

Some special conventions are recognized for the *Name*:

- # Refers to the previous file.
- Refers to the system mailbox (/var/spool/mail/UserID).
- & Refers to your personal mailbox (\$HOME/mbox).
- +Name Refers to a file in your folder directory.
 Lists the names of the folders in your folder directory.
 - (fo) Responds to a message, recording the response in a file whose name is derived from the author of the message. Overrides the **record** variable, if set.
 - (**F**) Responds to the first message in the *msglist*, sending the message to the author of each message in the *msglist*. The subject line is taken from the first message and the response is recorded in a file whose name is derived from the author of the first message.
 - (f) Displays the headings of messages in MessageList.
 - (g) Identical to the alias subcommand.
 - (h) Lists the headings in the current group of messages (each group of messages contains 20 messages by default; change this with the **set screen=** statement). If the mailbox contains more messages than can be displayed on the screen at one time, information about only the first group of messages will be displayed. To see information about the rest of the messages, use the h subcommand with a message number in the next range of messages, or use the z subcommand to change the current message group.

Displays a brief summary of mailbox subcommands. Identical to the ? subcommand.

(ho) Marks each message in *MessageList* to be saved in your system mailbox (/var/spool/mail/UserID) instead of in your \$HOME/mbox file. Does not override the delete subcommand. Identical to the preserve subcommand.

help

hold [MessageList]

if Condition else endif Construction for conditional execution of the **mail** subcommands. Subcommands following **if** are executed if *Condition* is true. Subcommands following **else** are executed if *Condition* is not true. The **else** is not required. The **endif** ends the construction and is required. The *Condition* can be receive (receiving mail) or send (sending mail).

ignore [FieldList]

Adds the header fields in *FieldList* to the list of fields to be ignored. Ignored fields are not displayed when you look at a message with either the **type** or **print** subcommand. Use this subcommand to suppress machine-generated header fields. Use either the **Type** or **Print** subcommand to print a message in its entirety, including ignored fields. The **ignore** subcommand with no arguments lists all header fields that are not included when you use a **type** or **print** subcommand to display a message. Identical to the **discard** subcommand.

list (I) Displays a list of all mailbox subcommands with no explanation of what they do.

mail AddressList

(m) Starts the mail editor. Enables you to create and send a message to people specified in *AddressList*. The newly created message is independent from any receive messages.

mbox [MessageList]

Indicates that the messages in MessageList are to be sent to your personal mailbox (\$HOME/mbox) when you quit the Mail program. This operation is the default action for messages that you have read if you are looking at your system mailbox (/var/spool/mail/UserID) and the hold option is not set.

more [MessageList]

(mo) Displays the messages in *MessageList* using the defined pager program to control display to the screen. Identical to the page subcommand.

More [MessageList]

(Mo) Similar to the more subcommand, but also displays ignored header fields.

new [MessageList]

Marks each message in MessageList as not having been read. Identical to the New, unread, and Unread subcommands.

New [MessageList]

Marks each message in *MessageList* as *not* having been read. Identical to the **new**, unread, and Unread subcommands.

next [Message]

(n) Makes the next message in the mailbox the current message and displays that message. With an argument list, it displays the next matching message.

page [MessageList]

(pa) Displays the messages in MessageList using the defined pager program to control display to the screen. Identical to the **more** subcommand.

Page [MessageList]

(Pa) Similar to the page subcommand but also displays ignored header fields.

command]]

pipe [[msglist command]] I [[msglist] (pi) Pipe the messages through the given command by invoking the command interpreter specified by SHELL with two arguments: -c and command. The command must be given as a single argument. This can be accomplished by quoting. If no arguments are given, the current message will be piped through the command specified by the value of the cmd variable. If the page variable is set, a form-feed character will be inserted after each message.

preserve

print [MessageList]

Print [MessageList]

quit

(pre) Identical to the hold subcommand.

- (p) Displays the text of a specific message. Identical to the type subcommand.
- (P) Displays the text of a specific message along with the ignored header fields. Identical to the Type subcommand.
- (q) Leaves the mailbox and returns to the operating system. All messages read, but not deleted or saved are stored in your personal mailbox (\$HOME/mbox). All messages you have marked to be deleted are removed from the mailbox and cannot be recovered. All messages marked with the hold or preserve option and messages you have not viewed are saved in the system mailbox (/var/spool/mail/UserID). If the quit subcommand is given while editing a mailbox file with the -f flag, the edit file is saved with changes. If the edit file cannot be saved, the Mail program does not exit. Use the exit subcommand to exit without saving the changes.
- (r) Allows you to reply to the sender of a message and to all others who receive copies of the message. Identical to the **respond** subcommand.
- (R) Allows you to reply to only the sender of a message. Identical to the Respond subcommand.

Allows you to reply to the sender of a message and to all others who receive copies of a message. Identical to the reply subcommand.

Allows you to reply to only the sender of a message. Identical to the Reply subcommand.

reply [Message]

Reply [Message]

respond [Message]

Respond [Message]

retain [FieldList]

save [File]

save [MessageList] File

Save [MessageList]

set [OptionList | Option=Value...]

shell size [MessageList] source File top [MessageList]

touch [MessageList]

type [MessageList]

Type [MessageList]

unalias

undelete [MessageList]

unread [MessageList]

Unread [MessageList]

unset OptionList

version

Adds the header fields in *FieldList* to the list of fields to be retained. Retained fields are displayed when you look at a message with the **type** subcommand or **print** subcommand. Use this subcommand to define which header fields you want displayed. Use the **Type** or **Print** subcommand to print a message in its entirety, including fields that are not retained. If the **retain** subcommand is executed with no arguments, it lists the current set of retained fields.

Note: The retain subcommand overrides the discard subcommand.

- (s) Saves the current message including header information to a file or folder. If the file already exists, the message is appended to the file. If *File* is omitted, the message will be saved to the user's **mbox**.
- (s) Saves a *MessageList* including heading information to a file or folder. If the file already exists, the *MessageList* is appended to the file. Displays the file name and the size of the file when the operation is complete. If you save a message to a file, that message is not returned to the system mailbox (/var/spool/mail/UserID) nor saved in your personal mailbox (\$HOME/mbox) when you quit the Mail program.
- (S) Saves the specified messages in a file whose name is derived from the author of the first message. The name of the file is taken to be the author's name with all network addressing stripped off.

(se) With no arguments, displays the options that are currently enabled. Otherwise, sets an option as specified. The argument following the set command can be either:

- An OptionList giving the name of a binary option (an option that is either set or unset)
- An Option=Value entry used to assign a value to an option.

The options are listed in the **.mailrc** file format.

Note: The form **unset name** is equivalent to **noname**.

(sh) Starts an interactive version of the shell.

Displays the sizes in lines/characters of the messages in MessageList.

(so) Reads and executes the mail subcommands from File.

Displays the top few lines of the messages specified by *MessageList*. The number of lines displayed is determined by the valued option **toplines** and defaults to five.

Within your system mailbox (/var/spool/mail/UserID), this subcommand marks the messages in MessageList to be moved to your personal mailbox (\$HOME/mbox) when you quit the Mail program. The messages are moved even though you have not read them. The messages are displayed in your personal mailbox as unread messages. The last message in MessageList becomes the current message.

- (t) Displays the text of a specific message. Identical to the **print** subcommand.
- (T) Displays the text of a specific message along with the ignored header fields, Identical to the **Print** subcommand.

Deletes the specified alias names.

- (\mathbf{u}) Removes the messages in *MessageList* from the list of messages to be deleted when you quit the Mail program. Entering the \mathbf{u} subcommand without a message list recalls the last deleted message.
- (U) Marks each message in *MessageList* as *not* having been read. Identical to the **new**, **New**, and **Unread** subcommands.

Marks each message in *MessageList* as *not* having been read. Identical to the **new**, **New**, and **unread** subcommands.

Disables the values of the options specified in *OptionList*. This action is the inverse of the **set** subcommand.

Note: The form **unset name** is equivalent to **noname**.

(ve) Displays the version banner for the Mail program.

visual [MessageList] (v) Starts the visual editor using the MessageList as the input field. (This

editor can be defined with the set VISUAL= statement.) Any changes made

during the editor session are saved back to the messages in the

MessageList.

write [MessageList] File (w) Saves a message without heading information to a file or folder. Displays

the file name and the size of the file when the operation is complete. Does

not include message headers in the file.

xit (x) Identical to the exit subcommand.

> Changes the current message group (group of 20 messages) and displays the headings of the messages in that group. If a + or no argument is given,

then headings in the next group are shown. If a - argument is given, the

headings in the previous group are shown.

Mail Editor Subcommands for the mail, Mail Command

By default, the Mail program treats lines beginning with the ~ (tilde) character as subcommands. The following list describes the subcommands used while in the mail editor. The editor recognizes subcommands only if you enter them at the beginning of a new line.

~? Displays a summary of the mail subcommands.

~!Command The command interpreter specified by **SHELL** will be invoked with two arguments:

-c and command. The standard output of command will be inserted into the

message.

Inserts the value of the sign variable into the text of the message, followed by a ~a

newline character. Identical to ~i sign.

~A Inserts the value of the Sign variable into the text of the message, followed by a

newline character. Identical to ~i Sign.

~b AddressList Adds names in AddressList to the list of addresses to receive blind copies of the

message. The ~b subcommand can only be used to add to, not change or delete,

the contents of the Bcc: List.

~c AddressList Adds names in AddressList to the list of people to receive copies of the message.

The ~c subcommand can only be used to add to, not change or delete, the

contents of the Cc: List.

Appends the contents of the dead.letter file to the end of the message. ~d

Starts the alternate editor using the message text as the input file. (This editor can ~e

> be defined with the set EDITOR= statement in the Bourne shell.) When you exit that editor, you return to the mail editor, where you may add text, or send the

message by exiting the Mail program.

Includes a MessageList in the current message to forward the message to another ~f [MessageList]

> user. This subcommand reads each message in the MessageList and appends it to the current end of the message, but does not indent the appended message. This subcommand is also used to append messages for reference whose margins are too wide to embed with the ~m subcommand. This subcommand works only if you entered the mail editor from the mailbox prompt using either the mail, reply, or

Reply subcommand.

~F [MessageList] Equivalent of the ~f, except that all headers will be included in the message,

regardless of previous discard, ignore, and retain commands.

~h Enables you to add or change information in all of the heading fields. The system

> displays each of the four heading fields, one at a time. You can view the contents of each field and delete or add information to that field. Press the Enter key to save

any changes to the field and to display the next field and its contents.

Inserts the value of the named variable, followed by a newline character, into the ~i string

text of the message. If the string is unset or null, the message will not be changed.

z [+ | -]

~m [MessageList]

Includes a *MessageList* in the current message for reference purposes. This subcommand reads each message in the *MessageList* and appends it to the current end of the message. The included message is indented one tab character from the usual left margin of the message. This subcommand works only if you entered the mail editor from the mailbox prompt using either the **mail**, **reply**, or **Reply** subcommand.

~M [MessageList]

Equivalent of the $\sim\!m$, except that all headers will be included in the message,

regardless of previous discard, ignore, and retain commands.

~p ~q Displays the entire message, including header information.

Quits the editor without sending the message. Saves the message in the **dead.letter** file in your home directory, unless the **nosave** option is set. The previous contents of the **dead.letter** file are replaced with the partially completed message.

Note: You can also quit the editor by using the Interrupt (Ctrl+C) key sequence twice.

~r File

Reads the contents of a file into the current message.

~s String

Changes the subject field to the phrase specified in *String*. You cannot append to

the subject field with this subcommand.

~t AddressList

Adds the addresses in *AddressList* to the To: field of the message. The ~t

subcommand can only be used to add to, not change or delete, the contents of the

To: List.

~V

Starts the visual editor using the message text as the input file. This editor can be defined with the **set VISUAL**= statement in the Bourne shell.) When you exit that editor, you return to the mail editor where you may add text to the message, or send the message by exiting the Mail program.

~w File

Writes the message to the named file.

~X

Exits as with ~q, except the message will not be saved in the dead.letter file.

Executes the subcommand specified by Subcommand and returns to the mail

editor.

~I Command

~: Subcommand

Pipes the message through the command *Command* as a filter. If *Command* gives no output or terminates unusually, it retains the original text of the message. Otherwise, the output of *Command* replaces the current message. The **fmt** command is often used as *Command* to format the message.

~< file

Reads the contents of a file into the current message.

~<!Command

Allows you to run a shell command. The shell runs with the -c flag and the Command specified. The standard output of Command is inserted into the

message

0101

Allows you to use the $^{\sim}$ (tilde) character in a message without it being interpreted as a command prefix. The $^{\sim\sim}$ key sequence results in only one $^{\sim}$ character being sent in the message.

Files

\$HOME/.mailrcContains the **mail** subcommands to customize the Mail program for a

specific user.

\$HOME/mbox Contains your personal mailbox.

/usr/share/lib/Mail.rc Contains the file with mail subcommands to change the Mail program for

all users on the system.

/var/spool/mail/* Contains system mailboxes for all users.

/usr/bin/mailContains the mail command./usr/bin/MailContains the Mail command./usr/bin/mailxContains the mailx command.

Related Information

The **bellmail** command, **fmt** command, **pg** command, **sendmail** command.

The .mailrc file format.

Mail applications, Creating and sending mail, Mail handling and receiving in Networks and communication management.

Reading mail options, Subcommands for replying to mail, Mailbox content display options, Message editing, Mail folders in Networks and communication management.

Mail program customization options, Subcommands for starting the mail editor, Subcommand for displaying lines of a message while in the mail editor, Editing the header information in Networks and communication management.

Checking for misspelling in the mail editor, Message reformats in the mail editor, Text editors for typing messages in Networks and communication management.

Mailbox Subcommands for the mail Command.

mailq Command

Purpose

Prints the contents of the mail queue.

Syntax

/usr/sbin/mailq [-v]

Description

The mailg and MAILQ commands print a list of messages that are in the mail gueue. The first line printed for each message shows:

- The internal identifier used on this host for the message with a possible status character
- · The size of the message in bytes
- · The date and time the message is accepted into the queue
- the envelope sender of the message

The second line shows the error message that caused the message to be retained in the in the queue, it is not displayed if the message is being displayed for the first time. The status characters are either:

- Indicates the job is being processed
- X Indicates that the load is too high to process the job
- Indicates that the job is too young to process

The following lines show message recipients, one per line.

The **mailq** command is the same as the **sendmail -bp** command.

Specify the **-v** flag to display message priority.

Flags

-v Prints verbose information. This adds the priority of the message and a single character indicator (+ or blank) indicating wheather a warning message has been sent on the first line of the message. Additionally, extra lines may be intermixed with the recipents indicating the *controlling user* information; this shows who owns any program that are executed on behalf of this message and the name of the alias this command expanded from, if any.

Exit Status

The command returns the following exit values:

0 Exits successfully.

>0 An error occurred.

Examples

The mailq command prints two types of lists:

• The **mailq** command lists the mail queue as shown in the following example:

```
Mail Queue (1 request)
---QID---- --Size-- ----Q-Time----- ----Sender/Recipient-----
AA02508 3 Thu Dec 17 10:01 root
(User unknown)
bad user
```

• The mailq -v command lists the mail queue as follows:

```
Mail Queue (1 request)
---QID---- --Size-- -Priority- ---Q-Time--- --Sender/Recipient--
AA02508 3 1005 Dec 17 10:01 root

(User unknown)
bad_user
```

The fields have the following meanings:

QID Contains the message queue ID of the message.

Size Contains the number of bytes in the body of the message (heading information not

included).

Priority Contains the priority of the message, based primarily on the size of the message.

Q-Time Contains the time the message entered the queue.

Sender/Recipient Contains the user ID of the sender and the recipient of the message. A message on the

line between the sender and the recipient indicates the status of the message.

Files

/usr/sbin/mailq Contains the mailq command.

/var/spool/mqueue directory Contains the log file and temporary files associated with the messages in

the mail queue.

Related Information

The sendmail command.

Mail queue concepts and tasks in Networks and communication management.

mailstats Command

Purpose

Displays statistics about mail traffic.

Syntax

mailstats [-o][-p] [-C CfFile] [-f StatFile]

Description

The mailstats command displays the current mail statistics. The time at which the statistics started displays reads the information in the format specified by ctime. The statistics for each mailer are displayed on a single line, with the following fields:

Contains the mailer number.

Contains the number of messages received by the local machine from the indicated mailer. msgsfr Contains the number of Kbytes in the messages received by the local machine from the bytes from

indicated mailer.

Contains the number of messages sent from the local machine using the indicated mailer. msqsto bytes_to Contains the number of bytes in the messages sent from the local machine using the

indicated mailer.

msgsrej Contains the number of messages rejected. msgsdis Contains the number of messages discarded.

Contains the name of mailer. Mailer

After the statistics are displayed, a line totaling the value of all of the mailers displays, preceded with a T. This information is separated from the statistics by a line containing only = (equal characters). Another line preceded with a C lists the number of connections.

Flags

-C cfFile Specifies use of the cfFile instead of the default sendmailcf file.

-f StatFile Specifies use of the StatFile instead of the statistics file specified in the sendmail.cf file.

-0 Specifies that the name of the mailer does not display in the output. Outputs information in program readable mode and clears the statistics. -p

Exit Status

Successful completion. >0 An error occurred.

Files

/etc/mail/statistics Default sendmail statistics file. /etc/mail/sendmail.cf Default sendmail configuration file.

Related Information

The mailq command and sendmail command.

Mail queue concepts and tasks in Networks and communication management.

Displaying mailer information, Mailer statistics logs in Networks and communication management.

make Command

Purpose

Maintains, updates, and regenerates groups of programs.

Syntax

make [-D Variable] [-d Option] [-e] [-i] [-j[Jobs]] [-k] [-n] [-p] [-q] [-r] [-S] [-s] [-t] [-f MakeFile ...] [Target ...]

Description

The **make** command assists you in maintaining a set of programs. Input to the **make** command is a list of file dependency specifications.

There are four types of lines in a makefile: file dependency specifications, shell commands, variable assignments, and comments. In general, lines can be continued from one line to the next by ending them with a \ (backslash). The trailing newline character and initial white space on the following line are compressed into a single space.

File Dependency Specifications

Dependency lines consist of one or more targets, an operator, and zero or more prerequisites (sources). This creates a relationship where the targets depend on the prerequisites and are usually created from them. The exact relationship between the target and the prerequisite is determined by the operator that separates them. The operators are as follows:

- A target is considered out-of-date if its modification time is less than that of any of its prerequisites. Prerequisites for a target accumulate over dependency lines when this operator is used. The target is removed if the make command is interrupted, unless the target has the .PRECIOUS attribute.
- If no prerequisites are specified, the target is always recreated. Otherwise, a target is considered out-of-date :: if any of its prerequisites were modified more recently than the target. Prerequisites for a target do not accumulate over dependency lines when this operator is used. The target is not removed if the make command is interrupted.

File dependency specifications have two types of rules, inference and target. Inference rules specify how a target is to be made up-to-date. These rules have one target with no / (slash) and a minimum of one . (period). Target rules specify how to build the target. These rules can have more than one target.

Makefile Execution

The **make** command executes the commands in the makefile line by line. As **make** executes each command, it writes the command to standard output (unless otherwise directed, for example, using the -s flag). A makefile must have a Tab in front of the commands on each line.

When a command is executed through the make command, it uses make's execution environment. This includes any macros from the command line to the make command and any environment variables specified in the MAKEFLAGS variable. The make command's environment variables overwrite any variables of the same name in the existing environment.

Note: When the make command encounters a line beginning with the word include followed by another word that is the name of a makefile (for example, include depend), the make command attempts to open that file and process its contents as if the contents were displayed where the include line occurs. This behavior occurs only if the first noncomment line of the first makefile read by the make command is not the **.POSIX** target; otherwise, a syntax error occurs.

Comments: Comments begin with a # character, anywhere but in a shell command line, and continue to the end of the line.

Environment: The make command uses the MAKEFLAGS environment variable, if it exists.

Target Rules

Target rules have the following format:

target[target...] : [prerequisite...] [;command] <Tab>command

Multiple targets and prerequisites are separated by spaces. Any text that follows the ; (semicolon) and all of the subsequent lines that begin with a Tab character are considered commands to be used to update the target. A new target entry is started when a new line does not begin with a Tab or # character.

Note: The list of prerequisites can be empty.

Special Targets

Special targets cannot be included with other targets; that is, they must be the only target specified. These targets control the operation of the **make** command. These targets are:

.DEFAULT This is used as the rule for any target (that was used only as a prerequisite) that the make

> command cannot figure out any other way to create. Only the shell script is used. The < (left angle bracket) variable of a target that inherits .DEFAULT's commands is set to the target's own name.

.IGNORE Prerequisites of this target are targets themselves: this causes errors from commands associated

with them to be ignored. If no prerequisites are specified, this is the equivalent of specifying the -i

POSIX Causes the make command to use a different default rules file. The file, /usr/ccs/lib/posix.mk,

provides the default rules as specified in the POSIX standard.

.PRECIOUS Prerequisites of this target are targets themselves. .PRECIOUS prevents the target from being

> removed. If no prerequisites are specified, the .PRECIOUS attribute is applied to every target in the file. Usually, when make is interrupted (for example, with SIGHUP, SIGTERM, SIGINT, or SIGQUIT), it removes any partially made targets. If make was invoked with the -n, -p, or -q flags,

the target is considered to have the .PRECIOUS attribute.

.SCCS_GET This special target must be specified without prerequisites. If this special target is included in a

> makefile, the commands associated with this special target are used to get all SCCS files that are not found in the current directory. The default commands that are used to retrieve the source files from SCCS are replaced by the commands associated with this special target. When source files are named in a dependency list, make treats them just like any other target. When a target has no dependencies, but is present in the directory, make assumes that the file is up-to-date. If, however, a SCCS file named SCCS/s.source_file is found for a target source_file, make additionally checks to assure that the target is up-to-date. If the target is missing, or if the SCCS file is newer, make automatically issues the commands specified for the .SCCS_GET special target to retrieve the most recent version. However, if the target is writable by anyone, make does not retrieve a new

.SILENT Prerequisites of the target are targets themselves. This causes commands associated with the

target to not be written to standard output before they are executed. If no prerequisites are

specified, the .SILENT attribute is applied to every command in the file.

.SUFFIXES Use this name to add more suffixes to the list of file suffixes that make recognizes. Prerequisites of the target are appended to the list of known suffixes. If no suffixes are specified, any previously

specified suffixes are deleted. These suffixes are used by the inference rules. To change the order of suffixes, you need to specify an empty .SUFFIXES entry and then a new list of .SUFFIXES

entries. A makefile must not associate commands with .SUFFIXES.

Inference Rules

The **make** command has a default set of inference rules, which you can supplement or overwrite with additional inference rules definitions in the makefile. The default rules are stored in the external file,

/usr/ccs/lib/aix.mk. You can substitute your own rules file by setting the MAKERULES variable to your own file name from the command line. The following line shows how to change the rules file from the command line:

make MAKERULES=/pathname/filename

Inference rules consist of target suffixes and commands. From the suffixes, the make command determines the prerequisites, and from both the suffixes and their prerequisites, the make command determines how to make a target up-to-date. Inference rules have the following format:

rule: <Tab>command

where rule has one of the following forms:

- A single-suffix inference rule that describes how to build a target that is appended with one of the single .s1 suffixes.
- A double-suffix inference rule that describes how to build a target that is appended with .s2 with a .s1.s2 prerequisite that is appended with .s1.

The .s1 and .s2 suffixes are defined as prerequisites of the special target, .SUFFIXES. The suffixes .s1 and .s2 must be known suffixes at the time the inference rule is displayed in the makefile. The inference rules use the suffixes in the order in which they are specified in .SUFFIXES. A new inference rule is started when a new line does not begin with a <Tab> or # character.

If rule is empty, for example:

rule: ;

execution has no effect, and the make command recognizes that the suffix exists, but takes no actions when targets are out-of-date.

A ~ (tilde) in the preceding rules refers to an SCCS file. Therefore, the rule, .c~.o, would transform an SCCS C language prerequisite file into an object file (.o). Because the s. of the SCCS file is a prefix, it is incompatible with the make command's suffix view. The ~ (tilde) is a way of changing any file reference into an SCCS file reference.

Libraries

A target or prerequisite can also be a member of an archive library and is treated as such if there are parentheses in the name. For example, library(name) indicates that name is a member of the archive library library. To update a member of a library from a particular file, you can use the format .s1.a, where a file with the .s1 suffix is used to update a member of the archive library. The .a refers to an archive library.

Using Macros

In makefiles, macro definitions are defined in the format:

variable=value

Macros can be displayed throughout the makefile, as follows:

- If a macro is displayed in a target line, it is evaluated when the target line is read.
- · If a macro is displayed in a command line, it is evaluated when the command is executed.
- · If a macro is displayed in a macro definition line, it is evaluated when the new macro is displayed in a rule or command.

If a macro has no definition, it defaults to NULL. A new macro definition overwrites an existing macro of the same name. Macros assignments can come from the following, in the listed order:

1. Default inference rules

- 2. Contents of the environment
- 3. Makefiles
- 4. Command lines.

Note: The -e flag causes environment variables to override those defined in the makefile.

The SHELL macro is special. It is set by the make command to the path name of the shell command interpreter (/usr/bin/sh). However, if it is redefined in the makefile or on the command line, this default setting is overridden.

Note: The SHELL macro does not affect, and is not affected by the SHELL environment variable.

Shell Commands

Each target can have associated with it a series of shell commands, usually used to create the target. Each of the commands in this script must be preceded by a Tab. While any target can be displayed on a dependency line, only one of these dependencies can be followed by a creation script, unless the :: operator is used.

If the first, or first two characters, of the command line are one or all of @ (at sign), - (hyphen), and + (plus sign), the command is treated specially, as follows:

- @ Causes the command not to be echoed before it is executed.
- Causes any nonzero exit status of the command line to be ignored.
- Causes a command line to be executed, even though the options -n, -q, or -t are specified.

A command that has no metacharacters is directly executed by the make command. For example, the make command consigns the first command in the following example to the shell because it contains the > (greater than sign) shell metacharacter. The second command in the following example does not contain any shell metacharacters, so the make command executes it directly:

```
target: dependency
       cat dependency > target
        chmod a+x target
```

Bypassing the shell saves time, but it can cause problems. For example, attempting to execute a C shell script from within a makefile by setting the SHELL macro to /bin/csh will not work unless the command line also contains at least one shell metacharacter.

```
SHELL=/bin/csh
target: dependency
        my_csh_script
```

This makefile fails because the make command attempts to run my_csh_script instead of consigning it to the C shell.

Variable Assignments

Variables in the **make** command are much like variables in the shell and consist of all uppercase letters. The = operator assigns values to variables. Any previous variable is then overridden. Any white space before the assigned value is removed.

Values can be appended to macro values as follows:

```
macro += word ...
macro += macro1
```

The += operator when used in place of = appends the new value with a single space is inserted between the previous contents of the variable and the appended value.

Variables are expended by surrounding the variable name with either { } (braces) or () (parentheses) and preceding it with a \$ (dollar sign). If the variable name contains only a single letter, the surrounding braces or parentheses are not required. This shorter form is not recommended.

Variable substitution occurs at two distinct times, depending on where the variable is being used. Variables in dependency lines are expanded as the line is read. Variables in shell commands are expanded when the **shell** command is executed.

The four classes of variables (in order of increasing precedence) are:

Environment Global Command line Local

Variables defined as part of the **make** command's environment. Variables defined in the makefile or in included makefiles.

Variables defined as part of the command line.

Variables defined specific to a certain target. The local variables are as follows:

- \$< Represents either the full name of a prerequisite that made a target out-of-date (inference rule), or the full name of a target (.DEFAULT rule).
- \$* Represents the file name section of a prerequisite that made a target out-of-date (in an inference rule) without a suffix.
- \$@ Represents the full target name of the current target or the archive file name part of the library archive target.
- **\$**% Represents a library member in a target rule if the target is a member of the archive library.

You can also use these local variables appended with **D** or **F**:

- Indicates that the local variable applies to the directory part of the name. This is the path name prefix without a trailing / (slash). For current directories, **D** is a . (period).
- **F** Indicates that the local variable applies to the file name part of the name.

In addition, the **make** command sets or knows about the following variables:

A single \$ (dollar sign); that is, \$\$ expands to a single dollar sign.

Determines the locale to use for the locale categories when both LC_ALL and the corresponding environment variable (beginning with LC_) do not specify a locale.

Determines the locale to be used to override any values for locale categories specified by the setting of **LANG** or any other **LC**_ environment variable.

Determines the locale for the interpretation of sequences of bytes of text data as characters;

for example, single- versus multibyte characters in arguments.

Determines the language in which messages should be written.

The environment variable, MAKEFLAGS, can contain anything that can be specified on make's command line. Anything specified on make's command line is appended to the MAKEFLAGS variable, which is then entered into the environment for all programs that make executes. Note that the operation of the -f and -p flags in the MAKEFLAGS variable is undefined. Command line flags take precedence over the -f and -p flags in this variable. Allows you to specify a list of directories to search for prerequisites. The list of directories works like the PATH variable in the SHELL. The VPATH variable can specify multiple directories separated by colons. For example:

VPATH=src:/usr/local/src

This tells the **make** command to search for the following directories in the order given:

- The current directory (this happens even without VPATH)
- src (a subdirectory in the current directory)
- /usr/local/src.

\$

LANG

LC ALL

LC_CTYPE

LC_MESSAGES
MAKEFLAGS

VPATH

Flags

-DVariable -dOption	Sets the value of <i>Variable</i> to 1. Displays detailed information about the files and times that make examines (debug mode). The -d flag without any options or with the <i>A</i> option displays all the debug information available. Individually selectable debug options follow:
	A Displays all possible debug information.
	a Displays debug information about archive searching and caching.
	d Displays debug information about directory searching.
	g1 Displays debug information about input graph before making anything.
	g2 Displays debug information about input graph after making everything, or before exiting on an error.
	m Displays debug information about making targets, including modification dates.
	s Displays debug information about suffix searching.
-е	 Displays debug information about variable assignments. Specifies that environmental variables override macro assignments within makefiles.
-f MakeFile	Specifies a makefile to read instead of the default makefile. If <i>MakeFile</i> is - (hyphen), standard input is read. Multiple makefiles can be specified and are read in the order specified.
-i	Ignores nonzero exit of shell commands in the makefile. Equivalent to specifying - (hyphen) before each command line in the makefile.
-j[Jobs]	Specifies the number of parallel jobs that make should use to build the independent targets. The <i>Jobs</i> parameter can take any positive integral values. If <i>Jobs</i> is not specified, make does not limit the number of parallel jobs for building the main target. For more information, see Using the make Command in Parallel Execution Mode in the make Command Overview section in <i>AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs</i> .
-k	Continues processing after errors are encountered, but only on those targets that do not depend on the target whose creation caused the error.
-n	Displays commands, but does not run them. However, lines beginning with a + (plus sign) are executed.
-p	Displays the complete set of macro definitions and target descriptions before performing any commands.
-q	Returns a zero status code if the target file is up-to-date; returns a one status code if the target file is not up-to-date. Targets will not be updated when this option is specified. However, a command line with the + (plus sign) prefix will be executed.
-r	Does not use the default rules.
-S	Terminates the make command if an error occurs. This is the default and the opposite of -k flag.
-S	Does not display commands on the screen as they are performed.
-t	Creates a target or updates its modification time to make it seem up-to-date. Executes

Specifies a target name of the form *Target* or sets the value of variables.

Exit Status

Target

When the -q flag is specified, this command returns the following exit values:

command lines beginning with a + (plus sign).

- 0 Successful completion.
- The target was not up-to-date. 1
- >1 An error occurred.

Otherwise, this command returns the following exit values:

0 Successful completion. >1 An error occurred.

Examples

- 1. To make the first target found in the makefile, type:
- 2. To display, but not run, the commands that the make command would use to make a file:

```
make -n search.o
```

Doing this will verify that a new description file is correct before using it.

3. To create a makefile that says that **pgm** depends on two files, **a.o** and **b.o**, and that they, in turn, depend on their corresponding prerequisite files (**a.c** and **b.c**) and a common file, **incl.h**, type:

```
pgm: a.o b.o c89 a.o b.o -o pgm a.o: incl.h a.c c89 -c a.c b.o: incl.h b.c c89 -c b.c
```

4. To make optimized .o files from .c files, type:

```
.c.o:

c89 -c -o $*.c

or:

.c.o:

c89 -c -o $<
```

5. To view the contents of the built-in rules, type:

```
make -p -f /dev/null 2>/dev/null
```

6. To use the **make** command in parallel mode with a maximum of 10 parallel jobs to be used for building the target specified in the makefile, type:

```
make -j10
```

Files

makefileContains a list of dependencies.MakefileContains a list of dependencies.

s.makefileContains a list of dependencies. It is an SCCS file.s.MakefileContains a list of dependencies. It is an SCCS file./usr/ccs/lib/posix.mkContains default POSIX rules for the make command.

/usr/ccs/lib/aix.mk Contains default rules for the make command.

Related Information

The sh command.

The make Command Overview in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs.

The Commands in *Operating system and device management*.

makedbm Command

Purpose

Makes a Network Information Services (NIS) database map.

Syntax

To Create an NIS Map

/usr/sbin/makedbm [-b][-i NISInputFile][-o NISOutputFile][-d NISDomainName][-m NISMasterName | InputFile OutputFile

To Create a Non-dbm Formatted NIS Map

/usr/sbin/makedbm [-u dbmFileName]

Description

The **makedbm** command makes an NIS map. It does this by converting the file named in the *InputFile* parameter into two output files: OutputFile.pag and OutputFile.dir. Each line in each input file is converted into a single Data Base Manager (DBM) record.

The makedbm command is most often invoked from the /var/yp/Makefile file to generate NIS maps. All characters leading up to the first space or tab in each line of the /var/yp/Makefile file form the key. The rest of the line contains value data. If a line ends with a \ (backslash), data for that record is continued on the next line. NIS clients must interpret the # (pound sign) symbol since the makedbm command does not treat it as a comment character. If the *InputFile* parameter is a - (minus sign), the **makedbm** command reads standard input instead.

This command generates a special entry in the output map by using the YP LAST MODIFIED key, which is the date that the file specified by the InputFile parameter was created (or the current time, if the InputFile parameter is a - (minus sign)).

Flags

- -b Propagates a map to all servers using the **named** name server.
- -i Creates a special entry with the YP_INPUT_FILE key.
- Creates a special entry with the YP_OUTPUT_FILE key. -0
- -d Creates a special entry with the YP_DOMAIN_NAME key.
- Creates a special entry with the YP_MASTER_NAME key. -m
- Undoes a DBM file. That is, prints out a DBM file one entry per line, with a single space separating keys from -u values.

Files

/var/yp/Makefile

Contains rules for making NIS maps.

Related Information

The **vpinit** command, **vppush** command.

Network Information Services (NIS) Overview for System Management in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide.

Network File System (NFS) Overview for System Management in Networks and communication management.

How to Create a Non-Standard NIS Maps in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide.

List of NDBM and DBM Programming References in AIX 5L Version 5.3 Communications Programming Concepts.

NIS Reference in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide.

makedepend Command

Purpose

Create dependencies in makefiles.

Syntax

makedepend [-DName=Def] [-DName] [-IncludeDir] [-YIncludeDir] [-a] [-fMakeFile] [-oObjSuffix] [-pObjPrefix] [-sString] [-wWidth] [-v] [-m] [—Options—] SourceFile ...

Description

The makedepend command reads each SourceFile in sequence and parses it like a C-preprocessor. It processes all #include, #define, #undef, #ifdef, #ifndef, #endif, #if, and #else directives to determine which #include directives need to be used in a compilation. Any #include directives can reference files having other #include directives, and parsing occurs in these files as well.

Every file that a SourceFile includes, directly or indirectly, is what makedepend calls a "dependency." These dependencies are then written to a makefile in such a way that the make command can determine which object files must be recompiled when a dependency has changed.

By default, makedepend places its output in the file named makefile if it exists, otherwise Makefile. An alternate makefile may be specified with the -f flag. makedepend first searches the available makefile for the line:

```
# DO NOT DELETE THIS LINE - make depend depends on it.
```

or one provided with the -s flag, as a delimiter for the dependency output. If it finds the line, it deletes everything following the line to the end of the makefile and puts the output after the line. If makedepend does not find the line, it appends the delimited string to the end of the makefile and places the output immediately after the string.

For each SourceFile appearing on the command line, makedepend puts lines in the makefile in the following form.

```
SourceFile.o: dfile ...
```

Where SourceFile.o is the name from the command line with its suffix replaced with .o, and dfile is a dependency discovered in an #include directive while parsing the SourceFile or one of the files it included.

The algorithm used in this command assumes that all files compiled by a single makefile will be compiled with roughly the same -I and -D flags, and that most files in a single directory will include largely the same files.

Given these assumptions, makedepend expects to be called once for each makefile, with all source files that are maintained by the make file appearing on the command line. It parses each source and include file only once, maintaining an internal symbol table for each. As a result, the first file on the command line takes an amount of time proportional to the amount of time that a normal C preprocessor takes. On subsequent files, if it encounters an include file that it has already parsed, it does not parse again.

For example, imagine you are compiling two files, file1.c and file2.c, each includes the header file header.h. The header.h file includes the files def1.h and def2.h. When you run the command: makedepend file1.c file2.c

then makedepend will first parse file1.c and consequently, header.h and then def1.h and def2.h. It then decides that the dependencies for this first file are:

file1.o: header.h def1.h def2.h

But when the program parses the second file, file2.c and discovers that it, too, includes header.h, it does not parse the file, but simply adds header.h, def1.h and def2.h to the list of dependencies for file2.o.

Note: If you do not have the source for cpp (the Berkeley C preprocessor), then makedepend will compile in such a way that all #if directives will evaluate to False, regardless of their actual value. This may cause the wrong #include directives to be evaluated. In these cases, it is recommended that you write a new parser for #if expressions. The need for a new parser should be clear from the following example:

Imagine you are parsing two files file1.c and file2.c, each includes the file def.h. The list of files that def.h includes might be very different when def.h is included by file1.c than when it is included by file2.c. But once makedepend arrives at a list of dependencies for a file, it is cast in concrete.

Flags

Note: The makedepend command ignores flags it does not understand. Flag usage is similar to that of the cc command.

-DName=Def or -DName	Places a definition for the <i>Name</i> variable in the makedepend command's symbol table. Without the <i>=Def</i> specifier, the symbol is defined as 1.
-IIncludeDir	Prepends the <i>IncludeDir</i> variable to the list of directories searched by the makedepend command when it encounters an #include directive. By default, the makedepend command searches only the /usr/include directory.
-Y IncludeDir	Replaces all of the standard include directories with a single specified include directory, you can omit <i>IncludeDir</i> to prevent searching the standard include directories.
-a	Appends the dependencies to the end of the file instead of replacing them.
-fMakeFile	Enables you to specify an alternate makefile in which to place command output.
-o ObjSuffix	Specifies an object suffix. For example, some systems may have object files whose suffix is something other than .o. This flag allows you to specify another suffix, such as ".b" with -o.b or ":obj" with -o.obj and so forth.
-p ObjPrefix	Prepends the object file prefix to the name of the object file. This flag is used to designate a different directory for the object file. The default is the empty string.
-sString	Specifies the starting string delimiter. This flag permits you to specify a different string for makedepend to search for in the makefile.
-w Width	Changes the maximum line width of output lines. The default maximum is 78 characters.
-V	Causes makedepend to display a list of files included by each input file on standard input.
-m	Causes makedepend to display a warning if any input file includes another file more than once. In previous version of makedepend this was the default behavior. This flag is provided for backward compatibility and to aid in debugging problems related to multiple inclusion.

—Options—

Ignores any unrecognized argument contained within a beginning and ending double hyphen. When **makedepend** encounters a double hyphen (—) in the argument list, any unrecognized argument following it is silently ignored; a second double hyphen terminates this treatment. The double hyphens enable **makedepend** to safely ignore esoteric compiler arguments that might normally be found in a CFLAGS **make** command macro (see the Examples section). All flags that **makedepend** recognizes and that appear between the pair of double hyphens are processed normally.

Examples

Normally, **makedepend** will be used in a makefile target so that typing makedepend updates the dependencies for the makefile.

```
SRCS=file1.c file2.c ...
CFLAGS=-0 -DHACK -I../foobar -xyz
depend:
    makedepend -- $(CFLAGS) -- $(SRCS)
```

Related Information

The cc command, make command.

makedev Command

Purpose

Creates binary description files suitable for reading by the troff command and its postprocessors.

Syntax

makedev DESC | FontFile ...

Description

The **makedev** command creates binary files suitable for reading by the **troff** command and its postprocessors. When the **DESC** file is specified, the **makedev** command creates a **DESC.out** file and a set of font description files using the information contained in the **DESC** file. When a font file is specified, the **makedev** command creates the corresponding font description file.

Options

DESC Causes a **DESC.out** file to be created.

Parameters

FontFile Causes a FontFile.out file to be created.

Examples

The following command:

makedev B

creates a **B.out** file, which contains the font tables for the Times-Bold fonts.

Related Information

The troff command.

The troff Font File Format.

makekey Command

Purpose

Generates an encryption key.

Syntax

makekey

Description

The **makekey** command generates an encryption key for use with programs that perform encryption. Its input and output are usually pipes.

The makekey command reads 10 characters from standard input and writes 13 characters to standard output. The first 8 of the 10 input characters can be any sequence of ASCII characters, as specified by the ASCIICharacters parameter. The last two input characters, called the salt, are chosen from the sets 0 through 9, a through z, A through Z, . (period), and / (slash). The salt characters are repeated as the first two characters of the output. The remaining 11 output characters are chosen from the same set as the salt and constitute the output key that you use as the encryption key parameter of programs that perform encryption.

Examples

1. To generate an encryption key for input string 1234567890, type the following:

\$ makekev 1234567890

Then press the Ctrl-D key. The following encryption key is generated, and the \$ (shell prompt) follows immediately after the generated key on the same line:

90y744T/NXw1U\$

2. To allow **makekey** to accept input strings through pipe, type the following command:

```
$ echo 1234567890 | makekey
```

3. To allow makekey to accept input strings from a file, type the following command:

```
$ cat infile
1234567890
$ makekey < infile</pre>
```

Alternatively, you can type the following command:

```
$ cat infile | makekey
```

Related Information

The crypt, encrypt, or setkey subroutine.

makemap Command

Purpose

Creates database maps for sendmail.

Syntax

makemap [-C -N -c CacheSize -d -e -f -l -o -r -s -u -v] Maptype Mapname

Description

The makemap command creates the database maps used by the keyed map lookups in the sendmail command. It reads input from the standard input and outputs them to the indicated Mapname.

Parameters

Maptype Depending upon how it is compiled, this command handles up to three different database

formats:

dbm DBM format maps. This requires the **ndbm** library.

btree B-tree format maps. This requires the new Berkeley DB library. hash Hash format maps. This requires the new Berkeley DB library.

Note: In all cases, this command reads lines from the standard input, consisting of two words separated by white space. The first is the database key, the second is the value. The value may contain "%n" strings to indicate parameter substitution. Literal percents should

be doubled ("%%"). Blank lines and lines beginning with a "#" are ignored.

Mapname Name of the map.

Flags

-c CacheSize -C -d	Specifies to use the hash and B-tree cache size. Indicates to use the specified sendmail configuration file for looking up the TrustedUser option. Allows duplicate keys in the map. This is only allowed on B-Tree format maps. If two identical keys are read, they are both inserted into the map.
-е	Allows empty values, right hand side.
-f	Disables the function of folding all upper case letters in the key to lowercase. This is intended to mesh with the -f flag in the K line in the sendmail.cf file. The value is never case folded.
-1	Lists supported map types.
-N	Includes the Null byte that terminates strings in the map. This must match the -N flag in the sendmail.cf "K" line.
-0	Specifies to append to an existing file. This allows you to augment an existing file.
-r	Allows replacement of existing keys. Normally, the makemap command complains if you repeat a key and does not perform the insert.
-s	lignores safety checks on maps being created. This includes checking for hard or symbolic links in world writeable directories.
-u	Dumps, unmaps, the contents of the database to standard output.
-v	Specifies that the command verbosely print its status.

Related Information

The sendmail command.

man Command

Purpose

Displays manual entries online.

Syntax

```
man [ [ [ -c ] [ -t ] [ section ] ] | [ -k | -f ] ] [ -F ] [ -m ] [ -Mpath ] [ -r ] [ -a ] title ...
```

Description

The man command provides reference information on topics, such as commands, subroutines, and files. The man command provides one-line descriptions of commands specified by name. The man command also provides information on all commands whose descriptions contain a set of user-specified keywords.

The man command formats a specified set of manual pages. If you specify a section for the section parameter, the man command searches in that section of the manual pages for the title specified by the title parameter. The value of the section parameter can be either an Arabic number from 1 through 8 or a letter.

The section letters are:

- C Specifies commands (including system management commands).
- F Specifies file-type manual pages.
- Specifies library functions. L
- n Specifies new.
- Specifies local.
- Specifies old. 0
- Specifies public. р

Note: The n, I, o, and p section specifiers are not valid for reading the hypertext information bases, which contain the operating system documentation.

The section numbers are:

- 1 Indicates user commands and daemons.
- 2 Indicates system calls and kernel services.
- 3 Indicates subroutines.
- 4 Indicates special files, device drivers, and hardware.
- 5 Indicates configuration files.
- 6 Indicates games.
- 7 Indicates miscellaneous commands.
- 8 Indicates administrative commands and daemons.

Note: The operating system documentation in the hypertext information databases is grouped into three sections only: command manual pages (in section 1, equivalent to section C), subroutine manual pages (in section 3, equivalent to section L), and file manual pages (in section 4, equivalent to section F). When searching for hypertext information, specifying section 1, 6, 7, or 8 will default to the command manual pages, section 2 or 3 will default to the subroutine manual pages, and section 4 or 5 will default to the file manual pages.

If the section parameter is omitted, the man command searches all sections of the manual.

The search path the man command uses is a list of directories separated by a: (colon) in which manual subdirectories can be found. The MANPATH environment variable value is used for the default path. The MANPATH environment variable is not valid when reading the hypertext information bases.

The **man** command displays the manual pages as follows:

- 1. The man command searches the nroff directories (man?) under the /usr/share/man directory.
- 2. The man command searches the formatted version directories (cat?) under the /usr/share/man directory. If the formatted version is available, and if it has a more recent modify time than the nroff command source, the man command displays the formatted version. Otherwise, the manual page is formatted with the nroff command and displayed. If the user has permission, the formatted manual page is deposited in the proper place, so that later invocations of the man command do not format the page again.

Note: There is no nroff source for the supplied manual pages. However, you can put nroff source for manual pages into the man directories and the man command can locate and process the nroff source.

- 3. If the man command does not find a manual page in the /usr/share/man/man or /usr/share/man/cat directory, the man command searches the paths specified through -M option or MANPATH environment variable for nroff directories (man?) and formatted version directories (cat?).
- 4. If the man command does not find a manual page in the /usr/share/man/man or /usr/share/man/cat or the user-specified man/cat directory, the man command reads from the hypertext information bases. The hypertext information bases reside in the /usr/share/man/info directory structure and contain the operating system documentation. When reading from the hypertext databases, the man command does not put any manual pages in the /usr/share/man/cat directory structure. The man command converts the HTML file into a formatted text file to fit on the display, and displays the manual page using the command described by the PAGER environment variable.
- 5. If the man command does not find a manual page in the hypertext information bases residing in the /usr/share/man/info directory structure, it looks for user-specified hypertext information base (through -M or MANPATH). The user-defined hypertext information base, should follow the following directory structure:

BasePath[/%{ L | 1 }]/DocLibraryname/Section/command or routine or filename.htm

Where:

- %L represents the ISO language notation specified using the LC_MESSAGES, %1 represents the first 2 characters of the ISO language notation specified using the LC MESSAGES. For example, for LC MESSAGES=en US the documents can be placed in Path/en US or Path/en.
- DocLibraryname represents the name of the documentation library.
- Section represents the section name, which must be one of the following:
 - cmds Represents Commands Section
 - libs Represents Library Section
 - files Represents Files Section

Note: If -m option is specified, then the search for manual pages will be done only in the order of paths specified through -M or the MANPATH environment variable.

When accessing the HTML databases, man looks for the operating system library before it proceeds to other LPP libraries. Within these libraries, it processes information in the following order:

Commands Reference cmds libs Subroutines, System Calls

Files Reference files

If the standard output is a tty, the man command pipes its output using the more command with the -s and -v flags. The -s flag eliminates multiple blank lines and stops after each page on the screen. The -v flag suppresses the display of nonprinting characters to the screen. To continue scrolling, press the space bar. To scroll an additional 11 lines when the output stops, press the Ctrl-D key sequence.

The **PAGER** environment variable can be set to whatever pager is desired. The default value is the **more** command. To change the default pager, enter:

PAGER=Somepager export PAGER

For example, if there are customized manual pages which are formatted with reverse or fractional line feeds, the PAGER environment variable may be set to /usr/bin/pg so that the line feeds are not printed as control characters. This procedure is not necessary for the manual pages.

When the man command uses a hypertext database, it can retrieve several articles. For example, man open displays several articles. The use of SIGINT (Ctrl-C) exits the man command completely. On the other hand, man open close also displays several articles but the use of SIGINT (Ctrl-C) causes man to display the close command information instead of exiting. Using SIGINT (Ctrl-C) again exits the man command completely.

When specifying one of the Network Computing System library routines that contains a \$ (dollar sign) in its name, enter a \ (backslash) preceding the \$.

Flags

-k

-Mpath

Display all matching entries. -a

Displays the manual information using the cat command. -C

-f Displays entries in the keyword database related only to the command name given as the final parameter. You can enter more than one command name, each separated by a space. Use this flag to search for command articles only. To use the -f flag, a root user must have previously entered catman -w to create the /usr/share/man/whatis file.

-F Display only the first matching entry.

> Displays each line in the keyword database that contains a string of characters matching the title given as the final parameter. You can enter more than one title, each separated by a space. To use the -k flag, a root user must have previously entered catman -w to create the /usr/share/man/ whatis file.

Only search in the paths specified in MANPATH or -M. -m

> Changes the standard location where the man command searches for manual information. The path is a colon-separated list of paths, where the following special symbols can be used:

- %D The default AIX paths for man pages.
- · %L A locale-specific directory location corresponding to the LC_MESSAGES category of the current locale.
- · %I A locale-specific directory location corresponding to the first 2 characters of the LC_MESSAGES category of the current.

- Searches remotely for the manual information. If for any reason the remote search fails, then man -r performs a local search for the requested man page. Any of the following conditions can cause the remote search to fail:
 - · The remote machine is not reachable.
 - · There is a problem reading the URL.
 - · Java is not installed or it is not found in the user's search path, specified in the PATH environment variable.

Note: The DOCUMENT_SERVER_MACHINE_NAME environment variable should be set to the name of the documentation search server machine the user wants to use. If the AIX Base Documentation is not supported for the host's locale, the man command searches for the documentation for an alternate locale. If the search is successful, the documentation page is displayed after conversion to the local host's locale. If the alternate locale is not installed on the local host, the man command fails to display the documentation page.

-t Formats the manual information using the troff command. This flag is ignored if the manual page is found in a hypertext information base.

Exit Status

This command returns the following exit values:

- Successful completion.
- >0 An error occurred.

Examples

1. To display information about the **grep** command, enter:

2. To display information about the **rpc \$register** library routine, enter:

```
man rpc \$register
```

3. To display all entries in the /usr/share/man/whatis keyword database that contain the "mkdir" string, enter:

```
man -k mkdir
```

The output is equivalent to the apropos command. You receive output from the -k flag only when the /usr/share/man/whatis keyword database already exists.

4. To display all entries from the keyword database related to the **nroff** and **troff** commands, enter:

```
man -f nroff troff
```

The output is equivalent to the whatis command. You receive output from the -f flag only when the /usr/share/man/whatis keyword database already exists.

5. To display all **ftp** command related articles in the **/usr/share/man** or **/usr/share/man/local** path, enter:

```
man -M/usr/share/man:/usr/share/man/local ftp
```

6. To display all matching entries, type the following:

```
man —a title
```

7. To display only the first matching entry, type the following:

```
man -F title
```

8. To search only in the paths specified in MANPATH or -M, type the following:

```
man -m -M PATH title
```

9. To search in the user-defined PATH, type the following:

```
man -M PATH title
```

Files

/usr/bin/man Contains the man command. /usr/share/man Standard manual directory structure. /usr/share/man/cat?/* Directory containing preformatted pages.

/usr/share/man/whatis Contains the keyword database.

/usr/share/man/man?/* Directory containing **nroff** format manual pages.

Related Information

The apropos command, catman command, more command, whatis command, whereis command.

managefonts Command

Purpose

Provides the user with a simple menu-based interface to update or change the set of installed font families on the system.

Note: You must have root user authority to run the managefonts script. The managefonts script is contained in the /usr/lib/ps/ditroff.fonts/managefonts file.

Syntax

managefonts [Option]

Description

The managefonts command provides the user with a simple menu-based interface to update or change the set of installed font families on the system. If no command line arguments are provided, the menu-based interface is used. Command-line arguments can be used to provide the equivalent of the menu selections.

A set of font families is installed on the system at the time the TranScript Tools option of the Text Formatter Services Package is installed on the system. This default setup includes the standard 13 fonts comprising the Times, Courier, and Helvetica font families. You can use the program called up by the managefonts command to erase the current configuration and replace it with a new one. There are several predefined packages of font families that can be installed this way:

Times Family Only This is the most minimal configuration that allows the TranScript Tools option to

Standard13 Package This package builds the Times, Courier, and Helvetica font families. This was the

package installed on your system with TranScript.

This font family package includes the Standard13 package font families in Standard35 Package

addition to the following: Avant Garde, Bookman, New Century Schoolbook, and

Palatino font families.

All Font Families This package installs all the font families available for installation.

You can also use the managefonts command to add new font families one at a time. A menu of available fonts is displayed and users can select which font family they want to be built. The program prevents building of font families that are already installed.

The managefonts command includes help screens to assist the user in installing font families.

Notes:

- 1. Font families cannot be deleted directly. To delete font families, it is first necessary to install a package containing the minimal subset of families desired. After the package is installed, it is possible to add font families, one at a time, from the Individual Fonts Menu. For instance, if your current configuration is Times, Courier, and Helvetica, and you want only Times and Courier, you can use the managefonts program to install the Times Only Package.
- 2. There is no command-line syntax equivalent to the menu items in the managefonts program.

The command line arguments are acted upon in the order they are given, reading left to right. The following are the valid values for the option parameter and their meanings:

init0 Initialize for the installation of a font package.

clean Remove all temporary files and previously installed fonts.

Remove all the temporary files, the previously installed fonts, and the TranScript troff cleanall

font files installed.

Install the Standard 13 fonts. default standard13 Install the Standard 13 fonts. standard35 Install the Standard 35 fonts. all Install all possible fonts. CourierFamily Install the Courier Family. **HelveticaFamily** Install the Helvetica Family.

HelvNarrowFamily Install the Helvetica Narrow Family. **AvantGardeFamily** Install the Avant Garde Family. Install the Bookman Family. BookmanFamily GaramondFamily Install the Garamond Family. LubalinFamily Install the Lubalin Family. **NewCenturyFamily** Install the New Century Family. **OptimaFamily** Install the Optima Family. **PalatinoFamily** Install the Palatino Family. SouvenirFamily Install the Souvenir Family. ZapfFamily Install the Zapf Family.

BaseFamily Install the Base Family, such as Times Roman.

Examples

1. To install the standard 13 fonts:

managefonts cleanall standard13

2. To install the standard 35 fonts:

managefonts cleanall standard35

3. To install all the fonts:

managefonts cleanall all

4. To install the Courier Family (the Times Roman or Base Family must have been previously installed): managefonts init0 CourierFamily clean

Related Information

The enscript command, ps630 command, psrev command, ps4014 command, psdit command, psplot command.

mant Command

Purpose

Typesets manual pages.

Syntax

mant [-M Media] [-a] [-c] [-e] [-t] [-z] [-T Name] [troffFlags] [File ... | -]

Description

The mant command uses the manual page macros (man macro package) to typeset manual pages. The File parameter specifies the files to be processed by the mant command. Files must be displayed after all flags. If no file name is specified, the mant command prints a list of its flags. If a - (minus sign) is specified for the File parameter, standard input is read.

The mant command has flags to specify preprocessing by the tbl command, cw command, or eqn command. Flags from the **troff** command can be specified with the *troffFlags* parameter.

If the input contains a troff command comment line consisting solely of the string '\" x (single quotation mark, backslash, double quotation mark, x), where x is any combination of the three letters c, e, and t, and where there is exactly one character space between the double quotation mark and x, then the input is processed through the appropriate combination of the cw command, eqn command, and tbl command, respectively, regardless of the command-line options.

Note: Use the -oList flag of the troff command to specify ranges of pages to be output. Calling the mant command with one or more of the -c flag, -e flag, and - (minus) flags together with the -oList flag of the troff command, give a broken pipe message if the last page of the document is not specified by the List variable. This broken pipe message is not an indication of any problem and can be ignored.

The mant command, unlike the troff command, automatically pipes its output to a specific postprocessor, according to the following flags, environment variable, or default setting unless specifically requested not to do so:

Indicates that no postprocessors are used. -Z

-TName Prepares the output for the printing device specified by the *Name* variable.

TYPESETTER Specifies a particular printing device for the system environment.

default Sends to ibm3816.

Flags, other than the ones in the following list, are passed to the troff command or to the macro package, as appropriate. All flags must be displayed before the specified file names.

Flags

All flags must appear before the specified file names.

- -a Calls the -a flag of the troff command.
- Preprocesses the input files with the **cw** command. -C
- -6 Preprocesses the input files with the eqn command.

-M Media Specifies a paper size in order to determine the amount of imageable area on the paper. Valid values

for the Media variable are:

Α4 Specifies a paper size of 8.3 X 11.7 inches (210 X 297 mm).

A5 Specifies a paper size of 5.83 X 8.27 inches (148 X 210 mm).

B5 Specifies a paper size of 6.9 X 9.8 inches (176 X 250 mm).

Specifies a paper size of 7.25 X 10.5 inches (184.2 X 266.7 mm).

LEGAL Specifies a paper size of 8.5 X 14 inches (215.9 X 355.6 mm).

LETTER

Specifies a paper size of 8.5 X 11 inches (215.9 X 279.4 mm). This is the default value.

Note: The Media variable is not case-sensitive.

-t Preprocesses the input files with the tbl command.

Prepares the output without the postprocessor.

-TName Prepares the output for the specified printing device. Possible Name variables are:

ibm3812

3812 Pageprinter II.

ibm3816

3816 Pageprinter.

hpli Hewlett-Packard LaserJet II.

ibm5587G

5587-G01 Kanji Printer multi-byte language support.

psc PostScript printer.

X100 AlXwindows display.

Forces input to be read from standard input.

Related Information

The cw command, eqn command, nroff command, tbl command, tc command, troff command.

mark Command

Purpose

Creates, modifies, and displays message sequences.

Syntax

mark [+Folder] [-list] [-sequence Name [Messages...] [-add | -delete] [-zero | -nozero] [-public | -nopublic]]

Description

The mark command creates, deletes, adds, and lists messages in a sequence. The mark command by default lists all of the sequences and their messages for the current folder. If you use the -add or -delete flag, you must also use the **-sequence** flag. When all messages are deleted from a sequence, the mark command removes the sequence name from the folder.

To create a new sequence, enter the **-sequence** flag with the name of the sequence you want to create. The mark command creates the sequence starting with the current message. By default, the mark command places the sequence in the current folder. If you specify a folder, that folder becomes the current folder.

Flags

-add Adds messages to a sequence. The -add flag is the default. If you do not specify a

message, the mark command uses the current message.

Note: You can only use this flag with the -sequence flag.

Deletes messages from a sequence. If you do not specify a message, the current -delete

message is deleted by default.

Note: You can only use this flag with the -sequence flag.

+Folder Specifies the folder to examine.

-help Lists the command syntax, available switches (toggles), and version information.

Note: For MH, the name of this flag must be fully spelled out.

-list Displays the messages in a sequence. By default, the -list flag displays all the sequence

names and messages defined for the current folder. To see a specific sequence, use the

-sequence flag with the -list flag.

Restricts a sequence to your usage. The -nopublic flag does not restrict the messages in -nopublic

the sequence, only the sequence itself. This option is the default if the folder is

write-protected from other users.

Modifies the sequence by adding or deleting only the specified messages. This flag is the -nozero

default.

-public Makes a sequence available to other users. The -public flag does not make protected

messages available, only the sequence itself. This flag is the default if the folder is not

write-protected from other users.

Specifies a sequence for the -list, -add, and -delete flags. You cannot use new as a -sequence Name

sequence name.

Clears a sequence of all messages except the current message. When the -delete flag is -zero

also specified, the -zero flag places all of the messages from the folder into the sequence

before deleting any messages.

Specifies messages in a sequence. You can specify more than one message at a time. Messages

Messages are identified with following references:

Number

Number of the message

all All the messages in a folder

cur or . (period)

Current message (the default)

first First message in a folder

last Last message in a folder

new New messages in a folder

next Message following the current message

prev Message preceding the current message

If the -list flag is used, the default for the Messages parameter is all. Otherwise, the default is the current message.

Profile Entries

The following entry is found in the *UserMHDirectory*/context file:

Current-Folder: Specifies the default current folder. The following entry is found in the **\$HOME/.mh_profile** file:

Path: Specifies the MH directory.

Examples

1. To see the list of all sequences defined for the current folder, enter:

mark

The system displays a message similar to the following:

cur: 94 test: 1-3 7 9

In this example, message 94 is the current message number in the current folder. The message sequence called test includes message numbers 1, 2, 3, 7, and 9.

2. To see the list of all the sequences defined for the meetings folder, enter:

```
mark +meetings
```

The system displays a message similar to the following:

cur: 5 dates: 12 15 19

3. To create a new message sequence called schedule in the current folder, enter:

```
mark -sequence schedule
```

The system displays the shell prompt to indicate that the schedule sequence was created. By default, the system adds the current message to the new sequence.

4. To delete message 10 from the schedule sequence, enter:

```
mark -sequence schedule 10 -delete
```

Files

\$HOME/.mh_profile Specifies the MH user profile. /usr/bin/mark Contains the mark command.

Related Information

The pick command.

The **mh_alias** file format, **mh_profile** file format.

Mail applications in *Networks and communication management*.

mesg Command

Purpose

Permits or refuses write messages.

Syntax

mesg [n | y]

Description

The **mesg** command controls whether other users on the system can send messages to you with either the **write** command or the **talk** command. Called without arguments, the **mesg** command displays the current workstation message-permission setting.

The shell startup process permits messages by default. You can override this default action by including the line mesg n in your **\$HOME/.profile** file. A user with root user authority can send write messages to any workstation, regardless of its message permission setting. Message permission has no effect on messages delivered through the electronic mail system (**sendmail**).

If you add mesg y to your **\$HOME/.profile**, you will be able to receive messages from other users via the **write** command or the **talk** command.

If you add mesg n to your **\$HOME/.profile**, you will not be able to receive messages from other users using the **write** command or the **talk** command.

Flags

- n Allows only the root user the permission to send messages to your workstation. Use this form of the command to avoid having others clutter your display with incoming messages.
- y Allows all workstations on the local network the permission to send messages to your workstation.

Exit Status

This command returns the following exit values:

- **0** Receiving messages is allowed.
- Receiving messages is not allowed.
- >1 An error occurred.

Examples

1. To allow only the root user the permission to send messages to your workstation, enter:

```
mesg n
```

2. To allow everyone the permission to send messages to your workstation, enter:

```
mesg y
```

3. To display what your current message-permission setting is, enter:

mes

Information similar to the following is displayed:

```
is y
```

In the previous example, the current message-permission setting is y (allowing all users on the local network the permission to send messages to your workstation). If you change the message-permission setting to n (allowing only the root user the permission to send messages to your workstation), information similar to the following is displayed:

```
is n
```

Files

/dev/tty* Supports the controlling terminal interface. \$HOME/.profile Controls startup processes and daemons.

Related Information

The **sendmail** command, **talk** command, **write** command.

Communications and networks in Networks and communication management.

mhl Command

Purpose

Produces formatted listings of messages.

Syntax

mhl [-form FormFile] [-folder +Folder] [-moreproc Command | -nomoreproc [-bell | -nobell] [-clear | -noclear | | [-length Number | [-width Number |

Description

The mhl command creates formatted lists of messages. The command is usually started through the showproc: profile entry or through the -showproc flag in other MH commands. When displaying messages, the mhl command uses the directions listed in the format file. If you specify more than one message, the **mhl** command provides a prompt before displaying each screen of messages.

If the -nomoreproc flag is specified, the mhl command prompts the user to press the Return key (the Ctrl-D key sequence is also acceptable) to see the next message. To stop the current message output and receive a prompt for the next message, press the Ctrl-D key sequence. Press the QUIT key sequence to stop the command output.

Note: To use the mhl command, you must make the folder you wish to work with the current directory.

Flags

-length Number

-bell	Produces a bell at the end of each page. When the -nomoreproc flag is specified or the moreproc: profile entry is defined, but empty, the -bell flag is the default.
-clear	Clears the screen after each page when the output device is a display. The mhl command uses the \$TERM environment variable to determine the type of display. When the output device is not a display, the -clear flag inserts a form feed character at the end of each message. This flag affects the mhl command only if the moreproc: profile entry is defined and empty.
-folder +Folder	Identifies the folder to be used for the mhl.format file's MessageName: entry. The default is the value of the \$mhfolder environment variable.
-form FormFile	Specifies a file containing an alternate output format. The default format is described in the <i>UserMHDirectory</i> /mhl.format file. If this file does not exist, the mhl command uses the system default format described in the /etc/mh/mhl.format file.
-help	Lists the command syntax, available switches (toggles), and version information.
	Note: For MH, the name of this flag must be fully spelled out.

Sets the screen length for the output. The default is the value indicated by the **\$TERM** environment variable. If that value is not appropriate, the default is 40 lines.

Uses the value of the Command variable instead of the value of the moreproc: -moreproc Command

entry specified in the \$HOME/.mh_profile file.

Suppresses the bell at the end of each page. This flag affects the mhl command -nobell

only if the output device is a display, the -nomoreproc flag is used, or the

moreproc: profile entry is defined and empty.

Prevents clearing of the screen at the end of each page when the output device is -noclear

> a display. When the output device is not a display, the -clear flag does not insert a form-feed character at the end of each message. This flag is the default when the

-moreproc flag is used or the moreproc: entry is defined and is empty.

Sets the moreproc: entry as an empty value. -nomoreproc

Sets the screen width for the output. The default is the value indicated by the -width Number

\$TERM environment variable. If that value is not appropriate, the default is 80

characters.

Profile Entries

The following entry is found in the *UserMHDirectory*/.mh profile file:

moreproc: Specifies the interactive program for communicating with the user.

Examples

1. To list message 5 in the **inbox** folder, change the directory to **inbox**:

cd /home/mickey/Mail/inbox

Then enter:

/usr/lib/mh/mhl 5

A display similar to the following appears:

--- Using template MHL.FORMAT ---

Date:

To: cc:

From:

Subject:

Message Text

2. To display more than one message, enter:

/usr/lib/mh/mhl 5 6 7

Files

\$HOME/.mh profile Contains the MH user profile.

/etc/mh/mhl.format Defines the default MH message template.

UserMHDirectory/mhl.format Specifies a user's default message template. (If it exists, it

overrides the default MH message template.)

/usr/lib/mh/mhl Contains the mhl command.

Related Information

The ap command, dp command, next command, prev command, show command.

The **mh_alias** file format, **mh_profile** file format.

mhmail Command

Purpose

Sends or receives mail.

Syntax

```
mhmail User ... [ -cc User ... ] [ -from User ... ] [ -subject "String" ] [ -body "String" ]
```

Description

The **mhmail** command composes, sends, and files messages. To file a message, enter the **mhmail** command without any flags. The default folder is **\$HOME/inbox**.

If you specify one or more user addresses with the *User* parameter, the **mhmail** command accepts text from your terminal and composes a message. You can end the message text by pressing the Ctrl-D key sequence. The **mhmail** command sends a copy of the message to each specified address.

Flags

-body "String"	Sends a message with the specified string as the body. You must enclose the string in quotes. When you specify the -body flag, the mhmail command does not accept text from the terminal.
-cc User	Sends a copy of the message to the specified users. The mhmail command puts the addresses in the cc: field.
-from User	Places the specified user address in the From: field of the message.
-help	Lists the command syntax, available switches (toggles), and version information.
	Note: For MH, the name of this flag must be fully spelled out.
-subject "String"	Places the specified text string in the Subject: field of the message.

Examples

 To receive new mail and file it into the default mail folder, \$USER/Mail/inbox, enter: mhmail

The system displays a message similar to the following:

In this example, two messages are filed in the inbox file. The subject of the first message is Meeting, and the first line starts with the words The meeting will. The subject of the second message is Schedule, and the first line starts with the words Schedule change.

2. To send a message regarding a schedule change to user jamie on system venus, enter:

```
mhmail jamie@venus -subject "Schedule Change"
```

The system waits for you to enter the text of the message. After completing the last line of the text, press the Enter key and then the Ctrl-D key sequence to send the message.

Files

/var/spool/Mail/\$USER /usr/bin/mhmail

Defines the location of the mail drop. Contains the mhmail command.

Related Information

The inc command, post command.

The mh_alias file format, mh_profile file format.

Mail applications in Networks and communication management.

mhpath Command

Purpose

Prints full path names of messages and folders.

Syntax

mhpath [+Folder] [Messages [,Messages] ...]

Description

The mhpath command lists the path names of folders and messages. By default, the command lists the path name of the current folder.

Flags

+Folder Specifies which folder path to list.

-help Lists the command syntax, available switches (toggles), and version information.

Note: For MH, the name of this flag must be fully spelled out.

Messages

Specifies the messages for which you want to list path names. The *Messages* parameter can specify several messages, a range of messages, or a single message. Use the following references to specify messages.

Number

Number of the message. When specifying multiple messages, separate each message number with a comma. When specifying a range of messages, separate the upper and lower ends of the range with a hyphen.

Note: You cannot use the **new** variable when specifying a range.

Sequence

A group of messages specified by the user. Recognized values include:

all All the messages in a folder.

cur or . (period)

Current message.

first message in a folder.

last Last message in a folder.

new Path name that the system will assign to the next message that is incorporated.

next Message following the current message.

prev Message immediately before the current message.

Profile Entries

The following entries are entered in the UserMhDirectory/.mh_profile file:

Current-Folder: Sets the default current folder.
Path: Specifies a user's MH directory.

Examples

1. To list the path name of the current folder, enter:

mhpath

The system responds with a message similar to the following:

/home/tom/Mail/inbox

2. To list the path names for messages 2 through 4 in the **source** folder, enter:

```
mhpath +source 2-4
```

The system responds with a message similar to the following:

/home/tom/Mail/source/2 /home/tom/Mail/source/3 /home/tom/Mail/source/4

3. To list the path name the system will assign to the next message added to the current folder, enter:

mhpath new

The system responds with a message similar to the following:

/home/tom/Mail/source/5

In this example, the next message will be message 5 in user tom's current folder, /home/tom/Mai1/ source.

Files

\$HOME/.mh_profile Defines the user's MH profile. /usr/bin/mhpath Contains the **mhpath** command.

Related Information

The folder command.

The **mh_alias** file format, **mh_profile** file format.

Mail applications in *Networks and communication management*.

migratelp Command

Purpose

Moves allocated logical partition from one physical partition to another physical partition on a different physical volume.

Syntax

migratelp LVname/LPartnumber[/Copynumber] DestPV[/PPartNumber]

Description

The migratelp moves the specified logical partition LPartnumber of the logical volume LVname to the DestPV physical volume. If the destination physical partition PPartNumber is specified it will be used, otherwise a destination partition is selected using the intra region policy of the logical volume. By default the first mirror copy of the logical partition in question is migrated. A value of 1, 2 or 3 can be specified for Copynumber to migrate a particular mirror copy.

Notes:

- 1. You must consider the partition usage, reported by Ivmstat, on the other active concurrent nodes in case of a concurrent volume group.
- 2. Strictness and upper bound settings are not enforced when using migratelp.

The **migratelp** command fails to migrate partitions of striped logical volumes.

Security

To use migratelp, you must have root user authority.

Examples

- 1. To move the first logical partitions of logical volume Iv00 to hdisk1, type: migratelp lv00/1 hdisk1
- 2. To move second mirror copy of the third logical partitions of logical volume hd2 to hdisk5, type: migratelp hd2/3/2 hdisk5
- 3. To move third mirror copy of the 25th logical partitions of logical volume testly to 100th partition of hdisk7, type:

migratelp testlv/25/3 hdisk7/100

Files

/usr/sbin

Directory where the migratelp resides.

Related Information

The **Islv** command, and **Ivmstat** command.

The Logical volume storage in the Operating system and device management.

migratepy Command

Purpose

Moves allocated physical partitions from one physical volume to one or more other physical volumes.

Syntax

migratepv [-i] [-l LogicalVolume] SourcePhysicalVolume DestinationPhysicalVolume...

Description

The migratepy command moves allocated physical partitions and the data they contain from the SourcePhysicalVolume to one or more other physical volumes. To limit the transfer to specific physical volumes, use the names of one or more physical volumes in the DestinationPhysicalVolume parameter; otherwise, all the physical volumes in the volume group are available for the transfer. All physical volumes must be within the same volume group. The specified source physical volume cannot be included in the list of *DestinationPhysicalVolume* parameters.

Notes:

- 1. To use this command, you must either have root user authority or be a member of the **system** group.
- 2. The migratepy command is not allowed on a snapshot volume group or a volume group that has a snapshot volume group.

The allocation of the new physical partitions follows the policies defined for the logical volumes that contain the physical partitions being moved.

The migratepy command (only when the source and target physical volumes are specified) fails when a boot logical volume is found on the source physical volume. When you migrate a physical volume, the boot logical volume must remain intact. Two contiguous physical partitions and the new boot image must be built on the new boot logical volume.

If you specify a logical volume that contains the boot image, the migratepv -I command attempts to find enough contiguous partitions on one of the target physical volumes. If the migration is successful, the migratepy command prints a message that recommends the user run the bosboot command to indicate a change in the boot device. The attempted migration fails if the migratepv -I command is unable to find enough contiguous space to satisfy the request.

Note: All Logical Volume Manager migrate functions work by creating a mirror of the logical volumes involved, then resynchronizing the logical volumes. The original logical volume is then removed. If the **migratepy** command is used to move a logical volume containing the primary dump device, the system will not have an accessible primary dump device during the execution of the command. Therefore, a dump taken during this execution may fail. To avoid this, reassign the primary dump device using the sysdumpdev command or ensure there is a secondary dump device defined before using migratepv.

You can use the Volumes application in Web-based System Manager (wsm) to change volume characteristics. You could also use the System Management Interface Tool (SMIT) smit migratepv fast path to run this command.

Note: For concurrent mode volume groups migratepv can only be used while active in enhanced concurrent mode or active in concurrent mode on SSA disks.

Flags

Reads the *DestinationPhysicalVolume* parameter from standard input.

Moves only the physical partitions allocated to the specified logical volume and -I LogicalVolume

located on the specified source physical volume.

Examples

1. To move physical partitions from hdisk1 to hdisk6 and hdisk7, enter:

migratepv hdisk1 hdisk6 hdisk7

Physical partitions are moved from one physical volume to two others within the same volume group.

2. To move physical partitions in logical volume 1v02 from hdisk1 to hdisk6, enter:

migratepv -1 lv02 hdisk1 hdisk6

Only those physical partitions contained in 1v02 are moved from one physical volume to another.

Files

/usr/sbin Directory where the migratepv command resides.

/tmp Directory where the temporary files are stored while the command is running.

Related Information

The cplv command, Islv command.

Migrating the contents of a physical volume in Operating system and device management.

Logical volume storage in Operating system and device management.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

System management interface tool in *Operating system and device management*.

System Dump Facility in AIX 5L Version 5.3 Kernel Extensions and Device Support Programming Concepts.

mirrorvg Command

Purpose

Mirrors all the logical volumes that exist on a given volume group.

Syntax

mirrorvg [-S | -s] [-Q] [-c Copies] [-m] VolumeGroup [PhysicalVolume ...]

Description

The mirrorvg command takes all the logical volumes on a given volume group and mirrors those logical volumes. This same functionality may also be accomplished manually if you execute the mklvcopy command for each individual logical volume in a volume group. As with mklvcopy, the target physical drives to be mirrored with data must already be members of the volume group. To add disks to a volume group, run the extendvg command.

By default, mirrorvg attempts to mirror the logical volumes onto any of the disks in a volume group. If you wish to control which drives are used for mirroring, you must include the list of disks in the input parameters, *PhysicalVolume*. Mirror strictness is enforced. Additionally, **mirroryg** mirrors the logical volumes, using the default settings of the logical volume being mirrored. If you wish to violate mirror strictness or affect the policy by which the mirror is created, you must execute the mirroring of all logical volumes manually with the **mklycopy** command.

When mirrorvg is executed, the default behavior of the command requires that the synchronization of the mirrors must complete before the command returns to the user. If you wish to avoid the delay, use the -S or -s option. Additionally, the default value of 2 copies is always used. To specify a value other than 2, use the **-c** option.

Restriction:

- To use this command, you must either have root user authority or be a member of the system group.
- You cannot use the **mirrorvg** command on a snapshot volume group.

Attention: The mirrorvg command may take a significant amount of time before completing because of complex error checking, the amount of logical volumes to mirror in a volume group, and the time is takes to synchronize the new mirrored logical volumes.

You can use the Volumes application in Web-based System Manager (wsm) to change volume characteristics. You could also use the System Management Interface Tool (SMIT) smit mirrorvg fast path to run this command.

Flags

-Q Quorum Keep

Specifies the minimum number of copies that each logical volume must have after -c Copies the mirrorvg command has finished executing. It may be possible, through the independent use of mklvcopy, that some logical volumes may have more than the minimum number specified after the mirrorvg command has executed. Minimum value is 2 and 3 is the maximum value. A value of 1 is ignored. Allows mirroring of logical volumes in the exact physical partition order that the -m exact map original copy is ordered. This option requires you to specify a Physical Volume(s) where the exact map copy should be placed. If the space is insufficient for an exact mapping, then the command will fail. You should add new drives or pick a different set of drives that will satisfy an exact logical volume mapping of the entire volume group. The designated disks must be equal to or exceed the size of the drives which are to be exactly mirrored, regardless of if the entire disk is used. Also, if any logical volume to be mirrored is already mirrored, this command will fail.

> By default in mirrorvg, when a volume group's contents becomes mirrored, volume group quorum is disabled. If the user wishes to keep the volume group quorum requirement after mirroring is complete, this option should be used in the command. For later quorum changes, refer to the chvg command.

-S Background Sync Returns the mirrorvg command immediately and starts a background syncvg of

the volume group. With this option, it is not obvious when the mirrors have completely finished their synchronization. However, as portions of the mirrors become synchronized, they are immediately used by the operating system in

mirror usage.

-s Disable Sync Returns the mirrorvg command immediately without performing any type of mirror synchronization. If this option is used, the mirror may exist for a logical volume

but is not used by the operating system until it has been synchronized with the

syncvg command.

The following is a description of **rootvg**:

rootvg mirroring When the rootvg mirroring has completed, you must perform three additional

tasks: bosboot, bootlist, and reboot.

The bosboot command is required to customize the bootrec of the newly mirrored drive. The **bootlist** command needs to be performed to instruct the system which

disk and order you prefer the mirrored boot process to start.

Finally, the default of this command is for Quorum to be turned off.

When this volume group has been mirrored, the default command causes Quorum

to be deactivated.

rootvg and non-rootvg mirroring The system dump devices, primary and secondary, should not be mirrored. In

some systems, the paging device and the dump device are the same device. However, most users want the paging device mirrored. When mirrorvg detects that a dump device and the paging device are the same, the logical volume will be

mirrored automatically.

If mirrorvg detects that the dump and paging device are different logical volumes, the paging device is automatically mirrored, but the dump logical volume is not. The dump device can be queried and modified with the **sysdumpdev** command.

Examples

non-rootvg mirroring

1. To triply mirror a volume group, enter:

mirrorvg -c 3 workvg

The logical partitions in the logical volumes held on workvg now have three copies.

2. To get default mirroring of rootvg, enter:

mirrorvg rootvg

rootvg now has two copies.

3. To replace a bad disk drive in a mirrored volume group, enter

unmirrorvg workvg hdisk7 reducevg workvg hdisk7 rmdev -1 hdisk7 -d replace the disk drive, let the drive be renamed hdisk7 extendvg workvg hdisk7 mirrorvg workvg

Note: By default in this example, mirrorvg will try to create 2 copies for logical volumes in workyg. It will try to create the new mirrors onto the replaced disk drive. However, if the original system had been triply mirrored, there may be no new mirrors created onto hdisk7, as other copies may already exist for the logical volumes.

4. To sync the newly created mirrors in the background, enter:

```
mirrorvg -S -c 3 workvg
```

5. To create a second and third copy of the logical volumes within datavg, where the physical partition maps on each disk match each other exactly, enter:

```
mirrorvg -m -c 3 datavg hdisk2 hdisk3
```

The logical partitions in the logical volumes held on datavg now have three copies.

Files

/usr/sbin

Directory where the mirrorvg command resides.

Related Information

The mklvcopy command, unmirrorvg command, syncvg command, extendvg command, reducevg command, sysdumpdev command.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

The Logical volume storage in *Operating system and device management*.

mirscan Command

Purpose

Search for and correct physical partitions that are stale or unable to perform I/O operations.

Syntax

strictness] [-u upperbound]

Description

The mirscan command examines each allocated partition on the specified device. A report is generated that lists whether the partition is stale or fresh, and lists whether it is capable of performing I/O operations. The LVM device driver is queried to determine whether the partition is stale or fresh. Regardless of whether the partition is stale or fresh, it is read to determine whether it is capable of performing I/O operations. By default the entire partition is read, but if the -q flag is specified, the nblks value determines how much of the partition will be read. If the -a flag is not specified, the report is printed and execution ends after all partitions are read.

If the -a flag is used, corrective action is taken after all the partitions have been examined. Stale partitions will be synced. If a partition is not capable of performing I/O, mirscan attempts to trigger bad block relocation or hardware relocation with a forced sync operation, which should write a good copy of the data to the block that is incapable of performing I/O operations. If the partition is still unreadable, the mirscan command attempts to migrate that partition to a new location. By default, the new location that is selected adheres to the strictness and upperbound policies for the logical volume that contains the partition. Using the -s flag causes the strictness value specified on the command line to override the natural strictness value of the logical volume that contains the partition. Similarly, using the -u flag causes the upperbound value specified on the command line to override the natural upperbound value of the logical volume that contains the partition.

The mirscan command prints (to standard output) a status report for the partitions scanned. If the -a flag is specified, the mirscan command also prints (to standard output) a status report containing each corrective action that is taken. If the -o flag is specified, the report will be in colon-separated output format. If the **-o** flag is not specified, the default behavior is to print the report in human-readable format.

Partitions on nonmirrored logical volumes are scanned and included in all reports, but no sync or migration operation is possible for such partitions. Partitions on striped logical volumes can be synced but cannot be migrated. Partitions on paging devices cannot be migrated, because this would result in a system hang if the mirscan process were to be paged out. Partitions on the boot logical volume cannot be migrated. An informative error message is generated in the corrective action report for each of the preceding cases.

By default, the mirscan command does not take any lock on the volume group. This should allow the mirscan command to run in the background without interfering with other Ivm commands. If the -a flag is specified and there are partitions that need to be migrated, the volume group is locked, all the migration operations are performed, and the volume group lock is released. Therefore, if the -a flag is specified, the impact to other Ivm commands is minimized because the volume group is only locked during the migration operations, which are all performed at once just before the end of execution.

Flags

Specifies that corrective action should be taken.

-c lvcopy Identifies a particular copy of the logical volume. The -c flag can only be specified in

conjunction with the -I flag. The -c flag is ignored if it is used in conjunction with the -p, -r,

or -v flag.

-I Ivname Specifies the logical volume to be scanned.

Specifies colon-separated output format should be used for the report. If this option is not

used, the default behavior is to print a report in human-readable format.

Specifies the physical volume to be scanned. -p pvname

Specifies which portions of the partition should be read. If the nblks value is 0, only the -q nblks

first, middle, and last 512 bytes of each partition are read to determine whether the partition is capable of performing I/O operations. A nonzero nblks value indicates that only the first nblks 512 byte blocks of each partition should be read to determine whether the partition is capable of performing I/O operations. If the -q flag is not specified, the entire

partition is read.

Specifies that any partitions in the volume group should be scanned if they do not reside -r reverse pvname

> on pvname but they do have a mirror copy on pvname. This could be run prior to removing pvname from the system, in case pvname somehow has the last good copy of a

partition.

-s strictness (y, n, s) Specifies a strictness value that should override the natural strictness value. Legal values

> are v. n. and s. where v enables strictness, n disables strictness, and s enables "superstrictness." By default, when mirscan has to perform a migration operation on a partition it will adhere to the natural strictness value of the logical volume that contains that partition. If the -s flag is used, the override strictness value will be used. If the -s flag is used in conjunction with the -p, -r, or -v flags, the override strictness value could

override the natural strictness of multiple logical volumes.

-u upperbound Specifies an upperbound value that should override the natural upperbound value. The

> upperbound value should be between 1 and the total number of physical volumes in the volume group. By default, when mirscan has to perform a migration operation on a partition it will adhere to the natural upperbound value of the logical volume that contains the partition. If the -u flag is used, the override upperbound value will be used. If the -u flag is used in conjunction with the -p, -r, or -v flags, the override upperbound value could

override the natural upperbound value of multiple logical volumes.

Specifies the volume group to be scanned. -v vgname

Exit Status

An exit code of 0 indicates that mirscan was able to complete its execution and was able to correct any error conditions that were encountered along the way. An exit code of 1 indicates that mirscan was able to complete its execution, but it was unable to correct every error that it found; further corrective action is still required. For example, if corrective actions would be required but the -a flag was not specified, an exit code of 1 is used. An exit code of 2 indicates that mirscan was unable to complete its execution. For example, if the target device is not listed in the ODM, an exit code of 2 is used.

Examples

1. To scan logical volume lv33, report the status of each partition, and have every block of each partition read to determine whether it is capable of performing I/O operations, type:

```
mirscan -1 lv33
```

2. To scan logical volume lv33, report the status of each partition, and have only the first two blocks of each partition read to determine whether it is capable of performing I/O operations, type:

```
mirscan -1 1v33 -q 2
```

3. To scan logical volume lv33, report the status of each partition, sync any stale partitions found, and migrate any partitions that are not capable of performing I/O operations, type:

```
mirscan -1 1v33 -a
```

4. To scan every allocated logical partition on hdisk4 and report the status of each partition, type:

```
mirscan -p hdisk4
```

5. To find every allocated partition in the volume group that resides on hdisk4, and scan and report the status of all partitions that do not reside on hdisk4 but are mirror copies of a partition that resides on hdisk4, type:

```
mirscan -r hdisk4
```

This would be useful to run before removing hdisk4 from the system.

6. To scan volume group vg05, report the status of each allocated partition, and have the first, middle. and last 512 bytes of each partition read to determine whether that partition is capable of performing I/O operations, type:

```
mirscan -v vg05 -q 0
```

Restrictions

Unmirrored partitions and striped partitions are not eligible for migration. Partitions on paging devices will not be migrated by mirror scan because it would result in a system hang if the mirscan process happened to get paged out. Partitions from the boot logical volume cannot be migrated.

Location

/usr/sbin/mirscan

Standard Output

Each line in the report corresponds to an operation on a physical partition. There are 4 types of operation that mirscan can perform. A scan operation determines whether the partition is synced and whether it is capable of performing I/O operations. A resync operation is a corrective action performed on stale partitions that attempts to return them to synced state. A force resync operation is a corrective action performed on partitions that are not capable of performing I/O operations, in an attempt to trigger bad block relocation or hardware relocation. At the end of the force resync operation, the partition is read again to determine whether it is capable of performing I/O operations. A migration operation is a corrective action performed on partitions that are not capable of performing I/O operations, in an attempt to move the data to a physical location that is capable of performing I/O.

The default format for the reports contains the following column headings. If the -o flag is specified, no header is displayed and the output report is printed in colon-separated output format. The columns and their meanings are as follows:

OP The valid values for this field are s, r, f, and m. A value of s signifies a scan operation. A value of r

> signifies a resync operation. A value of f signifies a force resync operation, which is performed in an effort to trigger bad block relocation or hardware relocation. A value of \mathbf{m} signifies a migration

operation.

STATUS The valid values for this field are SUCCESS or FAILURE. For a scan operation, FAILURE is indicated

> if the partition being scanned is stale or incapable of performing I/O. For a resync operation, FAILURE is indicated if the partition was not synchronized. For a force resync operation, FAILURE is indicated if the partition is still incapable of performing I/O operations. For a migration operation, FAILURE is

indicated if the migration operation was not completed.

PVNAME Identifies the name of the physical volume where the partition being operated on resides. For a

migration operation, PVNAME refers to the source physical volume and TARGETPV refers to the

destination physical volume.

PP Identifies the physical partition number of the partition being operated on. The first partition on a

particular physical volume has a PP value of 1, not 0.

SYNC The valid values for this field are synced or stale. The value indicated refers to the state of the

partition after the operation has been completed. For example, if a resync operation succeeds, a

value of synced will be displayed.

IOFAIL The valid values for this field are yes or no. The value indicated refers to the state of the partition after

the operation has been completed. For example, if a migration operation succeeds then a value of no

is displayed to indicate that the partition no longer has a problem performing I/O operations.

Identifies the name of the logical volume where the partition being operated on resides. LVNAME

Identifies the logical partition number of the partition being operated on. The first partition on a LP

particular logical volume has an LP value of 1, not 0.

CP Identifies the logical copy number of the partition being operated on. The first logical copy of a logical

volume has a CP value of 1, not 0.

Identifies the name of the physical volume that was used as the target for a migration operation. For **TARGETPV**

any type of operation other than a migration operation, this field is left blank.

TARGETPP Identifies the physical partition number of the partition that was used as the target for a migration

operation. For any type of operation other than a migration operation, this field is left blank. The first

partition on a particular physical volume has a TARGETPP value of 1, not 0.

Related Information

The "lymo Command" on page 473, "lymstat Command" on page 475, replacepy Command.

mk niscachemgr Command

Purpose

Uncomments the entry in the /etc/rc.nfs file for the nis cachemor daemon and invokes the daemon by using the startsrc command.

Syntax

/usr/sbin/mk niscachemgr [-I] | [-B] | [-N]

Description

The mk_niscachemgr command uncomments the entry in the /etc/rc.nfs file for the nis_cachemgr daemon. The **mk niscachemgr** command starts the daemon by using the **startsrc** command.

Note: The mk_nisd, mk_cachemgr, mk_nispasswdd, rm_nisd, rm_cachemgr, and rm_nispasswdd commands do two things:

- Alter the entries of daemon startup calls in /etc/rc.nfs.
- Alter the default behavior of the daemon src entities.

For example, if the **rpc.nisd** daemon is supposed to start with the **-Y** flag, this will not be explicitly set in the /etc/rc.nfs entry for starting the rpc.nisd daemon. Instead, a chssys is executed to place the default options which are added (if any) to the daemons during startup. To verify that these options exist, use the Issrc -S -s subsystem command to show the default options.

Flags

- -1 Uncomments the entry in the /etc/rc.nfs file to start the nis_cachemgr daemon on the next system restart.
- -B Uncomments the entry in the /etc/rc.nfs file to start the nis_cachemgr daemon and uses the startsrc command to start the nis_cachemgr daemon. This flag is the default.
- -N Uses the startsrc command to start the nis_cachemgr daemon. This flag does not change the /etc/rc.nfs file.

Examples

To modify the /etc/rc.nfs file to invoke the nis_cachemgr daemon on the next system restart, enter: mk niscachemgr -I

Files

/etc/rc.nfs

Contains the startup script for the NFS and NIS daemons.

Related Information

The **smit** command, **startsrc** command, and the **nis cachemgr** daemon.

Network Information Services+ (NIS+) Overview for System Management in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide.

System management interface tool in Operating system and device management.

Network File System (NFS) Overview for System Management in Networks and communication management.

How to Start and Stop the NIS+ Daemons in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide and How to Export a File System Using Secure NFS in Security.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide.

mk_nisd Command

Purpose

Uncomments the entry in the /etc/rc.nfs file for the rpc.nisd daemon and invokes the daemon by using the startsrc command.

Syntax

/usr/sbin/mk_nisd [-I] | [-B] | [-N] [-s] [-y] [-b]

Description

The mk_nisd command uncomments the entry in the /etc/rc.nfs file for the rpc.nisd daemon. The mk_nisd command starts the daemon by using the startsrc command.

Note: The mk_nisd, mk_cachemgr, mk_nispasswdd, rm_nisd, rm_cachemgr, and rm_nispasswdd commands do two things:

- Alter the entries of daemon startup calls in /etc/rc.nfs.
- · Alter the default behavior of the daemon src entities.

For example, if the **rpc.nisd** daemon is supposed to start with the **-Y** flag, this will not be explicitly set in the /etc/rc.nfs entry for starting the rpc.nisd daemon. Instead, a chssys is executed to place the default options which are added (if any) to the daemons during startup. To verify that these options exist, use the Issrc -S -s subsystem command to show the default options.

Flags

- -1 Uncomments the entry in the /etc/rc.nfs file to start the rpc.nisd daemon on the next system-restart.
- -B Uncomments the entry in the /etc/rc.nfs file to start the rpc.nisd daemon and uses the startsrc command to start the rpc.nisd daemon. This flag is the default.
- -N Uses the startsrc command to start the rpc.nisd daemon. This flag does not change the /etc/rc.nfs file.
- Starts the rpc.nisd with no DES authentication. If this flag is not used, the default rpc.nisd behavior is to -S always start with DES authentication. The -s option is used to make the rpc.nisd compatible with NIS(YP) clients.
- Causes the **rpc.nisd** daemon to emulate a NIS(YP) service. This is not the default setting of **rpc.nisd** or -y mk nisd.
- Causes the rpc.nisd daemon to emulate the NIS(YP) DNS resolver service. This is not the default setting of -b rpc.nisd or mk nisd.

Note: The settings that result from using the -a, -y, and -b flags remain the default behavior of rpc.nisd after a system reboot if the -I or -B flags were used. The only way to restore settings is by executing rm nisd and then executing mk nisd once again.

Examples

- 1. To modify the /etc/rc.nfs file to invoke the rpc.nisd daemon on the next system-restart, enter: mk nisd -I
- 2. To start the rpc.nisd daemon without DES authentication and to modify the /etc/rc.nfs file to invoke the **rpc.nisd** daemon without DES authentication upon reboot:

```
mk nisd -B -s
```

Files

/etc/rc.nfs

Contains the startup script for the NFS and NIS daemons.

Related Information

The **smit** command and the **startsrc** command.

The **rpc.nisd** daemon.

Network Information Services+ (NIS+) Overview for System Management in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide.

System management interface tool in *Operating system and device management*.

Network File System (NFS) Overview for System Management in Networks and communication management.

How to Start and Stop the NIS+ Daemons in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide and How to Export a File System Using Secure NFS in Security.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide.

mk nispasswdd Command

Purpose

Uncomments the entry in the /etc/rc.nfs file for the rpc.nispasswdd daemon and invokes the daemon by using the startsrc command.

Syntax

/usr/sbin/mk nispasswdd [-I] | [-B] | [-N]

Description

The mk_nispasswdd command uncomments the entry in the /etc/rc.nfs file for the rpc.nispasswdd daemon. The **mk nispasswdd** command starts the daemon using the **startsrc** command.

Note: The mk nisd, mk cachemar, mk nispasswdd, rm nisd, rm cachemar, and rm_nispasswdd commands do two things:

- Alter the entries of daemon startup calls in /etc/rc.nfs.
- Alter the default behavior of the daemon src entities.

For example, if the **rpc.nisd** daemon is supposed to start with the **-Y** flag, this will not be explicitly set in the /etc/rc.nfs entry for starting the rpc.nisd daemon. Instead, a chssys is executed to place the default options which are added (if any) to the daemons during startup. To verify that these options exist, use the Issrc -S -s subsystem command to show the default options.

Flags

- Uncomments the entry in the /etc/rc.nfs file to start the rpc.nispasswdd daemon on the next system restart.
- -B Uncomments the entry in the /etc/rc.nfs file to start the rpc.nispasswdd daemon and uses the startsrc command to start the rpc.nispasswdd daemon. The -B flag is the default.
- -N Uses the startsrc command to start the rpc.nispasswdd daemon. The -N flag does not change the /etc/rc.nfs

Examples

1. To modify the /etc/rc.nfs file to invoke the rpc.nispasswdd daemon on the next system restart, enter: mk nispasswdd -I

Files

/etc/rc.nfs

Contains the startup script for the NFS and NIS daemons.

Related Information

The **smit** command and **startsrc** command.

The rpc.nispasswdd daemon.

Network Information Services (NIS) Overview for System Management in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide.

System management interface tool in Operating system and device management.

Network File System (NFS) Overview for System Management in Networks and communication management.

How to Start and Stop the NIS+ Daemons in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide and How to Export a File System Using Secure NFS in Security.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

NIS+ Reference.

mkboot Command

Purpose

Creates the boot image, the boot record, and the service record. This command is not a user-level command and is NOT supported in AIX 4.2 or later.

Syntax

mkboot -d Device [-b] [-D] [-c] [-h] [-i] [-l] [-l LVDev] { -k Kernel | -e Expander } [-L] [-s] [-r] [-p Offset] [-w] -f FileSystem

Description

The mkboot command combines a kernel and file system into a boot image. The resulting image is written to standard out. It is copied to a boot device with the appropriate boot record information. The boot image can be made compressed or uncompressed and with or without a boot record at the beginning of the image. An image created for a tape is compressed with the boot record at the start of the image file. A disk boot image may be created without compression and has no boot record. The boot record is written to the first sector of the disk. The record contains information about the size and location of the image after it is written to the boot logical volume on that disk.

If the boot logical volume is mirrored, the **mkboot** command not only writes the boot image to each copy of the boot logical volume but also writes a boot record to each physical disk comprising the mirror. As long as the mkboot command is able to update at least one of the copies of a mirrored boot logical volume, no error is returned. To enable booting from each copy of a mirrored boot logical volume, each of the physical disks must be specified using the bootlist command. For more information regarding mirrored logical volumes, see Logical volume storage in Operating system and device management.

The **mkboot** command is usually called by the **bosboot** command. However, you can run the **mkboot** command a second time to put expand code at the beginning of a compressed boot image.

Flags

-b

Zeros out save-base fields. This flag is optional.

-d Device Specifies the device required for the IPL record. This flag is required.

Zeros out the boot record on the device. This flag is optional. -C

Loads the low-level debugger at boot time. -e Expander Specifies kernel expansion code to create a compressed boot image file.

Either the -e flag or the -k flag must be specified.

-f FileSystem Specifies the boot file system. This flag is required.

Prevents the **mkboot** command from updating the boot header. This flag -h

is optional.

Writes the normal portion of the boot record. -I (uppercase i) Invokes the low-level debugger at boot time.

Specifies the kernel in the boot image. Either the -k flag or the -e flag -k Kernel

must be specified.

-I (lowercase L) LVDev Specifies the logical volume device that contains the loadable boot code. Enables lock instrumentation for MP systems. This flag has no effect on

systems that are not using the MP kernel.

-p Offset Specifies the address to use as boot pr start field in the boot record.

This flag is used in creating the CD-ROM boot image. This flag is

Creates an image that is read-only storage (ROS) emulation code. -r

Writes the service portion of the boot record. -s

Outputs first two blocks of boot logical volume before the boot image. -w

This flag is applicable to disk boot image only.

Security

-D

Access Control: Only the root user can read and execute this command.

Examples

1. To create an uncompressed boot image, using the kernel /usr/lib/boot/unix and the /tmp/bootfs file system for the device /dev/hdisk0, enter

```
mkboot -d /dev/hdisk0 -k /usr/lib/boot/unix -f /tmp/bootfs \
-b -i -s > /tmp/boot.image
```

2. To clear the boot record but leave the PVID for disk hdisk0, enter:

mkboot -d /dev/hdisk0 -c

3. Although the **mkboot** command combines a kernel and a random access memory (RAM) file system to create one boot image, you can run the mkboot command a second time to put expand code at the beginning of a compressed boot image. For example, enter:

```
mkboot -b -d /dev/rmt0 -k unix -f ramfs | compress > /tmp/image
mkboot -b -i -s -d /dev/rmt0 -k bootexpand -f /tmp/image \
> bootfile
```

for a bootable tape where:

unix Specifies the kernel.

Specifies the RAM disk file system. ramfs

compress Specifies the compression or compact routine. Specifies the expansion or kernel uncompact routine. bootexpand

Files

/usr/include/sys/bootrecord.h

Specifies the structure of the boot record.

Related Information

The bosboot command, and lockstat command.

Boot process in Operating system and device management.

mkC2admin Command

Purpose

Configure a system to operate in C2 Security Mode.

Syntax

mkC2admin { [-m] | [-a address] hostname }

Description

The mkC2admin command initializes the security directories for use in a C2 System configuration. The distributed database directories are created and symbolic links initialized. When a system is being configured as the Administrative Host (using the -m flag), an additional file system is created to hold the master copies of the administrative database files. Those files are stored in the directory /etc/data.master which has a logical volume name of **hd10sec**.

The administrative database files are divided into three categories. Those files that must be shared, those files that optionally may be shared, and those files that may not be shared. Optionally sharable files are described in the file /etc/security/files.config. That file consists of multiple lines of the format:

[y|n]|filename

and is editable by the administrator. To select an optionally sharable filename, the administrator sets the first field to the value v. To make an optionally sharable file be unshared, the field is set to the value n. All hosts in the C2 System must have an identical /etc/security/files.config file.

The system hostname must be defined in the /etc/hosts file at the time this command is run. If not, the IP address of the new C2 System Administrative Host may be provided with the -a option, and an entry will be added to /etc/hosts.

Flags

-a address Use address as the IP address of hostname. Configure the host as the administrative master. -m

Parameters

hostname Specifies the hostname.

Exit Status

- 0 The system has been properly configured to operate in the C2 mode.
- 1 The system was not installed with the C2 option.
- 2 The system could not be successfully configured to operate in C2 mode.
- 3 The system was previously configured to operate in C2 mode without having first been unconfigured.

Files

/usr/sbin/mkC2admin

Contains the mkC2admin command.

Related Information

The chC2admin command, isC2host command, IsC2admin command, rmC2admin command.

mkcatdefs Command

Purpose

Preprocesses a message source file.

Syntax

mkcatdefs SymbolName SourceFile ... [-h]

Description

The **mkcatdefs** command preprocesses a message source file for input to the **gencat** command.

The SourceFile message file contains symbolic identifiers. The mkcatdefs command produces the SymbolName_msg.h file, containing statements that equate symbolic identifiers with the set numbers and message ID numbers assigned by the mkcatdefs command.

The **mkcatdefs** command creates two outputs. The first is a header file called *SymbolName* **msg.h**. You must include this SymbolName msq.h file in your application program to associate the symbolic names to the set and message numbers assigned by the **mkcatdefs** command.

The mkcatdefs command sends message source data, with numbers instead of symbolic identifiers, to standard output. This output is suitable as input to the gencat command. You can use the mkcatdefs command output as input to the **gencat** command in the following ways:

- Use the **mkcatdefs** command with a > (redirection symbol) to write the new message source to a file. Use this file as input to the gencat command.
- Pipe the **mkcatdefs** command output file directly to the **gencat** command.
- Use the runcat command rather than the mkcatdefs command. The runcat command automatically sends the message source file through the mkcatdefs command and then pipes the file to the gencat command.

After running the **mkcatdefs** command, you can use symbolic names in an application to refer to messages.

Flags

Suppresses the generation of a SymbolName msg.h file. This flag must be the last argument to the mkcatdefs command.

Examples

To process the symb.msg message source file and redirect the output to the symb.src file, enter: mkcatdefs symb symb.msg > symb.src

The generated symb msg.h file looks similar to the following:

```
_H_SYMB_MSG
_H_SYMB_MSG
#ifdef
#define
#include <limits.h>
#include <nl_types.h>
#define
            MF SYMB
                         "symb.cat"
/* The following was generated from symb.src. */
/* definitions for set MSFAC */
            SYM FORM
#define
                          1
#define
            SYM_LEN
                          2
#define
            MSG H 6
#endif
```

The **mkcatdefs** command also creates the symb.src message catalog source file for the **gencat** command with numbers assigned to the symbolic identifiers:

```
$quote " Use double quotation marks to delimit message text
$delset 1
$set 1
         "Symbolic identifiers can only contain alphanumeric \
1
characters or the _ (underscore character)\n"
2     "Symbolic identifiers cannot be more than 65 \
characters long\n"
5
         "You can mix symbolic identifiers and numbers\n"
$quote
         remember to include the "msg h" file in your program
```

The assigned message numbers are noncontiguous because the source file contained a specific number. The **mkcatdefs** program always assigns the previous number plus 1 to a symbolic identifier.

Note: The mkcatdefs command inserts a \$delset command before a \$set command in the output message source file. This means you cannot add, delete, or replace single messages in an existing catalog when piping to the gencat command. You must enter all messages in the set.

Files

/usr/bin/mkcatdefs

Contains the mkcatdefs command.

Related Information

The dspcat command, dspmsg command, gencat command, runcat command.

The catclose subroutine, catgets subroutine, catopen subroutine.

Using the Message Facility in AIX 5L Version 5.3 National Language Support Guide and Reference.

mkCCadmin Command

Purpose

Configure a system to operate in Common Criteria enabled Security Mode.

Syntax

```
mkCCadmin { [ -m ] | [ -a address ] hostname }
```

Description

The mkCCadmin command initializes the security directories for use in a Common Criteria enabled System configuration. The distributed database directories are created and symbolic links initialized. When a system is being configured as the Administrative Host (using the -m flag), an additional file system is

created to hold the master copies of the administrative database files. Those files are stored in the directory /etc/data.master which has a logical volume name of hd10sec.

The administrative database files are divided into three categories. Those files that must be shared, those files that optionally may be shared, and those files that may not be shared. Optionally sharable files are described in the file /etc/security/files.config. That file consists of multiple lines of the format: [y|n]|filename

and is editable by the administrator. To select an optionally sharable filename, the administrator sets the first field to the value y. To make an optionally sharable file be unshared, the field is set to the value n. All hosts in the Common Criteria enabled System must have an identical /etc/security/files.config file.

The system hostname must be defined in the /etc/hosts file at the time this command is run. If not, the IP address of the new Common Criteria enabled System Administrative Host may be provided with the -a option, and an entry will be added to /etc/hosts.

Flags

Use address as the IP address of hostname. -a address -m Configure the host as the administrative master.

Parameters

hostname Specifies the hostname.

Exit Status

- The system has been properly configured to operate in the Common Criteria enabled mode.
- 1 The system was not installed with the Common Criteria enabled option.
- 2 The system could not be successfully configured to operate in Common Criteria enabled mode.
- 3 The system was previously configured to operate in Common Criteria enabled mode without having first been unconfigured.

Files

/usr/sbin/mkCCadmin Contains the mkCCadmin command.

Related Information

The chCcadmin command, isCChost command, IsCCadmin command, rmCCadmin command.

mkcd Command

Purpose

Creates a multi-volume CD (or CDs) from a mksysb or savevg backup image.

Syntax

mkcd -r directory | -d cd_device | -S [-m mksysb_image | -M mksysb_target | -s savevg_image | -v savevg_volume_group] [-C cd_fs_dir] [-I cd_image_dir] [-V cdfs_volume_group] [-B] [-p pkg_source_dir][-R | -S][-i image.data][-u bosinst.data][-e][-P][-I package_list][-L][-b bundle_file | [-z custom_file | [-D | [-U | [-Y | [-n | [-a | [-A | [-c |

Description

The **mkcd** command creates a system backup image (**mksysb**) to CD-Recordable (CD-R) or DVD-Recordable (DVD-R, DVD-RAM) from the system rootvg or from a previously created mksysb image. It creates a volume group backup image (savevg) to CD-R from a user-specified volume group or from a previously created savevg image.

Note: If the system has a multibos environment where both instances are mounted, the only way to restore the backup is by using the alt_disk_mksysb command.

For DVD media, system backups made with the **mkcd** command have a limitation in that they expect the media to be 4.7 GB or larger per side. The **mkcd** command does not process the next volume until it writes over 4 GB on the current volume, thus the use of smaller media would result in corruption when going beyond the capacity of the media.

When a bootable backup of a root volume group is created, the boot image reflects the currently running kernel. If the current kernel is the 64-bit kernel, the backup boot image is also 64 bit, and it only boots 64-bit systems. If the current kernel is a 32-bit kernel, the backup boot image is 32 bit, and it can boot both 32-bit and 64-bit systems.

With the mkcd command, you can create bootable and non-bootable CDs in Rock Ridge (ISO9660) or UDF (Universal Disk Format) format.

See the -L flag for details about creating DVD-sized images. What applies to CDs also applies to DVDs, except where noted.

Note: The functionality required to create Rock Ridge format CD images and to write the CD image to the CD-R, DVD-R or DVD-RAM device is not part of the mkcd command. You must supply additional code to **mkcd** to do these tasks. The code is called using shell scripts and then linked to /usr/sbin/mkrr fs (for creating the Rock Ridge format image) and /usr/sbin/burn cd (for writing to the CD-R device). Both links are called from the **mkcd** command.

Some sample shell scripts are included for different vendor-specific routines. You can find these scripts in /usr/samples/oem cdwriters.

If you do not supply any file systems or directories as command parameters, the **mkcd** command creates the necessary file systems and removes them when the command finishes executing. File systems you supply are checked for adequate space and write access.

Notes:

- 1. While the **mkcd** command is running, ensure that system activity is minimal.
- 2. If **mkcd** creates file systems in the backup volume group, they are excluded from the backup.

If you need to create multi-volume CDs because the volume group image does not fit on one CD, the mkcd command provides instructions for CD replacement and removal until all the volumes have been created.

Flags

-a	Does not back up extended attributes or NFS4 ACLs.
-A	Backs up DMAPI file system files.
-c	Does not compress or pack files as they are backed up.
-d cd_device	Indicates the CD-R, DVD-R or DVD-RAM device (/dev/cd1, for instance).
	This flag is required unless you use the -S flag.
-r directory	Indicates existing directory structure to burn onto a CD or DVD. This makes a CD image that is a copy of the given directory structure.

- -m mksysb_image
- -s savevg_image
- -v savevg_volume_group
- -C cd fs dir

-M mksysb_target

-I cd image dir

-V cdfs_volume_group

Specifies a previously created **mksysb** image. If you do not give the -m flag, the mkcd command calls mksysb. (See the -M flag for more information about where the mksysb image is placed.)

Indicates a previously created savevg image. All savevg backup images are nonbootable. See Notes for details.

Denotes the volume group to be backed up using the **savevg** command. All savevg backup images are nonbootable. See the Notes below. (See the -M flag for more information about where the saveva image is placed.)

Specifies the file system used to create the CD file system structure, which must have at least 645 MB of available disk space (up to 4.38 GB for DVD sized images). The CD image only consumes as much room as necessary to contain all the data on the CD.

If you do not specify the -C flag and the /mkcd/cd_fs directory exists, mkcd uses that directory. If you do not specify the -C flag and the /mkcd/cd_fs directory does not exist, the mkcd command creates the file system /mkcd/cd_fs and removes it when the command finishes executing. The command creates the file system in the volume group indicated with the -V flag, or rootvg if that flag is not used. Each time you invoke the **mkcd** command, a unique subdirectory (using the process id) is created under the /mkcd/cd_fs directory, or in the directory specified with the -C flag.

Note: If performing DVD sized backups, the filesystems need to be large file enabled. This also requires setting the file ulimit size to unlimited. States the directory or file system where the mksysb or savevg image is stored if a previously created backup is not given with the -m or -s flags. If the -M flag is not used and a mksysb or savevg image is not provided, mkcd verifies that /mkcd/mksysb_image exists. If the directory does not exist, then **mkcd** creates a separate file system, /mkcd/mksysb_image, where the mksysb or savevg images are temporarily stored. The command creates the file system in the volume group given with the -V flag, or in rootvg if that flag is not used.

Note: Note: If performing DVD sized backups, the filesystems need to be large file enabled. This also requires setting the file ulimit size to unlimited

Specifies the directory or file system where the final CD images are stored before writing to the CD-R, DVD-R, or DVD-RAM device. If this flag is not used, **mkcd** uses the **/mkcd/**cd_images directory if it exists. If not, the command creates the /mkcd/cd_images file system in the volume group given with the -V flag, or in rootvg if that flag is not used.

If the **mkcd** command creates the file system, it is removed upon command completion, unless either the -R or -S flag is used. If the -R or -S flag is used, consideration must be made for adequate file system, directory, or disk space, especially when creating multi-volume CDs. The CD image only consumes as much room as necessary to contain all the data on the CD.

Note: If performing DVD sized backups, the files systems need to be large file enabled. This also requires setting the file ulimit size to unlimited.

Indicates the volume group used when creating the file systems needed for the mkcd command. If the -V flag is not given and a file system is needed but not there (because it was not supplied with other flags), then rootvg is the default volume group for creating the file systems. If the mkcd command creates the file systems in the backup volume group, those file systems are not included as part of the backup image. The mkcd-created file systems are removed upon completion of the command.

-p pkg_source_dir

-B

-R

-S

-u bosinst.data

-i image.data

-е

-P

-I package_list

-b bundle_file

Names the directory or device that contains device and kernel package images. The device can only be a CD device (for example, /dev/cd0). If you use the same CD-R, DVD-R or DVD-RAM device that you gave with the -d flag, the product CD media must be inserted into the CD-R drive first. The **mkcd** command then prompts you to insert the writeable CD before the actual CD creation.

Prevents the **mkcd** command from adding boot images (non-bootable CD) to the CD. Use this flag if creating a mksysb CD that you will not boot. Before installing the non-bootable mksysb CD, you must boot a same level (V.R.M.) product CD. The **mkcd** command defaults to creating a bootable CD for the machine type of the source system. See Notes for details.

Prevents the **mkcd** command from removing the final CD images. The **mkcd** command defaults by removing everything that it creates when it finishes executing. The -R flag allows multiple CD image sets to be stored, or for CD creation (burn) to occur on another system. If multiple volumes are needed, the final images are uniquely named using the process ID and volume suffixes.

Stops the **mkcd** command before writing to the CD-R. DVD-R. or DVD-RAM without removing the final CD images. The -S flag allows multiple CD sets to be created, or for CDs to be created on another system. The images remain in the directory marked by the -I flag, or in the /mkcd/cd_images directory if the -I flag is not used. If multiple volumes are required, the final images are uniquely named using the process ID and volume suffixes.

Specifies the user-supplied bosinst.data file. This data file takes precedence over the bosinst.data file in the mksysb image. If you do not give the -u flag, then mkcd restores bosinst.data from the given mksysb image, or generates a new bosinst.data file during the creation of mksysb.

Specifies the user-supplied image.data file. This data file takes precedence over the image.data file in the mksysb image. If you do not give the -i flag, then the mkcd command restores the image.data from the given mksysb image, or generates a new image.data file during the creation of mksysb.

Note: The -i flag cannot be used to specify a user-supplied vgname.data file for use with a savevg image.

Excludes the files and/or directories from the backup image listed in the /etc/exclude.volume_group file. You cannot use this flag with the -m or -s flags.

Creates physical partition mapping during the mksysb or savevg creation. You cannot use this flag with the -m or -s flags.

Specifies the file containing a list of additional packages you want copied to the ./usr/lpp/inst.images directory of the CD file system. The images are copied from the location named with the -p flag. If you use the -I flag you must also use the -p flag.

Creates final CD images that are DVD sized (up to 4.38 GB). Gives the full pathname of the file containing a list of filesets to be installed after the mksysb is restored. This file is copied to ./usr/sys/inst.data/user_bundles/bundle_file in the CD file system and also copied to RAM in case the CD is unmounted. The file would be listed as BUNDLES=/../usr/sys/inst.data/user bundles/bundle file in the bosinst.data file.

-z custom_file

-D

-U

-Y

-n

States the full pathname of the file to be copied to the root directory of the CD file system. This file could be a customization script specified in the **bosinst.data** file, such as CUSTOMIZATION FILE=filename.

For example: If the file my script is in /tmp on the machine where mkcd is running, then enter -z/tmp/my script and specify CUSTOMIZATION FILE=my script. The code copies the script to the root directory of the RAM file system before it executes.

Turns on the debug output information feature. The default is no debug output.

Creates a **UDF** (Universal Disk Format) file system on DVD-RAM media. It does not require the amount of free space needed to create Rock Ridge format backups. It does not need the /mkcd/cd fs and /mkcd/cd images file systems. Therefore, the only temporary disk space it needs is to create the backup image that will be copied to the media. This means that the -I and -C flags do not apply to the -U flag. Because the backup is copied to the media, images cannot be created and burned later or on another system. So, the -R flag and -S flag do not apply when using the -U flag. You need to specify a device to write to with the -d flag. The -U flag does not use the /usr/sbin/mkrr_fs or /usr/sbin/burn_cd file systems.

Accepts licenses.

Backs up user volume group information and administration data files. This backs up files such as /tmp/vgdata/vgname/vgname.data and map files, if any exist. This does not back up user data files. This backup can be used to create a user volume group without restoring user data files. This cannot be done to rootvg.

Notes:

- 1. If you are creating a non-bootable CD (using the **-B** flag), you cannot use the **-p** or **-I** flags.
- 2. If you are creating a non-bootable CD with a savevg image (using the -s or -v flags), you cannot use the -p, -I, -u, -i, -z, or -b flags.

Examples

- 1. To generate a bootable system backup to the CD-R device named /dev/cd1, enter: mkcd -d /dev/cd1
- 2. To generate a system backup to the DVD-R or DVD-RAM device named /dev/cd1, enter: mkcd -d /dev/cd1 -L
- 3. To generate a non-bootable volume group backup of the volume group myvg to /dev/cd1, enter: mkcd -d /dev/cd1 -v myvg

Note: All savevg backup images are non-bootable.

Note:

- 4. To generate a non-bootable system backup, but stop mkcd before the CD is created and save the final images to the /mydata/my cd file system, and create the other mkcd filesystems in myvg, enter:
 - mkcd -B -I /mydata/my cd -V myvg -S
- 5. To create a CD or DVD that duplicates an existing directory structure such as:

/mycd/a /mycd/b/d /mycd/c/f/g

enter:

mkcd -r /mycd -d /dev/cd1

After mounting with mount -o ro /dev/cdl /mnt, cd to /mnt; a find . -print command displays:

./a ./b ./b/d ./c ./c/f

./c/f/q

Files

/usr/bin/mkcd Contains the mkcd command.

Related Information

The **mksysb** command and **savevg** command.

The /image.data file and the bosinst.data file stanza descriptions.

A procedure to verify the backup can be found in the article Creating system backups in the *Installation* and migration.

For more information about CD-R drives (including DVD-R and DVD-RAM drives) and CD-R creation software, refer to the following README file: /usr/lpp/bos.sysmgt/README.oem cdwriters

mkcfsmnt Command

Purpose

Mounts a CacheFS directory.

Syntax

mkcfsmnt -d PathName -t { nfs | cdrom}] [-h RemoteHost] [-p { RemoteDirectory | LocalDeviceName } [-c CacheDirectory] [-o MountOptions] [-b BackingFileSystem] [-I | -B | -N]

Description

The mkcfsmnt command constructs an entry that will be appended to the /etc/filesystems file, thus making a file system available for use as a cache file system. If the mount is to be permanent, this entry will remain. If the mount is temporary, the flags will be used directly for the mount command. CacheFS file systems are used to cache accesses to backing file systems. Backing file systems are generally NFS mounts.

Flags

-d PathName Specifies the mount point for the cache directory.

-t Selects file systems to be cached.

> nfs Specifies that the CacheFS file system is backed by an NFS mount.

cdrom Specifies that the CacheFS file system is backed by a CDROM file

system. (Currently not supported.)

-h RemoteHost Specifies the NFS server that is exporting the directory.

Specifies the directory that is mounted on the path name specified. This is -p RemoteDirectory

commonly a remote file system that will be mounted via NFS or a local device

name in the case of CDROM (Currently not supported.)

Specifies the location of the CacheFS file system. This must have been -c CacheDirectory

previously created by execution of the **cfsadmin** command.

Specifies the directory that is mounted on the path name specified. -d RemoteDirectory

-o MountOptions Specifies a comma-separated string of mount options that are dependent on

> the backing file system type. For instance, if it is NFS, the options would be those typically specified by the **-o** Options string to mount. See the **mount**

command documentation for the acceptable values.

Specifies a backing file system if it is already mounted. If this is not specified, -b BackingFileSystem

then the command will do the mount itself on a temporary mount point. If this is not specified, then RemoteHost and RemoteDirectory must be specified. Causes an entry to be added to the /etc/filesystems file. The directory is not

-B Adds an entry to the /etc/filesystems file and attempts to mount the file

system. This flag is the default.

-N Mounts the directory with the options specified, but does not modify the

/etc/filesystems file.

Examples

-1

To specify a CacheFS mount, type:

/usr/sbin/mkcfsmnt -t nfs -d /usr/share/man -p /usr/share/man -h host1 -c /cache/cache1 -o ro, intr -N

In this example, the mkcfsmnt command caches the remote directory /usr/share/man that resides on host1 on the local /usr/share/man directory. The cache is kept in /cache/cache1, which was created with the cfsadmin command. CacheFS takes care of doing the NFS backing mount, because the -b flag has not been specified.

/usr/sbin/mkcfsmnt -t nfs -d /usr/share/man -p /usr/share/man -h host1 -c /cache/cache1 -b /backs/man -o ro, intr -N

In this example, the **mkcfsmnt** command caches the remote directory **/usr/share/man** residing on host1 on the local /usr/share/man directory. The cache is kept in /cache/cache1, which was created with the cfsadmin command. The backing file system has already been mounted on /backs/man.

Files

/etc/filesystems

Lists the remote file systems to be mounted during the system restart.

mkcifscred Command

Purpose

Adds CIFS credentials to the /etc/cifs fs/cifscred file to allow future mounting of CIFS shares with stored credentials.

Syntax

mkcifscred -h RemoteHost **-u** user [**-p** password]

Description

The mkcifscred command takes a server and user name as input, and prompts for a password. The password is encrypted, and the credentials are stored in the cifscred file. If the password is not passed in with the -p option when mounting to a CIFS server, the credentials are either retrieved from the cifscred file, or, if the credentials do not exist in cifscred, the password is prompted for and read in as hidden input.

The credentials are stored as a server/user/password set. Multiple sets of credentials for the same server are permitted with different user names. Multiple sets with the same user name on different servers are also permitted.

Flags

-h RemoteHost Specifies the name of the remote host (CIFS server). This

can be provided as a host name, an IP address, or a fully

qualified domain name.

Specifies the password for a particular user on a particular -p password

remote host.

Specifies the user name whose credentials are being -u user

defined for access to the given remote host.

Exit Status

0 The command completed successfully.

>0 An error occurred.

Examples

1. To add credentials for user1 to mount on server1, enter:

mkcifscred -h server1 -u user1

Location

/usr/sbin/mkcifscred

Files

/etc/cifs_fs/cifscred

Stores the CIFS credentials.

Related Information

The chcifscred command, chcifsmnt command, "Iscifscred Command" on page 331, "Iscifsmnt Command" on page 332, "mkcifsmnt Command," rmcifscred command, rmcifsmnt command.

mkcifsmnt Command

Purpose

Adds a CIFS mount to the /etc/filesystems file and performs the mount.

Syntax

mkcifsmnt -f MountPoint -d RemoteShare -h RemoteHost -c user [-p password] [-m MountTypeName] [-Al-a] [-Il-Bl-N] [-t {rwlro}] [-u uid] [-g gid] [-x fmode] [-w wrkgrp]

Description

The **mkcifsmnt** command constructs a CIFS entry that is appended to the **/etc/filesystems** file. It then attempts to mount the CIFS file system. Its options are parsed and prepared to be passed into the crfs command, which actually adds the CIFS entry to /etc/filesystems.

Flags

-a Specifies that the /etc/filesystems entry for this file system should not be automatically mounted at system restart. This is the default.

Specifies that the /etc/filesystems entry for this file -A system should be automatically mounted at system restart. -B Specifies that the entry should be added to the /etc/filesystems and that it should be mounted at system restart. Specifies user name used to gain access to the CIFS -c user -d RemoteShare Specifies the share name on the CIFS server that should be mounted -f MountPoint Specifies the path name over which the CIFS share should be mounted. Specifies the GID that is assigned to files in the mount. -g gid The default is 0. Specifies the name of the remote host (CIFS server). This -h RemoteHost can be provided as a host name, an IP address, or as a fully qualified domain name. Specifies that the entry should be added to the -1 /etc/filesystems file, but should not be mounted. -m MountTypeName Defines the mount type that will be added to the /etc/filesystems file, which allows for mounting all file systems of a specific type using the -t option of the mount command. By default, no type value will be added to /etc/filesystems. -N Mounts the CIFS share with the options specified, but does not modify the /etc/filesystems file. -p password Specifies the password used to grant access to the specific user on the specific server. The specific credentials (server/user/password) are added to the cifscred file (the password will be encrypted). If the -p option is not specified, and the credentials do not already exist in the cifscred file, the command line prompts the user to provide the password, and the credentials will be added to the **cifscred** file. If the server/user credentials already exist in the cifscred file, this option is ignored, and the existing credentials are used for mounting. -t {rwlro} Specifies whether file system should be mounted as read-only. The default is read-write (rw). Specifies the UID that is assigned to files in the mount. -u uid The default is 0. Specifies the owner, group, and other permission bits -x fmode assigned to files in the mount. The default is 755. -w wrkgrp Specifies the domain that should be used to authenticate

Exit Status

>0

Security

You must have root authority to run this command.

The command completed successfully. An error occurred.

the user during mount. If this option is not used, authentication is handled locally by the CIFS server.

Examples

1. To add a mount over /mnt to share1 on server1, and then authenticate as user1, enter: mkcifsmnt -f /mnt -d share1 -h server1 -c user1

Location

/usr/sbin/mkcifsmnt

Files

/etc/cifs_fs/cifscred /etc/filesystems

Stores the CIFS credentials. Stores the CIFS entry.

Related Information

The chcifscred command, chcifsmnt command, "Iscifscred Command" on page 331, "Iscifsmnt Command" on page 332, "mkcifscred Command" on page 549, rmcifscred command, rmcifsmnt command.

mkcimreg Command

Purpose

Registers Common Information Model (CIM) classes and Common Manageability Programming Interface (CMPI) providers with RMC.

Syntax

To register a class:

mkcimreg [-I include_directory...] [-f] [-h] definition_file...

To register a provider:

mkcimreg [-I include directory...] [-p provider directory] [-h] registration file...

To compile the CIM schema:

mkcimreg [-I include_directory...] -b schema_path [-h]


Description

The mkcimreg command registers Common Information Model (CIM) classes and Common Manageability Programming Interface (CMPI) providers with the resource monitoring and control (RMC) subsystem. You can specify one or more class definition files or provider registration files with this command. Use the -I flag to add directories to the search path. The output from mkcimreg includes the names of the files that the CIM resource manager needs for working with CIM classes.

Registering classes

If you upgrade a class using the -f flag (that is, if the class definition has changed somehow), you must re-register all classes that are subclasses of the upgraded class so that the changes introduced into the new class propagate to its subclasses. This must be done in "descending" order, because changes propagate from parent to child. The hierarchy is:

```
Hardware Component
-----
```



If, for example, Hardware_Component is upgraded using mkcimreg -f, Hardware_Adapter and then Hardware Ethernet must both be registered afterward, in that order.

After you register any classes: You must restart RMC.

Restarting RMC

As the final step in the CIM class registration process, the RMC subsystem must be restarted. The sequence of commands to run follows:

1. To shut down the RMC subsystem, enter:

/usr/sbin/rsct/bin/rmcctrl -k

When you shut down RMC:

Any RMC-dependent resource monitoring that is in place at the time of shutdown is deactivated. Environments that rely on RMC or any of its resource managers for high availability or other critical system functions may become temporarily disabled.

2. Wait until the following command lists the status of **ctrmc** as "inoperative":

1ssrc -s ctrmc

3. Shut down the CIM resource manager and confirm it has been stopped:

stopsrc -s IBM.CIMRM lssrc -s IBM.CIMRM

4. To restart the RMC subsystem, enter:

/usr/sbin/rsct/bin/rmcctrl -A

Registering providers

The -p flag indicates that the registration file on the command line contains provider registration information. The provider library's directory is expected as this flag's parameter. Provider library names follow the CMPI/Pegasus convention of appending lib to the beginning of the ProviderName property. For example, the provider with the property ProviderName=Linux Processor is searched for in the ProviderDirectory under the name libLinux Processor.so. Auxiliary libraries required by providers that are not explicitly declared in the registration file must be either in the directory supplied on the command line, or in a standard system directory such as /usr/lib or /lib.

Compiling a schema

Version 2.9 of the CIM schema is shipped with the CIM resource manager. Use the -b flag if you want to upgrade to a higher version. The schema file (CIM_Schemaversion.mof) must be passed as the parameter to this flag. This file contains the entire CIM schema, usually in the form of a series of #include statements that bring in other schema MOF files.

After a CIM schema is compiled with the -b flag, mkcimreg will not need further access to the schema managed object format (MOF) files. User classes that are registered by **mkcimreg** against previous versions of the CIM schema need to be re-registered, so changes from the new version of the schema are reflected in any derived classes.

Flags

-I include_directory...

Specifies one or more additional directories to be searched.

- -f Overwrites any existing class registration data with the definitions that are provided in the class definition files.
- -p provider directory

Specifies a path to the provider library.

-b schema_path

Compiles the CIM schema file.

-h Writes the command's usage statement to standard output.

Parameters

definition file...

Specifies one or more class definition files.

registration_file...

Specifies one or more provider registration files.

Security

This command requires root authority.

Exit Status

- 0 The command has run successfully.
- 1 An internal command error occurred.
- 2 An error occurred with the command-line interface (CLI) script.
- 3 An incorrect flag was specified on the command line.
- 4 An incorrect parameter was specified on the command line.
- 5 A class registration error occurred.

Restrictions

You cannot register a class that derives from a class that has not yet been registered.

Implementation Specifics

This command is part of the rsct.exp.cimrm fileset, in the rsct.exp package on the AIX Expansion Pack.

Standard Output

When the -h flag is specified, this command's usage statement is written to standard output.

Standard Error

When the -T flag is specified, this command's trace messages are written to standard error.

Examples

1. To register the Linux_ComputerSystem CIM class if the class definition file is located in the **\$CIMDEFS** directory, enter:

```
mkcimreg $CIMDEFS/Linux ComputerSystem.mof
```

You must also register the CMPI provider for this class.

2. To register a CMPI provider when the registration file is located in the **\$CIMDEFS** directory and the provider library is in the **\$CMPIHOME** directory, enter:

```
mkcimreg -p $CMPIHOME $CIMDEFS/Linux ComputerSystemRegistration.mof
```

3. To compile Version 2.12 of the CIM schema, enter:

```
mkcimreg -I $SCHEMA DIR -b CIM Schema2.12.mof
```

\$SCHEMA_DIR, which indicates a search path for schema MOF files, is not required, but could help **mkcimreq** find the required MOF files if they are not in the current working directory from which the command is run.

Location

/usr/sbin/rsct/bin/mkcimreg

Related Information

Books: RSCT: Administration Guide, for information about viewing instance property values

Commands: Issrc, rmcctrl, stopsrc

Files: ct class ids

Web sites: http://www.dmtf.org, for information about the Distributed Management Task Force (DMTF), which develops and maintains CIM

mkclass Command

Purpose

Create a Workload Management class.

Syntax

mkclass [-a Attribute=Value ...] [-c | -m | -b | -v | -C | -B | -P | -T | -V | -L | -A KeyWord=Value] [-d Config_Dir] [-S SuperClass] Name

Description

The **mkclass** command creates a superclass or a subclass identified by the *Name* parameter. The class must not already exist. The Name parameter can contain only uppercase and lowercase letters, numbers, and underscores. The name is in the format supername or subname (with the -S supername flag) or supername.subname. The supername and subname parameters are each limited to 16 characters in length. The names Default, System, and Shared are reserved. They refer to predefined classes. Any Attribute=Value or KeyWord=Value argument initializes the specified attribute or resource limit. See "Attributes" on page 556 for more information. To set the process total limits (the limits that apply to each process of the class), use one or more of the options -C (totalCPU), -B (totalDiskIO), -A (totalConnectTime), or -v (totalVirtualMemoryLimit), with the keyword value of hardmax. To set the class total limits (the limits that apply to the whole class), use one or more of the options -P (totalProcesses), -T (totalThreads), -L (totalLogins), or -V (totalVirtualMemoryLimit) with the keyword value of hardmax. To reset any total limit, use - for Value. Process, class, or both total limits may be disabled when starting or updating the WLM (see wimcntrl command).

Normally, mkclass adds the class and its attributes in the relevant WLM property files, and the modifications is applied to the in-core class definitions (active classes) only after an update of WLM using the wimcntrl command.

If an empty string is passed as the configuration name (Config_dir) with the -d flag, the class is created only in the WLM in-core data structures, and no property file is updated, making the new class temporary (the change is lost if WLM is stopped and restarted or the system is rebooted).

Note: This command cannot apply to a set of time-based configurations (do not specify a set with the -d flag). If the current configuration is a set, the -d flag must be given to indicate which regular configuration the command should apply to.

Attributes

localshm

The following attributes can be changed:

Class properties:

tier	Specifies the tier value. The tier value for a class is the position of the class in the hierarchy

of resource limitation desirability for all classes. A class with a lower tier value is more

favored. The tier value ranges from 0 through 9 (the default is 0).

If the inheritance attribute is set to ves, the children of processes in this class remain in the inheritance

class upon **exec** regardless of the automatic assignment rules in effect. If the **inheritance** attribute is set to no, the assignment rules apply normally. The default if not specified is no. Indicates whether memory segments that are accessed by processes in different classes

remain local to the class they were initially assigned to or if they go to the **Shared** class. You

can specify a value of Yes or No. If not specified, the default is No.

authuser Specifies the user name of the user who is allowed to assign processes to this class. The

default when the attribute is not specified is root.

Specifies the group name of the group of users that is allowed to assign processes to this authgroup

class. There is no default value.

Specifies the name of a resource set that the processes in the class have access to. By rset

default, the class has access to all resources on the system.

vmenforce Specifies whether all processes or only the offending processes in the class need to be

terminated when the class hits the maximum VM limit. You can specify the value of class or

proc. The default value is proc.

Specifies whether the shared segments will be deleted when the last process referencing delshm

them ends because virtual memory is exceeded. You can specify the value of yes or no. The

default value is no.

Specifies the user name of the user who is allowed to administer the subclasses of this adminuser

> superclass. This attribute is valid only for superclasses. The default, when the attribute is not specified, is a null string, and in this case, only root users can administer the subclasses. **Note:** If the adminuser or admingroup attribute is changed for a superclass that belongs to the running configuration (or to a configuration of the running set), a global WLM update should be performed to reflect these changes to the in-core configuration, elsewhere, updates

that are restricted to superclass by such a user might fail due to lack of authority.

admingroup Specifies the group name of the group of users that is allowed to administer the subclasses

of this superclass. This attribute is valid only for superclasses. The default value, when the attribute is not specified, is a null string, meaning that no group can administer the

Note: If the **adminuser** or **admingroup** attribute is changed for a superclass that belongs to the running configuration (or to a configuration of the running set), a global WLM update should be performed to reflect these changes to the in-core configuration, elsewhere, updates

that are restricted to superclass by such a user might fail due to lack of authority.

Class limits and shares for CPU, memory, or disk I/O resource:

min Specifies the minimum percentage of the resource that must be made available when requested,

expressed as a percentage of the total resource available in the system. Possible values range from 0

through 100 (the default is 0).

Specifies the maximum ratio of the resource that can be made available if there is contention. This shares

> parameter is expressed in shares of the total resource available in the system. The actual ratio of the resource is dynamically computed, proportionally to the shares of all active classes. If a class has no running process, its shares are excluded from the computation. The shares are arbitrary numbers ranging from 1 through 65535. If shares is specified as a hyphen (-), the class is always considered on target and its utilization for this resource is not regulated by WLM, but the minimum and maximum

limits if any still apply. This is the default if the shares for a resource are not specified.

softmax Specifies the maximum percentage of the resource that can be made available, when there is

contention. Possible values range from 1 through 100 (the default is 100). A class can exceed its soft

maximum for a given resource if there is no contention on the resource.

hardmax Specifies the maximum percentage of the resource that can be made available, even if there is no

contention. Possible values range from 1 through 100 (the default is 100). Specifying a value different from the default value of 100 for memory can result in some memory pages remaining unused, while

some processes in the class use more.

Specifies the maximum percentage of the resource that can be made available, even if there is no max

contention. Possible values range from 1 through 100 (the default is 100). Specifying a value different from the default value of 100 for memory can result in some memory pages remaining unused, while

some processes in the class use more.

Note: The default values for a class can be read using the Isclass -D command and can be changed by manually editing the property files classes, shares, or limits to add a default stanza. For more information about these files, see the AIX 5L Version 5.3 Files Reference.

Class description:

description The class description text can be composed of any ASCII character, except colons (:) and commas (,).

Flags

-A hardmax=Value Sets the maximum amount of time a login session in the class can stay active. Value is

> specified as an integer, possibly appending the unit (s for seconds, m for minutes, h for hours, d for days, and w for weeks, default is seconds). As a user approaches this connection time limit, WLM will send a warning message to the session terminal. When the limit is reached, the user will be notified and the session leader will be sent the SIGTERM

signal, and after a short grace period, the session will be terminated (SIGKILL).

-B hardmax=Value Sets the total amount of disk I/Os allowed for each process in the class. Value is specified

as an integer, possibly appending the unit (KB for kilobytes, MB for megabytes, TB for terabytes, PB for petabytes, and EB for exabytes, default is kilobytes). After a process has used this amount of disk I/Os, the process will be sent the SIGTERM signal, and after a

grace period, it will be killed (SIGKILL).

-C hardmax=Value Sets the total amount of CPU time allowed for each process in the class. Value is specified as an integer, possibly appending the unit (s for seconds, m for minutes, h for hours, d for

days, and w for weeks, default is seconds). After a process has used this amount of time, the process will be sent the SIGTERM signal, and after a grace period, it will be killed

(SIGKILL).

-d Config_Dir Use /etc/wlm/Config_Dir as an alternate directory for the properties files. When this flag is

not used, **mkclass** uses the configuration files in the directory pointed to by

/etc/wlm/current. If an empty string is passed as the configuration name (-d "") the new class is created only in the WLM in-core data structures and no configuration file is

modified.

-L hardmax=Value Sets the total number of login sessions simultaneously available in the class. If a user tries

to log onto the system and the login shell would end up in a class that has reached the

total logins limit, the login operation will fail.

-P hardmax=Value Sets the maximum number of processes allowed in the class. If an operation would result

in a new process entering the class when the class has this many processes in it, the

operation will fail.

Specifies the name of the superclass when creating a subclass. There are two ways of -S SuperClass

creating the subclass Sub of superclass Super:

1. Specify the full name of the subclass as Super.Sub for Name and not use -S

2. Specify the -S flag to give the superclass name and use the short name for the subclass:

mkclass options -S Super Sub

-T hardmax=Value Sets the maximum number of threads allowed in the class. If an operation would result in a

> new thread entering the class when the class has this many processes in it, the operation will fail. The total thread limit must be at least as large as the total process limit for a class. If a class has a total thread limit but no total process limit specified, the total process limit

will be set to the total thread limit.

-v hardmax=Value Specifies the virtual memory limit allowed per process in the specified class. The maximum

amount of virtual memory allowed per process is (2^31)-1 for 32-bit kernels and (2^63)-1

for 64-bit kernels.

-V hardmax=Value Specifies the virtual memory allowed for the specified class. The maximum amount of

virtual memory allowed per process is (2^31)-1 for 32-bit kernels and (2^63)-1 for 64-bit

Security

Access control: Only the root user can create a superclass. Only root or authorized users whose user ID or group ID matches the user name or group name specified in the attributes adminuser and admingroup of a superclass can create a subclass of this superclass.

Files

classes Contains the names and definitions of the classes. limits Contains the resource limits enforced each class. shares Contains the resource shares attributed to each class.

Related Information

The wimcntri command, isclass command, chclass command, and rmclass command.

mkclient Command

Purpose

Uncomments the entry in the /etc/rc.nfs file for the ypbind daemon and starts the ypbind daemon to configure a client.

Syntax

/usr/sbin/mkclient [-I | -B | -N] [-S server]

Description

The mkclient command uncomments the entry to the /etc/rc.nfs file to start the ypbind daemon to configure a client. The mkclient command starts the ypbind daemon by using the appropriate System Resource Controller (SRC) command.

You can use the File Systems application in Web-based System Manager (wsm) to change file system characteristics.

You could also use the System Management Interface Tool (SMIT) smit mkclient fast path to run this command.

Flags

- Uncomments the entry for starting the ypbind daemon to the /etc/rc.nfs file. This entry causes the ypbind -1 daemon to start during the next system restart.
- -B Uncomments the entry to the /etc/rc.nfs file and starts the ypbind daemon. This flag is the default.
- Causes the startsrc command to start the ypbind daemon. This flag does not affect the /etc/rc.nfs file. -N
- Specifies which NIS server to use instead of broadcasting for one. This option must be used when no NIS -S server exists on the networks directly connected to the client machine.

Examples

To modify the /etc/rc.nfs file so that the ypbind daemon is started on the next system restart, enter: mkclient -I

Files

/var/yp/domainname directory /etc/rc.nfs

Contains the NIS maps for the NIS domain. Contains the startup script for the NFS and NIS daemons.

Related Information

The **mkmaster** command, **rmyp** command, **smit** command, **startsrc** command.

The **ypbind** daemon, **yppasswdd** daemon, **ypserv** daemon, **ypupdated** daemon.

Network File System (NFS) Overview for System Management in Networks and communication management.

System Resource Controller in Operating system and device management.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

System management interface tool in Operating system and device management.

Network Information Services (NIS) Overview for System Management in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide.

NIS Reference.

mkcomg Command

Purpose

Creates a new communication group definition for a peer domain.

Syntax

mkcomg [-s sensitivity] [-p period | [-t priority] [-x b | r | br] [-e NIM path] [-m NIM parameters] [-i n:network interface1[:node1] [,network interface2[:node2]...] | -S n:"network interface selection string"] [-h] [-TV] communication group

Description

The **mkcomg** command creates a new communication group definition for an online peer domain with the name specified by the communication group parameter. The communication group is used to define heartbeat rings for use by topology services and to define the tunables for each heartbeat ring. The communication group determines which devices are used for heartbeating in the peer domain. There can be more than one communication group in a peer domain.

The **mkcomg** command must be run on a node that is currently online in the peer domain where the communication group is to be defined. More than half of the nodes must be online to create a new communication group for the domain.

The -e and -m flags are used to set the network interface module (NIM) path and parameters. The NIM path is the path to the NIM that supports the adapter types used in the communication group. The NIM parameters are passed to NIM when it is started. If -m is not specified, the parameters predefined by topology services are used.

The communication group can be assigned to one or more interface resources. Use the -i flag to assign the communication group to a specific interface resource name. The interface resource can be limited to one on a particular node. An interface resource can also be specified using the -S flag and a selection string. This is used when specifying the interface resource name is not sufficient. The -i and -S flags cannot be used together. The chcomg command can also be used to assign a communication group to an interface resource.

Flags

-s sensitivity

Specifies the heartbeat sensitivity. This is the number of missed heartbeats that constitute a failure. The sensitivity value is an integer greater than or equal to 2. The default value is 4.

-p period

Specifies the number of seconds between heartbeats. The period is an integer greater than or equal to 1. The default value is 1.

-t priority

Specifies the priority. This value indicates the importance of this communication group with respect to others. It is used to order the heartbeat rings. The lower the number means the higher the priority. The highest priority is 1. The default value is 1 for IP networks and 255 for RS232 networks.

-x b | r | br

Excludes controls for heartbeat mechanisms. This flag indicates that one or more controls for heartbeat mechanisms should not be used even if the underlying media support it. The following features can be excluded:

- Specifies that the broadcast feature should not be used even if the underlying media b support it. If -x b is not specified, the broadcast feature will be used if the underlying media support it.
- Specifies that the source routing feature should not be used even if the underlying media r support it. If -x r is not specified, the source routing feature will be used if the underlying media support it.

To exclude more than one control, specify the feature characters consecutively: -x br.

-e NIM path

Specifies the network interface module (NIM) path name. This character string specifies the path name to the NIM that supports the adapter types in the communication group.

-m NIM parameters

Specifies the NIM start parameters. This character string is passed to the NIM when starting it.

-i n:network_interface1[:node1] [,network_interface2[:node2]...

Assigns this communication group to the network interface resource defined by the network interface resource name and optionally the node name where it can be found.

If -i is specified, -S cannot be specified.

-S n:"network interface selection string"

Assigns this communication group to the interface specified by the network interface selection string.

If -S is specified, -i cannot be specified.

- -h Writes the command's usage statement to standard output.
- -T Writes the command's trace messages to standard error. For your software service organization's use only.
- -V Writes the command's verbose messages to standard output.

Parameters

communication_group

Specifies the name of the new communication group that is to be created for the online peer domain. The name can contain any printable character.

Security

The user of the **mkcomg** command needs write permission for the **IBM.CommunicationGroup** resource class. Write permission for the IBM.NetworkInterface resource class is required to set the communication group for a network interface resource. By default, root on any node in the peer domain has read and write access to these resource classes through the configuration resource manager.

Exit Status

- 0 The command ran successfully.
- 1 An error occurred with RMC.
- 2 An error occurred with a command-line interface script.
- 3 An incorrect flag was entered on the command line.
- An incorrect parameter was entered on the command line.
- 5 An error occurred that was based on incorrect command-line input.

Environment Variables

CT CONTACT

Determines the system where the session with the resource monitoring and control (RMC) daemon occurs. When CT CONTACT is set to a host name or IP address, the command contacts the RMC daemon on the specified host. If CT_CONTACT is not set, the command contacts the RMC daemon on the local system where the command is being run. The target of the RMC daemon session and the management scope determine the resource classes or resources that are processed.

CT IP AUTHENT

When the CT IP AUTHENT environment variable exists, the RMC daemon uses IP-based network authentication to contact the RMC daemon on the system that is specified by the IP address to which the CT_CONTACT environment variable is set. CT_IP_AUTHENT only has meaning if CT_CONTACT is set to an IP address; it does not rely on the domain name system (DNS) service.

Restrictions

This command must be run on a node that is defined and online to the peer domain where the communication group is to be defined.

Implementation Specifics

This command is part of the Reliable Scalable Cluster Technology (RSCT) fileset for AIX.

Standard Input

When the -f "-" or -F "-" flag is specified, this command reads one or more node names from standard input.

Standard Output

When the -h flag is specified, this command's usage statement is written to standard output. All verbose messages are written to standard output.

Standard Error

All trace messages are written to standard error.

Examples

- 1. To define the communication group ComGrp1 for the peer domain ApplDomain and nodeA is defined and online to **ApplDomain**, run this command on **nodeA**:
 - mkcomg ComGrp1
- 2. To define the communication group **ComGrp1** for the peer domain **ApplDomain**, using a sensitivity of 1 and period of 3, and nodeA is defined and online to ApplDomain, run this command on nodeA: mkcomg -s 1 -p 3 ComGrp1
- 3. To define the communication group ComGrp1 for the peer domain ApplDomain, not using broadcast, using a priority of 3, and nodeA is defined and online to ApplDomain, run this command on nodeA: mkcomg -x b -t 3 ComGrp1
- 4. To define the communication group **ComGrp1** for the peer domain **ApplDomain**, not using broadcast, not using source routing, and nodeA is defined and online to ApplDomain, run the following command on nodeA:

```
mkcomg -x br ComGrp1
```

5. To define the communication group ComGrp1 for the peer domain ApplDomain, using a NIM path of /usr/sbin/rsct/bin/hats nim, NIM parameters -I 5 to set the logging level, and nodeA is defined and online to **ApplDomain**, run this command on **nodeA**:

```
mkcomg -e /usr/sbin/rsct/bin/hats nim -m "-1 5" ComGrp1
```

6. To define the communication group ComGrp1 for the peer domain ApplDomain, assign ComGrp1 to the network interface resource named eth0 on nodeB, and nodeA is defined and online to **ApplDomain**, run this command on **nodeA**:

```
mkcomg -i n:eth0:nodeB ComGrp1
```

7. To define the communication group ComGrp1 for the peer domain ApplDomain, assign ComGrp1 to the network interface resource that uses the subnet 9.123.45.678, and nodeA is defined and online to ApplDomain, run this command on nodeA:

```
mkcomg -S n: "Subnet == 9.123.45.678" ComGrp1
```

Location

/usr/sbin/rsct/bin/mkcomg

Related Information

Books: RSCT: Administration Guide, for information about peer domain operations

Commands: Iscomg, Isrpdomain, Isrpnode, mkrpdomain, preprpnode, rmcomg, startrpdomain

Information Files: rmccli, for general information about RMC-related commands

mkcondition Command

Purpose

Creates a new condition definition which can be monitored.

Syntax

```
mkcondition -r resource_class -e"event_expression" [ -E"rearm_expression" ]
[ -d "event_description" ] [ -D "rearm_description" ]
[ -m I | m | p ] [-n node_name1[,node_name2...]]
[-p node_name] [ --qnotoggle | --qtoggle ]
[-s "selection_string"] [-S c |w |i]
[-h] [-TV] condition
mkcondition -c existing_condition[:node_name] [-r resource_class]
[ -e "event_expression" ] [ -E "rearm_expression" ]
[ -d "event_description" ] [ -D "rearm_description" ]
[-m | m | p | [-n node_name1[,node_name2...]]
[-p node_name][ --qnotoggle | --qtoggle ]
[-s "selection_string"] [ -S c | w | i ]
[-h] [-TV] condition
```

Description

The **mkcondition** command creates a new condition with the name specified by the *condition* parameter. The condition is used to monitor a resource for the occurrence of the condition (or event). Use the mkresponse command to define one or more responses to an event. You can then link the conditions to the responses using the mkcondresp command, or you can use the startcondresp command to link the responses and start monitoring.

In a cluster environment, use the -p flag to specify the node in the domain that is to contain the condition definition. If you are using **mkcondition** on the management server and you want the condition to be defined on the management server, do not specify the -p flag. If the -p flag is not specified, the condition is defined on the local node. If the node where the condition will be defined is:

- in a cluster of nodes, the condition can monitor resources on more than one node. Use the -n flag to specify the nodes on which the condition will be monitored.
- the management server in a management domain, a management scope (-m) of local (I) or management domain (m) can be specified to indicate how the condition applies. The selection string will be evaluated using the entire management domain when management scope is set to the management domain and the node is the management server.
- a managed node in a management domain, only a management scope (-m) of local (I) can be used.
- in a peer domain, a management scope (-m) of peer domain (p) or local (I) can be used to indicate how the condition and the selection string apply.
- in both a management domain and a peer domain, a management scope (-m) of management domain (m), peer domain (p), or local (I) can be used to indicate how the condition and its selection string apply.

To lock a condition so it cannot be modified or removed, use the **chcondition** command (with its **-L** flag).

If Cluster Systems Management (CSM) is installed on your system, you can use CSM defined node groups as node name values to refer to more than one node. For information about working with CSM node groups and using the CSM nodegrp command, see the CSM: Administration Guide and the CSM: Command and Technical Reference.

Flags

-c existing condition[:node name]

Copies an existing condition. The existing condition is defined on node_name. If node_name is not specified, the local node is used. node name is a node within the scope determined by the CT_MANAGEMENT_SCOPE environment variable. If any other flags are specified, update the new condition as indicated by the flags. Links with responses are not copied.

-e "event expression"

Specifies an event expression, which determines when an event occurs. An event expression consists of a dynamic attribute or a persistent attribute of resource class, a mathematical comparison symbol (> or <, for example), and a constant. When this expression evaluates to TRUE, an event is generated.

-E "rearm expression"

Specifies a rearm expression. After event expression has evaluated to TRUE and an event is generated, the rearm expression determines when monitoring for the event expression will begin again. Typically,the rearm expression prevents multiple events from being generated for the same event evaluation. The rearm expression consists of a dynamic attribute of resource class, a mathematical comparison symbol (>, for example), and a constant.

-d "event description"

Describes the event expression.

-D "rearm_description"

Describes the rearm expression.

-n node name1[,node name2...]

Specifies the host name for a node (or a list of host names separated by commas for multiple nodes) where this condition will be monitored. Node group names can also be specified, which are expanded into a list of node names. You must specify the -m flag with a value of m or p if you want to use the -n flag. This way, you can monitor conditions on specific nodes instead of the entire domain.

The host name does not have to be online in the current configuration, but once the condition is monitored, the condition will be in error if the node does not exist. The condition will remain in error until the node is valid.

-p node name

Specifies the name of the node where the condition is defined. This is used in a cluster environment and the node name is the name by which the node is known in the domain. The default node_name is the local node on which the command runs. node_name is a node within the scope determined by the CT MANAGEMENT SCOPE environment variable.

If you are using **mkcondition** on the management server and you want the condition to be defined on the management server, do not specify the -p flag.

--qnotoggle

Specifies that monitoring does not toggle between the event expression and the rearm expression, but instead the event expression is always evaluated.

--qtoggle

Specifies that monitoring toggles between the event expression and the rearm expression.

-r resource_class

Specifies the resource class to be monitored by this condition. You can display the resource class names using the Isrsrcdef command.

-s "selection_string"

Specifies a selection string that is applied to all of the resource class attributes to determine which resources should be monitored by the event_expression. The default is to monitor all resources within the resource class. The resources used to evaluate the selection string is determined by the management scope (the -m flag). The selection string must be enclosed within double or single quotation marks. For information on how to specify selection strings, see the RSCT: Administration Guide .

-S c | w | i

Specifies the severity of the event:

- Critical
- w Warning
- i Informational (the default)

-m I | m | p

Specifies the management scope to which the condition applies. The management scope determines how the condition is registered and how the selection string is evaluated. The scope can be different from the current configuration, but monitoring cannot be started until an appropriate scope is selected. The valid values are:

- ī Specifies local scope. This is the default. The condition applies only to the local node (the node where the condition is defined; see the -p flag). Only the local node is used in evaluating the selection string.
- Specifies management domain scope. The condition applies to the management domain in m which the node where the condition is defined belongs (see the -p flag). All nodes in the management domain are used in evaluating the selection string. The node where the condition is defined must be the management server in order to use management domain scope.
- Specifies peer domain scope. The condition applies to the peer domain in which the node р where the condition is defined belongs (see the -p flag). All nodes in the peer domain are used in evaluating the selection string.
- -h Writes the command's usage statement to standard output.
- _T Writes the command's trace messages to standard error. For your software service organization's use only.
- -V Writes the command's verbose messages to standard output.

Parameters

condition

The *condition* name is a character string that identifies the condition. If the name contains spaces, it must be enclosed in quotation marks. A name cannot consist of all spaces, be null, or contain embedded double quotation marks.

Security

The user needs write permission for the IBM.Condition resource class to run mkcondition. Permissions are specified in the access control list (ACL) file on the contacted system. See the RSCT: Administration Guide for details on the ACL file and how to modify it.

Exit Status

- 0 The command ran successfully.
- 1 An error occurred with RMC.
- 2 An error occurred with a command-line interface script.
- 3 An incorrect flag was entered on the command line.
- 4 An incorrect parameter was entered on the command line.
- 5 An error occurred that was based on incorrect command-line input.

Environment Variables

CT CONTACT

Determines the system where the session with the resource monitoring and control (RMC) daemon occurs. When CT CONTACT is set to a host name or IP address, the command contacts the RMC daemon on the specified host. If CT CONTACT is not set, the command contacts the RMC daemon on the local system where the command is being run. The target of the RMC daemon session and the management scope determine the resource classes or resources that are processed.

CT_IP_AUTHENT

When the CT IP AUTHENT environment variable exists, the RMC daemon uses IP-based network authentication to contact the RMC daemon on the system that is specified by the IP address to which the CT_CONTACT environment variable is set. CT_IP_AUTHENT only has meaning if CT_CONTACT is set to an IP address; it does not rely on the domain name system (DNS) service.

CT MANAGEMENT SCOPE

Determines the management scope that is used for the session with the RMC daemon in processing the resources of the event-response resource manager (ERRM). The management scope determines the set of possible target nodes where the resources can be processed. The valid values are:

- Specifies *local* scope.
- 1 Specifies *local* scope.
- 2 Specifies peer domain scope.
- Specifies management domain scope.

If this environment variable is *not* set, *local* scope is used.

Implementation Specifics

This command is part of the Reliable Scalable Cluster Technology (RSCT) fileset for AIX.

Standard Output

When the **-h** flag is specified, this command's usage statement is written to standard output. All verbose messages are written to standard output.

Standard Error

All trace messages are written to standard error.

Examples

These examples apply to standalone systems:

1. To define a condition with the name "FileSystem space used" to check for percentage of space used greater than 90% and to rearm when the percentage is back down below 85%, enter:

```
mkcondition -r IBM.FileSystem \
-e "PercentTotUsed > 90" -E "PercentTotUsed < 85" \
"FileSystem space used"</pre>
```

2. To define a condition with the name "tmp space used" to check for percentage of space used greater than 90% for /tmp and to rearm when the percentage is back down below 85%, including comments, enter:

```
mkcondition -r IBM.FileSystem \ -e "PercentTotUsed > 90" -E "PercentTotUsed < 85" \ -d "Generate event when tmp > 90% full" \ -D "Restart monitoring tmp again after back down < 85% full"\ -s 'Name=="/tmp"' "tmp space used"
```

3. To define a condition with the name "Space used" as a copy of "FileSystem space used", enter:

```
mkcondition -c "FileSystem space used" "Space used"
```

4. To define a condition with the name "var space used" as a copy of "tmp space used", but change the selection to **/var**, enter:

```
mkcondition -c "tmp space used" -s 'Name=="/var"' \
"var space used"
```

5. To define a condition with the name "vmstat is running" to monitor when user **joe** is running the **vmstat** program in a 64-bit environment, enter:

```
mkcondition -r "IBM.Program" \
-e "Processes.CurPidCount > 0" -E "Processes.CurPidCount <= 0" \
-d "Generate event when user starts vmstat" \
-D "Restart monitoring when vmstat is terminated" \
-s ProgramName == \"vmstat64\" && Filter==\"ruser==\\\"joe\\\"\"" \
-S "j" -m "]" "vmstat is running"</pre>
```

6. To define a condition with the name "myscript terminated" to monitor when a script has ended, enter:

```
mkcondition -r "IBM.Program" \
-e "Processes.CurPidCount <= 0" -E "Processes.CurPidCount > 0" \
-d "Generate event when myscript is down" \
-D "Rearm the event when myscript is running" \
-s ProgramName == \"ksh\" && Filter == 'args[1]==\"/home/joe/myscript\"'" \
-m "]" "myscript terminated"
```

In this example, **args** represents the array of argument strings that was passed to **main**. Because this is an array, **args[1]** references the first argument after the program name. Use the **ps -el** command to determine the **ProgramName**. See the **Isrsrcdef** command for more information.

These examples apply to management domains:

1. To define a condition with the name "FileSystem space used" to check for percentage of space used greater than 90%, to rearm when the percentage is back down below 85%, and to monitor all nodes in the domain, run this command on the management server:

```
mkcondition -r IBM.FileSystem -e "PercentTotUsed > 90" \
-E "PercentTotUsed < 85" -m d "FileSystem space used"</pre>
```

2. To define a condition with the name "FileSystem space used" to check for percentage of space used greater than 90%, to rearm when the percentage is back down below 85%, and to monitor nodes nodeA and nodeB in the domain, run this command on the management server:

```
mkcondition -r IBM.FileSystem -e "PercentTotUsed > 90" \
-E "PercentTotUsed < 85" -n nodeA,nodeB -m d \
"FileSystem space used"
```

3. To define a condition with the name "nodeB FileSystem space used" on nodeB to check for percentage of space used greater than 90%, to rearm when the percentage is back down below 85%, and to monitor the condition with local scope, run this command on the management server:

```
mkcondition -r IBM.FileSystem -e "PercentTotUsed > 90" \
-E "PercentTotUsed < 85" -m 1 -p nodeB \
"nodeB FileSystem space used"
```

4. To define a condition with the name "local FileSystem space used" to check for percentage of space used greater than 90%, to rearm when the percentage is back down below 85%, and to monitor the local node, run this command on a managed node:

```
mkcondition -r IBM.FileSystem -e "PercentTotUsed > 90" \
-E "PercentTotUsed < 85" -m 1 "local FileSystem space used"
```

These examples apply to peer domains:

1. To define a condition on nodeA with the name "FileSystem space used" to check for percentage of space used greater than 90%, to rearm when the percentage is back down below 85%, and to monitor all nodes in the domain, run this command:

```
mkcondition -r IBM.FileSystem -e "PercentTotUsed > 90" \
-E "PercentTotUsed < 85" -m p -p nodeA "FileSystem space used"
```

2. To define a condition on **nodeC** with the name "FileSystem space used" to check for percentage of space used greater than 90%, to rearm when the percentage is back down below 85%, and to monitor nodes nodeA and nodeB in the domain, run this command:

```
mkcondition -r IBM.FileSystem -e "PercentTotUsed > 90" \
-E "PercentTotUsed < 85" -n nodeA,nodeB -m p -p nodeC \
"FileSystem space used"
```

3. To define a condition with the name "local FileSystem space used" on **nodeB** to check for percentage of space used greater than 90%, to rearm when the percentage is back down below 85%, and to monitor the local node only, run this command:

```
mkcondition -r IBM.FileSystem -e "PercentTotUsed > 90" \
-E "PercentTotUsed < 85" -m l -p nodeB "local FileSystem space used"
```

Location

/usr/sbin/rsct/bin/mkcondition

Related Information

Books:

- CSM: Administration Guide, for information about node groups
- CSM: Command and Technical Reference, for information about the nodegrp command
- RSCT: Administration Guide, for information about RMC operations and about how to use expressions and selection strings

Commands: chcondition, Iscondition, mkcondresp, mkresponse, nodegrp, rmcondition, startcondresp

Information Files: rmccli

mkcondresp Command

Purpose

Creates a link between a condition and one or more responses.

Syntax

mkcondresp [-h] [-TV] condition[:node name] response1 [response2...]

Description

The **mkcondresp** command creates a link between a condition and one or more responses. A link between a condition and a response is called a *condition/response association*. This command creates one or more condition/response associations; it does not start monitoring. In a cluster environment, the condition and the response must be defined on the same node. You can start monitoring for this condition and its linked responses later using the **startcondresp** command.

To lock a condition/response association, use the **-L** flag of the **rmcondresp**, **startcondresp**, or **stopcondresp** command.

Flags

- -h Writes the command's usage statement to standard output.
- **-T** Writes the command's trace messages to standard error. For your software service organization's use only.
- -V Writes the command's verbose messages to standard output.

Parameters

condition Specifies the name of the condition to be linked to the response. The condition is always

specified first.

node name Specifies the node in the domain where the condition is defined. If node name is not

specified, the local node is used. *node_name* is a node within the scope determined by

the CT MANAGEMENT SCOPE environment variable.

response1 [response2...]

Specifies one or more response names. All responses are linked to condition.

Security

The user needs write permission for the **IBM.Association** resource class to run **mkcondresp**. Permissions are specified in the access control list (ACL) file on the contacted system. See the *RSCT: Administration Guide* for details on the ACL file and how to modify it.

Exit Status

- The command ran successfully.
- 1 An error occurred with RMC.
- 2 An error occurred with a command-line interface script.
- 3 An incorrect flag was entered on the command line.
- 4 An incorrect parameter was entered on the command line.
- 5 An error occurred that was based on incorrect command-line input.

Environment Variables

CT CONTACT

Determines the system where the session with the resource monitoring and control (RMC) daemon occurs. When CT_CONTACT is set to a host name or IP address, the command contacts the RMC daemon on the specified host. If CT_CONTACT is not set, the command contacts the RMC daemon on the local system where the command is being run. The target of the RMC daemon session and the management scope determine the resource classes or resources that are processed.

CT IP AUTHENT

When the CT IP AUTHENT environment variable exists, the RMC daemon uses IP-based network authentication to contact the RMC daemon on the system that is specified by the IP address to which the CT_CONTACT environment variable is set. CT_IP_AUTHENT only has meaning if CT_CONTACT is set to an IP address; it does not rely on the domain name system (DNS) service.

CT_MANAGEMENT_SCOPE

Determines the management scope that is used for the session with the RMC daemon in processing the resources of the event-response resource manager (ERRM). The management scope determines the set of possible target nodes where the resources can be processed. The valid values are:

- Specifies local scope.
- 1 Specifies local scope.
- 2 Specifies peer domain scope.
- Specifies management domain scope.

If this environment variable is not set, local scope is used.

Implementation Specifics

This command is part of the Reliable Scalable Cluster Technology (RSCT) fileset for AIX.

Standard Output

When the -h flag is specified, this command's usage statement is written to standard output. All verbose messages are written to standard output.

Standard Error

All trace messages are written to standard error.

Examples

These examples apply to standalone systems:

- 1. To link the condition "FileSystem space used" to the response "Broadcast event on-shift", run this command:
 - mkcondresp "FileSystem space used" "Broadcast event on-shift"
- 2. To link the condition "FileSystem space used" to the responses "Broadcast event on-shift" and "E-mail root anytime", run this command:

```
mkcondresp "FileSystem space used" "Broadcast event on-shift" "E-mail root anytime"
```

These examples apply to management domains:

1. To link the condition "FileSystem space used" on the management server to the response "Broadcast event on-shift" (also on the management server), run this command on the management server:

```
mkcondresp "FileSystem space used" "Broadcast event on-shift"
```

2. To link the condition "FileSystem space used" on the management server to the response "Broadcastevent on-shift", run this command on one of the nodes in the domain:

mkcondresp "FileSystem space used":nodeA "Broadcast event on-shift"

This example applies to peer domains:

1. To link the condition "FileSystem space used" on node **nodeA** to the response "Broadcastevent on-shift" (also on nodeA), run this command on one of the nodes in the domain:

mkcondresp "FileSystem space used":nodeA "Broadcast event on-shift"

Location

/usr/sbin/rsct/bin/mkcondresp

Related Information

Books: RSCT: Administration Guide, for more information about ERRM operations and about how to use expressions and selection strings

Commands: Iscondresp, mkcondition mkresponse, rmcondresp, startcondresp, stopcondresp

Information Files: rmccli

mkcosi Command

Purpose

Makes a Common Operating System Image (COSI) for use with thin servers.

Syntax

mkcosi -s Source [-I Location] [-S Server] [-v] COSI

Description

The mkcosi command creates a Common Operating System Image (COSI). A COSI is a repository that contains all the necessary software to bring a thin server up to a functional state. The mkcosi command takes a source (-s Source) containing installable images and attempts to install those software images into a specific location (-I Location). If the -S Server is specified, the COSI image is stored on that particular server. The result is an OS image that can be used by thin servers as its boot image and operating system.

This command is dependent upon the bos.sysmgt.nim.master fileset being present on the system. When this command is executed for the first time, the machine executing the command will be configured as a NIM master. The mkcosi command uses the nim_master_setup command to configure the machine as a NIM master. The -S parameter must point to a machine that is managed by the caller of the mkcosi command.

Flags

-s Source

Specifies the full path name to a location for storing the COSI.

-S Server Specifies the name of the machine where the COSI image resides.

> Specifies the source of installable images to be used in creating the COSI. The source can be an **lpp source**, a device with installable media, a directory to installable images, or a remote location to installable images.

Enables verbose debug output when the mkcosi command runs.

-v

Exit Status

The command completed successfully. An error occurred.

Security

Access Control: You must have root authority to run the **mkcosi** command.

Examples

1. To define a COSI named cosil from a CD-ROM cd0, and to store it at /export/cosil, enter: mkcosi -s cd0 -l /export/cosi1 cosi1

Location

/usr/sbin/mkcosi

Files

/etc/niminfo

Contains variables used by NIM.

Related Information

The chcosi command, cpcosi command, "Iscosi Command" on page 350, "mkts Command" on page 692, nim command, nim clients setup command, nim master setup command, nimconfig command, rmcosi command.

mkdev Command

Purpose

Adds a device to the system.

Syntax

mkdev { -c Class -s Subclass -t Type } [-I Name] [-a Attribute=Value] ... [-d | -S | -R] [-f File] [-h] [-p ParentName | [-q] [-w ConnectionLocation]

mkdev - | Name [- h] [-q] [- S]

Description

Attention: To protect the Configuration Database, the mkdev command is not interruptible. Stopping this command before it is complete could result in a corrupted database.

The **mkdev** command performs the following:

- Defines and makes available a device with the given device class (-c Class flag), type (-t Type flag), subclass (-s Subclass flag), connection location (-w ConnectionLocation flag), and the device logical name of the parent (-p ParentName flag)
- Makes available the previously defined device specified by the given device logical name (-I Name flag).

You can use any combination of the -c, -s, and -t flags you need to uniquely identify the predefined device.

If you specify the -d flag, the mkdev command only defines the device. If you specify the -S flag, the mkdev command brings the device to the Stopped state, if this state is supported, and does not make the device available. If you do not specify either the -d flag or the -S flag, the mkdev command makes the device available.

If you specify the -R flag, the mkdev command configures any previously-defined parents of the specified device that are not already configured. The -R flag is not compatible with the -d and -S flags.

By using the -I flag with the -c, -s, and -t flags, you can specify the name of the device. If you do not use the -I flag, a name will be automatically generated and assigned. Not all devices support user-supplied names.

Note: Queue device names must begin with an alphabetic character.

When using the mkdev command, you can supply the flags either on the command line or in the specified -f File flag.

You can use the Web-based System Manager Devices application (wsm devices fast path), or the System Management Interface Tool (SMIT) smit mkdev fast path to run this command.

Flags

Specifies the device attribute-value pairs to be used instead of the defaults. The <i>Attribute=Value</i> variable can be used to specify one attribute value pair or multiple attribute value pairs for one -a flag. Multiple attribute-value pairs must be enclosed in quotation marks with a blank space between the pairs. For example, entering -a Attribute=Value lists one attribute value pair per flag, while entering -a 'Attribute1=Value1 Attribute2=Value2' lists more than one attribute value pair. This flag cannot be used with the -I flag unless the -c , -s , and -t flags are also used.
Specifies the device class.
Defines the device in the Customized Devices object class. If you specify the -d flag, the mkdev command does not make the device available. This flag cannot be used with the -S flag.
Reads the necessary flags from the File parameter.
Displays the command usage message.
Specifies the predefined device, indicated by the <i>Name</i> variable, in the Customized Devices object class when not used with the -c , -s , and -t flags. The -a , -p , and -w flags cannot be used in this case. Queue device names must begin with an alphabetic character.
Specifies the device name, indicated by the <i>ParentName</i> variable, that you want assigned to the device when it is used with the -c , -s , and -t flags. Not all devices support this feature. This flag cannot be used with the -I flag unless the -c , -s , and -t flags are also used.
Suppresses the command output messages from standard output and standard error.
Configures any parents of the device that are not already configured. This flag cannot be used with the -d and -S flags.
Prevents the device from being set to the Available state. This flag is only meaningful for those devices that support the Stopped state. This flag cannot be used with the -d flag.
Specifies the subclass, indicated by the <i>Subclass</i> variable, of the device.
Specifies the device type from the Predefined Devices object class.

-w ConnectionLocation

Specifies the connection location, indicated by the ConnectionLocation variable, on the parent. This flag cannot be used with the -I flag unless the -c, -s, and -t flags are also used.

Exit Status

This command returns the following exit values:

Successful completion. An error occurred. >0

Security

Privilege Control: Only the root user and members of the system group should have execute (x) access to this command.

Auditing Events:

Information **Event**

DEV_Create Method name, parameters

DEV_Configure Errors Device name DEV_Start

DEV_Change **Parameters**

Examples

1. To define (but not configure) a 4.0 GB 4mm Tape Drive connected to the scsi0 SCSI adapter and using SCSI ID 5 and LUN of 0, type the following:

```
mkdev -d -c tape -t4mm2gb -s scsi -p scsi0 -w 5,0
```

The system displays a message similar to the following:

rmt4 defined

2. To make the predefined rmt0 tape device available to use, type the following:

```
mkdev -1 rmt0
```

The system displays a message similar to the following:

3. To define and configure an RS-232 tty device connected to port 0 on the IBM 8-Port EIA-232/RS-422A (PCI) Adapter with the speed attribute set to 19200, and other attributes set from the foo file, type the following:

```
mkdev -t tty -s rs232 -p sa3 -w 0 -a speed=19200 -f foo
```

The system displays a message similar to the following:

tty0 available

Files

/usr/sbin/mkdev Contains the mkdev command.

Related Information

The chdev command, Isattr command, Isconn command, Isdev command, Isparent command, rmdev command.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

For information about the SMIT application, see System management interface tool in Operating system and device management.

mkdir Command

Purpose

Creates one or more new directories.

Syntax

mkdir [-m Mode] [-p] Directory ...

Description

The **mkdir** command creates one or more new directories specified by the *Directory* parameter. Each new directory contains the standard entries. (dot) and .. (dot-dot). You can specify the permissions for the new directories with the -m Mode flag. You can use the umask subroutine to set the default mode for the mkdir command.

The owner-ID and group-ID of the new directories are set to the process's effective user-ID and group-ID, respectively. The setgid bit setting is inherited from the parent directory. To change the setgid bit, you can either specify the -m Mode flag or issue the chmod command after the creation of the directory.

Note: To make a new directory you must have write permission in the parent directory.

Flags

-m Mode

Sets the permission bits for the newly-created directories to the value specified by the Mode variable. The Mode variable takes the same values as the Mode parameter for the chmod command, either in symbolic or numeric form.

When you specify the -m flag using symbolic format, the op characters + (plus) and -(minus) are interpreted relative to the assumed permission setting a=rwx. The + adds permissions to the default mode, and the - deletes permissions from the default mode. Refer to the **chmod**command for a complete description of permission bits and formats. Creates missing intermediate path name directories. If the -p flag is not specified, the parent directory of each-newly created directory must already exist.

Intermediate directories are created through the automatic invocation of the following mkdir commands:

```
mkdir -p -m $(umask -S),u+wx $(dirname Directory) &&
mkdir [-m Mode] Directory
```

where the [-m Mode] represents any option supplied with your original invocation of the mkdir command.

The **mkdir** command ignores any *Directory* parameter that names an existing directory. No error is issued.

-p

Exit Status

This command returns the following exit values:

- 0 All the specified directories were created successfully, or the -p option was specified and all the specified directories now exist.
- >0 An error occurred.

Examples

1. To create a new directory called Test in the current working directory, enter:

mkdir Test

The Test directory is created with default permissions.

2. To create a new directory called Test with rwxr-xr-x permissions in the previously created /home/demo/sub1 directory, enter:

mkdir -m 755 /home/demo/sub1/Test

3. To create a new directory called Test with default permissions in the /home/demo/sub2 directory, enter: mkdir -p /home/demo/sub2/Test

The -p flag creates the /home, /home/demo, and /home/demo/sub2 directories if they do not already exist.

Files

/usr/bin/mkdir

Contains the mkdir command.

Related Information

The chmod command, rm command.

The **mkdir** subroutine, **umask** subroutine.

Directories in Operating system and device management.

File and directory access modes in the Operating system and device management introduces file ownership and permissions to access files and directories.

Shells in Operating system and device management.

mkdirhier Command

Purpose

Creates a hierarchy of directories or a single directory.

Syntax

mkdirhier Directory ...

Description

The mkdirhier command creates the specified directories. Unlike the mkdir command, if any of the parent directories of the specified directory do not exist, the mkdirhier command creates those directories as well as the specified directory.

Example

To create a directory named **foo2** or to create a hierarchy of directories named **foo, foo1**, and **foo2**, enter: mkdirhier ~/foo/foo1/foo2

If foo and foo1 already exist then the command creates foo2. However, if none of them exist then the command creates all three new directories.

Related Information

The mkdir command.

mkdvd Command

Purpose

Creates a multi-volume DVD (or DVDs) from a mksysb or savevg backup image.

Syntax

mkdvd -r directory | -d dvd_device | -S [-m mksysb_image | -M mksysb_target | -s savevg_image | -v savevg_volume_group] [-C cd_fs_dir] [-I cd_image_dir] [-V dvdfs_volume_group] [-B] [-p pkg_source_dir | [-R | -S | [-i image.data | [-u bosinst.data | [-e | [-P | [-I package_list | [-b bundle_file] [-z custom_file] [-D] [-U] [-Y] [-n] [-a] [-A] [-c]

Description

The **mkdvd** command creates a system backup image (**mksysb**) to DVD-Recordable (DVD-R, DVD-RAM) from the system rootvg or from a previously created mksysb image. It also creates a volume group backup image (savevg) to DVD from a user-specified volume group or from a previously created savevg image.

Note: If the system has a multibos environment where both instances are mounted, you can restore the backup only by using the alt disk mksysb command.

For DVD media, system backups made with the **mkdvd** command have a limitation in that they expect the media to be 4.7 GB or larger per side. The **mkdvd** command does not process the next volume until it writes over 4 GB on the current volume, thus the use of smaller media would result in corruption when going beyond the media capacity.

When a bootable backup of a root volume group is created, the boot image reflects the currently running kernel. If the current kernel is the 64-bit kernel, the backup boot image is also 64 bit, and it only boots 64-bit systems. If the current kernel is a 32-bit kernel, the backup boot image is 32 bit, and it can boot both 32-bit and 64-bit systems.

With the mkdvd command, you can create bootable and non-bootable DVDs in Rock Ridge (ISO9660) or UDF (Universal Disk Format) format.

Note: The functionality required to create Rock Ridge format DVD images and to write the DVD image to the DVD-RAM device is not part of the **mkdvd** command. You must supply additional code to the mkdvd command to do these tasks. The code will be called via shell scripts and then linked to /usr/sbin/mkrr fs (for creating the Rock Ridge format image) and /usr/sbin/burn cd (for writing to the DVD device). Both links are called from the **mkdvd** command.

Some sample shell scripts are included for different vendor-specific routines. You can find these scripts in /usr/samples/oem cdwriters.

If you do not supply any file systems or directories as command parameters, the **mkdvd** command creates the necessary file systems and removes them when the command finishes executing. File systems you supply are checked for adequate space and write access.

Note: If the mkdvd command creates file systems in the backup volume group, they are excluded from the backup.

If you need to create multi-volume DVDs because the volume group image does not fit on one DVD, the mkdvd command provides instructions for DVD replacement and removal until all the volumes have been created.

Flags

Does not back up extended attributes or NFS4 ACLs. -a

-A Backs up DMAPI file system files.

Does not compress or pack files as they are backed up. -C

-d dvd device Indicates the DVD-R or DVD-RAM device (/dev/cd1, for instance). This flag is

required unless you use the -S flag.

-r directory Indicates existing directory structure to burn onto a DVD. This makes a DVD image

that is a copy of the given directory structure.

-m mksysb_image Specifies a previously created mksysb image. If you do not specify the -m flag, the

mkdvd command calls mksysb. (See the -M flag for more information about where

the **mksysb** image is placed.)

-s savevg_image Indicates a previously created savevg image. See Notes for details.

Denotes the volume group to be backed up using the savevg command. See Notes -v savevg_volume_group

for details. (See the -M flag for more information about where the savevg image is

-C cd fs dir Specifies the file system used to create the DVD file system structure, which must

have up to 4.38 GB for DVD sized images. The DVD image only consumes as much

room as necessary to contain all the data on the DVD.

If you do not specify the -C flag and the /mkcd/cd_fs directory exists, the mkdvd command uses that directory. If you do not specify the -C flag and the /mkcd/cd_fs directory does not exist, the mkdvd command creates the file system /mkcd/cd_fs and removes it when the command finishes executing. The command creates the file system in the volume group indicated with the -V flag, or rootvg if that flag is not used. Each time you invoke the mkdvd command, a unique subdirectory (using the process id) is created under the /mkcd/cd_fs directory, or in the directory specified with the -C flag.

Note: If performing DVD sized backups, the file systems need to be large file

enabled. This also requires setting the file ulimit size to unlimited.

States the directory or file system where the mksysb or savevg image is stored if a previously created backup is not given with the -m or -s flags. If the -M flag is not used and a mksysb or savevg image is not provided, the mkdvd command verifies that /mkcd/mksysb_image exists. If the directory does not exist, then the mkdvd command creates a separate file system, /mkcd/mksysb_image, where the mksysb or savevg images are temporarily stored. The command creates the file system in

the volume group given with the -V flag, or in rootvg if that flag is not used. Note: If performing DVD sized backups, the file systems need to be large file

enabled. This also requires setting the file ulimit size to unlimited.

-M mksysb_target

-I cd_images_dir

Specifies the directory or file system where the final DVD images are stored before writing to the DVD-R or DVD-RAM device. If this flag is not used, the **mkdvd** command uses the **/mkcd/cd_images** directory if it already exists. If not, the command creates the **/mkcd/cd_images** file system in the volume group given with the **-V** flag, or in **rootvg** if that flag is not used.

If the **mkdvd** command creates the file system, it is removed upon command completion, unless either the **-R** or **-S** flag is used. If the **-R** or **-S** flag is used, consideration must be made for adequate file system, directory, or disk space, especially when creating multi-volume DVDs. The DVD image will only consume as much room as necessary to contain all the data on the DVD.

Note: If performing DVD sized backups, the file systems need to be *large file enabled*. This also requires setting the file **ulimit** size to *unlimited*.

Indicates the volume group used when creating the file systems needed for the **mkdvd** command. If the **-V** flag is not given and a file system is needed but not there (because it was not supplied with other flags), then **rootvg** is the default volume group for creating the file systems. If the **mkdvd** command creates the file systems in the backup volume group, those file systems are not included as part of the backup image. The **mkdvd**-created file systems are removed upon the command completion.

Names the directory or device that contains device and kernel package images. The device can only be a CD or DVD device (for example, /dev/cd0). If you use the same DVD-R or DVD-RAM device that you gave with the -d flag, the product media must be inserted into the drive first. The mkdvd command then prompts you to insert the writable DVD before the actual DVD creation.

Prevents the **mkdvd** command from adding boot images (non-bootable DVD) to the DVD. Use this flag if creating a **mksysb** DVD that you will not boot. Before installing the non-bootable **mksysb** DVD, you must boot a same level (V.R.M.) product media. The **mkdvd** command defaults to creating a bootable DVD for the machine type of the source system. See Notes for details.

Prevents the **mkdvd** command from removing the final DVD images. The **mkdvd** defaults by removing everything that it creates when it finishes executing. The **-R** flag allows multiple DVD image sets to be stored, or for DVD creation (burn) to occur on another system. If multiple volumes are needed, the final images are uniquely named using the process ID and volume suffixes.

Stops the **mkdvd** command before writing to the DVD-R or DVD-RAM without removing the final DVD images. The **-S** flag allows multiple DVD sets to be created, or for DVDs to be created on another system. The images remain in the directory marked by the **-I** flag, or in the **/mkcd/cd_images** directory if the **-I** flag is not used. If multiple volumes are required, the final images are uniquely named using the process ID and volume suffixes.

Specifies the user-supplied *bosinst.data* file. This data file takes precedence over the **bosinst.data** file in the **mksysb** image. If you do not give the **-u** flag, then the **mkdvd** command restores **bosinst.data** from the given **mksysb** image, or generates a new **bosinst.data** file during the creation of **mksysb**.

Specifies the user-supplied *image.data* file. This data file takes precedence over the **image.data** file in the **mksysb** image. If you do not specify the **-i** flag, then the **mkdvd** command restores the **image.data** from the given **mksysb** image, or generates a new **image.data** file during the creation of **mksysb**.

Note: The **-i** flag cannot be used to specify a user-supplied *vgname.data* file for use with a **savevg** image.

Excludes the files and directories from the backup image listed in the <code>/etc/exclude.volume_group</code> file. You cannot use this flag with the <code>-m</code> or <code>-s</code> flags. Creates physical partition mapping during the <code>mksysb</code> or <code>savevg</code> creation. You cannot use this flag with the <code>-m</code> or <code>-s</code> flags.

Specifies the file containing a list of additional packages you want copied to the <code>./usr/lpp/inst.images</code> directory of the DVD file system. The images are copied from the location named with the <code>-p</code> flag. If you use the <code>-I</code> flag you must also use the <code>-p</code> flag.

-V dvdfs_volume_group

-p pkg_source_dir

-B

-R

-S

-u bosinst.data

-i image.data

-е

-P

-I package_list

-b bundle_file

Gives the full path name of the file containing a list of filesets to be installed after the mksysb is restored. This file is copied to ./usr/sys/inst.data/user_bundles/ bundle_file in the DVD file system and also copied to RAM in case the DVD is unmounted. The file would be listed as BUNDLES=/../usr/sys/inst.data/ user_bundles/bundle_file in the bosinst.data file.

-z custom_file

States the full pathname of the file to be copied to the root directory of the DVD file system. This file could be a customization script specified in the bosinst.data file, such as CUSTOMIZATION FILE=filename.

For example: If the file my script is in /tmp on the machine where the mkdvd command is running, then enter -z/tmp/my script and specify CUSTOMIZATION FILE=my script. The code copies the script to the root directory of the RAM file system before it executes.

-D -U

Turns on the debug output information feature. The default is no debug output. Creates a UDF (Universal Disk Format) file system on DVD-RAM media. It does not require the amount of free space needed to create Rock Ridge format backups. It does not need the /mkcd/cd_fs and /mkcd/cd_images file systems. Therefore, the only temporary disk space it needs is to create the backup image that will be copied to the media. This means that the -I and -C flags do not apply to the -U flag. Because the backup is copied to the media, images cannot be created and burned later or on another system. So, the -R flag and -S flag do not apply when using the -U flag. You need to specify a device to write to with the -d flag. The -U flag does not use the /usr/sbin/mkrr_fs or /usr/sbin/burn_cd file systems. Accepts licenses.

-Y -n

Backs up user volume group information and administration data files. This backs up files such as /tmp/vgdata/vgname/vgname.data and map files, if any exist. This does not backup user data files. This backup can be used to create a user volume group without restoring user data files. This cannot be done to rootvg.

Notes:

- 1. If you are creating a non-bootable DVD (using the -B flag), you cannot use the -p or -I flags.
- 2. If you are creating a non-bootable DVD with a savevg image (using the -s or -v flags), you cannot use the -p, -I, -u, -i, -z, or -b flags.

Examples

- 1. To generate a bootable system backup to the DVD-R device named /dev/cd1, enter: mkdvd -d /dev/cd1
- 2. To generate a system backup to the DVD-R or DVD-RAM device named /dev/cd1, enter: mkdvd -d /dev/cd1
- 3. To generate a non-bootable volume group backup of the volume group myvg to /dev/cd1, enter: mkdvd -d /dev/cd1 -v myvg

Note: All **savevg** backup images are non-bootable.

- 4. To generate a non-bootable system backup, but stop **mkdvd** before the DVD is created and save the final images to the /mydata/my cd file system, and create the other mkdvd file systems in myvg, enter: mkdvd -B -I /mydata/my cd -V myvg -S
- 5. To create a DVD or DVD that duplicates an existing directory structure such as the following:

/mycd/a /mycd/b/d /mycd/c/f/g

enter:

mkdvd -r /mycd -d /dev/cd1

After mounting with mount -o ro /dev/cdl /mnt, cd to /mnt; a find . -print command displays:

./a ./b ./b/d ./c ./c/f

Files

/usr/bin/mkdvd

Contains the mkdvd command.

Related Information

The **mksysb** command and **savevg** command.

The /image.data file and the bosinst.data file stanza descriptions file.

A procedure to verify the backup can be found in the article Creating system backups in the *Installation* and migration.

mkfifo Command

Purpose

Makes first-in-first-out (FIFO) special files.

Syntax

mkfifo [-m Mode] File ...

Description

The **mkfifo** command creates FIFO special files specified by the *File* parameter, in the order specified. If the **-m** *Mode* flag is not specified, the file mode of the FIFO file is the bitwise inclusive OR of the **S_IRUSR**, **S_IWUSR**, **S_IRGRP**, **S_IWGRP**, **S_IROTH**, and **S_IWOTH** permissions as modified by the file mode creation (see the **umask** command).

The **mkfifo** command functions similarly to the **mkfifo** subroutine.

Flags

-m Mode

Sets the file permission bits of the newly created FIFO file to the specified mode values. The *Mode* variable is the same as the mode operand defined for the **chmod** command. The characters + (plus sign) and - (minus sign), if used, are interpreted relative to the initial value **a=rw** (that is, having permissions of **rw-rw-rw-**).

Exit Status

This command returns the following exit values:

- **0** All the specified FIFO special files were created successfully.
- >0 An error occurred.

Examples

1. To create a FIFO special file with permissions prw-r-r-, enter:

```
mkfifo -m 644 /tmp/myfifo
```

This command creates the /tmp/myfifo file with read/write permissions for the owner and read permission for the group and for others.

2. To create a FIFO special file using the - (minus sign) operand to set permissions of prw-r—-, enter:

```
mkfifo -m g-w,o-rw /tmp/fifo2
```

This command creates the /tmp/fifo2 file, removing write permission for the group and all permissions for others.

Note: If more than one file is created using the - (minus sign) operand, separate each mode specifier with a comma and no spaces.

Files

/usr/bin/mkfifo

Contains the mkfifo command.

Related Information

The **chmod** command.

The **mkfifo** subroutine, **umask** subroutine.

mkfilt Command

Purpose

Activates or deactivates the filter rules.

Syntax

mkfilt -v 4 | 6 [-d] [-u] [-z P | D] [-g start | stop] [-i]

Description

Use the mkfilt command to activate or deactivate the filter rules. This command can also be used to control the filter logging function. IPsec filter rules for this command can be configured using the genfilt command, IPsec smit (IP version 4 or IP version 6), or Web-based System Manager in the Virtual Private Network submenu.

Flags

-v	IP version of the rules you want to activate. The value of 4 specifies IP version 4 and the value of 6
	specifies IP version 6. The default (when this flag is not used) is to activate both IP version 4 and IP
	version 6. All the filter rules defined in the filter rule table for the IP version(s) will be activated or
	deactivated.

- -d Deactivates the active filter rules. This flag cannot be used with the -u flag.
- Activates the filter rules in the filter rule table. This flag cannot be used with the -d flag. -u
- Sets the action of the default filter rule to Permit (P) or Deny (D). The default filter rule is the last rule -z in the filter rule table that will apply to traffic that does not apply to any other filter rules in the table. Setting the action of this rule to Permit will allow all traffic that does not apply to any other filter rules. Setting this action to Deny will not allow traffic that does not apply to any other filter rules.

This flag is used to either start (start) or stop (stop) the log functionality of the filter rule module. -g -i

Initialization flag. This flag only applies when the -u flag is also used. If the -i flag is used, all the filter rules with an "active" status will be activated. If not used, all the filter rules in the filter rule table will be activated.

mkfont Command

Purpose

Adds a font path name to the Object Data Manager (ODM) that is loaded by the low function terminal (LFT) at boot time.

Syntax

mkfont [FontPathName]

Description

The mkfont command adds a fully qualified font file path name to the ODM. At boot time, the LFT loads the new font and any other fonts found in the ODM. The list of font information acquired by the LFT is passed to the default display device driver. The display driver selects from this list the font that best fits the display. If a default font was selected using the **chfont** command, the device driver uses that font.

Note: This command can be run only from an LFT.

You can use the Devices application in Web-based System Manager (wsm) to change device characteristics. You could also use the System Management Interface Tool (SMIT) smit mkfont fast path to run this command.

Parameter

FontPathName The fully qualified pathname of a font file.

Security

The user must have root authority to execute this command.

Example

To add the font file /usr/lpp/fonts/Rom10.snf, enter the following command:

mkfont /usr/lpp/fonts/Rom10.snf

Files

/bin/mkfont Contains the mkfont command. /usr/lpp/fonts Contains the font directory.

Related Information

The **chfont** command. **Isfont** command.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

mkfontdir Command

Purpose

Creates a **fonts.dir** file from a directory of font files.

Syntax

mkfontdir [DirectoryName ...]

Description

The **mkfontdir** command creates a **fonts.dir** file from a directory of font files. For each directory argument, the mkfontdir command reads all of the bitmapped font files in the directory, searching for properties named FONT or the name of the file stripped of its suffix. These are used as font names, which are written to the fonts.dir file in the directory along with the name of the font file. The fonts.dir file is then used by the X server and the Font server to determine which fonts are available.

The kinds of font files read by the **mkfontdir** command depend upon the configuration parameters and typically include the following formats:

Portable Compile Format	(suffix .pcf)
Compressed PCF	(suffix .pcf.Z)
Server Natural Format	(suffix .snf)
Compressed SNF	(suffix .snf.Z)
Bitmap Distribution Format	(suffix .bdf)
Compressed BDF	(suffix .bdf.Z)

If a font exists in multiple formats, the most efficient format is used (PCF format before SNF then BDF formats).

Scalable fonts are not automatically recognized by mkfontdir. You can contruct a fonts.scale file (the format is identical to that in the fonts.dir file) containing entries for scalable fonts. Then, when you run mkfontdir on a directory, it copies entries from the fonts.scale file in that directory into the fonts.dir file it constructs in that directory.

You can create the fonts.alias file, which can be put in any directory of the font path, to map new names to existing fonts. This file should be edited by hand. The format is two columns separated by white space, with the first column containing aliases and the second column containing font-name patterns.

When a font alias is used by an X client, the X server searches for the name it references by looking through each font directory in turn. Therefore, the aliases and the font files do not need to be in the same directory.

To embed white space in aliases or font-name patterns, enclose them in double-quotation marks. To embed double-quotation marks, or any other characters, precede each character with a \ (backslash).

```
"magic-alias with spaces" "\"font\name\"with quotes"
regular-alias
                                fixed
```

If the character string FILE_NAMES_ALIASES stands alone on a line, each file name in the directory when stripped of its suffix (such as .pcf or .pcf.Z) is used as an alias for that font.

The X server and the Font Server look for fonts.dir and fonts.alias files in each directory in the font path each time the font path is set.

Examples

To create a **fonts.dir** file from a directory of font files, enter:

mkfontdir DirectoryName

If no directory name is specified, the mkfontdir command reads the current directory.

Files

/usr/lib/X11/fonts Is the directory containing font files, fonts.dir and fonts.alias files.

mkfs Command

Purpose

Makes a file system.

Syntax

mkfs [-b Boot][-l Label][-i i-Nodes][-o Options][-p Prototype][-s Size][-v VolumeLabel][-V VfsName] Device

Description

The **mkfs** command makes a new file system on a specified device. The **mkfs** command initializes the volume label, file system label, and startup block.

The *Device* parameter specifies a block device name, raw device name, or file system name. If the parameter specifies a file system name, the **mkfs** command uses this name to obtain the following parameters from the applicable stanza in the **/etc/filesystems** file, unless these parameters are entered with the **mkfs** command:

devDevice namevolVolume IDsizeFile system size

boot Program to be installed in the startup block

vfs Definition of the virtual file system

options File-system implementation-specific options of the form Keyword, Keyword=Value

Notes:

- The file system is created with the setgid (set group ID) bit enabled. The setgid bit determines the
 default group permissions. All directories created under the new file system have the same default
 group permissions.
- 2. The **mkfs** command does not alter anything in a mounted file system, including the file system label. The file system label changes when you change the mount point, unless the file system is mounted.
- 3. For information about creating a filesystem on a striped logical volume, refer to "File Systems on Striped Logical Volumes" on page 606 in the **mklv** documentation.
- 4. To create a JFS2 file system on a logical volume, the minor number of the logical volume must be greater than 3071.

Flags

-b Boot Names the program to be installed in block 0 of the new file system.

-i i-Nodes Specifies the initial number of i-nodes on the file system. This flag is ignored when creating a

journaled file system.

-I Label Specifies the file system label for the new file system.

Specifies a comma-separated list of virtual file system implementation-specific options. -o Options

The following options are specific to the Journaled File System (JFS):

-o ag={ 8 | 16 | 32 | 64 } Specifies the allocation group size in megabytes. An allocation group is a grouping of

inodes and disk blocks similar to BSD cylinder groups. The default ag value is 8.

-o bf={ true | false } Specifies a large file enabled file system. See JFS and large files for more

information. If you do not need a large file enabled file system, set this option to false;

this is the default. Specifying bf=true requires a fragment size of 4096 and

compress=no.

-o frag={ 512 | 1024 | 2048 |

4096 }

-o compress={ no | LZ }

Specifies the JFS fragment size in bytes. A file system fragment is the smallest unit of disk storage that can be allocated to a file. The default fragment size is 4096 bytes. Specifies data compression. If you do not want data to be compressed, set this option

to no. Selecting compression requires a fragment size of 2048 or less.

-o nbpi={ 512 | 1024 | 2048 | 4096 |8192 | 16384 | 32768 |

65536 | 131072 }

Specifies the number of bytes per i-node (nbpi). The nbpi is the ratio of file system size in bytes to the total number of i-nodes. The default nbpi value is 4096 bytes. The values 32768, 65536, and 131072 only apply to AIX 4.2 or later.

Notes:

1. File systems created with an aq value greater than 8 is not recognized on an AIX 4.1 system.

2. The aq, bf, compress, fraq, and nbpi attributes are set at file system creation and cannot be changed after the file system is successfully created. The size attribute defines the minimum file system size, and you cannot decrease it after the file system is created.

3. The root filesystem (/) cannot be compressed.

4. Some **nbpi** values and allocation group sizes are mutually exclusive. See "Understanding JFS Size Limitations" for information.

The following options are specific to the Enhanced Journaled File System (JFS2):

-o agblksize={ 512 | 1024 | Specifies the JFS2 block size in bytes. A file system block is the smallest unit of disk 2048 | 4096 } storage that can be allocated to a file. The default block size is 4096 bytes.

-o name=mountpoint Specifies the mount point for the file system.

-o log=LVName Specifies the log logical volume name. The specified logical volume is the logging

device for the new JFS2.

-o log=INLINE Specifies to place the log in the logical volume with the JFS2 file system. The

INLINE log will default to .4% of the logical volume size if logsize is not specified.

Specifies the size for an INLINE log in MBytes. Ignored if INLINE log not being used. -o logsize=Value Cannot be greater than 2047 MBytes and cannot be greater than 10% of the size of

the filesystem.

-o ea={v1 | v2} Specifies the format to be used to store named extended attributes in the JFS2 file

system. The v2 format provides support for scalable named extended attributes as well as support for NFS4 ACLs. The v1 format is compatible with prior releases of

AIX. The default format is v1.

Note: The agblksize attribute is set at file system creation and cannot be changed after the file system is successfully created.

The ea attribute format is set at file system creation. The chfs command can be used to convert the extended attribute format from v1 to v2, but the format cannot be converted back. The conversion is done in an on-demand manner such that any extended attribute or ACL writes cause the conversion for that file object to occur.

Specifies the name of the prototype file. Options specified on the command line override -p Prototype attributes in the prototype file.

-s Size

Specifies the size of the file system. Size can be specified in units of 512-byte blocks. Megabytes (suffix M should be used) or Gigabytes (suffix G should be used). See JFS and JFS2 for more information.

Notes:

- 1. The volume group in which the file system resides defines a maximum logical volume size and also limits the file system size.
- 2. The -s Size flag specifies the minimum file size and cannot be decreased after the file system has been successfully created.

-v VolumeLabel Specifies the volume label for the new file system.

Specifies the virtual file system (VFS) type. The VFS must have an entry in the /etc/vfs -V VfsName

Security

Access Control: Only the root user or a member of the system group can run this command.

Examples

1. To specify the volume and file system name for a new file system, type:

```
mkfs -lworks -vvol001 /dev/hd3
```

This command creates an empty file system on the /dev/hd3 device, giving it the volume serial number vol 001 and file system name works. The new file system occupies the entire device. The file system has a default fragment size (4096 bytes) and a default nbpi ratio (4096).

2. To create a file system with nondefault attributes, type:

```
mkfs -s 8192 -o nbpi=2048, frag=512 /dev/lv01
```

This command creates an empty 4 MB file system on the /dev/1v01 device with 512-byte fragments and 1 i-node for each 2048 bytes.

3. To create a large file enabled file system, type:

```
mkfs -V jfs -o nbpi=131072,bf=true,ag=64 /dev/lv01
```

This creates a large file enabled JFS file system with an allocation group size of 64 megabytes and 1 inode for every 131072 bytes of disk. The size of the file system will be the size of the logical volume

4. To create a file system with nondefault attributes, type:

```
mkfs -s 4M -o nbpi=2048, frag=512 /dev/lv01
```

This command creates an empty 4 MB file system on the /dev/lv01 device with 512-byte fragments and one i-node for each 2048 bytes.

5. To create a JFS2 file system which can support NFS4 ACLs, type:

```
mkfs -V jfs2 -o ea=v2 / dev/1v01
```

This command creates an empty file system on the /dev/lv01 device with v2 format for extended attributes.

Files

/etc/vfs Contains descriptions of virtual file system types.

/etc/filesystems Lists the known file systems and defines their characteristics.

Related Information

The fsck command, mkproto command, proto command.

The **ioctl** subroutine.

The dir file, filesystems file, filsys.h file.

File systems in Operating system and device management.

Understanding JFS Size Limitations in Operating system and device management.

mkgroup Command

Purpose

Creates a new group.

Syntax

mkgroup [-R load module] [-a] [-A] [Attribute=Value ...] Group

Description

The **mkgroup** command creates a new group. The *Group* parameter must be a unique string (whose length is administrator-configurable by way of the chdev command) and cannot be the ALL or default keywords. By default, the **mkgroup** command creates a standard group. To create an administrative group, specify the -a flag. You must be the root user or a user with GroupAdmin authorization to create an administrative group.

To create a group with an alternate Identification and Authentication (I&A) mechanism, the -R flag can be used to specify the I&A load module used to create the group. Load modules are defined in the /usr/lib/security/methods.cfg file.

You can use the Users application in Web-based System Manager (wsm) to change user characteristics. You could also use the System Management Interface Tool (SMIT) smit mkgroups fast path to run this command.

The **mkgroup** command always checks the target group registry to make sure the ID for the new account is unique to the target registry. The **mkgroup** command can also be configured to check all group registries of the system using the dist uniqid system attribute. The dist uniqid system attribute is an attribute of the usw stanza of the /etc/security/login.cfg file, and can be managed using the chsec command.

The **dist uniqid** system attribute has the following values:

- never Does not check for ID collision against the non-target registries. This is the default setting.
- · always Checks for ID collision against all other registries. If collision is detected between the target registry and any other registry account creation or modification fails.
- · uniqbyname Checks for ID collision against all other registries. Collision between registries is allowed only if the account to be created has the same name as the existing account.

Note: ID collision detection in the target registry is always enforced regardless of the dist uniqid system attribute.

The uniqbyname system attribute setting works well against two registries. With more than two registries, and with ID collision already existing between two registries, the behavior of the mkgroup command is

unspecified when creating a new account in a third registry using the colliding ID values. The new account creation might succeed or fail depending the order in which the registries are checked.

The check for ID collision only enforces ID uniqueness between the local registry and remote registries or between remote registries. There is no guarantee of ID uniqueness between the newly created account on the remote registry and existing local users on other systems that make use of the same remote registry. The mkgroup command bypasses a remote registry if the remote registry is not reachable at the time the command is run.

Restrictions on Creating Group Names

To prevent login inconsistencies, you should avoid composing group names entirely of uppercase alphabetic characters. While the mkgroup command supports multibyte group names, it is recommended that you restrict group names to characters with the POSIX portable filename character set.

To ensure that your user database remains uncorrupted, you must be careful when naming groups. Group names must not begin with a - (dash), + (plus sign), @ (at sign), or ~ (tilde). You cannot use the keywords ALL or default in a group name. Additionally, do not use any of the following characters within a group-name string:

- Colon
- Double quote
- # Pound sign
- Comma
- Equal sign
- Back slash
- Slash
- Question mark
- Single quote
- Back quote

Finally, the *Name* parameter cannot contain any space, tab, or new-line characters.

Flags

Creates an administrative group. Only the root user can use this flag.

-Δ Sets the group administrator to the person who invoked the **mkgroup** command.

-R load_module Specifies the loadable I&A module used to create the user.

Attribute=Value Initializes a group with a specific attribute. See the **chgroup** command for more

information about the group attributes.

Exit Status

This command returns the following exit values:

The command runs successfully and all requested changes are made.

>0 An error occurred. The printed error message lists further details about the type of

failure.

Security

Access Control: This command should grant execute (x) access only to the root user and members of the security group. This command should be installed as a program in the trusted computing base (TCB). The command should be owned by the root user with the setuid (SUID) bit set.

Files Accessed:

Mode File

rw /etc/passwd
rw /etc/security/user
rw /etc/security/limits
rw /etc/security/environ

rw /etc/group

rw /etc/security/group

r /usr/lib/security/mkuser.default x /usr/lib/security/mkuser.sys

Auditing Events:

Event Information

USER_Create user

Limitations

Creating a group may not be supported by all loadable I&A modules. If the loadable I&A module does not support creating a group, an error is reported.

Examples

1. To create a new group account called finance, type:

mkgroup finance

2. To create a new administrative group account called payrol1, type:

mkgroup -a payroll

Only the root user can issue this command.

3. To create a new group account called managers and set yourself as the administrator, type:

mkgroup -A managers

4. To create a new group account called managers and set the list of administrators to steve and mike, type:

mkgroup adms=steve,mike managers

The users steve and mike must already exist on the system.

5. To create a new group that is a LDAP I&A loadable module user, type:

mkgroup -R LDAP monsters

Files

/usr/bin/mkgroupContains the mkgroup command./etc/groupContains the basic attributes of groups./etc/security/groupContains the extended attributes of groups.

/etc/passwdContains basic user information./etc/security/passwdContains password information.

Related Information

The **chgroup** command, **chgrpmem** command, **chuser** command, **Isgroup** command, **Isgroup** command, **mkuser** command, **pwdadm** command, **rmgroup** command, **rmuser** command, **setsenv** command.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

For more information about the identification and authentication of users, discretionary access control, the trusted computing base, and auditing, refer to the Security.

mkhosts Command

Purpose

Generates the host table file.

Syntax

/usr/sbin/mkhosts [-v] HostFile

Description

The **mkhosts** command can be used to generate a hashed host database, using the filename specified by the HostFile parameter. It is not used if name resolution is performed by the named daemon. The host file is usually the /etc/hosts file, and in any case must be in the same format as the /etc/hosts file.

The mkhosts command generates database files named hostfile.pag and hostfile.dir. Updates to these files are built in a set of temporary files named hostfile.new.pag and hostfile.new.dir. The temporary files are copied into the database files only if the hostfile.new.pag and hostfile.new.dir files are built without errors.

The host file is used by one version of the **gethostbyaddr** and **gethostbyname** library routines for name resolution.

Note: The version of the gethostbyaddr and gethostbyname library routines on this operating system do not support the hostfile.pag and hostfile.dir files.

After creating the host file, you can edit it to include the desired host entries.

Flags

Lists each host as it is added to the host file specified by the *HostFile* parameter.

Examples

Use the following command to generate the /etc/hosts.pag and /etc/hosts.dir files: mkhosts /etc/hosts

This command creates two host files called /etc/hosts.pag and /etc/hosts.dir.

Files

hostfile.pag One of two files containing the real database for name resolution. hostfile.dir One of two files containing the real database for name resolution. hostfile.new.pag One of two files containing the temporary database for name resolution. hostfile.new.dir One of two files containing the temporary database for name resolution.

Related Information

The gettable command, htable command.

The named daemon.

The **gethostbyname** subroutine, **gethostbyaddr** subroutine.

The hosts file format.

TCP/IP name resolution in Networks and communication management.

mkiscsi Command

Purpose

Adds iSCSI target data.

Syntax

mkiscsi -l AdapterName -g static -t TargetName -n PortNumber -i IPaddress [-p password]

mkiscsi -l AdapterName -g auto -t TargetName -p password

mkiscsi -l AdapterName -g group -f FileName

Description

The **mkiscsi** command adds iSCSI target data to ODM. There are two categories of data stored in ODM. The first is for statically configured iSCSI targets, which require that all the relevant iSCSI target information (such as target name, IP address, and port number) are specified in order for AIX to discover them. The second category of iSCSI target data is for iSCSI target devices that can be configured automatically, but require authentication from the host (such as passwords). These two categories of iSCSI target data are associated with the **static** and **auto** groups, respectively, specified by the **-q** flag.

Flags

-f FileName

-g group

-i IPaddress

-I AdapterName

-n NewPortNumber

-p password

-t TargetName

Specifies the filename from which iSCSI target information will be read and then placed into ODM.

Specifies which group this iSCSI target is associated with. There two valid groups are static and auto. The static group is for iSCSI targets that cannot be automatically discovered from this host; all relevant iSCSI target information for them (such as target name, IP address, and port number) must be specified. The auto group is for iSCSI targets that are automatically discovered, but require authentication information such as passwords.

Specifies the IP address of the iSCSI target.

Specifies the adapter name for the iSCSI TCP/IP Offload Engine (TOE) adapter that is attached to this iSCSI target. It can also specify the iSCSI protocol device for the iSCSI software solution device.

Specifies the port number on which the iSCSI target is accessed. The default port number is 3260. Specifies the new password for this iSCSI target. Specifies the iSCSI target name (for example. iqn.sn9216.iscsi-hw1).

Exit Status

>0

The command completed successfully. An error occurred.

Security

The **mkiscsi** command is executable only by root.

Examples

1. To add one statically configured iSCSI target, enter the following command:

```
mkiscsi -1 ics0 -g static -t iqn.sn1234.iscsi hw1
```

2. To add all the entries from the file /etc/iscsi/targetshw, enter the following command:

```
mkiscsi -1 ics0 -g static -f /etc/iscsi/targetshw
```

Location

/usr/sbin/mkiscsi

Files

src/bos/usr/sbin/iscsia

Contains the common source files from which the iSCSI commands are built.

Related Information

The chiscsi Command, "Isiscsi Command" on page 365, rmiscsi Command.

mkitab Command

Purpose

Makes records in the /etc/inittab file.

Syntax

mkitab [-i Identifier] { [Identifier] : [RunLevel] : [Action] : [Command] }

Description

The mkitab command adds a record to the /etc/inittab file. The Identifier:RunLevel:Action:Command parameter string specifies the new entry to the /etc/inittab file. You can insert a record after a specific record using the -i Identifier flag. The command finds the field specified by the Identifier parameter and inserts the new record after the one identified by the -i Identifier flag.

Parameters

The Identifier: RunLevel: Action: Command parameter string specifies the record in the /etc/inittab file, as follows:

Identifier

A 14-character parameter that uniquely identifies an object. The Identifier must be unique. If the Identifier is not unique, the command is unsuccessful. The Identifier cannot be changed; if you try to change it, the command is unsuccessful.

RunLevel

A 20-character parameter defining the run levels in which the *Identifier* can be processed. Each process started by the **init** command can be assigned one or more run levels in which it can be started.

Action

A 20-character parameter that informs the **init** command how to process the *Command* parameter that you specify. The **init** command recognizes the following actions:

respawn

If the process identified in this record does not exist, start the process. If the process currently exists, do nothing and continue scanning the /etc/inittab file.

wait When the **init** command enters the run level specified for this record, start the process and wait for it to stop. While the **init** command is in the same run level, all subsequent reads of the **/etc/inittab** file ignore this object.

once When the **init** command enters the run level specified for this record, start the process, do not wait for it to stop and when it does stop do not restart the process. If the system enters a new run level while the process is running, the process is not restarted.

Boot Read this record only when the system boots and reads the /etc/inittab file. The init command starts the process. Do not wait for the process to stop and when it does stop, do not restart the process. The run level for this process should be the default, or it must match the run level specified by the init command at startup time.

bootwait

Read this record only when the system boots and reads the **/etc/inittab** file. The **init** command starts the process. Wait for it to stop, and when it does stop, do not restart the process.

powerfail

Start the process identified in this record only when the **init** command receives a **SIGPWR** power fail signal.

powerwait

Start the process identified in this record only when the **init** command receives a **SIGPWR** power fail signal, and wait until it stops before continuing to process the **/etc/inittab** file.

off If the process identified in this record is currently running, send the warning signal SIGTERM and wait 20 seconds before sending the SIGKILL kill signal. If the process is nonexistent, ignore this line.

hold When the process identified in this record is terminated, do not start a new one. The **hold** action can only be activated by the **phold** command.

ondemand

Functionally identical to **respawn**. If the process identified in this record does not exist, start the process. If the process currently exists, do nothing and continue scanning the **/etc/inittab** file. Specify this action to perform the **respawn** action when using **a**, **b**, or **c** run levels.

initdefault

A line with this action is processed only when the **init** command is originally invoked. The **init** command uses this line to determine which run level to originally enter. The command does this by taking the highest run level specified in the *RunLevel* parameter and using that as the command's initial state. If the *RunLevel* parameter is empty, its value is interpreted as 0123456789, and the **init** command enters a run level of **9**. If the **init** command does not find an **initdefault** line in the **inittab** file, it requests an initial run level from the operator at initial program load (IPL) time.

sysinit Start the process identified in this record before the **init** command tries to access the console. For example, you might use this to initialize devices.

Command

A 1024-character field specifying the shell command.

Attention: To avoid possible corruption of system files, the stdin, stdout, and stderr files must be specified in the Command parameter with redirection, or they must be explicitly opened by the program being run by the command line.

Flags

-i Identifier

Specifies which record in the /etc/inittab file the new record follows.

Examples

- 1. To add a new record to the /etc/inittab file, telling the init command to handle a login on tty2, type: mkitab "tty002:2:respawn:/usr/sbin/getty/dev/tty2"
- 2. To add a new record to the /etc/inittab file, telling the init command to execute the /etc/rc.tcpip file after the /usr/sbin/srcmstr file is started, type:

```
mkitab -i srcmstr "rctcpip:2:wait:/etc/rc.tcpip > /dev/console"
```

3. To add a new record to the /etc/inittab file, telling the init command to execute the /etc/rc file and send its output to the boot log, type:

```
mkitab ((rc:2:wait:/etc/rc 2>&1 | alog -tboot > /dev/console))
```

Files

/etc/inittab

Contains the mkitab command.

Related Information

The **chitab** command, **Isitab** command, **rmitab** command, **init** command.

mkinstallp Command

Purpose

Creates software packages in **installp** format.

Syntax

mkinstallp [-d BaseDirectory] [-T TemplateFile]

Description

The **mkinstallp** command allows users to create their own software packages for AIX. Packages created with the **mkinstallp** command are in **installp** format and can be installed or removed with the **installp** command.

Files to be packaged by the **mkinstallp** command must be in a directory structure such that the location of the file relative to the root build directory is the same as the destination of the file after installation. For example, if /usr/bin/somecommand is to be installed through a mkinstallp package, the somecommand parameter must be in the buildroot/usr/bin directory when the mkinstallp command is run.

After the contents of a package are located in the correct directory structure, the mkinstallp command prompts for basic package data. This data includes the package name, requisites, descriptions of files to be packaged, and more. The mkinstallp command will then generate a template file based on responses given by the user. To prevent command-line prompting, template files can be created and edited directly by the user and passed to the **mkinstallp** command with the -T flag.

Flags

-d Specifies the root build directory containing the files to be packaged. If not specified, the current BaseDirectory working directory is used.

-T Specifies the full path name of the template file to be passed to the mkinstallp command. If not TemplateFile specified, the mkinstallp command prompts for package information and creates a new template file

based on user responses.

Note: Do not use the .info directory located in the BaseDirectory to store a template file. The template file may be removed when you run the mkinstallp command.

Examples

This example demonstrates how to package the file /usr/bin/foo using the /tmp/packages directory as the root build directory.

First, create the directory structure by typing the following at the command line:

mkdir -p /tmp/packages/usr/bin

Then, type the following to create the file /usr/bin/foo:

touch /tmp/packages/usr/bin/foo

Then, type the following to create the package using the **mkinstallp** command:

mkinstallp -d /tmp/packages

For more examples, see the /usr/lpp/bos/README.MKINSTALLP file.

Files

/usr/sbin/mkinstallp

Contains the **mkinstallp** command.

Related Information

The **installp** command.

mkkeyserv Command

Purpose

Uncomments the entry in the /etc/rc.nfs file for the keyserv daemon and invokes the daemon by using the startsrc command.

Syntax

/usr/sbin/mkkeyserv [-I | -B | -N]

Description

The mkkeyserv command uncomments the entry in the /etc/rc.nfs file for the keyserv daemon. The mkkeyserv command starts the daemon by using the startsrc command.

You can use the File Systems application in Web-based System Manager (wsm) to change file system characteristics. You could also use the System Management Interface Tool (SMIT) smit mkkeyserv fast path to run this command.

Flags

- Uncomments the entry in the /etc/rc.nfs file to start the keyserv daemon on the next system restart.
- Uncomments the entry in the /etc/rc.nfs file to start the keyserv daemon and uses the startsrc command to start the keyserv daemon. This flag is the default.
- Uses the startsrc command to start the keyserv daemon. This flag does not change the /etc/rc.nfs file. -N

Examples

To modify the /etc/rc.nfs file to invoke the keyserv daemon on the next system restart, enter: mkkeyserv -I

Files

/etc/rc.nfs

Contains the startup script for the NFS and NIS daemons.

Related Information

The **smit** command. **startsrc** command.

The keyserv daemon.

System management interface tool in Operating system and device management.

Network File System (NFS) Overview for System Management in Networks and communication management.

How to Start and Stop the NIS Daemons in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide and How to Export a File System Using Secure NFS in Security.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

Network Information Services (NIS) Overview for System Management in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide.

mkkrb5cInt Command

Purpose

Configures a Kerberos client.

Syntax

mkkrb5cInt -h | [-c KDC -r Realm -s Server -U [-a Admin] -d Domain [-A] [-i Database] [-K] [-T]] [-I {Idapserver | Idapserver:port}]

Description

This command configures the Kerberos client. The first part of the command reads realm name, KDC, VDB path, and domain name from the input and generates a **krb5.conf** file.

/etc/krb5/krb5.conf: Values for realm name, Kerberos admin server, and domain name are set as

specified on the command line. Also updates the paths for default_keytab_name,

kdc, and kadmin log files.

If DCE is not configured, this command creates a link to /etc/krb5/krb5.conf from /etc/krb5.conf.

The command also allows you to configure root as admin user, configure integrated Kerberos authentication, and configure Kerberos as default authentication scheme.

For integrated login, the -i flag requires the name of the database being used. For LDAP, use the load module name that specifies LDAP. For local files, use the keyword files.

Standard Output Consists of information messages when the -h flag is used.

Standard Error Consists of error messages when the command cannot complete successfully.

Flags

-a Admin Specifies the principal name of the Kerberos server admin. -A Specifies root to be added as a Kerberos administrative user.

-c KDC Specifies the KDC server.

-d Domain Specifies the complete domain name for the Kerberos client.

-h Specifies that the command is only to display the valid command syntax.

-i Database Configures integrated Kerberos authentication.

-K Specifies Kerberos to be configured as the default authentication scheme.

-I Idapserver I For servers, specifies the LDAP directory used to store the Network Authentication Service

Idapserver:port principal and policy information.

> For clients, specifies the LDAP directory server to use for Administration server and KDC discovery using LDAP. If the -I flag is used, then the KDC and server flags are optional. If the -I option is not used, the KDC and server flags must be specified. The port number can

optionally be specified.

For clients and servers, the port number can optionally be specified. If the port number is not specified, the client connects to the default LDAP server port 389 or 636 for SSL connections.

Note: Only the client configuration is updated.

-r Realm Specifies the full realm name for which the Kerberos client is to be configured.

-s Server Specifies the fully qualified host name for Kerberos admin server. -T Specifies the flag to acquire server admin TGT based admin ticket.

-U Undo the setup from the previous configuration command.

Exit Status

Failure of this command to execute successfully may result in incomplete client configuration.

Indicates the successful completion of the command.

1 Indicates that an error occurred.

Security

Only the root user is authorized to use this command.

Examples

1. To display the command syntax, type:

mkkrb5clnt -h

2. To configure **testbox.austin.ibm.com** as a client to **sundial.austin.ibm.com** where KDC is also running on **sundial.austin.ibm.com**, type:

3. To configure **testbox.austin.ibm.com** as the client, make root as the server admin, configure integrated login, configure Kerberos as default authentication scheme, type:

```
mkkrb5clnt -c sundial.austin.ibm.com -r UD3A.AUSTIN.IBM.COM \
    -s sundial.austin.ibm.com -d austin.ibm.com \
    -A -i files -K -T
```

Files

/usr/krb5/sbin

Contains the mkkrb5cInt command.

mkkrb5srv Command

Purpose

Configures a Kerberos server.

Syntax

mkkrb5srv -h | [-r Realm -d Domain -a AdminName] [-l Idapserver | Idapserver:port] [-u Idap_DN] [-p Idap_DN_pw] [-f {keyring | keyring:entry_dn}] [-k keyring_pw] [-b bind_type] [-m masterkey_location] [-U]

Description

The **mkkrb5srv** command configures the Kerberos server. This command creates the **kadm5.acl** file, the **kdc.conf** file, and the Kerberos database. It also adds the administrator to the database and updates the **/etc/inittab** file with Kerberos daemons. This command does the initial configuration once the variables are set. They can be modified by editing the following files:

/etc/krb5/krb5.conf: Values for realm name, Kerberos admin server, and domain name are set as

specified on the command line. Also updates the paths for

default_keytab_name, kdc, and kadmin log files.

/var/krb5/krb5kdc/kdc.conf This command sets the value for kdc_ports. Paths for database name,

admin_keytab, acl_file, dict_file, key_stash_file. Values for kadmin_port,

max_life, max_renewable_life, master_key_type, and

supported_enctypes.

/var/krb5/krb5kdc/kadm5.acl Sets up the acls for admin, root, and host principals.

If DCE is not configured, this command creates a link to /etc/krb5/krb5.conf from /etc/krb5.conf.

Standard Output Consists of information messages when the **-h** flag is used.

Standard Error Consists of error messages when the command cannot complete successfully.

Flags

-a AdminName

Specifies the Kerberos Principal name for the administrator.

-b bind_type Specifies the LDAP bind type. Supported values are the following:

simple

cram-md5

external

These bind types can be specified in either upper case or lower case.

Specifies the domain name for the Kerberos realm.

Specifies the LDAP keyring database file name if you are using SSL

communication.

Specifies that the command is only to display the valid command syntax. Specifies the password for the LDAP keyring database file. If not specified, SSL uses the password that is encrypted in the appropriate password stash

For servers, specifies the LDAP directory used to store the Network -I Idapserver | Idapserver:port

Authentication Service principal and policy information.

For clients, specifies the LDAP directory server to use for Administration server and KDC discovery using LDAP. If the -I flag is used, then the KDC and server flags are optional. If the -I option is not used, the KDC and server flags must be specified. The port number can optionally be specified.

For clients and servers, the port number can optionally be specified. If the port number is not specified, the client connects to the default LDAP server port 389 or 636 for SSL connections.

Note: Only the client configuration is updated.

Specifies the fully qualified file name for storing the master key in the local file

system when using LDAP to store data.

Note: This flag is only for use with the LDAP directory.

-p Idap_DN_pw Specifies the password for the entry being used for the *Idap_DN_pw*. -r Realm Specifies the realm for which the Kerberos server is to be configured.

Specifies the LDAP entry to be used as the Idap DN.

Note: With external bind, the -u and -p flags are not required, and the values

come form the certificate.

-U Undo the setup from the previous configuration command.

Exit Status

-u Idap_DN

-m masterkey_location

-d Domain

-kkeyring_pw

-h

-f {keyring | keyring:entry_dn}

Failure of this command to execute successfully results in incomplete server configuration.

Indicates the successful completion of the command.

Indicates that an error occurred.

Security

Only the root user is authorized to use this command.

Examples

1. To display the command syntax, type:

mkkrb5srv -h

2. To configure sundial as a Kerberos server, type:

mkkrb5srv -r UD3A.AUSTIN.IBM.COM -d austin.ibm.com

Files

/usr/sbin/mkkrb5srv

Contains the mkkrb5srv command.

mklost+found Command

Purpose

Creates a lost and found directory for the fsck command.

Syntax

mklost+found

Description

The mklost+found command creates a lost and found directory in the current directory. A number of empty files are created within the lost and found directory and then removed so that there are empty slots for the **fsck** command. The **fsck** command reconnects any orphaned files and directories by placing them in the lost and found directory with an assigned i-node number. The mklost+found command is not normally needed, since the fsck command automatically creates the lost and found directory when a new file system is created.

Examples

To make a lost+found directory for the **fsck** command, enter: mklost+found

Files

/usr/sbin/mklost+found

Contains the mklost+found command.

Related Information

The **fsck** command. **mkfs** command.

The Directories in Operating system and device management.

The Files in Operating system and device management.

mklpcmd Command

Purpose

Defines a new least-privilege (LP) resource to the resource monitoring and control (RMC) subsystem and specifies user permissions.

Syntax

mklpcmd [-n hosf] [-I] [-c 0 | 1 | 2 | 3] [-R RunCmdName] [-s FilterScript] [-A FilterArg] [-h] [-TV] resource name command path [ID perm] ...

Description

The **mklpcmd** command defines a new LP resource to the resource monitoring and control (RMC) subsystem subsystem. An LP resource is a root command or script to which users are granted access based on permissions in the LP access control lists (ACLs). Specify the LP resource using the resource_name parameter. The command_path parameter specifies the command or script that could be run with LP access. Specify the complete path name of the command or the script. If command path exists when a resource is created, the LP resource manager calculates the CheckSum and assigns the CheckSum attribute value. If command_path does not exist, the LP resource manager assigns 0 as the CheckSum attribute value.

Use the -I flag to lock the LP resource. The resource must be unlocked before it can be deleted. Use the -c flag to specify the control settings of the resource.

You can also use the **mklpcmd** command to specify permissions for users when you are creating a resource. To do this, you need to have administrator permission on the resources. Administrator permission gives you the ability to set and edit permissions. You can specify multiple user IDs and permissions with this command. See the **Examples** section for more information.

This command runs on any node. In a management domain or a peer domain, use the -n flag to define the LP resource on the node that is specified by host. Otherwise, this command runs on the local node.

Flags

-n host

Specifies the node in the domain on which the LP resource is to be defined. By default, the LP resource is defined on the local node. The -n flag is valid only in a management or peer domain. If the CT_MANAGEMENT_SCOPE variable is not set, the LP resource manager uses scope settings in this order:

- 1. The management domain, if it exists
- 2. The peer domain, if it exists
- 3. Local scope

The **mklpcmd** command runs once for the first valid scope that the LP resource manager finds.

-1 Defines the new LP resource as locked so that it cannot be changed accidentally. The resource cannot be removed from the RMC subsystem until the Lock attribute is unset.

If you do not specify this flag, the new resource is not locked. This is the default.

-c 0 | 1 | 2 | 3

Sets the ControlFlags attribute, which is used to specify the control features for an LP command. If ControlFlags is not specified, it is set to 1 by default. Use this flag to specify one of these values:

- Does not validate the CheckSum value.
- 1 Does not validate the **CheckSum** value. This is the default.
- 2 Validates the CheckSum value.
- 3 Validates the CheckSum value.

When an attempt is made to run the LP resource using the runlpcmd command, the value of the ControlFlags attribute determines which checks are performed before running the command represented by the resource.

In this release of RSCT, the ControlFlags attribute value specifies whether the CheckSum value is to be validated.

In previous releases of RSCT, the ControlFlags attribute value also specified whether the presence of certain characters in the input arguments to runlpcmd were to be disallowed. Checking for these characters is no longer necessary.

To maintain compatibility with LP resources that were defined in previous releases of RSCT, the ControlFlags attribute values, with respect to validating the CheckSum value, have remained the same. Consequently, values 0 and 1 indicate that the CheckSum value is not to be validated, and values 2 and 3 indicate that the CheckSum value is to be validated.

-R RunCmdName

Specifies the RunCmdName value for this resource, which will be used as a parameter of the runlpcmd command.

-s script_path

Specifies the fully-qualified path of the filter script.

-A argument

Specifies a string of arguments to be passed to the filter script.

- **-h** Writes the command's usage statement to standard output.
- -T Writes the command's trace messages to standard error.
- **-V** Writes the command's verbose messages to standard output.

Parameters

resource name

Is the name or identifier of the LP resource that is to be defined to the RMC subsystem.

command_path

Is the complete, fully-qualified path name of the command or script.

ID perm ...

Specifies permissions for users when you are creating a resource. This parameter is optional.

ID Specifies the user identity for the ACL entry. See the **User identities** section of the **Ipacl** information for the valid forms of this parameter.

perm Specifies the user permissions for the ACL entry. This parameter can consist of a combination of any of the following values:

- r Read permission (consists of the q, I, e, and v permissions)
- w Write permission (consists of the d, c, s, and o permissions)
- a Administrator permission
- x Execute permission
- **q** Query permission
- I Enumerate permission
- e Event permission
- v Validate permission
- **d** Define and undefine permission
- **c** Refresh permission
- s Set permission
- o Online, offline, and reset permission
- **0** No permission

See the **User permissions** section of the **IpacI** information for descriptions of these permissions.

Security

- To run the **mklpcmd** command with one or more *ID*:perm parameters, you need:
 - read and write permission in the Class ACL of the IBM.LPCommands resource class.
 - read and administrator permission in the Resource Initial ACL.

As an alternative, the Resource Initial ACL can direct the use of the Resource Shared ACL if these permissions exist in the Resource Shared ACL.

• To run the **mklpcmd** command with no *ID*:perm parameters, you need write permission in the Class ACL of the IBM.LPCommands resource class.

Permissions are specified in the LP ACLs on the contacted system. See the IpacI file for general information about LP ACLs and the RSCT Administration Guide for information about modifying them.

Exit Status

- 0 The command has run successfully.
- An error occurred with RMC. 1
- 2 An error occurred with the command-line interface (CLI) script.
- 3 An incorrect flag was specified on the command line.
- 4 An incorrect parameter was specified on the command line.
- 5 An error occurred with RMC that was based on incorrect command-line input.
- The resource was not found.

Environment Variables

CT CONTACT

Determines the system that is used for the session with the RMC daemon. When CT_CONTACT is set to a host name or IP address, the command contacts the RMC daemon on the specified host. If CT_CONTACT is not set, the command contacts the RMC daemon on the local system where the command is being run. The target of the RMC daemon session and the management scope determine the LP resources that are processed.

CT_MANAGEMENT_SCOPE

Determines the management scope that is used for the session with the RMC daemon to process the LP resource. The management scope determines the set of possible target nodes where the resource can be processed. The valid values are:

- Specifies local scope.
- 1 Specifies local scope.
- 2 Specifies peer domain scope.
- 3 Specifies management domain scope.

If this environment variable is not set, local scope is used.

Implementation Specifics

This command is part of the Reliable Scalable Cluster Technology (RSCT) fileset for AIX.

Standard Output

When the -h flag is specified, this command's usage statement is written to standard output. When the -V flag is specified, this command's verbose messages are written to standard output.

Standard Error

All trace messages are written to standard error.

Examples

1. To create an LP resource called LP1 that points to a command called /tmp/user1/lpcmd1 on the local node, enter:

```
mklpcmd LP1 /tmp/user1/lpcmd1
```

2. To create an LP resource called LP2 that points to a command called /tmp/my_command1 on nodeB in the management domain, enter:

```
mklpcmd -n nodeB LP2 /tmp/my command1
```

3. To create an LP resource called Ip3 with ControlFlags set to 3 (which means verify the CheckSum value), enter:

```
mklpcmd -c 3 LP3 /tmp/cmd lp3
```

4. To create an LP resource called Ip4 that points to /tmp/testscript, has a RunCmdName value of test, a FilterScript value of /tmp/filterscr, and filter arguments node1 and node2, enter:

```
mklpcmd -R test -f /tmp/filterscr -A "node1,node2" lp4 /tmp/testscript
```

5. To create an LP resource called Ip5 that points to /usr/bin/mkrsrc and gives users user1@LOCALHOST and user2@LOCALHOST read, write, and execute permission, enter:

```
mklpcmd lp5 /usr/bin/mkrsrc user1@LOCALHOST rwx user2@LOCALHOST rwx
```

Location

/usr/sbin/rsct/bin/mklpcmd Contains the **mklpcmd** command

Related Information

Books: RSCT Administration Guide, for information about modifying LP ACLs.

Commands: chlpcmd, lphistory, lslpcmd, mkrsrc, rmlpcmd, runlpcmd

Information Files: IpacI, for general information about LP ACLs

mkly Command

Purpose

Creates a logical volume.

Syntax

mklv [-a Position] [-b BadBlocks] [-c Copies] [-C Stripe_width] [-d Schedule] [-e Range] [-i] [-L Label | [-m MapFile | [-o y / n | [-r Relocate | [-s Strict | [-t Type | [-t O | [-u UpperBound | [-v Verify [-w MirrorWriteConsistency] [-x Maximum] [-y NewLogicalVolume | -Y Prefix] [-S StripSize] [-U Userid] [-G Groupid] [-P Modes] VolumeGroup Number [PhysicalVolume ...]

Description

The **mklv** command creates a new logical volume within the *VolumeGroup*. For example, all file systems must be on separate logical volumes. The mklv command allocates the number of logical partitions to the new logical volume. If you specify one or more physical volumes with the *PhysicalVolume* parameter, only those physical volumes are available for allocating physical partitions; otherwise, all the physical volumes within the volume group are available.

The default settings provide the most commonly used characteristics, but use flags to tailor the logical volume to the requirements of your system. After a logical volume is created, its characteristics can be changed with the chlv command.

The default allocation policy is to use a minimum number of physical volumes per logical volume copy, to place the physical partitions belonging to a copy as contiguously as possible, and then to place the physical partitions in the desired region specified by the -a flag. Also, by default, each copy of a logical partition is placed on a separate physical volume.

The -m flag specifies exact physical partitions to be used when creating the logical volume.

The -U, -G, and -P flags can be used to set the ownership, group, and permissions, respectively, of the logical volume device special files. Only root users can set these values. For scalable and big vg format volume groups that are exported, specify the -R flag with the importvg command to restore these values upon import.

You can specify logical volumes sizes in 512 Blocks/KB/MB/GB when using the mklv command. (See "Examples" on page 610.)

Physical partitions are numbered starting at the outermost edge with number one.

- 1. Changes made to the logical volume are not reflected in the file systems. To change file system characteristics use the chfs command.
- 2. Each logical volume has a control block. This logical volume control block is the first few hundred bytes within the logical volume. Care has to be taken when reading and writing directly to the logical volume to allow for the control block. Logical volume data begins on the second 512-byte block.
- 3. To use this command, you must either have root user authority or be a member of the system group.
- 4. When creating a striped logical volume using the -S flag, you must specify two or more physical volumes or use the -C or -u flag.
- 5. When creating a striped logical volume, the number of partitions must be an even multiple of the striping width. If not, the number of partitions will be rounded up to the next valid value.
- 6. To create a striped logical volume with more than one copy, all active nodes should be at least AIX 4.3.3 or later when the volume group is in the concurrent mode.
- 7. The **mklv** command is not allowed on a snapshot volume group.
- 8. Mirror Write Consistency (MWC) and Bad Block Relocation (BBR) are not supported in a concurrent setup with multiple active nodes accessing a disk at the same time. These two options must be disabled in this type of concurrent setup.

You can use the Volumes application in Web-based System Manager to change volume characteristics. You could also use the System Management Interface Tool (SMIT) smit mklv fast path to run this command.

File Systems on Striped Logical Volumes

If you want to create a filesystem on a striped logical volume, you should create the striped logical volume before you run the crfs command or mkfs command to create the filesystem. In order to maximize the use of disk space within the striping width, you should choose hard disks of the same size when creating the striped logical volume. The striping width is the number of hard disks that form the striped logical volume.

Flags

-a Position

- -b BadBlocks
- -c Copies
- -C Stripe_width
- -d Schedule

-e Range

- -G Groupid
- -L

Sets the intra-physical volume allocation policy (the position of the logical partitions on the physical volume). The Position variable can be one of the following:

- m Allocates logical partitions in the outer middle section of each physical volume. This is the default position.
- Allocates logical partitions in the center section of each C physical volume.
- Allocates logical partitions in the outer edge section of е each physical volume.
- ie Allocates logical partitions in the inner edge section of each physical volume.
- Allocates logical partitions in the inner middle section of im each physical volume.

Sets the bad-block relocation policy. The *Relocation* variable can be one of the following:

- ٧ Causes bad-block relocation to occur. This is the default.
- Prevents bad-block relocation from occurring. Sets the number of physical partitions allocated for each logical partition. The Copies variable can be set to a value from 1 to 3; the default is 1.

Sets the Stripe width of the logical volume. If the Stripe_width is not entered it is assumed to be the *upper_bound* or the total number of disks specified on the command line.

Sets the scheduling policy when more than one logical partition is written. The Schedule variable can be one of the following:

- Establishes a parallel scheduling policy. This is the default р for scheduling policy.
- Parallel write with sequential read policy. All mirrors are ps written in parallel but always read from the first mirror if the first mirror is available.
- pr Parallel write round robin read. This policy is similar to the parallel policy except an attempt is made to spread the reads to the logical volume more evenly across all mirrors.
- Establishes a sequential scheduling policy.

Sets the inter-physical volume allocation policy (the number of physical volumes to extend across, using the volumes that provide the best allocation). The Range value is limited by the UpperBound variable, (set with the -u flag) and can be one of the following:

- X Allocates across the maximum number of physical volumes.
- m Allocates logical partitions across the minimum number of physical volumes. This is the default range.

Specifies group ID for the logical volume special file.

Reads the PhysicalVolume parameter from standard input. Use the -i flag only when PhysicalVolume is entered through standard input.

Sets the logical volume label. The default label is None. The maximum size of the label file is 127 characters.

Note: If the logical volume is going to be used as a journaled file system (JFS), then the JFS will use this field to store the mount point of the file system on that logical volume for future reference. -m MapFile

-oy / n

-P Modes

-r Relocate

-s Strict

-S StripSize

Specifies the exact physical partitions to allocate. Partitions are used in the order given by the file designated by the *MapFile* parameter. All physical partitions belonging to a copy are allocated before allocating for the next copy. The *MapFile* format is:

PVname: PPnum1[-PPnum2]

where *PVname* is a physical volume name (for example, hdisk0). It is one record per physical partition or a range of consecutive physical partitions.

PVname Name of the physical volume as specified by the system.

PPnum Physical partition number.

Important: When you use map files, you must understand and adhere to all LV-allocation parameters such as strictness, upperbound, and stripe width. Using map files bypasses the checks done in the LVM-allocation routines. This is important for striped LVs, which are assumed to have a typical striped allocation pattern conforming to the stripe width.

Turns on/off serialization of overlapping IOs. If serialization is turned on then overlapping IOs are not allowed on a block range and only a single IO in a block range is processed at any one time. Most applications like file systems and databases do serialization so serialization should be turned off. The default for new logical volumes is off.

Specifies permissions (file modes) for the logical volume special file

Sets the reorganization relocation flag. For striped logical volumes, the *Relocate* parameter must be set to $\bf n$ (the default for striped logical volumes). The *Relocate* parameter can be one of the following:

- y Allows the logical volume to be relocated during reorganization. This is the default for relocation.
- Prevents the logical volume from being relocated during reorganization.

Determines the strict allocation policy. Copies of a logical partition can be allocated to share or not to share the same physical volume. The *Strict* parameter is represented by one of the following:

- y Sets a strict allocation policy, so copies for a logical partition cannot share the same physical volume. This is the default for allocation policy.
- n Does not set a strict allocation policy, so copies for a logical partition can share the same physical volume.
- Sets a super strict allocation policy, so that the partitions allocated for one mirror cannot share a physical volume with the partitions from another mirror.

Specifies the number of bytes per strip (the strip size multiplied by the number of disks in an array equals the stripe size). Valid values include 4K, 8K, 16K, 32K, 64K, 128K, 256K, 512K, 1M, 2M, 4M, 8M, 16M, 32M, 64M, and 128M.

Note: The **-d**, **-e**, and **-s** flags are not valid when creating a striped logical volume using the **-S** flag.

-t Type

-T O

- -U Userid
- -u UpperBound

-v Verify

-w MirrorWriteConsistency

-x Maximum

Sets the logical volume type. The standard types are <code>jfs</code> (journaled file systems), <code>jfslog</code> (journaled file system logs), <code>jfs2</code> (enhanced journaled file system), <code>jfs2log</code> (enhanced journaled file system logs), and <code>paging</code> (paging spaces), but a user can define other logical volume types with this flag. You cannot create a striped logical volume of type <code>boot</code>. The default is <code>jfs</code>. If a log is manually created for a filesystem, the user must run the <code>logform</code> command to clean out the new <code>jfslog</code> before the log can be used. For example, to format the logical volume <code>logdev</code>, type:

logform /dev/logdev

where /dev/logdev is the absolute path to the logical volume. For big vg format volume groups, the **-T O** option indicates that the logical volume control block will not occupy the first block of the logical volume. Therefore, the space is available for application data. Applications can identify this type of logical volume with the **IOC INFO** ioctl. The logical volume has a device subtype of **DS_LVZ**. A logical volume created without this option has a device subtype of **DS_LV**. This option is ignored for old and scalable vg format volume groups.

Specifies user ID for logical volume special file.

Sets the maximum number of physical volumes for new allocation. The value of the *Upperbound* variable should be between one and the total number of physical volumes. When using super strictness, the upper bound indicates the maximum number of physical volumes allowed for each mirror copy. When using striped logical volumes, the upper bound must be multiple of *Stripe_width*. If *upper_bound* is not specified it is assumed to be *stripe_width* for striped logical volumes.

Sets the write-verify state for the logical volume. Causes (y) all writes to the logical volume to either be verified with a follow-up read, or prevents (n) the verification of all writes to the logical volume. The *Verify* parameter is represented by one of the following:

- Prevents the verification of all write operations to the logical volume. This is the default for the -v flag.
- y Causes the verification of all write operations to the logical volume.
- y or a Turns on *active* mirror write consistency that ensures data consistency among mirrored copies of a logical volume during typical I/O processing.
- Turns on passive mirror write consistency that ensures data consistency among mirrored copies during volume group synchronization after a system interruption.
 Note: This functionality is only available on Big Volume Groups.
- n No mirror write consistency. See the -f flag of the syncvg command.

Sets the maximum number of logical partitions that can be allocated to the logical volume. The default value is 512. The number represented by the *Number* parameter must be equal to or less than the number represented by the *Maximum* variable.

-y NewLogicalVolume

Specifies the logical volume name rather than having the name generated automatically. Logical volume names must be unique system wide and can range from 1 to 15 characters. If the volume group is varied on in concurrent mode, the new logical volume name should be unique across all the concurrent nodes where the volume group is varied on. The name cannot begin with a prefix already defined in the PdDv class in the Device Configuration Database for other devices.

The logical volume name created is sent to standard output. The logical volume name can only contain the following characters:

- "A" through "Z"
- "a" through "z"
- "0" through "9"
- "_" (the underscore)
- "-" (the minus sign)
- "." (the period)

All other characters are considered not valid. Specifies the *Prefix* to use instead of the prefix in a system-generated name for the new logical volume. The prefix must be less than or equal to 13 characters. The name cannot begin with a prefix already defined in the PdDv class in the Device Configuration Database for other devices, nor be a name already used by another device.

-Y Prefix

Examples

1. To make a logical volume in volume group vg02 with one logical partition and a total of two copies of the data, type:

```
mklv -c 2 vg02 1
```

2. To make a logical volume in volume group vg03 with nine logical partitions and a total of three copies spread across a maximum of two physical volumes, and whose allocation policy is not strict, type:

```
mklv -c 3 -u 2 -s n vg03 9
```

3. To make a logical volume in vg04 with five logical partitions allocated across the center sections of the physical volumes when possible, with no bad-block relocation, and whose type is paging, type:

```
mklv -a c -t paging -b n vg04 5
```

4. To make a logical volume in vg03 with 15 logical partitions chosen from physical volumes hdisk5, hdisk6, and hdisk9, type:

```
mklv vg03 15 hdisk5 hdisk6 hdisk9
```

5. To make a striped logical volume in vg05 with a strip size of 64K across 3 physical volumes and 12 logical partitions, type:

```
mklv -u 3 -S 64K vg05 12
```

6. To make a striped logical volume in vg05 with a strip size of 8K across hdisk1, hdisk2, and hdisk3 and 12 logical partitions, type:

```
mklv -S 8K vg05 12 hdisk1 hdisk2 hdisk3
```

7. To request a logical volume with a minimum size of 10MB, type:

```
mklv VGNAME 10M #
```

The mklv command will determine the number of partitions needed to create a logical volume of at least that size.

You can use uppercase and lowercase letters as follows:

```
512 byte blocks
B/b
K/k
M/m
         MB
         GB
G/q
```

Files

/usr/sbin Directory where the **mklv** command resides.

Directory where the temporary files are stored while the command is running. /tmp

/dev Directory where the character and block device entries for the logical volume are created.

Related Information

The chfs command, chlv command, chpv command, extendiv command, mklvcopy command, **rmlvcopy** command, **syncvg** command.

The Logical volume storage in *Operating system and device management*.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

The System management interface tool in Operating system and device management.

mklvcopy Command

Purpose

Provides copies of data within the logical volume.

Syntax

```
mklvcopy [ -a Position ] [ -e Range ] [ -k ] [ -m MapFile ] [ -s Strict ] [ -u UpperBound ]
LogicalVolume Copies [ PhysicalVolume... ]
```

Description

The **mklycopy** command increases the number of copies in each logical partition in *LogicalVolume*. This is accomplished by increasing the total number of physical partitions for each logical partition to the number represented by Copies. The Logical Volume parameter can be a logical volume name or logical volume ID. You can request that the physical partitions for the new copies be allocated on specific physical volumes (within the volume group) with the *PhysicalVolume* parameter; otherwise, all the physical volumes within the volume group are available for allocation.

The logical volume modified with this command uses the *Copies* parameter as its new **copy** characteristic. The data in the new copies are not synchronized until one of the following occurs: the -k option is used. the volume group is activated by the varyonvg command, or the volume group or logical volume is synchronized explicitly by the syncvg command. Individual logical partitions are always updated as they are written to.

The default allocation policy is to use minimum numbering of physical volumes per logical volume copy, to place the physical partitions belong to a copy as contiguously as possible, and then to place the physical partitions in the desired region specified by the -a flag. Also, by default, each copy of a logical partition is placed on a separate physical volume.

Notes:

• To use this command, you must either have root user authority or be a member of the **system** group.

- To create a copy of a striped logical volume, all active nodes using the volume group must be at least AIX 4.3.3 or later. Older versions will not be able to use the volume group after a mirror copy has been added to the striped logical volume.
- The mklvcopy command is not allowed on a snapshot volume group.
- When you create a copy of a logical volume with a superstrict allocation policy, the **mklvcopy** command first attempts to mimic the physical-partition mapping of the first mirror copy onto another set of disks in the volume group. This algorithm ignores the interphysical and intraphysical volume allocation policies, even when the policies are specified as arguments to the mklvcopy command. If it is not possible to mimic the first copy's physical partition mapping, the usual allocation algorithm, which utilizes the interphysical and intraphysical volume allocation policies, is used.

You can use the Volumes application in Web-based System Manager (wsm) to change volume characteristics. You could also use the System Management Interface Tool (SMIT) smit mklvcopy fast path to run this command.

Flags

Note: The **-e** and **-s** flags are not valid with a striped logical volume.

-a Position

Sets the intra-physical volume allocation policy (the position of the logical partitions on the physical volume). The *Position* variable can be one of the following:

- Allocates logical partitions in the outer middle section of each physical volume. This is the default position.
- Allocates logical partitions in the center section of each physical volume. C
- Allocates logical partitions in the outer edge section of each physical volume. е
- ie Allocated logical partitions in the inner edge section of each physical volume.

Allocates logical partitions in the inner middle section of each physical volume. im Sets the inter-physical volume allocation policy (the number of physical volumes to extend across, using the volumes that provide the best allocation). The Range value is limited by the *Upperbound* variable (set with the **-u** flag), and can be one of the following:

- Allocates across the maximum number of physical volumes. X
- Allocates logical partitions across the minimum number of physical volumes. This is the default for the -e flag.

Synchronizes data in the new partitions.

Specifies the exact physical partitions to allocate. Partitions are used in the order given by the file designated by the MapFile parameter. All physical partitions belonging to a copy are allocated before allocating for the next copy. The MapFile format is:

PVname: PPnum1[-PPnum2]

where PVname is a physical volume name (for example, hdisk0). It is one record per physical partition or a range of consecutive physical partitions.

Name of the physical volume as specified by the system. **PVname**

Physical partition number. **PPnum**

Important: When you use map files, you must understand and adhere to all LV-allocation parameters such as strictness, upperbound, and stripe width. Using map files bypasses the checks done in the LVM-allocation routines. This is important for striped LVs, which are assumed to have a typical striped allocation pattern conforming to the stripe width.

-e Range

-m MapFile

-s Strict

Determines the strict allocation policy. Copies of a logical partition can be allocated to share or not to share the same physical volume. The Strict variable is represented by one of the following:

- Sets a strict allocation policy, so copies for a logical partition cannot share the У same physical volume. flag.
- Does not set a strict allocation policy, so copies for a logical partition can share the n same physical volume.
- Sets a super strict allocation policy, so that the partitions allocated for one mirror cannot share a physical volume with the partitions from another mirror. See Note 4 for other effects of the superstrict allocation policy on mklvcopy behavior.

Note: When changing a nonsuper strict logical volume to a super strict logical volume, you must specify physical volumes or use the -u flag.

-u UpperBound

Sets the maximum number of physical volumes for new allocation. The value of the Upperbound variable should be between one and the total number of physical volumes. When using super strictness, the upper bound indicates the maximum number of physical volumes allowed for each mirror copy. When using striped logical volumes, the upper bound must be multiple of *Stripe_width*.

Example

To add physical partitions to the logical partitions in the logical volume 1v01, so that a total of three copies exists for each logical partition, enter:

mklvcopy lv01 3

The logical partitions in the logical volume represented by directory 1v01 have three copies.

Files

/usr/sbin/mklvcopy

Contains the **mklvcopy** command.

Related Information

The chiv command, isiv command, mkiv command, syncvg command, varyonvg command.

The Logical volume storage in Operating system and device management.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

The System management interface tool in *Operating system and device management*.

mkmaster Command

Purpose

Executes the **ypinit** command and starts the NIS daemons to configure a master server.

Syntax

/usr/sbin/mkmaster [-s HostName [,HostName ...]] [-O | -o] [-E | -e] [-P | -p] [-U | -u] [-C | -c] [-I | -B | -N]

Description

The **mkmaster** command invokes the **ypinit** command to build the NIS maps for the current domain, if the domain name of the system is currently set. After the ypinit command completes successfully, the mkmaster command uncomments the entries in the /etc/rc.nfs file for the vpserv command, vppasswdd command, ypupdated command, and ypbind command.

You can use the File Systems application in Web-based System Manager (wsm) to change file system characteristics. You could also use the System Management Interface Tool (SMIT) smit mkmaster fast path to run this command.

Flags

-s HostName [,HostName]	Specifies the slave host names for this master server. These slave hosts must be configured after the master server has been configured. The mkmaster command automatically adds the current host to this list.
-O	Overwrites existing maps for this domain.
-0	Prevents the overwriting of existing maps for this domain. This flag is the default.
-E	Prevents further action if errors are encountered while building new maps. This is true for both the ypinit command and the mkmaster command. This flag is the default.
-e	Does not exit from the ypinit command and the mkmaster command if errors are encountered.
-P	Starts the yppasswdd daemon along with the ypserv daemon.
-р	Suppresses the start of the yppasswdd daemon. This flag is the default.
-U	Starts the ypupdated daemon along with the ypserv daemon.
-u	Suppresses the start of the ypupdated daemon. This flag is the default.
-C	Starts the ypbind daemon along with the ypserv daemon. This flag is the default.
-c	Suppresses the start of the ypbind daemon.
-1	Directs the mkmaster command to change the /etc/rc.nfs file to start the appropriate daemons on the next system restart. The execution of the ypinit command occurs when this command is invoked.
-В	Executes the ypinit command, uncomments the entries in the /etc/rc.nfs file, and starts the daemons. This flag is the system default.
-N	Executes the ypinit command and starts the appropriate daemons without changing the /etc/rc.nfs file.

Example

To execute the **ypinit** command, overwrite any existing maps for the current domain, and make host1 and host3 slave servers, enter:

```
mkmaster -s host1, host3 -0 -p -u -B
```

This command will not start the **yppasswdd** daemon or the **ypupdated** daemon.

Files

/var/yp/domainname directory	Contains the NIS maps for the NIS domain.
/etc/rc.nfs	Contains the startup script for the NFS and NIS daemons.

Related Information

The **chmaster** command, **rmyp** command, **smit** command, **ypinit** command.

The **ypbind** daemon, **yppasswdd** daemon, **ypserv** daemon, **ypupdated** daemon.

System management interface tool in Operating system and device management.

Network File System (NFS) Overview for System Management in Networks and communication management.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

Network Information Services (NIS) Overview for System Management in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide.

NIS Reference.

mknamsv Command

Purpose

Configures TCP/IP-based name service on a host for a client.

Syntax

mknamsv { -a "Attribute=Value ..." | -A FileName }

Description

The mknamsv high-level command configures a TCP/IP instance to use a name server. It calls the namersly low-level command to configure the resolv.conf file appropriately.

You can use the Devices application in Web-based System Manager (wsm) to change device characteristics. You could also use the System Management Interface Tool (SMIT) smit mknamersIv fast path to run this command.

Flags

-A FileName -a "Attribute=Value..."

Specifies the name of the file containing named daemon initialization information. Specifies a list of attributes with corresponding values to be used for updating the named server initialization files in the database. Attributes available are:

domain Domain name

nameserver

Internet address of name server in dotted decimal format

Examples

1. To configure the name server initialization files, enter the command in the following format:

```
mknamsv -a"domain=austin.century.com nameserver=192.9.200.1"
```

In this example the domain name and name server address are updated. The previous domain and name server are overwritten.

2. To configure name server initialization files according to information in another file, enter the command in the following format:

```
mknamsv -A namsv.file
```

In this example, the file that contains the configuration information is namsv.file.

Files

/etc/resolv.conf

Contains domain name server information for local resolver routines.

Related Information

The namersly command.

TCP/IP name resolution in Networks and communication management.

Name server resolution in Networks and communication management.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

Transmission Control Protocol/Internet Protocol in Networks and communication management.

System management interface tool in Operating system and device management.

mknetid Command

Purpose

Generates data for the netid.byname map for use by the Network Information Services (NIS).

Syntax

To Create an NIS Map:

/usr/sbin/mknetid [-q] [-p PasswordFile] [-g GroupFile] [-h HostsFile] [-m NetidFile]

Description

The **mknetid** command is used to produce the data for the **netid.byname** NIS map. It will parse the files specified on the command line and build the corresponding netid keys and values. Users will get the following entries:

```
unix.<uid>@<domainname> <uid>:<gid1>,<gid2>,...
```

Hosts will get the following entries:

unix.<hostname>@<domainname> 0:<hostname>

The domainname that is used is the same that is configured on the system at the time **mknetid** is run. The generated data is sent to stdout. Each line contains one entry, with the key and the data separated by a space.

Flags

Quiet mode - do not report any warnings about the data.

Specifies which passwd file to be used for reading the list of users. -p PasswordFile

Specifies which groups file to be used for reading the list of group memberships. **-g** GroupFile

-h HostsFile Specifies which hosts file to be used for reading the list of hostnames.

-m NetidFile Specifies a file from which to read any additional netid entries to be included.

Files

/var/yp/Makefile mknetid is most commonly used when rebuilding the NIS databases using /var/yp/Makefile.

/etc/passwd Where PasswordFile resides. Where GroupFile resides. /etc/groups /etc/hosts Where HostsFile resides. /etc/netid Where NetidFile resides.

Related Information

The **ypinit** command.

AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide

mknfs Command

Purpose

Configures the system to run NFS.

Syntax

/usr/sbin/mknfs [-I | -N | -B]

Description

The mknfs command configures the system to run the Network File System (NFS) daemons. The mknfs command adds an entry to the inittab file so that the /etc/rc.nfs file is executed on system restart.

Flags

- Adds an entry to the inittab file to execute the /etc/rc.nfs file on system restart. The mknfs command also executes the /etc/rc.nfs file immediately to start the NFS daemons. This flag is the default.
- Adds an entry to the inittab file to execute the /etc/rc.nfs file on system restart. -1
- Starts the /etc/rc.nfs file to start the NFS daemons immediately. When started this way, the daemons run until the next system restart.

Files

inittab Controls the initialization process of the system.

/etc/rc.nfs Contains the startup script for the NFS and NIS daemons.

Related Information

The chnfs command, mknfsexp command, mknfsmnt command, rmnfs command.

NFS Installation and Configuration in Networks and communication management.

Network File System (NFS) Overview for System Management in Networks and communication management.

List of NFS commands in Networks and communication management.

mknfsexp Command

Purpose

Exports a directory to NFS clients.

Syntax

/usr/sbin/mknfsexp -d Directory [-e pathname] [-f Exports_File] [-t [{ rw | ro | remove } { rm -h HostName [, HostName ...]]] [-a UID] [-r HostName [, HostName ...]] [-c HostName [, HostName ...]][-s|-n][-I|-B|-N][-P|-p][-D {yes|no}][-v][-x|-X][-S flavor[,flavor]][-G rootpath@host[+host][:rootpath@host[+host]]] [-g rootpath@host[+host][:rootpath@host[+host]]] [-o Ordering]

Description

The **mknfsexp** command takes the flags and parameters specified and constructs a line that is syntactically correct for the /etc/exports file. If this command is invoked with the -B flag, an entry will be added to the /etc/exports file and the exportfs command is invoked to export the directory specified. Alternatively, the -I flag adds an entry to the exports file and does not export the directory, or the -N flag does not add an entry to the exports file but does export the directory.

Flags

-d Directory -D {yes no} -e pathname -f Exports_File -t Type	Specifies the directory that is to be exported or changed. Enables or disables file delegation for the specified export. This option overrides the system-wide delegation enablement for this export. The system-wide enablement is done through nfso . Specifies an export name for the directory. Specifies the full path name of the exports file to use if other than the /etc/exports file. Specifies whether the directory is read-write, read-only, or read-mostly. The possible values for the <i>Type</i> variable are:	
	rw	Exports the read-write directory. This is the system default.
	ro	Exports the read-only directory.
	remove	Removes the exported directory.
	rm	Exports the read-mostly directory. If chosen, the -h flag must be used to specify the hosts that have read-write permission.
-h HostName [, HostName]		s which hosts have read-write access to the directory. This option is valid only when orted file is to be read-mostly.
-a UID		e UID variable as the effective user ID only if a request comes from an unknown
	Note: Fare inclu	ne default value of this option is -2. Root users (UID 0) are always considered unknown by the NFS server, unless they used in the root option. Setting the value of UID to -1 disables anonymous access.
-r HostName [, HostName]		oot users on the specified hosts access to the directory. The default is for no hosts anted root access.
-c HostName [, HostName]	Gives m	nount access to each of the clients listed. A client can either be a host or a netgroup. ault is to allow all hosts access.
-s		s clients to use a more secure protocol when accessing the directory.
-n	Does not require the client to use the more secure protocol. This flag is the default. Adds an entry to the /etc/exports file and the exportfs command is executed to export the	
-В		. This flag is the default.
-I		n entry to the /etc/exports file so that the next time the exportfs command is run system restart, the directory will be exported.
-N	Does not add an entry to the /etc/exports file but the exportfs command is run with the correct parameters so that the directory is exported.	

-P

Specifies that the exported directory is to be a public directory. This flag only applies to AIX 4.2.1 or later.

-p

Specifies that the exported directory is not a public directory. This flag only applies to AIX 4.2.1 or later.

-S flavor[,flavor]

May be used in conjunction with the **-c**, **-t**, or **-r** options to associate the option with one or more specific security methods. Most **exportfs** options can be clustered using the **sec** option. Any number of **sec** stanzas may be specified, but each security method can be specified only once.

Allowable flavor values are:

sys UNIX authentication.dh DES authentication.

none Use the anonymous ID if it has a value other than -1. Otherwise, a weak auth

error is returned.

krb5 Kerberos. Authentication only.

krb5i Kerberos. Authentication and integrity.

krb5p Authentication, integrity, and privacy.

-G rootpath@host [+host] [:rootpath@host [+host]] A namespace referral will be created at the specified path. The referral directs clients to the specified alternate locations where they can continue operations. A referral is a special object. If a nonreferral object exists at the specified path, the export is disallowed and an error message is printed. If nothing exists at the specified path, a referral object is created there that includes the path name directories leading to the object. A referral cannot be specified for the **nfsroot**. The name localhost cannot be used as a *hostname*. The **-G** option is allowed only for version 4 exports. If the export specification allows version 2 or version 3 access, an error message will be printed and the export will be disallowed. The administrator should ensure that appropriate data exists at the referral locations. For a more complete description of referrals, see the exportfs command. The **-G** option is available only on AIX 5L Version 5.3 with the 5300-03 Recommended Maintenance package or later. **Note:** A referral or replica export can only be made if replication is enabled on the server. Use **chnfs -R on** to enable replication.

-g rootpath@host [+host]
[:rootpath@host [+host]]

The specified directory will be marked with replica information. If the server becomes unreachable by an NFS client, the client can switch to one of the specified servers. This option is only accessible using NFS version 4 protocol, and version 4 access must be specified in the options. Because the directory is being exported for client access, specifying NFS version 2 or version 3 access will not cause an error, but the request will simply be ignored by the version 2 or version 3 server. This option cannot be specified with the **-G** flag. Only the host part of each specification is verified. The administrator must ensure that the specified *rootpaths* are valid and that the target servers contain appropriate data. If the directory being exported is not in the replica list, that directory will be added as the first replica location. The administrator should ensure that appropriate data exists at the replica locations. For a more complete description of replication, see the exportfs command. The **-g** option is available only on AIX 5.3 with 5300-03 or later.

Note: A referral or replica export can only be made if replication is enabled on the server. Use **chnfs** -**R on** to enable replication.

Defines how the alternate locations list is generated from the servers specified on the **refer** or **replicas** option. The option applies only to directories exported for access by NFS version 4 protocol. The *Ordering* parameter has three allowable values:

full All of the servers are scattered to form the combinations of alternate locations.

partial The first location of all the combinations is fixed to the first server specified on the refer or replicas option. The rest of the locations and the first location are scattered as if they are scattered using the scatter=full method.

none No scatter is to be used. The value can also be used to disable scattering if enabled previously.

-o Ordering

The directory specified by the -d option is made available to clients using the specified NFS -v number[, number] versions. Valid values are 2, 3, or 4. It is possible to export two entries for the same directory with different versions 2 (or 3) and 4. Accepts the replica location information specified with the -g option as-is. Does not insert -x the server's primary hostname into the list if it is not present. This flag is intended for use with servers with multiple network interfaces. If none of the server's host names are in the replica list, NFSv4 clients might treat the location information as faulty and discard it. Enables auto-insert of the primary hostname into the replica list. If the server's primary -X hostname is not specified in the replica list, the hostname will be added as the first replica location.

Examples

1. To export a directory with read-only permission, enter:

```
mknfsexp -d /usr -t ro
```

In this example, the mknfsexp command exports the /usr directory with read-only permission.

2. To export a directory with read-mostly permission and a secure protocol to specific hosts, enter:

```
mknfsexp -d /home/guest -t rm -h bighost, littlehost -s
```

In this example the mknfsexp command exports the /home/quest directory with read-mostly permission. using more secure protocol.

3. To export a directory with read-write permission to a specific netgroup and specific hosts, and to make the export effective on the next system restart, enter:

```
mknfsexp -d /usr -t rw -c host1,host3,qrp3 -I
```

In the above example, the mknfsexp command exports the /usr directory and gives read and write permission to host1, host2, and grp3. The -I flag makes this change effective on the next system

4. To export a directory with read-only permission to an exports file other than /etc/exports, enter: mknfsexp -d /usr -t ro -f /etc/exports.other

In the above example, the mknfsexp command exports the /usr directory with read-only permission to the /etc/exports.other file.

5. To export the /common/documents directory to allow access only to clients using NFS version 4 protocol, enter:

```
mknfsexp -d /common/documents -v 4
```

6. To export the /common/documents directory, allowing access to client1 and client2 for clients using krb5 access, enter:

```
mknfsexp -d /common/documents -S krb5 -r client1,client2
```

7. To export the /common/documents directory with full scattering for the hosts named s1 and s2 specified as referrals, enter the following command:

```
mknfsexp -d /common/documents -v 4 -G /common/documents@s1:/common/
documents@s2 -o full
```

8. To export the /common/documents directory with partial scattering at hosts named s1, s2 and s3, specified as replicas, enter the following command:

```
mknfsexp -d /common/documents -v 4 -g /common/documents@s1:/common/
documents@s2:/common/documents@s3 -o partial
```

9. To export the /common/documents directory with the export name /exports1/cool/mike, enter the following command:

```
mknfsexp -d /common/documents -e /exports1/cool/mike -S sys -v 4
```

Files

/etc/exports Lists the directories that the server can export.

Related Information

The **chnfsexp** command, **exportfs** command, **rmnfsexp** command.

NFS Installation and Configuration, and Network File System (NFS) Overview for System Management in Networks and communication management.

List of NFS commands.

mknfsmnt Command

Purpose

Mounts a directory from an NFS server.

Syntax

/usr/sbin/mknfsmnt -f PathName -d RemoteDirectory -h RemoteHost [-t { rw | ro }] [-m MountTypeName] [-w { fg | bg }] [-X | -x] [-S | -H] [-Y | -y] [-Z | -z] [-e | -E] [-a | -A] [-j | [-J] [-q | [-Q] [-g | [-G] [-s | -n] [-I | -B | -N] [-r TimesToRetry] [-R NumRetrans] [-b ReadBufferSize] [-c WriteBufferSize] [-o TimeOut] [-P PortNumber] [-u AcRegMin] [-U AcRegMax] [-v AcDirMin] [-V AcDirMax] [-T AcTimeOut] [-p NumBiods] [-K { any | 2 | 3 | 4 }] [-k { any | tcp | udp }] [-l | -L] [-M security methods] [-i { dio | cio }]

Description

The mknfsmnt command constructs an entry that is appended to the /etc/filesystems file, thus making a file system available for mounting. If the mount is to be permanent, this entry remains. If the mount is temporary, the flags are used directly for the **mount** command. If the mount is soft and the server does not respond, the system returns an error. If the mount is hard, the client continues trying until the server responds. The hard mount is the default mount.

Flags

-A	The /etc/filesystems entry for this file system specifies that it should be automatically mounted at system restart.
-a	The /etc/filesystems entry for this file system specifies that it should not be automatically mounted at system restart. This is the default flag.
-В	Adds an entry to the /etc/filesystems file and attempts to mount the file system. This is the default flag.
-b ReadBufferSize	Indicates the size of the read buffer in bytes specified by the <i>ReadBufferSize</i> variable.
-c WriteBufferSize	Indicates the size of the write buffer in bytes specified by the <i>WriteBufferSize</i> variable.
-d RemoteDirectory	Specifies the directory that is mounted on the path name specified.
-E	Allows keyboard interrupts on hard mounts.
-e	Prevents keyboard interrupts on hard mounts. This is the default flag.
-f PathName	Specifies the mount point for the remote directory.
-G	Directs any file or directory created on the file system to inherit the group ID of the parent directory.
-g	Does not direct new files or directories created on the file system to inherit the group ID of the parent directory. This is the default flag.

-H

-h RemoteHost

-1

-i

-J

-j -K

-k

L

-M security_methods

-m MountTypeName

-N

-o TimeOut

-P PortNumber

-p NumBiods

Creates a hard mount, which causes the client to continue retrying until the server responds. This is the default flag.

Specifies the NFS server that is exporting the directory.

Causes an entry to be added to the /etc/filesystems file. The directory is not mounted.

Specifies I/O mode for the mount. The options are:

cio Specifies concurrent I/O mode. Specifies the file system to be mounted for concurrent readers and writers. I/O on files in this file system will behave as if they had been opened with O_CIO specified in the open() system call.

dio Specifies direct I/O mode. Specifies that I/O on the file system will behave as if all the files had been opened with O_DIRECT specified in the open() system call.

Note: For more information on the cio and dio options, see the mount command

Indicates that acls are used on this mount.

Indicates that acls are not used on this mount. This is the default flag. Specifies the NFS version used for this NFS mount. The options are:

- Uses the mount command to determine the correct match. Refer to the any mount command for a description of the current default behavior.
- 2 Specifies NFS Version 2.
- 3 Specifies NFS Version 3.
- Specifies NFS Version 4.

Specifies the transport protocol used for the mount. The options are:

Uses the mount command to select the protocol to use. TCP protocol is any the preferred protocol.

Specifies the TCP protocol. tcp

Specifies the UDP protocol.

Indicates that the lock requests are handled locally without connecting to the

Indicates that the lock requests are not handled locally. The server handles the lock requests.

A list of security methods to use when attempting the mount. A comma separated list of the values sys. dh. krb5, krb5p, which correspond to Unix, DES. Kerberos 5, Kerberos 5 with integrity, and Kerberos 5 with privacy. Multiple values are allowed, but are meaningful only with NFS Version 4 mounts. If multiple methods are given for a Version 2 or 3 protocol mount, the first method is used. For a NFS Version 4 mount, the methods are tried in the listed order.

Specifies the type of file system to mount. File system types are specified in the /etc/filesystems file with the type variables. When the mount -t MountTypeName command is issued, all of the currently unmounted file systems with a type equal to the MountTypeName are mounted.

Mounts the directory with the options specified but does not modify the /etc/filesystems file.

Instructs the mount not to use a more secure protocol. This is the default flag. Indicates the length of the NFS timeout in tenths of a second as specified by the TimeOut variable.

Indicates the Internet Protocol port number for the server.

Specifies the number of **biod** daemons that are allowed to work on a particular file system. The biod daemons handle client requests. The default number of daemons is 6.

-Q	Requests that no posix pathconf information be exchanged and made available on an NFS Version 2 mount. Requires a mount Version 2 rpc.mountd at the NFS server.		
-q	Specifies that no posix pathconf information is exchanged if mounted as an NFS Version 2 mount. This is the default flag.		
-r TimesToRetry -R NumRetrans	Indicates the number of times to retry a mount. The default value is 1000. For a soft mount, this flag specifies the number of times that a request has to be transmitted if it is not acknowledged by the server. If the request is unacknowledged after <i>NumRetrans</i> transmissions, the client gives up the request. If this flag is not specified, the default value 3 is used.		
-S	Creates a soft mount, which means the system returns an error if the server does not respond.		
-s	Instructs the mount to use a more secure protocol.		
-T AcTimeOut	Sets the minimum and maximum times allowed for regular files and directories to the number of seconds specified by the <i>Actimeo</i> variable. If this flag is specified, the other cached attribute times are overridden.		
-t Type	Specifie	es that the directory is either read-write or read-only.	
	rw	Mounts the directory read-write. This type is the default for the system.	
	ro	Mounts the directory read-only.	
-U AcRegMax	AcRegl	cached attributes for no more than the number of seconds specified by the <i>Max</i> variable after file modification.	
-u AcRegMin		cached attributes for at least the number of seconds specified by the <i>Min</i> variable after file modification.	
-V AcDirMax	Holds cached attributes for no more than the number of seconds specified by the <i>AcDirMax</i> variable after directory update.		
-v AcDirMin	Holds cached attributes for at least the number of seconds specified by the <i>AcDirMin</i> variable after directory update.		
-w Location		es where the mount should be attempted. The <i>Location</i> variable can have the following values:	
	fg	Attempts the mount in the foreground. This is the default value.	
	bg	Attempts the mount in the background. If background is specified and the attempt to mount the directory fails, the mount will be retried in the background.	
-x	Specifie	es that the server does not support long device numbers.	
		s flag when mounting from an NFS server that does not correctly handle numbers that are 32 bits long.	
-X	Specifies that the server does support long device numbers. This is the default flag.		
-у	Indicates that the execution of suid and sgid programs is not allowed in this file system.		
-Y	Indicates that the execution of suid and sgid programs are allowed in this file system. This is the default flag.		
-z	Indicates that device access through this mount is not allowed; that is, the device cannot be opened on this mount point.		
-Z	Indicates that device access through this mount is allowed. This is the default flag.		

Example

To add the mount of a remote directory, enter:

mknfsmnt -f /usr/share/man -d /usr/share/man -h host1

In this example, the mknfsmnt command mounts the remote directory /usr/share/man on the /usr/share/man directory that resides on host1.

Files

/etc/filesystems

Lists the remote file systems to be mounted during the system restart.

Related Information

The **chnfsmnt** command, **mount** command, **rmnfsmnt** command.

How to Mount a NFS File System Explicitly in Networks and communication management.

Network File System (NFS) Overview for System Management in Networks and communication management.

List of NFS commands.

mknfsproxy Command

Purpose

Creates a new NFS proxy-enabled Cachefs instance that is backed with an NFS client mount to a back-end NFS server.

Syntax

/usr/sbin/mknfsproxy [-L] -c local_cache_directory -d Cachefs_mount_point [-o param=n[, param=n]] -m [nfs mount options] remote server.remote directory [-e [export option, [export option]]]

Description

The local file system used by the created Cachefs instance must be a JFS2 file system. The required inputs include the remote server and directory (remote_server.remote_directory) that the Cachefs instance will access, the local directory (local cache directory) where information will be cached, and the directory where the Cachefs will be mounted.

After the cache is initialized, the Cachefs instance is mounted and ready to be NFS exported. Provide NFS export information so that the cached view will also be NFS exported using the specified options.

Flags

-с	Specifies the local JFS2 file system directory where Cachefs will store cached data and state. This is a required option.
-d	Specifies the directory where Cachefs will be mounted. This is a required option.
-e	Specifies the NFS server export options for the created Cachefs instance. If this is supplied, the created Cachefs instance will also be NFS exported using the supplied options. If this option is not supplied, the created Cachefs instance will be exported with the same NFS version specified by the -m option.
-L	Causes the Cachefs instance to acquire a single lock from its associated NFS back-end that covers the entire file when any byte range locks are requested. When the count of byte range locks drops to 0 (zero), the lock on the

back-end NFS server is released.

-m

-0

Specifies the NFS client mount, which might optionally include NFS client mount options as described in the **mount** man page. This is a required option, and the remote server and remote directory must be supplied. Specifies Cachefs configuration options in the form **param=n**. For descriptions of the Cachefs resource parameters, refer to the **cfsadmin** command.

Parameters

Cachefs_mount_point

export_option

local_cache_directory
nfs_mount_options
remote_directory

remote_server

Specifies where the proxy-enabled Cachefs instance is to be mounted.

Specifies which options of the **export** command are used for the Cachefs instance.

Specifies the local directory where information is cached. Specifies the NFS client options of the **mount** command. Specifies the remote directory that the Cachefs instance accesses.

Specifies the remote server that the Cachefs instance accesses.

Exit Status

υ >0 The command completed successfully. An error occurred.

Examples

 To create a proxy-enabled Cachefs instance at /edge that accesses /project1 at NFS server foo, enter:

mknfsproxy -c /cache/project1 -d /edge -m hard, vers=4, intr foo:/project1

In the preceding example, information accessed through /edge is cached at /cache/project1.

The following variation of the preceding example also exports the created Cachefs instance (proj1_cached) for NFS V4 access with authentication flavor of Kerberos 5 and an external name set to /nfs4/projects/project1:

mknfsproxy -c /cache/project1 -d /edge -m hard,vers=4,intr foo:/project1
 -e sec=krb5,vers=4,exname=/nfs4/projects/project1

Location

/usr/sbin/mknfsproxy

Related Information

The cfsadmin command, "mount Command" on page 722, rmnfsproxy command.

mknod Command

Purpose

Creates a special file.

Syntax

Only executed by root or system group member

mknod Name { b | c } Major Minor

Creates FIFOs (named pipelines)

mknod Name { p }

Description

The **mknod** command makes a directory entry and corresponding i-node for a special file. The first parameter is the name of the Name entry device. Select a name that is descriptive of the device. The mknod command has two forms that have different flags.

The first form of the **mknod** command can only be executed by root or a member of the system group. In the first form, the **b** or **c** flag is used. The **b** flag indicates the special file is a block-oriented device (disk, diskette, or tape). The **c** flag indicates the special file is a character-oriented device (other devices).

The last two parameters of the first form are numbers specifying the Major device, which helps the operating system find the device driver code, and the Minor device, that is the unit drive or line number, which may be either decimal or octal. The major and minor numbers for a device are assigned by the device's configure method and are kept in the CuDvDr class in ODM. It is important that major and minor numbers be defined in this object class to insure consistency of device definitions through the system.

In the second form of the **mknod** command, the **p** flag is used to create FIFOs (named pipelines).

Flags

- b Indicates the special file is a block-oriented device (disk, diskette, or tape).
- Indicates the special file is a character-oriented device (other devices). С
- Creates FIFOs (named pipelines).

Examples

To create the special file for a new diskette drive, enter:

mknod /dev/fd2 b 1 2

This creates the /dev/fd2 special file that is a special block file with the major device number 1 and the minor device number 2.

Files

/usr/sbin/mknod Contains the **mknod** command.

Related Information

The **mknod** subroutine.

The List of Device Configuration Subroutines in AIX 5L Version 5.3 Kernel Extensions and Device Support Programming Concepts.

mknotify Command

Purpose

Adds a notify method definition to the Notify object class.

Syntax

mknotify -n NotifyName -m NotifyMethod

Description

The **mknotify** command adds a notify method definition to the **Notify** object class. When a notify method is defined for both a subsystem name and a group name, the subsystem name takes precedence. For example, if the subsystem notify method is executed by the System Resources Controller (SRC), the group notify method is not performed.

The SRC places the name of the unsuccessful subsystem as the first argument to the method and the name of the unsuccessful subsystem group as the second argument.

Flags

-m NotifyMethod Specifies an absolute path to an executable program that starts when the subsystem

stops abnormally.

Specifies the subsystem or group name to which the notify method belongs. The -n NotifyName

NotifyName variable must exist as either a valid subsystem name or a valid group name in the Subsystem object class. The mknotify command is unsuccessful if the

NotifyName variable already exists in the Notify object class.

Examples

1. To add a notify method for the srctest subsystem, enter:

```
mknotify -n srctest -m /usr/lpp/srctest/failure
```

This adds a subsystem notify method for the srctest subsystem, with a notify method designated in the /usr/lpp/srctest/failure file.

2. To add a notify method for the tcpip group, enter:

```
mknotify -n tcpip -m /usr/lpp/tcpip/tcpfailure
```

This adds a group notify method for the tcpip group, with a notify method designated in the /usr/lpp/tcpip/tcpfailure file.

Files

/etc/objrepos/SRCsubsys Specifies the SRC Subsystem Configuration object class. /etc/objrepos/SRCnotify Specifies the SRC Notify Method object class.

Related Information

The **rmnotify** command, **Issrc** command, **mkssys** command, **rmssys** command.

System Resource Controller in the Operating system and device management.

System Resource Controller (SRC) Overview for Programmers in the in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs.

Defining Your Subsystem to the SRC in the in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs.

mkpasswd Command

Purpose

Organizes the basic user database for efficient searches.

Syntax

mkpasswd [-v] { -f | -d | -c} | indexname

Description

The **mkpasswd** generates indexes over certain security files. These indexes are used by the **getpwnam**, **getpwuid**, **getuserattr**, and **putuserattr** library subroutines.

This approach significantly enhances performance for large user base systems. The following indexes, defined in /usr/include/usersec.h, are created:

/etc/passwd.nm.idx: Index over /etc/passwd file using username as key.
/etc/passwd.id.idx: Index over /etc/passwd file using userid number as key.

/etc/security/passwd.idx: Index over /etc/security/passwd file.
/etc/security/lastlog.idx: Index over /etc/security/lastlog file.

Notes:

- Modifying the security files over which indexes are built by an editor disables the use of indexing mechanism.
- 2. Indexed read of a data file is automatically done if a corresponding index exists over the file and is not older than it (except for lastlog index).
- In order for indexed mechanism to be used at login, the mkpasswd command must have generated indexes.
- 4. The indexing mechanism replaces the previous hashing mechanism which used dbm files.

Flags

-v Reports progress if index built.-f Forces building of all indexes.

-d Deletes all indexes.

-c Checks all indexes and rebuilds the ones that look suspicious.

indexname Forces building of a particular index.

Security

Access Control: Only the root user and members of the security group should have execute (x) access to this command. The command should be setuid to the root user so the command has access to the user database. Members of the security group should have access to all the files listed in the Files section. This command should have the **trusted computing base** attribute.

Files Accessed:

Mode File

r /etc/passwd

rw /etc/passwd.nm.idxnnnn.tmp and /etc/passwd.id.idxnnnn.tmp

where *nnnn* is the process id.

r /etc/security/passwd rw /etc/security/passwd.idx

rw /etc/security/passwd.idxnnnn.tmp

where *nnnn* is the process id

r /etc/security/lastlog rw /etc/security/lastlog.idx

rw /etc/security/lastlog.idxnnnn.tmp

where nnnn is the process id

Examples

1. To create and enable indexed read of security files, enter:

mkpasswd -f

2. To create and enable indexed read of only the /etc/security/passwd file, enter:

mkpasswd /etc/security/passwd.idx

3. To check and rebuild outdated or bad indexes, enter:

mkpasswd -c

Files

/usr/sbin/mkpasswdContains the mkpasswd command./etc/passwdContains basic user attributes./etc/security/passwdContains user password attributes/etc/security/lastlogContains lastlog related attributes

Related Information

The passwd command, pwdadm command mkuser command chuser command rmusers command.

The getpwnam subroutine, getpwuid subroutine, getuserattr subroutine, putuserattr subroutine.

For more information about the identification and authentication of users, discretionary access control, the trusted computing base, and auditing, refer to the *Security*.

mkpath Command

Purpose

Adds to the system another path to an MPIO capable device.

Syntax

mkpath [-I Name] [-p Parent] [-w Connection] [-d]

mkpath -h

Description

The **mkpath** command defines, and possibly configures, one or more paths to the target device (-I Name). The paths are identified by a combination of the -I Name, -p Parent, and -w Connection flags. Both the target device and parent must be previously defined in the system to define a path. They both must be "AVAILABLE" to configure a path.

If the -d flag is specified, the mkpath command only defines the new path definition to the system. If the -d flag is not specified, the mkpath command attempts to define the path, if it does not already exist, before it attempts to configure the path. Configuring a path requires the path to already be defined and both the device and the parent device to already be configured.

The **mkpath** command displays a status message upon completion. It is possible for some paths to configure and others to fail.

Note that any device that cannot be manually defined using the **mkdev** command will not be able to have paths manually defined to using the **mkpath** command. These limitations are due to the way that path information is stored for these devices. Fiber channel devices fall into this category.

The **mkpath** command provides status messages about the results of operation. Messages in one of the following formats will be generated:

path [available | defined]

This message is displayed when **mkpath** is run on a single path. If the path is successfully configured the message "path available" is displayed. If the path is not successfully configured and there is no explicit error code returned by the method, the message "path defined" is displayed.

paths available

This message is displayed if multiple paths were identified and all paths were successfully configured.

some paths available

This message is displayed if multiple paths were identified, but only some of them were successfully configured.

no paths processed

This message is generated if no paths were found matching the selection criteria.

Flags

-d Defines a new path to a device by adding a path definition to the system. The new path

will not automatically be configured when the -d flag is specified. Note that only one path

may be defined at a time.

-h Displays the command usage message.

-I Name Specifies the logical device name of the target device to which the path(s) are being

added. The path(s) to be added are qualified by the -p and -w flags.

Indicates the logical device name of the parent device associated with the path(s) to be -p Parent

added. This flag is required if the -d flag is specified.

Indicates the connection information associated with the path to be added. This flag is -w Connection

required if the -d flag is specified.

Security

Privilege Control: Only the root user and members of the system group have execute access to this command.

Auditing Events:

Event	Information
DEV_Change	mkpath,Define, <define arguments="" method=""></define>
DEV_Change	mkpath,Configure, <configure arguments="" method=""></configure>

Examples

1. To define and configure an already defined path between scsi0 and the hdisk1 device at SCSI ID 5 and LUN 0 (i.e., connection 5,0), enter:

```
mkpath -1 hdisk1 -p scsi0 -w 5,0
```

The system displays a message similar to the following:

path available

2. To configure an already defined path from 'fscsi0' to fiber channel disk 'hdisk1', the command would

```
mkpath -1 hdisk1 -p fscsi0
```

The message would look similar to:

path available

3. To only add to the Customized Paths object class a path definition between scsi0 and the hdisk1 disk device at SCSI ID 5 and LUN 0, enter:

```
mkpath -d -l hdisk1 -p scsi0 -w 5,0
```

The system displays a message similar to the following:

path defined

Files

/usr/sbin/mkpath

Contains the mkpath command.

Related Information

The **chpath** command, **Ispath** command, **rmpath** command.

mkprojldap Command

Purpose

Configures the LDAP client and server machines for handling advanced accounting subsystem data.

Syntax

mkprojldap -s -h hostname -D bindDN -w bindPWD -i -p projectInstallPoint -a adminInstallPoint

mkprojldap -u -h hostname -D bindDN -w bindPWD

mkprojldap -c -D bindDN -w bindPWD [-p accountingProjectDN] [-a accountingAdminDN] [-r cron]

mkprojldap { -I | -L [-D bindDN -w bindPWD] | -V } [-p] [-a]

Description

The **mkproildap** command configures the LDAP server and client machines for handling the advanced accounting subsystem data. The LDAP server and client relationship must already be defined, and mkproildap makes only incremental changes. The mkproildap command can be used to configure the basic LDAP connection.

To add advanced accounting support to the LDAP server, the LDAP schema for advanced accounting must be uploaded to the server. The schema describes the format of advanced accounting data to the server, enabling the server to process accounting data without being enabled specifically for accounting. This is accomplished with the -u option. The LDAP server is not dependent on advanced accounting. This command needs to be run only once for each LDAP server. After this command is run, use the -s option to define the location on the LDAP server where advanced accounting data is to be stored. This command can be run one or more times to establish one or more accounting domains. An LDAP client can only access only one accounting domain at a time.

To configure an LDAP client so that it receives advanced accounting data, use the -c option to specify the location of the advanced accounting data sets on the LDAP server that are to be used by the LDAP client. The **mkproildap** command is used to configure absolute paths, which are known as distinguished names (DNs), to projects and admin policies. The advanced accounting subsystem stores project definitions and admin policies on LDAP servers, so there are two advanced accounting DNs that can be configured. The mkprojldap -c command must be run on each client.

Flags

-a accountingAdminDN	Specifies the accounting admin DN location on the LDAP server, when used with -s or -c options. When used with -I or -L options, this flag displays the accounting admin DN.
-C	Configures the LDAP client.
-D bindDN	Specifies the Bind DN to be used during the server configuration.
-h hostname	Specifies the host name of the LDAP server during the server configuration.
-i	Provides the admin (-a) and project (-p) install points during the server configuration.
-L	Displays the potential accounting DNs that are visible from the server.
-1	Displays the accounting DNs in the Idap.cfg file.
-p accountingProjectDN	Specifies the accounting project DN location on the LDAP server when used with the -s or -c options. When used with -I or -L options, this flag displays the accounting project DN.
-r con	Specifies the frequency for refreshing the LDAP repositories (hourly, daily, or off).
-s	Configures the LDAP server.
-u	Uploads the advanced accounting schema to the LDAP server.
-V	Displays the current LDAP client configuration details in a colon separated format.
-w bindPWD	Used to provide the Bind password for the Bind DN specified with the -D option.

Note: When using the preceding flags with this command, use the following guidelines:

• During server and client configuration, both the -p and -a arguments can be specified at the same time, but neither is required. If neither is specified, the mkproildap command tries to compute the missing accounting DNs by searching for the objects on the LDAP server. These

- objects are **ou=projects** and **ou=adminpolicy**. If an object is found, the corresponding accounting DN is computed and added to the **Idap.cfg** file.
- While listing the accounting DNs using the -I or -L options, both -p and -a can be used. If neither of them are provided, all accounting DNs in the Idap.cfg file are listed.
- The colon-separated data displayed by the **-V** option takes the following format: ldap-server-hostname:bind DN:bind password:default-projectdn:default-admindn:cron

Exit Status

0 Successful completion.>0 An error occurred.

Examples

1. To upload the advanced accounting schema, type:

```
mkprojldap -u -h mozilla -D cn=root -w mozillapasswd
```

2. To configure the LDAP server, type:

This command creates two DNs in the following format:

ou=projects,ou=aacct,cn=aixdata,o=ibm and ou=adminpolicy,ou=aacct,cn=aixdata,o=ibm

3. To configure the LDAP client, type:

4. To display the currently configured accounting DNs, type:

```
mkprojldap -1
```

Files

/usr/sbin/mkprojldap /etc/security/ldap/ldap.cfg /etc/project/ldap/accountingSchema.ldif

Contains the **mkprojldap** command.

Contains the LDAP configuration data.

Contains the LDAP schema for advanced accounting.

Related Information

The projetl command, secidapcintd command.

AIX 5L Version 5.3 Advanced Accounting Subsystem.

mkproto Command

Purpose

Constructs a prototype file system.

Syntax

mkproto Special Prototype

Description

The **mkproto** command is used to construct a prototype for a new file system. It exists solely for Berkeley Software Distribution (BSD) compatibility.

The Special parameter can be a block device name, raw device name, or file system name. The Prototype parameter is the name of the prototype file that specifies the structure and contents of the file system to be created. The **mkproto** command calls the **mkfs** command with the *Prototype* and *Special* parameters.

Prototype Files

The mkproto and mkfs commands require an extended prototype file to create a Journaled File System (JFS). A prototype file is a formatted listing of the contents and structure of a file system. A prototype file describes the file system by a series of tokens separated by spaces and new lines. The main body of a prototype file defines the objects of the file system.

A JFS prototype file consists of the main body, which can be created by the **proto** command, preceded by five special tokens. These five tokens are defined as follows:

1st token Name of a file to be copied onto block 0 as the bootstrap program or the special token <noboot>.

2nd token Size of the file system. For a JFS, the size is expressed in units of 512-byte blocks. If the 2nd

token is 0, the **mkfs** command creates the file system to fill the entire logical volume.

Number of i-nodes on the file system. This token is not used by a JFS but must be provided to 3rd token

preserve the position.

4th token Size of the file system fragment in bytes. If the 4th token is 0 (zero), the mkfs command uses the

default fragment size. For JFS, the token must be either 0 (default value used), 512, 1024, 2048, or 4096. The default fragment size is 4096 for a JFS. An invalid fragment size causes the mkfs

5th token Number of bytes per i-node (nbpi). If this token is 0, the mkfs command uses the default nbpi. For

a JFS, this token must be either 0 (default value used), 512, 1024, 2048, 4096, 8192, or 16384. The default number of bytes per i-node is 4096 for a JFS. An invalid nbpi causes the mkfs

command to fail.

The remaining tokens define the contents and structure of the file system. These tokens are grouped into sets, with each set defining one object of the file system. The syntax of each set is as follows:

{ [Name] { - | d | b | c | I | L | p } { - | u } { - | g } { - | t } Mode Owner Group { Major Minor | SourceFile | DirectoryListing \ \ \ \ \ \ \ \

where:

Name

Specifies the name of the object as it is to appear in the new file system. The *Name* token is required for every object except for the root directory definition.

{-|d|b|c||L|p}{-|u}{-|g}{-|t}

Represents a string of 4 positional characters, where:

{-|d|b|c|||L|p}

Defines the object type. Valid types are:

- Regular file
- d Directory
- **b** Block special file
- c Character special file
 - Symbolic link
- L Hard link
- p Named pipe

{ - | u }

Toggles the set UID bit of the object, as follows:

- u Set UID on execution
- Do not set UID on execution
- { I g } Toggles the set group ID (GID) bit of the object, as follows:
 - g Set GID on execution
 - Do not set GID on execution
- { I t } Toggles the sticky bit of the object, as follows:
 - t Sticky bit on
 - Sticky bit off

This 4-character token is required for every object. Represents a string of 3 octal characters defining the read, write, and execute permissions of the object. The *Mode* token is required of every object. See the **chmod** command for more information about permissions.

Specifies the UID of the owner of the object. The owner token is required for every object.

Specifies the GID of the owner of the object. The group token is required for every object.

Specifies the major and minor device numbers of the object if its type is a block or character special file. If the object is not a block or character special file, these tokens are omitted.

Applies only to regular file, hard link, and symbolic link objects. For regular files, this token is the path name to the file from which the object file is to be initialized. For both symbolic and hard links, this token is the source of the link. The source of the link is relative to the new file system for hard links.

Defines the contents of the object if it is a directory. The contents of the directory are defined using the token syntax described here. For example, a directory listing can include one or more regular files, one or more block files, and one or more directory listings. The **mkfs** command creates the directory entries . (dot) and .. (dot dot). Each directory listing is terminated with the special \$ token. Ends the current directory listing or indicates the end of the prototype file.

Mode

Owner

Group

Major Minor

SourceFile

DirectoryListing

\$

Example Prototype Specification

The following prototype specification describes a JFS that does not have a boot program in block 0 and occupies the entire device. The 3rd token is ignored. The 4th and 5th tokens define the fragment size as 1024 bytes and the number of bytes per i-node as 2048. The main body of this prototype defines the file system contents.

```
<noboot> 0 0 1024 2048
d--- 755 0 0
dir1
      d--- 755 0 2
 block dev b--- 644 0 0
                           880 881
 990 991
 named pipe p--- 644 0 0
 regfile3 ---- 644 0 0
                           /tmp/proto.examp/dir1/regfile3
 regfile4
            ---- 644 0 0
                          /tmp/proto.examp/dir1/regfile4
 dir2
        d--- 755 205 300
 regfile6 ---- 644 0 0
                           /tmp/proto.examp/dir2/regfile6
 symlnOutofFS 1--- 644 0 0 /tmp/proto.examp/dir2/regfile6
 symlnNoExist 1--- 644 0 0 /home/foobar
 symlnInFs 1--- 644 0 0
                           /dir2/regfile6
           ---- 644 0 0
                           /tmp/proto.examp/dir2/regfile5
 regfile5
 hardlink L--- 644 0 0
                           /dir2/regfile5
      d--- 755 0 0
dir3
 setgid
         --g- 755 0 0
                           /tmp/proto.examp/dir3/setgid
           -u-- 755 0 0
                           /tmp/proto.examp/dir3/setuid
 setuid
           ---t 755 0 0
                           /tmp/proto.examp/dir3/sticky
 sticky
dir4 d--- 755 0 0
 dir5 d--- 755 0 0
  dir6 d--- 755 0 0
   $
  dir7 d--- 755 0 0
   $
  $
                           /tmp/proto.examp/dir4/regfile7
 regfile7
          ---- 644 0 0
regfile1
            ---- 555 205 1 /tmp/proto.examp/regfile1
            ---- 744 0 0
regfile2
                           /tmp/proto.examp/regfile2
$
```

Three entries for the dir2 object deserve further examination:

```
symlnOutofFS 1-- 644 0 0 /tmp/proto.examp/dir2/
regfile6
symlnNoExist 1-- 644 0 0 /home/foobar
symlnInFs 1-- 644 0 0 /dir2/regfile6
```

This entry defines a symbolic link to a file outside the file system to be created. The command 1s -1 lists something similar to sym1nOutofFS -> /tmp/proto.examp/dir2/ regfile6.

This entry defines a symbolic link to a file outside the file system to be created to a file that does not exist. The command 1s -1 lists something similar to sym1nNoExist -> /home/foobar.

This entry defines a symbolic link to a file within the file system to be created. The command 1s -1 lists something similar to symlnInFS -> /dir/regfile6.

Examples

To make a prototype JFS using the prototype file described in the "Example Prototype File Specification":

- 1. Generate the main body of the prototype file using the **proto** command or a text editor. For the purposes of this example, call the file /tmp/ProtoFile.
- 2. Add the first 5 tokens as required for a JFS. In the example prototype file, the tokens are:

```
<noboot> 0 0 1024 2048
```

3. Create a logical volume to hold the file system, as follows:

```
mklv -y protolv -t jfs SomeVGname 5
```

This command creates a logical volume named protol v in the Some VG name volume group. The size of the logical volume is 5 logical partitions.

4. Add an appropriate stanza to the /etc/filesystem file. A minimal example stanza is:

/protofs: dev = /dev/protolv vfs = jfs = /dev/loglv00 log mount = false

5. Run the following **mkproto** command:

```
mkproto /dev/protolv /tmp/ProtoFile
```

This command creates a JFS on the protoly logical volume. The size of the JFS is 5 logical partitions, its fragment size is 1024 bytes, and its hbpi ratio is 2048. The structure and contents of the file system are as specified in the prototype file /tmp/ProtoFile.

Files

/usr/sbin/mkproto

Contains the **mkproto** command.

Related Information

The mkfs command, fsck command, fsdb command, proto command.

The filsys.h file, dir file.

File systems in Operating system and device management.

mkprtldap Command

Purpose

Configures IBM Directory (LDAP) for Directory enabled System V print. It also configures client machines to use the Directory for System V print information.

Syntax

To configure the IBM Directory to store System V Print information:

```
mkprtldap -s -a AdminDN -p Adminpasswd -w ACLBindPasswd [-f] [-d nodeDN]
```

To configure clients to use the IBM Directory for System V Print information:

```
mkprtldap -c -h DirectoryServerHostname -w ACLBindPasswd [ -d PrintBindDN ] [-U]
```

To get usage information for the **mkprtldap** command:

mkprtldap?

Description

The **mkprtIdap** command configures the IBM Directory (LDAP) server, and one or more clients to use the Directory (LDAP) for System V Print information. This command must be run on the system being setup as the server and on all the client systems. Once the Directory (LDAP) server is configured for System V print, the directory enabled System V Print commands (dslpadmin, dslpaccess, dslpsearch, dslpenable, dslpdisable, dslpaccept, lp, lpstat, cancel and dslpreject) must be run to add, remove and manage System V print information (printers and print queues) on the Directory (LDAP) server. The mkprtldap command configures client machines to use the Directory (LDAP) server for System V print information.

The **mkprtIdap** command requires the IBM Directory server software to be installed on the machine being configured as the server. The command also requires the IBM Directory client software to be installed on all client machines that will use the Directory (LDAP) server for System V print information.

Note: The client (-c flag) and the server (-s server) options cannot be run at the same time. When setting up a system as the server, the mkprtldap command should be run twice on that system. Once to set up the server, and again to set up the client.

During the server side configuration, using the -s flag, the mkprtldap command:

- · Requires the IBM Directory Administrator's DN and password if the Directory has been configured. If the Directory Administrator's DN and password have not been set, mkprtldap will set them with the values passed to the command.
- Creates the AIX Information tree DN (cn=aixdata container object) on the Directory if one is not present. The print subtree will be created under the AIX Information subtree. If an existing AIX Information subtree exists on the Directory, the print subtree will be created under it. All System V print information will be stored under the print subtree. The directory enabled System V print commands have to be run to add printers and print queues under the print subtree created.
- The default suffix and AIX Information tree for the **mkprtIdap** command is a top level container object cn=aixdata. The Print subtree (ou=print) will be created under the AIX Information tree.
- The print subtree is ACL protected with the value of the ACLBindPasswd parameter passed to the command. The same value must be used when configuring clients to use the Directory for System V print information. Select a password value that is difficult for people or password cracking programs to quess.
- · If the -d option is used and a valid existing node on the Directory is passed to the command, the AIX Information subtree is created under the given node. The print subtree is then created under the AIX Information subtree.
- · Starts the IBM Directory server after all the above is done
- · Adds the IBM Directory server process (slapd) to the /etc/inittab file to have the server start after a reboot.

During the client configuration, the **mkprtldap** command:

- · Saves the IBM Directory (LDAP) server host name in the /etc/ldapsvc/server.print file.
- Saves the AIX Print Bind DN in the /etc/ldapsvc/server.print file.
- Saves the ACL Bind Password for the AIX Print Bind DN in the /etc/ldapsvc/system.print file. The value of the ACL Bind password must be the same as the one specified during the configuration of the Directory server.
- Undo a previous client configuration if the -U flag is specified. This option will replace the /etc/ldapsvc/system.print and /etc/ldapsvc/server.print files with the previous saved copies of the files (/etc/ldapsvc/server.print.save and /etc/ldapsvc/system.print.save).

Flags

Server

-a AdminDN Specifies the Directory (LDAP) Administrator's DN.

-d nodeDN This advanced option requires a valid existing node DN on the Directory under

which the AIX Information tree and Print Subtree will be created.

-f The force flag is required by the **mkprtldap** command to force the creation of the

Print subtree (and AIX Information subtree if needed) when one or more AIX

Information trees exist on the Directory.

-p adminpasswd
 Specifies the Directory (LDAP) Administrator's password.

Indicates the command is being run to configure the Directory for System V print.
 ACLBindPasswd
 Specifies the password to ACL protect the Print Subtree on the Directory. Select a

password value that is difficult for people or password cracking programs to guess.

Client

-c Indicates the command is being run to configure clients to use the Directory

for System V Print information.

-d PrintBindDN Specifies the Print Bind DN. The default Print Bind DN is

ou=print,cn=aixdata. The Print Bind DN to use during Client configuration is

displayed at the end of the server setup of the mkprtldap command.

-h DirectoryServerHostname Hostname of the IBM Directory server setup to store System V Print

information.

-U Undo a previous configuration of a client.

-w ACLBindPasswd The ACL Bind Password for the print subtree. The ACL Bind password is

specified during the server setup of the **mkprtIdap** command. The value of the ACL Bind Password must match the one used during the setup of the

Directory server.

Usage

? Displays usage information for the **mkprtIdap** command.

Security

This command can be run by the root user only.

Examples

1. To configure System V print on a machine with a configured IBM Directory server -

The Administrator DN and password are required to configure System V print on the Directory. Assume the existing Administrator's DN and password are **cn=admin** and **passwd**.

```
mkprtldap -s -a cn=admin -p passwd -w pass123wd
```

2. The mkprtldap command provides the option to configure the IBM Directory to store the print information under a pre-existing node (e.g. o=ibm,c=us) on the Directory [Advanced Option]. This is only recommended when it is necessary to store the print information under the existing node on the Directory for specific reasons. The recommend option is to store the print subtree in the default location on the Directory by not specifying the -d option. The Administrator DN and password are required to configure System V print on the Directory Assume the existing Administrator's DN and password are cn=admin and passwd.

mkprtldap -a cn=admin -p passwd -w acl123passwd -d o=ibm,c=us

- Running the command will create an AIX Information tree (cn=aixdata) under the o=ibm,c=us object. The print subtree will be created under this new object (cn=aixdata, o=ibm, c=us).
- 3. To configure System V print on a machine with a configured IBM Directory server and an existing AIX Information tree. There might be situations where the Directory contains an existing AIX information tree with other subsystem specific information (e.g Security or NIS information). It might be required to store the print information in a separate location on the Directory under a different AIX Information tree. The command, by default, will not create a new AIX Information tree if one exists on the Directory. To force the command to create a new AIX Information tree to store the print information, use the -f flag with the command. Consider the case where the Security and NIS subsystem information is stored under the AIX Information tree at cn=aixdata,o=ibm,c=us. To create a new AIX Information tree for print information different from the existing one, run the command with the -f flag and specify the default location or another node. The Administrator DN and password are required to configure System V print on the Directory. Assume the existing Administrator's DN and password are cn=admin and passwd

mkprtldap -a cn=admin -p passwd -w passwd123 -f

Running the command will create a new AIX Information tree (cn=aixdata) with the suffix (cn=aixdata) and the print information will be stored under this new AIX Information tree (ou=print, cn=aixdata). There will be two AIX Information trees on the Directory in this example cn=aixdata,o=ibm,c=us and cn=aixdata. The print information will be under the cn=aixdata object (suffix - cn=aixdata). For mkprtldap, it is recommend to use the default location to add the print information to the Directory.

4. To configure a client to use an IBM Directory setup for System V Print on host server.ibm.com, type: mkprtldap -c -h server.ibm.com -w passwd

Please ensure that the ACL Bind Password (passwd) is the same as the one specified during the setup of the Directory Server. Running the command without specifying a Print Bind DN value with the -d option will cause the command to use the default Print Bind DN ou=print,cn=aixdata. The Print Bind DN must match the one displayed at the end of running the mkprtldap command to configure the

5. To change the information in the client side configuration files, run the mkprtldap command with the new information

mkprtldap -c -h server.ibm.co.uk -w aclpasswd -d ou=print,cn=aixdata,c=uk

Executing this command on a client that has already been configured will change the information in the /etc/ldapsvc/server.print and /etc/ldapsvc/system.print files to contain the new configuration information. The original contents of the /etc/ldapsvc/server.print and /etc/ldapsvc/system.print will stored in the /etc/ldapsvc/server.print.save and /etc/ldapsvc/system.print.save files.

Files

Mode	File	Description
rw	/etc/slapd32.conf	(Server configuration) - Contains the IBM Directory
		(LDAP Version 5.2) configuration information.
rw	/home/ldapdb2/idsslapd-ldapdb2/etc/ibmslapd.conf	(Server configuration) - Contains the IBM Directory
		(LDAP Version 6.0 or later) configuration information.
rw	/etc/ldapsvc/server.print	(Client configuration) - Contains information about the
		Directory Server configured to store System V Print
		information. (Machine name, Location of Print subtree
		on the Directory and LDAP port)
rw	/etc/ldapsvc/system.print	(Client configuration) - Contains the ACL Bind
		Password for the Print subtree on the Directory.

Related Information

Configuring Directory Enabled System V print in the *Printers and printing*.

The dslpadmin command, dslpaccess command, dslpsearch command, dslpenable command, dslpdisable command, dslpaccept command, lp command, lpstat command, cancel command, dslpreject command, and mksecldap command.

The /etc/ldapsvc/server.print and /etc/ldapsvc/system.print files.

The /etc/slapd32.conf file, /home/ldapdb2/idsslapd-ldapdb2/etc/ibmslapd.conf file.

mkprtsv Command

Purpose

Configures TCP/IP-based print service on a host.

Syntax

To Configure and Start Print Service for a Client Machine

mkprtsv -c [-S][-q QueueName -v DeviceName -b "Attribute =Value ..." -a "Attribute =Value ..." | -A FileName]

To Configure and Start Print Service for a Server Machine

mkprtsv -s [-S] [-q QueueName -v DeviceName -b "Attribute = Value ..." -a "Attribute = Value ..." | -A FileName] [-h "HostName ..." | -H FileName]

Description

The **mkprtsv** high-level command configures a TCP/IP-based print service on a host. The print service configuration can be done for a host functioning as a client or for a host functioning as a server.

Use the command to configure and start the print service.

To configure print service for a client, the **mkprtsv** command calls the spooler **mkque** and **mkquedev** commands to change the /etc/lpd/qconfig file (or its object class equivalent) appropriately and set up a spooler queue on the client machine.

To configure print service for a server, the **mkprtsv** command does the following:

- 1. Calls the **ruser** command to set up remote users to print on the server.
- 2. Calls the **mkque** and **mkquedev** commands to change the server's **/etc/lpd/qconfig** file appropriately and set up the necessary device queues on the server machine.
- 3. Calls the **startsrc** command to activate the **lpd** and **gdaemon** server daemons. The **gdaemon** server daemon starts the **piobe** printer backend.

Flags

-A FileName Specifies name of file containing entries related to the **qconfig** file. -a "Attribute = Value..."

Specifies a list of attributes and their corresponding values to be used for updating the spooler's qconfig file or object class. The -a flag is optional. Valid attribute types are listed below:

acctfile (true/false)

Identifies the file used to save print command accounting information. The default value of false suppresses accounting. If the named file does not exist, no accounting is done.

argname

Specifies the logical printer name.

device Identifies the symbolic name that refers to the device stanza.

discipline

Defines the queue-serving algorithm. The default value of fcfs means first come, first served. A sin value means shortest job next.

pserver

Specifies the remote print server.

up (true/false)

Defines the state of the queue. The default value of true indicates that it is running. A false value indicates that it is not.

-b "Attribute = Value..."

Specifies a list of attributes and their corresponding values to be used for updating the spooler's **qconfig** file or object class. At least one attribute must be defined for the **-b** option. The **backend** attribute is required. Valid attribute types are listed below:

access (true/false)

Specifies the type of access the backend has to the file specified by the **file** attribute. The **access** attribute has a value of **write** if the backend has write access to the file, or a value of **both** if the backend has both read and write access. This field is ignored if the file field has a value of **false**.

align (true/false)

Specifies whether the backend sends a form-feed control before starting the job if the printer has been idle. The default value is **false**.

backend

Specifies the full path name of the backend, optionally followed by flags and parameters to be passed to it. The **backend** attribute is required.

feed Specifies the number of separator pages to print when the device becomes idle, or takes a **never** value, which indicates that the backend is not to print separator pages.

file Identifies the special file where the output of the backend is to be redirected. The default value of **false** indicates no redirection. In this case, the backend opens the output file.

header (never/always/group)

Specifies whether a header page prints before each job or group of jobs. The default value of **never** indicates no header page. To produce a header page before each job, specify an **always** value. To produce a header before each group of jobs for the same user, specify a **group** value.

trailer (never/always/group)

Specifies whether a trailer page prints after each job or group of jobs. The default value of **never** indicates no trailer page. To produce a trailer page after each job, specify an **always** value. To produce a trailer after each group of jobs for the same user, specify a **group** value.

host Specifies the host name from which to print.

s_statfilter

Translates short queue-status information to a format recognized by this operating system.

l_statfilter

Translates long queue-status information to a format recognized by this operating system.

Performs print service configuration for a client machine. Use the **-q** flag with the **-c** option.

Specifies the name of a file containing a list of host names.

-h "HostName..." Specifies a list of host names to be included in the list of remote users who can use

the print server. The queuing system does not support multibyte host names.

Specifies the name of a queue in the **qconfig** file.

Starts print service after it is configured. If the -S flag is omitted, print service is

configured but not started.

Performs print service configuration for a server machine. Use the -h, -H, and -q flags

with the -s flag.

-v DeviceName Specifies the name of the device stanza in the qconfig file.

Examples

-C

-S

-s

-H FileName

-q QueueName

1. To configure and enable print service for a client, enter the command in the following format:

```
mkprtsv -c -S -a"argname=rp1 backend=piobe \
pserver=print802"
```

In this example, rp1 is the logical printer name, piobe is the printer backend, and print802 is the remote print server.

2. To configure a print server using initialization information and allow remote printing, enter the command in the following format:

```
mkprtsv -s -H hnames -A ginfo
```

In this example, attribute information stored in the ginfo file initializes the spooler, and the list of host names stored in the hnames file is the list of remote hosts that have access rights to the print server.

Files

/etc/lpd/qconfig

Contains configuration information for the printer queuing system.

Related Information

The **mkque** command, **mkquedev** command, **qadm** command, **ruser** command, **startsrc** command.

The **lpd** daemon, **qdaemon** daemon.

TCP/IP daemons in Networks and communication management.

mkps Command

Purpose

Adds an additional paging space.

Syntax

To Add a Logical Volume for Additional Paging Space

mkps [-t | v | [ps_helper psname]] [-a] [-n] [-c ChksumSize]-s LogicalPartitions VolumeGroup [PhysicalVolume]

To Add Additional Paging Space On an NFS Server

mkps [-a] [-n] -t nfs ServerHostName ServerFileName

Description

The **mkps** command adds an additional paging space. Before the paging space can be used it must be activated, using the **swapon** command. The *VolumeGroup* parameter specifies the volume group within which the logical volume for the paging space is to be made. The *PhysicalVolume* parameter specifies the physical volume of the VolumeGroup on which the logical volume is to be made.

Note: There is a paging space limit of 64 GB per device.

In the second form of the mkps command, the ServerHostName parameter specifies the NFS server where the ServerFileName resides. The ServerFileName specifies the file which will be used for the NFS paging of the system. The ServerFileName file must exist and be exported correctly to the client that will use the file for paging.

If the -t flag is specified, the argument will be assumed to be a third-party helper executable. If the helper executable is present in the /sbin/helpers/pagespace path then it will be spawned passing all the arguments and with the -m flag to specify mkps command. An entry will be added into /etc/swapspaces path if the helper executable returns zero. In this case, if psname starts with /, it is considered to be absolute path of device entry, or else /dev is prepended to the psname. The helper executable must take care of creating the device, making it pageable and adding an entry into ODM. If the helper program doesn't exist in the /sbin/helpers/pagespace directory the mkps command will display the usage error. The helper executable must exit with a 0 if successful and a non-zero if it fails.

You can use the File Systems application in Web-based System Manager (wsm) to change file system characteristics. You could also use the System Management Interface

Flags

-a	opecines that the paging space is configured at subsequent restarts.	
-c	Specifies the size of the checksum to use for the paging space, in bits. Valid options are 0 (checksum disabled), 8, 16 and 32. If -c is not specified it will default to 0.	
-n	Activates the paging space immediately.	
-s LogicalPartitions	Specifies the size of the paging space and the logical volume to be made in logical partitions.	
-t	Specifies the type of paging space to be created. One of the following variables is required:	
	Iv Specifies that a paging space of type logical volume should be created on the system.	
	nfs Specifies that a paging space of type NFS should be created on the system.	
	<pre>ps_helper Name of the helper program for a third party device.</pre>	

psname

Name of the device entry for paging space.

Specifies that the paging space is configured at subsequent restarts

Examples

1. To create a paging space in volume group myvg that has four logical partitions and is activated immediately and at all subsequent system restarts, enter:

```
mkps - a - n - s4 myvq
```

2. To create an NFS paging space on the NFS server swapserve where the host swapserve has the /export/swap/swapclient file exported, enter:

mkps -t nfs swapserve /export/swap/swapclient

3. To create a paging space myps using helper executable foo:

mkps -t foo /dev/myps -s1 myvg mydisk

Files

/etc/swapspaces

Specifies the paging space devices that are activated by the swapon -a command.

Related Information

The chps command, Isps command, rmps command, mklv command, swap command, swapon command, swapoff command.

Paging space in Operating system and device management.

Logical volume storage in Operating system and device management.

File systems in Operating system and device management.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

The system management interface tool in Operating system and device management.

mkqos Command

Purpose

Configures the system to support QoS.

Syntax

/usr/sbin/mkqos [-I | -N | -B]

Description

The **mkqos** command configures the system to support Quality of Service (QoS).

Flags

-В	Adds an entry to the inittab file to execute the /etc/rc.qos
	file now and on the next system restart. This flag is the default.
-I	Adds an entry to the inttab file to execute the /etc/rc.qos
	file on the next system restart.
-N	Executes the /etc/rc.qos file to start the QoS daemons.
	When invoked in this way, the QoS daemons run until the

next system restart.

Files

inittab Controls the initialization process of the system.
/etc/rc.qos Contains the startup script for the QoS daemons.

Related Information

The **rmqos** command.

QoS installation and TCP/IP Quality of Service in the Networks and communication management.

mkque Command

Purpose

Adds a printer queue to the system.

Syntax

```
mkque [ -D ] -q Name [ -a 'Attribute = Value' ... ]
```

Description

The **mkque** command adds a printer queue to the system by adding the stanza described on the command line to the end of the /etc/qconfig file.

You can use the Printer Queues application in Web-based System Manager (wsm) to change printer characteristics. You could also use the System Management Interface Tool (SMIT) smit mkque fast path to run this command.

To use the SMIT fast path to go directly to the Add a Local Queue dialog, enter: smit mklque

To use the SMIT fast path to go directly to the Add a Remote Queue dialog, enter: smit mkrque

Recommendation: To edit the /etc/qconfig file, use the chque, mkque, rmque, chquedev, mkquedev, and **rmquedev** commands or SMIT. Further, it is recommended to run these commands during slow or off-peak time.

If manual editing of the /etc/qconfig file is necessary, you can first issue the eng -G command to bring the queuing system and the **qdaemon** to a halt after all jobs are processed. Then you can edit the /etc/qconfig file and restart the qdaemon with the new configuration.

Flags

-D

-q Name

-a 'Attribute = Value'	Specifies a line to be added to the queue stanza in the /etc/qconfig file.
	This flag must be the last flag when entering the mkque command on the

command line. For a list of all valid attributes, see the /etc/qconfig file.

Note: It is recommended that you do not use the 'device = ' attribute. This attribute is handled automatically by the mkquedev command. Also note that the queuing system does not support multibyte host names.

Specifies that the queue defined by the Name variable queue is added to the top of the /etc/qconfig file and is therefore the default queue. If you do not specify this flag, the Name variable is added to the bottom of the

/etc/qconfig file and is not the default queue. Specifies the name of the gueue to be added.

Note: The queue name must not exceed 20 characters.

Examples

To add the print queue 1p0 specifying a host name of 1eo and a remote print queue named 1p013, enter:

mkque -qlp0 -a 'host = leo' -a 'rq = lp013'

Files

/usr/bin/mkque Contains the mkque command.

/etc/qconfig Configuration file.

Related Information

The chque command, Isque command, mkquedev command, rmque command.

The **gconfig** file.

Printing administration in the Printers and printing.

Print spooler in the Printers and printing.

Printer-specific information in the *Printers and printing*.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

Installing support for additional printers in the Printers and printing.

mkquedev Command

Purpose

Adds a printer queue device to the system.

Syntax

mkquedev -d Name -q Name -a 'Attribute = Value' ...

Description

The **mkquedev** command adds a printer queue device to the system by adding the stanza described on the command line to the **/etc/qconfig** file.

You can use the Printer Queues application in Web-based System Manager (wsm) to change printer characteristics. You could also use the System Management Interface Tool (SMIT) **smit mkquedev** fast path to run this command.

Recommendation: To edit the **/etc/qconfig** file, use the **chque**, **mkque**, **rmque**, **chquedev**, **mkquedev**, and **rmquedev** commands or SMIT. Further, it is recommended to run these commands during slow or off-peak time.

If manual editing of the **/etc/qconfig** file is necessary, you can first issue the **enq -G** command to bring the queuing system and the **qdaemon** to a halt after all jobs are processed. Then you can edit the **/etc/qconfig** file and restart the **qdaemon** with the new configuration.

Flags

-a 'Attribute = Value'

Specifies the 'Attribute = Value' attribute to be added to the device stanza in the /etc/qconfig file. This flag must be the last flag when entering the mkquedev command on the command line. For a list of valid attributes, see the /etc/qconfig file.

Note: The 'backend = ' attribute must be included when entering this command on the command line.

Specifies with the *Name* variable the name of the queue device to add.

Note: The queue device name must not exceed 20 characters. Specifies with the *Name* variable the name of the queue (this name must already exist) to which the queue device is added. The **mkquedev** command automatically adds the 'device = ' attribute to the specified queue stanza.

-d Name

-q Name

Examples

To add the postscript print queue device to the 1p0 queue, specify the backend program to be the piobe command (backend = /usr/lib/lpd/piobe) and direct the backend program not to align the paper (align = FALSE), enter:

```
mkquedev -qlp0 -dpostscript -a 'backend = /usr/lib/lpd/piobe' \
 -a 'align = FALSE'
```

Files

/usr/bin/mkguedev Contains the **mkquedev** command. /etc/qconfig Contains the configuration file.

Related Information

The **chquedev** command, **Isquedev** command, **mkque** command, **rmquedev** command.

The /etc/qconfig file.

Printing administration in the Printers and printing.

Print spooler in the Printers and printing.

Adding a print queue device in the *Printers and printing*.

Installing support for additional printers in the Printers and printing.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

mkramdisk Command

Purpose

Creates a RAM disk using a portion of RAM that is accessed through normal reads and writes.

Syntax

mkramdisk [-u] size[M | G]

Description

The mkramdisk command is shipped as part of bos.rte.filesystems, which allows the user to create a RAM disk. Upon successful execution of the mkramdisk command, a new RAM disk is created, a new entry added to /dev, the name of the new RAM disk is written to standard output, and the command exits with a value of 0. If the creation of the RAM disk fails, the command prints an internalized error message, and the command will exit with a nonzero value.

The size can be specified in terms of MB or GB. By default, it is in 512 byte blocks. A suffix of M will be used to specify size in megabytes and G to specify size in gigabytes.

The names of the RAM disks are in the form of /dev/rramdiskx where x is the logical RAM disk number (0 through 63).

The **mkramdisk** command also creates block special device entries (for example, **/dev/ramdisk5**) although use of the block device interface is discouraged because it adds overhead. The device special files in **/dev** are owned by root with a mode of 600. However, the mode, owner, and group ID can be changed using normal system commands.

Up to 64 RAM disks can be created.

Note: The size of a RAM disk cannot be changed after it is created.

The **mkramdisk** command is responsible for generating a major number, loading the ram disk kernel extension, configuring the kernel extension, creating a ram disk, and creating the device special files in **/dev**. Once the device special files are created, they can be used just like any other device special files through normal **open**, **read**, **write**, and **close** system calls.

RAM disks can be removed by using the **rmramdisk** command. RAM disks are also removed when the machine is rebooted.

By default, RAM disk pages are pinned. Use the -u flag to create RAM disk pages that are not pinned.

Flags

size

Specifies that the ram disk that is created will not be pinned. By default, the ram disk will be pinned.

Parameters

Indicates the amount of RAM (in 512 byte increments) to use for the new RAM disk. For example, typing:

creates a RAM disk that uses 512 bytes of RAM. To create a RAM disk that uses approximately 20 MB of RAM, type:

mkramdisk 40000

Exit Status

The following exit values are returned:

Successful completion.

>0 An error occurred.

Examples

1. To create a new ram disk using a default 512-byte block size, and the size is 500 MBs (1048576 * 512), enter:

mkramdisk 1048576 /dev/rramdisk0

The /dev/rramdisk0 ramdisk is created.

2. To create a new ramdisk with a size of 500 Megabytes, enter:

mkramdisk 500M /dev/rramdisk0

The /dev/rramdisk0 ramdisk is created. Note that the ramdisk has the same size as example 1 above.

3. To create a new ram disk with a 2-Gigabyte size, enter:

mkramdisk 2G /dev/rramdisk0 4. To set up a RAM disk that is approximately 20 MB in size and create a JFS file system on that RAM disk, enter the following:

```
mkramdisk 40000
ls -1 /dev | grep ram
mkfs -V jfs /dev/ramdiskx
mkdir /ramdisk0
mount -V jfs -o nointegrity /dev/ramdiskx /ramdiskx
```

where x is the logical RAM disk number.

For using RAM file system on JFS2, where nointegrity is not supported by the mount command, the example is as follows:

```
mkramdisk 40000
ls -1 /dev | grep ram
/sbin/helpers/jfs2/mkfs -V jfs2 -o log=INLINE /dev/ramdiskx
mkdir /ramdiskx
mount -V jfs2 -o log=/dev/ramdiskx /dev/ramdiskx /ramdiskx
```

where x is the logical RAM disk number.

Note: If using file system on a RAM disk, the RAM disk must be pinned.

Files

/usr/sbin/mkramdisk Contains the mkramdisk command.

Related Information

The **rmramdisk** command.

mkresponse Command

Purpose

Creates a new response definition.

Syntax

To create a response with no actions:

```
mkresponse [-p node_name] [-h] [-TV] response
```

To create a response with one action:

```
mkresponse -n action [-d days_of_week[,days_of_week...]]
[-t time_of_day[,time_of_day...]] -s action_script [-r return_code]
[-e a | r | b ] [-o] [-E env_var=value[,env_var=value...]]
[-u] [-p node_name] [-h] [-TV] response
```

To copy a response:

mkresponse -c existing_response[:node_name] [-p node_name] [-h] [-TV] response

Description

The **mkresponse** command creates a new response definition with the name specified by the *response* parameter. One action can also be specified when the response is defined. Actions define commands to be run when the response is used with a condition and the condition occurs. The action defines days of

the week when the action can be used, the time of day for those days of the week, the script or command to be run, what type of event causes the command to be run, the expected return code of the script or command, and whether to keep standard output. The days and times are paired so that different times can be specified for different days. A response with no actions only logs the events.

In a cluster environment, use the -p flag to specify the node in the domain that is to contain the response definition. If you are using mkresponse on the management server and you want the response to be defined on the management server, do not specify the -p flag. If the -p flag is not specified, the response is defined on the local node.

The **chresponse** command can be used to add actions to a response or to remove actions from a response. Monitoring can be started by using the startcondresp command. The startcondresp command links a response to a condition if they are not already linked.

To lock a response so it cannot be modified or removed, use the **chresponse** command (with its **-L** flag).

Flags

-c existing response[:node name]

Copies an existing response. Links with conditions are not copied. The existing response is defined on the node known as node_name in a cluster. If node_name is not specified, the local node is used. node_name is a node within the scope determined by the CT_MANAGEMENT_SCOPE environment variable. If any other flags are specified, update the new response as indicated by the flags.

-n action

Specifies the name of the action being defined. Only one action can be defined when the response is created. Use the chresponse command to add more actions to the response.

-d days of week

Specifies the days of the week when the action being defined can be run. days of week and time of day together define the interval when the action can be run.

Enter the numbers of the days separated by a plus sign (+) or as a range of days separated by a hyphen (-). More than one days_of_week parameter can be specified, but the parameters must be separated by a comma (,). The number of days of week parameters specified must match the number of time of day parameters specified. The default is all days. If no value is specified but a comma is entered, the default value is used. The values for each day follow:

- 1 Sunday
- 2 Monday
- 3 Tuesday
- 4 Wednesday
- 5 Thursday
- 6 Friday
- 7 Saturday

-t time_of_day

Specifies the time range when action can be run, consisting of the start time followed by the end time, separated by a hyphen. days_of_week and time_of_day together define the interval when the action can be run.

The time is in 24-hour format (HHMM) where the first two digits represent the hour and the last two digits represent the minutes. The start time must be less than the end time because the time is specified by day of the week. More than one time of day parameter can be specified, but the parameters must be separated by a comma (,). The number of days_of_week parameters specified must match the number of time of day parameters specified. The default value is 0000-2400. If no value is specified but a comma is entered, the default value is used.

-s action script

Specifies the fully-qualified path for the script or command to run for the action being defined. See the logevent, notifyevent, and wallevent commands for descriptions of the predefined response scripts provided with the application.

-r return code

Specifies the expected return code for action_script. If the expected return code is specified, the actual return code of action_script is compared to the expected return code. A message is written to the audit log indicating whether they match. If the -r flag is not specified, the actual return code is written to the audit log, and no comparison is performed.

-e a | r | b

Specifies the type of event that causes the action being defined to run:

- Event. This is the default.
- Rearm event. r
- Both event and rearm event.
- Directs all standard output from action script to the audit log. The default is not to keep standard -0 output. Standard error is always directed to the audit log.

-E env_var=value[,env_var=value...]

Specifies any environment variables to be set before running the action. If multiple env var=value variables are specified, they must be separated by commas.

-u Specifies that the action is to be run when a monitored resource becomes undefined.

-p node_name

Specifies the name of the node where the response is defined. This is used in a cluster environment and the node name is the name by which the node is known in the domain. The default node name is the local node on which the command runs, node name is a node within the scope determined by the CT MANAGEMENT SCOPE environment variable.

If you are using mkresponse on the management server and you want the response to be defined on the management server, do not specify the -p flag.

- -h Writes the command's usage statement to standard output.
- -TWrites the command's trace messages to standard error. For your software service organization's use only.
- -V Writes the command's verbose messages to standard output.

Parameters

response

The response name is a character string that identifies the response. If the name contains spaces, it must be enclosed in quotation marks. A name cannot consist of all spaces, be null, or contain embedded double quotation marks.

Security

The user needs write permission for the **IBM.EventResponse** resource class to run **mkresponse**. Permissions are specified in the access control list (ACL) file on the contacted system. See the RSCT: Administration Guide for details on the ACL file and how to modify it.

Exit Status

- The command ran successfully.
- 1 An error occurred with RMC.
- 2 An error occurred with a command-line interface script.

- 3 An incorrect flag was entered on the command line.
- 4 An incorrect parameter was entered on the command line.
- 5 An error occurred that was based on incorrect command-line input.

Environment Variables

CT CONTACT

Determines the system where the session with the resource monitoring and control (RMC) daemon occurs. When CT_CONTACT is set to a host name or IP address, the command contacts the RMC daemon on the specified host. If CT CONTACT is not set, the command contacts the RMC daemon on the local system where the command is being run. The target of the RMC daemon session and the management scope determine the resource classes or resources that are processed.

CT_IP_AUTHENT

When the CT_IP_AUTHENT environment variable exists, the RMC daemon uses IP-based network authentication to contact the RMC daemon on the system that is specified by the IP address to which the CT_CONTACT environment variable is set. CT_IP_AUTHENT only has meaning if CT_CONTACT is set to an IP address; it does not rely on the domain name system (DNS) service.

CT_MANAGEMENT_SCOPE

Determines the management scope that is used for the session with the RMC daemon in processing the resources of the event-response resource manager (ERRM). The management scope determines the set of possible target nodes where the resources can be processed. The valid values are:

- 0 Specifies local scope.
- 1 Specifies local scope.
- 2 Specifies peer domain scope.
- Specifies management domain scope.

If this environment variable is *not* set, *local* scope is used.

Implementation Specifics

This command is part of the Reliable Scalable Cluster Technology (RSCT) fileset for AIX.

Standard Output

When the -h flag is specified, this command's usage statement is written to standard output. All verbose messages are written to standard output.

Standard Error

All trace messages are written to standard error.

Examples

These examples apply to standalone systems:

- 1. To define a response with the name "Log event in audit log", run this command: mkresponse "Log event in audit log"
- 2. To define a response with the name "E-mail root anytime" that has an action named "E-mail root", to be used any time Saturday and Sunday and uses the command /usr/sbin/rsct/bin/notifyevent root for both events and rearm events, run this command:

```
mkresponse -n "E-mail root" -d 1+7 \ -s "/usr/sbin/rsct/bin/notifyevent root" -e b \ "E-mail root anytime"
```

3. To define a response with the name "E-mail root anytime" that has an action named "E-mail root", to be used anytime Saturday and Sunday but only 8 am to 5 pm Monday through Friday and that uses the command /usr/sbin/rsct/bin/notifyevent root for events, run this command:

```
mkresponse -n "E-mail root" \
-d 1+7,2-6 -t 0000-2400,0800-1700 \
-s "/usr/sbin/rsct/bin/notifyevent root" -e a \
"E-mail root anytime"
```

4. To define a response with the name "E-mail root anytime" that has an action named "E-mail root" to be used any time Saturday and Sunday, that uses the command /usr/sbin/rsct/bin/notifyevent root for both events and rearm events, and that sets the environment variable LANG to en_US, run this command:

```
mkresponse -n "E-mail root" -d 1+7 \
-s "/usr/sbin/rsct/bin/notifyevent root" -e b \
-E LANG="en US" "E-mail root anytime"
```

5. To define a response with the name "E-mail root first shift" that has an action named "E-mail root" to be used Monday through Friday from 8 am to 6 pm, that uses the command /usr/sbin/rsct/bin/notifyevent root for rearm events, and that saves standard output in the audit log, expecting return code 5, run this command:

```
mkresponse -n "E-mail root" -d 2-6 -t 0800-1800 \ -s "/usr/sbin/rsct/bin/notifyevent root" -e r -o \ -r 5 "E-mail root first shift"
```

6. To define a response with the name "Critical notifications" as a copy of "Warning notifications", enter: mkresponse -c "Warning notifications" "Critical notifications"

These examples apply to management domains:

1. To define a response on the management server with the name "E-mail root anytime" that has an action named "E-mail root", to be used any time Saturday and Sunday and uses the command /usr/sbin/rsct/bin/notifyevent root for both events and rearm events, run this command on the management server:

```
mkresponse -n "E-mail root" -d 1+7 \
-s "/usr/sbin/rsct/bin/notifyevent root" -e b \
"E-mail root anytime"
```

2. To define a response on the managed node **nodeB** with the name "E-mail root anytime" that has an action named "E-mail root", to be used any time Saturday and Sunday and uses the command /usr/sbin/rsct/bin/notifyevent root for both events and rearm events, run this command on the management server:

```
mkresponse -n "E-mail root" -d 1+7 \
-s "/usr/sbin/rsct/bin/notifyevent root" -e b \
-p nodeB "E-mail root anytime"
```

3. To define a response on the managed node **nodeB** with the name "nodeB Warning notifications" as a copy of "nodeA Warning notifications" on the managed node **nodeA**, run this command on the management server:

```
mkresponse -c "nodeA Warning notifications":nodeA \
-p nodeB "nodeB Warning notifications"
```

These examples apply to peer domains:

1. To define a response on the current node with the name "E-mail root anytime" that has an action named "E-mail root", to be used any time Saturday and Sunday and uses the command /usr/sbin/rsct/bin/notifyevent root for both events and rearm events, run this command from any node in the domain:

```
mkresponse -n "E-mail root" -d 1+7 \
-s "/usr/sbin/rsct/bin/notifyevent root" -e b \
"E-mail root anytime"
```

2. To define a response on the node **nodeB** in the domain with the name "E-mail root anytime" that has an action named "E-mail root", to be used any time Saturday and Sunday, that uses the command /usr/sbin/rsct/bin/notifyevent root for both events and rearm events, and that sets two environment variables (PAGE ALL and TIMER SET), run this command from any node in the domain:

```
mkresponse -n "E-mail root" -d 1+7 \
-s "/usr/sbin/rsct/bin/notifyevent root" -e b \
-p nodeB -E 'ENV1="PAGE ALL", ENV2="TIMER SET"' \
"E-mail root anytime"
```

3. To define a response on the node **nodeB** in the domain with the name "nodeB Warning notifications" as a copy of "nodeA Warning notifications" on the node **nodeA** in the domain, run this command from any node in the domain:

```
mkresponse -c "nodeA Warning notifications":nodeA \
-p nodeB "nodeB Warning notifications"
```

Location

/usr/sbin/rsct/bin/mkresponse

Related Information

Books: RSCT: Administration Guide, for more information about ERRM operations

Commands: chresponse, Isresponse, mkcondition, mkcondresp, rmresponse, startcondresp

Information Files: rmccli

mkrole Command

Purpose

Creates new roles. This command applies only to AIX 4.2.1 and later.

Syntax

mkrole [Attribute=Value ...] Name

Description

The **mkrole** command creates a new role. The *Name* parameter must be a unique role name. You cannot use the **ALL** or **default** keywords as the role name.

You can use the Users application in Web-based System Manager to change user characteristics. You could also use the System Management Interface Tool (SMIT) to run this command.

Restrictions on Creating Role Names

To prevent inconsistencies, restrict role names to characters with the POSIX portable filename character set. You cannot use the keywords **ALL** or **default** as a role name. Additionally, do not use any of the following characters within a role-name string:

- : Colon
- Double quotation mark

#

. Comma

- Equal sign
- Backslash
- Slash
- ? Question mark
- Single quotation mark
- Back quotation mark

Finally, the Name parameter cannot contain any space, tab, or new-line characters.

Restrictions on Creating Roles

To ensure the integrity of the role information, only users with the RoleAdmin authorization can create a role.

Parameters

Attribute=Value Initializes a role attribute. Refer to the chrole command for the valid attributes and

values.

Security

Files Accessed:

Mode File

/etc/security/roles rw /etc/security/user.roles

Auditing Events:

Event Information

ROLE_Create role

Examples

To create the ManageObjects role and set the **groups** attribute to objects, type: mkrole groups=objects ManageObjects

Files

/etc/security/roles Contains the attributes of roles. /etc/security/user.roles Contains the role attribute of users.

Related Information

The chrole command, chuser command, Isrole command, Isuser command, mkuser command, rmrole command.

For more information about the identification and authentication of users, discretionary access control, the trusted computing base, and auditing, refer to the Security.

Administrative roles in Security.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

mkrpdomain Command

Purpose

Creates a new peer domain definition.

Syntax

To create a peer domain definition...

- · ...by specifying node names on the command line: mkrpdomain [-t TS_port] [-g GS_port] [-Q quorum_type | quorum_type_name] [-c] [-m fanout] [-k cssk_type [-r refresh_interval]] [-h] [-TV] peer_domain node_name1 [node_name2 ...]
- ...using a list of node names in an input file: mkrpdomain -f | -F { file_name | "-" } [-t TS_port] [-g GS_port] [-Q {quorum_type | quorum type name}] [-c] [-m fanout] [-k cssk type [-r refresh interval]] [-h] [-TV] peer domain

Description

The mkrpdomain command creates a new peer domain definition with the name specified by the peer domain parameter. The nodes specified by node name are defined to the new peer domain. A peer domain can be used to provide high-availability services when configuring application and system resources.

The **preprpnode** command must have been run on each of the nodes to be defined to the peer domain. The preprpnode command prepares the security environment for the peer domain operations. See the preprpnode command for more information about peer domain definition requirements. Only those nodes that have the appropriate security setup will be successfully defined to the peer domain.

If the UDP port numbers for group services and topology services are not available on all of the nodes to be defined to the peer domain, the mkrpdomain command will fail. The command will also fail if the peer domain name is already being used or if any node cannot be successfully defined to the peer domain. Use the -c flag to enable mkrpdomain to continue when there is an error on one of the nodes.

The peer domain quorum rules can be modified using the -Q flag. The quorum rules determine under what conditions operational changes, such as starting or stopping resources, and configuration changes, such as adding or removing a node, can be made. Start-up quorum defines how many nodes are contacted to get configuration information to start the peer domain. In a typical environment, two guorum rule types are used: **normal** and **quick**. For the **quick** quorum type, only one node is contacted before starting the peer domain. Operational and configuration quorum rules are the same. To see what quorum rule types are available on a node, run:

lsrsrc -c IBM.PeerDomain AvailableQuorumTypes

If you are running RSCT 2.4.7.1 or later, you can use the -k flag to set the cluster shared secret key (CSSK). The CSSK is used for message authentication in the peer domain. By default, the CSSK is disabled (that is, set to CSSKTYPE_None). To enable message authentication, use a CSSK value such as CSSKTYPE DES MD5 with the -k flag. Enabling message authentication will affect performance. The complexity of the encryption algorithm determines the effect.

Message authentication also requires that the time-of-day clocks (TODs) of the nodes in the peer domain are synchronized — according to the system time — to within two minutes of each other. When the nodes' TODs are synchronized across the peer domain, this function helps to defend against message replay attacks. If the nodes' TODs are not synchronized to within two minutes of each other, messages passed between a sending node and a receiving node with a time difference that is longer than two minutes will be discarded.

When message authentication is enabled using the -k flag, a key refresh interval can be specified using the -r flag. By default, the key is refreshed daily.

To change the CSSK type for a peer domain, use the **chrsrc** command. For example:

chrsrc -c IBM.RSCTParameters CSSKType=cssk type

To list the CSSK type that is used for an online peer domain, use the Isrsrc command. For example:

lsrsrc -c IBM.RSCTParameters CSSKType

To cause the CSSK to be refreshed, use the **runact** command. For example:

runact -c IBM.PeerDomain UpdateKey

For information about setting up and managing CSSK settings, see the RSCT: Administration Guide.

The mkrpdomain command does not bring the peer domain online automatically. To bring the peer domain online, run the startrpdomain command. You can add nodes to the peer domain using the addrpnode command. To remove nodes from the peer domain, use the rmrpnode command.

A node can be defined in more than one peer domain but it can be online in only one peer domain at a time.

Flags

-t TS port

Specifies the topology services port number. This UDP port is used for daemon-to-daemon communication. Any unused port in the range 1024 to 65535 can be assigned. The command will fail if the specified port is unavailable. The default is 12347.

-q GS port

Specifies the group services port number. This UDP port is for daemon-to-daemon communication. Any unused port in the range 1024 to 65535 can be assigned. The command will fail if the specified port is unavailable. The default is 12348.

Continues to run the **mkrpdomain** command on the remaining nodes. -c

> By default, if the **mkrpdomain** command fails on any node, it will fail on all nodes. The **-c** flag overrides this behavior, so that the **mkrpdomain** command will run on the other nodes, even if it fails on one node.

-Q quorum_type | quorum_type_name

Specifies the quorum rules that are used for start-up, operational, and configuration quorum. Start-up quorum defines how many nodes are contacted to obtain configuration information before starting the peer domain. Operational guorum defines how many nodes must be online in order to start and stop resources and how tie breaking is used. Configuration quorum defines how many nodes must be online to make changes to the peer domain (adding or removing a node, for example). To see what quorum rule types are available on a node, run:

lsrsrc -c IBM.PeerDomain AvailableQuorumTypes

The valid values are:

0 | normal

Specifies normal quorum rules. This is the default. For start-up quorum, at least half of the nodes will be contacted for configuration information. For configuration quorum, more than half of the nodes must be online to make configuration changes. For operational quorum, the cluster or subcluster must have a majority of the nodes in the peer domain. If a tie exists between subclusters, the subcluster that holds the tiebreaker has operational quorum.

1 | quick

Specifies quick quorum rules. For start-up quorum, even if no other nodes can be contacted, the node will still come online. For configuration quorum, more than half of the nodes must be online to make configuration changes. For operational quorum, the cluster or subcluster must have a majority of the nodes in the peer domain. If a tie exists between subclusters, the subcluster that holds the tiebreaker has operational quorum.

-m fanout

Specifies the maximum number of threads to use in parallel operations for the specified peer domain. This value is stored as a persistent attribute in the peer domain's IBM.PeerNode class. fanout can be an integer from 16 to 2048. If this flag is not specified, the default value (128) is used.

-f | -F { *file_name* | "-" }

Reads a list of node names from file_name. Each line of the file is scanned for one node name. The pound sign (#) indicates that the remainder of the line (or the entire line if the # is in column 1) is a comment.

Use **-f** "-" or **-F** "-" to specify **STDIN** as the input file.

-k cssk type

Specifies the cluster shared secret key (CSSK) to be used for message authentication in the peer domain. Use the CSSK that best suits your applications in terms of the degree of data protection, overhead, and performance. The longer the key, the stronger the encryption algorithm. The stronger the algorithm, the slower the performance. The valid key types are:

CSSKTYPE None

Indicates that message authentication is disabled. This is the default.

CSSKTYPE DES MD5

Indicates that a Data Encryption Standard (DES) key with the message digest function MD5 is used to generate a 16-byte signature. This CSSK is recommended if a high degree of data protection is not required and if you want good performance with less data overhead.

CSSKTYPE_3DES_MD5

Indicates that a triple DES key with an MD5 digest is used to generate a 16-byte signature. Compared to CSSKTYPE_DES_MD5, this CSSK provides added data protection with slower performance, but with the same data overhead.

CSSKTYPE_AES256_MD5

Indicates that an Advanced Encryption Standard (AES) 256-bit key with an MD5 digest is used to generate a 24-bit signature. This CSSK provides the most data protection, but with slower performance and more data overhead.

You must be running RSCT 2.4.7.1 or later to use this flag.

-r refresh interval

Specifies the CSSK refresh interval when message authentication is enabled in the peer domain. This is the interval at which the CSSK is refreshed. The format of refresh interval is: dd:hh:mm:ss, where dd is the number of days between key refreshes, hh is the number of hours, mm is the number of minutes, and ss is the number of seconds. The refresh interval value can be truncated on the right, so -r 5 means refresh every 5 days and -r 0:12 means refresh every 12 hours.

The default refresh interval is one day. The minimum refresh interval is 30 seconds. The maximum refresh interval is 30 days.

The **-r** flag can only be specified when the **-k** flag is used.

You must be running RSCT 2.4.7.1 or later to use this flag.

-h Writes the command's usage statement to standard output.

- -T Writes the command's trace messages to standard error. For your software service organization's
- -V Writes the command's verbose messages to standard output.

Parameters

peer domain

Specifies the name of the new peer domain to be created. You can only use these ASCII characters in the peer domain name: A to Z, a to z, 0 to 9, (period), and (underscore). In addition, the peer domain name cannot be IW.

node_name1 [node_name2 ...]

Specifies the node (or nodes) to include in this peer domain definition. The node name is the IP address or the long or short version of the DNS hostname. The node name must resolve to an IP address.

Security

The user of the mkrpdomain command needs write permission to the IBM.PeerDomain resource class on each node that is to be defined to the peer domain. This is set up by running the preprpnode command on each node that is to be defined to the domain, specifying the name of the node on which the user will run mkrpdomain.

Exit Status

- The command ran successfully.
- 1 An error occurred with RMC.
- 2 An error occurred with a command-line interface script.
- 3 An incorrect flag was entered on the command line.
- An incorrect parameter was entered on the command line.
- 5 An error occurred that was based on incorrect command-line input.

Environment Variables

CT_CONTACT

Determines the system where the session with the resource monitoring and control (RMC) daemon occurs. When CT_CONTACT is set to a host name or IP address, the command contacts the RMC daemon on the specified host. If CT CONTACT is not set, the command contacts the RMC daemon on the local system where the command is being run. The target of the RMC daemon session and the management scope determine the resource classes or resources that are processed.

CT_IP_AUTHENT

When the CT IP AUTHENT environment variable exists, the RMC daemon uses IP-based network authentication to contact the RMC daemon on the system that is specified by the IP address to which the CT CONTACT environment variable is set. CT IP AUTHENT only has meaning if CT_CONTACT is set to an IP address; it does not rely on the domain name system (DNS) service.

Restrictions

Any node to be defined to the peer domain must be reachable from the node on which this command runs.

Implementation Specifics

This command is part of the Reliable Scalable Cluster Technology (RSCT) fileset for AIX.

Standard Input

When the -f "-" or -F "-" flag is specified, this command reads one or more node names from standard input.

Standard Output

When the -h flag is specified, this command's usage statement is written to standard output. All verbose messages are written to standard output.

Standard Error

All trace messages are written to standard error.

Examples

1. To define a peer domain called **ApplDomain** that consists of a node called **nodeA**, run this command on nodeA:

mkrpdomain ApplDomain nodeA

2. To define a peer domain called ApplDomain that consists of three nodes called nodeA, nodeB, and **nodeC**, run this command on **nodeA**, **nodeB**, or **nodeC**:

mkrpdomain ApplDomain nodeA nodeB nodeC

3. To define a peer domain called **ApplDomain** that consists of two nodes called **nodeA** and **nodeB**, with a topology services port number of 1200 and a group services port number of 2400, run this command on nodeA or nodeB:

mkrpdomain -t 1200 -g 2400 ApplDomain nodeA nodeB

4. To define a peer domain called **ApplDomain** that consists of two nodes called **nodeA** and **nodeB** using message authentication key algorithm CSSKTYPE DES MD5, run this command on nodeA or nodeB:

mkrpdomain -k CSSKTYPE DES MD5 ApplDomain nodeA nodeB

Location

/usr/sbin/rsct/bin/mkrpdomain

Files

The /etc/services file is modified.

Related Information

Books: RSCT: Administration Guide, for information about peer domain operations, including setting up and managing CSSK settings

Commands: addrpnode, chrsrc, Isrpdomain, Isrpnode, Isrsrc, preprpnode, rmrpdomain, rmrpnode, runact, startrpdomain, stoprpdomain

Information Files: rmccli, for general information about RMC-related commands

mkrset Command

Purpose

Makes an rset containing the specified CPUs and memory regions and places it in the system registry.

Syntax

mkrset -c CPUlist [-m MEMlist] rsetname

Description

The **mkrset** command creates and places into the system registry an rset or exclusive rset (xrset) with the specified set of CPUs and/or memory regions. The rset name must not exist in the registry. The owner and group IDs of the rset will be set to the owner and group IDs of the command issuer. The rset will have read/write owner permissions and read permission for group and other. When used to create an xrset, the mkrset command changes the state of the corresponding CPUs on the system to exclusive mode. Creating an xrset requires root privilege.

Flags

- List of CPUs to be in the rset. This can be one or more CPUs or CPU ranges. -C
- List of memory regions to be in the rset. This can be one or more memory regions or ranges. -m

Parameters

rsetname

The name of the rset to be placed in the system registry. The name consists of a namespace and an rsname separated by a "/" (slash). Both the namespace and rsname may contain up to 255 characters. See the rs_registername() service for additional information about character set limits of rset names.

Security

The user must have root authority or CAP NUMA ATTACH and CAP PROPAGATE capability.

Examples

1. To make an **rset** containing CPUs 0-7 named **test/cpus0to7**, type:

```
mkrset -c 0-7 test/cpus0to7
```

2. To make an rset containing CPUs 1, 3, 5, 6, 7, 10 named test/lotsofcpus, type:

```
mkrset -c 1 3 5-7 10 test/lotsofcpus
```

Files

/usr/bin/mkrset

Contains the mkrset command.

Related Information

The attachrset, detachrset, execrset, Isrset, and rmrset commands.

mkrsrc Command

Purpose

Defines a new resource.

Syntax

To define a new resource, using data that is...

entered on the command line:

mkrsrc [-v] [-h] [-TV] resource_class attr=value...

predefined in an input file:
 mkrsrc -f resource data input file [-v] [-h] [-TV] resource class

To see examples of the **mkrsrc** command for a resource class:

mkrsrc -e [-h] [-TV] resource_class

Description

The **mkrsrc** command requests that the RMC subsystem define a new resource instance for the class specified by the *resource_class* parameter. At least one persistent attribute name and its value must be specified either as a parameter or by a resource definition file using the **-f** flag.

Before you run **mkrsrc**, you should run the **Isrsrcdef** command to determine which attributes are designated as **reqd_for_define** (required) or **option_for_define** (optional). Only attributes that are designated as **reqd_for_define** or **option_for_define** can be defined using the **mkrsrc** command. The **Isrsrcdef** command also identifies the datatype for each attribute. The value specified for each attribute must match this datatype.

To verify that all of the attribute names that are specified on the command line or in resource_data_input_file are defined as persistent attributes and are designated as reqd_for_define or option_for_define, use the -v flag. When the mkrsrc command is run with the -v flag, the resource is not defined. Instead, the resource attributes are merely verified to be persistent and designated as reqd_for_define or option_for_define. Once you have run mkrsrc -v to verify that all of the attributes that are specified on the command line or in resource_data_input_file are valid, you can issue the mkrsrc command without the -v flag to define the new resource.

Flags

- **-e** Displays examples of **mkrsrc** command-line input for:
 - 1. required attributes only
 - 2. required and optional attributes
- -f resource_data_input_file

Specifies the name of the file that contains resource attribute information.

- -v Verifies that all of the attribute names specified on the command line or in the input file are defined as persistent attributes and are designated as reqd_for_define or option_for_define. The mkrsrc command does not define any resources when you use this flag.
- **-h** Writes the command's usage statement to standard output.
- **-T** Writes the command's trace messages to standard error. For your software service organization's use only.
- **-V** Writes the command's verbose messages to standard output.

Parameters

resource class

Specifies the resource class name of the resource to be defined.

attr=value...

Specifies the attributes of the resource being defined. When defining a new resource instance, there are specific required attributes for each resource that must be defined. These attributes can be specified as parameters on the command line or defined in an input file by using the **-f** flag.

attr The name of a persistent attribute for this resource. This attribute must be designated as reqd_for_define or option_for_define. Use the Isrsrcdef command to check the designation.

value The value for this persistent attribute. The data type for this value must match the defined data type for the value of this attribute. Use the Isrsrcdef command to verify the data type for each attribute.

Security

The user needs write permission for the resource_class specified in mkrsrc to run mkrsrc. Permissions are specified in the access control list (ACL) file on the contacted system. See RSCT Administration Guide for information about the ACL file and how to modify it.

Exit Status

- The command has run successfully.
- An error occurred with RMC. 1
- 2 An error occurred with the command-line interface (CLI) script.
- An incorrect flag was specified on the command line.
- 4 An incorrect parameter was specified on the command line.
- 5 An error occurred with RMC that was based on incorrect command-line input.

Environment Variables

CT CONTACT

When the CT_CONTACT environment variable is set to a host name or IP address, the command contacts the Resource Monitoring and Control (RMC) daemon on the specified host. If the environment variable is not set, the command contacts the RMC daemon on the local system where the command is being run. The resource class or resources that are displayed or modified by the command are located on the system to which the connection is established.

CT_IP_AUTHENT

When the CT IP AUTHENT environment variable exists, the RMC daemon uses IP-based network authentication to contact the RMC daemon on the system that is specified by the IP address to which the CT_CONTACT environment variable is set. CT_IP_AUTHENT only has meaning if CT_CONTACT is set to an IP address; it does not rely on the domain name system (DNS) service.

CT MANAGEMENT SCOPE

Determines the management scope that is used for the session with the RMC daemon to monitor and control the resources and resource classes. The management scope determines the set of possible target nodes where the resources and resource classes can be monitored and controlled. The valid values are:

- Specifies local scope.
- 1 Specifies *local* scope.
- 2 Specifies peer domain scope.
- 3 Specifies management domain scope.

If this environment variable is *not* set, *local* scope is used.

Implementation Specifics

This command is part of the Reliable Scalable Cluster Technology (RSCT) fileset for AIX.

Standard Output

When the -h flag is specified, this command's usage statement is written to standard output.

The command output and all verbose messages are written to standard output.

Standard Error

All trace messages are written to standard error.

Examples

1. To create a new resource in the IBM.Host class, assuming you already know which persistent attributes are required when defining a resource of this class, enter:

```
mkrsrc IBM.Host Name=c175n05
```

2. To create a new resource in the IBM.Processor class by first generating a template to aid in the defining of these resources, enter:

```
lsrsrcdef -i IBM.Processor > /tmp/IBM.Processor.rdef
```

Then, edit the file /tmp/IBM.Processor.rdef and enter values for all of the attributes, substituting the type for an appropriate value, or leaving it blank for the default value.

Finally, enter:

```
mkrsrc -f /tmp/IBM.Processor.rdef IBM.Processor
```

3. To create two new IBM.Host resources using the information defined in file /tmp/IBM.Host.rdef, enter:

```
mkrsrc -f /tmp/IBM.Host.rdef IBM.Host
```

where the file /tmp/IBM.Host.rdef looks like this:

```
PersistentResourceAttributes::
resource 1:
   Name
                = c175n04
resource 2:
    Name
                = c175n05
```

4. This example creates a new resource in the IBM.Foo class. In this class, Name and NodeList are required attributes. The Binary, SD, StringArray, and SDArray attributes are optional. This example shows how to enter the more difficult data types from the command line. The data types for the optional attributes (Binary, SD, StringArray, and SDArray) are self-explanatory. Enter:

```
mkrsrc IBM.Foo Name=c175n05 \
NodeList=\{1\} \
Binary="0xaabbccddeeff00" \
SD='[testing123,1,{2,4,6}]' \
StringArray='{"testing 1 2 3", testing123, "testing 1 2 3"}' \
SDArray='{["testing 1 2 3",1,{1,3,5}],[testing,2,{2,4,6}]}'
```

Note: As discussed in the rmccli general information file, attribute values for certain data types (structured data, array of structured data, and arrays containing strings enclosed in double quotation marks) should be enclosed in single quotation marks.

Location

/usr/sbin/rsct/bin/mkrsrc

Related Information

Books: RSCT Administration Guide, for information about RMC operations

Commands: chrsrc, Isrsrc, Isrsrcdef, rmrsrc

Information Files:

- · resource data input
- · rmccli, for general information about RMC commands

mkseckrb5 Command

Purpose

Migrates existing operating system users to Kerberos.

Syntax

mkseckrb5 [-h | -r]

Description

This command gets the list of user names and creates Kerberos users. If the -r flag is not specified, the command prompts for a new password for each user.

Standard Output Consists of information messages when the -h flag is used.

Standard Error Consists of error messages when the command cannot complete successfully.

Flags

Specifies that the command is only to display the valid command syntax. -h

Specifies that random passwords are to be used.

Exit Status

Failure of this command to execute successfully results in incomplete migration. The admin must check the Kerberos database for the users that were migrated before taking further action.

Indicates the successful completion of the command.

1 Indicates that an error occurred.

Security

Only the root user is authorized to use this command.

Examples

1. To display the command syntax, type:

mkseckrb5 -h

2. To migrate existing users to Kerberos users, type:

3. To migrate user trojan to Kerberos user with random passwd, type:

mkseckrb5 -r trojan

Files

/usr/sbin/mkseckrb5

Contains the mkseckrb5 command.

mksecldap Command

Purpose

Sets up an AIX system as an LDAP server or client for security authentication and data management.

Syntax

The syntax to set up a server is:

mksecldap -s -a adminDN -p adminpasswd -S schematype [-d baseDN] [-n port] [-k SSLkeypath] [-w SSLkeypasswd] [-x proxyDN -X proxypasswd] [-u NONE] [-v LDAPVersion] [-U]

The syntax to set up a client is:

mksecldap -c -h serverlist -a bindDN -p bindpwd [-d baseDN] [-n serverport] [-k SSLkeypath] [-w SSLkeypasswd] [-t cachetimeout] [-C cachesize] [-P NumberofThreads] [-T heartBeatInt] [-M searchMode | [-D defaultEntry | [-A authType | [-u userlist | [-U]

Description

The mksecidap command can be used to set up IBM Directory servers and clients for security authentication and data management.

Notes:

- 1. The client (-c flag) and the server (-s flag) options cannot be used at the same time. When setting up a server, the mksecldap command might need to be run twice on that machine. Once to set up the server, and again to set up the system as a client.
- 2. The name and location of the LDAP server configuration file depends on the version of LDAP software installed. Refer to the LDAP software documentation of the installed release for more information.


Server Setup

Make sure that the LDAP server fileset is installed. When installing the LDAP server fileset, the LDAP client fileset and the backend DB2® software are automatically installed as well. No DB2 pre-configuration is required to run this command for LDAP server setup. When you run the mksecldap command to set up the server, the command will:

1. Create a DB2 instance with **Idapdb2** as the default instance name.

Note: If IBM Directory Server 5.1 or later is in use then prompts for the Idapdb2 password will appear.

- 2. If IBM Directory Server 6.0 or later is being configured then an LDAP server instance with the default name of 1dapdb2 is created. A prompt is displayed for the encryption seed to use to create the key stash files. The input encryption seed must be at least 12 characters.
- 3. Create a DB2 database with Idapdb2 as the default database name. If a database already exists, mksecldap will bypass the above two steps. (This is the case when the LDAP server has been set up for other usage.) The mksecldap command will use the existing database to store the AIX user/group data.
- 4. Create the base DN (suffix) of the directory information tree (DIT). It is required that the base DN start with one of these attributes: dc, o, ou, c, cn. If no baseDN is supplied from the command line, the default suffix is set to **cn=aixdata** and the user/group data is placed under the **cn=aixdata** DN. Otherwise, the mksecldap command uses the user-supplied DN specified with the -d option. Users and groups will be exported to LDAP using the sectoldif command. The directory information tree (DIT) that will be created by default is shown below.



- 5. If -u NONE is not specified, then export the data from the security database files from the local host into the LDAP database. If -u NONE is specified, then mksecldap does not create the ou=People and ou=Group containers as it normally would, nor does it export users and groups. Depending on the -S option, the mksecldap command exports users/groups using one of the three LDAP schemas:
 - AIX AIX schema (aixaccount and aixaccessgroup objectclasses)
 - RFC2307 RFC 2307 schema (posixaccount, shadowaccount, and posixgroup objectclasses)
 - RFC2307AIX RFC 2307 schema with full AIX support (posixaccount, shadowaccount, and posixgroup object classes, plus the aixauxaccount and aixauxgroup object classes). Attention: Systems running AIX 4.3 and AIX 5.1 which are configured as LDAP clients will only work with servers of AIX schema type. They will not talk to Idap servers of RFC2307 or RFC2307AIX types.
- 6. Set the LDAP server administrator DN and password.
- 7. Set the server to listen to a specified port if -n is used. The default port is 389 (636 for SSL).
- 8. Create the proxy entry if the -x and -X options are specified. Create an ACL for the base DN using the proxy entry. The default ACL can be found in /etc/security/ldap/proxyuser.ldif.template. The proxy entry can be used by client systems to bind to the server (see client setup section in this file).
- 9. Set the server to use SSL (secure socket layer) if the -k option is specified for secure data transfer between this server and the clients. This setup requires the GSKIT to be installed and creation of an SSL key.
- 10. Installs the /usr/ccs/lib/libsecIdapaudit.a LDAP server plug-in. This plugin supports AIX audit of the LDAP server.
- 11. Start/restart the LDAP server after all the above is done.
- 12. Add the LDAP server process (slapd) to /etc/inittab to have the LDAP server start after reboot.

Note: The -U option resets a previous setup for the server configuration file. It has no effect on the database. The first time the mksecldap command is run, it saves two copies of the server configuration file in the /etc/security/ldap directory. One is saved as the server configuration file name appended with .save.orig and the other is appended with .save. During each subsequent run of the **mksecldap** command, only the current server configuration is saved as a .save file. The undo option restores the server configuration file with the .save copy. In AIX 5.3 it is possible to invoke mksecldap -s in succession to create and populate multiple suffixes. If this has been performed then the .save.orig file will need to be manually restored in order to revert to the initial configuration file.

Client Setup

Make sure that the LDAP client fileset is installed and the LDAP server has been setup and is running. The **mksecldap** command performs the following steps during client setup:

- 1. Saves the LDAP server(s)' host name.
- 2. Saves the user base DN and group base DN of the server. If no -d option is supplied from command line, the mksecldap command searches the LDAP server for aixaccount, aixaccessgroup, posixaccount, posixgroup, and aixauxaccount object classes, and sets up the base DNs accordingly. If the server has multiple user/group bases, you must supply the -d option with a RDN® so that the mksecldap command can setup the base DNs to the ones within that RDN. If the posixaccount objectclass is found during client setup, mksecldap will also try to search for base DNs for these entities: hosts, networks, services, netgroups, protocols, and rpc from the server and save any that are found.
- 3. Determines the schema type used by the LDAP server AIX specific schema, RFC 2307 schema, RFC 2307 schema with full AIX support, or MicroSoft Services for Unix 3.0 schema. It sets the

- objectclasses and attribute maps in the /etc/security/ldap/ ldap.cfg file accordingly. The mksecldap command does not recognize other schema types, so clients must be setup manually.
- 4. Sets SSL for secure data transfer between this host and the LDAP server. This step requires that the client SSL key and the key password are created in advance, and the server must be setup to use SSL for the client SSL to work.
- 5. Encrypts the bind password.
- 6. Saves the LDAP server bind DN and password. The DN/password pair must exist on the LDAP
- 7. Sets the optionally specified configuration values as defined in the client setup flags section.
- 8. Optionally sets the list of users or all users to use LDAP by modifying their SYSTEM line in the /etc/security/user file. For more information on enabling LDAP login, see the following note.
- 9. Starts the client daemon process (secidapcintd).
- 10. Adds the client side daemon process to /etc/inittab to have this daemon start after a reboot.

Note: All client configuration data is saved to the /etc/security/ldap/ldap.cfg configuration file. The -U option resets a previous setup to the /etc/security/ldap/ldap.cfg file by replacing the file with the configuration stored in /etc/security/ldap/ldap.cfg.save. Setting the SYSTEM to LDAP for the default stanza of /etc/security/user only allows LDAP users to login to the system. Setting the SYSTEM to LDAP or compat allows both LDAP users and local users to login to the system.

Flags

-s

For Server Setup

-a AdminDN	Specifies the LDAP server administrator DN.

-d baseDN Specifies the suffix or base DN of the AIX subtree. The default is

cn=aixdata.

Specifies the full path to the SSL key database of the server. -k SSLkevpath

Specifies the port number that the LDAP server listens to. Default is 389 for -n port

non-SSL and 636 for SSL.

-p adminpasswd Specifies the clear text password for the administrator DN.

-S schematype Specifies the LDAP schema used to represent user/group entries in the

LDAP server. Valid values are AIX, RFC2307, and RFC2307AIX.

Indicates that the command is being run to setup the server.

Specifies the password for the SSL key. -w SSLkeypasswd

Specifies to undo the previous server setup to the LDAP configuration file.

The database is not affected.

Specifies not to migrate users and groups from local system. The only valid -u NONE

> value is NONE. Any other values are ignored. When this option is used, mksecldap does not create the ou-People and ou-Group containers as it normally would, nor does it export users and groups. No -S option is

required with this option.

-v LDAPVersion Denotes a specific version of the LDAP server fileset to configure. The

> value must be in the format #.# where # is a number. For example, 6.0. If not specified, the **mksecldap** command configures the most recent version

of the LDAP server fileset that is installed.

-X proxypasswd Specifies the password for the proxy DN.

Specifies the DN of the proxy entry. This entry can be used by client -x proxyDN

systems to bind to this server.

For Client Setup

-a bindDN Specifies the DN to bind to the LDAP server. The DN must exist on the LDAP server. If authtype is unix_auth, bindDN must have read access to

the userPassword field on the LDAP server.

-A authType

- -C Cachsize
- -D defaultEntryLocation
- -d baseDN
- -h serverlist
- -k SSLkeypath
- -M searchMode

- -n serverport
- -p bindpasswd
- -P NumberofTreads
- -t Cachetimeout
- -T heartBeatInt
- -u userlist
- -w SSLkeyfilepath

Specifies the authentication mechanism used to authenticate users. Valid values are unix_auth and Idap_auth. The default is unix_auth. The values are defined as follows:

- unix_auth Retrieve user password from LDAP and perform authentication locally.
- Idap_auth Bind to LDAP server, sending password in clear text, for authentication.

Note: When using Idap_auth type authentication, the use of SSL is strongly recommended since during authentication passwords will be sent in clear text to the LDAP server.

Indicates the command is being run to setup the client.

Specifies the maximum number of user entries used in the client side daemon cache. Valid values are 100-10,000 for user cache. The default value is 1,000. The group cache is 10% of that of user cache.

Specifies the location of the default entry. Valid values are **Idap** and local. The default is Idap. The values are defined as follows:

- Idap Use the default entry in LDAP for all attribute default values.
- local Use the default stanza from local /etc/security/user file for all attribute default values.

Specifies the base DN for the **mksecIdap** command to search for the user base DN and group base DN. If not specified from the command line, the entire database is searched.

Specifies a comma separated list of hostnames (server and backup servers).

Specifies the full path to the client SSL key.

Specifies the set of user and group attributes to be retrieved. Valid values are **ALL** and **OS**. The default is **ALL**. The values are defined as follows:

- · ALL Retrieve all attributes of an entry.
- OS Retrieve only the operating system required attributes of an entry. Non-OS attributes like telephone number, binary images etc. will not be returned.

Note: Use OS only when entries have many non-OS required attributes or attributes with large value, e.g. binary data, to reduce sorting effort by the LDAP server.

Specifies the port number that the LDAP server is listening to. Specifies the clear text password for the bindDN used to bind to the LDAP server.

Specifies the number of threads the client side daemon uses. Valid values are 1-1,000. The default is 10.

Specifies the maximum time length that a cache entry expires. Valid values are 60-3,600 seconds. The default is 300 seconds. Set this value to 0 to disable caching.

Specifies the time interval of heartbeat between this client and the LDAP server. Valid values are 60-3,600 seconds. Default is 300.

Specifies the comma separated list of user names to enable for LDAP authentication. These users will have their registry and SYSTEM attributes set to use LDAP. Specify **ALL** to enable all users on the client.

Note: Alternatively, the SYSTEM attribute in the default stanza of /etc/security/user can be set to LDAP, allowing only LDAP users to log in. Setting the SYSTEM attribute to LDAP or compat allows both LDAP users and local users to log in to the system.

Specifies the password for the client SSL key.

Specifies to undo the previous client setup to the LDAP client configuration file.

Examples

1. To setup a LDAP server of RFC2307AIX specific schema for users and groups, enter:

```
mksecldap -s -a cn=admin -p adminpwd -S rfc2307aix
```

This sets up a LDAP server with LDAP server administrator DN being cn=admin, password being adminpwd. User and group data is exported from local files to the default cn=aixdata suffix using RFC2307AIX schema.

2. To setup a LDAP server with a baseDN other than the default and with SSL secure communication,

```
mksecldap -s -a cn=admin -p adminpwd -d o=mycompany,c=us -S rfc2307 \ -k /usr/ldap/serverkey.kdb
 -w keypwd
```

This sets up a LDAP server with LDAP server administrator DN being cn=admin, password being adminpwd. User and group data is exported from local files to the o=mycompany,c=us suffix using RFC2307 schema. The LDAP server uses SSL communications by using the key stored at /usr/ldap/serverkey.kdb. The password to the key, keypwd, must also be supplied.

3. To setup a LDAP server of RFC2307AIX schema type and create a proxy account, enter:

```
mksecldap -s -a cn=admin -p adminpwd -d c=us -S rfc2307aix -x cn=proxy,c=us -X proxypwd
```

This sets up a LDAP server with LDAP server administrator DN being cn=admin, password being adminpwd. User and group data is exported from local files to the c=us suffix using RFC2307AIX schema. A proxy identity is setup with DN being cn=proxy,c=us and password proxypwd. The ACL specified in /etc/security/ldap/proxy.ldif.template will also have been applied on the server for the cn=proxy,c=us DN.

4. To undo a previous server setup:

```
mksecldap -s -U
```

This undoes the previous setup to the server configuration file. Note, for safety reasons, this does not remove any database entries or database created by a previous setup. One has to remove the database entries/database manually if they are not needed any more.

5. To setup a client to use the **server1.ibm.com** and **server2.ibm.com** LDAP servers, enter:

```
mksecldap -c -a cn=admin -p adminpwd -h server1.ibm.com,server2.ibm.com
```

The LDAP server administrator DN and password is supplied for this client to authenticate to the server. The mksecldap command contacts the LDAP server for schema type used, and sets up the client accordingly. Without the -d option from the command line, the entire server DIT is searched for the user base DN and the group base DN.

6. To setup the client to talk to the server3.ibm.com LDAP server using SSL, enter:

```
mksecldap -c -a cn=admin -p adminpwd -h server3.ibm.com -d o=mycompany,c=us -k /usr/ldap/clientkey.kdb -w keypwd -u user1,user2
```

This sets up a LDAP client similar to case 3, but with SSL communication. The mksecldap command searches the o=mycompany,c=us RDN for user base DN and group base DN. Account user1 and user2 are configured to authenticate through LDAP.

Note: The -u ALL option enables all LDAP users to login to this client.

7. To setup a client to talk to **server4.ibm.com** and use **ldap auth** authentication with a proxy bind, enter:

```
mksecldap -c -a cn=proxy,c=us -p proxypwd -h server4.ibm.com -A ldap auth
```

This sets up an LDAP client to bind to the LDAP server with the cn=proxy,c=us DN. Because the administrator DN is not used, the access granted to the client is dependent on the ACL setup on the LDAP server for the cn=proxy,c=us DN. The client is also setup to use Idap_auth-type authentication which sends passwords in clear text to the LDAP server for comparison.

Note: When using Idap_auth-type authentication, the use of SSL is strongly recommended because during authentication passwords will be sent in clear text to the LDAP server.

8. To undo a previous client setup, enter:

Eila

mksecldap -c -U

This undoes the previous setup to the /etc/security/ldap/ldap.cfg file. This does not remove the SYSTEM=LDAP and registry=LDAP entries from the /etc/security/user file.

Files Accessed

Mode	FIIE
r	/etc/passwd
r	/etc/group
r	/etc/security/passwd
r	/etc/security/limits
r	/etc/security/user (on the server)
rw	/etc/security/user (on the clients)
r	/etc/security/environ
r	/etc/security/user.roles
r	/etc/security/lastlog
r	/etc/security/smitacl.user
r	/etc/security/mac_user
r	/etc/security/group
r	/etc/security/smitacl.group
r	/etc/security/roles
rw	/etc/security/login.cfg (on the server)
rw	/etc/slapd32.conf (on the server)
rw	/etc/security/ldap/ldap.cfg (on the client)

Related Information

The secidapcintd daemon.

The start-secidapcintd, stop-secidapcintd, restart-secidapcintd, is-secidapcintd, flush-secidapcintd, sectoldif, and nistoldif commands.

The /etc/security/ldap/ldap.cfg file.

Setting up an LDAP security information server in Security.

mksecpki Command

Purpose

mksecpki configures AIX PKI server components. The components of AIX PKI are Certificate Authority, Registration Authority, and Audit subsystems.

Syntax

mksecpki {-u username -f reference_file [-p CA_port] [-H Idap_host] [-D dn -w password] [-i certificate_issuer_dn] | -U username}

Description

The **mksecpki** command configures AIX PKI server components. **mksecpki** must be run after configuring an LDAP server to publish certificates. The values for the options -H, -D, -w, and -i must be the same values as the ones specified during the LDAP configuration. Otherwise, the CA will not be able to publish certificates to LDAP.

The -u option specifies the AIX username which will host AIX PKI. The username must follow AIX username rules. Do not use -u and -U together. The invoker of the command will be asked to provide a password for the username. mksecpki will create a database instance with the same name.

The -f option specifies the file containing the reference number and passphrase. The client certificate requests will use these exact same values while communication with the CA. The reference number and passphrase are each specified on a separate line. The following is the contents of an example iafile:

11122233 temppwd1234

The -p option specifies the port that Certificate Authority accepts the certificate requests. If no port number is given, 1077 will be assumed.

The -H option specifies the hostname of the LDAP server where the certificates are published to. Prior to invoking the mksecpki command, an LDAP server must be setup to publish certificates. Otherwise, the certificates will not be published to LDAP, however, certificate will be returned to the requestor when certificate management commands are used. If the -H option is not given the localhost will be used as the hostname.

The -D option is used to specify the directory administrators distinguished name. This must be the same one that is specified during the configuration of the LDAP server.

The -w option specifies the password corresponding to the administrator DN. It is an error not to specify both the admin DN and password.

The -i option specifies the distinguish name of the Certificate Authority issuing the certificates. This must be the same value as the one given when setting an LDAP server for publishing certificates.

The **-U** option specifies the username that hosts the AIX PKI that will be unconfigured. The command will confirm the unconfiguration before starting its operation. This option removes the username from the system. The invokers of this command will be asked if they want to remove the home directory of the username. When this command runs without errors, it displays a message indicating the successful completion. The invoker of this command is recommended to wait for this message.

Flags

-u username	Specifies the name of the username that is going to be created that will host AIX PKI server components.
-f reference_file	Specifies the file which contains the reference number and passphrase that is used when making a certificate creation request.
-p CA_port	Specifies the Certificate Authority Communication Port.
-H Idap_host	Specifies the LDAP host where the certificates are going to be published.
-D adminDN	Specifies directory administrator distinguished name (DN). Note: The -D option requires that the -w password option also be specified.
-w password	Specifies directory administrator password.
-i certificate_issuer_dn	Specifies the distinguished name of the Certificate Authority issuing certificates.
-U username	Specifies the username which hosts the AIX PKI that will be unconfigured.

Security

This command should grant execute (x) access only to the root user and members of the security group.

Examples

To configure AIX PKI server side using **pkitest.ibm.com** as the LDAP host name for publish certificates and using o=aix,c=us as the issuer name, enter:

```
$ mksecpki -u pkiuser -f iafile -p 829 -H pkitest.ibm.com -D cn=admin
-w password -i o=aix,c=us
```

where iafile contains the reference number and passphrase.

To unconfigure the server, enter:

\$ mksecpki -U pkiuser

Files

/usr/lib/security/pki/ca.cfg

Related Information

The certadd, certcreate, certdelete, certget, certlink, certlist, certrevoke, certverify, keyadd, keydelete, keylist, and keypasswd commands.

mksensor Command

Purpose

Defines a sensor to the resource monitoring and control (RMC) subsystem.

Syntax

mksensor [-n host | -N { node_file | "-" }] [-i seconds] [-c n] [-e 0 | 1 | 2] [-u user-ID] [-h] [-v | -V] sensor_name ["]sensor_command["]

Description

The **mksensor** command defines a sensor resource to the resource monitoring and control (RMC) subsystem. A sensor is an RMC resource with attributes that you can monitor. You can use the event-response resource manager (ERRM) commands to set up monitoring of the sensor attributes. The response actions defined will run when a monitored sensor event occurs. This enables administrators to extend RMC monitoring capabilities without having to write a resource manager.

The sensor resource manager sets the values of the sensor attributes after these attributes have been monitored. The sensor resource manager updates the attribute values at defined intervals using commands or scripts that you specify with the sensor_command parameter.

You can also update the sensor values using the chsensor command or the refsensor command. Use the Issensor command to list the sensor attributes and values. To remove a sensor, use the rmsensor command.

The sensor is identified by the sensor name parameter specified on the **mksensor** command. The sensor command parameter specifies what will be run by the sensor resource manager to set values to the attributes of this sensor. The sensor consists of the following attributes that can be set by sensor_command:

Float32 The type float32 attribute for this sensor resource. Float64 The type float64 attribute for this sensor resource. Int32 The type int32 attribute for this sensor resource. Int64 The type int64 attribute for this sensor resource. Quantum The type quantum attribute for this sensor resource. String The type string attribute for this sensor resource. Uint32 The type uint32 attribute for this sensor resource. Uint64 The type uint64 attribute for this sensor resource.

The sensor_command parameter sets attribute values by sending the values to standard output in a format that the sensor resource manager can parse. The format is attr=value. For example, if sensor command sets the Int32 attribute to 57, it writes Int32=57 to standard output. To set more than one attribute value, sensor command can write multiple attr=value pairs to standard output. The attr=value pairs can be on one or more lines. If the standard output of sensor command is not in attr=value form, it is assumed to be a string and the value is placed in the **String** attribute.

Use the -e flag to control how the exit values from sensor_command are interpreted. Depending on this setting, when the exit value of the sensor command is considered to be an error, the sensor attributes are not set and information is written to the audit log.

The sensor command runs using the user ID that creates the sensor resource. Once a sensor resource is monitored, sensor command is run at intervals specified by the -i flag, which is expressed in seconds. The default interval is 60 seconds if none is specified. Specify a value of 0 to indicate that sensor command is not to run at intervals. In this case, the **refsensor** command is typically used to update the sensor values.

The **mksensor** command can be run on any node. If you are in a management or peer domain, you can use the -n flag to define the sensor on a node in the domain.

Flags

- -**c** n Specifies whether special handling is required for this sensor. *n* can be one of these values:
 - **0** Indicates that no special handling is required. This is the default.
 - 1 Indicates that the command in this sensor will be run any time, even at the initial stage (when Issensor is called or when monitoring is just started.) It is not recommanded that you specify this value, unless you expect the command to run very soon. Setting this value could block other requests to the sensor resource manager, so that those requests will not be processed until the command ends.
 - 2 Indicates that output from the command in the **SavedData** field is not saved permanently to SavedData persistent resource attributes. If this value is not specified, the sensor resource manager updates data in the registry's resource table whenever the command's standard output contains the line: SavedData="any-string".
 - 3 Indicates a combination of values 1 and 2.
 - 4 Indicates that the sensor resource manager will run the command when monitoring is stopped.
 - 5 Indicates a combination of values 1 and 4.
 - 6 Indicates a combination of values 2 and 4.
 - 7 Indicates a combination of values 1, 2, and 4.

-e 0 | 1 | 2

Specifies how the sensor resource manager interprets the exit code of sensor command. The values mean:

- **0** No exit value from *sensor_command* is an error.
- **1** A non-zero exit value from *sensor command* is an error.
- 2 An exit value of 0 from sensor_command is an error.

The default value is 1. The sensor attributes are not updated when the exit value is interpreted as an error. For an error, information is written to the audit log.

-h Writes the command's usage statement to standard output.

-i seconds

Specifies the interval in which sensor_command is run to update the values of the sensor attributes. seconds is an integer value and must be greater than or equal to 10. sensor_command is run at the specified interval only when a sensor resource is monitored. The default interval is 60 seconds. If the interval is set to 0, sensor command will not be run automatically. Using the refsensor command is independent of interval updates.

-n host

Specifies the node on which the sensor should be defined. By default, the sensor is defined on the local node. This flag is only appropriate in a management domain or a peer domain.

-N {node file | "-"}

Specifies a file or standard input listing the nodes on which the sensor must be removed. This flag is only appropriate in a Cluster Systems Management (CSM) or a peer domain cluster.

-u user-ID

Specifies the name of a user whose privileges will be used to run the sensor command. The user should already be defined on the system. The default value for user-ID is the user name that is associated with the current effective user ID.

-v | -V

Writes the command's verbose messages to standard output.

Parameters

sensor name

Specifies the name of the sensor to be defined.

["|sensor command["]

Specifies a command or script that the sensor resource manager will use to set the attribute values of the sensor. You should not call any of the sensor resource manager commands (chsensor, Issensor, mksensor, refsensor, or rmsensor) as part of this parameter.

If sensor_command contains any blank characters or any special charaters that can be interepreted by the shell it must be enclosed in double quotation marks.

When sensor_command is enclosed in double quotation marks, you must include a backslash escape character (\) before an "inner" double quotation mark. You must also include a \ before a dollar sign (\$). See Example 2 for more information.

Security

The user needs write permission for the IBM.Sensor resource class in order to run mksensor. Permissions are specified in the access control list (ACL) file on the contacted system. See the RSCT: Administration Guide for details on the ACL file and how to modify it.

Exit Status

- **0** The command has run successfully.
- 1 An incorrect combination of flags and parameters has been entered.
- n Based on other errors that can be returned by the RMC subsystem.

Environment Variables

CT CONTACT

When the CT CONTACT environment variable is set to a host name or IP address, the command contacts the resource monitoring and control (RMC) daemon on the specified host. If this environment variable is not set, the command contacts the RMC daemon on the local system where the command is being run. The resource class or resources that are displayed or modified by the command are located on the system to which the connection is established.

CT IP AUTHENT

When the CT_IP_AUTHENT environment variable exists, the RMC daemon uses IP-based network authentication to contact the RMC daemon on the system that is specified by the IP address to which the CT CONTACT environment variable is set. CT IP AUTHENT only has meaning if CT CONTACT is set to an IP address; it does not rely on the domain name system (DNS) service.

CT_MANAGEMENT_SCOPE

Determines the management scope that is used for the session with the RMC daemon to monitor and control the resources and resource classes. The management scope determines the set of possible target nodes where the resources and resource classes can be monitored and controlled.

The valid values are:

- **0** Specifies *local* scope.
- 1 Specifies *local* scope.
- 2 Specifies peer domain scope.
- 3 Specifies management domain scope.

If this environment variable is *not* set, *local* scope is used.

Restrictions

You should not call any of the sensor resource manager commands (chsensor, Issensor, mksensor, refsensor, or rmsensor) as part of the sensor command parameter, as this could cause a deadlock.

Implementation Specifics

This command is part of the Reliable Scalable Cluster Technology (RSCT) fileset for AIX.

Examples

1. To create a new sensor called **Sensor1** that runs the script /usr/bin/updateSensor1, which will update the sensor attributes every 30 seconds (once monitored), enter:

```
mksensor -i 30 Sensor1 "/usr/bin/updateSensor1"
```

The contents of /usr/bin/updateSensor1 may be like:

```
#!/usr/bin/perl
my $int32 = some fn that generates i32 value;
my $string = some fn that generates string value;
print "Int32=$int32 String=$string";
exit 0;
```

A sample condition could be:

```
mkcondition -r IBM.Sensor -s "Name==Sensor1" -e "Int32 > 100" Sensor1Int32
```

Using the response "E-mail root anytime", a start monitoring command may be: startcondresp Sensor1Int32 "E-mail root anytime"

2. To create a sensor called Sensor1 with a sensor command value of

```
df -m /var | sed '1d' | sed 's/%//g' | /bin/awk '{ print "Int32="$4}',
enter:
mksensor Sensor1 "df -m /var | sed '1d' | sed 's/%//g' | /bin/awk \
'{ print \"Int32=\"\$4}'"
```

When sensor_command is enclosed in double quotation marks, you must include a backslash escape character (\) before an "inner" double quotation mark. You must also include a \ before a dollar sign (\$). So in this example, the sensor command substring "Int32="\$4 becomes \"Int32=\"\\$4 when it is part of mksensor command.

Location

/usr/sbin/rsct/bin/mksensor

Related Information

Books: RSCT: Administration Guide, for information about the ACL authorization file and about monitoring resources with the ERRM commands

Commands: chsensor, Issensor, mkcondition, mkresponse, refsensor, rmsensor, startcondresp

Information Files: **rmccli**, for information about *attr=value* syntax

mkserver Command

Purpose

Adds a subserver definition to the subserver object class.

Syntax

mkserver -c CodePoint -s Subsystem -t Type

Description

The mkserver command adds a subserver definition to the Subserver object class.

Flags

-c CodePoint	Specifies the <i>CodePoint</i> integer that identifies the subserver. This is the value by which the subsystem knows the subserver. The mkserver command is unsuccessful if this <i>CodePoint</i> value already exists for this subsystem. The limit for <i>CodePoint</i> storage is the same as a short integer (1 through 32,768).
-s Subsystem	Specifies the name that uniquely identifies the subsystem to which the subserver belongs. The mkserver command is unsuccessful if the <i>Subsystem</i> name is not known in the subsystem object class, or if the <i>Subsystem</i> name is that of a known subsystem in the subsystem object class but uses signals as its communication method.
-t Type	Specifies the name that uniquely identifies the subserver. The mkserver command is unsuccessful if the <i>Type</i> name is already known in the Subserver Type object class.

Security

Auditing Events: If the auditing subsystem has been properly configured and is enabled, the **mkserver** command will generate the following audit record (event) every time the command is executed:

Event Information

Lists in an audit log subsystems that have been added and the entire Object Data SRC_Addserver

Management record.

See "Setting up Auditing" in Security for more details about how to properly select and group audit events and how to configure audit event data collection.

Examples

To add a subserver definition, enter:

```
mkserver -s srctest -t tester -c 1234
```

This adds a subserver definition to the **Subserver Type** object class, with an owning subsystem of srctest and a subserver code point of 1234.

Files

/etc/objrepos/SRCsubsys Specifies the SRC Subsystem Configuration object class. /etc/objrepos/SRCsubsvr Specifies the SRC Subserver Configuration object class.

Related Information

The auditpr command, chserver command, rmserver command, startsrc command, stopsrc command.

System Resource Controller in the Operating system and device management.

Auditing overview in the Security.

System Resource Controller (SRC) Overview for Programmers in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs.

Defining Your Subsystem to the SRC in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs.

mkslave Command

Purpose

Invokes the ypinit command to retrieve maps from an NIS master server and starts the ypserv daemon to configure a slave server.

Syntax

/usr/sbin/mkslave [-C | -c] [-O | -o] [-I | -B | -N] Master

Description

The mkslave command invokes the ypinit command to retrieve maps from the master server you specify on the command line. The **ypserv** daemon starts after the **ypinit** command has completed successfully. Use the Master parameter to specify the host name of the master server. The master server specified should already be configured and running.

You can use the Network application in Web-based System Manager (wsm) to change network characteristics. You could also use the System Management Interface Tool (SMIT) smit mkslave fast path to run this command.

Flags

- -C Invokes the ypinit command with the -n flag. The mkslave command continues on errors. This flag is the default.
- Stops execution when errors occur. -C
- -0 Overwrites any maps that exist in the domain.
- Prevents the overwriting of maps that exist in the domain. This flag is the default. -0
- Invokes the **ypinit** command immediately but does not start the **ypserv** daemon until the next system reboot.
- -N Invokes the **ypinit** command and starts the **ypserv** daemon.
- -B Invokes the **ypinit** command, starts the **ypserv** daemon and configures the **ypserv** to start at system reboot. This flag is the default.

Examples

To invoke the **ypinit** command so that the master server host2 will be contacted for maps, enter: mkslave -0 host42

This command will overwrite the current maps.

Files

/var/yp/DomainName directory

Contains the NIS maps for the NIS domain.

Related Information

The **chmaster** command, **mkclient** command, **rmyp** command, **smit** command, **ypinit** command.

The ypbind daemon, yppasswdd daemon, ypserv daemon, ypupdated daemon.

Network Information Services (NIS) Overview for System Management in AIX 5L Version 5.3 Network Information Services (NIS and NIS+) Guide.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

System management interface tool in *Operating system and device management*.

Network File System (NFS) Overview for System Management in Networks and communication management.

NIS Reference.

mkssys Command

Purpose

Adds a subsystem definition to the subsystem object class.

Syntax

mkssys { -p Path -s Subsystem -u UserID } [-a Arguments] [-e StandardError] [-i StandardInput] [-o StandardOutput] [-t Synonym] [-O | -R] [-d | -D] [-q | -Q] [-K | [-I MessageQueue -m MessageMType | -f StopForce -n StopNormal -S]] [-E Nice] [-G Group] [-w Wait]

Description

The mkssys command adds a new subsystem definition to the subsystem object class. If no flags are chosen after the -p, -s, and -u flags have been specified, the defaults are -e /dev/console, -i /dev/console, -o /dev/console, -O, -d, -Q, -K, -E 20, and -w 20.

Note: Any auditing performed by the System Resource Controller (SRC) when actions are taken for the subsystem is logged against the login ID of the user who created the subsystem by using the mkssys command. For example, if you are logged in with root user authority, the subsystem is added with root user authority as the audit account.

Flags

-a Arguments	Specifies any arguments that must be passed to the command, started as the subsystem. These <i>Arguments</i> variables are passed by the SRC to the subsystem according to the same rules used by the shell. For example, quoted strings are passed as a single argument, and blanks outside a quoted string delimit arguments. Single and double quotes can be used.
-d	Specifies that inactive subsystems are displayed when the Issrc -a command (status all) request is made. By default, if the -D and -d flags are not present, the -d flag is used.
-D	Specifies that inactive subsystems are not displayed when status-all or status-group requests are made.
-e StandardError	Specifies where the subsystem <i>StandardError</i> data is placed. If the -e flag is not specified, the /dev/console file is used for standard error.
-E Nice	Changes the execution priority of the subsystem. Valid values are 0 through 39 (ordinary <i>Nice</i> variables are mapped to all positive numbers). If the -E flag is not present, the subsystem priority defaults to 20. Values between 0 and 19 are reserved for users with root authority.
-f StopForce	Specifies the signal sent to the subsystem when a forced stop of the subsystem is requested. Use only when the subsystem uses signals. The mkssys command is unsuccessful if the <i>StopForce</i> parameter is not a valid signal.
-G Group	Specifies that the subsystem belongs to the <i>Group</i> specified, and that the subsystem responds to all group actions on the <i>Group</i> .
-i StandardInput	Specifies where the subsystem standard input is routed. This field is ignored when the subsystem uses sockets communication. If the -i flag is not specified, by default the /dev/console file is used for standard input.
-I MessageQueue	Specifies that the subsystem uses message queues as the communication method. The <i>MessageQueue</i> variable specifies the message queue key for creating the message queue for the subsystem. Use the ftok subroutine with the subsystem path name as input to generate a unique key.
-К	Specifies that the subsystem uses sockets as its communication method. If a communication method is not specified, sockets communication is used by default.
-m MessageMType	Specifies the message type key the subsystem expects on packets sent to the subsystem by the SRC. Use only when the subsystem uses message queues communication.
-n StopNormal	Specifies the signal sent to the subsystem when a normal stop of the subsystem is requested. Use only when the subsystem uses signals communication. The mkssys command is unsuccessful if the <i>StopNormal</i> variable is not a valid signal.
-o StandardOutput	Specifies where the subsystem standard output is placed. If the -o flag is not specified, by default the /dev/console file is used for standard out.
-0	Specifies that the subsystem is not restarted if it stops abnormally. The default is no restart.

-p Path Specifies the absolute path to the subsystem executable program.

Specifies that the subsystem can have multiple instances running at the same time. Specifies that multiple instances of the subsystem are not allowed to run at the -Q

same time and the subsystem is not to share the same interprocess communication

(IPC) queue. If the -q flag is not specified, the -Q flag is the default.

Specifies that the subsystem is restarted if the subsystem stops abnormally. -R

-s Subsystem Specifies a name that uniquely identifies the subsystem. The mkssys command is

unsuccessful if the subsystem name is already known in the subsystem object

-S Specifies that the subsystem uses the signals communication method. You cannot

define subservers for a subsystem name when your communication method is

signals.

-t Synonym Specifies an alternate name for the subsystem. The mkssys command is

unsuccessful if the synonym name is already known in the subsystem object class.

-u UserID Specifies the user ID for the subsystem. The UserID that creates the subsystem is

used for security auditing of that subsystem.

Specifies the time, in seconds, allowed to elapse between a stop cancel -w Wait

> (SIGTERM) signal and a subsequent SIGKILL signal. Also used as the time limit for restart actions. If the subsystem stops abnormally more than twice in the time limit specified by the Wait value, the subsystem is not automatically restarted. By default, if the -w flag is not present, the wait time default is 20 seconds.

Security

Auditing Events: If the auditing subsystem has been properly configured and is enabled, the mkssys command will generate the following audit record (event) every time the command is executed:

Event Information

SRC_Addssys Lists in an audit log the name of the subsystem being added to the Object Data Manager

(ODM) database and the entire ODM record.

See "Setting up Auditing" in Security for details about selecting and grouping audit events, and configuring audit event data collection.

Examples

1. To add a subsystem that uses sockets as its communication type, type the following:

```
mkssys -s srctest -p /usr/lpp/srctest/srctest -u 0 -K
```

This adds a subsystem definition to the subsystem object class, with a communication type of sockets, a user ID of 0 (root), and a subsystem name of srctest.

2. To add a subsystem that uses message queues as its communication type, type the following:

```
mkssys -s srctest -p /usr/lpp/srctest/srctest -u 0 -I 123456 \ > -m 789
```

This adds a subsystem definition to the subsystem object class, with a communication type of message queues, a message queue key of 123456, and a subsystem message type of 789.

3. To add a subsystem that uses signals as its communication type, type:

```
mkssys -s srctest -p /usr/lpp/srctest/srctest -u 0 -S -n 30 \ > -f \ 31
```

This adds a subsystem definition to the subsystem object class, with a communication type of signals, a stop normal signal of 30, a stop force signal of 31.

4. To add a subsystem that uses sockets as its communication type and is always passed an argument, type:

```
mkssys -s srctest -p /usr/lpp/srctest/srctest -u 0 -a "-x"
```

This adds a subsystem definition to the subsystem object class with a communication type of sockets and a command argument of "-x".

Files

/etc/objrepos/SRCsubsys Specifies the SRC Subsystem Configuration object class. /dev/SRC Specifies the AF_UNIX domain in the socket.h file. /dev/.SRC-unix Specifies the location for temporary file sockets.

Related Information

The auditor command, chssys command, Issrc command, refresh command, rmssys command, startsrc command, stopsrc command, traceson command, tracesoff command.

System Resource Controller in Operating system and device management.

Auditing overview in Security.

System Resource Controller (SRC) Overview for Programmers in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs.

Defining Your Subsystem to the SRC in AIX 5L Version 5.3 General Programming Concepts: Writing and Debugging Programs.

mkstr Command

Purpose

Creates an error message file.

Syntax

mkstr [-] MessageFile Prefix File ...

Description

The **mkstr** command creates a file of error messages that can be removed from a single C source file or from multiple source files. Its use can reduce the size of programs that contain many error diagnostics and reduce system overhead in running such programs, because error messages are then not constantly swapped in and out of the source files.

The **mkstr** command processes each file specified by the File parameter, placing a massaged version of the file in a file having the name specified by the *Prefix* parameter followed by the original name.

To process the error messages in the source to the file specified by the *MessageFile* parameter, the **mkstr** command keys on the string `error("' in the input stream. The string, starting at the '"' (two double quotation marks), is placed in the message file and followed by a null character and a new-line character. The null character terminates the message so it can be easily used when retrieved. The new-line character makes it possible to see the contents of the error message file by using the cat command.

The massaged copy of the input file then contains an Iseek pointer into the file, which can be used to retrieve the message to its appropriate source file, as shown in the following example:

```
char efilname[] = "/usr/lib/pistrings";
int
      efil = -1;
```

```
error(a1, a2, a3, a4)
{
    char buf[256];
    if (efil < 0) {
        efil = open(efilname, 0);
        if (efil < 0) {
        oops:
            perror(efilname);
                exit(1);
        }
     }
    if (lseek(efil,(long) a1,0) <0||
        read(efil,buf, 256) <= 0)
        goto oops;
    printf(buf, a2, a3, a4);
}</pre>
```

Flags

- The optional - (minus sign) causes the error messages to be placed at the end of the *MessageFile* for recompiling part of a large mkstr program.

Examples

- 1. To put the error messages from the current directory C source files into the file pistrings and to put processed copies of the source for these files into file names prefixed by xx, enter:
- 2. To append the error messages from an additional source file into the file pistrings, enter:

Files

/usr/ccs/bin/mkstr

Contains the mkstr command.

Related Information

mkstr pistrings xx *.c

mkstr - pistrings xx newfile.c

The cat command, xstr command.

The **Iseek** subroutine.

mksysb Command

Purpose

Creates an installable image of the root volume group either in a file or onto a bootable tape.

Syntax

```
mksysb [-a][-b Number][-e][-F filename][-i][-m][-p][-t argument][-v][-V][-X]
Device | File
```

Description

The **mksysb** command creates a backup of the operating system (that is, the root volume group). You can use this backup to reinstall a system to its original state if it is corrupted. If you create the backup on tape or UDFS capable media, the backup is bootable and includes the installation programs needed to install from the backup.

Note: If the system has a multibos environment where both instances are mounted, you can restore the backup only by using the alt disk mksysb command.

The file-system image is in backup-file format. The tape format includes a boot image, a bosinstall image, and an empty table of contents followed by the system backup (root volume group) image. The root volume group image is in backup-file format, starting with the data files and then any optional map files.

When a bootable backup of a root volume group is created, the boot image reflects the currently running kernel. If the current kernel is the 64-bit kernel, the boot image of the backup is also 64 bit, and it only boots 64-bit systems. If the current kernel is a 32-bit kernel, the backup's boot image is 32 bit, and it can boot both 32-bit and 64-bit systems.

One of the data files mksysb uses is the /bosinst.data file. If a /bosinst.data file does not exist, /var/adm/ras/bosinst.data is copied to / (root). In AIX 4.3.3 and later versions, mksysb always updates the target_disk_data stanzas in bosinst.data to match the disks currently in the root volume group of the system where the **mksysb** command is running.

If you are using a customized /bosinst.data file and do not want the target disk data stanzas updated, you must create the file /save bosinst.data file. The mksysb command does not update /bosinst.data if the /save bosinst.data file exists.

- 1. While the **mksysb** command is running, ensure that system activity is minimal.
- 2. The image that the **mksysb** command creates does not include data on raw devices or in user-defined paging spaces.
- 3. If you are using a system with a remote-mounted /usr file system, you cannot reinstall your system from a backup image.
- 4. The **mksvsb** command may not restore all device configurations for special features, such as **/dev/netbios** and some device drivers not shipped with the product.
- 5. Some rspc systems for AIX 5.1 and earlier do not support booting from tape. When you make a bootable mksysb image on an rspc system for AIX 5.1 and earlier that does not support booting from tape, the mksysb command issues a warning indicating that the tape will not be bootable. You can install a mksysb image from a system that does not support booting from tape by booting from a CD and entering maintenance mode. In maintenance mode, you can install the system backup from tape.
- 6. The **mksysb** command uses the **backup** command to create its archive image. The **mksysb** command also saves the EA format for any JFS2 filesystems being backed up. It uses the /usr/bin/mkvgdata shell script to save this information.

To create a backup of the operating system to CD, please refer to the **mkcd** command.

Flags

- Does not back up extended attributes or NFS4 ACLs. -a
- -A Backs up DMAPI file system files.
- -b Number Specifies the number of 512 - byte blocks to write in a single output operation. When the backup command writes to tape devices, the default is 100 for backups by name.

The write size is the number of blocks multiplied by the block size. The default write size for the backup command writing to tape devices is 51200 (100 * 512) for backups by name. The write size must be an even multiple of the tape's physical block size.

-e Ecludes files listed in the /etc/exclude.rootvg file from being backed up. The rules for exclusion follow the pattern matching rules of the grep command.

If you want to exclude certain files from the backup, create the <code>/etc/exclude.rootvg</code> file, with an ASCII editor, and enter the patterns of file names that you do not want included in your system backup image. The patterns in this file are input to the pattern matching conventions of the <code>grep</code> command to determine which files will be excluded from the backup. If you want to exclude files listed in the <code>/etc/exclude.rootvg</code> file, select the <code>Exclude Files</code> field and press the <code>Tab</code> key once to change the default value to <code>yes</code>.

For example:

 To exclude all the contents of the directory called scratch, edit the exclude file to read as follows:

/scratch/

2. To exclude the contents of the directory called /tmp, and avoid excluding any other directories that have /tmp in the path name, edit the exclude file to read as follows:

^./tmp/

All files are backed up relative to . (current working directory). To exclude any file or directory for which it is important to have the search match the string at the beginning of the line, use the ^ (caret character) as the first character in the search string, followed by . (dot character), followed by the filename or directory to be excluded.

If the filename or directory being excluded is a substring of another filename or directory, use the ^. (caret character followed by dot character) to indicate that the search should begin at the beginning of the line and use the \$ (dollar sign character) to indicate that the search should end at the end of the line.

-F filename

Specifies a previously created **mksysb** image from which a backup tape will be created. An attempt is made to make the backup tape bootable. Additionally, this flag must be used with a tape device.

-i

Calls the **mkszfile** command, which generates the **/image.data** file. The **/image.data** file contains details about volume groups, logical volumes, file systems, paging space, and physical volumes. This information is included in the backup for future use by the installation process.

Note: Before running the **mkszfile** command, ensure that enough space is available in the **/tmp** file to store a boot image. This space is needed during both backup and installation. To determine the amount of space needed in the **/tmp** file, issue the following command:

bosboot -q -a -d device

If you use the **-X** flag with the **mksysb** command, you do not need to run the **bosboot** command to determine the amount of space needed in the **/tmp** file.

-m

Calls the mkszfile command, with the -m flag to generate map files.

Note: The use of the -m flag causes the functions of the -i flag to be executed also.

-p

Disables software packing of the files as they are backed up. Some tape drives use their own packing or compression algorithms.

-t argument

Specifies the path to the directory or file system used to create a boot image from the **mksysb** file specified by the **-F** flag. If the **-t** flag is not used with the **-F** flag, the boot image is created in the **/tmp** file by default. Approximately 100 MB of free space is required. After the boot image is created, this space is freed.

Verbose mode. Lists files as they are backed up.

-V

Verifies a tape backup. This flag causes the **mksysb** command to verify the file header of each file on the backup tape and report any read errors as they occur.

-X

Specifies to automatically expand the **/tmp** file system if necessary. The **/tmp** file system may need to be extended to make room for the boot image when creating a bootable backup to tape.

Parameters

Device | File

Specifies the name of the device or file.

Exit Status

This command returns the following exit values:

- 0 The command completed successfully.
- 1 An error in the **mksysb** command usage occurred.
- 2 An error in the savevg command usage occurred. The savevg is a link to mksysb.
- 3 An error occurred before any file systems were mounted.
- 4 Exit because of trap.
- 5 Exit because there was no space.
- Exit because a volume group name was not valid.

Examples

1. To generate a system backup and create an /image.data file (generated by the mkszfile command) to a tape device named /dev/rmt0, type:

```
mksysb -i /dev/rmt0
```

2. To generate a system backup and create an /image.data file with map files (generated by the mkszfile command) to a tape device named /dev/rmt1, type:

```
mksysb -m /dev/rmt1
```

3. To generate a system backup with a new /image.data file, but exclude the files in directory /home/user1/tmp, create the file /etc/exclude.rootvg containing the line /home/user1/tmp/, and type: mksysb -i -e /dev/rmt1

This command backs up the /home/user1/tmp directory but not the files it contains.

4. To generate a system backup file named /mksysb_images/node1 and a new /image.data file for that image, type:

```
mksysb -i /mksysb images/node1
```

Note: This file will not be bootable and can only be installed using Network Installation Management

5. To generate a system backup on the tape in /dev/rmt0, and then verify the readability of file headers, enter:

```
mksysb /dev/rmt0 -V
```

6. To generate a system backup and create an /image.data file (generated by the mkszfile command) to a UDFS capable device named /dev/usbms0, enter the following command:

```
mksysb -i /dev/usbms0
```

Files

/usr/bin/mksysb

Contains the mksysb command.

Related Information

The backup command, bosboot command, mkcd command, mkszfile command.

The /image.data file.

A procedure to verify the mksysb backup can be found in the article Creating system backups in the Installation and migration.

mkszfile Command

Purpose

Saves the system state for reinstallation on the current system or another system.

Syntax

mkszfile [-X] [-m]

Description

Attention: The mkszfile command overwrites an existing /image.data file with new information.

The **mkszfile** command saves the system state for reinstallation on the current system or on another system. The information saved includes the following:

- System installation information
- · Logical volume information for the root volume group
- File system information.

The saved information allows the bosinstall routine to recreate the logical volume information as it existed before the backup.

The mkszfile command creates the /image.data file. The contents of this file are defined by the system in which the image was created. The user can edit the /image.data file before calling the mksysb command. The mksysb command, in turn, only backs up the file systems specified in the /image.data file, which reflects the requirements of the rootvg file system.

All the saved information is obtained using list commands. The commands are listed in the /image.data file as comments for the user's reference when editing this file.

Files on tape cannot be changed. However, in order to override the data files on the tape, the user can create a diskette with the desired files.

The **mkszfile** command checks to be sure there is at least 8MB of free space available in the /tmp file system for the boot image.

Note: Before running the mkszfile command, ensure that enough space is available in the /tmp file to store a boot image. This space is needed during both backup and installation. To determine the amount of space needed in the /tmp file, issue the following command:

Flags

Creates map files that specify the mapping of the logical-to-physical partitions for each logical volume in the volume group. This mapping can be used to allocate the same logical-to-physical mapping when the image is restored. The map file locations are stored in the MAPFILE field in the /image.data file for each logical volume. Sufficient space would exist in the /tmp file system for map creation because the installation routines place the maps in the /tmp file system before issuing the mklv command.

For example, for the hd7 logical volume, the location of the map file is /tmp/vgdata/rootvg/hd7.map. The MAPFILE field in the /image.data file for the hd7 logical volume is under the entry MAPFILE=/tmp/vgdata/ rootvg/hd7.map.

The map files in the backup image are copied after the /bosinst.data and /image.data files.

-X Expands /tmp if needed.

Files

/usr/bin/mkszfile

Contains the mkszfile command.

Related Information

The **mksysb** command.

The /image.data file.

mktcpip Command

Purpose

Sets the required values for starting TCP/IP on a host.

Syntax

mktcpip { -S Interface | -h HostName -a Address -i Interface [-s] [-m SubnetMask] [-r RingSpeed] [-t CableType | [-g DefaultGateway | [-n NameServerAddress [-d Domain]] [[-c Subchannel] -D Destination 1 }

Description

The **mktcpip** command sets the required minimal values required for using TCP/IP on a host machine. These values are written to the configuration database.

Note: The **mktcpip** command currently supports IPv4 only.

The basic functions of the **mktcpip** command include:

- Setting the host name in both the configuration database and the running machine.
- · Setting the IP address of the interface in the configuration database.
- · Making entries in the /etc/hosts file for the host name and IP address.
- Setting the domain name and IP address of the nameserver, if applicable.
- Setting the subnetwork mask, if applicable.
- · Adding a static route to both the configuration database and the running machine, if applicable.
- Starting the specified TCP/IP daemons.

You can use the Network application in Web-based System Manager (wsm) to change network characteristics. You could also use the System Management Interface Tool (SMIT) smit mktcpip fast path to run this command.

Flags

-a Address Sets the Internet address of the host. Specify the address in dotted decimal

> notation. Each network interface on the host should have a unique Internet address. The following is the standard format for setting the Internet address:

127.10.31.2

-c Subchannel Specifies the subchannel address for a System/370 channel adapter.

-D Destination Sets the destination address for a static route. Specify the address in dotted

decimal notation. The following is the standard format for setting the

destination address for a static route:

192.9.52.1

-d Domain Specifies the domain name of the name server the host should use for name

resolution, if any. The domain name should be in the following format:

subdomain.subdomain.rootdomain

-g DefaultGateway Adds the default gateway address to the routing table. Specify the address in

dotted decimal notation. The following is the standard format for setting the

default gateway address:

192.9.52.0

-h HostName Sets the name of the host. If using a domain naming system, the domain and

any subdomains must be specified. The following is the standard format for

setting the host name:

hostname

The following is the standard format for setting the host name in a domain

naming system:

hostname.subdomain.subdomain.rootdomain

-i Interface Specifies a particular network interface, for example:

-m SubnetMask Specifies the mask the gateway should use in determining the appropriate

> subnetwork for routing. The subnet mask is a set of 4 bytes, as in the Internet address. The subnet mask consists of high bits (1s) corresponding to the bit

positions of the network and subnetwork address, and low bits (0s)

corresponding to the bit positions of the host address.

-n NameServerAddress Specifies the Internet address of the name server the host uses for name

resolution, if applicable. The address should be entered in dotted decimal

notation, as follows:

127.1.0.1

Specifies the ring speed for a token-ring adapter. Valid values for the -r RingSpeed

RingSpeed variable are either 4- or 16-Mbps.

-S Interface Retrieves information for System Management Interface Tool (SMIT) display.

Starts the TCP/IP daemons.

-t CableType Specifies cable size for Standard Ethernet or IEEE 802.3 Ethernet networks.

Valid values for the CableType variable are dix for thick cable, bnc for thin cable, or N/A for Not Applicable. The -t CableType flag should be used only

for Standard Ethernet (en) and IEEE 802.3 Ethernet (et) interfaces.

Examples

To set the required values for starting TCP/IP enter:

mktcpip -h fred.austin.century.com -a 192.9.200.4 -i en0 \ -n 192.9.200.1 -d austin.century.com -s

Note: Use the mktcpip command only to minimally configure TCP/IP for the first time. For further configuration changes, use the **smitty configtop** fastpath.

Files

/usr/bin/mktcpip Contains the **mktcpip** command.

/etc/resolv.conf Contains the default system configuration database. /etc/hosts Contains the host name and IP address entries.

Related Information

The **hostname** command, **hostent** command.

The **resolv.conf** file format.

TCP/IP name resolution in *Networks and communication management*.

TCP/IP addressing in Networks and communication management.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

System management interface tool in Operating system and device management.

mkts Command

Purpose

Makes a thin server.

Syntax

mkts -i ipaddress -m subnetmask -g gateway [-s speed] [-d duplex] -c cosi [-p size] [-H | -h] [-t] [-t] [-v] thinserver

Description

The **mkts** command creates a thin server so that it can use the common image created with the **mkcosi** command. When a thin server is created, several directories are also created for the thin server to mount and use, including /root, /dump, /home, /tmp, /shared_home, and /paging. If you specify the -I flag when creating a thin server, the resulting thin server is a diskless client. That is, all resources are created on the server that calls the mkts command, except for the /root directory, which is created on the server storing the common image. However, if you do not specify the -I flag, the thin server is a dataless client. In this case, only the /root directory is created on the server storing the common image; all other directories are created locally on the thin server. If necessary, the 512 MB default size used for the paging can be changed by specifying a size value with the -p flag.

Flags

-c cosi Specifies the common image for the thin server to obtain its operating system, which is required for the thin server to start up and run. Specifies the duplex setting (optional). Use this setting to -d duplex configure the client's network interface. This value can be full or half. **-g** gateway Specifies the thin server gateway. Defines or uses home resource. The home resource is a network installation management (NIM) home resource. It is a directory that is created on a NIM master or any NIM resource server. The directory is exported to the thin server to be mounted and used. It is basically the thin server's /home directory. -H Defines or uses shared_home resource. The shared_home resource is a network installation management (NIM) resource. It is a directory that is shared among all thin servers. The directory is exported and mounted on the clients from the NIM master. -i ipaddress Specifies a thin server IP address or hostname.

-1

Specifies whether local resources are used when configuring the thin server. If you specify this flag, all resources are created remotely from the thin server. If you do not specify this flag, only the /root resource is created remotely from the thin server, and all other resources are created locally on the thin server.

Specifies the thin server subnet mask.

Specifies the size (in megabytes) of the paging space for the thin server. The minimum size is 64 MB of paging space. The default size is 512 MB of the paging space. If you specify the size less than 64 MB, 512 MB is used.

Specifies speed setting (optional). This is the

communication speed to use when configuring the client's network interface. This value can be 10, 100, or 1000.

Defines or uses the TMP resource.

Enables verbose debug output when the mkts command

runs.

-s speed

-p size

-m subnetmask

-t

Exit Status

The command completed successfully.

>0 An error occurred.

Security

Access Control: You must have root authority to run the mkts command.

Examples

1. To define a thin server called lobo and have it use a common image called cosil for its operating system with an IP address of 9.3.6.234, a subnet mask of 255.255.25.0, and a gateway of 9.3.6.1, enter:

mkts -i 9.3.6.234 -m 255.255.255.0 -g 9.3.6.1 -c cosil lobo

Location

/usr/sbin/mkts

Files

/etc/niminfo Contains variables used by NIM.

Related Information

The dbts command, "lsts Command" on page 449, "mkcosi Command" on page 571, nim command, nim_clients_setup command, nim_master_setup command, nimconfig command, rmcosi command, swts command.

mktun Command

Purpose

Activates tunnel(s).

Syntax

mktun [-v 4|6] [-t tid_list] [-i] [-l]

Description

Use the **mktun** command to activate tunnel(s). For IBM tunnels, this command initiates the security protocol exchanges between the local and the destination host.

Flags

- -i Initiation flag. If the -i flag is not used, all the tunnels in the tunnel database (or those listed with the -t flag) will be activated. If the -i flag is used, only the tunnels whose tunnel definitions status in the tunnel database "active" will be activated.
- -I If the -I flag is specified, manual tunnels will be activated.
- -t If the -t flag is specified, only the tunnel(s) that follows this flag will be activated. If the -t flag is not used, all tunnel(s) currently defined in the tunnel database will be activated. The *tid_list* can be a single tunnel ID or a sequence of tunnel IDs separated by "," or "-" (1, 3, 5-7).
- The IP version of the tunnels to be activated. The value of **4** specifies IP version 4 tunnels. The value of **6** specifies IP version 6 tunnels. If the **-v** flag is not used, all tunnels for IP version 4 and IP version 6 will be activated.

Related Information

The **chtun** command, **exptun** command, **gentun** command, **imptun** command, **Istun** command, **rmtun** command.

mkuser Command

Purpose

Creates a new user account.

Syntax

mkuser [-R load_module] [-a] [Attribute=Value ...] Name

Description

The **mkuser** command creates a new user account. The *Name* parameter must be a unique string (whose length is administrator-configurable via the **chdev** command). You cannot use the **ALL** or **default** keywords in the user name. By default, the **mkuser** command creates a standard user account. To create an administrative user account, specify the **-a** flag.

To create a user with an alternate Identification and Authentication (I&A) mechanism, the **-R** flag can be used to specify the I&A load module used to create the user. Users created without the **-R** flag are created locally. Load modules are defined in the **/usr/lib/security/methods.cfg** file.

The **mkuser** command does not create password information for a user. It initializes the **password** field with an * (asterisk). Later, this field is set with the **passwd** or **pwdadm** command. New accounts are disabled until the **passwd** or **pwdadm** commands are used to add authentication information to the **/etc/security/passwd** file.

You can use the Users application in Web-based System Manager to change user characteristics. You could also use the System Management Interface Tool (SMIT) **smit mkuser** fast path to run this command.

The mkuser command always checks the target user registry to make sure the ID for the new account is unique to the target registry. The mkuser command can also be configured to check all user registries of the system using the dist_uniqid system attribute. The dist_uniqid system attribute is an attribute of the usw stanza of the /etc/security/login.cfg file, and can be managed using the chsec command.

The **dist uniqid** system attribute has the following values:

- never Does not check for ID collision against the non-target registries. This is the default setting.
- · always Checks for ID collision against all other registries. If collision is detected between the target registry and any other registry account creation or modification fails.
- uniqbyname Checks for ID collision against all other registries. Collision between registries is allowed only if the account to be created has the same name as the existing account.

Note: ID collision detection in the target registry is always enforced regardless of the dist_uniqid system attribute.

The uniqbyname system attribute setting works well against two registries. With more than two registries, and with ID collision already existing between two registries, the behavior of the mkuser command is unspecified when creating a new account in a third registry using colliding ID values. The new account creation might succeed or fail depending the order in which the registries are checked.

The check for ID collision only enforces ID uniqueness between the local registry and remote registries or between remote registries. There is no guarantee of ID uniqueness between the newly created account on the remote registry and existing local users on other systems that make use of the same remote registry. The **mkuser** command bypasses a remote registry if the remote registry is not reachable at the time the command is run.

Restrictions on Creating User Names

To prevent login inconsistencies, you should avoid composing user names entirely of uppercase alphabetic characters. While the **mkuser** command supports multi-byte user names, it is recommended that you restrict user names to characters with the POSIX portable filename character set.

To ensure that your user database remains uncorrupted, you must be careful when naming users. User names must not begin with a - (dash), + (plus sign), @ (at sign), or ~ (tilde). You cannot use the keywords ALL or default in a user name. Additionally, do not use any of the following characters within a user-name string:

- Colon
- Double quote
- Pound sign
- Comma
- Equal sign
- Back slash
- Slash
- Question mark
- Single quote
- Back quote

Finally, the *Name* parameter cannot contain any space, tab, or new-line characters.

Flags

Specifies that the user is an administrator. Only the root user can use this flag or alter the attributes of an administrative user.

-R load_module Specifies the loadable I&A module used to create the user.

Parameters

Attribute=Value Initializes a user attribute. Refer to the chuser command for the valid attributes and

Name Specifies a unique string. The length of this string is set by an administrator by using

the chdev command.

Exit Status

This command returns the following exit values:

The command runs successfully and all requested changes are made.

>0 An error occurred. The printed error message lists further details about the type of

failure.

Security

Access Control: This command should grant execute (x) access only to the root user and members of the security group. This command should be installed as a program in the trusted computing base (TCB). The command should be owned by the root user with the setuid (SUID) bit set.

Files Accessed:

Mode File /etc/passwd rw /etc/security/user rw /etc/security/user.roles rw /etc/security/limits rw /etc/security/environ

/etc/group rw

/etc/security/group rw

/usr/lib/security/mkuser.default /usr/lib/security/mkuser.sys

Auditing Events:

Information **Event**

USER_Create user

Limitations

Creating a user may not be supported by all loadable I&A modules. If the loadable I&A module does not support creating a user, an error is reported.

Examples

1. To create the davis user account with the default values in the /usr/lib/security/mkuser.default file, type:

mkuser davis

2. To create the davis account with davis as an administrator, type:

mkuser -a davis

Only the root user or users with the UserAdmin authorization can create davis as an administrative user.

3. To create the davis user account and set the **su** attribute to a value of false, type:

mkuser su=false davis

4. To create the davis user account that is identified and authenticated through the LDAP load module,

mkuser -R LDAP davis

Files

/usr/bin/mkuser Contains the mkuser command.

/usr/lib/security/mkuser.default Contains the default values for new users. /etc/passwd Contains the basic attributes of users. Contains the extended attributes of users. /etc/security/user

/etc/security/user.roles Contains the administrative role attributes of users.

/etc/security/passwd Contains password information.

/etc/security/limits Defines resource quotas and limits for each user. /etc/security/environ Contains the environment attributes of users. /etc/group Contains the basic attributes of groups. /etc/security/group Contains the extended attributes of groups.

/etc/security/.ids Contains standard and administrative user IDs and group IDs.

Related Information

The **chfn** command, **chgroup** command, **chgrpmem** command, **chsh** command, **chuser** command, Isgroup command, Isuser command, mkgroup command, mkuser.sys command, passwd command, pwdadm command, rmgroup command, rmuser command, setgroups command, setsenv command.

For more information about the identification and authentication of users, discretionary access control, the trusted computing base, and auditing, refer to the Security.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

For more information about administrative roles, refer to Administrative roles in Security.

mkuser.sys Command

Purpose

Customizes a new user account.

Syntax

mkuser.sys Directory User Group Shell

Description

The mkuser.sys command customizes the new user account specified by the User parameter. The mkuser command calls the mkuser.sys command after it has created and initialized the new account. The tsm, login, and getty commands and the pam mkuserhome module call the mkuser.sys command at your login time if you do not have a home directory already.

The program as shipped creates the home directory specified by the *Directory* parameter, with the owner specified by the *User* parameter, the primary group specified by the *Group* parameter, and a copy of the

appropriate profile for the user's shell. The shipped program can be replaced at installation by another program to customize local new-user creation. The installation-specific program should adhere to the error conventions of the supplied program.

Security

Access Control: This command should grant read (r), write (w), and execute (x) access for the root user and members of the security group.

Files Accessed:

Mode File

/etc/passwd /etc/security/user

Files

/usr/lib/security/mkuser.sys

Contains the mkuser.sys command.

Related Information

The **mkuser** command, **tsm** command, **login** command, **getty** command.

The pam mkuserhome module.

For more information about the identification and authentication of users, discretionary access control, the trusted computing base, and auditing, refer to the Security.

mkvg Command

Purpose

Creates a volume group.

Syntax

mkvg [-B][-t factor][-S[-v LogicalVolumes][-P Partitions]][-C][-G][-f][-i][-i][-c][-x][-L LTGSize | [-n] [-s Size | [-V MajorNumber | [-y VolumeGroup | PhysicalVolume ...

Description

The mkvg command creates a new volume group, using the physical volumes represented by the PhysicalVolume parameter. After creating the volume group, the **mkvg** command automatically varies on the new volume group using the varyonvg command. The exception to this fact is when the volume group is created with the -C flag. When the volume group is successfully created, the volume group will not be varied on automatically. Instead, the user must manually varyon the volume group.

The mkvg command by default creates a volume group that can accommodate 255 logical volumes and 32 physical volumes (disks). These limits can be extended by specifying either the -B or -S flag.

The mkvg command will attempt to determine a proper partition size (-s) and factor (-t) if none is specified on the command line.

Note: If a volume group is created with the -B option, it cannot be imported into AIX 4.3.1 or lower versions. If a volume group is created with the -S option, it cannot be imported into AIX 5.2 or lower versions.

Notes:

- 1. The physical volume is checked to verify that it is not already in another volume group. If the **mkvq** command determines the physical volume belongs to a volume group that is varied on, it will exit without creating the volume group. If the **mkvg** command determines the physical volume belongs to a volume group that is not varied on, the force option (-f) must be used to create the volume group. When using the force option, the previous contents of the physical volume are lost, so the user must use caution when using the force option.
- 2. To use this command, you must either have root user authority or be a member of the system group.
- 3. When creating the default VG type (with a maximum of 32 PVs) or the big VG type (with a maximum of 128 PVs), there is a limitation of 1016 physical partitions per PV. When specifying the physical partition size (-s), make sure the value is set large enough so that 1016 physical partitions per PV limit is not violated. For example, a partition size of at least 16 MB would be needed to create a volume group with a 10 GB disk. Using a factor size (-t) of 2, a smaller partition size of 8 MB can be used. If a factor value is specified, the maximum number of PVs that can be included in the volume group is MaxPVs/factor.
- 4. Whenever you create a volume group, the operating system automatically does a varyon. However if you create a volume group with the -C flag, the system will not autovaryon the volume group at the end of the Concurrent Capable volume group creation. Instead, the mkvq command notifies you to manually varyonvg the volume group in either non-concurrent or concurrent mode.
- 5. This command will fail to add a disk to the volume group if the disk indicates that it is managed by a third party volume manager. To override and clear the disk of the third party volume manger use chpv -C HDiskName.
- 6. On AIX 5.2 and later only Enhanced Concurrent Capable volume groups will be created when the -c or -C flags are specified.

Because the VGDA space has been increased substantially, every VGDA update operation (creating a logical volume, changing a logical volume, adding a physical volume, and so on) might take considerably longer to run.

You can use the Volumes application in Web-based System Manager to change volume characteristics. You could also use the System Management Interface Tool (SMIT) smit mkvg fast path to run this command.

Flags

-C

-C

-B Creates a Big-type volume group. This can accommodate up to 128 physical volumes and 512 logical volumes.

> Note: Because the VGDA space has been increased substantially, every VGDA update operation (creating a logical volume, changing a log ical volume, adding a physical volume, and so on) may take considerably longer to run.

Same as -C flag. On AIX 5.2 and later only Enhanced Concurrent Capable volume groups will be created.

Creates an Enhanced Concurrent Capable volume group. Only use the -C flag with the HACMP™ ES. It is not usable on volume groups and systems not using the HACMP ES product.

Use this flag to create an Enhanced Concurrent Capable volume group.

- 1. Enhanced Concurrent volume groups use Group Services. Group Services ships with HACMP ES and must be configured prior to activating a volume group in this mode.
- 2. Only Enhanced Concurrent Capable volume groups are supported when running with a 64 bit kernel. Concurrent Capable volume groups are not supported when running with a 64 bit kernel.

-f

-G

-i

-1

Forces the volume group to be created on the specified physical volume unless the physical volume is part of another volume group in the Device Configuration Database or a volume group that is active.

Same as -B flag.

Reads the *PhysicalVolume* parameter from standard input.

Creates a volume group that can be imported to AIX 5.1 and AIX 5.2. The LTGSize will behave as if the volume group had been created prior to AIX 5.3. If the logical volumes are later created with a strip size that is larger than the supported strip size on AIX 5.1 or AIX 5.2 (a strip size multiplied by the number of disks in an array equals the stripe size), then attempting to import the volume group back to AIX 5.1 or AIX 5.2 is not supported.

For volume groups created on AIX 5.3 without the -I flag, the -L flag is ignored. When the volume group is varied on the logical track group size will be set to the common max transfer size of the disks.

For volume groups created on AIX 5.3 with the -I flag or for volume groups created prior to AIX 5.3, the logical track group size is set to the LTGSize, which must be 128, 256, 512, or 1024. In addition, it should be less than or equal to the maximum transfer size of all disks in the volume group. The default LTGSize is 128 kilobytes.

Specifies that the volume group is not automatically available during a system restart. The default value activates the volume group automatically.

Total number of partitions in the volume group, where the *Partitions* variable is represented in units of 1024 partitions. Valid values are 32, 64, 128, 256, 512 768, 1024 and 2048. The default is 32 k (32768 partitions). The chvg command can be used to increase the number of partitions up to the maximum of 2048 k (2097152 partitions). This option is only valid with the -S option.

Creates a Scalable-type volume group. By default, this volume group can accommodate up to 1024 physical volumes, 256 logical volumes and 32768 physical partitions. To increase the number of logical volumes, use the -v option. To increase the number of physical partitions, use the -P option.

Note: Increasing maxivs and maxpps beyond the default values for a scalable volume group can significantly increase the size of the VGDA proportionately. The maxivs and maxpps values should only be increased as needed because they cannot be decreased. Meanwhile, as the VGDA space increases all VGDA update operations (creating a logical volume, changing a logical volume, adding a physical volume, and so on) can take longer and longer to run.

Sets the number of megabytes in each physical partition, where the Size variable is expressed in units of megabytes from 1 (1 MB) through 131072 (128 GB). The Size variable must be equal to a power of 2 (example 1, 2, 4, 8). The default value for 32 and 128 PV volume groups will be the lowest value to remain within the limitation of 1016 physical partitions per PV. The default value for scalable volume groups will be the lowest value to accommodate 2040 physical partitions per PV.

Changes the limit of the number of physical partitions per physical volume, specified by factor. The factor should be between 1 and 16 for 32 PV volume groups and 1 and 64 for 128 PV volume groups. The maximum number of physical partitions per physical volume for this volume group changes to factor x 1016. The default will be the lowest value to remain within the physical partition limit of factor x 1016. The maximum number of PVs that can be included in the volume group is MaxPVs/factor. The -t option is ignored with the -S option.

Specifies the major number of the volume group that is created.

Number of logical volumes that can be created. Valid values are 256, 512, 1024, 2048 and 4096. The default is 256. The chvg command can be used to increase the number of logical volumes up to the maximum of 4096. This option is only valid with the **-S** option. The last logical volume is reserved for metadata. This flag is ignored. On AIX 5.2 and later only Enhanced Concurrent Capable volume groups will be created.

-L LTGSize

-n

-P Partitions

-S

-s Size

-t factor

-V MajorNumber

-v

-x

-y VolumeGroup

Specifies the volume group name rather than having the name generated automatically. Volume group names must be unique system wide and can range from 1 to 15 characters. The name cannot begin with a prefix already defined in the PdDv class in the Device Configuration database for other devices. The volume group name created is sent to standard output.

The volume group name can only contain the following characters: "A" through "Z," "a" through "z," "0" through "9," or "_" (the underscore), "-" (the minus sign), or "." (the period). All other characters are considered invalid.

Examples

1. To create a volume group that contains three physical volumes with partition size set to 1 megabyte.

```
mkvg -s 1 hdisk3 hdisk5 hdisk6
```

The volume group is created with an automatically generated name, which is displayed and available at system restart time.

```
mkvg -s 2 -t 2 -y newvg hdisk1
```

The volume group newvg is created with a physical partition size of 2MB and maximum number of physical partitions per physical volume of 2032. The above configuration means that the size of hdisk1 could not be larger than 4064MB (2032*2)

2. To create a volume group that can accommodate a maximum of 1024 physical volumes and 2048 logical volumes, type:

```
mkvg -S -v 2048 hdisk6
```

Files

/usr/sbin Directory where the **mkvg** command resides.

/tmp Directory where the temporary files are stored while the command is running. /dev Directory where the character device entry for the volume group is created.

Related Information

The **chvg** command, **Isvg** command, **varyonvg** command.

The Logical volume storage in *Operating system and device management*.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

The System management interface tool in *Operating system and device management*.

mkvgdata Command

Purpose

Creates a file containing information about a volume group for use by the **savevg** and **restvg** commands.

Syntax

mkvgdata [-X] [-m] VGName

Description

The mkvgdata command creates a file containing information about a volume group for use by the savevg and restvg commands. The information includes the list of logical volumes, file systems and their sizes, and the volume group name. One of the following files is created, depending on the type of volume group:

/image.data Created for information about the root volume group (rootvg). The savevg command uses this

file to create a backup image that can be used by the bosinstall routine to reinstall the volume group to the current system or to a new system. The mkvgdata command overwrites this file if

it already exists. The /image.data file is located in the / directory.

Created for information about a user volume group. The vgname variable reflects the name of vgname.data

> the volume group. The savevg command uses this file to create a backup image that can be used by the restvg command to reinstall the user volume group. The mkvgdata command

overwrites this file if it already exists. The vaname.data file is located in the /tmp/vgdata/vgname directory, where vgname is the volume group name.

The information in either of these files can be edited by the user before issuing the savevg command.

Flag

Creates map files that specify the mapping of the logical-to-physical partitions for each logical volume in -m the volume group. This mapping can be used to allocate the same logical-to-physical mapping when the image is restored. The map file locations are stored in the MAPFILE field in the /image.data file for each

> logical volume. Sufficient space would exist in the /tmp file system for map creation because the installation routines place the maps in the /tmp file system before issuing the mklv command.

For example, for the hd7 logical volume, the location of the map file is /tmp/vgdata/rootvg/hd7.map.

The MAPFILE field in the /image.data file for the hd7 logical volume is under the entry

MAPFILE=/tmp/vgdata/rootvg/hd7.map.

The map files in the backup image are copied after the image.data or vgname.data files.

-X Expands /tmp if needed.

vgname Name of volume group to backup.

Files

/image.data Created when the volume group is **rootvg**.

/tmp/vgdata/vgname/vgname.data Created when the volume group is not rootvg and where

vgname is the name of the volume group.

Related Information

The **mkszfile** command, **restvg** command, **savevg** command.

mkvirprt Command

Purpose

Makes a virtual printer.

Syntax

mkvirprt [-A AttachmentType] -d QueueDevice -n Device -q PrintQueue -s DataStream -t PrinterType -T

mkvirprt - A AttachmentType

Description

The **mkvirprt** command creates a virtual printer definition and assigns it to the specified print gueue and queue device. A virtual printer definition is a set of attribute values that describe a particular data stream for a particular printer. Before a print job can be gueued with the eng command, qprt command, lp command, or Ipr command, a virtual printer definition must be created for the printer's print queue and queue device.

Printers that support only one printer data stream, such as the 4201-3 Proprinter III, need only one virtual printer defined. Printers that support multiple printer data streams, such as the IBM 4216-31 Page Printer II, need a virtual printer defined for each data stream.

To create a virtual printer definition for a printer attached to an ASCII terminal, use the -T flag with the mkvirprt command.

After a virtual printer definition is created, its attribute values can be displayed with the Isvirprt command and changed with the **chvirprt** command.

The mkvirprt command becomes interactive if only the -A flag is specified with the command. Prompts are issued requesting the necessary parameter values. Prerequisite spooler queues and spooler queue devices are generated automatically, and all virtual printer definitions needed for the printer are defined with a single invocation of the **mkvirprt** command for the specified attachment type.

When the first prompt asks for a device name, if the device name entered is not that of a printer, or if an * (asterisk) precedes the device name, a list of printers is displayed. Otherwise, the printer type is assumed to be the same as that of the device.

Also, when a prompt asks for a print queue name, the queue name entered may optionally be followed by a colon and a queue device name. If no queue device name is provided, the queue device name is assumed to be the same as the device name.

Note: Queue and device names must begin with an alphabetic character.

You can use the Printer Queues application in Web-based System Manager (wsm) to change printer characteristics. You could also use the System Management Interface Tool (SMIT) smit mkvirprt fast path to run this command.

Flags

-A AttachmentType Specifies the type of printer attachment. The most common values for the AttachmentType variable value are:

Attachment Type

Represents

local Locally connected printers

remote Remote print queues

Printers attached to an ASCII terminal ascii file Print output redirected to a regular file.

This flag is optional, and if the -A flag is not specified the default attachment type is file. If the -A flag is the only flag specified on the command line, the mkvirprt command goes into interactive mode and executes steps specified in the corresponding .config file.

Specifies the name of an existing queue device to which the virtual printer is assigned.

-d QueueDeviceName

-n DeviceName Specifies the name of the printer device. Device names include Ip0 for printer 0,

Ip1 for printer 1, and so on.

Specifies the special file name of an existing print queue to which the virtual -q PrintQueueName

printer is to be assigned. Note that you do not have to specify the path name to

the file, such as the /dev/lp0 file, you just need to specify lp0.

Specifies the printer data stream type. Data stream types include: -s DataStreamType

> Type Description

Extended ASCII asc

ps **PostScript**

pcl Hewlett-Packard PCL

630 Diablo 630

855 Texas Instruments 855 Hewlett-Packard GL gl

Kanji

-t PrinterType Specifies the printer type. Printer types include 4201-3, ti2115, and so on. For

more information on available printer types, see Installing support for additional

printers and Printer-specific information in Printers and printing.

Specifies that the printer is attached to an ASCII terminal.

Examples

-T

1. To make a virtual printer for the asc printer data stream for the 4029 printer attached locally, enter: mkvirprt -A local -d mypro -n lp0 -q proq -s asc -t 4019

2. To make a virtual printer for a printer connected to an ENA 4033 network adapter, and to be prompted for the parameter values, enter:

mkvirprt -A ena

Files

/usr/sbin/mkvirprt Contains the mkvirprt command. Contains configuration files. /etc/qconfig

/usr/lib/lpd/pio/predef/* Contains predefined printer attribute files.

/var/spool/lpd/pio/@local/custom/* Contains customized virtual printer attribute files.

/usr/lib/lpd/pio/etc/*.attach Contains attachment type files.

/usr/lib/lpd/pio/etc/*.config Contains the configuration file for the printer. /var/spool/lpd/pio/@local/ddi* Contains digested virtual printer attribute files.

Related Information

The chvirprt command, Ip command, Ipr command, Isvirprt command, mkque command, mkquedev command, qprt command, rmvirprt command.

The **/etc/qconfig** file.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

Printing administration in Printers and printing.

Print spooler in Printers and printing.

Printer-specific information in *Printers and printing*.

Installing support for additional printers in Printers and printing.

Virtual printer definitions and attributes in *Printers and printing*.

Printer Addition Management Subsystem: Programming Overview in AIX 5L Version 5.3 Kernel Extensions and Device Support Programming Concepts.

mm Command

Purpose

Prints documents formatted with memorandum macros.

Syntax

mm [-M Media] [-c] [-e] [-E] [-t] [-12] [-TName] { File ... | - }

Description

The mm command formats documents that use the nroff command and the mm macro package. The mm command has flags that specify preprocessing by the tbl and negn commands and postprocessing by various terminal-oriented output filters. The proper pipelines and the required flags for the nroff command are generated depending on the flags that are selected.

Notes:

- 1. Use the -oList flag of the nroff command to specify ranges of output pages. Remember that if the **mm** command is called with the **-e**, **-t**, or **-** (minus sign) flags together with the **-o**List flag, and if the last page of the document is not specified by the List variable, you may receive a broken pipe message. This message is not an indication of any problem and can be ignored.
- 2. The mm command calls the nroff command with the -h flag. With this flag, the nroff command assumes that the workstation has tabs set every 8 character positions.
- 3. If you use the -s flag of the nroff command (to stop between pages of output), use a linefeed (rather than the Enter key or a newline character) to restart the output. The -s flag of the nroff command does not work with the -c flag of the mm command or if the mm command automatically calls the col command.
- 4. Providing inaccurate information to the mm command about the kind of workstation its output is to be printed on will produce unsatisfactory results. However, if you are redirecting output to a file, use the -T37 flag. Then, use the appropriate workstation filter when you print the file.

To obtain a list of mm command flags, enter the command name with no parameters. The flags can occur in any order, but they must come before the File parameter. Any other flags (for instance, -rANumber) are passed to the **nroff** command.

Flags

-M Media

Specifies a paper size in order to determine the amount of imageable area on the paper. Valid values for the Media variable are:

Α4 Specifies a paper size of 8.27 X 11.69 inches (210 X 297 mm).

B5 Specifies a paper size of 6.93 X 9.84 inches (176 X 250 mm).

EXEC Specifies a paper size of 7.25 X 10.5 inches (184.2 X 266.7 mm).

LEGAL Specifies a paper size of 8.5 X 14 inches (215.9 X 355.6 mm).

LETTER

Specifies a paper size of 8.5 X 11 inches (215.9 X 279.4 mm). This is the default value.

Note: The *Media* variable is not case sensitive.

-C Calls the col command. Note that the col command is called automatically by the mm command for the following terminal names. The following devices can be specified by the -TName flag, the \$TERM shell variable, or by using the default:

- ppds
- Ip
- 2631
- 8510
- -e Calls the negn command; also causes the negn command to read the /usr/share/lib/pub/eqnchar file. See the eqnchar file format.
- -E Calls the **-e** flag of the **nroff** command.
- -t Calls the tbl command.
- Uses 12-pitch font. Use this when the \$TERM shell variable is set to 300, 300s, 450, or 1620. (The -12 pitch switch on the DASI 300 and 300s workstations must be manually set to 12 if this flag is used.)
- -TName Uses the workstation type specified by the *Name* variable.

By default, the mm command uses the value of the \$TERM shell variable from the environment as the value of the Name variable. If the **\$TERM** shell variable is not set, the **mm** command uses **Ip** (the generic name for printers that can underline and tab). If several workstation types are specified, the last one listed applies.

Forces input to be read from standard input.

Parameters

File Specifies the file that the **mm** command formats.

Examples

1. When the **\$TERM** shell variable is set in the environment to the **hplj** command, the following two command lines are equivalent:

```
mm -t -rC3 File
tbl File | nroff -mm -Thplj -h -rC3
```

2. The mm command reads the standard input when you specify a - (minus sign) flag instead of a value for the File variable. This option allows you to use the mm command as a filter, as follows:

```
cat File | mm -
```

Note: Using other files together with a - (minus sign) flag leads to undesired results.

Environment Variables

\$TERM Specifies the terminal names.

Files

/usr/share/lib/pub/eqnchar

Contains special character definitions for the eqn command and the neqn command.

Related Information

The col command, env command, eqn command, greek command, hplj command, mmt command, negn command, **nroff** command, **tbl** command.

The eqnchar file, profile file.

The **nterm** file format describes terminal driving tables for the nroff command.

The article "mm Macro Package for the mm, mmt, nroff, and troff Commands" in the troff Command.

mmt Command

Purpose

Typesets documents.

Syntax

mmt [-M Media] [-a] [-c] [-e] [-g] [-p] [-t] [-z] [-TName | -DDestination] [File | -]

Description

Similar to the mm command, the mmt command typesets its input using the troff command, rather than formatting it with the **nroff** command. The **mmt** command uses the **mm** macro package. There are flags to specify preprocessing by the tbl, pic, eqn, and grap commands. The proper pipelines, required parameters, and flags for the troff command and the mm macro package are generated, depending on the flags selected.

There are several flags that are specific to the **mmt** command. Any other parameters or flags (for instance, -rANumber or -a) that you give the mmt command are passed to the troff command. You can put flags in any order, but they must be listed before any input files. File specifies the file that the mmt command formats. If you do not give File parameters or other flag variables, the mmt command prints a list of its flags.

The mmt command, unlike the troff command, automatically pipes its output to a postprocessor, unless specifically requested not to do so. The user should not specify a postprocessor when using the mmt command. The precedence is as follows:

- 1. The **-z** flag; no postprocessor is used.
- 2. The **-T**Name flag.
- 3. The **TYPESETTER** environment variable is read.
- 4. The default is set to ibm3816.

The **mmt** command reads standard input when you specify a - (minus sign) instead of any File parameters.

Use the **-o**List flag of the **troff** command to specify ranges of pages to be output.

Note: If you call the mmt command with one or more of the -e, -c, -t, -p, -g, and - (minus sign) flags together with the -oList flag of the troff command, you may receive a broken pipe message if the last page of the document is not specified by the List variable. This broken pipe message is not an indication of any problem and can be ignored.

Flags

-M Media Specifies a paper size in order to determine the amount of imageable area on the paper. Valid values for the Media variable are:

> Specifies a paper size of 8.27 X 11.69 inches (210 X 297 mm). Α4

Α5 Specifies a paper size of 5.83 X8.27 inches (148 X 210 mm).

B5 Specifies a paper size of 6.93 X 9.84 inches (176 X 250 mm).

Specifies a paper size of 7.25 X 10.5 inches (184.2 X 266.7 mm).

LEGAL Specifies a paper size of 8.5 X 14 inches (215.9 X 355.6 mm).

LETTER

Specifies a paper size of 8.5 X 11 inches (215.9 X 279.4 mm). This is the default value.

Note: The *Media* variable is not case sensitive.

Displays readable troff output to the terminal. -a

Preprocesses the input files with the cw command. -C

Calls the eqn command; also causes the eqn command to read the /usr/share/lib/pub/ -е

eqnchar file (see the eqnchar file format).

Calls the grap command, which in turn calls the pic command. -g

Calls the **pic** command. -p -t Calls the tbl command.

-z Starts no output filter to process or redirect the output of the troff command.

-DDestination Directs the output to a device specified by the Destination variable. Supported destination

devices for English-language output is 4014, which is the Tektronix 4014 terminal by way of

the tc command.

-TName Creates output for a troff device as specified by the Name variable. The output is sent

through the appropriate postprocessor.. The default value is ibm3816. Possible Name

variables are:

ibm3812

3812 Pageprinter II.

ibm3816

3816 Pageprinter.

hplj Hewlett-Packard LaserJet II.

ibm5587G

5587-G01 Kanji Printer multi-byte language support.

psc PostScript printer. X100 AlXwindows display.

Forces input to be read from standard input.

Related Information

The cw command, eqn command, grap command, mm command, mvt command, pic command, tbl command, tc command, troff command.

The **eqnchar** file format contains special character definitions for the eqn and negn commands.

The article "mm Macro Package for the mm, mmt, nroff, and troff Commands" in the troff Command.

mmtu Command

Purpose

Displaying, adding, and deleting maximum transfer unit (MTU) values used for path MTU discovery.

Syntax

mmtu { -a Value | -d Value | -s }

Description

Use the mmtu command to display, add, and delete maximum transfer unit (MTU) values to the list of potential path MTU values. Path MTU discovery uses the list of potential path MTU values to detect the path MTU. The list of potential path MTU values is only used when there are routers in the path that do not comply with RFC 1191. The user must have administrative authority to add or delete MTU values.

Flags

Adds the new MTU to the list of potential path MTU values. -a Value -d Value Deletes the value from the list of potential path MTU values. Displays the current list of potential path MTU values.

Examples

1. To add a value to the list of potential path MTU values, enter:

```
mmtu -a mtu-value
```

2. To delete a value from the list of potential path MTU values, enter:

```
mmtu -d mtu-value
```

3. To display the contents of the list of potential path MTU values, enter:

```
mmtu -s
```

Files

/usr/sbin/mmtu

Contains the mmtu command.

Related Information

The **netstat** command, **no** command.

mobip6ctrl Command

Purpose

Configures and manages the mobile IPv6 home agent and correspondent node functionality.

Syntax

mobip6ctrl [-c] [-R] [-b] [-S { 0 | 1 }] [-n { 0 | 1 }] [-l LifeTime] [-a | -d HomeAddress CareOfAddress MyAddress 1

Description

The mobip6ctrl command is used to configure and manage the mobile IPv6 home agent and correspondent node. It can enable and disable NDP proxy and IP security checking, and it can be used to display or modify the mobile IPv6 binding cache.

NDP proxy must be enabled if the system is configured as a home agent. This allows the home agent to intercept packets addressed to mobile nodes that are not currently on their home network.

IP security checking enables checking to ensure that IP security is used for the Binding Update and Binding Acknowledgement messages sent for mobile IPv6. Because these two types of messages have the ability to affect the routing of packets addressed to a mobile node, they would represent a significant security vulnerability if not protected by IP security. If checking is enabled, the mobile IPv6 home agent or correspondent node will discard any Binding Update or Binding Acknowledgement packets that are not protected by IP security.

The mobile IPv6 binding cache on a home agent or correspondent node maps home addresses to the current care-of addresses for each mobile node. This allows the home agent to tunnel traffic to the mobile node at its current location, and allows a correspondent node to send packets directly to a mobile node at its current location. The **mobip6ctrl** command can be used to view the binding cache or manually edit it for debugging purposes.

Normally, this command is used from the **/etc/rc.mobip6** script when mobile IPv6 has been configured using system management.

Flags

-I LifeTime

-n 0 | 1

-S 0 | 1

-R

-a HomeAddress CareOfAddress MyAddress
 -b Adds this entry to the binding cache.
 Displays all binding cache entries.

Compatibility option which enables the support of the mobiles implementing the draft #13 of the *Mobility support in IPv6* specification. Using this option, the home agent or correspondent node will accept the binding update messages sent using a

Destination Option and using an Authentication Header (AH) to protect these packets with IPsec.

-dHomeAddress CareOfAddress MyAddress Delete this entry from the binding cache.

Specifies the default life time value for binding cache entries in

seconds.

Activates or deactivates NDP proxy capabilities. A value of 1 activates the NDP proxy capabilities, and a value of 0 disables NDP

proxy capabilities. The default value is 0. Resets all the binding cache entries.

Enables or disables checking to ensure that IP security is used for all Binding Update and Binding Acknowledgement packets. A value of 1 enables checking, and a value of 0 disables checking. The

default value is 0.

Exit Status

- The command completed successfully.
- >0 An error occurred.

Security

You must be the root user or a member of the system group to execute this command.

Examples

- The following example enables NDP proxy and IP security checking for mobile IPv6: mobipctrl -S 1 -n 1
- 2. The following example displays all entries in the binding cache: mobip6ctrl -b

The output from this command looks similar to the following:

```
BINDING CACHE LIST (1 elem)
Home Address...... 3ffe:300:20:1102::217
Care-Of Address.....: 3ffe:300:20:1101::217
My Address..... 3ffe:300:20:1102::223
Life time..... 518
Time since last usage: 50
Rate limit time....: 0
Retransmit count....: 0
Sequence number....: 14
Registered by me....: 1
```

Related Information

Prefix length..... 64

The kmodctrl command, mobip6reqd command, ndpd-router command, rc.mobip6 command.

The Mobile IPv6 in *Networks and communication management*.

mobip6reqd Daemon

Purpose

Provides the Mobile IPv6 home agent daemon.

Syntax

To run the daemon using the System Resource Controller:

startsrc -s mobip6reqd

To run the daemon without using the System Resource Controller:

mobip6reqd

Description

The mobip6reqd daemon must be running in order for the system to function as a mobile IPv6 home agent. This daemon enables the home agent to perform NDP proxying for mobile nodes. The daemon is normally started automatically by the /etc/rc.mobip6 script if the mobile IPv6 home agent has been enabled using system management.

Exit Status

- The command completed successfully.
- >0 An error occurred.

Security

You must be the root user or a member of the system group to execute this command.

Examples

1. The following example starts the **mobip6reqd** daemon:

```
startsrc -s mobip6reqd
```

2. The following example stops the **mobip6reqd** daemon:

```
stopsrc -s mobip6reqd
```

Related Information

The kmodctrl command, mobip6ctrl command, ndpd-router command, rc.mobip6 command.

The Mobile IPv6 in Networks and communication management.

monacct Command

Purpose

Performs monthly or periodic accounting.

Syntax

/usr/sbin/acct/monacct [-X] [Number]

Description

The **monacct** command performs monthly or periodic accounting. The intervals are set in the **crontab** file. You can set the cron daemon to run the monacct command once each month or at some other specified time period. The **monacct** example shows how to set up this command for use with the **cron** daemon. See the **crontab** command for more information about setting up **cron** files.

The Number parameter indicates which month or other accounting period to process. The default value of the Number parameter is the current month. The monacct command creates summary files in the /var/adm/acct/fiscal file and restarts summary files in the /var/adm/acct/sum file, the cumulative summary to which daily reports are appended.

Note: You should not share accounting files among nodes in a distributed environment. Each node should have its own copy of the various accounting files.

Flags

-X Processes all available characters for each user name instead of truncating to the first 8 characters. The -X flag will also cause the monacct command to use the /var/adm/acct/sumx and /var/adm/acct/ fiscalx directories instead of the /var/adm/acct/sum and /var/adm/acct/fiscal directories.

Security

Access Control: This command should grant execute (x) access only to members of the administrative group.

Example

To produce automatically a monthly accounting report, add the following to the /var/spool/cron/crontabs/ root file:

15 5 1 * * /usr/sbin/acct/monacct

This example shows the instructions that the cron daemon will read and act upon. The monacct command will run at 5:15 (15 5) the first day of each month (1). This command is only one of the accounting instructions normally given to the cron daemon. See Setting up an accounting subsystem in Operating system and device management for more information on typical cron accounting entries.

Files

/usr/sbin/acct /var/adm/acct/fiscal

Contains the accounting commands. Contains accounting data files.

Cumulative daily accounting records. Contains the commands to be run by the cron daemon at regularly scheduled intervals.

Related Information

The acctcms command, prtacet command, acctmerg command, crontab command.

The **cron** daemon.

For more information about the Accounting System, the preparation of daily and monthly reports, and the accounting files, see the System accounting in Operating system and device management.

Setting up an accounting subsystem in Operating system and device management explains the steps you must take to establish an accounting system.

mon-cxma Command

Purpose

Monitor status of 128-port asynchronous subsystem and attached devices.

Syntax

To Display All 128-Port Adapters:

mon-cxma

To Display Syntax or Slots and Bus Information:

mon-cxma { -h | -x }

To Display Specific Slots and Bus Information:

mon-cxma { [-I [LogFile] [-f [DeviceFile]] [-s [SlotNumber]] [-b [BusNumber]] }

Description

The **mon-cxma** command is a software tool which provides a means to monitor the status of serial devices and remote async nodes (RAN) attached to the IBM 128-port asynchronous adapter. It is used for subsystem problem determination and can be accessed locally and remotely via modem. The only restriction on modem access is that the modem can not be physically attached to the 128-port adapter being monitored.

When the user enters the mon-cxma command at the command line, it automatically detects and displays all available 128-port adapters in the system. The bus and slot location within the system is displayed for each adapter and the user can select adapter to monitor.

You can use the Software application in Web-based System Manager (wsm) to run this command. You could also use the System Management Interface Tool (SMIT) smit 128psync fast path to advance directly to the "128-Port Asynchronous Adapter" menu. When run from SMIT, the mon-cxma command automatically displays all available 128-port adapters in the system.

Flags

-b [BusNumber]

Specifies the bus number of the device. Valid values for BusNumber are 0 to (n-1), where n is the number of buses the system has.

-f [DeviceFile] Specifies the device special file. Use this file to look at a specific device driver

without having to make a selection. The default device special file is /dev/cxma0.

-h Shows syntax information.

(Lowercase L) Specifies the file to be used as the log. Use this file to store -I [LogFile]

information from the screen when the IMAGE key is pressed. The default log file is

/tmp/mon-cxma.log.

-s [SlotNumber] Specifies the slot number of the device. Valid values for SlotNumber are 0 to (n-1),

where n is the number of slots the system has.

Shows the POS (Programmable Select Option) register values for all the slots and

buses.

Note: -x and -h ignore other options.

Security

Access Control: Root authority required to run this command.

Auditing Events: N/A

Examples

1. To run the mon-cxma command using the SMITfastpath, enter:

smit 128psync

2. To display all 128-port adapters, enter:

/usr/lbin/tty/mon-cxma

Files

/usr/lbin/tty/mon-cxma Contains the mon-cxma command.

/tmp/mon-cxma.log Contains the log file.

Related Topics

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

monitord Daemon

Purpose

Communicates with the License Use Management server and requests a concurrent-use license for each countable login.

Syntax

monitord [-t Minutes] [-v Version.Release]

Description

The operating system has multiple ways to access the system, and each of them has a different behavior upon exit. The monitord daemon provides a common interface to the License Use Management netlsd. monitord communicates with the License Use Management server and requests a concurrent-use license for each countable login.

Note: The License Use Management licensing mechanism is used only if the system has the floating license mode enabled.

After user logout, monitord requests netlsd to release the specific license the user was using, in order to make it available for further logins.

monitord is started when the chlicense -f on command is used to enable the floating license mode. When the *floating license mode* is enabled, **monitord** is started upon system startup via an entry in /etc/inittab. The default (invoked without -t option) is an interval of fifteen minutes.

The entry in /etc/inittab looks like the following:

monitord:2:once:/usr/sbin/monitord >/dev/console 2>&1

Flags

-t Minutes Sets the value in minutes of the heartbeat interval. A value of 0 sets an infinite

interval. The default is fifteen minutes.

-v Version.Release Enables the *floating license mode* for a license of the specified *Version* and

Release.

moo Command

Purpose

Starts the number-guessing game.

Syntax

moo

Description

The moo command picks a combination of four random, non-repeating numbers. You guess four numbers at the your guess? prompt. Each correct number in an incorrect position in the four number combination scores "cow." Each correct number in the correct position in the four number combination scores a "bull." For example:

```
your guess?
1470
bulls = 0 cows = 1
your guess?
```

In this example, one of the four numbers (1, 4, 7, and 0) is correct but in the incorrect position. None of the numbers are correct and in the correct position.

To quit the game, press the Interrupt (Ctrl-C) or End Of File (Ctrl-D) key sequence.

File

/usr/games Contains the system's games.

Related Information

The arithmetic command, back command, bj command, craps command, fish command, fortune command, hangman command, number command, quiz command, ttt command, turnoff command, turnon command, wump command.

more Command

Purpose

Displays file contents one screen at a time.

Syntax

```
more [ -c ] [ -d ] [ -e ] [ -H ] [ -i ] [ -N ] [ -s ] [ -u ] [ -v ] [ -z ] [ -n Number ] [ -p Subcommand ] [ -t
Tagstring ] [ -W Option ] [ -x Tabs ] [ File ... ]
```

Description

The more command reads files and displays the text one screen at a time. The command pauses after each screen and prints the word More at the bottom of the screen. If you then press a carriage return, the more command displays an additional line. If you press the space bar, the more command displays another full screen of text.

Note: On some terminal models, the more command clears the screen, instead of scrolling.

Instead of naming files to read, you can either redirect or pipe standard output, such as a long directory listing, to the more command. The command adds a % (percent sign) to its prompt when reading from a file rather than a pipe. This provides the percentage of the file (in characters, not lines) that the more command has read.

The more command sets the terminal to NOECHO mode so the output can be continuous. With the exception of the / and ! subcommands, commands that are typed do not normally show up on the terminal. If the standard output is not a terminal, the more command will act just like the cat command, except that a header will be printed before each file in a series.

Environment Variables

Environment variables affect the way the more command works. You can set some environment characteristics in the /etc/environment file and system profile files, such as the .ksh, .csh, and .profile files. Refer to User environment in Operating system and device management for discussions about determining and configuring your system environment.

The more command uses the TERM variable to determine terminal characteristics. If this variable is NULL or not set, the command uses the default terminal type. The /usr/share/lib/terminfo directory contains definitions for terminal characteristics.

By default, the more command window size is 2 lines less than what the system terminal is capable of. The command sets the default window size based on the LINES variable. Also, you can easily adjust the window size for each run of the command by adding the -n flag.

Use the MORE variable to customize the more command with your preferred configuration each time the system starts. This variable accepts more command flags.

Flags

-C	Prevents the screen from scrolling, which makes text easier to read as the more command
	writes to the screen. The system ignores the -c flag if the terminal cannot clear to the end
	of a line.
-d	Prints a massage, appended to the More prompt at the bottom of the screen, about which

Prints a message, appended to the More prompt at the bottom of the screen, about which keys continue, quit, and provide help for the more command. Displays error messages rather than ringing the terminal bell if an unrecognized command is used. This is helpful for inexperienced users.

Exits automatically after displaying the last line of the last file. -6

-H Disables the search pattern highlighting feature by default.

-i Searches for patterns without considering uppercase and lowercase.

Pauses after detecting a page break in the input. If the -1 flag is not used, the more command pauses to accept commands after any line containing a ^L (CTRL-L) character. Also, if a file begins with a FORMFEED, the screen is cleared before the file is printed. Suppresses line numbering. The default display, with line numbers, can slow the more -N command's performance on very large input files. The line numbering feature displays the line number in the = subcommand and passes the line number to the editor (if it is the vi

Configures the more command to display the specified number of lines in the window. Without the -n flag, the more command defaults to two lines less than what the terminal is capable of. For example, on a 24-line terminal, the default is 22 lines. The -n option overrides any values obtained from the environment.

Starts the more command and specified subcommand for each File operand. For example, more -p 50j text1 text2 displays the text1 file at the fiftieth line; then does the same for the text2 file when you finish the first. See "Subcommands" for descriptions of more subcommands.

If the command is a positioning command, such as a line number or a regular expression search, set the current position to represent the final results of the command, without writing any intermediate lines of the file. For example, the two commands:

more -p 1000j filename

more -p 1000G filename

are functionally the same and will start the display with the current position at line 1000. passing the lines that i would write and would scroll off the screen if it had been issued during the file examination.

If the positioning command is unsuccessful, the first line in the file will be the current position.

Reduces multiple blank lines in the output to only one blank line. The -s flag is particularly helpful in viewing output from the **nroff** command.

Displays the portion of the file that contains the specified tag. This flag works only on files containing tags created with the ctags command.

Prevents the **more** command from treating a backspace character as a printable control character (displayed as a ^H (CTRL-H)), suppressing backspacing, underlining, or creating reverse video text for underlined information in a source file. The -u flag also forces the more command to recognize a carriage-return character, if it exists, at the end of a line. Suppresses the graphical translation of nonprinting characters. Without the -v flag, the more command graphically interprets all non-ASCII and most control characters, except Tab, Backspace, and Return. For example, if you do not use the -v flag, the more command displays the non-ASCII characters Ctrl-x as ^X and x as M-x.

Provides the specified *Option* to the **more** command as an extension:

Prevents the more command from sending the terminal initialization string (either the ti termcap or the smcup terminfo capability) before displaying the file. This option also prevents the more command from sending the terminal de-initialization string (either the te termcap or the rmcup terminfo capability) before exiting.

tite Causes the more command to send the initialization and de-initialization strings. This is the default.

These options control whether the more command sends the initialization strings described, which, for certain terminals (such as some xterms), cause the more command to switch to an alternative screen. The effect of switching screens is to erase the display of the file you were viewing.

Sets tab stops at the specified *Tabs* position. The default tab setting is 8 columns.

-p Subcommand

-n Number

-1

-s

-t Tagstring

-u

-v

-W Option

-x Tabs

Graphically displays the Tab, Backspace, and Return control characters. With the **-z** flag, the **more** command translates the Backspace character as ^H, Return as ^M, and Tab as ^T.

Subcommands

-Z

The **more** command accepts subcommands when the command pauses and as parameters for the **-p** flag. Many subcommands take an optional integer, symbolized here by K, which you must enter before the subcommand, with no space between. The **more** command, in the paused state, processes subcommands immediately and does not require you to press the Enter key.

letter.

beginning of the file.

The more command uses the following subcommands:

h v r or ^L R [K](Spacebar)
[K] f or [K] ^F or [K] z
[K] b or [K]^B
[<i>K</i>] d or [<i>K</i>]^ D
[<i>K</i>] u or [<i>K</i>]^ U
[K]j or [K](Enter) or [K]^E
[<i>K</i>] k or [<i>K</i>]^ Y
[<i>K</i>]g
$[\kappa]$ G
[<i>K</i>] p or [<i>K</i>]%
ma-z 'a-z
"
[K]/pattern

Displays a help screen that describes the more subcommands. Starts the vi editor, editing the current file in the current line. Refreshes the display. Refreshes the display and removes buffered input. Moves forward K lines when you press the spacebar. If you do not give a value for K, pressing the spacebar displays the next full screen by default. This spacebar subcommand is the same as [K]**f** or [K]^**F** or [K]**z**. Moves forward K lines, or one full screen if you do not give a Moves backward K lines, or one full screen if you do not give a value for *K*. Moves forward K lines, or half a screen if you do not give a value for *K*. If you give a value for *K*, the **more** command sets the \mathbf{d} and \mathbf{u} scroll size to K lines for the session. Moves backward K lines, or half a screen if you do not give a value for K. If you give a value for K, the **more** command sets the **d** and **u** scroll size to K lines for the session. Moves forward K lines, or one line if you do not give a value for Moves backward K lines, or one line if you do not give a value Moves to the beginning of the file, unless you give a line number for K. The default for K is line number 1. Moves to the last line in the file, unless you give a line number for *K*. The default for *K* is the last line in the file. Moves to the point in the file that is *K* percent of the total file. The default for *K* is one percent, or the first line in the file. Marks the current position in the file with the specified letter.

(Single quote) Moves to the position marked with the specified

(Two single quotes) Returns to the position from which the last large movement (moving more than a page) command was run.

If no such movements have been made, returns to the

default value for K is the first occurrence.

(Slash) Searches forward, from the current position, for the specified occurrence of the specified pattern of characters. The

(Slash, exclamation mark) Searches forward, from the current

[K]/!pattern

[K]?pattern (Question mark) Searches backward, from the current position, for the specified occurrence of the specified pattern of characters. The default value for K is the first occurrence. [K]?!pattern (Question mark, exclamation mark) Searches backward, from the current position, for the specified occurrence of a line that does not contain the specified pattern of characters. The default value for *K* is the first occurrence. [*K*]n Repeats the last search, specifying an occurrence of the pattern (or an occurrence *not* containing the pattern if the search subcommand included !). The default value for K is the first occurrence. Lists the file or files you named in the **more** command line. :f or ^G or = Displays information about the current file: · file name · order of the file in the list of files · current line number · current position in the file, given as a percentage current byte number and total bytes to display. Examines the specified file, provided you named it in the more :e[File] or E[File] command line. [K]:n or [K]N Examines either the next file (if you do not give a value for K) or the file K number of positions forward in the list of files you named in the more command line. [K]:p or [K]P Examines either the previous file (if you do not give a value for K) or the file K number of positions backward in the list of files you named in the more command line. :t Tagstring Displays the portion of the file that contains the specified tag. This subcommand works only on files containing tags created with the ctags command. The :t subcommand is the interactive version of the -t flag. :q or q or Q Exits the more command. :!command or !command

Starts the specified command in a new shell.

Toggles the search pattern highlighting feature on or off.

Exit Status

н

This command returns the following exit values:

- Successful completion.
- >0 An error occurred.

Examples

1. To view a file named myfile, enter:

more myfile

2. To view output from the **nroff** command, enter:

1s -1 | more

3. To view each file starting at its last screen, enter:

more -p G file1 file2

4. To view each file with the 100th line at the current position, enter:

more -p 100 file1 file2

Typically, the current position in a more command display is the third line on the screen. In this example, the first line on the screen is the 98th line in the file.

5. To view each file starting with the first line that contains the foo string, enter:

```
more -p /foo file1 file2
```

The **more** command displays the line in the current position, the third line on the screen.

Files

/usr/share/lib/terminfo

Indicates the terminal information database.

Related Information

The cat command, csh command, ctags command, ksh command, pg command, script command.

The environment file, terminfo file.

User environment in the Operating system and device management.

Understanding Locale Environment Variables in the AIX 5L Version 5.3 National Language Support Guide and Reference.

Shells in the Operating system and device management.

Input and output redirection in *Operating system and device management*.

Files in the Operating system and device management

File and directory access modes in the Operating system and device management.

mosy Command

Purpose

Converts the ASN.1 definitions of Structure and Identification of Management Information (SMI) and Management Information Base (MIB) modules into objects definition files for the snmpinfo command.

Syntax

```
mosy -o output_defs_file [ -s ] inputfile ...
```

```
mosy -x output_desc_file [ -o output_defs_file] [ -s ] inputfile ...
```

mosy -c output c file [-x output desc file] [-o output defs file] [-s] inputfile ...

Description

The mosy command reads in the ASN.1 definitions of SMI and MIB modules and produces objects definition files in specific formats. The resulting objects definition files are used by the snmpinfo command.

The inputfile parameter files are required to be in the smi.my or mibll.my format. Sample files are the /usr/samples/snmpd/smi.my and /usr/samples/snmpd/mibll.my files. See the smi.my and the mibll.my files for information on the required format of the file specified by the inputfile parameter.

The mosy -o command is used to create the objects definition file specified by the output defs file parameter for the snmpinfo command. This file is normally the /etc/mib.defs file.

The objects definition file can be created with one pass of the mosy compiler if the smi.my and mibli.my files are both specified as inputfile parameters. The smi.my file must precede the mibll.my file on the command line.

The mosy -o command can also be used to create subfiles. If subfiles are created separately from the SMI and MIB modules, you must concatenate the various subfiles before the snmpinfo command can successfully use the resultant mib.defs file. The SMI subfile must be at the top of the final objects definition file.

You can add objects definitions for experimental MIB modules or private-enterprise-specific MIB modules to the /etc/mib.defs file, but you must first obtain the private MIB module from the vendor that supports those MIB variables.

To update the **/etc/mib.defs** file to incorporate a vendor's private or experimental MIB objects definitions, create a subfile and then concatenate that subfile to the existing MIB II /etc/mib.defs file. See example 3.

Flags

-c output c file Creates a C code file.

-o output_defs_file Defines the path and file name of the MIB objects definition file for the snmpinfo

command. There is no default path and file name for this flag. If this flag is not specified,

the objects definition file is not created.

-s Suppresses the conversion verification messages. If this flag is not specified, the

conversion verification messages are printed to standard output.

Creates a description file in mib.desc file format. -x output_desc_file

Parameters

inputfile

Defines the ASN.1 object definitions module for input to the mosy compiler. This file can be formatted according to either the smi.my or mibll.my file format.

Examples

1. To create an objects definition file for use by the **snmpinfo** command with one pass of the **mosy** command. enter:

```
mosy -o /etc/mib.defs /usr/samples/snmpd/smi.my
/usr/samples/snmpd/mibII.my
```

In this example, /usr/samples/snmpd/smi.my and /usr/samples/snmpd/mibll.my are both specified as input files and the resultant objects definition file is the /etc/mib.defs file.

2. To create objects definition subfiles, enter:

```
mosy -o /tmp/smi.obj /usr/samples/snmpd/smi.my
mosy -o /tmp/mibII.obj /usr/samples/snmpd/mibII.my
cat /tmp/smi.obj /tmp/mibII.obj > /etc/mib.defs
```

In this example, the first command creates an SMI objects file, /tmp/smi.obj, from the /usr/samples/snmpd/smi.my file. The second command creates the MIB objects definition file, /tmp/mibII.obj, from the /usr/samples/snmpd/mibII.my file. The final command concatenates the subfiles, placing the SMI objects definition file first in the resultant /etc/mib.defs file.

3. To add private enterprise specific MIB objects definitions to an existing /etc/mib.defs file for use by the snmpinfo command, enter:

```
mosy -o /tmp/private.obj /tmp/private.my
cat /etc/mib.defs /tmp/private.obj > /tmp/mib.defs
mv /tmp/mib.defs /etc/mib.defs
```

In this example, the first command creates the /tmp/private.obj objects definition file. The second command concatenates the /etc/mib.defs MIB objects definition file with the /tmp/private.obj private MIB file and places the concatenated contents into the /tmp/mib.defs temporary MIB objects definition file. The final command moves the temporary file to the /etc/mib.defs file for use by the snmpinfo command.

4. To create a description file in /tmp/smi.desc, a C code file named /tmp/smi.c, and a Management Information Base (MIB) definition file named /tmp/smi.defs, enter:

```
mosy -x /tmp/smi.desc -c /tmp/smi.c -o /tmp/smi.defs -s smi.my mibII.my
```

Files

/etc/mib.defs Defines the Management Information Base (MIB) variables the

SNMP agent should recognize and handle. The format of the /etc/mib.defs file is required by the snmpinfo command.

Defines the ASN.1 definitions by which the SMI is defined as in

Defines the ASN.1 definitions for the MIB II variables as defined /usr/samples/snmpd/mibll.my

in RFC 1213.

Related Information

/usr/samples/snmpd/smi.my

The **snmpinfo** command.

Understanding the Management Information Base (MIB), Understanding Terminology Related to Management Information Base (MIB) Variables in AIX 5L Version 5.3 Communications Programming Concepts.

mount Command

Purpose

Makes a file system available for use.

Syntax

mount [-f] [-n node] [-o options] [-p] [-r] [-v vfsname] [-t type | [device | node:directory] directory | all | -a] [-V [generic_options] special_mount_points]

Description

The **mount** command instructs the operating system to make a file system available for use at a specified location (the mount point). In addition, you can use the **mount** command to build other file trees made up of directory and file mounts. The mount command mounts a file system expressed as a device using the device or node: directory parameter on the directory specified by the directory parameter. After the mount command has finished, the directory specified becomes the root directory of the newly mounted file system.

Only users with root authority or are members of the system group and have write access to the mount point can issue file or directory mounts. The file or directory may be a symbolic link. The mount command uses the real user ID, not the effective user ID, to determine if the user has appropriate access. System group members can issue device mounts, provided they have write access to the mount point and those mounts specified in the /etc/file systems file. Users with root user authority can issue any mount command.

Users can mount a device provided they belong to the system group and have appropriate access. When mounting a device, the mount command uses the device parameter as the name of the block device and the directory parameter as the directory on which to mount the file system.

If you enter the mount command without flags, the command displays the following information for the mounted file systems:

- the node (if the mount is remote)
- the object mounted
- the mount point
- the virtual-file-system type
- the time mounted
- · any mount options

If you specify only the *directory* or *node:directory* parameter, the **mount** command takes it to be the name of the directory or file on which a file system, directory, or file is usually mounted (as defined in the /etc/file systems file). The mount command looks up the associated device, directory, or file and mounts it. This is the most convenient way of using the **mount** command, because it does not require you to remember what is normally mounted on a directory or file. You can also specify only the device. In this case, the command obtains the mount point from the /etc/file systems file.

The /etc/file systems file should include a stanza for each mountable file system, directory, or file. This stanza should specify at least the name of the file system and either the device on which it resides or the directory name. If the stanza includes a mount attribute, the mount command uses the associated values. It recognizes five values for the mount attributes: automatic, true, false, removable, and readonly.

The mount all command causes all file systems with the mount=true attribute to be mounted in their normal places. This command is typically used during system initialization, and the corresponding mounts are referred to as automatic mounts.

Note: If the cdromd CD and DVD automount daemon is enabled, then those devices will be automatically mounted as specified in the /etc/cdromd.conf file. Use the cdumount or cdeject command to unmount an automounted CD or DVD. Use stopsrc -s cdromd to disable the CD/DVD automount daemon.

Note: For CacheFS, the remote file system that is to be cached locally must be exported such that the root ID of the local system is not remapped on the remote host to nobody (or the ID that the remote host uses as the anonymous user). For example, if host A were to export a file system /F, which would be mounted with CacheFS on host B, then the /etc/exports on host A would need to have an entry similar to:

```
/F -rw,root=B
/F -ro, root=B
```

depending on the mount options used for the local CacheFS mount.

Note: Mounting a JFS file system on a read-only logical volume is not supported.

Flags

-a	Mounts all file systems in the /etc/file systems file with stanzas that contain the true
	mount attribute.

all Same as the **-a** flag.

Requests a forced mount during system initialization to enable mounting over the root file -f

system.

-n node Specifies the remote node that holds the directory to be mounted. For NFS version 4

> mounts only, the node can be specified as a colon-separated IPv6 address. If this is done with the node:directory format, the colon-separated IPv6 address must be enclosed in

square brackets.

Mounts a file system as a removable file system. While open files are on it, a removable -p mounted file system behaves the same as a normally mounted file system. However, when

no files are open (and no process has a current directory on the file system), all of the file system disk buffers in the file system are written to the medium, and the operating system

forgets the structure of the file system.

Mounts a file system as a read-only file system, regardless of its previous specification in

the /etc/file systems file.

-t type Mounts all stanzas in the /etc/file systems file that contain the type=type attribute and are

not mounted. The *type* parameter specifies the name of the group.

Specifies that the file system is defined by the *vfsname* parameter in the /etc/vfs file. -v vfsname

File System Specific Options

-r

Specifies options. Options entered on the command line should be separated only by a comma. -o options The following file system-specific options do not apply to all virtual file system types:

> bsy Prevents the mount operation if the directory to be mounted over is the current working directory of a process.

cio Specifies the file system to be mounted for concurrent readers and writers. I/O on files in this file system will behave as if they had been opened with O_CIO specified in the open() system call. Using this option will prevent access in any manner other than CIO. It is impossible to use cached I/O on a file system mounted with the cio option. This means that mapping commands such as mmap() and shmat() will fail with EINVAL when used on any file in a file system mounted with the cio option. One side-effect of this is that it is impossible to run binaries out of a cio mounted file system, since the loader may use mmap().

dio Specifies that I/O on the file system will behave as if all the files had been opened with O DIRECT specified in the open() system call.

Note: Using the -odio or -ocio flags can help performance on certain workloads, but users should be aware that using these flags will prevent file caching for these file systems. Because readahead is disabled for these file systems, this may decrease performance for large sequential reads.

fmode=octal

Specifies the mode for a file and directory. The default is 755.

gid=gid

Specifies the GID that is assigned to files in the mount. The default is bin.

log=lvname

Specifies the full path name of the file system logging logical volume name where the following file-system operations are logged.

maxpout=value

Specifies the pageout level for files on this file system at which threads should be slept. If maxpout is specified, minpout must also be specified. Value must be non-negative and greater than **minpout**. The default is the kernel **maxpout** level.

minpout=value

Specifies the pageout level for files on this file system at which threads should be readied. If minpout is specified, maxpout must also be specified. Value must be non-negative. The default is the kernel minpout level.

noatime

Turns off access-time updates. Using this option can improve performance on file systems where a very large number of files are read frequently and seldom updated. If you use the option, the last access time for a file cannot be determined.

nocase

Turns-off case mapping. This is useful for CDROMs using the ISO 9660:1998/HSG standard.

nodev Specifies that you cannot open devices from this mount. This option returns a value of ENXIO if a failure occurs.

nosuid Specifies that execution of **setuid** and **setgid** programs by way of this mount is not allowed. This option returns a value of **EPERM** if a failure occurs.

rbr Mount file system with the release-behind-when-reading capability. When sequential reading of a file in this file system is detected, the real memory pages used by the file will be released once the pages are copied to internal buffers.

Note: When **rbr** is specified, the **D_RB_READ** flag is ultimately set in the **_devflags** field in the **pdtentry** structure.

rbw Mount file system with the release-behind-when-writing capability. When sequential writing of a file in this file system is detected, the real memory pages used by the file will be released once the pages written to disk.

Note: When rbw is specified, the D_RB_WRITE flag is set.

rbrw Mount file system with both release-behind-when-reading and release-behind-when-writing capabilities.

Note: If rbrw is specified, both the D_RB_READ and the D_RB_WRITE flags are set.

ro Specifies that the mounted file is read-only. The default value is **rw**.

rw Specifies that the mounted file is read/write accessible. rw is the default value.

snapshot

Specifies the *Device* to be mounted is a snapshot. The snapped file system for the specified snapshot must already be mounted or an error message will display.

snapto=snapshot

Specifies the location to start a snapshot with the value of *snapshot* when mounting the specified JFS2 file system.

upcase

Changes case mapping from default lowercase to uppercase. This is useful for CDROMs using the ISO 9660:1998/HSG standard.

uid=uid

Specifies the UID that is assigned to files in the mount, the default is bin.

wrkgrp=workgroup

Specifies the workgroup that the SMB server belongs.

NFS Specific Options

-o options

Specifies options. Options you enter on the command line should be separated only by a comma, not a comma and a space. The following NFS-specific options do not apply to all virtual file system types:

acdirmax=n

Holds cached attributes for no more than n seconds after directory update. The default is 60 seconds.

acdirmin=n

Holds cached attributes for at least n seconds after directory update. The default is 30 seconds.

acl Requests using the Access Control List RPC program for this NFS mount. If the acl option is used, the ACL RPC program is used only if the NFS server provides it. The default is **noacl**.

acregmax=n

Holds cached attributes for no longer that n seconds after file modification. The default is 60 seconds.

acregmin=n

Holds cached attributes for at least n seconds after file modification. The default is 30

actimeo=n

Sets minimum and maximum times for regular files and directories to n seconds. If this option is set, it overrides any settings for the acregmin, acregmax, acdirmin, and acdirmax options.

bg Attempts mount in background if first attempt is unsuccessful. The default value is fg.

biods=n

Sets the maximum number of biod threads that perform asynchronous I/O RPC requests for an NFS mount. The maximum value that can be set is 128. Values greater than 128 are limited to 128 within the NFS client. The NFS client dynamically manages the number of running biod threads up to the maximum based on activity. The default maximums for the different NFS protocols are 7 for NFS version 2, 4 for NFS version 3, and 16 for NFS version 4. These defaults are subject to change in future releases.

cio Specifies the file system to be mounted for concurrent readers and writers. I/O on files in this file system will behave as if they had been opened with O CIO specified in the open() system call. Using this option will prevent access in any manner other than CIO. It is impossible to use cached I/O on a file system mounted with the cio option. This means that mapping commands such as mmap() and shmat() will fail with EINVAL when used on any file in a file system mounted with the cio option. One side-effect of this is that it is impossible to run binaries out of a cio mounted file system, since the loader may use mmap().

dio Specifies that I/O on the file system will behave as if all the files had been opened with O_DIRECT specified in the open() system call.

Note: Using the -odio or -ocio flags can help performance on certain workloads, but users should be aware that using these flags will prevent file caching for these file systems. Because readahead is disabled for these file systems, this may decrease performance for large sequential reads.

fastattr Bypasses the requirement that files currently being written will be sent to the server before the attributes of the file is read. This option is to be used with caution, since it will cause the client to assume that the file data that has not yet reached the server will be written without problem. In case of write errors, the client and server will have different opinions on what the size of the file really is. Likewise, a client will not be aware of attribute changes to the file being made by another client, so this option must not be used in environments where two clients are writing to the same files.

fg Attempts mount in foreground if first attempt is unsuccessful. fg is the default value.

grpid Directs any file or directory created on the file system to inherit the group ID of the parent directory.

hard Retries a request until server responds. The option is the default value.

intr Allows keyboard interrupts on hard mounts.

llock Requests that files lock locally at the NFS client. NFS network file locking requests are not sent to the NFS server if the **llock** option is used.

maxgroups=n

Indicates that NFS RPC calls using **AUTH_UNIX** may include up to *n* member groups of information. Using this option to increase the number of member groups beyond the RPC protocol standard of 16 will only work against servers that support more than 16 member groups. Otherwise, the client will experience errors.

Values below 16 or greater than 64 will be ignored. By default, the protocol standard maximum of 16 is adhered to. AIX NFS servers will accept and process AUTH_UNIX credentials with up to 64 groups starting with AIX 5L Version 5.2 with the 5200-01 Recommended Maintenance package. The actual number of member groups sent by the NFS client is dependent on the number of groups the involved user is a member of, and may be limited by the length of the NFS client's hostname (which is included in the AUTH_UNIX information).

noac Specifies that the mount command performs no attribute or directory caching. If you do not specify this option, the attributes (including permissions, size, and timestamps) for files and directories are cached to reduce the need to perform over-the-wire NFSPROC_GETATTR Remote Procedure Calls (RPCs). The NFSPROC_GETATTR RPC enables a client to prompt the server for file and directory attributes. The acregmin, acregmax, acdirmin, and acdirmax options control the length of time for which the cached values are retained.

noacl Specifies not to use the Access Control List RPC program for this NFS mount request. The default is noacl.

Specifies no keyboard interrupts allowed on hard mounts.

port=n Sets server Internet Protocol (IP) port number to n. The default value is the 2049.

Requests that pathconf information be exchanged and made available on an NFS posix Version 2 mount. Requires a mount Version 2 rpc.mountd at the NFS server.

proto=[udpltcp]

Specifies the transport protocol. The default is tcp. Use the proto=[udpltcp] option to override the default.

proto=udp cannot be specified if vers=4.

retrans=n

Sets the number of NFS transmissions to n. The default value is 5. The **retrans** setting determines how many times the NFS client retransmits a given UDP RPC request to an NFS server for file system operations. The retrans setting is not used during communication with the NFS server rpc.mountd service when processing NFS version 2 and 3 mounts. Retries to **rpc.mountd** are controlled with the **retry mount** option.

retry=n

Sets the number of times the mount is attempted to n; the default value is 1000. When the retry value is 0, the system makes 10,000 attempts.

rsize=n

Sets the read buffer size to *n* bytes. The default value is 8192. For AIX 4.2.1 and later, the default value is 32768 when using Version 3 of the NFS protocol. For AIX 5.3 and later, the default value is 32768 when using Version 4 of the NFS protocol.

secure Specifies that the mount command uses Data Encryption Standard (DES) for NFS transactions.

sec=flavor[:flavor...]

Specifies a list of security methods that may be used to access files under the mount point. Allowable flavor values are:

UNIX authentication. This is the default method.

dh DES authentication.

krb5 Kerberos. Authentication only.

krb5i Kerberos. Authentication and integrity.

krb5p Kerberos. Authentication, integrity, and privacy.

> The **secure** option may be specified, but not in conjunction with a **sec** option. The **secure** option is deprecated and may be eliminated in a future release. Use **sec=dh** instead.

sec=[flavor1:...:flavorn]

The sec option specifies the security flavor list for the NFS mount. The available flavors are des, unix, sys, krb5, krb5i, and krb5p. This option only applies to AIX 5.3 or later.

shortdev

Specifies that you are mounting a file system from a host that does not support 32-bit device special files.

soft Returns an error if the server does not respond. The default value is hard.

timeo=n

Sets the Network File System (NFS) time out period to n tenths of a second. For TCP mounts, the default timeout is 100, which equals 10 seconds. For UDP mounts, the default timeout is 11, which equals 1.1 seconds, but varies depending on the NFS operation taking place. For UDP mounts, the timeout will increase for each failed transmission, with a maximum value of 20 seconds. Each transmission will be attempted twice, after which the timeout value is updated. The timeo option does not apply to communication from the NFS client to the rpc.mountd service on NFS servers. A timeout of 30 seconds is used when making calls to rpc.mountd.

vers=[2|3|4]

Specifies NFS version. The default is the version of NFS protocol used between the client and server and is the highest one available on both systems. If the NFS server does not support NFS Version 3, the NFS mount will use NFS Version 2. Use the vers=[2|3|4] option to select the NFS version. By default, the NFS mount will never use NFS Version 4 unless specified. The **vers=4** only applies to AIX 5.3 or later.

wsize=n

Sets the write buffer size to *n* bytes. The default value is 8192. For AIX 4.2.1 and later, the default value is 32768 when using Version 3 of the NFS protocol. For AIX 5.3 and later, the default value is 32768 when using Version 4 of the NFS protocol.

CacheFS Specific Options

The CacheFS-specific version of the mount command mounts a cached file system; if necessary, it NFS-mounts its back file system. It also provides a number of CacheFS-specific options for controlling the caching process.

To mount a CacheFS file system, use the mount command with the -V flag followed by the argument. The following mount flags are available.

The following arguments to the -o flag are specifically for CacheFS mounts. Options you enter on the command line should be separated only by a comma, not a comma and a space.

Note: The **backfstype** argument must be specified.

Specifies options. -0

acdirmax=n

Specifies that cached attributes are held for no more than n seconds after directory update. Before n seconds, CacheFS checks to see if the directory modification time on the back file system has changed. If it has, all information about the directory is purged from the cache and new data is retrieved from the back file system. The default value is 60 seconds.

acdirmin=n

Specifies that cached attributes are held for at least *n* seconds after directory update. After n seconds, CacheFS checks to see if the directory modification time on the back file system has changed. If it has, all information about the directory is purged from the cache and new data is retrieved from the back file system. The default value is 30 seconds.

acregmax=n

Specifies that cached attributes are held for no more than n seconds after file modification. After *n* seconds, all file information is purged from the cache. The default value is 30 seconds.

acregmin=n

Specifies that cached attributes are held for at least n seconds after file modification. After n seconds, CacheFS checks to see if the file modification time on the back file system has changed. If it has, all information about the file is purged from the cache and new data is retrieved from the back file system. The default value is 30 seconds.

actimeo=n

Sets acregmin, acregmax, acdirmin, and acdirmax to n.

backfstype=file_system_type

The file system type of the back file system (for example, nfs).

backpath=path

Specifies where the back file system is already mounted. If this argument is not supplied, CacheFS determines a mount point for the back file system.

cachedir=directory

The name of the cache directory.

cacheid=ID

ID is a string specifying a particular instance of a cache. If you do not specify a cache ID, CacheFS will construct one.

demandconst

Enables maximum cache consistency checking. By default, periodic consistency checking is enabled. When you enable demandconst, it checks on every read and write.

Note: Note: If this option is used the first time a specific CacheFS is mounted, then the option must also be specified for subsequent mounts. There is state information stored in the cache control files that enforces consistent use of this option.

local_access

Causes the front file system to interpret the mode bits used for access checking instead or having the back file system verify access permissions. Do not use this argument with secure NFS.

noconst

Disables cache consistency checking. By default, periodic consistency checking is enabled. Specify noconst only when you know that the back file system will not be modified. Trying to perform cache consistency check using cfsadmin-s will result in error. demandconst and noconst are mutually exclusive.

Note: Note: If this option is used the first time a specific CacheFS is mounted, then the option must also be specified for subsequent mounts. There is state information stored in the cache control files that enforces consistent use of this option.

Purge any cached information for the specified file system. purge

Note: Note: If this option is used the first time a specific CacheFS is mounted. then the option must also be specified for subsequent mounts. There is state information stored in the cache control files that enforces consistent use of this option.

rw I ro Read-write (default) or read-only.

suid | nosuid

Allow (default) or disallow set-uid execution

write-around | non-shared

Write modes for CacheFS. The write-around mode (the default) handles writes the same as NFS does; that is, writes are made to the back file system, and the affected file is purged from the cache. You can use the non-shared mode when you are sure that no one else will be writing to the cached file system.

Note: Note: If this option is used the first time a specific CacheFS is mounted, then the option must also be specified for subsequent mounts. There is state information stored in the cache control files that enforces consistent use of this option.

Mounts a CacheFS file system.

Examples

-V

1. To list the mounted file systems, enter:

mount

This command produces output similar to the following:

node	mounted	mounted over	vfs	date	options
	/dev/hd0	/	jfs	Dec 17 08:04	rw, log =/dev/hd8
	/dev/hd3	/tmp	jfs	Dec 17 08:04	rw, log =/dev/hd8
	/dev/hd1	/home	jfs	Dec 17 08:06	rw, log =/dev/hd8
	/dev/hd2	/usr	jfs	Dec 17 08:06	rw, log =/dev/hd8
sue	/home/local/src	/usr/code	nfs	Dec 17 08:06	ro, log =/dev/hd8

For each file system, the mount command lists the node name, the device name, the name under which it is mounted, the virtual-file-system type, the date and time it was mounted, and its options.

2. To mount all default file systems, enter:

```
mount all
```

This command sequence mounts all standard file systems in the /etc/file systems file marked by the mount=true attribute.

3. To mount a remote directory, enter:

```
mount -n nodeA /home/tom.remote /home/tom.local
```

This command sequence mounts the /home/tom.remote directory located on nodeA onto the local /home/tom.local directory. It assumes the default *VfsName* parameter=remote, which must be defined in the /etc/vfs file.

4. To mount a file or directory from the /etc/file systems file with a specific type, enter:

```
mount -t remote
```

This command sequence mounts all files or directories in the /etc/file systems file that have a stanza that contains the **type=remote** attribute.

5. To CacheFS-mount the file system which is already NFS-mounted on /usr/abc, enter:

```
mount -V cachefs -o backfstype=nfs,backpath=/usr/abc,
cachedir=/cache1 server1:/user2 /xyz
```

The lines similar to the following appear in the /etc/mnttab file after the mount command is executed:

server1:/user2 /usr/abc nfs /usr/abc /cache1/xyz cachefs backfstype=nfs

6. To mount a snapshot, type:

mount -o snapshot /dev/snapsb /home/janet/snapsb

This command mounts the snapshot contained on the /dev/snapsb device onto the /home/janet/snapsb directory.

7. To mount a file system and create a snapshot, type:

```
mount -o snapto=/dev/snapsb /dev/sb /home/janet/sb
```

This command mounts the file system contained on the /dev/sbdevice onto the /home/janet/sb directory and creates a snapshot for the file system on the /dev/snapsbdevice.

8. To access files on an SMB server as a local file system, type:

```
mount -v cifs -n pezman/user1/pass1 -o uid=201, fmode=750 /home /mnt
```

Files

/etc/file systems Lists the known file systems and defines their characteristics.

/etc/vfs Contains descriptions of virtual-file-system types.

Related Information

The cdcheck command, cdeject command, cdmount command, cdromd command, cdumount command, cdutil command, nfso command, umount command.

The **mntctl** subroutine, **mount** subroutine, **umount** subroutine.

The file systems file, vfs file.

For information on installing the Web-based System Manager, see Chapter 2: Installing Web-based System Manager in AIX 5L Version 5.3 Web-based System Manager Administration Guide.

Mounting and System management interface tool in Operating system and device management.

Performance implications of hard or soft NFS mounts in Performance management.

mountd Daemon

Purpose

Answers requests from clients for file system mounts.

Syntax

/usr/sbin/rpc.mountd [-n] [-N]

Description

The mountd daemon is a Remote Procedure Call (RPC) that answers a client request to mount a file system. The mountd daemon finds out which file systems are available by reading the /etc/xtab file.

In addition, the mountd daemon provides a list of currently mounted file systems and the clients on which they are mounted. You can display this list by using the **showmount** command.

The mountd daemon listens for requests on the port specified in the /etc/services file for the service mountd. If the /etc/services file does not specify a port, one will be chosen when the daemon starts. For example, adding the lines:

```
mountd
       6666/tcp
mountd 6666/udp
```

will cause mountd to listen for requests on port 6666.

Examples

The mountd daemon is started from the /etc/rc.nfs file. The mountd daemon can be started and stopped by the following System Resource Controller (SRC) commands:

```
startsrc -s rpc.mountd
stopsrc -s rpc.mountd
```

To change the parameters passed to the **mountd** daemon, use the **chssys** command. For example:

```
chssys -s rpc.mountd -a Argument
```

The change will not take effect until the daemon is restarted.

Flags

- Allows clients that use older versions of NFS to mount file systems. This option makes the system less -n secure. It is the default.
- Deny mount requests originating from non-privileged ports. This is the opposite of using the -n flag, and is -N not enabled by default.

Files

/etc/exports Lists the directories that the server can export.

Defines how the inetd daemon handles Internet service requests. /etc/inetd.conf

/etc/xtab Lists currently exported directories.

/etc/services Defines the sockets and protocols used for Internet services. Contains information

about the known services used in the DARPA Internet network.

Related Information

The chssys command, mount command, showmount command.

The **nfsd** daemon, **portmap** daemon.

Network File System in Networks and communication management.

System Resource Controller in Operating system and device management.

How to Mount a NFS File System Explicitly and How to Mount a File System Using Secure NFS in Security.

List of NFS commands.

mpcfq Command

Purpose

Manages remote maintenance service information.

Syntax

Display Service Information

mpcfg -d { -f -m -p -S}

Change Service Information

mpcfg -c { -f | -m | -p -S -w} Index Value...

Save or Restore Service Information

mpcfg { -r | -s }

Description

The mpcfg command enables a user with root authority to manage service information consisting of the service support and diagnostic flags (-S and -f flags), the modem and site configuration (-m flag), and the remote support phone numbers (-p flag).

The mpcfg command works only on multiprocessor systems with Micro Channel I/O for AIX 5.1 and earlier. For IBM systems, this includes the IBM 7012 Model G Series, the IBM 7013 Model J Series, and the IBM 7015 Model R Series for AIX 5.1 and earlier.

You can perform the following actions:

- Display (-d flag) the service information
- Change (-c flag) the service information
- Save (-s flag) the service information in the /etc/lpp/diagnostics/data/bump file
- Restore (-r flag) the service information to values read in the /etc/lpp/diagnostics/data/bump file.

Note: Generally the **mpcfg** command is not used directly but through the **diag** command.

Flags

Changes values of service information. The values that you want to modify are identified first by the flag -f, -m, -p or -S, and then by their index (Index parameter) within this category. The new value to assign (Value parameter) directly follows this index in the command. You can specify only one flag among -f, -m, -p, -S but several pairs "Index Value". The flag -w allows to change maintenance passwords.

- Displays the values of service information according to the -f, -m, -p and -S flags set in the command. These -d values are displayed associated with their corresponding indexes and names.
- Reads the service information in the /etc/lpp/diagnostics/data/bump file, and restores it in the non volatile -r memory (NVRAM).
- Saves the service information in the /etc/lpp/diagnostics/data/bump file. -s
- -f Indicates that the action (display or change) will be applied to the diagnostic flags.
- -m Indicates that the action (display or change) will be applied to the modem and site configuration.
- Indicates that the action (display or change) will be applied to the remote support phone numbers. -р
- Indicates that the action (display or change) will be applied to the service support flags. -S
- Indicates that the change will be applied to a password. -w

Security

Access Control: only the root user can run this command.

Examples

1. To display the modem and site configuration, enter the following command:

```
mpcfg -d m
```

This produces output similar to the following:

Index	Name	Value
1	Modem Parameters File Name	/usr/share/modems/plextel
2	Service Line Speed	2400
3	Protocol Inter Data Block Delay	15
4	Protocol Time Out	30
5	Retry Number	2
6	Customer ID	xyz
7	Login ID	abcd
8	Password ID	%qw!as

2. To assign the new value 22114433 to the first remote support phone number, enter the following command:

```
>mpcfg -c -p 1 22114433
```

3. To save the service information in the /etc/lpp/diagnostics/data/bump file, enter the following command:

```
mpcfg -s
```

4. To restore the service information from the /etc/lpp/diagnostics/data/bump file to NVRAM, enter the following command:

```
mpcfg -r
```

Files

/usr/sbin/mpcfg /etc/lpp/diagnostics/data/bump Contains the mpcfg command.

Contains the service support and diagnostic flags, remote support phone numbers, and modem and site configuration.

mpcstat Command

Purpose

Displays operational information about a Multi-Protocol Over ATM (MPOA) Client.

Syntax

mpcstat [-a -c -e -i -m -r -s -t -v] [Device Name]

Description

This command displays Multi-Protocol Over ATM (MPOA) Client operational information gathered by a specified MPOA Client device. If a MPOA Client (MPC) device name is not entered, information for the available MPC appear. You can use the flags to narrow down your search to specify specific categories of information such as Configuration, Egress Cache Entries, Ingress Cache Entries, MPOA Servers, Shortcut Virtual Connections, and Statistics, or you can elect to have all of the information categories display.

You can also toggle debug tracing on or off and reset statistics counters.

Parameters

Device_Name The name of the MPOA Client device name, for example, mpc0.

Flags

-a	Requests that all of the MPOA Client information appear. Note that this flag does not reset statistics counters or toggle trace. If a flag is not entered, the -a flag is the default flag.
-c	Requests the configuration
-е	Requests the egress (incoming) cache
-i	Requests the ingress (outgoing) cache.
-m	Requests the list of MPOA Servers in use.
-r	Resets the statistics counters after reading.
-s	Requests the statistics counters.
-t	Toggles full debug trace on or off.
-v	Requests the list of Shortcut Virtual Connections.

The following information appears for all valid calls and contains the following fields:

Device Name

Displays the device name of the MPOA Client.

MPC State

Displays the current state of the MPOA Client.

Example States:

Idle Registering with the ELAN. Initializing Registering with the switch. Operational Fully operational. Network Down Network is currently unavailable.

MPC Address

Displays the MPOA Client's 20-byte ATM address for a specific ATM adapter port device name. The adapter port device name is also displayed.

Elapsed Time

Displays the real time period which has elapsed since statistics were last reset.

MPC Configuration

Selected with the -a or -c flags. Displays the network administrator's pre-configured attributes for the MPOA Client, or the values provided by a Lan Emulation Configuration Server (LECS).

MPC Egress Cache

Selected with the -a or -e flags. Displays the current egress cache entries. Included are the state of the entry, its Level-3 address, and ATM shortcut address, as well as additional descriptive values associated with each entry.

Example States

Active Has active shortcut connection. Purging Purging the egress MPOA Server entry. DP Purge Purging the remote MPOA Client data plane. Inactive No current activity on shortcut connection.

MPC Ingress Cache:

Selected with the -a or -i flags. Displays the current ingress cache entries. Included are the state of the entry, its Level-3 address, and ATM shortcut address, as well as additional descriptive values associated with each entry.

Example States

Flow Detect Waiting for packet threshold to enable shortcut. Resolution Packet threshold reached, resolving shortcut. Hold Down Shortcut resolution failed, waiting for retry. Resolved Shortcut resolution sequence complete.

MPOA Server List

Selected with the -a or -m flags. Displays a list of MPOA Servers currently known by this MPC. Included in each entry are the name of the LE Client that identified the MPS, the MPS ATM address, and the MPS LAN MAC address.

MPC Statistics

Selected with the -a or -s flags. Displays the current Transmit, Receive, and General statistics for this MPOA Client.

Shortcut Virtual Connection

Selected with the -a or -v flags. Displays the current list of shortcut virtual circuits in use by the MPOA client. Included are virtual path and channel values, VC state, ATM device name, as well as additional descriptive values associated with each entry.

Example States:

Idle Call idle.

Signalling Call placed but not established. Operational Call connected; data path valid. Released Call released.

Temporary call failure; will be retried.

Hold Down Call failure; will be suspended for hold down period.

Exit Status

If an invalid Device_Name is specified, this command produces error messages stating that it could not connect to the device. Note that MPOA is a protocol extension to the ATM LAN Emulation protocol, and must have a corresponding and available LE Client to be operational. Examples of an invalid device error message are:

MPCSTAT: Device is not an MPOA device. MPCSTAT: No LEC device with MPOA enabled.

MPCSTAT: Device is not available.

Related Information

The atmstat command, entstat command, lecstat command, and tokstat command.

mpstat Command

Purpose

Collects and displays performance statistics for all logical CPUs in the system.

Syntax

```
mpstat [ { -d | -i | -s | -a | -h} ] [ -w ] [ interval [ count ] ]
```

Description

The **mpstat** command collects and displays performance statistics for all logical CPUs in the system. Users can define both, the number of times the statistics are displayed, and the interval at which the data is updated. When the mpstat command is invoked, it displays two sections of statistics. The first section displays the System Configuration, which is displayed when the command starts and whenever there is a change in the system configuration. The second section displays the Utilization Statistics which will be displayed in intervals and at any time the values of these metrics are deltas from pervious interval.

The following information is displayed in the system configuration section:

lcpu Number of online logical processors.

ent Entitled processing capacity in processor units. This information will be displayed only if the partition type is shared.

mode Indicates whether the partition processor capacity is capped or uncapped allowing it to consume idle cycles from the shared pool. Dedicated LPAR is capped or donating.

The performance statistics displayed by **mpstat** are detailed below:

CPU (All flags) The logical CPU ID.

min (Default, -a flag) The minor page faults (page faults with no IO).

(Default, -a flag) The major page faults (page faults with disk IO). maj

mpcs (-a, -i flag) The number of mpc send interrupts.

(-a, -i flag) The number of mpc receive interrupts. mpcr

(Only default) The total number of inter-processor calls. mpc

(-a, -i flag) The number of device interrupts. dev

soft (-a, -i flag) The number of software interrupts.

dec (-a, -i flag) The number of decrementer interrupts.

ph (-a, -i flag) The number of phantom interrupts.

int (Only default) The total number of interrupts.

CS (Default, -a flag) The total number of context switches.

ics (Default, -a flag) The total number of involuntary context switches.

bound

(-a, -d flag) The total number of threads that are bound.

(Default, -a, -d flag) The run queue size. rq

push (-a, -d flag) The number of migrations due to starvation load balancing.

S3pull

(-a, -d flag) The number of migrations outside the scheduling affinity domain 3 due to idle stealing.

- S3grd (-a, -d flag) The number of dispatches from global runqueue, outside the scheduling affinity domain 3.
- mig (Only default) The total number of thread migrations (to another logical processor).
- S0rd (-a, -d flag) The percentage of thread redispatches within the scheduling affinity domain 0.
- S1rd (-a, -d flag) The percentage of thread redispatches within the scheduling affinity domain 1.
- S2rd (-a, -d flag) The percentage of thread redispatches within the scheduling affinity domain 2.
- S3rd (-a, -d flag) The percentage of thread redispatches within the scheduling affinity domain 3.
- S4rd (-a, -d flag) The percentage of thread redispatches within the scheduling affinity domain 4.
- S5rd (-a, -d flag) The percentage of thread redispatches within the scheduling affinity domain 5.
- lpa (Only default) The logical processor affinity. The percentage of logical processor redispatches within the scheduling affinity domain 3.
- (Default, -a flag) The number of system calls. SYSC
- us (Default, -a flag) The percentage of physical processor utilization that occurred while executing at the user level (application).
- sy (Default, -a flag) The percentage of physical processor utilization that occurred while executing at the system level (kernel).
- wa (Default, -a flag) The percentage of time that the logical processor was idle during which it had an outstanding disk I/O request.
- id (Default, -a flag) The percentage of time that the logical processor was idle and it did not have an outstanding disk I/O request.

рс

(Default, -a flag, -h flag) The fraction of physical processor consumed. It is displayed in both shared partition and dedicated partition. For the default flag in the dedicated partition, it is not displayed when both donation and simultaneous multithreading are disabled.

The **pc** of the cpuid U row represents the number of unused physical processors.

- %ec (Default, -a flag) The percentage of entitled capacity consumed by the logical CPU. The %ec of the ALL CPU row represents the percentage of entitled capacity consumed. Because the time base over which this data is computed can vary, the entitled capacity percentage can sometimes exceed 100%. This excess is noticeable only with small sampling intervals. The attribute is displayed only in a shared partition.
- ilcs (-a, -d, -h flag) The number of involuntary logical CPU context switches, displayed only in shared partition. For the **-h** and **-a** flags, it is also displayed in dedicated partition.
- vlcs (-a, -d, -h flag) The number of voluntary logical CPU context switches. Displayed only in shared partition. For the **-h** and **-a** flags, it is also displayed in dedicated partition.
- lcs (Default) The total number of logical CPU context switches. Displayed only in shared partition or when dedicated partition is donating.

%idon

(-a, -h flag) The percentage of physical processor utilization that occurs while explicitly donating idle cycles. Displayed only in dedicated partition that is donating.

%bdon

- (-a, -h flag) The percentage of physical processor utilization that occurs while donating busy cycles. Displayed only in dedicated partition that is donating.
- **%istol** (-a, -h flag) The percentage of physical processor utilization that occurs while the Hypervisor is stealing idle cycles. Displayed only in dedicated partition.

%bstol

(-a, -h flag) The percentage of physical processor utilization that occurs while the Hypervisor is stealing busy cycles. Displayed only in dedicated partition.

%nsp (-a, -d flag) The current average processor speed as a percentage of nominal speed. Displayed only if the hardware uses the SPURR.

The mpstat command displays all the above statistics for every logical CPU in the partition. When running a shared partition, a special CPU row with the cpuid U can be displayed when the entitled processing capacity has not entirely been consumed.

The mpstat command also displays a special CPU row with the cpuid ALL which shows the partition-wide utilization. On that row, except for uncapped partitions with current physical processor consumption above their entitled capacity, the percentages are relative to the entitled processing capacity. For dedicated partitions, the entitled processing capacity is the number of physical processors.

When the -s flag is specified, the mpstat command reports simultaneous multi-threading utilization, if it is enabled. This report displays the Virtual CPU Engines Utilization and utilization of each thread (logical CPU) associated with the Virtual CPU engine.

If mpstat is running in a dedicated partition and simultaneous multi-threading is enabled, then only the thread (logical CPU) utilization is displayed.

Flags

- Displays all the statistics. -a
- Displays detailed affinity and migration statistics for AIX threads and dispatching statistics for logical -d processors.
- Displays detailed interrupts statistics. -i
- Display simultaneous multi-threading threads utilization, this flag is available only when mpstat runs in a -s simultaneous multi-threading enabled partition.
- -h Displays pc and CPU switches, with stolen and donation statistics for dedicated partitions.
- Displays wide column output, switches to wide output mode. Default is 80 column output mode. -w

Note: The -a, -d, and -i flags implicitly turn on wide-column output.

Parameters

interval

Specifies the interval between the iterations. If interval is not specified, just one snapshot of metrics will be displayed which actually reports the values from the time system is up. If interval is specified, the tool will wait for that duration before printing the first set of data. Each set of data will be followed by a separation line, a line with average values for each columns (except the CPU, which will be replace by ALL), followed by an empty line.

count

Specifies number of iterations. If interval is specified and count is not specified then mpstat will run infinitely. count can not be specified without specifying interval.

Examples

- 1. To see the default set of utilization metrics, type:
- 2. To see the default set of utilization metrics in wide display mode, type:
- 3. To see the detailed dispatch & affinity metrics, type:

```
mpstat -d 1 1
```

4. To see the detailed interrupts report, type:

```
mpstat -i 1 1
```

5. To see all the statistics, type:

```
mpstat -a 1 1
```

6. To see simultaneous multi-threading utilization, type:

```
mpstat -s 1 1
```

Files

/usr/bin/mpstat

Contains the mpstat command.

Related Information

The Iparstat command, iostat command, vmstat command, and the sar command.

mrouted Daemon

Purpose

Forwards a multicast datagram. This daemon only applies to AIX 4.2.1 or later.

Syntax

/usr/sbin/mrouted [-p] [-c Config_File] [-d [Debug_Level]]

Description

The **mrouted** daemon is an implementation of the Distance Vector Multicast Routing Protocol (DVMRP), an earlier version of which is specified in RFC 1075. It maintains topological knowledge using a distance vector routing protocol (like RIP, described in RFC 1058), on which it implements a multicast datagram forwarding algorithm called Reverse Path Multicasting.

The **mrouted** daemon forwards a multicast datagram along a shortest (reverse) path tree rooted at the subnet on which the datagram originates. The multicast delivery tree may be thought of as a broadcast delivery tree that has been pruned back so that it does not extend beyond those subnetworks that have members of the destination group. Hence, datagrams are not forwarded along those branches that have no listeners of the multicast group. The IP time-to-live of a multicast datagram can be used to limit the range of multicast datagrams.

To support multicasting among subnets that are separated by (unicast) routers that do not support IP multicasting, the mrouted daemon includes support for tunnels, which are virtual point-to-point links between pairs of the mrouted daemons located anywhere in an Internet. IP multicast packets are encapsulated for transmission through tunnels, so that they look like typical unicast datagrams to intervening routers and subnets. The encapsulation is added on entry to a tunnel, and stripped off on exit from a tunnel. By default, the packets are encapsulated using the IP-in-IP protocol (IP protocol number 4). Older versions of the **mrouted** tunnel use IP source routing, which puts a heavy load on some types of routers. This version does not support IP source-route tunneling.

The tunneling mechanism allows the **mrouted** daemon to establish a virtual Internet, for the purpose of multicasting only, which is independent of the physical Internet and which may span multiple Autonomous Systems. This capability is intended for experimental support of Internet multicasting only, pending widespread support for multicast routing by the regular (unicast) routers. The mrouted daemon suffers from the well-known scaling problems of any distance-vector routing protocol and does not support hierarchical multicast routing.

The mrouted daemon automatically configures itself to forward on all multicast-capable interfaces (that is, interfaces that have the IFF MULTICAST flag set, excluding the loopback interface), and it finds other mrouted daemons directly reachable using those interfaces.

The **mrouted** daemon does not initiate execution if it has fewer than two enabled virtual interfaces, where a virtual interface (Vif) is either a physical multicast-capable interface or a tunnel. It logs a warning if all of its virtual interfaces are tunnels; such an mrouted daemon's configuration would be better replaced by more direct tunnels.

The **mrouted** daemon handles multicast routing only; there might be unicast-routing software running on the same machine as the mrouted daemon. With the use of tunnels, it is unnecessary for the mrouted daemon to have access to more than one physical subnet to perform multicast forwarding.

Flags

-c Config_File

Starts the mrouted command using an alternate configuration file specified by the Config_File variable.

There are five types of configuration entries: phyint local-addr [disable] [metric m] [threshold t] [rate limit b] [boundary (boundary-name|scoped-addr/mask-len)] [altnet network/mask-len] tunnel local-addr remote-addr [metric m] [$\quad \textbf{threshold} \ t$] [$rate_limit b$ boundary boundary-name scoped-addr mask-len)] ${\tt cache_lifetime}\ ct$ pruning off name boundary-name scoped-addr mask-len

See mrouted.conf File in AIX 5L Version 5.3 Files Reference for more information.

-d

Sets the debug level. If no -d option is given, or if the debug level is specified as 0, themrouted daemon detaches from the invoking terminal. Otherwise, it remains attached to the invoking terminal and responsive to signals from that terminal. If -d is given with no argument, the debug level defaults to 2. Regardless of the debug level, the mrouted daemon always writes warning and error messages to the system log demon. Non-zero debug levels have the following effects:

level 1 All syslog'ed messages are also printed to stderr.

level 2 All level 1 messages plus notifications of significant events are printed to stderr.

level 3 All level 2 messages plus notifications of all packet arrivals and departures are printed to stderr.

Upon startup, the **mrouted** daemon writes its pid to the file **/etc/mrouted.pid**.

Turns off pruning. Default is pruning enabled.

Signals

-р

The following signals can be sent to the **mrouted** daemon:

HUP Restarts the **mrouted** daemon. The configuration file is reread every time this signal is evoked. INT Terminates execution gracefully (that is, by sending good-bye messages to all neighboring routers).

TERM Same as INT.

USR1 Dumps the internal routing tables to /usr/tmp/mrouted.dump.

USR2 Dumps the internal cache tables to /usr/tmp/mrouted.cache.

QUIT Dumps the internal routing tables to stderr (if the mrouted daemon was invoked with a nonzero debug

level).

For convenience in sending signals, the **mrouted** daemon writes its pid to **/etc/mrouted.pid** on startup.

Examples

1. To display routing table information, type:

```
kill -USR1 *cat /etc/mrouted.pid*
```

This produces the following output:

```
Virtual Interface Table
 Vif Local-Address
                                     Metric Thresh
                                                      Flags
  0 36.2.0.8
                 subnet: 36.2
                                              1
                                      1
                                                       querier
                 groups: 224.0.2.1
                         224.0.0.4
                pkts in: 3456
               pkts out: 2322323
  1 36.11.0.1
                 subnet: 36.11
                                       1
                                                 1
                                                       querier
                 groups: 224.0.2.1
                         224.0.1.0
                         224.0.0.4
                pkts in: 345
               pkts out: 3456
  2 36.2.0.8
                 tunnel: 36.8.0.77
                                                  1
                  peers: 36.8.0.77 (2.2)
             boundaries: 239.0.1
                       : 239.1.2
                pkts in: 34545433
               pkts out: 234342
  3 36.2.0.8
                 tunnel: 36.6.8.23
                                                  16
Multicast Routing Table (1136 entries)
                                      Metric Tmr In-Vif Out-Vifs
                 From-Gateway
Origin-Subnet
```

```
36.2
                                    45 0
                                             1* 2 3*
              36.8.0.77
                                   15 2
36.8
                                4
                                             0* 1* 3*
                                    20 1
                                             0* 2 3*
36.11
```

In this example, there are four virtual interfaces connecting to two subnets and two tunnels. The Vif 3 tunnel is not in use (no peer address). The Vif 0 and Vif 1 subnets have some groups present; tunnels never have any groups. This instance of the **mrouted** daemon is the one responsible for sending periodic group membership queries on the Vif 0 and Vif 1 subnets, as indicated by the querier flags. The list of boundaries indicate the scoped addresses on that interface. A count of the no. of incoming and outgoing packets is also shown at each interface.

Associated with each subnet from which a multicast datagram can originate is the address of the previous hop router (unless the subnet is directly connected), the metric of the path back to the origin, the amount of time since an update for this subnet was last received, the incoming virtual interface for multicasts from that origin, and a list of outgoing virtual interfaces. The * (asterisk) means that the outgoing virtual interface is connected to a leaf of the broadcast tree rooted at the origin, and a multicast datagram from that origin will be forwarded on that outgoing virtual interface only if there are members of the destination group on that leaf.

The **mrouted** daemon also maintains a copy of the kernel forwarding cache table. Entries are created and deleted by the **mrouted** daemon.

2. To display cache table information, type:

```
kill -USR2 *cat /etc/mrouted.pid*
```

This produces the following output:

```
Multicast Routing Cache Table (147 entries)
                                      Age Ptmr IVif Forwvifs
               Mcast-group
13.2.116/22
               224.2.127.255
                                  3m
                                       2m
                                                  0
                                                        1
>13.2.116.19
>13.2.116.196
138.96.48/21
              224.2.127.255
                                  5m
                                       2m
                                                  0
>138.96.48.108
              224.2.127.255
                                                  0
                                                        1
128.9.160/20
                                  3m
                                       2m
>128.9.160.45
198.106.194/24 224.2.135.190
                                  9m
                                       28s
                                            9m
                                                   0P
>198.106.194.22
```

Each entry is characterized by the origin subnet number and mask and the destination multicast group. The CTmr field indicates the lifetime of the entry. The entry is deleted from the cache table when the timer decrements to zero. The Age field is the time since this cache entry was originally created. Because cache entries get refreshed if traffic is flowing, routing entries can grow very old. The Ptmr field is a hyphen if no prune was sent upstream or the amount of time until the upstream prune will time out. The **Ivif** field indicates the incoming virtual interface for multicast packets from that origin. Each router also maintains a record of the number of prunes received from neighboring routers for a particular source and group. If there are no members of a multicast group on any downward link of the multicast tree for a subnet, a prune message is sent to the upstream router. They are indicated by a P after the virtual interface number. The **Forwvifs** field shows the interfaces along which datagrams belonging to the source group are forwarded. A p indicates that no datagrams are being forwarded along that interface. An unlisted interface is a leaf subnet with are no members of the particular group on that subnet. A b on an interface indicates that it is a boundary interface, that is, traffic will not be forwarded on the scoped address on that interface. An additional line with a > (greater-than sign) as the first character is printed for each source on the subnet. There can be many sources in one subnet.

Files

/etc/mrouted.conf

Contains the configuration information for the **mrouted** daemon.

/usr/tmp/mrouted.dump /etc/mrouted.pid /usr/tmp/mrouted.cache Contains the internal routing tables for the **mrouted** daemon. Contains the process ID for the mrouted daemon. Contains the internal cache tables for the mrouted daemon.

Related Information

/etc/mrouted.conf File in AIX 5L Version 5.3 Files Reference.

msgchk Command

Purpose

Checks for messages.

Syntax

msgchk [User ...]

Description

The msgchk command checks mail drops for messages. The msgchk command reports whether the mail drop for the specified user contains messages and indicates if the user has already seen these messages. By default, the **msgchk** command checks the mail drop for the current user.

Flags

Lists the command syntax, available switches (toggles), and version information. -help

Note: For the Message Handler (MH), the name of this flag must be fully spelled out.

Examples

1. To check to see if you have any new messages, enter: msgchk

If you have new messages, the system responds with a message similar to the following: You have new Internet mail waiting

If you have no messages, the system responds with a message similar to the following: You don't have any mail waiting

2. To check to see if user karen on your local system has any new messages, enter: msgchk karen

In this example, if user karen on your local system has new messages, the system responds with a message similar to the following:

karen has new Internet mail waiting

If user karen on your local system has no messages, the system responds with a message similar to the following:

karen doesn't have any mail waiting

Files

\$HOME/.mh_profile

Contains the user's MH profile.

/etc/mh/mtstailor /var/spool/Mail/\$USER /usr/bin/msqchk

Contains the MH tailor file.

Defines the location of the mail drop. Contains the msqchk command.

Related Information

The inc command.

The **mh** alias file format, **mh** profile file format.

Mail applications in Networks and communication management.

msh Command

Purpose

Creates a Message Handler (MH) shell.

Syntax

msh [File] [-prompt String] [-notopcur | -topcur]

Description

The msh command creates an MH shell for use with messages that are packed in a file. By default, this command looks for the msgbox file in the current directory. Within the MH shell, you can use the following MH commands:

ali	burst	comp	dist
folder	forw	inc	mark
mhmail	msgchk	next	packf
pick	prev	refile	repl
rmm	scan	send	show
sortm	whatnow	whom	

These commands operate with limited functionality in the MH shell. To see how a command operates in the MH shell, enter the command name followed by the -help flag. Entering help or a ? (question mark) displays a list of the MH commands you can use.

To leave the **msh** shell, press the Ctrl-D key sequence or enter quit.

Flags

-help Lists the command syntax, available switches (toggles), and version information.

Note: For MH, the name of this flag must be fully spelled out.

-notopcur Makes the current message track the center line of the vmh scan window when the msh

command is started using the vmh command. This flag is the default.

Prompts for the **msh** commands with the specified string. -prompt String

-topcur Makes the current message track the top line of the vmh scan window when the msh

command is started using the **vmh** command.

Profile Entries

The following entries are found in the *UserMhDirectoryl.***mh** profile file:

fileproc: Specifies the program used to refile messages. Msg-Protect: Sets the protection level for your new message files. Path: Specifies the user's MH directory.

showproc: Specifies the program used to show messages.

Examples

1. To start an msh shell, enter:

msh

If the **msgbox** file exists in the current directory, the system responds with a message similar to the following:

Reading ./msgbox, currently at message 1 of 10

Then, the system prompt appears as follows:

(msh)

In this example, the current message is message 1 in the msgbox file. You can now enter a modified subset of MH commands.

2. To start an **msh** shell to manipulate the messages stored in the meetings file, enter:

msh meetings

Files

\$HOME/.mh_profile Specifies the user's MH profile.

/etc/mh/mtstailor Contains the MH tailor file.

/usr/bin/msh Command.

Related Information

The ali command, burst command, comp command, dist command, folder command, forw command, inc command, mark command, mhmail command, msgchk command, next command, packf command, pick command, prev command, refile command, repl command, rmm command, scan command, send command, show command, sortm command, vmh command, whatnow command, whom command.

The mh_alias file format, mh_profile file format.

Mail applications in Networks and communication management.

mt Command (BSD)

Purpose

Gives subcommands to streaming tape device.

Syntax

mt [-f TapeName] Subcommand [Count]

Description

The **mt** command gives subcommands to a streaming tape device. If you do not specify the **-f** flag with the *TapeName* parameter, the **TAPE** environment variable is used. If the environment variable does not exist, the **mt** command uses the **/dev/rmt0.1** device. The *TapeName* parameter must be a raw (not block) tape device. You can specify more than one operation with the *Count* parameter.

Subcommands

eof, weof Writes the number of end-of-file markers specified by the Count parameter at the

current position on the tape.

fsf Moves the tape forward the number of files specified by the Count parameter and

positions it to the beginning of the next file.

Moves the tape backwards the number of files specified by the Count parameter and bsf

positions it to the beginning of the last file skipped. If using the bsf subcommand would cause the tape head to move back past the beginning of the tape, then the tape will be

rewound, and the mt command will return EIO.

Moves the tape forward the number of records specified by the *Count* parameter. fsr hsr Moves the tape backwards the number of records specified by the *Count* parameter.

rewoff1, rewind Rewinds the tape. The Count parameter is ignored.

Prints status information about the specified tape device. The output of the status status

command may change in future implementations.

Flag

-f TapeName Specifies the TapeName parameter.

Examples

1. To rewind the rmt1 tape device, enter:

mt -f /dev/rmt1 rewind

2. To move forward two files on the default tape device, enter:

mt fsf 2

3. To write two end-of-file markers on the tape in the /dev/rmt0.6 file, enter:

mt -f /dev/rmt0.6 weof 2

Exit Status

Indicates a successful completion.

>0 Indicates an error occurred.

Files

/dev/rmt/n.n Specifies the raw streaming tape interface.

/usr/bin/mt Contains the mt command file.

Related Information

The tctl command.

The **environment** file, **rmt** special file.

The **ioctl** subroutine.

Tape drives in Operating system and device management.

mtrace Command

Purpose

Prints a multicast path from a source to a receiver.

Syntax

```
mtrace [ -I ] [ -M ] [ -n ] [ -p ] [ -s ] [ -U ] [ -g gateway ] [ -i if_addr ] [ -m max_hops ] [ -q nqueries ] [ -r
resp_dest ] [ -S statint ] [ -t ttl] [ -w wait ] source [ receiver ] [ group ]
```

Description

A trace query is passed hop-by-hop along the path from the receiver to the source, collecting hop addresses, packet counts, and routing error conditions along the path, and then the response is returned to the requestor. The default receiver is the host running the mtrace command, and the default group is 0.0.0.0.

Note: The **mtrace** command is intended for use in network testing, measurement, and management. Because the mtrace command heavily loads on the network, avoid using the mtrace command during typical operations or from automated scripts. It should be used primarily or with manual fault isolation. If the -g flag is specified, the source defaults to the host running mtrace and the receiver defaults to the router being addressed.

By default, the mtrace command first attempts to trace the full reverse path, unless the number of hops to trace is explicitly set with the -m flag. If there is no response within a 3-second timeout interval (changed with the -w flag), an * (asterisk) is printed and the probing switches to hop-by-hop mode. Trace queries are issued starting with a maximum hop count of one and increasing by one until the full path is traced or no response is received. At each hop, multiple probes are sent (default is three, changed with -q flag). The first half of the attempts (default is two) are made with the reply address set to standard multicast address, mtrace.mcast.net (224.0.1.32) with the ttl set to 32 more than what is needed to pass the thresholds seen so far along the path to the receiver. For each additional attempt, the ttl is increased by another 32 each time up to a maximum of 192. Because the desired router may not be able to send a multicast reply, the remainder of the attempts request that the response be sent via unicast to the host running the mtrace command.

Alternatively, the multicast ttl can be set explicitly with the -t flag, the initial multicast attempts can be forced to use unicast instead with the -U flag, the final unicast attempts can be forced to use multicast instead with the -M flag, or if you specify -UM, the mtrace command will first attempt using unicast and then multicast. For each attempt, if no response is received within the timeout, an * (asterisk) is printed. After the specified number of attempts have failed, the mtrace command will try to query the next hop router with a DVMRP_ASK_NEIGHBORS2 request to see what kind of router it is. The mtrace command will try to query three (changed with the -e flag) hops past a non-responding router. Even though the mtrace command is incapable of sending a response, it might be capable of forwarding the request.

Flags

-g gateway	Sends the trace query via unicast directly to the multicast router <i>gateway</i> rather than multicasting the query. This must be the last-hop router on the path from the intended source to the receiver.
-i if_addr	Uses if_addr as the local interface address (on a multi-homed host) for sending the trace query and as the default for the receiver and the response destination.
-1	Loops indefinitely printing packet rate and loss statistics for the multicast path every 10 seconds (see -S stat_int).
-m max_hops	Sets <i>max_hops</i> to the maximum number of hops that will be traced from the receiver to the source. The default is 32 hops and infinity for the DVMRP routing protocol).

-M	Always requests the response using multicast rather than attempting unicast for the last half of the tries.
-n	Prints hop addresses numerically rather than symbolically and numerically (saves a name server address-to-name lookup for each router found on the path).
-p	Listens passively for multicast responses from traces initiated by others. This works best when run on a multicast router.
-q nqueries	Sets the maximum number of query attempts for any hop to nqueries. The default is 3.
-r resp_dest	Sends the trace response to dhost rather than to the host on which the mtrace command is being run, or to a multicast address other than the one registered for this purpose (224.0.1.32).
-s	Prints a short form output including only the multicast path and not the packet rate and loss statistics.
-S statint	Changes the interval between statistics gathering traces to statint seconds (default 10 seconds).
-t <i>ttl</i>	Sets the ttl (time-to-live, or number of hops) for multicast trace queries and responses. The default is 127, except for local queries to the all routers multicast group that use the ttl of 1.
-U	Forces initial multicast attempts to use unicast instead.
-w wait	Sets the time to wait for a trace response to wait seconds (default 3 seconds).

Parameters

source	Specifies the host for which the multicast path from a particular receiver is sought. This is a required parameter.
receiver	Specifies the host from which the multicast path is sought for a particular source. Default is the host in which the mtrace command is running. This is an optional parameter.
group	Specifies the multicast group. This is an optional parameter.

Examples

In the following example, the two machines, 10.27.41.57 and 10.27.40.20, are on two different subnets separated by a router having two interfaces, 10.27.40.11 and 10.27.41.11. To find the multicast path from 10.27.40.20 to 10.27.41.57, type the following:

```
# mtrace 10.27.41.57 224.2.0.1
```

The following is displayed:

```
Mtrace from 10.27.41.57 to 10.27.40.20 via group 224.2.0.1
Querying full reverse path...
 0 ? (10.27.40.20)
-1 ? (10.27.40.11) DVMRP thresh^ 1
-2 ? (10.27.41.57)
Round trip time 1 ms; total ttl of 2 required.
Waiting to accumulate statistics... Results after 10 seconds:
             Response Dest Overall Packet Statistics For 224.0.1.32 Packet 10.27.41.57 To 224.2.6
_/ rtt 1 ms Rate Lost/Sent = Pct Rate
                                                 Packet Statistics For Traffic From
  Source
10.27.41.57
                                                 10.27.41.57 To 224.2.0.1
10.27.41.11
10.27.40.11
                   ttl 2
                                     0 pps
10.27.40.20
                 10.27.40.20
  Receiver
                 Query Source
```

Related Information

Related commands include the **mrouted** daemon and the **traceroute** command.

multibos Command

Purpose

Creates, updates, and manages multiple versions of the Base Operating System (BOS) on a rootvg.

Syntax

```
multibos -s [-I device {-a | -f file | -b file}] [-e file] [-i file] [-L file] [-pntNX]
multibos -c -l device {-a | -f file | -b file} [-pnNX]
multibos -m [-pnX]
multibos -u [-pnX]
multibos -B [-ntX]
multibos -S [-nX]
multibos -R [-ptX]
multibos -M file [-snptNX]
```

Description

The **multibos** command allows the root level administrator to create multiple instances of AIX on the same rootvg. The multibos setup operation creates a standby Base Operating System (BOS) that boots from a distinct boot logical volume (BLV). This creates two bootable sets of BOS on a given rootvg. The administrator can boot from either instance of BOS by specifying the respective BLV as an argument to the bootlist command or using system firmware boot operations. Two bootable instances of BOS can be simultaneously maintained. The instance of BOS associated with the booted BLV is referred to as the active BOS. The instance of BOS associated with the BLV that has not been booted is referred to as the standby BOS. Currently, only two instances of BOS are supported per rootyg.

The **multibos** command allows the administrator to access, install maintenance and technology levels for, update, and customize the standby BOS either during setup or in subsequent customization operations. Installing maintenance and technology updates to the standby BOS does not change system files on the active BOS. This allows for concurrent update of the standby BOS, while the active BOS remains in production.

In addition, the multibos command copies or shares logical volumes and file systems. By default, the BOS file systems (currently /, /usr, /var, and /opt,) and the boot logical volume are copied. The administrator can make copies of additional BOS objects (using the -L flag).

All other file systems and logical volumes are shared between instances of BOS. Separate log device logical volumes (for example, those that are not contained within the file system) are not supported for copy and are shared.

In AIX 5L Version 5.3 with the 5300-09 Technology Level, you can populate the standby instance with a later version such as AIX 6.1 with the 6100-02 Technology Level. The function is done by creating a mksysb backup of a system at a later version and then using the backup to populate the standby instance. For example, system A is at a level of 5.3.9.0 and system B is at a level of 6.1.2.0. You can create a backup of system B using the mksysb -M command and use the mksysb backup to populate a standby instance of the operating system on system A.

Notes:

- 1. While the **multibos** command is running, ensure that system activity is minimal.
- 2. Any logical volume or file system attributes that are new to the higher level are not implemented when the standby instance is created because the operating system at a lower level has no knowledge of the attributes.
- 3. Do not keep both an AIX 6.1 instance and an AIX 5.3 instance for an extended period. You might not be able to switch between the instances because of incompatibilities. Commit to one of the instances and remove the other.

The file system types (JFS or JFS2) of the **mksysb** backup need to be the same as that of the system where the multibos command is to be run. For example, if the /usr file system is a JFS2 file system, the /usr file system on the mksysb backup needs to be a JFS2 file system.

A log is stored in the /etc/multibos/logs/op.alog file after you run the multibos command. You can view the log file using the alog -f /etc/multibos/logs/op.alog -o command.

Note: You can create a backup that contains both instances by first mounting the standby instance (using the -m flag), and then creating the backup. However, you can restore the backup onto a disk only by using the alt disk mksysb command

Flags

-a	Specifies the update_all install option. Valid with setup and customization operation.
-В	Build boot image operation. The standby boot image is created and written to the standby BLV using the AIX bosboot command.
-b file	Specifies the install bundle to be installed during the setup or customization operation. The install bundle syntax should follow geninstall conventions.
-c	Performs a customized update of the software in standby BOS.
-e file	Lists active BOS files to be excluded during the setup operation in regular expression syntax.
-f file	Lists fixes (such as APARs) that are to be installed during the setup or customization operation. The syntax of the list follows instfix conventions.
-i file	Specifies optional image.data file to use instead of the default image.data file created from the current rootvg .
-L file	Specifies a file that contains a list of additional logical volumes to include in standby BOS.
-I device	Installs device or directory for software update during the setup or customization operation.
-m	Mounts standby BOS.
-M file	Specifies a file that contains a mksysb image. The mksysb image must have been created using the mksysb -M command beginning with AIX 6.1 with 6100-02.
-N	Skips boot image processing. This flag should only be used by experienced administrators that have a good understanding of the AIX boot process.
-n	Does not perform cleanup upon failure. This option is useful to retain multibos data after a failed operation.
-p	Performs a preview of the given operation. Valid with setup, remove, mount, unmount, and customization operations.
-R	Removes all standby BOS objects.

-S	Initiates an interactive shell with chroot access to the standby BOS file systems.
-s	Creates an instance of standby BOS.
-t	Prevents multibos from changing the bootlist.
-u	Unmounts standby BOS.
-X	Allows for automatic file system expansion if space is needed to perform tasks related to multibos . It is recommended that all multibos operations are executed with this flag.

Exit Status

All the multibos command operations completed successfully. >0 An error occurred.

Security

Only the root user can run the multibos command.

Examples

1. To perform a standby BOS setup operation preview, type:

multibos -Xsp

2. To set up standby BOS, type:

multibos -Xs

3. To set up standby BOS with optional image.data file /tmp/image.data and exclude list /tmp/exclude.list, type:

```
multibos -Xs -i /tmp/image.data -e /tmp/exclude.list
```

4. To set up standby BOS and install additional software listed as bundle file /tmp/bundle and located in the images source /images,, type:

```
multibos -Xs -b /tmp/bundle -1 /images
```

5. To execute a customization operation on standby BOS with the **update all** install option, type:

```
multibos -Xac -1 /images
```

6. To mount all standby BOS file systems, type:

```
multibos -Xm
```

7. To perform a standby BOS remove operation preview, type:

```
multibos -RXp
```

8. To remove standby BOS, type:

```
multibos -RX
```

9. To use an existing mksysb file /backups/mksysb1 to populate the standby instance of rootvg, enter the following command:

```
multibos -M /backups/mksysb1 -sX
```

Restrictions

- The multibos command is supported on AIX 5L Version 5.3 with the 5300-03 Recommended Maintenance package and later.
- · The current rootvg must have enough space for each BOS object copy. BOS object copies are placed on the same disk or disks as the original.
- The total number of copied logical volumes cannot exceed 128. The total number of copied logical volumes and shared logical volumes are subject to volume group limits.

Files

/usr/sbin/multibos /etc/multibos

Contains the **multibos** command. Contains multibos data and logs.

Related Information

The multibos utility section in *Installation and migration*.

my Command

Purpose

Moves files.

Syntax

To Move and Rename a File

mv [-E{forcelignore|warn}] [-i | -f] [-l] SourceFile ... TargetFile

To Move and Rename a Directory

mv -E{forcelignore|warn}] [-i | -f] [-l] SourceDirectory ... TargetDirectory

To Move Files or Directories to a Directory Maintaining Original File Names

mv -E{forcelignore|warn}] [-i | -f] [-l] SourceFile/SourceDirectory TargetDirectory

Description

Attention: The mv command can overwrite many existing files unless you specify the -i flag. The -i flag prompts you to confirm before it overwrites a file. If both the -f and -i flags are specified in combination, the last flag specified takes precedence.

The **mv** command moves files and directories from one directory to another or renames a file or directory. If you move a file or directory to a new directory, it retains the base file name. When you move a file, all links to other files remain intact, except when you move it to a different file system. When you move a directory into an existing directory, the directory and its contents are added under the existing directory.

When you use the **mv** command to rename a file or directory, the *TargetDirectory* parameter can specify either a new file name or a new directory path name.

If moving the file would overwrite an existing file that does not have write-permission set and if standard input is a workstation, the mv command displays the file-permission code and reads a line from standard input. If that line begins with a y or the locale's equivalent of a y, the my command moves the file. If the response is anything other than a y, the mv command does nothing to that file and continues with the next specified file. The file-permission code displayed may not fully represent the access permission if the TargetFile is associated with an ACL. When the parent directory of the SourceFile is writable and has the sticky bit set, one or more of the following conditions are true:

- · The user must own the file.
- The user must own the directory
- · The user must be a privileged user.
- · The file must be writable by the user.

This warning message and prompt for input can be overridden by using the -f option.

You can use the mv command to move files within the same file system or between file systems. Whether you are working in one file system or across file systems, the mv command copies the file to the target and deletes the original file. The mv command preserves in the new file the time of the most recent data modification, the time of the most recent access, the user ID, the group ID, the file mode, the extended attributes, and ACLs of the original file. For symbolic links, the my command preserves only the owner and group of the link itself.

If it is unable to preserve the owner and group ID, the mv command clears S_ISUID and S_ISGID bits in the target. The mv command prints a diagnostic message to stderr if it is unable to clear these bits, though the exit code is not affected.

The **mv** command modifies either the source file or the destination path if the command is prematurely terminated.

Note: The mv command supports the — (dash, dash) parameter as a delimiter that indicates the end of the flags.

The **mv** command will not move an object if the object is exported as an NFS version 4 referral. The referral object is marked as busy and remains so until it is unexported."

Flags

Attention: The mv command can overwrite many existing files unless you specify the -i flag. The -i flag prompts you to confirm before it overwrites a file. If both the -f and -i flags are specified in combination, the last flag specified takes precedence.

- -E The -E option requires one of the following arguments. If you omit the -E option, warn is the default behavior.
 - Fails the mv operation on a file if the fixed extent size or space reservation of the file cannot be preserved.

ignore Ignores any errors in preserving extent attributes.

Issues a warning if the space reservation or the fixed extent size of the file cannot be preserved.

- Does not prompt you before overwriting an existing file. -f
- -i Prompts you before moving a file or directory to an existing path name by displaying the name of the file followed by a question mark. If you answer with a line starting with y or the locale's equivalent of a y, the move continues. Any other reply prevents the move from occurring.
- -1 Suppresses the warning message during ACL conversion.

Examples

1. To rename a file, enter:

mv appendix apndx.a

This command renames appendix to apndx.a. If a file named apndx.a already exists, its old contents are replaced with those of appendix.

2. To move a directory, enter:

mv book manual

This command moves all files and directories under book to the directory named manual, if manual exists. Otherwise, the directory book is renamed manual.

3. To move a file to another directory and give it a new name, enter:

mv intro manual/chap1

This command moves intro to manual/chap1. The name intro is removed from the current directory, and the same file appears as chap1 in the directory manual.

4. To move a file to another directory, keeping the same name, enter:

mv chap3 manual

This command moves chap3 to manual/chap3

Note: Examples 1 and 3 name two files, example 2 names two existing directories, and example 4 names a file and a directory.

5. To move several files into another directory, enter:

mv chap4 jim/chap5 /home/manual

This command moves the chap4 file to the /home/manual/chap4 file directory and the jim/chap5 file to the /home/manual/chap5 file.

6. To use the mv command with pattern-matching characters, enter:

mv manual/* .

This command moves all files in the manual directory into the current directory. (period), retaining the names they had in manual. This move also empties manual. You must type a space between the asterisk and the period.

Note: Pattern-matching characters expand names of existing files only. For example, the command mv intro man*/chap1 does not work if the file manual/chap1 does not exist.

Exit Status

- All input files were moved successfully.
- >0 An error occurred.

Files

/usr/bin/mv

Contains the mv command.

Related Information

The **chmod** command, **In** command, **rm** command.

The **rename** subroutine.

Files in the Operating system and device management.

Directories in Operating system and device management.

Input and output redirection in Operating system and device management.

mvdir Command

Purpose

Moves (renames) a directory.

Syntax

mvdir Directory1 Directory2

Description

The mvdir command renames directories within a file system. To use the mvdir command, you must have write permission to *Directory1* and *Directory2* as well as in the parent directories.

The Directory1 parameter must name an existing directory. If Directory2 does not exist, Directory1 is moved to Directory2. If Directory2 exists, Directory1 becomes a subdirectory of Directory2. Neither directory can be a subset of the other.

The mvdir Command can also be used to move or rename files. If the *Directory1* parameter is an existing file name and the *Directory2* parameter is an existing directory name, the file specified by *Directory1* is moved to the directory specified by Directory2. If the Directory1 parameter is an existing file name and the Directory2 parameter does not yet exist, Directory2 replaces the file name Directory1. If both are existing file names, the file specified by Directory1 is renamed Directory2, and the existing Directory2 is removed.

The **mv** command provides the same functionality as the **mvdir** command.

The mvdir command will not rename a directory if the directory is exported for use by NFS version 4, or if the directory leads to a directory exported for use by NFS version 4. NFS version 4-exported directories and directories leading to NFS version 4-exported directories are marked as busy and remain so until unexported.

Example

To rename or move a directory to another location, enter:

mvdir appendixes manual

If manual does not exist, this renames the appendixes directory to manual.

If a directory named manual already exists, this moves appendixes and its contents to manual/appendixes. In other words, appendixes becomes a subdirectory of manual.

Files

/usr/sbin/mydir

Contains the mvdir command.

Related Information

The **mkdir** command. **mv** command.

The **rename** subroutine.

Directories in Operating system and device management.

File and directory access modes in the Operating system and device management introduces file ownership and permissions to access files and directories.

myfilt Command

Purpose

Moves a filter rule.

Syntax

mvfilt -v 4|6 -p p_fid -n n_fid

Description

Use the mvfilt command to change the position of a filter rule in the filter rule table. IPsec filter rules for this command can be configured using the **genfilt** command, IPsec smit (IP version 4 or IP version 6), or Web-based System Manager in the Virtual Private Network submenu.

Flags

- IP version of the filter rule. The value 4 specifies IP version 4 and the value 6 specifies IP version 6. Filter rule ID. It specifies the previous position of the rule in the filter rule table. For IP version 4, the -p
 - value of 1 is invalid since the first filter rule is unmoveable.
- Filter rule ID. It specifies the new position of the rule in the filter rule table after the move. For IP -n version 4, the value of 1 is invalid since the first filter rule is reserved and thus is unmoveable.

mvt Command

Purpose

Typesets English-language view graphs and slides.

Syntax

```
mvt [ -a ] [ -c ] [ -e ] [ -p ] [ -t ] [ -z ] [ -TName | -DDestination ] [ File ... | - ]
```

Description

The mvt command typesets its input with the mv macro package for view graphs and slides in a manner similar to the mmt command. The mvt command has flags to specify preprocessing by the tbl, eqn, pic, cw, and grap commands. The flags you select determine which pipelines, flags, and parameters are generated for the **troff** command and the macro package.

The mvt command, unlike the troff command, automatically pipes its output to a postprocessor, unless specifically requested not to do so. The user should not specify a postprocessor when using the mvt command. The path that the **mvt** command takes is as follows:

- 1. The -z flag (no postprocessor is used).
- 2. The **-T**Name flag.
- 3. The **TYPESETTER** environment variable is read.
- 4. The default is set to ibm3816.

File specifies the file that the **mvt** command formats.

Flags

Flags can occur in any order, but they must be displayed before the File parameter. If no file is specified, the mvt command prints a list of its flags.

-a	Displays readable troff output to the terminal.
-c	Calls the cw command.
-е	Calls the eqn command; also causes the eqn command to read the /usr/share/lib/pub/eqnchar file.
-g	Calls the grap command, which in turn calls the pic command.
-p	Calls the pic command.
-t	Calls the tbl command.
-z	Calls no output filter (or postprocessor) to process or redirect the output of the troff command.
-DDestination	Directs the output to the specified device destination. Supported value for the <i>Destination</i> variable is 4014 , which is the Tektronix 4014 terminal by way of the tc command.
-TName	Creates output for the troff device as specified by the <i>Name</i> variable. The output is sent through the appropriate postprocessor. The default is ibm3816 .

Forces input to be read from standard input.

Any other parameters or flags that you give the mvt command (such as the -a flag) are passed to the troff command.

The **mvt** command reads standard input when you specify the - (minus) flag instead of the *File* parameter.

Use the **-o**List flag of the **troff** command to specify ranges of pages to be output.

Note: If you call the mvt command with one or more of the -e, -t, -p, -g, or - flags, together with the -oList flag of the troff command, you may receive a broken pipe message. This occurs if you do not specify the last page of the document in the List variable. This broken pipe message is not an indication of any problem and can be ignored.

Environment Variables

TYPESETTER Contains information about a particular printing device.

Files

/usr/share/lib/pub/eqnchar

Contains special character definitions.

Related Information

The cw command, eqn command, grap command, mmt command, pic command, tbl command, tc command, troff command.

The eqnchar file format.

The article "mv Macro Package for the mvt and troff Commands" in the troff Command.

mwm Command

Purpose

Runs the AlXwindows Window Manager (MWM).

Syntax

mwm -display Host:Display:ScreenID -xrm ResourceString -multiscreen -name Name -screens Name [Name ...]

Description

The **mwm** command runs the AlXwindows Window Manager (MWM) and is often started by a display or session manager. The AlXwindows Window Manager (MWM) is an X Window System client that provides window management functionality and some session management functionality. It provides functions that facilitate control (by the user and the programmer) of elements of window states such as placement, size, icon or normal display, and input-focus ownership. It also provides session management functions such as stopping a client.

The appearance and behavior of the window manager can be altered by changing the configuration of specific resources. Resources are defined under X Defaults .

By default, the mwm command manages only the single screen specified by the -display option or the DISPLAY environment variable (by default, screen 0). If the -multiscreen option is specified or if the multiScreen resource is True, the mwm command tries to manage all the screens on the display.

When the **mwm** command is managing multiple screens, the **-screens** option can be used to give each screen a unique resource name. The names are separated by blanks, for example, -screens mwm0 mwm1. If there are more screens than names, resources for the remaining screens are retrieved using the first name. By default, the screen number is used for the screen name.

For information on windows, icons, resources, events, button and key bindings, menus, and variables, see the following sections:

- Windows
- Icons
- · Icon Box
- Component Appearance Resources
- General Appearance and Behavior Resources
- · Client-Specific Resources
- Window Manager Event Specification
- Button Bindings
- · Key Bindings
- Menu Panes
- Environment
- Related Information

Flags

Host Specifies the host name of a valid system on the network. Depending on the situation, this could be the host name of the user or the host name of a remote system.

Display Specifies the number (usually 0) of the display on the system on which the output is to be displayed.

ScreenID

Specifies the number of the screen where the output is to be displayed. This number is 0 for single-screen systems.

-xrm ResourceString Enables the named resources when starting the **mwm** command.

-multiscreen Causes the mwm command to manage all screens on the display. The default is

to manage only a single screen.

Causes the mwm command to retrieve its resources using the specified name, -name Name

as in Name*Resource.

Specifies the resource names to use for the screens managed by MWM. If -screens Name [Name [...]]

MWM is managing a single screen, only the first name in the list is used. If multiple screens are being managed, the names are assigned to the screens in order, starting with screen 0. For example, screen 0 gets the first name and

screen 1 gets the second name.

Windows

Default window manager window frames have the following distinct components with associated functions:

title area In addition to displaying the client's title, the title area is used to move the window. To

> move the window, place the pointer over the title area, press button 1 and drag the window to a new location. A wire frame is moved during the drag to indicate the new location.

When the button is released, the window is moved to the new location.

title bar The title bar includes the title area, the Minimize button, the Maximize button, and the

Window Menu button. In shaped windows, such as round windows, the title bar floats

above the window.

Minimize button To turn the window into an icon, click button 1 on the Minimize button (the frame box with

a small square in it).

To make the window fill the screen (or enlarge to the largest size allowed by the **Maximize button**

configuration files), click button 1 on the Maximize button (the frame box with a large

square in it).

The Window Menu button is the frame box with a horizontal bar in it. To pull down the Window Menu button

window menu, press button 1. While pressing the button, drag the pointer on the menu to vour selection and release the button when your selection is highlighted. Pressing button 3 in the title bar or resize border handles also posts the window menu. Alternately, you can click button 1 to pull down the menu and keep it posted; then position the pointer and select. You can also post the window menu by pressing the Shift+Esc or Alt+Space key sequence. Double-clicking button 1 with the pointer on the Window Menu button closes

the window. The following table lists the contents of the window menu:

Default Window Menu

Selection	Accelerator	Description
Restore	Alt+F5	Restores the window to its size before
		minimizing or maximizing.
Move	Alt+F7	Allows the window to be moved with keys
		or mouse.
Size	Alt+F8	Allows the window to be resized.
Minimize	Alt+F9	Turns the window into an icon.
Maximize	Alt+F10	Makes the window fill the screen.
Lower	Alt+F3	Moves window to bottom of window stack.
Close	Alt+F4	Causes client to stop.

resize border handles

To change the size of a window, move the pointer over a resize border handle (the cursor changes), press button 1, and drag the window to a new size. When the button is released, the window is resized. While dragging is being done, a rubber-band outline is displayed to

indicate the new window size.

matte An optional matte decoration can be added between the client area and the window frame.

A matte is not actually part of the window frame. There is no functionality associated with a

matte.

Icons

Icons are small graphic representations of windows. A window can be iconified (minimized) using the Minimize button on the window frame. Icons provide a way to reduce clutter on the screen.

Pressing the left mouse button when the pointer is over an icon causes the icon's window menu to open. Releasing the button (press + release without moving mouse = click) causes the menu to stay posted. The menu contains the following selections:

Icon Window Menu

Selection	Accelerator	Description
Restore	Alt+F5	Opens the associated window.
Move	Alt+F7	Allows the icon to be moved with keys.
Size	Alt+F8	Inactive (not an option for icons).
Minimize	Alt+F9	Inactive (not an option for icons).
Maximize	Alt+F10	Opens the associated window and makes it fill the screen.
Lower	Alt+F3	Moves icon to bottom of icon stack.
Close	Alt+F4	Removes client from window manager management.

Pressing button 3 over an icon also causes the icon's window menu to open. To make a menu selection, drag the pointer over the menu and release button 3 when the desired item is highlighted.

Double-clicking button 1 on an icon calls the f.restore and raise function and restores the icon's associated window to its previous state. For example, if a maximized window is iconified, double-clicking button 1 restores it to its maximized state. Double-clicking button 1 on the icon box's icon opens the icon box and allow access to the contained icons. (Double-clicking a mouse button is a quick way to perform a function.) Pressing the Shift+Esc key sequence or the pop-up Menu key causes the icon window menu of the currently selected icon to open.

Icon Box

When icons begin to clutter the screen, they can be packed into an icon box. (To use an icon box, the window manager must be started with the icon box configuration already set.) The icon box is a window manager window that holds client icons. It includes one or more scroll bars when there are more window icons than the icon box can show at the same time.

Icons in the icon box can be manipulated with the mouse. The following button action descriptions summarize the behavior of this interface. Button actions apply whenever the pointer is on any part of the icon. Double-clicking an icon in the icon box calls the f.restore and raise function.

Button Action	Description
Button 1 click	Selects the icon.
Button 1 double-click	Normalizes (opens) the associated window.
Button 1 double-click	Raises an already open window to the top of the stack.
Button 1 drag	Moves the icon.
Button 3 press	Causes the menu for that icon to open.
Button 3 drag	Highlights items as the pointer moves across the menu.

Pressing mouse button 3 when the pointer is over an icon causes the menu for that icon to open.

Icon Menu for Icon Box

Selection	Accelerator	Description
Restore	Alt+F5	Opens the associated window (if not already open).
Move	Alt+F7	Allows the icon to be moved with keys.
Size	Alt+F8	Inactive.
Minimize	Alt+F9	Inactive.
Maximize	Alt+F10	Opens the associated window (if not already open) and maximizes its size.
Lower	Alt+F3	Inactive.
Close	Alt+F4	Removes client from window manager management.

To pull down the window menu for the icon box itself, press button 1 with the pointer over the menu button for the icon box. The window menu of the icon box differs from the window menu of a client window: The Close selection is replaced with the Packlcons (Shift+Alt+F7) selection. When selected, the Packlcons option packs the icons in the box to achieve neat rows with no empty slots.

You can also post the window menu by pressing the Shift+Esc or Alt+Space key sequence. Pressing the pop-up Menu key causes the icon window menu of the currently selected icon to open.

Input Focus

The **mwm** command supports (by default) a keyboard input focus policy of explicit selection. This means when a window is selected to get keyboard input, it continues to get keyboard input until the window is

withdrawn from window management, another window is explicitly selected to get keyboard input, or the window is iconified. Several resources control the input focus. The client window with the keyboard input focus has the active window appearance with a visually distinct window frame.

The following table and key action descriptions summarize the keyboard input focus selection behavior:

Button Action	Object	Function Description
Button 1 press	Window or window frame	Keyboard focus selection
Button 1 press	Icon	Keyboard focus selection

Key Action Function Description

Alt+Tab Moves the input focus to next window in the window stack.

Alt+Shift+Tab Moves the input focus to the previous window in the window stack (available only in explicit

focus mode).

Window Stacking

There are two types of window stacks: global window stacks and an application's local family window stack.

The global stacking order of windows can be changed as a result of setting the keyboard input focus, iconifying a window, or performing a window manager window stacking function. When keyboard focus policy is explicit the default value of the focusAutoRaise resource is True. This causes a window to be raised to the top of the stack when it receives input focus, for example, by pressing button 1 on the title bar. The key actions defined in the preceding list raises the window receiving focus to the top of the stack.

In pointer mode, the default value of the focusAutoRaise resource is False; that is, the window stacking order is not changed when a window receives keyboard input focus. The following key actions can be used to cycle through the global window stack:

Key Action Function Description

Alt+Esc Places top window on bottom of stack. Alt+Shift+Esc Places bottom window on top of stack.

By default, a window's icon is placed on the bottom of the stack when the window is iconified; however, the default can be changed by the lowerOnlconify resource.

Transient windows (secondary windows such as dialog boxes) stay above their parent windows by default. However, an application's local family stacking order can changed to allow a transient window to be placed below its parent top-level window. The following parameter values show the modification of the stacking order for the f.lower function:

f.lower Lowers the transient window within the family (staying above the parent) and

lowers the family in the global window stack.

Lowers the transient window within the family (staying above the parent) but f.lower [within]

does not lower the family in the global window stack.

f.lower [freeFamily] Lowers the window separate from its family stack (below the parent), but does

not lower the family in the global window stack.

The within and freeFamily parameter values can also be used with the f.raise and f.raise lower functions.

X Defaults

The **mwm** command is configured from its resource database. This database is built from the following sources. They are listed in order of precedence.

- 1. mwm command line options
- 2. XENVIRONMENT variable or \$HOME/.Xdefaults-host
- 3. RESOURCE_MANAGER root window property or \$HOME/.Xdefaults
- 4. \$HOME/Mwm
- 5. /usr/lib/X11/app-defaults/Mwm.

The /usr/lib/X11/app-defaults/Mwm and \$HOME/Mwm file names represent customary locations for these files. The actual location of the systemwide class resource file might depend on the XFILESEARCHPATH environment variable and the current language environment. The actual location of the user-specific class resource file might depend on the XUSERFILESEARCHPATH and XAPPLRESDIR environment variables and the current language environment.

Entries in the resource database can refer to other resource files for specific types of resources. These include files that contain bitmaps, fonts, and mwm-specific resources such as menus and behavior specifications (for example, button and key bindings).

Mwm is the resource class name of the mwm command and mwm is the resource name used by the mwm command to look up resources. (For looking up resources of multiple screens, the -screens command-line option specifies resource names such as mwm_b+w and mwm_color.) In the following discussion of resource specification, "Mwm" and "mwm" (and the aliased mwm resource names) can be used interchangeably, but "mwm" takes precedence over "Mwm". The mwm command uses the following types of resources:

component appearance resource set	These resources specify appearance attributes of window manager user-interface components. They can be applied to the appearance of window manager menus, feedback windows (for example, the window reconfiguration feedback window), client window frames, and icons.
frame and icon component resource set	This subset of component appearance resources specifies attributes that are specific to frame and icon components.
general appearance and behavior resource set	These resources specify the mwm command appearance and behavior (for example, window management policies). They are not set separately for different mwm command user-interface components.
client-specific resource set	These mwm resources can be set for a particular client window or class of client windows. They specify client-specific icon and client window frame appearance and behavior.

Resource identifiers can be either a resource name (for example, foreground) or a resource class (for example, Foreground). If the value of a resource is a file name and if the file name is prefixed by the ~/ (tilde followed by a slash) characters, it is relative to the path contained in the **HOME** environment variable (generally the user's home directory).

Component Appearance Resources

The syntax for specifying component appearance resources that apply to window manager icons, menus, and client window frames is as follows:

Mwm*ResourceID

For example, Mwm*foreground is used to specify the foreground color for the mwm command menus, icons, client window frames, and feedback dialogs.

The syntax for specifying component appearance resources that apply to a particular **mwm** component is as follows:

Mwm*[Menullcon|Client|Feedback]*ResourceID

If Menu is specified, the resource is applied only to Mwm menus; if *Icon* is specified, the resource is applied to icons; and if *Client* is specified, the resource is applied to client window frames. For example, Mwm*lcon*foreground is used to specify the foreground color for the mwm command icons, Mwm*Menu*foreground specifies the foreground color for the mwm command menus, and Mwm*Client*foreground is used to specify the foreground color for the mwm command client window frames.

The appearance of the title area of a client window frame (including window management buttons) can be separately configured. The syntax for configuring the title area of a client window frame is as follows:

Mwm*Client*Title*ResourceID

For example, Mwm*Client*Title*foreground specifies the foreground color for the title area. Defaults for title area resources are based on the values of the corresponding client window frame resources.

The appearance of menus can be configured based on the name of the menu. The syntax for specifying menu appearance by name is as follows:

Mwm*Menu*MenuName*ResourceID

For example, Mwm*Menu*MyMenu*foreground specifies the foreground color for the menu named MyMenu.

The user can also specify resources for window manager menu components (the gadgets that comprise the menu). These may include, for example, a menu title, a title separator, one or more buttons, and separators. If a menu contains more than one instance of a class, such as multiple PushButtonGadget gadgets, the name of the first instance is PushButtonGadget1, the second is PushButtonGadget2, and so on. The following list identifies the naming conventions used for window manager menu components:

TitleName Menu title LabelGadget **TitleSeparator** Menu title SeparatorGadget CascadeButtonGadgetn CascadeButtonGadget PushButtonGadgetn PushButtonGadget SeparatorGadgetn SeparatorGadget

The following component appearance resources that apply to all window manager parts can be specified.

Component Appearance Resource Set

Name	Properties
background	Class Background
	Value type color
	Default varies ¹
backgroundPixmap	Class BackgroundPixmap
	Value type string ²
	Default varies ¹

Name	Properties
bottomShadowColor	Class Foreground
	Value type
	color
	Default varies ¹
bottomShadowPixmap	Class BottomShadowPixmap
	Value type string ²
	Default varies ¹
fontList	Class FontList
	Value type string ³
	Default "fixed"
foreground	Class Foreground
	Value type
	color
	Default varies ¹
saveUnder	Class SaveUnder
	Value type True of False
	Default False
topShadowColor	Class Background
	Value type color
	Default varies ¹
topShadowPixmap	Class TopShadowPixmap
	Value type string ²
	Default varies ¹
background	Class Background
	Value type color
	Default varies ¹
backgroundPixmap	Class BackgroundPixmap
	Value type string ²
	Default varies ¹
	Dollant Valles

Name	Properties
bottomShadowColor	Class Foreground
	Value type
	color
	Default varies ¹
bottomShadowPixmap	Class BottomShadowPixmap
	Value type string ²
	Default varies ¹
fontList	Class FontList
	Value type string ³
	Default "fixed"
foreground	Class Foreground
	Value type color
	Default varies ¹
saveUnder	Class SaveUnder
	Value type
	True of False
	Default False
topShadowColor	Class Background
	Value type color
	Default varies ¹
topShadowPixmap	Class TopShadowPixmap
	Value type
	string ²
	Default varies ¹

Notes:

- 1. The default is chosen based on the visual type of the screen.
- 2. Image name.
- 3. X Version 11 Release 4 (X11R4) font description.

background (class Background)

backgroundPixmap (class
BackgroundPixmap)

bottomShadowColor (class Foreground)

Specifies the background color. Any legal X color can be specified. The default value is chosen based on the visual type of the screen. Specifies the background pixmap of the **mwm** decoration when the window is inactive (does not have the keyboard focus). The default value is chosen based on the visual type of the screen.

Specifies the bottom shadow color. This color is used for the lower and right bevels of the window manager decoration. Any legal X color can be specified. The default value is chosen based on the visual type of the screen.

bottomShadowPixmap (class Specifies the bottom shadow pixmap. This pixmap is used for the BottomShadowPixmap) lower and right bevels of the window manager decoration. The default is chosen based on the visual type of the screen. Specifies the font used in the window manager decoration. The fontList (class FontList) character encoding of the font needs to match the character encoding of the strings that are used. The default is the fixed value. foreground (class Foreground) Specifies the foreground color. The default is chosen based on the visual type of the screen. saveUnder (class SaveUnder) Controls the repainting of windows that are uncovered after being obscured. This resource indicates whether save unders are used for mwm components. For this to have any effect, save unders must be implemented by the X server. If save unders are implemented, the X server saves the contents of windows obscured by windows that have the save under attribute set. If the **saveUnder** resource is True, the mwm command sets the save under attribute on the window manager frame of any client that has it set. If the saveUnder resource is False, save unders is not used on any window manager frames. The default value is False. topShadowColor (class Background) Specifies the top shadow color. This color is used for the upper and left bevels of the window manager decoration. The default is chosen

topShadowPixmap (class TopShadowPixmap)

based on the visual type of the screen. Specifies the top shadow pixmap. This pixmap is used for the upper and left bevels of the window manager decoration. The default is chosen based on the visual type of the screen.

Frame and Icon Component Resource Set

Note: Hyphens in the following table are for readability purposes only. Do not include hyphens within names in programs.

Name	Propert	ies
activeBackground	Class	Background
	Value ty	ре
		color
	Default	varies ¹
activeBackground-Pixmap	Class	BackgroundPixmap
	Value ty	
		string ²
	Default	varies ¹
activeBottomShadow-Color	Class	Foreground
	Value ty	ре
		color
	Default	varies ¹
activeBottomShadow-Pixmap	Class	BottomShadow-Pixmap
	Value ty	ре
		string ²
	Default	varies ¹

Name	Properties
activeForeground	Class Foreground
	Value type
	color
	Default varies ¹
activeTopShadowColor	Class Background
	Value type
	color
antima Tam Ohandara Birmana	Default varies ¹
activeTopShadowPixmap	Class TopShadowPixmap
	Value type
	string ²
	Default varies ¹
activeBackground	Class Background
	Value type
	color
	Default varies ¹
activeBackgroundPixmap	Class BackgroundPixmap
	Value type
	string ²
	Default varies ¹
activeBottomShadowColor	Class Foreground
	Value type
	color
	Default varies ¹
activeBottomShadowPixmap	Class BottomShadowPixmap
	Value type
	string ²
	Default varies ¹
activeForeground	Class Foreground
	Value type
	color
	Default varies ¹
activeTopShadowColor	Class Background
	Value type
	color
	Default varies ¹

Name	Properties
activeTopShadowPixmap	Class TopShadowPixmap
	Value type string ²
	Default varies ¹

Notes:

- 1. The default is chosen based on the visual type of the screen.
- 2. Image name.

activeBackground (class Background)

activeBackgroundPixmap (class BackgroundPixmap)

activeBottomShadowColor (class Foreground)

activeBottomShadowPixmap (class BottomShadowPixmap)

activeForeground (class Foreground)

activeTopShadowColor (class Background)

activeTopShadowPixmap (class TopShadowPixmap)

Specifies the background color of the **mwm** decoration when the window is active (has the keyboard focus). The default is chosen based on the visual type of the screen. Specifies the background pixmap of the **mwm** decoration when the window is active (has the keyboard focus). The default is chosen based on the visual type of the screen. Specifies the bottom shadow color of the **mwm** decoration when the window is active (has the keyboard focus). The default is chosen based on the visual type of the screen. Specifies the bottom shadow pixmap of the **mwm** decoration when the window is active (has the keyboard focus). The default is chosen based on the visual type of the screen.

Specifies the foreground color of the **mwm** decoration when the window is active (has the keyboard focus). The default is chosen based on the visual type of the screen. Specifies the top shadow color of the **mwm** decoration when the window is active (has the keyboard focus). The default is chosen based on the visual type of the screen. Specifies the top shadow pixmap of the mwm decoration when the window is active (has the keyboard focus). The default is chosen based on the visual type of the screen.

General Appearance and Behavior Resources

The syntax for specifying general appearance and behavior resources is as follows:

Mwm*ResourceID

For example, Mwm*keyboardFocusPolicy specifies the window manager policy for setting the keyboard focus to a particular client window.

General Appearance and Behavior Resource Set

Note: Hyphens in the following table are for readability purposes only. Do not include hyphens within names in programs.

Name	Properties
autoKeyFocus	Class AutoKeyFocus Value type
	True or False
	Default True

Name	Properties
autoRaiseDelay	Class AutoRaiseDelay
	Value type
	millisec.
	Default 500
bitmapDirectory	Class BitmapDirectory
	Value type directory
	Default /usr/include/X11/bitmaps
buttonBindings	Class ButtonBindings
	Value type string
	Default "DefaultButton-Bindings"
cleanText	Class CleanText
	Value type
	True or False
	Default True
clientAutoPlace	Class ClientAutoPlace
	Value type
	True or False
	Default True
colormapFocusPolicy	Class ColormapFocus-Policy
	Value type
	string
	Default keyboard
configFile	Class ConfigFile
	Value type file
	Default .mwmrc
deiconifyKeyFocus	Class DeiconifyKeyFocus
	Value type
	True or False
	Default True
doubleClickTime	Class DoubleClickTime
	Value type milliseconds
	Default multiclick time

Name	Properties
enableWarp	Class enableWarp
	Value type
	True or False
	Default True
enforceKeyFocus	Class EnforceKeyFocus
	Value type
	True or False
	Default True
fadeNormallcon	Class FadeNormallcon
	Value type
	True or False
	Default False
feedbackGeometry	Class FeedbackGeometry
	Value type
	string
	Default center on screen
frameBorderWidth	Class FrameBorderWidth
	Value type
	pixels
	Default varies
iconAutoPlace	Class IconAutoPlace
	Value type True or False
	Default True
iconBoxGeometry	Class IconBoxGeometry
	Value type
	string
	Default 6x1+0-0
iconBoxName	Class IconBoxName
	Value type
	string
	Default iconbox
iconBoxSBDisplayPolicy	Class IconBoxSBDisplayPolicy
	Value type
	string
	Default all

Name	Properties
iconBoxTitle	Class IconBoxTitle
	Value type
	XmString
	Default Icons
iconClick	Class IconClick
	Value type True or False
	Default True
iconDecoration	Class IconDecoration
	Value type
	string
icenimose Mevimum	Default varies
iconlmage-Maximum	Class IconImage-Maximum
	Value type width x height
	Default 50x50
iconlmageMinimum	
	Class IconImageMinimum
	Value type width x height
	Default 16x16
iconPlacement	Class IconPlacement
	Value type
	string
	Default left bottom
iconPlacementMargin	Class IconPlacementMargin
	Value type pixels
	Default varies
interactivePlacement	
	Class InteractivePlacement
	Value type True or False
	Default False
keyBindings	Class KeyBindings
	Value type
	string
	Default "DefaultKeyBindings"

Name	Properties		
keyboardFocusPolicy	Class KeyboardFocusPolicy		
	Value type		
	string		
	Default explicit		
limitResize	Class LimitResize		
	Value type		
	True or False		
	Default True		
lowerOnlconify	Class LowerOnlconify		
	Value type		
	True or False		
	Default True		

maximumMaximuSize	alone H. Co. H. Co. O.		
	Class MaximumMaximuSize		
	Value type width x height (pixels)		
	Default 2X screen width & height		
moveOpaque	Class MoveOpaque		
	Value type		
	True or False		
	Default False		
moveThreshold	Class MoveThreshold		
	Value type pixels		
	Default 4		
multiScreen	Class MultiScreen		
	Value type True or False		
	Default False		
passButtons	Class PassButtons		
	Value type True or False		
	Default False		
PassSelectButton	Class PassSelectButton		
	Value type		
	True or False		
	Default True		

positionIsFrame			
positionisi rame	Class PositionIsFrame		
	Value type		
	True or False		
	Default True		
positionOnScreen	Class PositionOnScreen		
	Value type		
	True or False		
	Default True		
quitTimeout	Class QuitTimeout		
	Value type		
	milliseconds		
	Default 1000		
raiseKeyFocus	Class RaiseKeyFocus		
	Value type		
	True or False		
	Default False		
resizeBorderWidth	Class ResizeBorderWidth		
	Value type pixels		
	Default varies		
resizeCursors	Class ResizeCursors		
	Value type True or False		
	Default True		
screens			
	Class Screens		
	Value type string		
	Default varies		
showFeedback			
onom oodbaok	Class ShowFeedback		
	Value type string		
	Default all		
startupKeyFocus			
	Class StartupKeyFocus		
	Value type True or False		
	Default True		
transientDecoration	Class TransientDecoration		
	Value type		
	string		
	Default menu title		

transientFunctions	Class	TransientFunctions	
	Value type		
		string	
	Default	-minimize -maximize	
uselconBox	Class	UselconBox	
	Value type		
		True or False	
	Default	False	
wMenuButtonClick	Class	WMenuButtonClick	
	Value type		
		True or False	
	Default	True	
wMenuButtonClick2	Class	WMenuButtonClick2	
	Value type		
		True or False	
	Default	True	

autoKeyFocus (class AutoKeyFocus)

Controls whether the focus is set to the previous window that had the focus. If the autoKeyFocus resource is given a value of True and a window with the keyboard input focus is withdrawn from window management or is iconified, the focus is set to the previous window that had the focus. If the value given is False, there is no automatic setting of the keyboard input focus. It is recommended that both the autoKeyFocus resource and the startupKeyFocus resource be set to a value of True to work with tear-off menus. The default value is True. This resource is available only when the keyboard input focus policy is set to the explicit value.

autoRaiseDelay (class AutoRaiseDelay)

Specifies the amount of time in milliseconds (ms) that the mwm command waits before raising a window after it gets the keyboard focus. The default value of this resource is 500 (milliseconds). This resource is available only when the focusAutoRaise resource is True and the keyboard focus policy is the pointer value.

bitmapDirectory (class BitmapDirectory)

Identifies a directory to be searched for bitmaps referenced by mwm resources. This directory is searched if a bitmap is specified without an absolute path name. The default value for this resource is /usr/include/X11/bitmaps. The /usr/include/X11/bitmaps directory represents the customary locations for this directory. The actual location of this directory may vary on some systems. If the bitmap is not found in the specified directory, the XBMLANGPATH environment variable is searched.

buttonBindings (class ButtonBindings)

Identifies the set of button bindings for window management functions. The named set of button bindings is specified in the mwm resource description file. These button bindings are merged with the built-in default bindings. The default value for this resource is DefaultButtonBindings.

cleanText (class CleanText)

clientAutoPlace (class ClientAutoPlace)

colormapFocusPolicy (class ColormapFocusPolicy)

configFile (class ConfigFile)

deiconifyKeyFocus (class DeiconifyKeyFocus)

doubleClickTime (class DoubleClickTime)

enableWarp (class EnableWarp)

Controls the display of window manager text in the client title and feedback windows. If the default value of True is used, the text is drawn with a clear (no stipple) background. This makes text easier to read on monochrome systems where a backgroundPixmap is specified. Only the stippling in the area immediately around the text is cleared. If False, the text is drawn directly on top of the existing background.

Determines the position of a window when the window does not have a user-specified position. With a value of True, windows are positioned with the top left corners of the frames offset horizontally and vertically. A value of False causes the currently configured position of the window to be used. In either case, the mwm command attempts to place the windows totally on-screen. The default value is True.

Indicates the colormap focus policy that is to be used. If the resource value is explicit, a colormap selection action is done on a client window to set the colormap focus to that window. If the value is pointer, the client window containing the pointer has the colormap focus. If the value is keyboard, the client window that has the keyboard input focus has the colormap focus. The default value for this resource is keyboard.

Contains the path name for an mwm resource description file.

If the path name begins with the ~/ characters, the mwm command considers it to be relative to the user's home directory (as specified by the **HOME** environment variable). If the **LANG** environment variable is set, the mwm command looks for \$HOME/\$LANG/ configFile. If that file does not exist or if LANG is not set, mwm looks for \$HOME/configFile.

If the **configFile** path name does not begin with the ~/ characters, **mwm** considers it to be relative to the current working directory.

If the **configFile** resource is not specified or if that file does not exist, the **mwm** command uses several default paths to find a configuration file. If the LANG environment variable is set, the mwm command looks for the configuration file first in the \$HOME/\$LANG/.mwmrc file. If that file does not exist or if the LANG environment variable is not set, the mwm command looks for the \$HOME/.mwmrc file. If the \$HOME/.mwmrc file does not exist and if the LANG environment variable is set, the mwm command next looks for the /usr/lib/X11/\$LANG/system.mwmrc file. If the /usr/lib/X11/\$LANG/ system.mwmrc file does not exist or if the LANG environment variable is not set, the **mwm** command looks for /usr/lib/X11/system.mwmrc.

Determines whether a window receives the keyboard input focus when it is deiconified (normalized). The default value is True. This resource applies only when the keyboard input focus policy is set to the explicit value.

Sets the maximum time (in ms) between the clicks (button presses) that make up a double-click. The default value of this resource is the display's multiclick time.

Causes the **mwm** command to warp the pointer to the center of the selected window during keyboard-controlled resize and move operations. Setting the value to False causes the mwm command to leave the pointer at its original place on the screen unless the user explicitly moves it with the cursor keys or pointing device. The default value of this resource is True.

enforceKeyFocus (class EnforceKeyFocus)

fadeNormallcon (class FadeNormallcon)

feedbackGeometry (class FeedbackGeometry)

frameBorderWidth (class FrameBorderWidth)

iconAutoPlace (class IconAutoPlace)

iconBoxGeometry (class IconBoxGeometry)

iconBoxName (class IconBoxName)

iconBoxSBDisplayPolicy (class IconBoxSBDisplayPolicy)

iconBoxTitle (class IconBoxTitle)

iconClick (class IconClick)

Determines whether the keyboard input focus is always explicitly set to selected windows even if there is an indication that they are globally active input windows. (An example of a globally active window is a scroll bar that can be operated without setting the focus to that client.) If the resource is False, the keyboard input focus is not explicitly set to globally active windows. The default value is True. Determines whether an icon is unavailable whenever it is normalized (its window is opened). The default value is False.

Sets the position of the move and resize feedback window. If this resource is not specified, the default is to place the feedback window at the center of the screen. The value of the resource is a standard window geometry string with the following syntax:

[=][{+-}*XOffset*{+-}*YOffset*]

Specifies the width in pixels of a client window frame border without resize handles. The border width includes the three-dimensional (3-D) shadows. The default value is based on the size and resolution of the screen.

Indicates whether the window manager arranges icons in a particular area of the screen or places each icon where the window was when it was iconified. The True value indicates that icons are arranged in a particular area of the screen determined by the **iconPlacement** resource. The False value indicates that an icon is placed at the location of the window when it is iconified. The default is True. Indicates the initial position and size of the icon box. The value of the resource is a standard window geometry string with the following syntax:

[=][WidthxHeight][{+-}XOffset{+-}YOffset]

If the offsets are not provided, the iconPlacement policy is used to determine the initial placement. The units for width and height are columns and rows.

The actual screen size of the icon box window depends on the iconImageMaximum (size) and iconDecoration resources. The default value for size is (6 times iconWidth + padding) wide by (1 times iconHeight + padding) high. The default value of the location is

Specifies the name that is used to look up icon box resources. The default name is iconbox.

Specifies the scroll bar display policy of the window manager in the icon box. The resource has the following three possible values: all, vertical, and horizontal. The default value, all, causes both vertical and horizontal scroll bars always to be displayed. The vertical value causes a single vertical scroll bar to be displayed in the icon box and sets the orientation of the icon box to horizontal (regardless of the iconBoxGeometry specification). The horizontal value causes a single horizontal scroll bar to be displayed in the icon box and sets the orientation of the icon box to vertical (regardless of the iconBoxGeometry specification).

Specifies the name that is used in the title area of the icon box frame. The default value is Icons.

Specifies whether the system menu is posted and remains posted when an icon is clicked. The default value is True.

iconDecoration (class IconDecoration)

iconlmageMaximum (class IconImageMaximum)

iconlmageMinimum (class IconImageMinimum)

iconPlacement (class IconPlacement)

Specifies the general icon decoration. The resource value is label (only the label part is displayed) or image (only the image part is displayed) or label image (both the label and image parts are displayed). A value of activelabel can also be specified to get a label (not truncated to the width of the icon) when the icon is selected. The default icon decoration for icon box icons is that each icon has a label part and an image part (label image). The default icon decoration for standalone icons is that each icon has an active label part, a label part, and an image part (activelabel, label, and image).

Specifies the maximum size of the icon image. The resource value is Width x Height (for example, 64x64). The maximum supported size is 128x128. The default value of this resource is 50x50.

Specifies the minimum size of the icon image. The resource value is Width x Height (for example, 32x50). The minimum supported size is 16x16. The default value of this resource is 16x16.

Specifies the icon placement scheme to be used. The resource value has the following syntax:

PrimaryLayout SecondaryLayout [Tight]

The layout values are described as one of the following:

top Lays out the icons from top to bottom.

bottom Lays out the icons from bottom to top.

left Lays out the icons from left to right.

Lays out the icons from right to left.

A horizontal (vertical) layout value must not be used for both the PrimaryLayout and the SecondaryLayout (for example, do not use top for the PrimaryLayout and bottom for the SecondaryLayout). The PrimaryLayout indicates at the time an icon placement is done whether the icon is placed in a row or a column and the direction of placement. The SecondaryLayout indicates where to place new rows or columns.

For example, the top right value indicates that icons should be placed top to bottom on the screen and that columns should be added from right to left on the screen. The default placement is the left bottom value (icons are placed from left to right on the screen, with the first row on the bottom of the screen, and new rows added from the bottom of the screen to the top of the screen). A tight value places icons with zero spacing between icons. This value is useful for aesthetic reasons, as well as for terminals with small screens.

The following is a list of options for **iconPlacement** values:

Icon Placement

Appropriate Scheme

From left to right across the top of the screen, new rows below Left top

From right to left across the top of the screen, new rows below Right top

From left to right across the bottom of the screen, new rows above Left bottom

From right to left across the bottom of the screen, new rows above Right bottom

From bottom to top along the left of the screen, new columns to right Bottom left

From bottom to top along the right of the screen, new columns to left Bottom right

From top to bottom along the left of the screen, new columns to right Top left

From top to bottom along the right of the screen, new columns to left Top right

Sets the distance between the edge of the screen and the icons that are placed along the edge of the screen. The value should be greater than or equal to 0. A default value is used if the value specified is invalid. The default value for this resource is equal to the space between icons as they are placed on the screen (this space is based on maximizing the number of icons in each row and column). Controls the initial placement of new windows on the screen. If the value is True, the pointer shape changes before a new window is placed on the screen to indicate to the user that a position needs to be selected for the upper-left corner of the window. If the value is False, windows are placed according to the initial window configuration attributes. The default value of this resource is False.

Identifies the set of key bindings for window management functions. If specified, these key bindings replace the built-in default bindings. The named set of key bindings is specified in mwm resource description file. The default value for this resource is DefaultKeyBindings. Determines the keyboard focus policy. If set to the pointer value, the keyboard focus policy has the keyboard focus set to the client window that contains the pointer (the pointer could also be in the client window decoration that the mwm command adds). If set to the explicit value, the policy is to have the keyboard focus set to a client window when the user presses the left mouse button with the pointer on the client window or any part of the associated mwm decoration. The default value for this resource is explicit.

Determines whether the user is allowed to resize a window to greater than the maximum size. If this resource is True, the user is not allowed to resize a window to greater than the maximum size. The default value for this resource is True.

Determines whether a window icon is displayed on the bottom of the window stack when the window is iconified (minimized). A value of False places the icon in the stacking order at the same place as its associated window. The default value of this resource is True.

iconPlacementMargin (class IconPlacementMargin)

interactivePlacement (class InteractivePlacement)

keyBindings (class KeyBindings)

keyboardFocusPolicy (class **KeyboardFocusPolicy**)

limitResize (class LimitResize)

lowerOnlconify (class **LowerOnlconify**)

maximumMaximumSize (class MaximumMaximumSize)

moveOpaque (class MoveOpaque)

moveThreshold (class MoveThreshold)

multiScreen (class MultiScreen)

passButtons (class PassButtons)

passSelectButton (class PassSelectButton)

positionIsFrame (class PositionIsFrame)

positionOnScreen (class PositionOnScreen)

quitTimeout (class QuitTimeout)

raiseKeyFocus (class RaiseKeyFocus)

resizeBorderWidth (class ResizeBorderWidth)

resizeCursors (class ResizeCursors)

Limits the maximum size of a client window as set by the user or client. The resource value is Width x Height (for example, 1024x1024) where the width and height are in pixels. The default value of this resource is twice the screen width and height.

Controls whether the actual window is moved or a rectangular outline of the window is moved. A default value of False displays a rectangular outline on move operations.

Controls the sensitivity of dragging operations that move windows and icons. The value of this resource is the number of pixels that the locator is moved with a button down before the move operation is initiated. This is used to prevent window and icon movement when you click or double-click and there is unintentional pointer movement with the button down. The default value of this resource is 4 (pixels). Determines whether the **mwm** command manages all the screens on the display. If False, the mwm command manages only a single screen. The default value is False.

Indicates whether button press events are passed to clients after they are used to do a window manager function in the client context. If the resource value is False, the button press is not passed to the client. If the value is True, the button press is passed to the client window. The window manager function is done in either case. The default value for this resource is False.

Indicates whether to pass the select button press events to clients after they are used to do a window manager function in the client context. If the resource value is False, the button press is not passed to the client. If the value is True, the button press is passed to the client window. The window manager function is done in either case. The default value for this resource is True.

Indicates how client window position information (from the WM_NORMAL_HINTS property and from configuration requests) is to be interpreted. If the resource value is True, the information is interpreted as the position of the MWM client window frame. If the value is False, it is interpreted as being the position of the client area of the window. The default value of this resource is True.

Indicates that windows should initially be placed (if possible) so that they are not clipped by the edge of the screen (if the resource value is True). If a window is larger than the size of the screen, at least the upper-left corner of the window is on-screen. If the resource value is False, windows are placed in the requested position even if totally off-screen. The default value of this resource is True.

Specifies the amount of time in milliseconds that the mwm command waits for a client to update the WM_COMMAND property after the mwm command has sent the WM_SAVE_YOURSELF message. This protocol is used only for those clients that have a

WM_SAVE_YOURSELF atom and no WM_DELETE_WINDOW atom in the WM_PROTOCOLS client window property. The default value of this resource is 1000 (milliseconds). See the f.kill function for additional information.

Specifies whether a window raised by means of the f.normalize and raise function also receives the input focus. The default value of this resource is False. This resource is available only when the keyboard input focus policy is set to the explicit value. Specifies the width (in pixels) of a client window frame border with resize handles. The specified border width includes the 3-D shadows. The default value is based on the size and resolution of the screen. Indicates whether the resize cursors are always displayed when the pointer is in the window size border. If True, the cursors are shown; otherwise, the window manager cursor is shown. The default value is True.

screens (class Screens)

showFeedback (class ShowFeedback)

Specifies the resource names to use for the screens managed by the mwm command. If the mwm command is managing a single screen, only the first name in the list is used. If the mwm command is managing multiple screens, the names are assigned to the screens in order, starting with screen 0. For example, screen 0 gets the first name and screen 1 gets the second name. Examples of default screen names are 0 and 1.

Controls when feedback information is displayed. It controls both window position and size feedback during move or resize operations and initial client placement. It also controls window manager message and dialog boxes.

The value for this resource is a list of names of the feedback options to be enabled or disabled; the names must be separated by a space. If an option is preceded by a minus sign, that option is excluded from the list. The sign of the first item in the list determines the initial set of options. If the sign of the first option is - (a minus sign), the mwm command assumes all options are present and starts subtracting from that set. If the sign of the first decoration is + (a plus sign) or is not specified, the mwm command starts with no options and builds up a list from the resource.

The names of the feedback options are as follows:

all Shows all feedback (default value).

behavior

Confirms the behavior switch.

kill Confirms on receipt of the KILL signal.

move Shows position during the move.

none Shows no feedback.

placement

Shows position and size during initial placement.

quit Confirms quitting MWM.

resize Shows size during resize.

restart Confirms MWM restart.

The following command line illustrates the syntax for the showFeedback resource:

Mwm*showFeedback: placement resize behavior restart

This resource specification provides feedback for initial client placement and resize, and it enables the dialog boxes to confirm the restart and set behavior functions. It disables feedback for the move function.

The default value for this resource is the all value.

startupKeyFocus (class StartupKeyFocus)

Determines whether a window gets the keyboard input focus when the window is mapped (that is, initially managed by the window manager). It is recommended that both the autoKeyFocus resource and the startupKeyFocus resource be set to a value of True to work with tear-off menus. The default value is True. This resource is available only when the keyboard input focus policy is set to the explicit value.

transientDecoration (class TransientDecoration)

Controls the amount of decoration that Mwm puts on transient windows. The decoration specification is exactly the same as for the clientDecoration (client-specific) resource. Transient windows are identified by the WM_TRANSIENT_FOR property, which is added by the client to indicate a relatively temporary window. The default value for this resource is the menu title value (that is, transient windows have resize borders and a title bar with a window menu button).

An application can also specify which decorations the window manager should apply to its windows. If it does so, the window manager applies only those decorations indicated by both the application and the transientDecoration resource. Otherwise, the window manager applies only the decorations indicated by the transientDecoration resource.

Indicates which window management functions are applicable (or not applicable) to transient windows. The function specification is exactly the same as for the **clientFunctions** (client-specific) resource. The default value for this resource is -minimize -maximize.

An application can also specify which functions the window manager should apply to its windows. If it does so, the window manager applies only those functions indicated by both the application and the transientFunctions resource. Otherwise, the window manager applies only the functions indicated by the transientFunctions resource.

Determines whether icons are placed in an icon box. If this resource is given a value of True, icons are placed in an icon box. When an icon box is not used, the icons are placed on the root window (default

Indicates whether the window menu is posted and remains posted after a click of the mouse when the pointer is over the Window Menu button. If the value given this resource is True, the menu remains posted. True is the default value for this resource.

Indicates whether a double-click action on the Window Menu button performs an f.kill function. When this resource is given the default value of True, a double-click action on the Window Menu button performs an f.kill function.

transientFunctions (class TransientFunctions)

uselconBox (class UselconBox)

wMenuButtonClick (class WMenuButtonClick)

wMenuButtonClick2 (class WMenuButtonClick2)

Client-Specific Resources

The syntax for specifying client-specific resources is as follows:

Mwm*ClientNameOrClass*ResourceID

For example, Mwm*mterm*windowMenu is used to specify the window menu to be used with mterm clients.

The syntax for specifying client-specific resources for all classes of clients is as follows:

Mwm*ResourceID

Specific client specifications take precedence over the specifications for all clients. For example, Mwm*windowMenu is used to specify the window menu to be used for all classes of clients that do not have a window menu specified.

The syntax for specifying resource values for windows that have an unknown name and class (that is, windows that do not have a WM_CLASS property associated with them) is as follows:

Mwm*defaults*ResourceID

For example, Mwm*defaults*iconImage is used to specify the icon image to be used for windows that have an unknown name and class.

Client-Specific Resource Set

Note: Hyphens in the following table are for readability purposes only. Do not include hyphens within names in programs.

Name	Properties
clientDecoration	Class ClientDecoration
	Value type all
	Default
clientFunctions	Class ClientFunctions
	Value type string
	Default all
focusAutoRaise	Class FocusAutoRaise
	Value type
	True or False
	Default varies
iconImage	Class Iconimage
	Value type
	pathname
	Default (image)
iconImageBackground	Class Background
	Value type
	color
	Default icon background
iconImageBottomShadowColor	Class Foreground
	Value type
	color
	Default icon bottom shadow
iconImageBottomShadowPixmap	Class BottomShadowPixmap
	Value type
	color
	Default icon bottom shadow pixmap
iconlmageForeground	Class Foreground
	Value type color
	Default varies

Name	Properties
iconImageTopShadowColor	Class Background
	Value type color
	Default icon top shadow color
iconImageTopShadoPixmap	Class TopShadowPixmap
	Value type color
	Default icon top shadow pixmap
matteBackground	Class Background
	Value type color
	Default background
matteBottomShadowColor	Class Foreground
	Value type color
	Default bottom shadow color
matteBottomShadowPixmap	Class BottomShadowPixmap
	Value type color
	Default bottom shadow pixmap
matteForeground	Class Foreground
	Value type color
	Default foreground
matteTopShadowColor	Class Background
	Value type color
	Default top shadow color
matteTopShadowPixmap	Class TopShadowPixmap
	Value type color
	Default top shadow pixmap
matteWidth	Class MatteWidth
	Value type pixels
	Default 0

Name	Properties
maximumClientSize	Class MaximumClientSize
	Value type width x height, vertical, horizontal
	Default fill the screen
useClientIcon	Class UseClientIcon
	Value type True or False
	Default F
usePPosition	Class UsePPosition
	Value type
	string
	Default nonzero
windowMenu	Class WindowMenu
	Value type string
	Default DefaultWindowMenu

clientDecoration (class ClientDecoration)

Controls the amount of window frame decoration. The resource is specified as a list of decorations to specify their inclusion in the frame. If a decoration is preceded by - (a minus sign), that decoration is excluded from the frame. The sign of the first item in the list determines the initial amount of decoration. If the sign of the first decoration is a minus sign, the **mwm** command assumes all decorations are present and starts subtracting from that set. If the sign of the first decoration is plus (or not specified), the **mwm** command starts with no decoration and builds up a list from the resource.

An application can also specify which decorations the **mwm** command should apply to its windows. If it does so, the **mwm** command applies only those decorations indicated by both the application and the **clientDecoration** resource. Otherwise, the **mwm** command applies the decorations indicated by the **clientDecoration** resource. Following is a list of window frame decorations:

all Specifies to include all decorations (default value).

border Specifies the window border.

maximize

Specifies the Maximize button (includes title bar).

minimize

Specifies the Minimize button (includes title bar).

none Specifies no decorations.

resizeh

title

Specifies the border resize handles (includes border).

menu Specifies the Window Menu button (includes title

Specifies the title bar (includes border).

Following are examples of window frame decoration commands:

Mwm*XClock.clientDecoration: -resizeh -maximize

This removes the resize handles and Maximize button from XClock windows.

Mwm*XClock.clientDecoration: menu minimize border

This removes the resize handles and Maximize button from XClock windows. Note that either menu or minimize implies title.

clientFunctions (class ClientFunctions)

Indicates which **mwm** functions are applicable (or not applicable) to the client window. The value for the resource is a list of functions. If the first function in the list has - (a minus sign) in front of it, the mwm command starts with all functions and subtracts from that set. If the first function in the list has a + (plus sign) in front of it, the mwm command starts with no functions and builds up a list. Each function in the list must be preceded by the appropriate + (plus) or - (minus) sign and separated from the next function by a space.

An application can also specify which functions the mwm command should apply to its windows. If it does so, the mwm command applies only those functions indicated by both the application and the clientFunctions resource. Otherwise, the **mwm** command applies the functions indicated by the **clientFunctions** resource.

Following is a list of functions available for this resource:

all Specifies to include all functions (default value).

none Specifies no functions.

Specifies f.resize. resize

Specifies **f.move**. move

minimize

Specifies f.minimize.

maximize

Specifies f.maximize.

close Specifies f.kill.

Determines whether clients are raised when they get the keyboard input focus. If the value is False, the stacking of windows on the display is not changed when a window gets the keyboard input focus. The default value is True when the keyboardFocusPolicy is the explicit value and False when the keyboardFocusPolicy is the pointer value.

Specifies an icon image for a client (for example, Mwm*myclock*iconlmage). The resource value is a path name for a bitmap file. The value of the (client-specific) useClientIcon resource is used to determine whether user-supplied icon images are used instead of client-supplied icon images. The default value is to display a built-in window manager icon image.

Specifies the background color of the icon image that is displayed in the image part of an icon. The default value of this resource is the icon background color (that is, specified by Mwm*background or

Mwm*icon*background).

Specifies the bottom shadow color of the icon image that is displayed in the image part of an icon. The default value of this resource is the icon bottom shadow color (that is, specified by Mwm*icon*bottomShadowColor). Specifies the bottom shadow pixmap of the icon image that is displayed in the image part of an icon. The default value of this resource is the icon bottom shadow pixmap (that is, specified by Mwm*icon*bottomShadowPixmap).

focusAutoRaise (class FocusAutoRaise)

iconlmage (class Iconlmage)

iconlmageBackground (class Background)

iconlmageBottomShadowColor (class Foreground)

iconlmageBottomShadowPixmap (class BottomShadowPixmap)

iconlmageForeground (class Foreground)

iconlmageTopShadowColor (class Background)

iconImageTopShadowPixmap (class TopShadowPixmap)

matteBackground (class Background)

matteBottomShadowColor (class Foreground)

matteBottomShadowPixmap (class BottomShadowPixmap)

matteForeground (class Foreground)

matteTopShadowColor (class Background)

matteTopShadowPixmap (class TopShadowPixmap)

matteWidth (class MatteWidth)

maximumClientSize (class MaximumClientSize)

Specifies the foreground color of the icon image that is displayed in the image part of an icon. The default value of this resource varies depending on the icon background. Specifies the top shadow color of the icon image that is displayed in the image part of an icon. The default value of this resource is the icon top shadow color (that is, specified by Mwm*icon*topShadowColor).

Specifies the top shadow pixmap of the icon image that is displayed in the image part of an icon. The default value of this resource is the icon top shadow pixmap (that is, specified by Mwm*icon*topShadowPixmap).

Specifies the background color of the matte when the matteWidth resource is a positive value. The default value of this resource is the client background color (that is, specified by Mwm*background or Mwm*client*background).

Specifies the bottom shadow color of the matte when the matteWidth resource is a positive value. The default value of this resource is the client bottom shadow color (that is, specified by Mwm*bottomShadowColor or Mwm*client*bottomShadowColor).

Specifies the bottom shadow pixmap of the matte when the matteWidth resource is a positive value. The default value of this resource is the client bottom shadow pixmap (that is, specified by Mwm*bottomShadowPixmap or Mwm*client*bottomShadowPixmap).

Specifies the foreground color of the matte when the matteWidth resource is a positive value. The default value of this resource is the client foreground color (that is, specified by Mwm*foreground or Mwm*client*foreground).

Specifies the top shadow color of the matte when the matteWidth resource is a positive value. The default value of this resource is the client top shadow color (that is, specified by Mwm*topShadowColor or Mwm*client*topShadowColor).

Specifies the top shadow pixmap of the matte when the matteWidth resource is a positive value. The default value of this resource is the client top shadow pixmap (that is, specified by Mwm*topShadowPixmap or Mwm*client*topShadowPixmap).

Specifies the width of the optional matte. The default value is 0, which effectively disables the matte. Indicates the client size to be used when an application is maximized. The resource value is specified *WidthxHeight*. The width and height are interpreted in the units that the client uses (for example, this is generally characters for terminal emulators). Alternately, the vertical or horizontal value can be specified to indicate the direction in which the client maximizes. If this resource is not specified, the maximum size from the WM_NORMAL_HINTS property is used if set. Otherwise, the default value is the size where the client window with window management borders fills the screen. When the maximum client size is not determined by the maximumClientSize resource, the maximumMaximumSize resource value is used as a constraint on the maximum size

useClientIcon (class UseClientIcon)

usePPosition (class UsePPosition)

windowMenu (class WindowMenu)

Determines whether a client-supplied icon image takes precedence over a user-supplied icon image. The default value is False, giving the user-supplied icon image higher precedence than the client-supplied icon image. Specifies whether the window manager honors the program-specified position PPosition specified in the WM_NORMAL_HINTS property in the absence of a user-specified position. Setting this resource to On causes the mwm command to always honor the program-specified position. Setting this resource to Off causes the mwm command to always ignore the program-specified position. Setting this resource to the default value of nonzero causes the **mwm** command to honor program-specified positions other than (0,0). Indicates the name of the menu pane that is posted when the window menu is opened (usually by pressing button 1 on the Window Menu button on the client window frame). Menu panes are specified in the mwm resource description file. Window menus can be customized on a client class basis by specifying resources of the form Mwm*ClientNameOrClass*windowMenu (See mwm Resource Description File Syntax for more information.) The default value of this resource is DefaultWindowMenu.

Resource Description File

The **mwm** resource description file is a supplementary resource file that contains resource descriptions that are referred to by entries in the defaults files (.Xdefaults, app-defaults/Mwm). It contains descriptions of resources that are to be used by the mwm command and that cannot be easily encoded in the defaults files (a bitmap file is an analogous type of resource description file). A particular **mwm** resource description file can be selected using the **configFile** resource.

The following types of resources can be described in the **mwm** resource description file:

Window manager functions can be bound (associated) with button events. **buttons** keys Window manager functions can be bound (associated) with key press events.

menus Menu panes can be used for the window menu and other menus posted with key bindings and button

bindings.

mwm Resource Description File Syntax

The **mwm** resource description file is a standard text file that contains items of information separated by blanks, tabs, and new-line characters. Blank lines are ignored. Items or characters can be quoted to avoid special interpretation (for example, the # (comment character) can be quoted to prevent it from being interpreted as the comment character). A quoted item can be contained in " " (double quotation marks). Single characters can be quoted by preceding them with the \ (backslash). All text from an unquoted # (comment character) to the end of the line is regarded as a comment and is not interpreted as part of a resource description. If an! (exclamation mark) is the first character in a line, the line is regarded as a comment. If a line ends in a \ (backslash), the next line is considered a continuation of that line.

Window manager functions can be accessed with button and key bindings and with window manager menus. Functions are indicated as part of the specifications for button and key binding sets and for menu panes. The function specification has the following syntax:

Function = FunctionName [FunctionArguments] FunctionName = Window Manager Function FunctionArguments = {QuotedItem | UnquotedItem} The following functions are supported. If a function is specified that is not one of the supported functions, it is interpreted by the **mwm** command as the **f.nop** function.

f.circle down [Icon | Window]

f.circle_up [Icon | Window]

f.exec or !

f.focus_color

f.focus_key

f.kill

Causes a beep.

Causes the window or icon that is on the top of the window stack to be put on the bottom of the window stack (so that it no longer obscures any other window or icon). This function affects only those windows and icons that obscure other windows and icons or that are obscured by other windows and icons. Secondary windows (that is, transient windows) are restacked with their associated primary window. Secondary windows always stay on top of the associated primary window and there can be no other primary windows between the secondary windows and their primary window. If an Icon function argument is specified, the function applies only to icons. If a Window function argument is specified, the function applies only to windows

Raises the window or icon on the bottom of the window stack (so that it is not obscured by any other windows). This function affects only those windows and icons that obscure other windows and icons or that are obscured by other windows and icons. Secondary windows (that is, transient windows) are restacked with their associated primary window. If an Icon function argument is specified, the function applies only to icons. If a Window function argument is specified, the function applies only to windows.

Causes the command to be run (using the value of the MWMSHELL environment variable if it is set; otherwise, the value of the SHELL environment variable if it is set; otherwise, /usr/bin/sh is used). The ! notation can be used in place of the **f.exec** function name.

Sets the colormap focus to a client window. If this function is done in a root context, the default colormap (set up by the X Window System client for the screen where MWM is running) is installed and there is no specific client window colormap focus. This function is treated as f.nop if colormapFocusPolicy is not set to the explicit value. Sets the keyboard input focus to a client window or icon. This function is treated as **f.nop** if **keyboardFocusPolicy** is not set to the explicit value or the function is run in a root context.

Stops a client. If the WM DELETE WINDOW protocol is set up. the client is sent a client message event indicating that the client window needs to be deleted. If the WM_SAVE_YOURSELF protocol is set up and the WM_DELETE_WINDOW protocol is not set up, the client is sent a client message event indicating that the client needs to prepare to be stopped. If the client does not have the WM DELETE WINDOW or WM_SAVE_YOURSELF protocol set up, this function causes a client's X connection to be stopped (usually resulting in the end of the client).

See the description of the quitTimeout resource.

f.lower [-Client | within | freeFamily] f.maximize f menu f.minimize f.move f.next_cmap f.next_key [Icon | Window | Transient] f.nop f.normalize f.normalize_and_raise f.pack_icons

Lowers a client window to the bottom of the window stack (where it obscures no other window). Secondary windows (that is, transient windows) are restacked with their associated primary window. The Client argument indicates the name or class of a client to lower. If the Client argument is not specified, the context, in which the function was started, indicates the window or icon to lower.

Causes a client window to be displayed with its maximum

Associates a cascading (pull-right) menu with a menu pane entry or a menu with a button or key binding. The menu_name function argument identifies the menu to be

Causes a client window to be iconified (minimized). When a window is minimized and no icon box is used, its icon is placed on the bottom of the window stack (so that it obscures no other windows). If an icon box is used, the client's icon changes to its iconified form inside the icon box. Secondary windows (that is, transient windows) are minimized with their associated primary window. There is only one icon for a primary window and all its secondary windows.

Causes a client window to be interactively moved. Installs the next colormap in the list of colormaps for the window with the colormap focus.

Sets the keyboard input focus to the next window or icon in the set of windows and icons managed by the window manager (the ordering of this set is based on the stacking of windows on the screen). This function is treated as f.nop if keyboardFocusPolicy is not the explicit value. The keyboard input focus is moved only to windows that do not have an associated secondary window that is application-modal. If the Transient argument is specified, transient (secondary) windows are crossed (otherwise, if only the Window argument is specified, traversal is done only to the last focused window in a transient group). If an *Icon* function argument is specified, the function applies only to icons. If a Window function argument is specified, the function applies only to windows.

Does nothing. If a function is specified in a type of resource where it is not supported or is started in a context that does not apply, the function is treated as f.nop.

Causes a client window to be displayed with its normal size. Secondary windows (that is, transient windows) are placed in their normal state along with their associated primary window.

Causes the corresponding client window to be displayed with its normal size and raised to the top of the window stack. Secondary windows (that is, transient windows) are placed in their normal state along with their associated primary window.

Causes icons to be packed into the icon grid. This function is used to relay out icons (based on the layout policy being used) on the root window or in the icon box. f.pass_keys

f.post_wmenu

f.prev_cmap

f.prev key [Icon | Window | Transient]

f.quit_mwm

f.raise [-Client | within | freeFamily]

Enables or disables (toggles) processing of key bindings for window manager functions. When it disables key binding processing, all keys are passed on to the window with the keyboard input focus and no window manager functions are started. If the f.pass_keys function is started with a key binding to disable key-binding processing, the same key binding can be used to enable key-binding processing.

Posts the window menu. If a key is used to post the window menu and the Window Menu button is present, the window menu is automatically placed with its top-left corner at the bottom-left corner of the Window Menu button for the client window. If no Window Menu button is present, the window menu is placed at the top-left corner of the client window.

Installs the previous colormap in the list of colormaps for the window with the colormap focus.

Sets the keyboard input focus to the previous window or icon in the set of windows and icons managed by the window manager (the ordering of this set is based on the stacking of windows on the screen). This function is treated as f.nop if keyboardFocusPolicy is not the explicit value. The keyboard input focus is moved only to windows that do not have an associated secondary window that is application-modal. If the *Transient* argument is specified, transient (secondary) windows are crossed (otherwise, if only window is specified, traversal is done only to the last focused window in a transient group). If an *Icon* function argument is specified, the function applies only to icons. If a Window function argument is specified, the function applies only to windows. Stops the mwm command (but not the X Window System client).

Raises a client window to the top of the window stack (where it is obscured by no other window). Raises the secondary window (transient window or dialog box) within the client family. The arguments to this function are mutually exclusive. The Client argument indicates the name or class of a client to raise. If the Client argument is not specified, the context in which the function was started indicates the window or icon to raise. Specifying within raises the secondary window within the family but does not raise the client family in the global window stack. Specifying freeFamily raises the window to the top of its local family stack and raises the family to the top of the global window stack.

f.raise_lower [within | freeFamily]

f.refresh f.refresh win f.resize f.restart

f.restore

f.restore and raise

f.screen [next | prev | back | ScreenNumber]

f.send_msg MessageNumber

f.separator

Raises a primary window to the top of the window stack if it is partially obscured by another window; otherwise, it lowers the window to the bottom of the window stack. The arguments to this function are mutually exclusive.

Specifying within raises a secondary window within the family (staying above the parent window), if it is partially obscured by another window in the application's family; otherwise, it lowers the window to the bottom of the family stack. It has no effect on the global stacking order.

Specifying freeFamily raises the window to the top of its local family stack, if obscured by another window, and raises the family to the top of the global window stack; otherwise, it lowers the window to the bottom of its local family stack and lowers the family to the bottom of the global window stack.

Causes all windows to be redrawn.

Causes a client window to be redrawn.

Causes a client window to be interactively resized. Causes the **mwm** command to be restarted (effectively stopped and restarted).

Restores the previous state of an icon's associated window. If a maximized window is iconified, the f.restore function restores it to its maximized state. If a normalized window is iconified, the f.restore function restores it to its normalized state.

Restores the previous state of an icon's associated window and raises the window to the top of the window stack. If a maximized window is iconified, the f.restore and raise function restores it to its maximized state and raises it to the top of the window stack. If a normalized window is iconified, the f.restore and raise function restores it to its normalized state and raises it to the top of the window stack.

Causes the pointer to warp to a specific screen number or to the next, previous, or last visited screen. The arguments to this function are mutually exclusive. The following arguments are available:

ScreenNumber

prev

Indicates the screen number to which the pointer is warped. Screens are numbered starting from screen 0.

Warps the pointer to the next managed screen next (skipping over any unmanaged screens).

> Warps the pointer to the previous managed screen (skipping over any unmanaged screens).

back Warps the pointer to the last visited screen. Sends a client message of the _MOTIF_WM_MESSAGES type with the MessageType indicated by the MessageNumber function argument. The client message is sent only if MessageNumber is included in the client's _MOTIF_WM_MESSAGES property. A menu item label is unavailable if the menu item is used to perform the f.send_msg function of a message that is not included in the client's _MOTIF_WM_MESSAGES property. Causes a menu separator to be put in the menu pane at the specified location (the label is ignored).

f.set_behavior

Causes the window manager to restart with the default behavior (if a custom behavior is configured) or revert to the custom behavior. By default this is bound to the Shift+Ctrl+Meta+! key sequence.

The Meta+Shift+Ctrl+! key sequence switches (that is, toggles) between the default and custom behaviors. When the user switches to the default MWM behavior, a number of mwm resources assume their default values and the **mwm** command restarts. When the user switches back to the custom behavior, the resource values that were changed to default values are reset with the custom values and the mwm command restarts.

When an **f.set** behavior function is performed, the following user interaction occurs:

- 1. A system-modal dialog box is displayed prompting the user for confirmation of the f.set_behavior action.
- 2. The user can cancel the action at this point.
- 3. The window manager restarts.
- 4. The window manager applies the new (custom or default) configuration values.
- 5. Window manager components are mapped.

When the default MWM behavior is being set, default resource values are applied and, if specified, client properties that control window manager behavior are applied. This includes the _MOTIF_WM_HINTS and **MOTIF WM MENU** properties. These properties might alter default MWM behavior, but it is done in a way that is consistent for all users.

Inserts a title in the menu pane at the specified location.

f.title

Function Contexts

Each function may be constrained as to which resource types can specify the function (for example, menu pane) and also what context the function can be used in (for example, the function is done to the selected client window). The following are the function contexts:

root No client window or icon is selected as an object for the function.

window A client window is selected as an object for the function. This includes the window's title bar and frame.

Some functions are applied only when the window is in its normalized state (for example, f.maximize) or

its maximized state (for example, f.normalize).

An icon is selected as an object for the function. icon

If a function's context is specified as **iconlwindow** and the function is started in an icon box, the function applies to the icon box, not to the icons inside.

If a function is specified in a type of resource where it is not supported or is started in a context that does not apply, the function is treated as **f.nop**. The following table indicates the resource types and function contexts in which window manager functions apply:

Function	Contexts	Resources
f.beep	root, icon, window	button, key, menu
f.circle_down	root, icon, window	button, key, menu
f.circle_up	root, icon, window	button, key, menu

Function	Contexts	Resources
f.exec	root, icon, window	button, key, menu
f.focus_color	root, icon, window	button, key, menu
f.focus_key	root, icon, window	button, key, menu
f.kill	icon, window	button, key, menu
f.lower	icon, window	button, key, menu
f.maximize	icon, window (normal)	button, key, menu
f.menu	root, icon, window	button, key, menu
f.minimize	window	button, key, menu
f.move	icon, window	button, key, menu
f.next_cmap	root, icon, window	button, key, menu
f.next_key	root, icon, window	button, key, menu
f.nop	root, icon, window	button, key, menu

f.normalize	icon, window (maximized)	button, key, menu
f.normalize_and_raise	icon, window	button, key, menu
f.pack_icons	root, icon, window	button, key, menu
f.pass_keys	root, icon, window	button, key, menu
f.post_wmenu	root, icon, window	button, key
f.prev_cmap	root, icon, window	button, key, menu
f.prev_key	root, icon, window	button, key, menu
f.quit_mwm	root, icon, window	button, key, menu (root only)
f.raise	icon, window	button, key, menu
f.raise_lower	icon, window	button, key, menu
f.refresh	root, icon, window	button, key, menu
f.refresh_win	window	button, key, menu
f.resize	window	button, key, menu
f.restart	root, icon, window	button, key, menu
f.restore	icon, window	button, key, menu
f.restore_and_raise	icon, window	button, key, menu
f.screen	root, icon, window	button, key, menu
f.send_msg	icon, window	button, key, menu
f.separator	root, icon, window	menu
f.set_behavior	root, icon, window	button, key, menu
f.title	root, icon, window	menu

Window Manager Event Specification

Events are indicated as part of the specifications for button and key-binding sets and for menu panes.

Button events have the following syntax:

Button = [ModifierList] < ButtonEventName > ModifierList = Modifier Name {ModifierName} All modifiers specified are interpreted as being exclusive (this means that only the specified modifiers can be present when the button event occurs). Following is a list that indicates the values that can be used for the ModifierName parameter. The Alt key is frequently labeled Extend or Meta. Alt and Meta can be used interchangeably in event specification.

Modifier	Description
Ctrl	Control key
Shift	Shift key
Alt	Alt or Meta key
Meta	Meta or Alt key
Lock	Lock key
Mod1	Modifier1
Mod2	Modifier2
Mod3	Modifier3
Mod4	Modifier4
Mod5	Modifier5

Following is a list that indicates the values that can be used for the ButtonEventName parameter.

Button	Description
Btn1Down	Button 1 press
Btn1Up	Button 1 release
Rtn1Click	Button 1 press and

Button 1 press and release Btn1Click2 Button 1 double click Btn2Down Button 2 press

Btn2Up Button 2 release

Btn2Click Button 2 press and release Btn2Click2 Button 2 double click

Btn3Down Button 3 press Btn3Up Button 3 release

Btn3Click Button 3 press and release Btn3Click2 Button 3 double click

Btn4Down Button 4 press Btn4Up Button 4 release

Btn4Click Button 4 press and release Btn4Click2 Button 4 double click Btn5Down Button 5 press Btn5Up Button 5 release

Btn5Click Button 5 press and release Btn5Click2 Button 5 double click.

Key events that are used by the window manager for menu mnemonics and for binding to window manager functions are single key presses; key releases are ignored. Key events have the following syntax:

```
Key = [ModifierList] <Key> KeyName
ModifierList = ModifierName {ModifierName}
```

All modifiers specified are interpreted as being exclusive (this means that only the specified modifiers can be present when the key event occurs). Modifiers for keys are the same as those that apply to buttons. The KeyName parameter is an X11 keysym name. Key symbol names can be found in the keysymdef.h file (remove the XK_ prefix).

The key symbol names will be resolved to a single specific key code by the Window Manager during startup and will not change unless the Window Manager is restarted.

Button Bindings

The **buttonBindings** resource value is the name of a set of button bindings that are used to configure window manager behavior. A window manager function can be used when a button press occurs with the pointer over a framed client window, an icon, or the root window. The context for indicating where the button press applies is also the context for starting the window manager function when the button press is done (significant for functions that are context-sensitive).

Following is the button binding syntax:

```
Buttons BindingsSetName
Button Context Function
Button Context Function
Button Context Function
       }
```

Following is the syntax for the context specification:

```
Context = Object[|Context]
Object = root | icon | window | title | frame | border | app
```

The Context specification indicates where the pointer must be for the button binding to be effective. For example, a context of window indicates that the pointer must be over a client window or window management frame for the button binding to be effective. The frame context is for the window management frame around a client window (including the border and title bar), the border context is for the border part of the window management frame (not including the title bar), the title context is for the title area of the window management frame, and the app context is for the application window (not including the window management frame).

If an **f.nop** function is specified for a button binding, the button binding is not done.

Key Bindings

The **keyBindings** resource value is the name of a set of key bindings that are used to configure window manager behavior. A window manager function can be done when a particular key is pressed. The context in which the key binding applies is indicated in the key binding specification. The valid contexts are the same as those that apply to button bindings.

Following is the key binding syntax:

```
Keys BindingsSetName
Kev Context Function
Key Context Function
Key Context Function
```

If an **f.nop** function is specified for a key binding, the key binding is not done. If an **f.post_wmenu** or f.menu function is bound to a key, the mwm command automatically uses the same key for removing the menu from the screen after it is open.

The Context specification syntax is the same as for button bindings. For key bindings, the frame, title, border, and app contexts are equivalent to the window context. The context for a key event is the window or icon that has the keyboard input focus (root if no window or icon has the keyboard input focus).

Menu Panes

Menus can be opened using the f.post_wmenu and f.menu window manager functions. The context for window manager functions that are done from a menu is root, icon, or window, depending on how the menu is opened. In the case of the window menu or menus opened with a key binding, the location of the keyboard input focus indicates the context. For menus opened using a button binding, the context of the button binding is the context of the menu.

Following is the menu pane specification syntax:

```
Menu MenuName
Label [Mnemonic] [Accelerator] Function
Label [Mnemonic] [Accelerator] Function
Label [Mnemonic] [Accelerator] Function
```

Each line in the *Menu* specification identifies the label for a menu item and the function to be completed if the menu item is selected. Optionally, a menu button mnemonic and a menu button keyboard accelerator can be specified. Mnemonics are functional only when the menu is posted and keyboard traversal applies.

The label can be a string or a bitmap file. The Label specification has the following syntax:

```
Label = Text | BitmapFile
BitmapFile = @FileName
Text = QuotedItem | UnquotedItem
```

The string encoding for labels must be compatible with the menu font that is used. Labels are not available for menu items that use the f.nop function, an invalid function, or a function that does not apply in the current context.

A *Mnemonic* specification has the following syntax:

```
Mnemonic = Character
```

The first matching Character in the label is underlined. If there is no matching Character in the label, no mnemonic is registered with the window manager for that label. Although the Character must exactly match a character in the label, the mnemonic does not perform if any modifier (such as the Shift key) is pressed with the character key.

The Accelerator specification is a key event specification with the same syntax that is used for key bindings to window manager functions.

Environment

The **mwm** command does the following:

- Uses the HOME environment variable to specify the user's home directory.
- Uses the LANG environment variable to specify the user's choice of language for the mwm message catalog and the **mwm** resource description file.
- Uses the XFILESEARCHPATH, XUSERFILESEARCHPATH, XAPPLRESDIR, XENVIRONMENT, LANG, and HOME environment variables to determine search paths for resource defaults files. The mwm command can also use the XBMLANGPATH environment variable to search for bitmap files.
- Reads the \$HOME/.motifbind file, if it exists, to install a virtual key bindings property on the root window.
- Uses the MWMSHELL environment variable (or SHELL if MWMSHELL is not set) to specify the shell to use when running commands through the **f.exec** function.

Exit Status

This command returns the following exit values:

- 0 Indicates successful completion.
- >1 Indicates an error occurred.

Files

/usr/lib/X11/\$LANG/system.mwmrc

/usr/lib/X11/system.mwmrc

/usr/lib/X11/app-defaults/Mwm

\$HOME/Mwm

\$HOME/.Xdefaults

\$HOME/\$LANG/.mwmrc

\$HOME/.mwmrc

\$HOME/.motifbind

Related Information

The X command in AIX 5L Version 5.3 Commands Reference.

Appendix. Notices

This information was developed for products and services offered in the U.S.A.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing IBM Corporation North Castle Drive Armonk, NY 10504-1785 U.S.A.

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law: INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM Corporation
Dept. LRAS/Bldg. 003
11400 Burnet Road
Austin, TX 78758-3498
U.S.A.

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

© Copyright IBM Corp. 1997, 2009

IBM World Trade Asia Corporation Licensina 2-31 Roppongi 3-chome, Minato-ku Tokyo 106, Japan

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrates programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. You may copy, modify, and distribute these sample programs in any form without payment to IBM for the purposes of developing, using, marketing, or distributing application programs conforming to IBM's application programming interfaces.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurement may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Trademarks

IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at Copyright and trademark information at www.ibm.com/legal/copytrade.shtml

UNIX is a registered trademark of The Open Group in the United States and other countries.

Linux is a trademark of Linus Torvalds in the United States, other countries, or both.

Java and all Java-based trademarks and logos are registered trademarks of Sun Microsystems, Inc. in the United States, other countries, or both.

PostScript

Other company, product, or service names may be the trademarks or service marks of others.

Index

Special characters	attributes (continued)
/etc/filesystems file	displaying possible values of
listing entries	using Isattr command 318
using lsfs command 361	of exported symbols
/etc/inittab file	in ld command 193
listing records	
using Isitab command 366	D
making records	В
using mkitab command 593	behavior
/etc/rc.nfs	general
uncomments entry in	using mwm command 769
using mkclient command 558	behavior of window
/etc/vfs file	managing
listing entries	using mwm command 758
using lsvfs command 454	Behavior resource set
doing ione command to t	using mwm command 769
	bibliography
A	building inverted index for 39
account, user	finding references in
customizing	using lookbib command 242
using mkuser.sys command 697	binder
accounting system	using ld command 179
displaying information about last commands	binding
run 167	button
displaying previous logins and logouts 165	using mwm command 796
performing periodic accounting	key
using monacct command 712	using mwm command 797
updating last log in records 168	boot image
acct/* commands	creating
lastlogin 168	using mkboot command 538
monacct 712	boot record
adapters and devices	creating
displaying	using mkboot command 538
using Ismcode command 384	button
add, command in lb_admin 170	binding
address maps	using mwm command 797
in ld command 194	
AlXwindows Window Manager	C
running	•
using mwm command 758	C programming language
window management	checking source code for problems 211
using mwm command 758	reformatting programs 36
answering client requests	CacheFS directory
for file system mounts	mounting a
using mountd daemon 732	using mkcfsmnt command 548
appearance	CD-ROM
general	reporting statistics 106
using mwm command 769	clean, command in lb_admin 170
appearance of window	Client-Specific resource set
managing	using mwm command 783
using mwm command 758	code page
Appearance resource set	converting one page encoding set to another 7
using mwm command 769	command
attributes	mwm 758
displaying characteristics of	commands
using Isattr command 317	event response resource manager (ERRM) logevent 230
	IUGEVEIIL 200

© Copyright IBM Corp. 1997, 2009

commands (continued)	commands, mtrace 748
ikedb 24	component
installp 56	appearance resources
invscoutd 84	using mwm command 763
join 131	Component Appearance resource set
kdb 135	using mwm command 764
keycomp 139	computer languages
keyenvoy 142	C
ld 174	lexical analyzer 203
logevent 230	configuring system
Iphistory 279	to run NFS
lppchk 282	using mknfs command 617
lpr 289	connections
ls 305	displaying for a device
Isactdef 310	using Isconn command 346
Isattr 317	console device
Isaudrec 322	writing name to standard output
Iscomg 334	using Iscons command 348
Iscondition 337	CPU
Iscondresp 342	statistics 106
Iscons 348	creating
Islpcmd 372	boot image, boot record, and service record
Islpp 376	using mkboot command 538
Islv 380	error message file
Ismcode 384	using mkstr command 684
Isresponse 411	file system
Isrpdomain 417	using mkfs command 585
Isrpnode 420	logical volume
Isrsrc 424	using mklv command 605
Isrsrcdef 430	new user account
Issensor 440	using mkuser command 694
lsvsd 468	volume group
mail 482	using mkvg command 698
Mail 482	customizing
mailq 494	new user account
mailx 482	
make 497	using mkuser.sys command 697
mkboot 538	
mkcfsmnt 548	D
mkcimreg 552	
•	daemon
mkclient 558	launching Inventory Scout server
mkcomg 560 mkcondition 563	using invscoutd command 84
mkcondresp 569	daemons
mkfs 585	llbd 219
mkitab 593	lockd 227
	monitord 714
mklpemd 601 mklv 605	mountd 732
mknfs 617	mrouted 740
	datagram, multicast
mknfsmnt 621	forwarding a
mkprtsv 641	using mrouted daemaon 740
mkresponse 651	default window menu
mkrole 656	using mwm command
mkrpdomain 658	using mwm command 759
mkrsrc 663	delete, command in lb_admin 170
mksensor 675	description file
mkssys 681	creating
mkstr 684	using makedev command 507
mkuser 694	using mwm command 789
mkuser.sys 697	
mkvg 698	

device	environment variables
adding to the system	in ld command 195
using mkdev command 572	ERRM
Device Configuration Database 394	event information
listing acceptable devices from	logging 230
using Isparent command 394	ERRM commands
device stanza name	logevent 230
displaying the	ERRM scripts
using Isquedev command 407	logevent 230
devices	error message file
displaying characteristics of	creation
using Isdev command 352	using mkstr command 684
devices and adapters	error messages
displaying	issuing by optional programs 80
using Ismcode command 384	event information
diagnostic messages	logging 230
issuing by optional programs 81	event response resource manager (ERRM)
directories	commands
creating 575	logevent 230
creating a hierarchy 576	event information
displaying contents	logging 230
using Is command 305	scripts
moving 753, 755	logevent 230
renaming 755	event specification
directory	using mwm command 795
creating a lost and found	
using mklost+found command 601	_
mounting	F
using mount command 722	fields, data
using infocntr command 46	joining from two files
disks	using join command 131
reporting statistics 106	file
displaying	creating a special
directory contents	using mknod command 625
using Is command 305	finding lines in a sorted
displaying system images	using look command 241
for examining a dump using kdb command 135	resource description
	using mwm command 789
displays files	writing inode information 125
one screen at a time 716	file system
listing currently available on the system	constructing a prototype
using ledisp command 359	using mkproto command 633
document	making
typesetting	using mkfs command 585
using mmt command 707	making available for use using mount command 722
dump, examining	•
displaying system images	file system mounts
using kdb command 135	answering client requests using mountd daemon 732
and a second	files
	archive
E	using ld command 175
encryption	creating links 220
generating an encryption key	displaying
using makekey command 508	one screen at a time 716
enqueuing	2 2020 4. 4 41110 7 10
print jobs	import and export
provide the second seco	import and export using ld command 175
using lpr command 289	using ld command 175
using lpr command 289 environment variable	using ld command 175 joining the data fields of two
	using ld command 175

files (continued)	
moving 753	- I/O
filesets	reporting statistics 106
installing, associated with keywords or fixes 67	IBM 3812 Model 2 Pageprinter
fixes	postprocessing troff command output for 1
installing filesets associated with 67	IBM 3816 Pageprinter
flags ignored and unsupported	postprocessing troff command output for 2
using Id command 177	ibm3812 command 1
folder	ibm3816 command 2
incorporating new mail into 34	ibm5587G command 4
folders	IBM5587G printer
printing full path names of	postprocessing troff command output for 4
using mhpath command 524	ibm558H-T Command 3
font code	ibstat command 5
adding to the system	icon
using mkfont command 583	box menu
font files	using mwm command 761
creating fonts.dir file	putting in icon box using mwm command 761
using mkfontdir command 584	window menu
font set	using mwm command 760
changing	Icon Component resource set
using managefonts command 514	using mwm command 767
updating	iconifying window
using managefonts command 514	using mwm command 760
fonts	iconv command 7
listing the fonts available for use using Isfont command 360	id command 9
Frame Component resource set	idinstal 46
using mwm command 767	idnls 222
30g	idprocess 113
	ifconfig command 11
G	IKE database
games	retrieves, updates, deletes, imports, and exports
number-guessing game 715	information
garbage collection	using ikedb command 24 ikedb command 24
using ld command 177	IMAP commands
global location broker	imapd 28
administrative tools for 169	imapds 29
groups	imapd daemon 28
creating new groups	imapds daemon 29
using mkgroup command 588	impfilt command 30
displaying attributes of	import and export file format
using Isgroup command 363	-bl: and -bE: Flags
	using ld command 191
Н	importing filter rules
	from export files 30
help	importvg command 31
using files, editors, and macros 199	imptun command
hlpid 9 hlpindent 36	adding exported tunnel definitions and filter rules 33
hlpiostat 106	inc command 34 indent command 36
hlpipcs 114	index
hlplearn 199	
hlpleave 201	building inverted for bibliography 40 indxbib command 39
hlpline 209	inetd daemon 41
hlplint 211	infocmp command
hlpln 220	managing terminfo descriptions 43
hlplorder 242	infocntr command 46
hlpmkvgdata 701	inode numbers
	information about 125

input extension records listing	ioo command 90 iostat command 106
using listX11input command 218	ip security export files
input focus	import conversion 119
keyboard	ip security packets list 119
using mwm command 761	ip security tracing buffer 120
input method keymap file	ipcrm command 113
compiling a keyboard mapping file into an	ipcs command 114
using keycomp command 139	ipreport command 118
install applications	ipsec_convert command 119
Installation Assistant 50	ipsecstat command 119
install command (BSD) 52	ipsectrobuf command 120
install precedure	iptrace daemon 120
install procedure	Isallqdev command 315 isC2host command 123
saving files changed during 77	isCChost command 124
install_all_updates command 49 install assist command 50	Isconn command 346
install mh command 52	Isdev command 352
_	
installable software product	Isparent command
verify files	listing acceptable connection types from
using lppchk command 282 Installation Assistant	using Isparent command 394 istat command 125
starting	istat command 125
9	
using the install_assist command 50 installing	J
programs in compatible package	
using installp command 56	j2edlimit command 126
installing a command 46	job control 129
installios command 54	jobs command 129
installp command 56	join command 131
installp format	joining data fields
creating software packages 595	from two files
instfix command 67	using join command 131
intermediary between user processes	joinvg command 134
keyserv daemon	
using keyenvoy command 142	K
interprocess communication	
removing identifiers 113	kdb command 135
reporting status 114	key
inucp command 69	binding
inudocm command 70	using mwm command 797
inurecy command	keyadd command 138
description of 73	keyboard mapping file
performing archive operations for 75	into an input method keymap file, compiling
performing restore operations for 75	using keycomp command 139
inurest command 75	keyboard maps
inurid command	listing
removing installation information 76	using lskbd command 367
inusave command	keycomp command 139
description of 77	keydelete command 141
performing archive operations for 75	keyenvoy command 142
performing restore operations for 75	keylist command 142
recovering files saved by 73	keylogin command 144
inutoc command 80	keypasswd command 146
inuumsg command 80	keyserv daemon 147
Inventory Scout server daemon	intermediary between user processes
launching	using keyenvoy command 142
using invscoutd command 84	keywords
inverted index	installing filesets associated with 67 kill command 148
building for bibliography 40	killall command 150
invscoutd command 84	kmodetrl command 154

Korn shell	libraries
invoking 158	checking for incompatibilities 211
krlogind daemon	using ld command 176
server function	line command 209
providing 155	line printer
krshd daemon	generating a ripple pattern for a
server function	using lptest command 303
providing 157	sending requests to
ksh command 158	using Ip command 243
ksh93 command 161	line printer spooling queue
KS1195 COMMINANCE TO I	
	removing jobs from
L	using lprm command 294
L	link command 210
last command 165	link subroutine 210
lastcomm command 167	linking mode
lastlogin command 168	using ld command 175
launching	links
Inventory Scout server daemon	hard 220
using invscoutd command 84	symbolic 220
lb_admin	lint command 211
add command 170	listdgrp command 215
clean command 170	listing
command description of 169	software products
•	using Islpp command 376
delete command 170	listvgbackup command 216
help command 170	
lookup command 170	listX11input command 218
quit command 170	llbd (local location broker daemon)
register command 170	description of 219
set_broker command 171	In command 220
set_timeout command 171	locale command
unregister command 171	writes information about locales 222
use_broker command 171	localedef command
lb_find command 172	Processes locale and character map files 224
ld command 174	location broker 171
address maps 194	administrative tools for 169
archive files 175	lookup of 170
attributes of exported symbols 193	registering, via lb_admin 170
binder 179	lock command 226
environment variables 195	lock requests
examples 195	processing
files 196	using lockd daemon 227
	lockd daemon 227
garbage collection 177	locktrace command
ignored and unsupported flags 177	controls kernel lock tracing 229
import and export file format	logevent command 230
-bl: and -bE: Flags 191	logevent command 230
import and export files 175	·
libraries 176	logform command 231
linking mode 175	logger command 233
options (-bOptions) 180	logical volume
processing 176	adding mirrors to
run-time linking 191	using mklvcopy command 611
symbols 176	creating
ldd command 196	using mklv command 605
Idedit 197	displaying information about
learn command 199	using Islv command 380
leave command 201	mirroring
lex command	using mirrorvg command 528
definitions 204	login command 234
rules 205	login name
specification file 204	displaying the current process
lexical analyzer 203	using logname command 239
igalogi ahanyedi 200	coming together to the community to the contract of the contra

logins command 237 logname command 239 logoffs displaying all previous 165 logout command 240 look command 241 lookbib command 242 lookup, command in lb_admin 170 lorder command 242 lp command 243 lpar_netboot command 259 lparstat 261 lpd command 268 lphistory command 279 lppchk command 282 lppmgr command 284 lpq command 286 lpr command 286 lpr command 294 lpstat command 297 lptest command 303 ls command 305 ls-secldapcIntd 309 lsactdef command 314 lsarm command 316 lsattr command 317	Isnamsv command 388 Isnfsexp command 389 Isnfsmnt command 390 Isnim command 391 Isnlspath command 394 Ispath command 396 Isprtsv command 400 Isps command 401 Ispv command 403 Isque command 406 Isquedev command 407 Isquedev command displaying bus resources 408 Isresponse command 411 Isrole command 415 Isrpdomain command 417 Isrpnode command 420 Isrset command 423 Isrsrc command 424 Isrsrcdef command 430 Issavevg command 436 Issec Iisting attributes of security stanza files 438 Issensor command 440	
Isaudrec command 322	Issrc command 447	
Isauthent command	lsts command 449	
authentication methods 327	Istun command	
lsC2admin command 327	listing tunnel definitions 451	
IsCCadmin command 328	Isuser command 452	
lscfg command 328	Isvfs command 454	
Iscifscred command 331	Isvg command 455	
Iscifsmnt command 332	Isvgfs command 458	
Isclass command 333	Isvirprt command 459	
Iscomg command 334	Isvmode command 462	
Iscondition command 337	displaying current video mode 462	
Iscondresp command 342	Isvpd command 463	
Iscons command 348	Isvsd command 468	
Iscore 349	IswImconf command 470	
Iscosi command 350 Ivmo command 473		
Isdisp command 359	lvmstat 475	
Isfilt command		
listing filter rules 360 Isfont command 360	M	
Isfs command 361		
	m4 command	
Isgroup command 363 Isiscsi command 365	preprocessing files 477	
Isitab command 366	mach command 480 machstat command 480	
lskbd command 367	macref command	
Isldap command 368		
Islicense command	producing cross-reference listing of 481 macro file 481	
fixed and floating licenses	mail	
listing number and status of 371	incorporating into a folder 34	
Islpcmd command 372	receiving	
Islpp command 376	using mail command 482	
Islv command 380	using Mail command 482	
Ismaster command 383	sending 523	
Ismcode command 384	using mail command 482	
Ismksysb command 386	using Mail command 482	

mail command 482	MH
Mail command 482	install mh command 52
Mail commands	MH shell
mailq 494	creating
mailstats 496	using msh command 745
mail queue	mhl command 521
printing contents of	mhmail command 523
using mailq command 494	mhpath command 524
mail queue messages	microcode and firmware levels of system
printing list of	displaying
using mailq command 494	using Ismcode command 384
mail traffic statistics	migratelp 526
displaying 496	migratepy command 527
mailbox directories, setting up 52	mirrorvg command 528
mailq command 494	mirscan command 531
mailstats command 496	mkboot command 538
mailx command 482	mkC2admin command 540
maintaining groups of programs	mkcatdefs command 541
using make command 497	mkCCadmin command 542
make command 497	mkcd command 543
makedbm command 504	mkcfsmnt command 548
makedepend command 505	mkcifscred command 549
makedev command 507	mkcifsmnt command 550
man command 510	mkcimreg command 552
	mkclass command 555
man pages displaying information online 510	mkclient command 558
managefonts command 514	mkcomg command 560
mant command 515	mkcondition command 563
manual	mkcondresp command 569
	mkcosi command 571
typesetting pages of using mant command 515	mkdev command 572
mark command 517	mkdir command 575
memorandum macro 705	mkdirhier command 576
menu pane	mkdvd command 577
window manager	mkfifo command
using mwm command 797	making FIFO special files 581
mesg command 519	mkfilt command
message facility commands	activating or deactivating filter rules 582
mkcatdefs 541	mkfont command 583
message queues	mkfontdir command 584
removing identifiers 113	mkfs command 585
message sequences	mkgroup command
creating	description of 588
using mark command 517	mkhosts command 591
displaying	mkinstallp command 595
using mark command 517	mkiscsi command 592
modifying	mkitab command 593
using mark command 517	mkkeyserv command 596
message source file	mklost+found command 601
preprocessing 541	mklpcmd command 601
messages	mkly command 605
checking for	mklycopy command 611
using msgchk command 744	mkmaster command 613
permitting	mknamsv command 615
using mesg command 519	mknetid command 616
printing full path names of	mknfs command 617
using mhpath command 524	mknfsexp command 618
producing formatted lists of	mknfsmnt command 621
using mhl command 521	mknfsproxy command 624
refusing	mknod command 625
using mesg command 519	mkpasswd command 628
acing moog command off	mpacona commana ozo

mkpath command 629	multicast path
mkprojldap command 631	from a source to a receiver, printing a
mkproto command 633	using mtrace command 748
mkprtldap command 637	MultiPath I/O
mkprtsv command 641	Ispath command 396
mkps command 644	mkpath command 629
mkque command 646	mvt command 757
mkquedev command 648	MWM 758
mkramdisk command 649	mwm command 758
	mwm command 750
mkresponse command 651	
mkrole command 656	A.I.
mkrpdomain command 658	N
mkrset 662	NCS daemons
mkrsrc command 663	llbd 219
mksecpki command 673	
mksensor command 675	Network Install Manager 391
	new roles
mkslave command 680	creating
mkssys command 681	using mkrole command 656
mkstr command 684	NFS
mksysb command 685	configuring system to run
mkszfile command 689	using mknfs command 617
mktcpip command 690	3
mkts command 692	NFS commands
	mknfs 617
mkuser command 694	mknfsexp 618
mkuser.sys command 697	mknfsmnt 621
mkvg command 698	NFS daemons
mkvgdata command 701	lockd 227
mkvirprt command 702	mountd 732
mm command	
	NFS server
printing document formatted with	mounting a directory from
using mm command 705	using mknfsmnt command 621
mmt command 707	NIM commands
mmtu command 709	Isnim 391
mobip6ctrl commnad 709	NIS commands
mobip6reqd daemon 711	keyenvoy 142
mode, linking	
using ld command 175	keylogin 144
•	Ismaster 383
modify XCOFF header 197	Isnfsexp 389
monacct command 712	Isnfsmnt 390
monitord daemon 714	makedbm 504
mosy command 720	mkclient 558
mount command 722	mkkeyserv 596
mountd daemon 732	,
in the second se	
	mkslave 680
automatic	NIS daemons
using mount command 723	keyserv 147
CacheFS directory	NLSPATH,
using mkcfsmnt command 548	secure system configuration variable,
mounting a directory from	showing the value of 394
NFS server	•
using mknfsmnt command 621	notify object class (SRC)
	adding a notify method definition 627
mpcfg command 733	
mpstat 737	
mrouted daemon 740	0
msgchk command 744	object files
msh command 745	
mtrace command 748	linking
multibos command 750	using ld command 174
	reading one or more 242
multicast datagram	objects
forwarding a	shared
using mrouted daemaon 740	using ld command 175
	3 - 3

options (-bOptions)	program products
in ld command 180	listing optional
	using Islpp command 376
n	programs
P	creating make file dependencies 505
packet tracing	installing compatible
ipreport command 118	using installp command 56
iptrace daemon 120	providing a C preprocessor interface to the make
paging space	command 26
adding an additional	programs, groups of
using mkps command 644	maintaining
displaying the characteristics of	using make command 497
using lsps command 401	regenerating
password	using make command 497
reserving a terminal	updating
using lock command 226	using make command 497
performing simply copy operations 69	
physical volume	Q
moving partitions from one volume to another volume	
using migratepv command 527	queue
plotter queue	displaying the stanza name for the
listing device names with a queue	using Isquedev command 407
using Isallqdev command 315	displaying the stanza name of
policy	using Isque command 406
keyboard input	queues
using mwm command 761	listing the names of all configured
port	using Isaliq command 314
stopping all processes on a	quit, command in lb_admin 170
using logout command 240	
port 515	R
monitoring for print requests using lpd command 268	
print server	RAM disk 649
providing on a network	read operations
using lpd command 268	copying from standard input 209
print services	receiving mail
configuring TCP/IP-based	using mail command 482
configuring 641	records, makes
printer	in /etc/inittab file
enqueuing	using mkitab command 593
using lpr command 289	regenerating groups of programs using make command 497
line	register, command in lb_admin 170
sending requests to a 243	resource
printer queue	client-specific
adding to the system	using mwm command 782
using mkque command 646	resource description file
using mkquedev command 648	using mwm command 789
listing device names with a queue	resource set
using Isallqdev command 315	Client-Specific 783
printing a multicast path	Component Appearance 764
from a source to a receiver	Frame and Icon Component 767
using mtrace command 748	General Appearance and Behavior 769
process	roles
stopping 148	creating new
process groups 129	using mkrole command 656
processes	run-time linking
canceling all 150	
· · · · · · · · · · · · · · · · · · ·	using id command 191
stopping all port	using ld command 191

S	subsystem
screens	getting status
	using Issrc command 447
displaying text one screen at a time 716	subsystems
scripts	adding a definition to SRC object class
event response resource manager (ERRM)	mkssys command examples 683
logevent 230	using mkssys command 681
logevent 230	adding a notification method 627
sending mail	mknotify command examples 627
using mail command 482	system
service record	adding a device to
creating	using mkdev command 572
making mkboot command 538	system images, displaying
session	for examining a dump
initiating a user	using kdb command 135
using login command 234	_
session management	system log
stopping client	making entries in
using mwm command 758	using the logger command 233
set_broker, command in lb_admin 170	system resource controller 627, 679, 681
set_timeout, command in lb_admin 171	
shared objects	T
using Id command 175	I
shells	tape device
Korn 158	giving subcommands
standard 158	mt command 746
	TCP/IP
slide	hosts
typesetting	generating table file 591
using mvt command 757	setting required values 690
smit	internet packets 120
turning on/off maintenance of I/O history 106	name service
spool queue	displaying information 388
examining	name services
using lpq command 286	configuring 615
spooling queue	network interface
removing jobs from the line printer 294	
SRC	
adding a definition to subsystem object class	network options
mkssys command examples 683	displaying, adding, and deleting 709
using mkssys command 681	packet trace report
adding a subserver object 679	generating 118
mkserver command example 680	print services
adding a subsystem notification method 627	configuring 641
mknotify command examples 627	displaying information about 400
SRC configuration commands	service management 41
mknotify 627	TCP/IP commands
mkserver 679	ifconfig 11
mkssys 681	ipreport 118
standard input	Isnamsv 388
reading 209	Isprtsv 400
standard output	mkhosts 591
writing 209	mknamsv 615
stanza name, device	mkprtsv 641
	mktcpip 690
displaying the	mmtu 709
using Isquedev command 407	TCP/IP daemons
storing public and private keys 147	inetd 41
subserver	iptrace 120
getting status	TCP/IP smit commands
using Issrc command 447	Isnamsv 388
subservers	Isprtsv 400
adding a definition to SRC object class 679	mknamsv 615
mkserver command example 680	miniamov 010

TCD/ID are it as remainder (continued)	values a suscess
TCP/IP smit commands (continued) mkprtsv 641	volume group creating
mktcpip 690	using mkvg command 698
terminal	displaying information about
reserving 226	using Isvg command 455
time management	displaying information about a physical volume
creating reminders 201	using Ispv command 403
timeout setting in lb_admin 171	importing new definition 31
TTY	
reporting statistics 106	W
typesetting document	
using mmt command 707	window
	default components 759
U	default menu
U	using mwm command 759
unregister, command in lb_admin 171	iconifying
updating	using mwm command 760
instructions	menu pane
getting copies of 70	using mwm command 798
procedure	window manager
saving files changed during 77	event specification
updating groups of programs	using mwm command 795
using make command 497	window stacking 762
use_broker	Workload Manager (WLM)
command in lb_admin 171	listing configurations 470
user	IswImconf command 470
initiating a session for a	
using login command 234	V
user account	X
creating	x defaults 763
using mkuser command 694	X Window System
customizing	window management
using mkuser.sys command 697	using mwm command 758
user database	XCOFF
creating a version for searches	modify 197
using mkpasswd command 628	•
users	
displaying	Υ
system ID 9	ypbind daemon
displaying attributes	starting
using Isuser command 452	using mkclient command 558
displaying role attributes	doning minority dominants.
using Isrole command 415	
V	
verify files	
installable software product	
instandore software product	

view graph typesetting

virtual printer

making

virtual RAM disk making 649

using lppchk command 282

using mvt command 757

displaying the attribute values of using Isvirprt command 459

using mkvirprt 702

Readers' Comments — We'd Like to Hear from You

AIX 5L Version 5.3 Commands Reference, Volume 3, i - m

Publication No. SC23-4890-06

We appreciate your comments about this publication. Please comment on specific errors or omissions, accuracy, organization, subject matter, or completeness of this book. The comments you send should pertain to only the information in this manual or product and the way in which the information is presented.

For technical questions and information about products and prices, please contact your IBM branch office, your IBM business partner, or your authorized remarketer.

When you send comments to IBM, you grant IBM a nonexclusive right to use or distribute your comments in any way it believes appropriate without incurring any obligation to you. IBM or any other organizations will only use the personal information that you supply to contact you about the issues that you state on this form.

Thank you for your support.

Submit your comments using one of these channels:

- · Send your comments to the address on the reverse side of this form.
- Send your comments via e-mail to: pserinfo@us.ibm.com

If you would like a response from IBM, please fill in the following information:

Name	Address		
Company or Organization			
Phone No	F-mail address		

Readers' Comments — We'd Like to Hear from You SC23-4890-06



Cut or Fold Along Line

Fold and Tape

Please do not staple

Fold and Tape



Haalladalaaladalaalaalladallaallaallaala

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY MAIL

FIRST-CLASS MAIL PERMIT NO. 40 ARMONK, NEW YORK

POSTAGE WILL BE PAID BY ADDRESSEE

IBM Corporation Information Development Department 04XA-905-6B013 11501 Burnet Road Austin, TX 78758-3400



Fold and Tape

Please do not staple

Fold and Tape

IBM.

Printed in U.S.A.

SC23-4890-06

