

---

# OpenVMS RTL String Manipulation (STR\$) Manual

**December 1995**

This manual documents the string manipulation routines contained in the STR\$ facility of the OpenVMS Run-Time Library.

**Revision/Update Information:** This manual supersedes the *OpenVMS RTL String Manipulation (STR\$) Manual*,  
OpenVMS AXP Version 6.1 and  
OpenVMS VAX Version 6.1.

**Software Version:** OpenVMS Alpha Version 7.0  
OpenVMS VAX Version 7.0

**Digital Equipment Corporation  
Maynard, Massachusetts**

---

**December 1995**

Digital Equipment Corporation makes no representations that the use of its products in the manner described in this publication will not infringe on existing or future patent rights, nor do the descriptions contained in this publication imply the granting of licenses to make, use, or sell equipment or software in accordance with the description.

Possession, use, or copying of the software described in this publication is authorized only pursuant to a valid written license from Digital or an authorized sublicensor.

Digital conducts its business in a manner that conserves the environment and protects the safety and health of its employees, customers, and the community.

© Digital Equipment Corporation 1995. All rights reserved.

The following are trademarks of Digital Equipment Corporation: Alpha, Bookreader, CDA, DDIF, DEC, DECdtm, DECnet, DECUS, DECwindows, DECwriter, DEQNA, Digital, GIGI, HSC, LiveLink, LN03, MASSBUS, MicroVAX, OpenVMS, PrintServer 40, Q-bus, ReGIS, ULTRIX, UNIBUS, VAX, VAXcluster, VAX RMS, VAXserver, VAXstation, OpenVMS, VT, XUI, and the DIGITAL logo.

The following is a third-party trademark:

PostScript is a registered trademark of Adobe Systems Incorporated.

All other trademarks and registered trademarks are the property of their respective holders.

ZK5936

This document is available on CD-ROM.

---

# Contents

<b>Preface</b> .....	v
<b>1 Overview of the STR\$ Facility</b>	
1.1 Run-Time Library STR\$ Routines .....	1-1
1.1.1 The STR\$ Routines .....	1-2
1.1.2 64-bit Addressing Support .....	1-3
<b>2 Introduction to String Manipulation (STR\$) Routines</b>	
2.1 String Semantics in the Run-Time Library .....	2-1
2.1.1 Fixed-Length Strings .....	2-1
2.1.2 Varying-Length Strings .....	2-2
2.1.3 Dynamic-Length Strings .....	2-3
2.1.4 Examples .....	2-3
2.2 Descriptor Classes and String Semantics .....	2-4
2.2.1 Conventions for Reading Input String Arguments .....	2-6
2.2.2 Semantics for Writing Output String Arguments .....	2-7
2.3 Selecting String Manipulation Routines .....	2-9
2.3.1 Efficiency .....	2-9
2.3.2 Argument Passing .....	2-9
2.3.3 Error Handling .....	2-10
2.4 Allocating Resources for Dynamic Strings .....	2-11
2.4.1 String Zone .....	2-13
<b>STR\$ Reference Section</b>	
STR\$ADD .....	STR-3
STR\$ANALYZE_SDESC .....	STR-7
STR\$ANALYZE_SDESC_64 (Alpha only) .....	STR-9
STR\$APPEND .....	STR-11
STR\$CASE_BLIND_COMPARE .....	STR-13
STR\$COMPARE .....	STR-15
STR\$COMPARE_EQL .....	STR-17
STR\$COMPARE_MULTI .....	STR-19
STR\$CONCAT .....	STR-22
STR\$COPY_DX .....	STR-25
STR\$COPY_R .....	STR-27
STR\$COPY_R_64 (Alpha Only) .....	STR-29
STR\$DIVIDE .....	STR-31
STR\$DUPL_CHAR .....	STR-35
STR\$ELEMENT .....	STR-37

STR\$FIND_FIRST_IN_SET .....	STR-39
STR\$FIND_FIRST_NOT_IN_SET .....	STR-41
STR\$FIND_FIRST_SUBSTRING .....	STR-44
STR\$FREE1_DX .....	STR-47
STR\$GET1_DX .....	STR-49
STR\$GET1_DX_64 (Alpha Only) .....	STR-51
STR\$LEFT .....	STR-53
STR\$LEN_EXTR .....	STR-56
STR\$MATCH_WILD .....	STR-59
STR\$MUL .....	STR-62
STR\$POSITION .....	STR-66
STR\$POS_EXTR .....	STR-69
STR\$PREFIX .....	STR-71
STR\$RECIP .....	STR-73
STR\$REPLACE .....	STR-77
STR\$RIGHT .....	STR-80
STR\$ROUND .....	STR-83
STR\$TRANSLATE .....	STR-87
STR\$TRIM .....	STR-90
STR\$UPCASE .....	STR-92

## Index

## Tables

1-1	STR\$ Routines .....	1-2
2-1	String Passing Techniques Used by the Run-Time Library .....	2-5
2-2	How Run-Time Library Routines Read Strings .....	2-6
2-3	Output String Semantics and Descriptor Classes .....	2-8
2-4	Severe Errors, by Facility .....	2-10
2-5	String Zone Attributes .....	2-13

---

# Preface

This manual provides users of the OpenVMS operating system with detailed usage and reference information on string manipulation routines supplied in the STR\$ facility of the Run-Time Library.

## Intended Audience

This manual is intended for system and application programmers who want to call Run-Time Library routines.

## Document Structure

This manual is organized into two parts as follows:

- Part I contains two introductory chapters. The material is covered as follows:
  - Chapter 1 provides a brief overview of the STR\$ routines and lists the routines and their functions.
  - Chapter 2 discusses in detail how to use the Run-Time Library STR\$ routines.
- Part II provides detailed reference information on each routine contained in the STR\$ facility of the Run-Time Library. This information is presented using the documentation format described in *OpenVMS Programming Interfaces: Calling a System Routine*. Routine descriptions appear in alphabetical order by routine name.

## Related Documents

The Run-Time Library routines are documented in a series of reference manuals. A description of how the Run-Time Library routines are accessed is presented in *OpenVMS Programming Interfaces: Calling a System Routine*. A description of OpenVMS features and functionality available through calls to the STR\$ Run-Time Library appears in the *OpenVMS Programming Concepts Manual*. Descriptions of other RTL facilities and their corresponding routines and usages are discussed in the following books:

**Alpha**

- *OpenVMS Alpha Guide to 64-Bit Addressing*
- *Digital Portable Mathematics Library*♦



- *OpenVMS VAX RTL Mathematics (MTH\$) Manual*◆
- *OpenVMS RTL DECTalk (DTK\$) Manual*
- *OpenVMS RTL Library (LIB\$) Manual*
- *OpenVMS RTL General Purpose (OTS\$) Manual*
- *OpenVMS RTL Parallel Processing (PPL\$) Manual*
- *OpenVMS RTL Screen Management (SMG\$) Manual*

The *Guide to DECthreads* contains guidelines and reference information for DECthreads, the Digital Multithreading Run-Time Library.

The *OpenVMS Calling Standard* contains useful information for anyone who wants to call Run-Time Library routines.

Application programmers using any programming language can refer to the *Guide to Creating OpenVMS Modular Procedures* for writing modular and reentrant code.

High-level language programmers will find additional information on calling Run-Time Library routines in their language reference manual. Additional information may also be found in the language user's guide provided with your OpenVMS language software.

For a complete list and description of the manuals in the OpenVMS documentation set, see the *Overview of OpenVMS Documentation*.

For additional information on OpenVMS products and services, access the Digital OpenVMS World Wide Web site. Use the following URL:

<http://www.openvms.digital.com>

## Reader's Comments

Digital welcomes your comments on this manual.

Print or edit the online form `SYSSHELP:OPENVMSDOC_COMMENTS.TXT` and send us your comments by:

Internet	<b><code>openvmsdoc@zko.mts.dec.com</code></b>
Fax	603 881-0120, Attention: OpenVMS Documentation, ZK03-4/U08
Mail	OpenVMS Documentation Group, ZK03-4/U08 110 Spit Brook Rd. Nashua, NH 03062-2698

## How To Order Additional Documentation

Use the following table to order additional documentation or information. If you need help deciding which documentation best meets your needs, call 800-DIGITAL (800-344-4825).

## Telephone and Direct Mail Orders

Location	Call	Fax	Write
U.S.A.	DECdirect 800-DIGITAL 800-344-4825	Fax: 800-234-2298	Digital Equipment Corporation P.O. Box CS2008 Nashua, NH 03061
Puerto Rico	809-781-0505	Fax: 809-749-8300	Digital Equipment Caribbean, Inc. 3 Digital Plaza, 1st Street, Suite 200 P.O. Box 11038 Metro Office Park San Juan, Puerto Rico 00910-2138
Canada	800-267-6215	Fax: 613-592-1946	Digital Equipment of Canada, Ltd. Box 13000 100 Herzberg Road Kanata, Ontario, Canada K2K 2A6 Attn: DECdirect Sales
International	—	—	Local Digital subsidiary or approved distributor
Internal Orders	DTN: 264-4446 603-884-4446	Fax: 603-884-3960	U.S. Software Supply Business Digital Equipment Corporation 10 Cotton Road Nashua, NH 03063-1260

ZK-7654A-GE

## Conventions

The name of the OpenVMS AXP operating system has been changed to OpenVMS Alpha. Any references to OpenVMS AXP or AXP are synonymous with OpenVMS Alpha or Alpha.

The following conventions are used to identify information specific to OpenVMS Alpha or to OpenVMS VAX:



The Alpha icon denotes the beginning of information specific to OpenVMS Alpha.



The VAX icon denotes the beginning of information specific to OpenVMS VAX.



The diamond symbol denotes the end of a section of information specific to OpenVMS Alpha or to OpenVMS VAX.

In this manual, every use of DECwindows and DECwindows Motif refers to DECwindows Motif for OpenVMS software.

The following conventions are also used in this manual:

Ctrl/x

A sequence such as Ctrl/x indicates that you must hold down the key labeled Ctrl while you press another key or a pointing device button.

PF1 <i>x</i> or GOLD <i>x</i>	A sequence such as PF1 <i>x</i> or GOLD <i>x</i> indicates that you must first press and release the key labeled PF1 or GOLD and then press and release another key or a pointing device button. GOLD key sequences can also have a slash (/), dash (-), or underscore (_) as a delimiter in EVE commands.
<span style="border: 1px solid black; padding: 2px;">Return</span>	In examples, a key name enclosed in a box indicates that you press a key on the keyboard. (In text, a key name is not enclosed in a box.)
...	Horizontal ellipsis points in examples indicate one of the following possibilities: <ul style="list-style-type: none"> <li>• Additional optional arguments in a statement have been omitted.</li> <li>• The preceding item or items can be repeated one or more times.</li> <li>• Additional parameters, values, or other information can be entered.</li> </ul>
.	Vertical ellipsis points indicate the omission of items from a code example or command format; the items are omitted because they are not important to the topic being discussed.
( )	In command format descriptions, parentheses indicate that, if you choose more than one option, you must enclose the choices in parentheses.
[ ]	In command format descriptions, brackets indicate optional elements. You can choose one, none, or all of the options. (Brackets are not optional, however, in the syntax of a directory name in an OpenVMS file specification or in the syntax of a substring specification in an assignment statement.)
{ }	In command format descriptions, braces indicate a required choice of options; you must choose one of the options listed.
<b>boldface text</b>	Boldface text represents the introduction of a new term or the name of an argument, an attribute, or a reason. Boldface text is also used to show user input in Bookreader versions of the manual.
<i>italic text</i>	Italic text indicates important information, complete titles of manuals, or variables. Variables include information that varies in system output (Internal error <i>number</i> ), in command lines ( <i>/PRODUCER=name</i> ), and in command parameters in text (where <i>device-name</i> contains up to five alphanumeric characters).
UPPERCASE TEXT	Uppercase text indicates a command, the name of a routine, the name of a file, or the abbreviation for a system privilege.
Monospace type	Monospace type indicates code examples and interactive screen displays. In the C programming language, monospace type in text identifies the following elements: keywords, the names of independently compiled external functions and files, syntax summaries, and references to variables or identifiers introduced in an example.
-	A hyphen at the end of a command format description, command line, or code line indicates that the command or statement continues on the following line.



numbers

All numbers in text are assumed to be decimal unless otherwise noted. Nondecimal radices—binary, octal, or hexadecimal—are explicitly indicated.

Other conventions used in the documentation of Run-Time Library routines are described in *OpenVMS Programming Interfaces: Calling a System Routine*.



---

# Overview of the STR\$ Facility

## 1.1 Run-Time Library STR\$ Routines

The *OpenVMS RTL String Manipulation (STR\$) Manual* discusses the Run-Time Library STR\$ routines that perform string functions. This chapter gives a brief overview of the STR\$ routines and lists the routines and their functions. Chapter 2 explains in detail how the RTL handles strings. The second part of this manual is a reference section describing all the Run-Time Library STR\$ routines.

The STR\$ facility provides you with routines that perform the following functions:

- Perform mathematical operations on strings
- Compare strings
- Extract and replace substrings
- Append and concatenate strings
- Copy strings
- Search characters and substrings
- Free and allocate dynamic strings
- Perform miscellaneous functions on strings

### Mathematical Operation Routines

STR\$ADD, STR\$DIVIDE, STR\$MUL, STR\$RECIP, and STR\$ROUND are routines that perform mathematical functions on strings. These routines allow you to add, divide, and multiply two strings. You can also take the reciprocal of a string or round a string.

### Compare Routines

STR\$CASE\_BLIND\_COMPARE, STR\$COMPARE, STR\$COMPARE\_EQL, and STR\$COMPARE\_MULTI compare the contents of two strings and return a value (-1, 0, or 1) that denotes whether the first string is less than, equal to, or greater than the second string.

### Extract and Replace Routines

STR\$ELEMENT, STR\$LEFT, STR\$LEN\_EXTR, STR\$POS\_EXTR, STR\$REPLACE, and STR\$RIGHT are routines that extract a substring from a string or replace a substring with another substring.

### Append and Concatenate Routines

STR\$APPEND and STR\$CONCAT allow you to append a string to another string, or to concatenate up to 254 strings into one string.

### Copy Routines

STR\$COPY\_DX, STR\$COPY\_R, and STR\$COPY\_R\_64 allow you to copy a string passed by descriptor or by reference to another string.

# Overview of the STR\$ Facility

## 1.1 Run-Time Library STR\$ Routines

### Search Routines

STR\$FIND\_FIRST\_IN\_SET, STR\$FIND\_FIRST\_NOT\_IN\_SET, and STR\$FIND\_FIRST\_SUBSTRING are routines that search a string one character at a time, comparing each character to the characters in a specified set of characters.

### Allocate and Deallocate Routines

STR\$FREE1\_DX, STR\$GET1\_DX, and STR\$GET1\_DX\_64 deallocate and allocate a dynamic string.

### Miscellaneous Routines

STR\$ANALYZE\_SDESC, STR\$ANALYZE\_SDESC\_64, STR\$DUPL\_CHAR, STR\$MATCH\_WILD, STR\$POSITION, STR\$TRANSLATE, STR\$TRIM, and STR\$UPCASE analyze string descriptors, duplicate a character, match wildcard specifications, prefix a string, return a relative position, translate matched characters, trim trailing blanks and tabs, and convert strings to uppercase characters.

### 1.1.1 The STR\$ Routines

Table 1–1 contains all of the STR\$ routines and their functions.

**Table 1–1 STR\$ Routines**

Routine Name	Function
STR\$ADD	Add two decimal strings
STR\$ANALYZE_SDESC	Analyze a string descriptor
STR\$ANALYZE_SDESC_64	Analyze a string descriptor
STR\$APPEND	Append a string
STR\$CASE_BLIND_COMPARE	Compare strings without regard to case
STR\$COMPARE	Compare two strings
STR\$COMPARE_EQL	Compare two strings for equality
STR\$COMPARE_MULTI	Compare two strings for equality using the DEC Multinational Character Set
STR\$CONCAT	Concatenate two or more strings
STR\$COPY_DX	Copy a source string passed by descriptor to a destination string
STR\$COPY_R	Copy a source string passed by reference to a destination string
STR\$COPY_R_64	Copy a source string passed by reference to a destination string
STR\$DIVIDE	Divide two decimal strings
STR\$DUPL_CHAR	Duplicate character <i>n</i> times
STR\$ELEMENT	Extract delimited element substring
STR\$FIND_FIRST_IN_SET	Find the first character in a set of characters
STR\$FIND_FIRST_NOT_IN_SET	Find the first character that does not occur in the set
STR\$FIND_FIRST_SUBSTRING	Find the first substring in the input string
STR\$FREE1_DX	Free one dynamic string

(continued on next page)

**Table 1–1 (Cont.) STR\$ Routines**

Routine Name	Function
STR\$GET1_DX	Allocate one dynamic string
STR\$GET1_DX_64	Allocate one dynamic string
STR\$LEFT	Extract a substring of a string
STR\$LEN_EXTR	Extract a substring of a string
STR\$MATCH_WILD	Match a wildcard specification
STR\$MUL	Multiply two decimal strings
STR\$POSITION	Return relative position of a substring
STR\$POS_EXTR	Extract a substring of a string
STR\$PREFIX	Prefix a string
STR\$RECIP	Return the reciprocal of a decimal string
STR\$REPLACE	Replace a substring
STR\$RIGHT	Extract a substring of a string
STR\$ROUND	Round or truncate a decimal string
STR\$TRANSLATE	Translate matched characters
STR\$TRIM	Trim trailing blanks and tabs
STR\$UPCASE	Convert string to all uppercase

### 1.1.2 64-bit Addressing Support

**Alpha**

On Alpha systems, the String Manipulation (STR\$) routines provide 64-bit virtual addressing capabilities as follows:

- Most routines now accept 64-bit addresses for arguments passed by reference. For those that do not, a footnote to the routine in the Reference Section of this manual indicates whether support is planned for Theta EFT or not at all.
- Most routines also accept either 32-bit or 64-bit descriptors for arguments passed by descriptor. For those that do not, a footnote to the routine in the Reference Section of this manual indicates whether support is planned for Theta EFT or not at all.
- In some cases a new routine was added to support a 64-bit addressing or data capability. These routines carry the same name as the original routine but with a `_64` suffix. In general, both versions of the routine support 64-bit addressing but the routine with the `_64` suffix also supports additional 64-bit capability. The 32-bit capabilities of the original routine are unchanged.

See the *OpenVMS Alpha Guide to 64-Bit Addressing* for more information about 64-bit virtual addressing capabilities. ♦



---

# Introduction to String Manipulation (STR\$) Routines

This chapter explains in detail the following topics:

- Types of strings recognized by Run-Time Library routines
- Relationship of descriptor classes to string semantics
- Differences in string handling among the LIB\$, OTS\$, and STR\$ facilities of the Run-Time Library
- Conventions for reading and writing string arguments in the Run-Time Library string routines
- Selection of the proper string manipulation routines
- Allocation and deallocation of dynamic string resources

## Descriptor Names and Field Names

In this chapter and throughout this manual it is generally the practice to use only the main part of a descriptor name or a descriptor field name, without the 32-bit or 64-bit prefix used in the actual code. For example, the length field is referred to using LENGTH rather than by mentioning both DSC\$W\_LENGTH and DSC64\$Q\_LENGTH. The complete descriptor or field name, including the prefix, is used only when referring to one particular form of the descriptor.

## 2.1 String Semantics in the Run-Time Library

The **semantics** of a string refers to the conventions that determine how a string is stored, written, and read. The Alpha and VAX architectures support three string semantics: fixed length, varying length, and dynamic length.

### 2.1.1 Fixed-Length Strings

Fixed-length strings have two attributes:

- An address
- A length

The length of a fixed-length string is constant. It is usually initialized when the program is compiled or linked. After initialization, this length is read but never written. When a Run-Time Library routine copies a source string into a longer fixed-length destination string, the routine pads the destination string with trailing blanks.

When you pass a string to a Run-Time Library routine, you pass the string by descriptor. For a fixed-length string, the descriptor must contain this information:

- The descriptor class
- The data type of the string

## Introduction to String Manipulation (STR\$) Routines

### 2.1 String Semantics in the Run-Time Library

- The length of the string in bytes
- The address of the beginning of the string

In most cases, you do not have to construct an actual descriptor. By default, most OpenVMS Alpha and OpenVMS VAX languages pass strings by descriptor. For information about how the language you are using handles strings, see your language reference manual. For more information about descriptors used for fixed-length strings, refer to *OpenVMS Programming Interfaces: Calling an OpenVMS Routine*.

---

#### Note

---

In contrast to Run-Time Library routines, system services do not pad output strings. For this reason, when a program calls a system service that returns a fixed-length string, the program should supply an additional argument that indicates how many bytes the system service actually deposited in the fixed-length buffer of the calling program. Some system service routines have corresponding Run-Time Library routines that provide the proper semantics for fixed-length, varying-length, and dynamic output strings.

---

#### 2.1.2 Varying-Length Strings

Varying-length strings have the following three attributes:

- A current length
- An address
- A maximum length

The current length, in bytes, of a varying-length string is stored in a two-byte field, called CURLEN, preceding the text of the string. The address of the string points to the beginning of this CURLEN field, not to the beginning of the string's text.

The maximum string length is a field in the string's descriptor. The maximum string length field specifies how much space is allocated to the string in a program. The maximum string length is fixed and does not change.

The value in the CURLEN field specifies how many bytes beyond the CURLEN field are occupied by the string's text. The character positions beyond this range are reserved for the growth of the string. Their contents are undefined.

For example, assume a varying string whose CURLEN is 3 and whose maximum length is 6. If a string 'ABCD' is copied into this string, the result is 'ABCD' and the CURLEN is changed to 4. If a string 'XYZ' is now copied into the same varying string, the resulting string is 'XYZ' with a CURLEN of 3. The maximum length is still 6. The bytes beyond the range designated by CURLEN are undefined.

For varying-length strings pointed to by both 32-bit and 64-bit descriptors, CURLEN is a two-byte field. Because of this, the maximum length of a varying-length string is limited to  $2^{16} - 1$ , or 65,535, characters.



### 2.1.3 Dynamic-Length Strings

Dynamic-length strings have two attributes:

- A current length
- An address pointing to the beginning of the text

Theoretically, dynamic strings have unbounded length. However, the descriptor LENGTH field contains the length of the string as an unsigned value. This effectively limits the maximum length of the string to the maximum unsigned integer value this field can hold.

For 32-bit dynamic descriptors, the LENGTH field is an unsigned value occupying two bytes. Because its maximum value is  $2^{16} - 1$ , or 65,535, the maximum length of a string is limited to 65,535 characters.

Alpha

On Alpha systems, the LENGTH field of a 64-bit dynamic descriptor is an unsigned value occupying eight bytes. Because its maximum value is  $2^{64} - 1$ , the maximum length of a string is  $2^{64} - 1$  characters. ♦

The actual space for a dynamic-length string is allocated from heap storage by the Run-Time Library. When a Run-Time Library routine copies a character string into a dynamic string, and the currently allocated heap storage is not large enough to contain the string, the currently allocated storage returns to a pool of heap storage maintained by the string routines. Then the string routines obtain a new area of the correct size. As a result of this process of deallocation and reallocation, both the current-length field and the address portion of the string's descriptor may change. Often, dynamic strings are the most convenient type to write.

---

**Note**

---

The Run-Time Library string manipulation routines are the only routines that you should use to alter the length or address of a dynamic string. Do not use LIB\$GET\_VM or LIB\$GET\_VM\_64 for this purpose.

---

### 2.1.4 Examples

The following examples illustrate what happens when the string 'ABCDEF' (of length 6) is copied into various destination strings.

- Fixed-length string

If 'ABCDEF' is copied into a fixed-length string, three results are possible:

1. If the length of the output string is greater than the length of the source string, the string is padded with trailing spaces.

Length of output string	10
Result	'ABCDEF '

2. If the length of the output string is the same as that of the input string, the string is simply copied with no modification.

Length of output string	6
Result	'ABCDEF'

## Introduction to String Manipulation (STR\$) Routines

### 2.1 String Semantics in the Run-Time Library

3. If the length of the output string is less than the length of the source string, truncation on the right occurs.

Length of output string	3
Result	'ABC'

- Varying-length string

If the same string ('ABCDEF') is copied into a varying-length string, two results are possible:

1. If the MAXSTRLEN field of the destination is greater than or equal to the length of the source, the input string is written into the output string without modification, and the CURLEN (current length) field of the output string becomes 6.
2. If the MAXSTRLEN field of the destination is less than the length of the source string, the source string is truncated on the right and the CURLEN field is rewritten to its current length. For example, if MAXSTRLEN = 4, the resulting string contains 'ABCD' and CURLEN = 4.

- Dynamic-length string

If a Run-Time Library routine copies the string 'ABCDEF' into a dynamic destination string, three results are possible:

1. If the length of the destination string is greater than the length of the source string (6), the result is a dynamic string of length 6 containing 'ABCDEF'. No padding takes place. The Run-Time Library may deallocate the string and reallocate a new string closer in length to the length of the source string.
2. If the length of the destination string is less than the length of the source string, the result is also 'ABCDEF', with a length of 6. The Run-Time Library deallocates the destination string and allocates a new string large enough to hold the 6 characters.
3. If the destination string and source string are of equal length, a simple copy is done. No allocation, deallocation, or padding takes place, and the destination descriptor is not modified.

### 2.2 Descriptor Classes and String Semantics

A calling program passes strings to a Run-Time Library STR\$ routine by descriptor. That is, the argument list entry for an input or output string is actually the address of a string descriptor. All STR\$ routines handle both 32-bit and 64-bit descriptors in the argument list.

The calling program allocates a descriptor for the input string that indicates the string's address and length, so that the called routine can find the string's text and operate on it. The calling program also allocates a descriptor for the output string. In addition to length and address fields, each descriptor contains a field (DSC\$B\_CLASS or DSC64\$B\_CLASS) indicating the descriptor's class. The STR\$ routine reads the class field to determine whether to write the output string as fixed length, varying length, or dynamic string.

To determine the address and length of the data in the input string, Run-Time Library routines call one of the string descriptor analysis routines: LIB\$ANALYZE\_SDESC, LIB\$ANALYZE\_SDESC\_64, STR\$ANALYZE\_SDESC, or STR\$ANALYZE\_SDESC\_64.

## Introduction to String Manipulation (STR\$) Routines

### 2.2 Descriptor Classes and String Semantics

The STR\$ routines provide a centralized facility for analyzing string descriptors, allowing string-handling routines to function independently of the class of the input string. This means that if the Run-Time Library recognizes new string types, only the analysis routine needs to be changed, not the string routines themselves. If you are writing a routine that recognizes all the string types recognized by the Run-Time Library, your routine should first call the appropriate string-descriptor analysis routine to obtain the address and length of the input string.

You can also use the string descriptor analysis routines to find the length of a returned string. Assume that your called routine calls one of the Run-Time Library string-copying routines to create a new string. You now want the called routine to return the actual length of the new string to the calling program. The called routine calls one of the string-descriptor analysis routines to determine this length. This sequence of calls allows you to create the new string without knowing its ultimate length at the time it is created.

The Run-Time Library routines recognize the following classes of string descriptors:

- Z—unspecified
- S—scalar, fixed-length string
- SD—decimal scalar
- VS—varying-length string
- D—dynamic string
- A—array
- NCA—noncontiguous array

For a detailed description of these descriptor classes and their fields, see the *OpenVMS Calling Standard*.

Table 2-1 indicates how the Run-Time Library routines access the fields of the descriptor for input and output string arguments. Given the class of the string and the field of the descriptor, the table shows whether the routine reads, writes, or modifies the field.

**Table 2-1 String Passing Techniques Used by the Run-Time Library**

String Type	String Descriptor Fields		
	Class	Length	Pointer
<b>Input Argument to Routines</b>			
Input string passed by descriptor	Read	Read	Read
<b>Output Argument from Routines; Called Routine Assumes the Descriptor Class</b>			
Output string passed by descriptor, fixed-length	Ignored	Read	Read
Output string passed by descriptor, dynamic	Ignored	Read, can be modified	Read, can be modified

(continued on next page)

## Introduction to String Manipulation (STR\$) Routines

### 2.2 Descriptor Classes and String Semantics

Table 2–1 (Cont.) String Passing Techniques Used by the Run-Time Library

String Type	String Descriptor Fields		
	Class	Length	Pointer
<b>Output Argument from Routines; Calling Program Specifies the Descriptor Class in the Descriptor</b>			
Output string, fixed-length— Descriptor class: S, Z, A, NCA, SD	Read	Read	Read
Output string, dynamic— Descriptor class: D	Read	Read, can be modified	Read, can be modified
Output string, varying-length— Descriptor class: VS	Read	MAXSTRLEN is read; CURLLEN is modified	Read

#### 2.2.1 Conventions for Reading Input String Arguments

When a calling program passes a string as an argument to a Run-Time Library routine, the argument contains the address of a descriptor. The called routine examines the CLASS field of the descriptor to determine in which fields it can find the length of the string and the first byte of the string's text. For each descriptor class, Table 2–2 indicates which descriptor fields the routine uses to locate this information. For diagrams of the descriptors, see the *OpenVMS Calling Standard* manual.

Table 2–2 How Run-Time Library Routines Read Strings

Class	String Length	Address of First Byte of Data
Z	DSC\$W_LENGTH DSC64\$Q_LENGTH	DSC\$A_POINTER DSC64\$PQ_POINTER
S	DSC\$W_LENGTH DSC64\$Q_LENGTH	DSC\$A_POINTER DSC64\$PQ_POINTER
D	DSC\$W_LENGTH DSC64\$Q_LENGTH	DSC\$A_POINTER DSC64\$PQ_POINTER
A	DSC\$L_ARSIZE DSC64\$Q_ARSIZE	DSC\$A_POINTER DSC64\$PQ_POINTER
SD	DSC\$W_LENGTH DSC64\$Q_LENGTH	DSC\$A_POINTER DSC64\$PQ_POINTER
NCA	DSC\$L_ARSIZE DSC64\$Q_ARSIZE	DSC\$A_POINTER DSC64\$PQ_POINTER
VS	Word at DSC\$A_POINTER or at DSC64\$PQ_POINTER (CURLLEN field)	Value of DSC\$A_POINTER + 2 or of DSC64\$PQ_POINTER + 2 (byte after CURLLEN field)

**Note:**

- If the descriptor class is NCA, it is assumed that the string is actually contiguous.
- If the descriptor class is A or NCA, the element size is assumed to be 1 byte.
- If the descriptor class is A or NCA and the array being passed is multidimensional, you should be aware of how your language stores arrays (by column or by row).

## Introduction to String Manipulation (STR\$) Routines

### 2.2 Descriptor Classes and String Semantics

#### 2.2.2 Semantics for Writing Output String Arguments

Normally, Run-Time Library routines return the result of an operation in one of two ways:

- The called routine returns the result as a **function value** in R0/R1. If the result is too large to fit in R0/R1, it is returned as a function value in the first position in the argument list, and the other arguments are shifted one position to the right.
- The called routine returns the result as an **output argument**. The calling program passes to the called routine an argument naming a variable in which the routine writes the output string. In each RTL routine, the access field of an output argument contains “write only”.

The STR\$ routines that produce string results use the first method to pass the results back to the calling program. Because a return string, by definition, does not fit in R0/R1, the function value from a STR\$ routine is placed in the first position in the argument list.

On the other hand, the string manipulation routines in the LIB\$ and OTS\$ facilities use the second method. They return their results as output arguments.

For example, there are three entry points for the string-copying routine, LIB\$COPY\_DXDX, OTS\$COPY\_DXDX, and STR\$COPY\_DX. These copy the source string (**source-string**) to the destination string (**destination-string**). Their formats are as follows:

```
LIB$COPY_DXDX(source-string ,destination-string)
OTS$COPY_DXDX(source-string ,destination-string)
STR$COPY_DX(destination-string ,source-string)
```

Because the STR\$ entry point places the result string in the first position, you can call STR\$COPY\_DX using a function reference in languages that support string functions. In Fortran, for example, you can use a function reference to invoke STR\$COPY\_DX in the following two ways:

```
CHARACTER*80 STR$COPY_DX
RETURN_STATUS = STR$COPY_DX(DESTINATION_STRING, SOURCE_STRING)
```

or

```
DESTINATION_STRING = STR$COPY_DX(SOURCE_STRING)
```

If you use the second form, you cannot access the return status, which is used to indicate truncation.

If you use a function reference to invoke a string manipulation routine in a language that does not support the concept of a string function (such as MACRO, BLISS, and Pascal), you must place the destination string variable in the argument list. In Pascal, for example, you can use a function reference to invoke STR\$COPY\_DX as follows:

```
STATUS := STR$COPY_DX(DESTINATION_STRING, SOURCE_STRING);
```

However, the following statement results in an error:

```
DESTINATION_STRING := STR$COPY_DX(SOURCE_STRING)
```

In addition to allocating a variable for the output string, the calling program must allocate the space for and fill in the fields of the output string descriptor at compile, link, or run time. High-level languages do this automatically.

## Introduction to String Manipulation (STR\$) Routines

### 2.2 Descriptor Classes and String Semantics

When a Run-Time Library routine returns an output string argument to the calling program, the argument list entry is the address of a descriptor. The routine determines the semantics of the output string (fixed, varying, or dynamic) by examining the class of the descriptor for the destination string. Given the class of the output string's descriptor, Table 2-3 specifies the semantics used by Run-Time Library routines when writing the string.

**Table 2-3 Output String Semantics and Descriptor Classes**

Class	Description	Restrictions	Semantics
Z	Unspecified	Treated as class S.	Fixed-length string
S	Scalar, string	None.	Fixed-length string
D	Dynamic string	String length: $DSC\$W\_LENGTH < 2^{16}$ (64K) $DSC64\$Q\_LENGTH < 2^{64}$	Dynamic-length string
A	Array	Array is one-dimensional (DIMCT = 1). String length: $DSC\$L\_ARSIZE < 2^{16}$ (64K) $DSC64\$Q\_ARSIZE < 2^{64}$ Length of array elements is 1 byte (LENGTH = 1).	Fixed-length string
SD	Scalar decimal	The DIGITS and SCALE fields are ignored.	Fixed-length string
NCA	Noncontiguous array	Array is one-dimensional (DIMCT = 1). String length: $DSC\$L\_ARSIZE < 2^{16}$ (64K) $DSC64\$Q\_ARSIZE < 2^{64}$ Length of array elements is 1 byte (LENGTH = 1). Array is contiguous (S1 = LENGTH).	Fixed-length string
VS	Varying string	Current length less than maximum string length. ( $CURLen \leq MAXSTRLEN \leq 2^{16}$ (64K))	Varying-length string

When a called routine returns a string whose length cannot be determined by the calling routine, the calling routine should also pass an optional argument to contain the output length. If the output string is a fixed-length string, the length argument would reflect the number of characters written, not counting the fill characters.

The output length argument is useful, for instance, when your program is reading variable-length records. The program can read the input strings into a buffer that is large enough to contain the largest. When you wish to perform the next operation on the contents of the buffer, the length argument indicates exactly how many characters have been read, so that the program does not need to manipulate the whole buffer.

For example, LIB\$GET\_INPUT has the optional argument **resultant-length**. If LIB\$GET\_INPUT is called with a fixed-length, five-character string as an argument, and the routine reads a record containing 'ABC', then **resultant-length** has a value of 3 and the output string, 'ABC ', contains the characters ABC followed by two blanks. But if the routine reads a record containing the value 'ABCDEFG', **resultant-length** has a value of 5, and the output string is 'ABCDE'. In either case, the calling program knows exactly how many characters (not counting fillers) the routine has read.

A routine such as STR\$COPY\_DX does not need the length argument, because the calling program can determine the length of the output string. If the output string is dynamic, the length is the same as the input string length. If the output string is fixed-length, the length is the shorter of the two input lengths.

## **2.3 Selecting String Manipulation Routines**

To perform a given string manipulation operation, you can often choose one of several routines from the Run-Time Library. The LIB\$, OTS\$, and STR\$ facilities all contain string copying and dynamic string allocation routines. Furthermore, a MACRO or BLISS program can call several of these routines using either a JSB or CALL entry point.

You should consider the factors discussed in the following sections when choosing a routine to perform the desired operation.

### **2.3.1 Efficiency**

One of the major considerations in choosing among several routines is the efficiency of the various options.

In general, LIB\$ and STR\$ routines execute more efficiently than the corresponding OTS\$ routines. OTS\$ routines usually invoke the LIB\$ entry point to perform an operation.

JSB entry points usually execute more efficiently than CALL entry points. However, a high-level language cannot explicitly access a JSB entry point. Further, a JSB entry point does not establish a stack frame and executes entirely in the environment of the calling program. This means, for instance, that the called routine cannot establish its own condition handler, so it cannot regain control if an exception occurs during execution. Also, some of the efficiency gained by using the JSB entry point may be lost because the calling routine must explicitly save all of the registers that the called routine uses.

Some routines perform a specific operation that is a subset of a more general capability. These more specialized routines are usually more efficient. For example, if you want to join two strings together, STR\$APPEND and STR\$PREFIX are more specific, and more efficient, than STR\$CONCAT. Similarly, STR\$LEFT and STR\$RIGHT are subsets of the capabilities of STR\$POS\_EXTR.

### **2.3.2 Argument Passing**

The mechanism by which a routine passes or receives arguments may also help you to decide among several routines that perform basically the same function.

Routines in the LIB\$ and STR\$ facilities pass scalar input arguments by reference to CALL entry points and by immediate value to JSB entry points. OTS\$ routines pass scalar input arguments by immediate value to all entry points. For most high-level languages, the default passing mechanism is by reference. Thus, if you call a LIB\$ or STR\$ routine from one of these languages, it is not necessary to specify the passing mechanism for input scalar arguments.

Some routines require you to set up and pass more arguments than others. For example, some use a single string descriptor, while others require separate arguments for the length and the address of the string. Which routine you choose then depends on the form of the information already available in your program.



## Introduction to String Manipulation (STR\$) Routines

### 2.3 Selecting String Manipulation Routines

#### 2.3.3 Error Handling

Routines from the LIB\$, OTS\$, and STR\$ facilities handle errors in string copying differently:

- LIB\$

The LIB\$ string-copying routines return a completion status. When an output string must be truncated and its length depends on input arguments, LIB\$ routines consider this to be a partial success; they therefore return LIB\$\_STRTRU instead of a severe error. This process corresponds to the convention of many higher-level languages, which do not consider truncation to be an error.

- STR\$

The STR\$ string-copying routines generally signal errors instead of returning a completion status. In the case of truncation errors, STR\$ routines return an error status with a severity of WARNING (STR\$\_TRU). STR\$ routines consider range errors to be qualified success.

- OTS\$

The OTS\$ string-copying routines also signal errors that are considered fatal (such as invalid descriptor class). In addition, the routine returns in R0 the number of bytes in the source string that were not moved to the destination string. For VAX systems, this is the same as a MOVC5 instruction. The JSB entry points for OTS\$ string-copying routines also leave registers R1 through R5 as they would be after a VAX MOVC5 instruction. See the *VAX Architecture Reference Manual* for a complete description of the MOVC5 instruction.

Table 2-4 indicates the errors that each facility considers severe and the corresponding message.

**Table 2-4 Severe Errors, by Facility**

Error	LIB\$_	OTS\$_	STR\$_
Fatal internal error	FATERRLIB	FATINTERR	FATINTERR
Illegal string class	INVSTRDES	INVSTRDES	ILLSTRCLA
Insufficient virtual memory	INSVIRMEM	INSVIRMEM	INSVIRMEM

Some Run-Time Library routines require you to specify the length of a string or the position of a character within a string. When you refer to character positions in a string, the first position is 1. Given a string with length  $L$ , containing a substring specified by character positions  $M$  to  $N$ , the following evaluation rules apply:

- If  $M$  is less than 1,  $M$  is considered to equal 1.
- If  $M$  is greater than  $L$ , the substring specified is the null string.
- If  $N$  is greater than  $L$ ,  $N$  is considered to equal the length of the source string.
- If  $M$  is greater than  $N$ , the substring specified is the null string.



## Introduction to String Manipulation (STR\$) Routines

### 2.3 Selecting String Manipulation Routines

When specifying a substring of length  $L$ , the following applies:

- If  $L$  is less than 0, the substring specified is the null string. (A null string is a descriptor with zero length. A descriptor with a nonzero length and a zero pointer generates an error and yields unspecified results.)

If any of these evaluation rules applies, the range error status (qualified success) is returned. STR\$POSITION represents the exception to this convention. This routine returns a function value giving the character position of a substring within a string. If the function value is 0, the substring was not found.

## 2.4 Allocating Resources for Dynamic Strings

This section tells how to use the Run-Time Library string resource allocation routines. These routines allocate virtual memory for a dynamic string and place the address of the allocated memory in a descriptor.

Dynamic strings may be the most convenient type to write, since you need not specify constant length, maximum length, or position for them. However, there are some restrictions on dynamic strings.

- They may cause program execution to be slower at run time.
- They require larger address space.
- They are not supported by all OpenVMS Alpha and OpenVMS VAX languages.

In most cases, when you call a Run-Time Library routine to manipulate dynamic strings, the Run-Time Library routine itself allocates the required memory for the string. Your program needs to allocate only the descriptors.

For example, if you are copying a source string into a dynamic destination string, simply use one of the library's string-copying routines. Copy the input string into a dynamic string whose length and address are initialized to zero. The string-copying routine then allocates the space that the calling program needs.

However, if your program must explicitly construct or modify a dynamic string descriptor, it must use the Run-Time Library allocation and deallocation routines. This technique may be necessary, for instance, if you are constructing a string out of components that are not themselves in string form. Further, you can use one of the deallocation routines to free the dynamic string after the string resources are no longer needed, in order to optimize the program's use of resources.

The Run-Time Library provides eight entry points for string resource allocation and deallocation, all with slightly different input arguments, calling techniques, or methods of indicating errors. The following lists summarize these routines and their functions.

The following routines allocate a specified number of bytes of dynamic virtual memory to a specified string descriptor.

Routine	JSB Entry Point
LIB\$SGET1_DD	LIB\$SGET1_DD_R6
LIB\$SGET1_DD_64	LIB\$SGET1_DD_R6
OT\$SGET1_DD	OT\$SGET1_DD_R6
STR\$GET1_DX	STR\$GET1_DX_R4

## Introduction to String Manipulation (STR\$) Routines

### 2.4 Allocating Resources for Dynamic Strings

Routine	JSB Entry Point
STR\$GET1_DX_64	STR\$GET1_DX_R4

The following routines return one dynamic string area to free storage, and set the descriptor POINTER and LENGTH fields to zero.

Routine	JSB Entry Point
LIB\$SFREE1_DD	LIB\$SFREE1_DD6
OT\$SFREE1_DD	OT\$SFREE1_DD6
STR\$FREE1_DX	STR\$FREE1_DX_R4

The following routines return one or more dynamic string areas to free storage, and set the descriptor POINTER and LENGTH fields to zero.

Routine	JSB Entry Point
LIB\$SFREEN_DD	LIB\$SFREEN_DD6
OT\$SFREEN_DD	OT\$SFREEN_DD6

If you find it necessary to call the dynamic string allocation routines, there are several factors to consider:

- When your program calls a string allocation routine, it needs to allocate space only for the string descriptor before making the call. Your program does this using the statement of the particular language, either statically at compile time or dynamically in local stack storage or heap storage.
- If your routine explicitly allocates dynamic string descriptors in stack storage, it must explicitly free the associated dynamic string areas by calling the LIB\$SFREE1\_DD, OT\$SFREE1\_DD, or STR\$FREE1\_DX routine. Then your routine must free the storage for the descriptor. After both areas have been freed, your routine can return to the calling program. If the deallocation is not done, the dynamic string area becomes unavailable when the RET instruction removes the descriptors that point to the string area.
- If a routine has explicitly allocated dynamic string areas, and the routine is then unwound by the condition handling facility, the allocated address space cannot be referenced again. For this reason, your program should establish a handler that frees the associated dynamic string areas when the SSS\_UNWIND condition is signaled. The handler can free these areas by calling one of the deallocation routines. This technique is especially important if a large amount of address space is involved, or if the routine allocates space within a repeating loop.

You can call the string resource allocation routines only from user mode, at AST or non-AST level. However, be extremely careful if you manipulate dynamic strings at AST level. The string manipulation routines in the Run-Time Library do not prevent the strings that they are manipulating at non-AST level from being modified at AST level.

For example, consider the case in which a string manipulation routine has calculated the lengths and addresses involved in a concatenation operation. This string manipulation routine may be interrupted by an AST. The user, at AST level, may write to the same string, changing its length and address. It is then

## Introduction to String Manipulation (STR\$) Routines

### 2.4 Allocating Resources for Dynamic Strings

possible to resume execution of the routine with addresses that are no longer allocated or string lengths that are no longer valid. For this reason, if you use dynamic strings at AST level, you should allocate, use, and deallocate them within the AST code.

The dynamic string manipulation routines are intended for use at user mode only. If you need to manipulate dynamic strings at another access mode, you should allocate and deallocate storage for each string at that access mode to avoid side effects. Link each segment of your program that runs at a different access mode with the /NOSYSSHR qualifier. In this way, you establish a separate copy of the string database for each access mode.

#### 2.4.1 String Zone

All virtual memory for dynamic strings is allocated from a Run-Time Library zone called the string zone.

The string zone has the following benefits:

- Efficient memory utilization.
- Allocation and deallocation for long strings (more than 136 bytes for a VAX system and more than 272 bytes for an Alpha system) is twice as fast.
- Elimination of paging contention with the default zone by isolation of the string virtual memory accesses to a separate zone. A direct side effect of this is that corruptions caused by writing into previously freed strings no longer affect items allocated in the default zone, directly easing the debugging effort for such problems.

Table 2–5 shows attribute values for 32-bit and 64-bit string zones. VAX systems have a 32-bit string zone; Alpha systems have both a 32-bit and a 64-bit string zone.

**Table 2–5 String Zone Attributes**

Attribute	32-bit String Zone	64-bit String Zone
Algorithm	Quick fit	Quick fit
Number of lookaside lists	17 (short strings from 8 to 136 bytes)	17 (short strings from 8 to 272 bytes)
Area of initial size	4 pages	4 pages
Area of extension size	32 pages	32 pages
Block size	8 bytes	16 bytes
Alignment	Longword boundary	Quadword boundary
Smallest block size	16 bytes (includes boundary tags)	32 bytes (includes boundary tags)
Boundary tags	Boundary tags are used for long strings	Boundary tags are used for long strings
Page limit	No page limit	No page limit
Fill on allocate	No fill on allocate	No fill on allocate
Fill on free	No fill on free	No fill on free



# **STR\$ Reference Section**

---

This section provides detailed descriptions of the routines provided by the OpenVMS RTL String Manipulation (STR\$) Facility.



---

## STR\$ADD

### Add Two Decimal Strings

The Add Two Decimal Strings routine adds two decimal strings of digits.

#### Format

STR\$ADD *assign* ,*aexp* ,*adigits* ,*bsign* ,*bexp* ,*bdigits* ,*csign* ,*cexp* ,*cdigits*

#### Returns

OpenVMS usage: *cond\_value*  
type: longword (unsigned)  
access: write only  
mechanism: by value

#### Arguments

##### **assign**

OpenVMS usage: *longword\_unsigned*  
type: longword (unsigned)  
access: read only  
mechanism: by reference

Sign of the first operand. The **assign** argument is the address of an unsigned longword containing this sign. A value of 0 is considered positive; a value of 1 is considered negative.

##### **aexp**

OpenVMS usage: *longword\_signed*  
type: longword (signed)  
access: read only  
mechanism: by reference

Power of 10 by which **adigits** is multiplied to get the absolute value of the first operand. The **aexp** argument is the address of a signed longword containing this exponent.

##### **adigits**

OpenVMS usage: *char\_string*  
type: character string  
access: read only  
mechanism: by descriptor

Text string of unsigned digits representing the absolute value of the first operand before **aexp** is applied. The **adigits** argument is the address of a descriptor pointing to this string. This string must be an unsigned decimal number.

##### **bsign**

OpenVMS usage: *longword\_unsigned*  
type: longword (unsigned)  
access: read only  
mechanism: by reference

## STR\$ Routines

### STR\$ADD

Sign of the second operand. The **bsign** argument is the address of an unsigned longword containing the second operand's sign. A value of 0 is considered positive; a value of 1 is considered negative.

#### **bexp**

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: read only  
mechanism: by reference

Power of 10 by which **bdigits** is multiplied to get the absolute value of the second operand. The **bexp** argument is the address of a signed longword containing the second operand's exponent.

#### **bdigits**

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Text string of unsigned digits representing the absolute value of the second operand before **bexp** is applied. The **bdigits** argument is the address of a descriptor pointing to this string. This string must be an unsigned decimal number.

#### **csign**

OpenVMS usage: longword\_unsigned  
type: longword (unsigned)  
access: write only  
mechanism: by reference

Sign of the result. The **csign** argument is the address of an unsigned longword containing the result's sign. A value of 0 is considered positive; a value of 1 is considered negative.

#### **cexp**

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: write only  
mechanism: by reference

Power of 10 by which **cdigits** is multiplied to get the absolute value of the result. The **cexp** argument is the address of a signed longword containing this exponent.

#### **cdigits**

OpenVMS usage: char\_string  
type: character string  
access: write only  
mechanism: by descriptor

Text string of unsigned digits representing the absolute value of the result before **cexp** is applied. The **cdigits** argument is the address of a descriptor pointing to this string. This string is an unsigned decimal number.



## Description

STR\$ADD adds two strings of decimal numbers (**a** and **b**). Each number to be added is passed to STR\$ADD in three arguments:

1. **xdigits**—the string portion of the number
2. **xexp**—the power of ten needed to obtain the absolute value of the number
3. **xsign**—the sign of the number

The value of the number **x** is derived by multiplying **xdigits** by  $10^{xexp}$  and applying **xsign**. Therefore, if **xdigits** is equal to '2' and **xexp** is equal to 3 and **xsign** is equal to 1, then the number represented in the **x** arguments is  $2 * 10^3$  plus the sign, or -2000.

The result of the addition **c** is also returned in those three parts.

## Condition Values Returned

SS\$_NORMAL	Routine successfully completed.
STR\$_TRU	String truncation warning. The destination string could not contain all the characters in the result string.

## Condition Values Signaled

LIB\$_INVARG	Invalid argument.
STR\$_FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$_INSVIRMEM	Insufficient virtual memory. STR\$ADD could not allocate heap storage for a dynamic or temporary string.
STR\$_WRONUMARG	Wrong number of arguments.

## STR\$ Routines

### STR\$ADD

#### Example

```
100 !+
    ! This is a sample arithmetic program
    ! showing the use of STR$ADD to add
    ! two decimal strings.
    !-

    ASIGN% = 1%
    AEXP% = 3%
    ADIGITS$ = '1'
    BSIGN% = 0%
    BEXP% = -4%
    BDIGITS$ = '2'
    CSIGN% = 0%
    CEXP% = 0%
    CDIGITS$ = '0'
    PRINT "A = "; ASIGN%; AEXP%; ADIGITS$
    PRINT "B = "; BSIGN%; BEXP%; BDIGITS$
    CALL STR$ADD      (ASIGN%, AEXP%, ADIGITS$, &
                      BSIGN%, BEXP%, BDIGITS$, &
                      CSIGN%, CEXP%, CDIGITS$)
    PRINT "C = "; CSIGN%; CEXP%; CDIGITS$
999 END
```

This BASIC example uses STR\$ADD to add two decimal strings, where the following values apply:

A = -1000 (ASIGN = 1, AEXP = 3, ADIGITS = '1')  
B = .0002 (BSIGN = 0, BEXP = -4, BDIGITS = '2')

The output generated by this program is listed below; note that the decimal value of C equals -999.9998 (CSIGN = 1, CEXP = -4, CDIGITS = '9999998').

```
A = 1 3 1
B = 0 -4 2
C = 1 -4 9999998
```

---

## STR\$ANALYZE\_SDESC

### Analyze String Descriptor

The Analyze String Descriptor routine extracts the length and starting address of the data for a variety of string descriptor classes.

#### Format

STR\$ANALYZE\_SDESC input-descriptor ,integer-length ,data-address

#### Corresponding JSB Entry Point

STR\$ANALYZE\_SDESC\_R1

#### Returns

OpenVMS usage: word\_unsigned  
type: word (unsigned)  
access: write only  
mechanism: by value

Length of the data. The return value is the same value returned to the **integer-length** argument.

#### Arguments

##### input-descriptor

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Input descriptor from which STR\$ANALYZE\_SDESC extracts the length of the data and the address at which the data starts. The **input-descriptor** argument is the address of a descriptor pointing to the input data.

##### integer-length

OpenVMS usage: word\_unsigned  
type: word (unsigned)  
access: write only  
mechanism: by reference for CALL entry point, by value for JSB entry point

Length of the data; this length is extracted from the descriptor by STR\$ANALYZE\_SDESC. The **integer-length** argument is the address of an unsigned word integer into which STR\$ANALYZE\_SDESC writes the data length.

##### data-address

OpenVMS usage: address  
type: longword (unsigned)  
access: write only  
mechanism: by reference for CALL entry point, by value for JSB entry point

## STR\$ Routines

### STR\$ANALYZE\_SDESC

Address of the data; this address is extracted from the descriptor by STR\$ANALYZE\_SDESC. The **data-address** argument is an unsigned longword into which STR\$ANALYZE\_SDESC writes the address of the data.

### Description

STR\$ANALYZE\_SDESC takes as input a 32-bit descriptor argument and extracts from the descriptor the length of the data and the address at which the data starts for a variety of string descriptor classes. See LIB\$ANALYZE\_SDESC for a list of classes.

STR\$ANALYZE\_SDESC returns the length of the data in the **integer-length** argument and the starting address of the data in the **data-address** argument.

STR\$ANALYZE\_SDESC signals an error if an invalid descriptor class is found.

### Condition Values Signaled

STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
-----------------	---

## STR\$ANALYZE\_SDESC\_64 (Alpha only) Analyze String Descriptor

The Analyze String Descriptor routine extracts the length and starting address of the data for a variety of string descriptor classes.

### Format

```
STR$ANALYZE_SDESC_64 input-descriptor ,integer-length ,data-address  
                        [,descriptor-type]
```

### Corresponding JSB Entry Point

Refer to the STR\$ANALYZE\_SDESC routine for information about the JSB entry point, STR\$ANALYZE\_SDESC\_R1. This JSB entry point returns 64-bit results on Alpha systems.

### Returns

OpenVMS usage: quadword\_unsigned  
type: quadword (unsigned)  
access: write only  
mechanism: by value

Length of the data. The return value is the same value returned to the **integer-length** argument.

### Arguments

#### input-descriptor

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Input descriptor from which STR\$ANALYZE\_SDESC\_64 extracts the length of the data and the address at which the data starts. The **input-descriptor** argument is the address of a descriptor pointing to the input data. The input descriptor can be a longword (unsigned) or a quadword (unsigned).

#### integer-length

OpenVMS usage: quadword\_unsigned  
type: quadword (unsigned)  
access: write only  
mechanism: by reference for CALL entry point, by value for JSB entry point

Length of the data; this length is extracted from the descriptor by STR\$ANALYZE\_SDESC\_64. The **integer-length** argument is the address of an unsigned quadword integer into which STR\$ANALYZE\_SDESC\_64 writes the data length.

## STR\$ Routines

### STR\$ANALYZE\_SDESC\_64 (Alpha only)

#### **data-address**

OpenVMS usage: address  
type: quadword (unsigned)  
access: write only  
mechanism: by reference for CALL entry point, by value for JSB entry point

Address of the data; this address is extracted from the descriptor by STR\$ANALYZE\_SDESC\_64. The **data-address** argument is an unsigned quadword into which STR\$ANALYZE\_SDESC\_64 writes the address of the data.

#### **descriptor-type**

OpenVMS usage: word\_unsigned  
type: word (unsigned)  
access: write only  
mechanism: by reference

Flag value indicating the type of input descriptor. The **descriptor-type** argument contains the address of an unsigned word integer to which STR\$ANALYZE\_SDESC\_64 writes a zero (0) for a 32-bit input descriptor or a one (1) for a 64-bit descriptor.

This argument is optional.

## Description

STR\$ANALYZE\_SDESC\_64 takes as input a descriptor argument and extracts from the descriptor the length of the data and the address at which the data starts for a variety of string descriptor classes. See LIB\$ANALYZE\_SDESC\_64 for a list of classes.

STR\$ANALYZE\_SDESC\_64 returns the length of the data in the **integer-length** argument and the starting address of the data in the **data-address** argument.

STR\$ANALYZE\_SDESC\_64 signals an error if an invalid descriptor class is found.

## Condition Values Signaled

STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
-----------------	---

---

## STR\$APPEND

### Append String

The Append String routine appends a source string to the end of a destination string.

#### Format

STR\$APPEND destination-string ,source-string

#### Returns

OpenVMS usage: cond\_value  
type: longword (unsigned)  
access: write only  
mechanism: by value

#### Arguments

##### destination-string

OpenVMS usage: char\_string  
type: character string  
access: write only  
mechanism: by descriptor

Destination string to which STR\$APPEND appends the source string. The **destination-string** argument is the address of a descriptor pointing to the destination string. This destination string must be dynamic or varying-length. The maximum length of the destination string for a 32-bit descriptor is  $2^{16} - 1$ , or 65,535, bytes.

#### Alpha

On Alpha systems, the maximum length of the destination string for all 64-bit descriptor classes, except varying-length strings, is  $2^{64} - 1$  bytes. The maximum length of a varying-length string is  $2^{16} - 1$  for both 32-bit and 64-bit descriptors. ♦

##### source-string

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Source string that STR\$APPEND appends to the end of the destination string. The **source-string** argument is the address of a descriptor pointing to this source string.

#### Description

STR\$APPEND appends a source string to the end of the destination string. The destination string must be a dynamic string or a varying-length string.

## STR\$ Routines

### STR\$APPEND

#### Condition Values Returned

SS\$ _NORMAL	Routine successfully completed.
STR\$ _TRU	String truncation warning. The destination string could not contain all of the characters from the concatenated string.

#### Condition Values Signaled

STR\$ _FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
STR\$ _ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$ _INSVIRMEM	Insufficient virtual memory. STR\$APPEND could not allocate heap storage for a dynamic or temporary string.
STR\$ _STRTOOLON	The combined lengths of the source and destination strings exceeded the maximum allowed for the <b>destination-string</b> descriptor.

#### Example

```
10 !+
! This example program uses
! STR$APPEND to append a source
! string to a destination string.
!-
DST$ = 'DOG/'
SRC$ = 'CAT'
CALL STR$APPEND (DST$, SRC$)
PRINT "DST$ = ";DST$
END
```

This BASIC example uses STR\$APPEND to append a source string 'CAT', to a destination string 'DOG/'.

The output generated by this program is as follows:

```
DST$ = DOG/CAT
```



## STR\$CASE\_BLIND\_COMPARE

### Compare Strings Without Regard to Case

The Compare Strings Without Regard to Case routine compares two input strings of any supported class and data type without regard to whether the alphabetic characters are uppercase or lowercase.

#### Format

STR\$CASE\_BLIND\_COMPARE first-source-string ,second-source-string

#### Returns

OpenVMS usage: longword\_signed  
 type: longword (signed)  
 access: write only  
 mechanism: by value

The values returned by STR\$CASE\_BLIND\_COMPARE and the conditions to which they translate are as follows:

Returned Value	Condition
-1	<b>first-source-string</b> is less than <b>second-source-string</b> .
0	Both are the same (with blank fill for shorter string).
1	<b>first-source-string</b> is greater than <b>second-source-string</b> .

#### Arguments

##### first-source-string

OpenVMS usage: char\_string  
 type: character string  
 access: read only  
 mechanism: by descriptor

First string. The **first-source-string** argument is the address of a descriptor pointing to the first string.

##### second-source-string

OpenVMS usage: char\_string  
 type: character string  
 access: read only  
 mechanism: by descriptor

Second string. The **second-source-string** argument is the address of a descriptor pointing to the second string.

#### Description

STR\$CASE\_BLIND\_COMPARE does not distinguish between uppercase and lowercase characters. The contents of both strings are converted to uppercase before the strings are compared, but the source strings themselves are not changed. STR\$CASE\_BLIND\_COMPARE uses the DEC Multinational Character Set.

## STR\$ Routines

### STR\$CASE\_BLIND\_COMPARE

#### Condition Value Signaled

STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
-----------------	---

#### Example

```
PROGRAM CASE_BLIND(INPUT, OUTPUT);
{+}
  This program demonstrates the use of
  STR$CASE_BLIND_COMPARE.
  First, declare the external function.
{-}

FUNCTION STR$CASE_BLIND_COMPARE(STR1 : VARYING
  [A] OF CHAR; STR2 : VARYING [B] OF
  CHAR) : INTEGER; EXTERN;

{+}
  Declare the variables to be used in the
  main program.
{-}

VAR
  STRING1      : VARYING [256] OF CHAR;
  STRING2      : VARYING [256] OF CHAR;
  RET_STATUS   : INTEGER;

{+}
  Begin the main program. Read values for
  the strings to be compared. Call
  STR$CASE_BLIND_COMPARE. Print the
  result.
{-}

BEGIN
  WRITELN('ENTER THE FIRST STRING: ');
  READLN(STRING1);
  WRITELN('ENTER THE SECOND STRING: ');
  READLN(STRING2);
  RET_STATUS := STR$CASE_BLIND_COMPARE(STRING1, STRING2);
  WRITELN(RET_STATUS);
END.
```

**This Pascal example shows how to call STR\$CASE\_BLIND\_COMPARE to determine whether two strings are equal regardless of case. One example of the output of this program is as follows:**

```
$ RUN CASE_BLIND
ENTER THE FIRST STRING: KITTEN
ENTER THE SECOND STRING: kItTeN
0
```

---

## STR\$COMPARE

### Compare Two Strings

The Compare Two Strings routine compares the contents of two strings.

#### Format

STR\$COMPARE first-source-string ,second-source-string

#### Returns

OpenVMS usage: longword\_signed  
type: longword integer (signed)  
access: write only  
mechanism: by value

The values returned by STR\$COMPARE and the conditions to which they translate are as follows:

Returned Value	Condition
-1	<b>first-source-string</b> is less than <b>second-source-string</b> .
0	<b>first-source-string</b> is equal to <b>second-source-string</b> .
1	<b>first-source-string</b> is greater than <b>second-source-string</b> .

#### Arguments

##### first-source-string

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

First string. The **first-source-string** argument is the address of a descriptor pointing to the first string.

##### second-source-string

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Second string. The **second-source-string** argument is the address of a descriptor pointing to the second string.

#### Description

STR\$COMPARE compares two strings for the same contents. If the strings are unequal in length, the shorter string is considered to be filled with blanks to the length of the longer string before the comparison is made. This routine distinguishes between uppercase and lowercase alphabetic characters.

## STR\$ Routines STR\$COMPARE

### Condition Value Signaled

STR\$\_ILLSTRCLA

Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.

### Example

```
100 EXTERNAL INTEGER FUNCTION STR$COMPARE
    SRC1$ = 'ABC'
    SRC2$ = 'BCD      '

    !+
    ! Note that STR$COMPARE will treat SRC1$ as if it were the same
    ! length as SRC2$ for the purpose of the comparison. Thus, it
    ! will treat the contents of SRC1$ as 'ABC      '. However, it
    ! will only 'treat' the contents as longer; the contents of
    ! the source string are not actually changed.
    !-

    I% = STR$COMPARE(SRC1$, SRC2$)
    IF I% = 1 THEN RESULT$ = ' IS GREATER THAN '
    IF I% = 0 THEN RESULT$ = ' IS EQUAL TO '
    IF I% = -1 THEN RESULT$ = ' IS LESS THAN '
    PRINT SRC1$; RESULT$; SRC2$
999 END
```

This BASIC program uses STR\$COMPARE to compare two strings. The output generated by this program is as follows:

```
ABC IS LESS THAN BCD
```

## STR\$COMPARE\_EQL

### Compare Two Strings for Equality

The Compare Two Strings for Equality routine compares two strings to see if they have the same length and contents. Uppercase and lowercase characters are not considered equal.

#### Format

STR\$COMPARE\_EQL first-source-string ,second-source-string

#### Returns

OpenVMS usage: longword\_unsigned  
 type: longword (unsigned)  
 access: write only  
 mechanism: by value

The values returned by STR\$COMPARE and the conditions to which they translate are as follows:

Returned Value	Condition
0	The length and the contents of <b>first-source-string</b> are equal to the length and contents of <b>second-source-string</b> .
1	Either the length of <b>first-source-string</b> is not equal to the length of <b>second-source-string</b> , or the contents of <b>first-source-string</b> are not equal to the contents of <b>second-source-string</b> , or both.

#### Arguments

##### first-source-string

OpenVMS usage: char\_string  
 type: character string  
 access: read only  
 mechanism: by descriptor

First source string. The **first-source-string** argument is the address of a descriptor pointing to the first source string.

##### second-source-string

OpenVMS usage: char\_string  
 type: character string  
 access: read only  
 mechanism: by descriptor

Second source string. The **second-source-string** argument is the address of a descriptor pointing to the second source string.

## STR\$ Routines

### STR\$COMPARE\_EQL

#### Condition Values Signaled

STR\$\_ILLSTRCLA                      Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.

#### Example

```
PROGRAM COMPARE_EQL(INPUT, OUTPUT);

{+}
  This program demonstrates the use of
  STR$COMPARE_EQL to compare two strings.
  Strings are considered equal only if they
  have the same contents and the same length.
{-}

  First, declare the external function.
{-}

FUNCTION STR$COMPARE_EQL(SRC1STR : VARYING
  [A] OF CHAR; SRC2STR : VARYING [B]
  OF CHAR) : INTEGER; EXTERN;

{+}
  Declare the variables used in the main program.
{-}

VAR
  STRING1      : VARYING [256] OF CHAR;
  STRING2      : VARYING [256] OF CHAR;
  RET_STATUS   : INTEGER;

{+}
  Begin the main program. Read the strings
  to be compared. Call STR$COMARE_EQL to compare
  the strings. Print the result.
{-}

BEGIN
  WRITELN('ENTER THE FIRST STRING: ');
  READLN(STRING1);
  WRITELN('ENTER THE SECOND STRING: ');
  READLN(STRING2);
  RET_STATUS := STR$COMPARE_EQL(STRING1, STRING2);
  WRITELN(RET_STATUS);
END.
```

**This Pascal example demonstrates the use of STR\$COMPARE\_EQL. A sample of the output generated by this program is as follows:**

```
$ RUN COMPARE_EQL
ENTER THE FIRST STRING:  frog
ENTER THE SECOND STRING:  Frogs
1
```

---

## STR\$COMPARE\_MULTI

### Compare Two Strings for Equality Using Multinational Character Set

The Compare Two Strings for Equality Using Multinational Character Set routine compares two character strings for equality using the DEC Multinational Character Set.

#### Format

```
STR$COMPARE_MULTI first-source-string ,second-source-string [,flags-value]
                  [,foreign-language]
```

#### Returns

OpenVMS usage: longword\_signed  
 type: longword (signed)  
 access: write only  
 mechanism: by value

The values returned by STR\$COMPARE\_MULTI and the conditions to which they translate are as follows:

Returned Value	Condition
-1	<b>first-source-string</b> is less than <b>second-source-string</b> .
0	Both strings are the same; the shorter string is blank filled.
1	<b>first-source-string</b> is greater than <b>second-source-string</b> .

#### Arguments

##### first-source-string

OpenVMS usage: char\_string  
 type: character string  
 access: read only  
 mechanism: by descriptor

First string in the comparison. The **first-source-string** argument is the address of a descriptor pointing to the first string.

##### second-source-string

OpenVMS usage: char\_string  
 type: character string  
 access: read only  
 mechanism: by descriptor

Second string in the comparison. The **second-source-string** argument is the address of a descriptor pointing to the second string.

## STR\$ Routines

### STR\$COMPARE\_MULTI

#### flags-value

OpenVMS usage: mask\_longword  
type: longword (unsigned)  
access: read only  
mechanism: by value

A single flag bit. The **flags-value** argument is a signed longword integer that contains this flag bit. The **flags-value** argument indicates whether the comparison is to be case sensitive or case blind. The default value of **flags-value** is 0, indicating a case sensitive comparison. The following table lists the meaning of the bit values:

Value	Meaning
0	Uppercase and lowercase characters are not equivalent. (The comparison is case sensitive.)
1	Uppercase and lowercase characters are equivalent. (The comparison is case blind.)

#### foreign-language

OpenVMS usage: longword\_unsigned  
type: longword (unsigned)  
access: read only  
mechanism: by value

Indicator that determines the foreign language table to be used. The **foreign-language** argument is an unsigned longword that contains this foreign language table indicator. The default value of **foreign-language** is 1. The following table lists the value of the **foreign-language** argument associated with each language table:

Value	Language
1	Multinational table
2	Danish table
3	Finnish/Swedish table
4	German table
5	Norwegian table
6	Spanish table

## Description

STR\$COMPARE\_MULTI compares two character strings to see whether they have the same contents. Two strings are "equal" if they contain the same characters in the same sequence, even if one of them is blank filled to a longer length than the other. The DEC Multinational Character Set, or foreign language variations of the DEC Multinational Character Set, are used in the comparison.

See the *OpenVMS I/O User's Reference Manual* for more information about the DEC Multinational Character Set.



Condition Values Signaled

STR\$\_ILLSTRCLA

Illegal string class. Severe error. The descriptor of **first-source-string** and/or **second-source-string** contains a class code that is not supported by the OpenVMS Calling Standard.

LIB\$\_INVARG

Invalid argument. Severe error.

## STR\$CONCAT

### Concatenate Two or More Strings

The Concatenate Two or More Strings routine concatenates all specified source strings into a single destination string.

#### Format

STR\$CONCAT destination-string ,source-string [,source-string...]

#### Returns

OpenVMS usage: cond\_value  
type: longword (unsigned)  
access: write only  
mechanism: by value

#### Arguments

##### destination-string

OpenVMS usage: char\_string  
type: character string  
access: write only  
mechanism: by descriptor

Destination string into which STR\$CONCAT concatenates all specified source strings. The **destination-string** argument is the address of a descriptor pointing to this destination string.

##### source-string

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

First source string; STR\$CONCAT requires at least one source string. The **source-string** argument is the address of a descriptor pointing to the first source string. The maximum number of source strings that STR\$CONCAT allows is 254.

##### source-string

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Additional source strings; STR\$CONCAT requires at least one source string. The **source-string** argument is the address of a descriptor pointing to the additional source string. The maximum number of source strings that STR\$CONCAT allows is 254.

## Description

STR\$CONCAT concatenates all specified source strings into a single destination string. The strings can be of any class and data type, provided that the length fields of the descriptors indicate the lengths of the strings in bytes. You must specify at least one source string, and you can specify up to 254 source strings. The maximum length of a concatenated string for a 32-bit descriptor is  $2^{16} - 1$ , or 65,535, bytes.

### Alpha

On Alpha systems, the maximum length of the destination string for all 64-bit descriptor classes, except varying-length strings, is  $2^{64} - 1$  bytes. The maximum length of a varying-length string is  $2^{16} - 1$  for both 32-bit and 64-bit descriptors. ♦

A warning status is returned if one or more input characters are not copied to the destination string.

## Condition Values Returned

SS\$_NORMAL	Normal successful completion. All characters in the input strings were copied into the destination string.
STR\$_TRU	String truncation warning. One or more input characters were not copied into the destination string.

## Condition Values Signaled

STR\$_FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$_INSVIRMEM	Insufficient virtual memory. STR\$CONCAT could not allocate heap storage for a dynamic or temporary string.
STR\$_STRTOOLON	The combined length of all the source strings exceeded the maximum allowed for the <b>destination-string</b> descriptor.
STR\$_WRONUMARG	Wrong number of arguments. You tried to pass fewer than two or more than 255 arguments to STR\$CONCAT.

## STR\$ Routines

### STR\$CONCAT

#### Examples

```
1. 10 !+
    ! This example program uses STR$CONCAT
    ! to concatenate four source strings into a
    ! single destination string.
    !-
    EXTERNAL INTEGER FUNCTION STR$CONCAT
    STATUS% = STR$CONCAT (X$, 'A', 'B', 'C', 'D')
    PRINT "X$ = ";X$
    END
```

The output generated by this BASIC program is as follows:

```
X$ = ABCD
```

---

## STR\$COPY\_DX

### Copy a Source String Passed by Descriptor to a Destination String

The Copy a Source String Passed by Descriptor to a Destination String routine copies a source string to a destination string. Both strings are passed by descriptor.

#### Format

STR\$COPY\_DX destination-string ,source-string

#### Corresponding JSB Entry Point

STR\$COPY\_DX\_R8

#### Returns

OpenVMS usage: cond\_value  
 type: longword (unsigned)  
 access: write only  
 mechanism: by value

#### Arguments

##### destination-string

OpenVMS usage: char\_string  
 type: character string  
 access: write only  
 mechanism: by descriptor

Destination string into which STR\$COPY\_DX writes the source string; depending on the class of the destination string, the following actions occur:

Descriptor Class	Action
S, Z, SD, A, NCA	Copy the source string. If needed, space is filled or truncated on the right.
D	If the area specified by the destination descriptor is large enough to contain the source string, copy the source string and set the new length in the destination descriptor. If the area specified is not large enough, return the previous space allocation (if any) and then dynamically allocate the amount of space needed. Copy the source string and set the new length and address in the destination descriptor.
VS	Copy the source string to the destination string up to the limit of the descriptor's MAXSTRLEN field with no padding. Adjust the string's current length (CURLLEN) field to the actual number of bytes copied.

The **destination-string** argument is the address of a descriptor pointing to the destination string.

## STR\$ Routines

### STR\$COPY\_DX

#### source-string

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Source string that STR\$COPY\_DX copies into the destination string; the descriptor class of the source string can be unspecified, fixed length, dynamic length, scalar decimal, array, noncontiguous array, or varying length. The **source-string** argument is the address of a descriptor pointing to this source string. (See the description of LIB\$ANALYZE\_SDESC for possible restrictions.)

## Description

STR\$COPY\_DX copies a source string to a destination string, where both strings are passed by descriptor. All conditions except success and truncation are signaled; truncation is returned as a warning condition value.

STR\$COPY\_DX passes the source string by descriptor. In addition, an equivalent JSB entry point is provided, with R0 being the first argument (the descriptor of the destination string), and R1 the second (the descriptor of the source string).

## Condition Values Returned

SS\$_NORMAL	Normal successful completion. All characters in the input string were copied to the destination string.
STR\$_TRU	String truncation warning. The destination string could not contain all of the characters copied from the source string.

## Condition Values Signaled

STR\$_FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$_INSVIRMEM	Insufficient virtual memory. STR\$COPY_DX could not allocate heap storage for a dynamic or temporary string.

---

## STR\$COPY\_R

### Copy a Source String Passed by Reference to Destination String

The Copy a Source String Passed by Reference to a Destination String routine copies a source string passed by reference to a destination string passed by descriptor.

#### Format

STR\$COPY\_R destination-string ,word-integer-source-length ,source-string-address

#### Corresponding JSB Entry Point

STR\$COPY\_R\_R8

#### Returns

OpenVMS usage: cond\_value  
type: longword (unsigned)  
access: write only  
mechanism: by value

#### Arguments

##### destination-string

OpenVMS usage: char\_string  
type: character string  
access: write only  
mechanism: by descriptor

Destination string into which STR\$COPY\_R copies the source string. The **destination-string** argument is the address of a descriptor pointing to the destination string.

The class field determines the appropriate action.

See the description of LIB\$ANALYZE\_SDESC for restrictions associated with specific descriptor classes.

##### word-integer-source-length

OpenVMS usage: word\_unsigned  
type: word (unsigned)  
access: read only  
mechanism: by reference

Length of the source string. The **word-integer-source-length** argument is the address of an unsigned word containing the length of the source string.

##### source-string-address

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by reference

Source string that STR\$COPY\_R copies into the destination string. The **source-string-address** argument is the address of the source string.

## STR\$ Routines

### STR\$COPY\_R

#### Description

STR\$COPY\_R copies a source string passed by reference to a destination string passed by descriptor. All conditions except success and truncation are signaled; truncation is returned as a warning condition value.

A JSB entry point is provided, with R0 being the first argument, R1 the second, and R2 the third. The length argument is passed in bits 15:0 of R1.

The actions taken by STR\$COPY\_R depend on the descriptor class of the destination string. The following table describes these actions for each appropriate descriptor class:

Descriptor Class	Action
S, Z, SD, A, NCA	Copy the source string. If needed, space fill or truncate on the right.
D	If the area specified by the destination descriptor is large enough to contain the source string, copy the source string and set the new length in the destination descriptor. If the area specified is not large enough, return the previous space allocation, if any, and then dynamically allocate the amount of space needed. Copy the source string and set the new length and address in the destination descriptor.
VS	Copy source string to destination string up to the limit of the descriptor's MAXSTRLEN field with no padding. Readjust the string's current length (CURLen) field to the actual number of bytes copied.

#### Condition Values Returned

SS\$ _NORMAL	Normal successful completion. All characters in the input string were copied to the destination string.
STR\$ _TRU	String truncation warning. The destination string could not contain all of the characters copied from the source string.

#### Condition Values Signaled

STR\$ _FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
STR\$ _ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$ _INSVIRMEM	Insufficient virtual memory. STR\$COPY_R could not allocate heap storage for a dynamic or temporary string.



---

## STR\$COPY\_R\_64 (Alpha Only)

### Copy a Source String Passed by Reference to Destination String

The Copy a Source String Passed by Reference to a Destination String routine copies a source string passed by reference to a destination string passed by descriptor.

#### Format

STR\$COPY\_R\_64 destination-string ,quad-integer-source-length  
,source-string-address

#### Returns

OpenVMS usage: cond\_value  
type: longword (unsigned)  
access: write only  
mechanism: by value

#### Arguments

##### destination-string

OpenVMS usage: char\_string  
type: character string  
access: write only  
mechanism: by descriptor

Destination string into which STR\$COPY\_R\_64 copies the source string. The **destination-string** argument is the address of a descriptor pointing to the destination string.

The class field determines the appropriate action.

See the description of LIB\$ANALYZE\_SDESC for restrictions associated with specific descriptor classes.

##### quad-integer-source-length

OpenVMS usage: quadword\_unsigned  
type: quadword (unsigned)  
access: read only  
mechanism: by reference

Length of the source string. The **quad-integer-source-length** argument is the address of an unsigned quadword containing the length of the source string.

##### source-string-address

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by reference

Source string that STR\$COPY\_R\_64 copies into the destination string. The **source-string-address** argument is the address of the source string.

## STR\$ Routines

### STR\$COPY\_R\_64 (Alpha Only)

#### Description

STR\$COPY\_R\_64 copies a source string passed by reference to a destination string passed by descriptor. All conditions except success and truncation are signaled; truncation is returned as a warning condition value.

A JSB entry point is provided, with R0 being the first argument, R1 the second, and R2 the third. The length argument is passed in bits 15:0 of R1.

The actions taken by STR\$COPY\_R\_64 depend on the descriptor class of the destination string. The following table describes these actions for each appropriate descriptor class:

Descriptor Class	Action
S, Z, SD, A, NCA	Copy the source string. If needed, space fill or truncate on the right.
D	If the area specified by the destination descriptor is large enough to contain the source string, copy the source string and set the new length in the destination descriptor. If the area specified is not large enough, return the previous space allocation, if any, and then dynamically allocate the amount of space needed. Copy the source string and set the new length and address in the destination descriptor.
VS	Copy source string to destination string up to the limit of the descriptor's MAXSTRLEN field with no padding. Readjust the string's current length (CURLen) field to the actual number of bytes copied.

#### Condition Values Returned

SS\$_NORMAL	Normal successful completion. All characters in the input string were copied to the destination string.
STR\$_TRU	String truncation warning. The destination string could not contain all of the characters copied from the source string.

#### Condition Values Signaled

STR\$_FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$_INSVIRMEM	Insufficient virtual memory. STR\$COPY_R_64 could not allocate heap storage for a dynamic or temporary string.



## STR\$ Routines

### STR\$DIVIDE

Sign of the second operand. The **bsign** argument is the address of an unsigned longword containing the second operand's string. A value of 0 is considered positive; a value of 1 is considered negative.

#### **bexp**

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: read only  
mechanism: by reference

Power of 10 by which **bdigits** is multiplied to get the absolute value of the second operand. The **bexp** argument is the address of the second operand's exponent.

#### **bdigits**

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Second operand's numeric text string. The **bdigits** argument is the address of a descriptor pointing to the second operand's number string. The string must be an unsigned decimal number.

#### **total-digits**

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: read only  
mechanism: by reference

Number of digits to the right of the decimal point. The **total-digits** argument is the address of a signed longword containing the number of total digits. STR\$DIVIDE uses this number to carry out the division.

#### **round-truncate-indicator**

OpenVMS usage: mask\_longword  
type: longword (unsigned)  
access: read only  
mechanism: by reference

Indicator of whether STR\$DIVIDE is to round or truncate the result; a value of 0 means truncate; a value of 1 means round. The **round-truncate-indicator** argument is the address of a longword bit mask containing this indicator.

#### **csign**

OpenVMS usage: longword\_unsigned  
type: longword (unsigned)  
access: write only  
mechanism: by reference

Sign of the result. The **csign** argument is the address of an unsigned longword containing the sign of the result. A value of 0 is considered positive; a value of 1 is considered negative.

**cexp**

OpenVMS usage: longword\_signed  
 type: longword (signed)  
 access: write only  
 mechanism: by reference

Power of 10 by which **cdigits** is multiplied to get the absolute value of the result. The **cexp** argument is the address of a signed longword containing the exponent.

**cdigits**

OpenVMS usage: char\_string  
 type: character string  
 access: write only  
 mechanism: by descriptor

Result's numeric text string. The **cdigits** argument is the address of a descriptor pointing to the numeric string of the result. This string is an unsigned decimal number.

**Description**

STR\$DIVIDE divides two decimal strings. The divisor and dividend are passed to STR\$DIVIDE in three parts: (1) the sign of the decimal number, (2) the power of 10 needed to obtain the absolute value, and (3) the numeric string. The result of the division is also returned in those three parts.

**Condition Values Returned**

SS\$NORMAL	Normal successful completion.
STR\$_TRU	String truncation warning. The destination string could not contain all of the characters in the result.

**Condition Values Signaled**

LIB\$_INVARG	Invalid argument.
STR\$_DIVBY_ZER	Division by zero.
STR\$_FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$_INSVIRMEM	Insufficient virtual memory. STR\$DIVIDE could not allocate heap storage for a dynamic or temporary string.
STR\$_WRONUMARG	Wrong number of arguments.

## STR\$ Routines

### STR\$DIVIDE

#### Example

```
100 !+
    ! This BASIC example program uses STR$DIVIDE
    ! to divide two decimal strings and truncates
    ! the result.
    !-

    ASIGN% = 1%
    AEXP% = 3%
    ADIGITS$ = '1'
    BSIGN% = 0%
    BEXP% = -4%
    BDIGITS$ = '2'
    CSIGN% = 0%
    CEXP% = 0%
    CDIGITS$ = '0'
    PRINT "A = "; ASIGN%; AEXP%; ADIGITS$
    PRINT "B = "; BSIGN%; BEXP%; BDIGITS$
    CALL STR$DIVIDE (ASIGN%, AEXP%, ADIGITS$, &
                    BSIGN%, BEXP%, BDIGITS$, &
                    3%, 0%, CSIGN%, CEXP%, CDIGITS$)
    PRINT "C = "; CSIGN%; CEXP%; CDIGITS$
1500 END
```

This BASIC program uses STR\$DIVIDE to divide two decimal strings, A divided by B, where the following values apply:

A = -1000 (ASIGN = 1, AEXP = 3, ADIGITS = '1')  
B = .0002 (BSIGN = 0, BEXP = -4, BDIGITS = '2')

The output generated by this program is as follows:

```
A = 1 3 1
B = 0 -4 2
C = 1 -3 5000000000
```

Thus, the decimal value of C equals -5000000 (CSIGN = 1, CEXP = -3, CDIGITS = 5000000000).

---

## STR\$DUPL\_CHAR

### Duplicate Character *n* Times

The Duplicate Character *n* Times routine generates a string containing *n* duplicates of the input character. If the destination string is an “empty” dynamic-length string descriptor, STR\$DUPL\_CHAR allocates and initializes the string.

#### Format

STR\$DUPL\_CHAR destination-string [,repetition-count] [,ASCII-character]

#### Corresponding JSB Entry Point

STR\$DUPL\_CHAR\_R8

#### Returns

OpenVMS usage: cond\_value  
 type: longword (unsigned)  
 access: write only  
 mechanism: by value

#### Arguments

##### destination-string

OpenVMS usage: char\_string  
 type: character string  
 access: write only  
 mechanism: by descriptor

Destination string into which STR\$DUPL\_CHAR writes **repetition-count** copies of the input character. The **destination-string** argument is the address of a descriptor pointing to the destination string. The maximum length of the destination string for a 32-bit descriptor is  $2^{16} - 1$ , or 65,535, bytes.

#### Alpha

On Alpha systems, the maximum length of the destination string for all 64-bit descriptor classes, except varying strings, is  $2^{64} - 1$  bytes. The maximum length of a varying string is  $2^{16} - 1$  for both 32-bit and 64-bit descriptors. ♦

##### repetition-count

OpenVMS usage: longword\_signed  
 type: longword (signed)  
 access: read only  
 mechanism: by reference

Number of times **ASCII-character** is duplicated; this is an optional argument (if omitted, the default is 1). The **repetition-count** argument is the address of a signed longword containing the number.

##### ASCII-character

OpenVMS usage: char\_string  
 type: character string  
 access: read only  
 mechanism: by reference

## STR\$ Routines

### STR\$DUPL\_CHAR

ASCII character that STR\$DUPL\_CHAR writes **repetition-count** times into the destination string. The **ASCII-character** argument is the address of a character string containing this character. This is an optional argument; if omitted, the default is a space.

#### Condition Values Returned

SS\$_NORMAL	Normal successful completion.
STR\$_NEGSTRLEN	Alternate success. The length argument contained a negative value; zero was used.
STR\$_TRU	String truncation warning. The destination string could not contain all of the characters.

#### Condition Values Signaled

STR\$_FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$_INSVIRMEM	Insufficient virtual memory. STR\$DUPL_CHAR could not allocate heap storage for a dynamic or temporary string.
STR\$_STRTOOLON	String length exceeds the maximum allowed for the <b>destination-string</b> descriptor.

#### Example

```
10 !+
! This example uses STR$DUPL_CHAR to
! duplicate the character 'A' four times.
!-

EXTERNAL INTEGER FUNCTION STR$DUPL_CHAR
STATUS% = STR$DUPL_CHAR (X$, 4%, 'A' BY REF)
PRINT X$
END
```

These BASIC statements set X\$ equal to 'AAAA'.

The output generated by this program is as follows:

```
AAAA
```



---

## STR\$ELEMENT

### Extract Delimited Element Substring

The Extract Delimited Element Substring routine extracts an element from a string in which the elements are separated by a specified delimiter.

#### Format

STR\$ELEMENT destination-string ,element-number ,delimiter-string ,source-string

#### Returns

OpenVMS usage: cond\_value  
type: longword (unsigned)  
access: write only  
mechanism: by value

#### Arguments

##### destination-string

OpenVMS usage: char\_string  
type: character string  
access: write only  
mechanism: by descriptor

Destination string into which STR\$ELEMENT copies the selected substring. The **destination-string** argument is the address of a descriptor pointing to the destination string.

##### element-number

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: read only  
mechanism: by reference

Element number of the delimited element substring to be returned. The **element-number** argument is the address of a signed longword containing the desired element number. Zero is used to represent the first delimited element substring, one is used to represent the second, and so forth.

##### delimiter-string

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Delimiter string used to separate element substrings. The **delimiter-string** argument is the address of a descriptor pointing to the delimiter string. The **delimiter-string** argument must be exactly one character long.

##### source-string

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

## STR\$ Routines

### STR\$ELEMENT

Source string from which STR\$ELEMENT extracts the requested delimited substring. The **source-string** argument is the address of a descriptor pointing to the source string.

#### Description

STR\$ELEMENT extracts an element from a string in which the elements are separated by a specified delimiter.

For example, if **source-string** is MON^TUE^WED^THU^FRI^SAT^SUN, **delimiter-string** is ^, and **element-number** is 2, then STR\$ELEMENT returns the string WED.

Once the specified element is located, all the characters in that delimited element are returned. That is, all characters between the **element-number** and the **element-number** + 1 delimiters are written to **destination-string**. At least **element-number** delimiters must be found. If exactly **element-number** delimiters are found, then all values from the **element-number** delimiter to the end of the string are returned. If **element-number** equals 0 and no delimiters are found, the entire input string is returned.

STR\$ELEMENT duplicates the functions of the DCL lexical function F\$ELEMENT.

#### Condition Values Returned

SS\$_NORMAL	Normal successful completion.
STR\$_INVDELIM	Delimiter string is not exactly one character long (warning).
STR\$_NOELEM	Not enough delimited characters found to satisfy requested element number (warning).
STR\$_TRU	String truncation. The destination string could not contain all the characters in the delimited substring (warning).

#### Condition Values Signaled

STR\$_FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$_INSVIRMEM	Insufficient virtual memory. STR\$ELEMENT could not allocate heap storage for a dynamic or temporary string.

---

## STR\$FIND\_FIRST\_IN\_SET

### Find First Character in a Set of Characters

The Find First Character in a Set of Characters routine searches a string one character at a time, from left to right, comparing each character in the string to every character in a specified set of characters for which it is searching.

#### Format

STR\$FIND\_FIRST\_IN\_SET source-string ,set-of-characters

#### Returns

OpenVMS usage: longword\_signed  
 type: longword (signed)  
 access: write only  
 mechanism: by value

Position in **source-string** where the first match is found; zero if no match is found.

#### Alpha

On Alpha systems, if the relative position of the substring can exceed  $2^{32} - 1$ , assign the return value to a quadword to ensure that you retrieve the correct relative position. ♦

#### Arguments

##### source-string

OpenVMS usage: char\_string  
 type: character string  
 access: read only  
 mechanism: by descriptor

String that STR\$FIND\_FIRST\_IN\_SET compares to the set of characters, looking for the first match. The **source-string** argument is the address of a descriptor pointing to the character string.

##### set-of-characters

OpenVMS usage: char\_string  
 type: character string  
 access: read only  
 mechanism: by descriptor

Set of characters that STR\$FIND\_FIRST\_IN\_SET is searching for in the string. The **source-string** argument is the address of a descriptor pointing to the set of characters.

#### Description

STR\$FIND\_FIRST\_IN\_SET compares each character in the string to every character in the specified set of characters. As soon as the first match is found, STR\$FIND\_FIRST\_IN\_SET returns the position in the string where the matching character was found. If no match is found, 0 is returned. If either **source-string** or **set-of-characters** is of zero length, 0 is returned.

## STR\$ Routines

### STR\$FIND\_FIRST\_IN\_SET

#### Condition Value Signaled

STR\$\_ILLSTRCLA                   Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.

#### Example

```
PROGRAM FIND_FIRST(INPUT, OUTPUT);
{+}
  This example uses STR$FIND_FIRST_IN_SET
  to find the first character in the source
  string (STRING1) that matches a character
  in the set of characters being searched for
  (CHARS).
{-}
  First, declare the external function.
{-}
FUNCTION STR$FIND_FIRST_IN_SET (STRING :
    VARYING [A] OF CHAR; SETOFCHARS :
    VARYING [B] OF CHAR) : INTEGER;
    EXTERN;

{+}
  Declare the variables used in the main program.
{-}
VAR
  STRING1      : VARYING [256] OF CHAR;
  CHARS        : VARYING [256] OF CHAR;
  RET_STATUS   : INTEGER;

{+}
  Begin the main program. Read the source string
  and the set of characters being searched for. Call
  STR$FIND_FIRST_IN_SET to find the first match.
  Print the result.
{-}
BEGIN
  WRITELN('ENTER THE STRING: ');
  READLN (STRING1);
  WRITELN('ENTER THE SET OF CHARACTERS: ');
  READLN (CHARS);
  RET_STATUS := STR$FIND_FIRST_IN_SET (STRING1, CHARS);
  WRITELN (RET_STATUS);
END.
```

This Pascal program demonstrates the use of STR\$FIND\_FIRST\_IN\_SET. If you run this program and set STRING1 equal to ABCDEFGHIJK and CHARS equal to XYZA, the value of RET\_STATUS is 1. The output generated by this program is as follows:

```
ENTER THE STRING:
ABCDEFGHIJK
ENTER THE SET OF CHARACTERS:
XYZA
1
```

## STR\$FIND\_FIRST\_NOT\_IN\_SET

### Find First Character That Does Not Occur in Set

The Find First Character That Does Not Occur in Set routine searches a string, comparing each character to the characters in a specified set of characters. The string is searched character by character, from left to right. STR\$FIND\_FIRST\_NOT\_IN\_SET returns the position of the first character in the string that does not match any of the characters in the selected set of characters.

#### Format

STR\$FIND\_FIRST\_NOT\_IN\_SET source-string ,set-of-characters

#### Returns

OpenVMS usage: longword\_signed  
 type: longword (signed)  
 access: write only  
 mechanism: by value

Position in **source-string** where a nonmatch was found.

#### Alpha

On Alpha systems, if the relative position of the substring can exceed  $2^{32} - 1$ , assign the return value to a quadword to ensure that you retrieve the correct relative position. ♦

Returned value	Condition
0	Either all characters in <b>source-string</b> match some character in <b>set-of-characters</b> , or there were no characters in <b>set-of-characters</b> .
1	Either the first nonmatching character in <b>source-string</b> was found in position 1, or there were no characters in <b>source-string</b> .
N	The first nonmatching character was found in position N within <b>source-string</b> .

#### Arguments

##### source-string

OpenVMS usage: char\_string  
 type: character string  
 access: read only  
 mechanism: by descriptor

String that STR\$FIND\_FIRST\_NOT\_IN\_SET searches. The **source-string** argument is the address of a descriptor pointing to the string.

##### set-of-characters

OpenVMS usage: char\_string  
 type: character string  
 access: read only  
 mechanism: by descriptor

## STR\$ Routines

### STR\$FIND\_FIRST\_NOT\_IN\_SET

The set of characters that STR\$FIND\_FIRST\_NOT\_IN\_SET compares to the string, looking for a nonmatch. The **set-of-characters** argument is the address of a descriptor pointing to this set of characters.

### Description

STR\$FIND\_FIRST\_NOT\_IN\_SET searches a string, comparing each character to the characters in a specified set of characters. The string is searched character by character, from left to right. When STR\$FIND\_FIRST\_NOT\_IN\_SET finds a character from the string that is not in **set-of-characters**, it stops searching and returns, as the value of STR\$FIND\_FIRST\_NOT\_IN\_SET, the position in **source-string** where it found the nonmatching character. If all characters in the string match some character in the set of characters, STR\$FIND\_FIRST\_NOT\_IN\_SET returns 0. If the string is of zero length, the position returned is 1 since none of the elements in the set of characters (particularly the first element) can be found in the string. If there are no characters in the set of characters, 0 is returned since “nothing” can always be found.

### Condition Value Signaled

STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
-----------------	---

### Example

```
PROGRAM NOT_IN_SET(INPUT, OUTPUT);
{+}
  This example uses STR$FIND_FIRST_NOT_IN_SET
  to find the position of the first nonmatching
  character from a set of characters (CHARS)
  in a source string (STRING1).
{-}
  First, declare the external function.
{-}
FUNCTION STR$FIND_FIRST_NOT_IN_SET (STRING :
    VARYING [A] OF CHAR; SETOFCHARS :
    VARYING [B] OF CHAR) : INTEGER;
    EXTERN;
{+}
  Declare the variables used in the main program.
{-}
VAR
    STRING1      : VARYING [256] OF CHAR;
    CHARS        : VARYING [256] OF CHAR;
    RET_STATUS   : INTEGER;
{+}
  Begin the main program.  Read the source string
  and set of characters.  Call STR$FIND_FIRST_NOT_IN_SET.
  Print the result.
{-}
```

## STR\$ Routines STR\$FIND\_FIRST\_NOT\_IN\_SET

```
BEGIN
  WRITELN('ENTER THE STRING: ');
  READLN(String1);
  WRITELN('ENTER THE SET OF CHARACTERS: ');
  READLN(CHARS);
  RET_STATUS := STR$FIND_FIRST_NOT_IN_SET(String1, CHARS);
  WRITELN(RET_STATUS);
END.
```

This Pascal program demonstrates the use of STR\$FIND\_FIRST\_NOT\_IN\_SET. If you run this program and set STRING1 equal to FORTUNATE and CHARS equal to FORT, the value of RET\_STATUS is 5.

The output generated by this program is as follows:

```
ENTER THE STRING:
FORTUNATE
ENTER THE SET OF CHARACTERS:
FORT
```

5

---

## STR\$FIND\_FIRST\_SUBSTRING

### Find First Substring in Input String

The Find First Substring in Input String routine finds the first substring (in a provided list of substrings) occurring in a given string.

#### Format

STR\$FIND\_FIRST\_SUBSTRING source-string ,index ,substring-index ,substring  
[,substring...]

#### Returns

OpenVMS usage: longword\_unsigned  
type: longword (unsigned)  
access: write only  
mechanism: by value

The values returned by STR\$FIND\_FIRST\_SUBSTRING and the conditions to which they translate are as follows:

Returned Value	Condition
0	<b>Source-string</b> did not contain any of the specified substrings.
1	STR\$FIND_FIRST_SUBSTRING found at least one of the specified substrings in the string.

#### Arguments

##### source-string

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

String that STR\$FIND\_FIRST\_SUBSTRING searches. The **source-string** argument is the address of a descriptor pointing to the string.

##### index

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: write only  
mechanism: by reference

Earliest position within **source-string** at which STR\$FIND\_FIRST\_SUBSTRING found a matching substring; zero if no matching substring was found. The **index** argument is the address of a signed longword containing this position.

##### substring-index

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: write only  
mechanism: by reference



## STR\$ Routines STR\$FIND\_FIRST\_SUBSTRING

Ordinal number of the **substring** that matched (1 for the first, 2 for the second, and so on), or zero if STR\$FIND\_FIRST\_SUBSTRING found no substrings that matched. The **substring-index** argument is the address of a signed longword containing this ordinal number.

### substring

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Specified substring for which STR\$FIND\_FIRST\_SUBSTRING searches in **source-string**. The **substring** argument is the address of a descriptor pointing to the first substring. You can specify multiple substrings to be searched for.

### substring

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Additional specified substrings for which STR\$FIND\_FIRST\_SUBSTRING searches in **source-string**. The **substring** argument is the address of a descriptor pointing to the substring. You can specify multiple substrings to be searched for.

## Description

STR\$FIND\_FIRST\_SUBSTRING takes as input a string to be searched and an unspecified number of substrings for which to search. It searches the specified string and returns the position of the substring that is found earliest in the string. This is not necessarily the position of the first substring specified. That is, STR\$FIND\_FIRST\_SUBSTRING returns the position of the leftmost matching substring. The order in which the substrings are searched for is irrelevant.

Unlike many of the compare and search routines, STR\$FIND\_FIRST\_SUBSTRING does not return the position in a return value. The position of the substring which is found earliest in the string is returned in the **index** argument. If none of the specified substrings is found in the string, the value of **index** is 0.

Zero-length strings, or null arguments, produce unexpected results. Any time the routine is called with a null substring as an argument, STR\$FIND\_FIRST\_SUBSTRING always returns the position of the null substring as the first substring found. All other substrings are interpreted as appearing in the string after the null string.

## Condition Values Signaled

STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$_WRONUMARG	Wrong number of arguments. You must supply at least one substring.

## STR\$ Routines

### STR\$FIND\_FIRST\_SUBSTRING

#### Example

```
1  !+
   ! This is a BASIC program demonstrating the use of
   ! STR$FIND_FIRST_SUBSTRING. This program takes as input
   ! four strings that are listed in a data statement
   ! at the end of the program. STR$FIND_FIRST_SUBSTRING
   ! is called four times (once for each string)
   ! to find the first substring occurring in the given
   ! string.
   !-

   OPTION TYPE = EXPLICIT

   DECLARE STRING    MATCH_STRING
   DECLARE LONG      RET_STATUS, &
                   INDEX, &
                   I, &
                   SUB_STRING_NUM
   EXTERNAL LONG FUNCTION STR$FIND_FIRST_SUBSTRING

   FOR I = 1 TO 4
     READ MATCH_STRING
     RET_STATUS = STR$FIND_FIRST_SUBSTRING( MATCH_STRING, &
     INDEX, SUB_STRING_NUM, 'ING', 'CK', 'TH')
     IF RET_STATUS = 0% THEN
       PRINT MATCH_STRING;" did not contain any of the substrings"
     ELSE
       SELECT SUB_STRING_NUM
         CASE 1
           PRINT MATCH_STRING;" contains ING at position";INDEX
         CASE 2
           PRINT MATCH_STRING;" contains CK at position";INDEX
         CASE 3
           PRINT MATCH_STRING;" contains TH at position";INDEX
       END SELECT
     END IF
   NEXT I

2  DATA CHUCKLE, RAINING, FOURTH, THICK
3  END
```

This BASIC program demonstrates the use of STR\$FIND\_FIRST\_SUBSTRING. The output generated by this program is as follows:

```
$ BASIC FINDSUB
$ LINK FINDSUB
$ RUN FINDSUB
CHUCKLE contains CK at position 4
RAINING contains ING at position 5
FOURTH contains TH at position 5
THICK contains TH at position 1
```

Note that "THICK" contains both the substrings "TH" and "CK". STR\$FIND\_FIRST\_SUBSTRING locates the "CK" substring in "THICK", and then locates the "TH" substring. However, since the "TH" substring is the earliest, or leftmost matching substring, its ordinal number is returned in **substring-index**, and the point at which "TH" occurs is returned in **index**.

---

## STR\$FREE1\_DX

### Free One Dynamic String

The Free One Dynamic String routine deallocates one dynamic string.

#### Format

STR\$FREE1\_DX string-descriptor

#### Corresponding JSB Entry Point

STR\$FREE1\_DX\_R4

#### Returns

OpenVMS usage: cond\_value  
 type: longword (unsigned)  
 access: write only  
 mechanism: by value

#### Argument

**string-descriptor**  
 OpenVMS usage: char\_string  
 type: character string  
 access: modify  
 mechanism: by descriptor

Dynamic string descriptor of the dynamic string that STR\$FREE1\_DX deallocates. The **string-descriptor** argument is the address of a descriptor pointing to the string to be deallocated. The descriptor's CLASS field is checked.

#### Description

STR\$FREE1\_DX deallocates the described string space and flags the descriptor as describing no string at all. The descriptor's POINTER and LENGTH fields contain 0.

#### Condition Values Returned

SS\$NORMAL	Normal successful completion.
------------	-------------------------------

#### Condition Values Signaled

STR\$_FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
-----------------	--

**STR\$ Routines**  
**STR\$FREE1\_DX**

STR\$\_ILLSTRCLA

Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.

---

## STR\$GET1\_DX

### Allocate One Dynamic String

The Allocate One Dynamic String routine allocates a specified number of bytes of virtual memory to a specified dynamic string descriptor.

#### Format

STR\$GET1\_DX word-integer-length ,character-string

#### Corresponding JSB Entry Point

STR\$GET1\_DX\_R4

#### Returns

OpenVMS usage: cond\_value  
type: longword (unsigned)  
access: write only  
mechanism: by value

#### Arguments

##### **word-integer-length**

OpenVMS usage: word\_unsigned  
type: word (unsigned)  
access: read only  
mechanism: by reference

Number of bytes that STR\$GET1\_DX allocates. The **word-integer-length** argument is the address of an unsigned word containing this number.

##### **character-string**

OpenVMS usage: char\_string  
type: character string  
access: modify  
mechanism: by descriptor

Dynamic string descriptor to which STR\$GET1\_DX allocates the area. The **character-string** argument is the address of the descriptor.

The descriptor's CLASS field is checked.

#### Description

STR\$GET1\_DX allocates a specified number of bytes of dynamic virtual memory to a specified string descriptor. The descriptor must be dynamic.

If the string descriptor already has dynamic memory allocated to it, but the amount allocated is less than **word-integer-length**, STR\$GET1\_DX deallocates that space before it allocates new space.

---

#### Note

Digital recommends use of the STR\$GET1\_DX or STR\$GET1\_DX\_64 (Alpha only) routine for allocating a string to a dynamic-length string

## STR\$ Routines

### STR\$GET1\_DX

descriptor. Simply filling in the length and pointer fields of a dynamic-length string descriptor can cause serious and unexpected problems with string management.

---

Use STR\$FREE1\_DX to deallocate a string allocated by STR\$GET1\_DX.

#### Condition Values Returned

SS\$_NORMAL	Normal successful completion.
-------------	-------------------------------

#### Condition Values Signaled

STR\$_FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$_INSVIRMEM	Insufficient virtual memory. STR\$GET1_DX could not allocate heap storage for a dynamic or temporary string.

---

## STR\$GET1\_DX\_64 (Alpha Only) Allocate One Dynamic String

The Allocate One Dynamic String routine allocates a specified number of bytes of virtual memory to a specified dynamic string descriptor.

### Format

STR\$GET1\_DX\_64 quad-integer-length ,character-string

### Returns

OpenVMS usage: cond\_value  
type: longword (unsigned)  
access: write only  
mechanism: by value

### Arguments

#### quad-integer-length

OpenVMS usage: quadword\_unsigned  
type: quadword (unsigned)  
access: read only  
mechanism: by reference

Number of bytes that STR\$GET1\_DX\_64 allocates. The **quad-integer-length** argument is the address of an unsigned quadword containing this number.

#### character-string

OpenVMS usage: char\_string  
type: character string  
access: modify  
mechanism: by descriptor

Dynamic string descriptor to which STR\$GET1\_DX\_64 allocates the area. The **character-string** argument is the address of the descriptor.

The descriptor's CLASS field is checked.

### Description

STR\$GET1\_DX\_64 allocates a specified number of bytes of dynamic virtual memory to a specified 64-bit string descriptor. The descriptor must be dynamic.

If the string descriptor already has dynamic memory allocated to it, but the amount allocated is less than **quad-integer-length**, STR\$GET1\_DX\_64 deallocates that space before it allocates new space.

---

#### Note

---

Digital recommends use of the STR\$GET1\_DX or STR\$GET1\_DX\_64 (Alpha only) routine for allocating a string to a dynamic-length string descriptor. Simply filling in the length and pointer fields of a dynamic-length string descriptor can cause serious and unexpected problems with string management.

---

## STR\$ Routines

### STR\$GET1\_DX\_64 (Alpha Only)

Use STR\$FREE1\_DX to deallocate a string allocated by STR\$GET1\_DX\_64.

#### Condition Values Returned

SS\$_NORMAL	Normal successful completion.
-------------	-------------------------------

#### Condition Values Signaled

STR\$_FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$_INSVIRMEM	Insufficient virtual memory. STR\$GET1_DX_64 could not allocate heap storage for a dynamic or temporary string.



---

## STR\$LEFT

### Extract a Substring of a String

The Extract a Substring of a String routine copies a substring of a source string into a destination string. The relative starting position in the source string is 1.

#### Format

STR\$LEFT destination-string ,source-string ,end-position

#### Corresponding JSB Entry Point

STR\$LEFT\_R8

#### Returns

OpenVMS usage: cond\_value  
type: longword (unsigned)  
access: write only  
mechanism: by value

#### Arguments

##### destination-string

OpenVMS usage: char\_string  
type: character string  
access: write only  
mechanism: by descriptor

Destination string into which STR\$LEFT copies the substring. The **destination-string** argument is the address of a descriptor pointing to the destination string.

##### source-string

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Source string from which STR\$LEFT extracts the substring that it copies into the destination string. The **source-string** argument is the address of a descriptor pointing to the source string.

##### end-position

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: read only  
mechanism: by reference

Relative position in the source string at which the substring ends. The **end-position** argument is the address of a signed longword containing the ending position.

STR\$LEFT copies all characters in the source string from position 1 (the leftmost position) to the position number specified in this **end-position** argument.

## STR\$ Routines

### STR\$LEFT

#### Description

STR\$LEFT extracts a substring from a source string and copies that substring into a destination string. STR\$LEFT defines the substring by specifying the relative ending position in the source string. The relative starting position in the source string is 1. The source string is unchanged, unless it is also the destination string.

This is a variation of STR\$POS\_EXTR. Other routines that may be used to extract and copy a substring are STR\$RIGHT and STR\$LEN\_EXTR.

#### Condition Values Returned

SS\$NORMAL	Normal successful completion.
STR\$_ILLSTRPOS	Alternate success. An argument referenced a character position outside the specified string. A default value was used.
STR\$_ILLSTRSPE	Alternate success. The length of the substring was too long for the specified destination string. Default values were used.
STR\$_TRU	String truncation warning. The destination string could not contain all the characters copied from the source string.

#### Condition Values Signaled

STR\$_FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$_INSVIRMEM	Insufficient virtual memory. STR\$LEFT could not allocate heap storage for a dynamic or temporary string.

#### Example

```
PROGRAM LEFT(INPUT, OUTPUT);
{+}
{ This Pascal program demonstrates the use of
  STR$LEFT. This program reads in a source string
  and the ending position of a substring.
  It returns a substring consisting of all
  characters from the beginning (left) of the
  source string to the ending position entered.
  -}
{+}
{ Declare the external procedure, STR$LEFT.
  -}
```

```
PROCEDURE STR$LEFT(%DESCR DSTSTR: VARYING
[A] OF CHAR; SRCSTR :
VARYING [B] OF CHAR; ENDPOS :
INTEGER); EXTERN;

{+}
{ Declare the variables used by this program.
{-}

VAR
  SRC_STR : VARYING [256] OF CHAR;
  DST_STR : VARYING [256] OF CHAR;
  END_POS : INTEGER;

{+}
{ Begin the main program. Read the source string
and ending position. Call STR$LEFT. Print the
results.
{-}

BEGIN
  WRITELN('ENTER THE SOURCE STRING: ');
  READLN(SRC_STR);
  WRITELN('ENTER THE ENDING POSITION');
  WRITELN('OF THE SUBSTRING: ');
  READLN(END_POS);
  STR$LEFT(DST_STR, SRC_STR, END_POS);
  WRITELN;
  WRITELN('THE SUBSTRING IS: ', DST_STR);
END.
```

**This Pascal example shows the use of STR\$LEFT. One sample of the output of this program is as follows:**

```
$ PASCAL LEFT
$ LINK LEFT
$ RUN LEFT
ENTER THE SOURCE STRING:  MAGIC CARPET
ENTER THE ENDING POSITION OF
THE SUBSTRING:  9

THE SUBSTRING IS:  MAGIC CAR
```

## STR\$LEN\_EXTR

### Extract a Substring of a String

The Extract a Substring of a String routine copies a substring of a source string into a destination string.

#### Format

STR\$LEN\_EXTR destination-string ,source-string ,start-position  
,longword-integer-length

#### Corresponding JSB Entry Point

STR\$LEN\_EXTR\_R8

#### Returns

OpenVMS usage: cond\_value  
type: longword (unsigned)  
access: write only  
mechanism: by value

#### Arguments

##### destination-string

OpenVMS usage: char\_string  
type: character string  
access: write only  
mechanism: by descriptor

Destination string into which STR\$LEN\_EXTR copies the substring. The **destination-string** argument is the address of a descriptor pointing to the destination string.

##### source-string

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Source string from which STR\$LEN\_EXTR extracts the substring that it copies into the destination string. The **source-string** argument is the address of a descriptor pointing to the source string.

##### start-position

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: read only  
mechanism: by reference

Relative position in the source string at which STR\$LEN\_EXTR begins copying the substring. The **start-position** argument is the address of a signed longword containing the starting position.

**longword-integer-length**

OpenVMS usage: longword\_signed  
 type: longword (signed)  
 access: read only  
 mechanism: by reference

Number of characters in the substring that STR\$LEN\_EXTR copies to the destination string. The **longword-integer-length** argument is the address of a signed longword containing the length of the substring.

**Description**

STR\$LEN\_EXTR extracts a substring from a source string and copies that substring into a destination string.

STR\$LEN\_EXTR defines the substring by specifying the relative starting position in the source string and the number of characters to be copied. The source string is unchanged, unless it is also the destination string.

If the starting position is less than 1, 1 is used. If the starting position is greater than the length of the source string, the null string is returned. If the length is less than 1, the null string is also returned.

Other routines that may be used to extract and copy a substring are STR\$RIGHT, STR\$LEFT and STR\$POS\_EXTR.

**Condition Values Returned**

SS\$_NORMAL	Normal successful completion.
STR\$_ILLSTRPOS	STR\$LEN_EXTR completed successfully, except that an argument referenced a character position outside the specified string. A default value was used.
STR\$_ILLSTRSPE	STR\$LEN_EXTR completed successfully, except that the length was too long for the specified string. Default values were used.
STR\$_NEGSTRLEN	STR\$LEN_EXTR completed successfully, except that <b>longword-integer-length</b> contained a negative value. Zero was used.
STR\$_TRU	String truncation warning. The destination string could not contain all the characters copied from the source string.

**Condition Values Signaled**

STR\$_FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.

## STR\$ Routines STR\$LEN\_EXTR

STR\$\_INSVIRMEM

Insufficient virtual memory. STR\$LEN\_EXTR could not allocate heap storage for a dynamic or temporary string.

### Example

```
CHARACTER*131  IN_STRING
CHARACTER*1    FRONT_CHAR
CHARACTER*1    TAIL_CHAR
INTEGER STR$LEN_EXTR, STR$REPLACE, STR$TRIM
INTEGER FRONT_POSITION, TAIL_POSITION
10  WRITE (6, 800)
800  FORMAT (' Enter a string, 131 characters or less:', $)
    READ (5, 900, END=200) IN_STRING
900  FORMAT (A)
    ISTATUS = STR$TRIM (IN_STRING, IN_STRING, LENGTH)

    DO 100 I = 1, LENGTH/2
    FRONT_POSITION = I
    TAIL_POSITION = LENGTH + 1 - I
    ISTATUS = STR$LEN_EXTR ( FRONT_CHAR, IN_STRING, FRONT_POSITION,
A      %REF(1))
    ISTATUS = STR$LEN_EXTR ( TAIL_CHAR, IN_STRING, TAIL_POSITION,
A      %REF(1))
    ISTATUS = STR$REPLACE ( IN_STRING, IN_STRING, FRONT_POSITION,
A      FRONT_POSITION, TAIL_CHAR)
    ISTATUS = STR$REPLACE ( IN_STRING, IN_STRING, TAIL_POSITION,
A      TAIL_POSITION, FRONT_CHAR)
100  CONTINUE
    WRITE (6, 901) IN_STRING
901  FORMAT (' Reversed string is : ',/,1X,A)
    GOTO 10
200  CONTINUE
    END
```

This Fortran program accepts a string as input and writes the string in reverse order as output. This program continues to prompt for input until Ctrl/Z is pressed. One sample of the output generated by this program is as follows:

```
$ FORTRAN REVERSE
$ LINK REVERSE
$ RUN REVERSE
Enter a string, 131 characters or less: Elephants often have
flat feet.
  Reversed string is :
  .teef talF evah netfo stnahpeL
Enter a string, 131 characters or less: CTRL/Z
$
```

---

## STR\$MATCH\_WILD

### Match Wildcard Specification

The Match Wildcard Specification routine is used to compare a pattern string that includes wildcard characters with a candidate string. It returns a condition value of STR\$\_MATCH if the strings match and STR\$\_NOMATCH if they do not match.

#### Format

STR\$MATCH\_WILD candidate-string ,pattern-string

#### Returns

OpenVMS usage: cond\_value  
 type: longword (unsigned)  
 access: write only  
 mechanism: by value

#### Arguments

##### candidate-string

OpenVMS usage: char\_string  
 type: character string  
 access: read only  
 mechanism: by descriptor

String that is compared to the pattern string. The **candidate-string** argument is the address of a descriptor pointing to the candidate string.

##### pattern-string

OpenVMS usage: char\_string  
 type: character string  
 access: read only  
 mechanism: by descriptor

String containing wildcard characters. The **pattern-string** argument is the address of a descriptor pointing to the pattern string. The wildcards in the pattern string are translated when STR\$MATCH\_WILD searches the candidate string to determine if it matches the pattern string.

#### Description

STR\$MATCH\_WILD translates wildcard characters and searches the candidate string to determine if it matches the pattern string. The pattern string may contain either one or both of the two wildcard characters, asterisk (\*) and percent (%). The asterisk character is mapped to zero or more characters. The percent character is mapped to only one character.

The two wildcard characters that may be used in the pattern string may be used only as wildcards. If the candidate string contains an asterisk or percent character, the condition STR\$\_MATCH is returned. Wildcard characters are translated literally. There is no restriction on whether either wildcard character in the pattern string can match a percent or asterisk that is translated literally in the candidate string.

## STR\$ Routines

### STR\$MATCH\_WILD

#### Condition Values Returned

STR\$_MATCH	The candidate string and the pattern string match.
STR\$_NOMATCH	The candidate string and the pattern string do not match.

#### Condition Value Signaled

STR\$_ILLSTRCLA	Illegal string class. Severe error. The descriptor of <b>candidate-string</b> and/or <b>pattern-string</b> contains a class code that is not supported by the OpenVMS Calling Standard.
-----------------	---

#### Example

```
/*
 * Example program using STR$MATCH_WILD.
 *
 * The following program reads in a master pattern string and then
 * compares that to input strings until it reaches the end of the
 * input file. For each string comparison done, it prints
 * either 'Matches pattern string' or 'Doesn't match pattern string'.
 */
declare str$match_wild
  external entry (character(*) varying, character(*) varying)
  returns (bit(1));
example: procedure options(main);
  dcl pattern_string character(80) varying;
  dcl test_string character(80) varying;
  on endfile(sysin) stop;
  put skip;
  get list(pattern_string) options(prompt('Pattern string> '));
  do while( '1'b );
    get skip list(test_string) options(prompt('Test string> '));
    if str$match_wild(test_string,pattern_string)
      then put skip list('Matches pattern string');
      else put skip list('Doesn't match pattern string');
    end;
  end;
end;
```



## STR\$ Routines STR\$MATCH\_WILD

This PL/I program demonstrates the use of STR\$MATCH\_WILD. The output generated by this program is as follows:

```
$ PLI MATCH
$ LINK MATCH
$ RUN MATCH
Pattern string> 'Must match me exactly.'
Test string> 'Will this work? Must match me exactly.'
Doesn't match pattern string
Test string> 'must match me exactly'
Doesn't match pattern string
Test string> 'must match me exactly.'
Doesn't match pattern string
Test string> 'Must match me exactly'
Doesn't match pattern string
Test String> 'Must match me exactly.'
Matches pattern string
```

## STR\$MUL

### Multiply Two Decimal Strings

The Multiply Two Decimal Strings routine multiplies two decimal strings.

#### Format

STR\$MUL assign ,aexp ,adigits ,bsign ,bexp ,bdigits ,csign ,cexp ,cdigits

#### Returns

OpenVMS usage: cond\_value  
type: longword (unsigned)  
access: write only  
mechanism: by value

#### Arguments

##### assign

OpenVMS usage: longword\_unsigned  
type: longword (unsigned)  
access: read only  
mechanism: by reference

Sign of the first operand. The **assign** argument is the address of an unsigned longword containing the first operand's sign. A value of 0 is considered positive; a value of 1 is considered negative.

##### aexp

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: read only  
mechanism: by reference

Power of 10 by which **adigits** is multiplied to get the absolute value of the first operand. The **aexp** argument is the address of a signed longword containing this exponent.

##### adigits

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

First operand's numeric text string. The **adigits** argument is the address of a descriptor pointing to the numeric string of the first operand. The string must be an unsigned decimal number.

##### bsign

OpenVMS usage: longword\_unsigned  
type: longword (unsigned)  
access: read only  
mechanism: by reference

Sign of the second operand. The **bsign** argument is the address of an unsigned longword containing the sign of the second operand. A value of 0 is considered positive; a value of 1 is considered negative.

**bexp**

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: read only  
mechanism: by reference

Power of 10 by which **bdigits** is multiplied to get the absolute value of the second operand. The **bexp** argument is the address of a signed longword containing this exponent.

**bdigits**

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Second operand's numeric text string. The **bdigits** argument is the address of a descriptor pointing to the second operand's numeric string. The string must be an unsigned decimal number.

**csign**

OpenVMS usage: longword\_unsigned  
type: longword (unsigned)  
access: write only  
mechanism: by reference

Sign of the result. The **csign** argument is the address of an unsigned longword containing the sign of the result. A value of 0 is considered positive; a value of 1 is considered negative.

**cexp**

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: write only  
mechanism: by reference

Power of 10 by which **cdigits** is multiplied to get the absolute value of the result. The **cexp** argument is the address of a signed longword containing this exponent.

**cdigits**

OpenVMS usage: char\_string  
type: character string  
access: write only  
mechanism: by descriptor

Result's numeric text string. The **cdigits** argument is the address of a descriptor pointing to the numeric string of the result. The string is an unsigned decimal number.

## STR\$ Routines

### STR\$MUL

#### Description

STR\$MUL multiplies two decimal strings. The numbers to be multiplied are passed to STR\$MUL in three parts: (1) the sign of the decimal number, (2) the power of 10 needed to obtain the absolute value, and (3) the numeric string. The result of the multiplication is also returned in those three parts.

#### Condition Values Returned

SS\$ _NORMAL	Normal successful completion.
STR\$ _TRU	String truncation warning. The destination string could not contain all the characters in the result.

#### Condition Values Signaled

LIB\$ _INVARG	Invalid argument.
STR\$ _FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
STR\$ _ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$ _INSVIRMEM	Insufficient virtual memory. STR\$MUL could not allocate heap storage for a dynamic or temporary string.
STR\$ _WRONUMARG	Wrong number of arguments.

#### Example

```
100 !+
! This example program uses
! STR$MUL to multiply two decimal
! strings (A and B) and place the
! results in a third decimal string,
! (C)
!-

ASIGN% = 1%
AEXP% = 3%
ADIGITS$ = '1'
BSIGN% = 0%
BEXP% = -4%
BDIGITS$ = '2'
CSIGN% = 0%
CEXP% = 0%
CDIGITS$ = '0'
PRINT "A = "; ASIGN%; AEXP%; ADIGITS$
PRINT "B = "; BSIGN%; BEXP%; BDIGITS$
CALL STR$MUL      (ASIGN%, AEXP%, ADIGITS$, &
                  BSIGN%, BEXP%, BDIGITS$, &
                  CSIGN%, CEXP%, CDIGITS$)
PRINT "C = "; CSIGN%; CEXP%; CDIGITS$
999 END
```

This BASIC example uses STR\$MUL to multiply two decimal strings, where the following values apply:

A = -1000 (ASIGN = 1, AEXP = 3, ADIGITS = '1')  
B = .0002 (BSIGN = 0, BEXP = -4, BDIGITS = '2')

The output generated by this program is as follows; note that the decimal value C equals  $-.2$  (CSIGN = 1, CEXP = -1, CDIGITS = 2).

A = 1 3 1  
B = 0 -4 2  
C = 1 -1 2

---

## STR\$POSITION

### Return Relative Position of Substring

The Return Relative Position of Substring routine searches for the first occurrence of a single substring within a source string. If STR\$POSITION finds the substring, it returns the relative position of that substring. If the substring is not found, STR\$POSITION returns a zero.

#### Format

STR\$POSITION source-string ,substring [,start-position]

#### Corresponding JSB Entry Point

STR\$POSITION\_R6

#### Returns

OpenVMS usage: longword\_unsigned  
type: longword (unsigned)  
access: write only  
mechanism: by value

Relative position of the first character of the substring. Zero is the value returned if STR\$POSITION did not find the substring.

#### Alpha

On Alpha systems, if the relative position of the substring can exceed  $2^{32} - 1$ , assign the return value to a quadword to ensure that you retrieve the correct relative position. ♦

#### Arguments

##### source-string

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Source string within which STR\$POSITION searches for the substring. The **source-string** argument is the address of a descriptor pointing to the source string.

##### substring

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Substring for which STR\$POSITION searches. The **substring** argument is the address of a descriptor pointing to the substring.

##### start-position

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: read only  
mechanism: by reference

Relative position in the source string at which STR\$POSITION begins the search. The **start-position** argument is the address of a signed longword containing the starting position. Although this is an optional argument, it is required if you are using the JSB entry point.

If **start-position** is not supplied, STR\$POSITION starts the search at the first character position of **source-string**.

## Description

STR\$POSITION returns the relative position of the first occurrence of a substring in the source string. The value returned is an unsigned longword. The relative character positions are numbered 1, 2, 3, and so on. A value of 0 indicates that the substring was not found.

If the substring has a zero length, the minimum value of **start-position** (and the length of **source-string** plus one) is returned by STR\$POSITION.

If the source string has a zero length and the substring has a nonzero length, zero is returned, indicating that the substring was not found.

## Condition Values Signaled

STR\$_ILLSTRCLA	Illegal string class. The class code found in the string class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
-----------------	--

## Example

```
PROGRAM POSITION(INPUT,OUTPUT);
{+}
This example uses STR$POSITION to determine
the position of the first occurrence of
a substring (SUBSTRING) within a source
string (STRING1) after the starting
position (START).
{-}
First, declare the external function.
{-}
FUNCTION STR$POSITION(SRCSTR : VARYING [A]
    OF CHAR; SUBSTR : VARYING [B] OF CHAR;
    STARTPOS : INTEGER) : INTEGER; EXTERN;
{+}
Declare the variables used in the main program.
{-}
VAR
    STRING1      : VARYING [256] OF CHAR;
    SUBSTRING    : VARYING [256] OF CHAR;
    START        : INTEGER;
    RET_STATUS   : INTEGER;
{+}
Begin the main program. Read the string and substring.
Set START equal to 1 to begin looking for the substring
at the beginning of the source string. Call STR$POSITION
and print the result.
{-}
```

## STR\$ Routines

### STR\$POSITION

```
BEGIN
  WRITELN('ENTER THE STRING: ');
  READLN (STRING1);
  WRITELN('ENTER THE SUBSTRING: ');
  READLN (SUBSTRING);
  START := 1;
  RET_STATUS := STR$POSITION (STRING1, SUBSTRING, START);
  WRITELN (RET_STATUS);
END.
```

**This Pascal program demonstrates the use of STR\$POSITION. If you run this program and set STRING1 equal to KITTEN and substring equal to TEN, the value of RET\_STATUS is 4.**

**The output generated by this program is as follows:**

```
ENTER THE STRING:
KITTEN
ENTER THE SUBSTRING:
TEN
      4
```



---

## STR\$POS\_EXTR

### Extract a Substring of a String

The Extract a Substring of a String routine copies a substring of a source string into a destination string.

#### Format

STR\$POS\_EXTR destination-string ,source-string ,start-position ,end-position

#### Corresponding JSB Entry Point

STR\$POS\_EXTR\_R8

#### Returns

OpenVMS usage: cond\_value  
 type: longword (unsigned)  
 access: write only  
 mechanism: by value

#### Arguments

##### destination-string

OpenVMS usage: char\_string  
 type: character string  
 access: write only  
 mechanism: by descriptor

Destination string into which STR\$POS\_EXTR copies the substring. The **destination-string** argument is the address of a descriptor pointing to the destination string.

##### source-string

OpenVMS usage: char\_string  
 type: character string  
 access: read only  
 mechanism: by descriptor

Source string from which STR\$POS\_EXTR extracts the substring that it copies into the destination string. The **source-string** argument is the address of a descriptor pointing to the source string.

##### start-position

OpenVMS usage: longword\_signed  
 type: longword (signed)  
 access: read only  
 mechanism: by reference for CALL entry point, by value for JSB entry point

Relative position in the source string at which STR\$POS\_EXTR begins copying the substring. The **start-position** argument is the address of a signed longword containing the starting position.

## STR\$ Routines

### STR\$POS\_EXTR

#### end-position

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: read only  
mechanism: by reference for CALL entry point, by value for JSB entry point

Relative position in the source string at which STR\$POS\_EXTR stops copying the substring. The **end-position** argument is the address of a signed longword containing the ending position.

## Description

STR\$POS\_EXTR extracts a substring from a source string and copies the substring into a destination string. STR\$POS\_EXTR defines the substring by specifying the relative starting and ending positions in the source string. The source string is unchanged, unless it is also the destination string.

If the starting position is less than 1, 1 is used. If the starting position is greater than the length of the source string, the null string is returned. If the ending position is greater than the length of the source string, the length of the source string is used.

Other routines that can be used to extract and copy a substring are STR\$LEFT, STR\$RIGHT, and STR\$LEN\_EXTR.

## Condition Values Returned

SS\$_NORMAL	Normal successful completion.
STR\$_ILLSTRPOS	Alternate success. An argument referenced a character position outside the specified string. A default value was used.
STR\$_ILLSTRSPE	Alternate success. <b>End-position</b> was less than <b>start-position</b> . Default values were used.
STR\$_TRU	String truncation warning. The destination string could not contain all the characters copied from the source string.

## Condition Values Signaled

STR\$_FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$_INSVIRMEM	Insufficient virtual memory. STR\$POS_EXTR could not allocate heap storage for a dynamic or temporary string.

---

## STR\$PREFIX

### Prefix a String

The Prefix a String routine inserts a source string at the beginning of a destination string. The destination string must be dynamic or varying length.

#### Format

STR\$PREFIX destination-string ,source-string

#### Returns

OpenVMS usage: cond\_value  
 type: longword (unsigned)  
 access: write only  
 mechanism: by value

#### Arguments

##### destination-string

OpenVMS usage: char\_string  
 type: character string  
 access: write only  
 mechanism: by descriptor

Destination string (dynamic or varying length); STR\$PREFIX copies the source string into the beginning of this destination string. The **destination-string** argument is the address of a descriptor pointing to the destination string.

##### source-string

OpenVMS usage: char\_string  
 type: character string  
 access: read only  
 mechanism: by descriptor

Source string that STR\$PREFIX copies into the beginning of the destination string. The **source-string** argument is the address of a descriptor pointing to the source string.

#### Description

STR\$PREFIX inserts the source string at the beginning of the destination string. The destination string must be dynamic or varying length.

#### Condition Values Returned

SS\$NORMAL	Normal successful completion.
STR\$_TRU	String truncation warning. The destination string could not contain all of the characters in the result.

## STR\$ Routines

### STR\$PREFIX

#### Condition Values Signaled

STR\$_FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$_INSVIRMEM	Insufficient virtual memory. STR\$PREFIX could not allocate heap storage for a dynamic or temporary string.

#### Example

```
10 !+
! This example uses STR$PREFIX to
! prefix a destination string (D$)
! with a source string ('ABCD').
!-

EXTERNAL INTEGER FUNCTION STR$PREFIX
D$ = 'EFG'
STATUS% = STR$PREFIX (D$, 'ABCD')
PRINT D$
END
```

These BASIC statements set D\$ equal to 'ABCDEF'.

---

## STR\$RECIP

### Reciprocal of a Decimal String

The Reciprocal of a Decimal String routine takes the reciprocal of the first decimal string to the precision limit specified by the second decimal string and returns the result as a decimal string.

#### Format

STR\$RECIP assign ,aexp ,adigits ,bsign ,bexp ,bdigits ,csign ,cexp ,cdigits

#### Returns

OpenVMS usage: cond\_value  
type: longword (unsigned)  
access: write only  
mechanism: by value

#### Arguments

##### assign

OpenVMS usage: longword\_unsigned  
type: longword (unsigned)  
access: read only  
mechanism: by reference

Sign of the first operand. The **assign** argument is the address of an unsigned longword containing the first operand's sign. A value of 0 is considered positive; a value of 1 is considered negative.

##### aexp

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: read only  
mechanism: by reference

Power of 10 by which **adigits** is multiplied to get the absolute value of the first operand. The **aexp** argument is the address of a signed longword containing this exponent.

##### adigits

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

First operand's numeric text string. The **adigits** argument is the address of a descriptor pointing to the first operand's numeric string. The string must be an unsigned decimal number.

##### bsign

OpenVMS usage: longword\_unsigned  
type: longword (unsigned)  
access: read only  
mechanism: by reference

## STR\$ Routines

### STR\$RECIP

Sign of the second operand. The **bsign** argument is the address of an unsigned longword containing the sign of the second operand. A value of 0 is considered positive; a value of 1 is considered negative.

#### **bexp**

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: read only  
mechanism: by reference

Power of 10 by which **bdigits** is multiplied to get the absolute value of the second operand. The **bexp** argument is the address of a signed longword containing this exponent.

#### **bdigits**

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Second operand's numeric text string. The **bdigits** argument is the address of a descriptor pointing to the second operand's numeric string. The string must be an unsigned decimal number.

#### **csign**

OpenVMS usage: longword\_unsigned  
type: longword (unsigned)  
access: write only  
mechanism: by reference

Sign of the result. The **csign** argument is the address of an unsigned longword containing the result's sign. A value of 0 is considered positive; a value of 1 is considered negative.

#### **cexp**

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: write only  
mechanism: by reference

Power of 10 by which **cdigits** is multiplied to get the absolute value of the result. The **cexp** argument is the address of a signed longword containing this exponent.

#### **cdigits**

OpenVMS usage: char\_string  
type: character string  
access: write only  
mechanism: by descriptor

Result's numeric text string. The **cdigits** argument is the address of a descriptor pointing to the result's numeric string. The string is an unsigned decimal number.

## Description

STR\$RECIP takes the reciprocal of the first decimal string to the precision limit specified by the second decimal string and returns the result as a decimal string.

## Condition Values Returned

SS\$ _NORMAL	Routine successfully completed.
STR\$ _TRU	String truncation warning. The destination string could not contain all of the characters in the result.

## Condition Values Signaled

STR\$ _DIVBY_ZER	Division by zero.
LIB\$ _INVARG	Invalid argument.
STR\$ _FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
STR\$ _ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$ _INSVIRMEM	Insufficient virtual memory. STR\$RECIP could not allocate heap storage for a dynamic or temporary string.
STR\$ _WRONUMARG	Wrong number of arguments.

## Example

```

100 !+
    ! This example program uses
    ! STR$RECIP to find the reciprocal of
    ! the first decimal string (A) to the
    ! precision specified in the second
    ! decimal string (B), and place the
    ! result in a third decimal string (C).
    !-

    ASIGN% = 1%
    AEXP% = 3%
    ADIGITS$ = '1'
    BSIGN% = 0%
    BEXP% = -4%
    BDIGITS$ = '2'
    CSIGN% = 0%
    CEXP% = 0%
    CDIGITS$ = '0'

    PRINT "A = "; ASIGN%; AEXP%; ADIGITS$
    PRINT "B = "; BSIGN%; BEXP%; BDIGITS$
    CALL STR$RECIP      (ASIGN%, AEXP%, ADIGITS$, &
                        BSIGN%, BEXP%, BDIGITS$, &
                        CSIGN%, CEXP%, CDIGITS$)
    PRINT "C = "; CSIGN%; CEXP%; CDIGITS$

```

## STR\$ Routines

### STR\$RECIP

999 END

This BASIC example uses STR\$RECIP to find the reciprocal of A to the precision level specified in B.

The following values apply:

A = -1000 (ASIGN = 1, AEXP = 3, ADIGITS = '1')  
B = .0002 (BSIGN = 0, BEXP = -4, BDIGITS = '2')

The output generated by this program is as follows, yielding a decimal value of C equal to  $-.001$ :

A = 1 3 1  
B = 0 -4 2  
C = 1 -3 1



---

## STR\$REPLACE

### Replace a Substring

The Replace a Substring routine copies a source string to a destination string, replacing part of the string with another string. The substring to be replaced is specified by its starting and ending positions.

#### Format

```
STR$REPLACE destination-string ,source-string ,start-position ,end-position
              ,replacement-string
```

#### Corresponding JSB Entry Point

STR\$REPLACE\_R8

#### Returns

OpenVMS usage: cond\_value  
type: longword (unsigned)  
access: write only  
mechanism: by value

#### Arguments

##### destination-string

OpenVMS usage: char\_string  
type: character string  
access: write only  
mechanism: by descriptor

Destination string into which STR\$REPLACE writes the new string created when it replaces the substring. The **destination-string** argument is the address of a descriptor pointing to the destination string.

##### source-string

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Source string. The **source-string** argument is the address of a descriptor pointing to the source string.

##### start-position

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: read only  
mechanism: by reference for CALL entry point, by value for JSB entry point

Position in the source string at which the substring that STR\$REPLACE replaces begins. The **start-position** argument is the address of a signed longword containing the starting position. The position is relative to the start of the source string.

## STR\$ Routines

### STR\$REPLACE

#### end-position

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: read only  
mechanism: by reference for CALL entry point, by value for JSB entry point

Position in the source string at which the substring that STR\$REPLACE replaces ends. The **end-position** argument is the address of a signed longword containing the ending position. The position is relative to the start of the source string.

#### replacement-string

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Replacement string with which STR\$REPLACE replaces the substring. The **replacement-string** argument is the address of a descriptor pointing to this replacement string. The value of **replacement-string** must be equal to **end-position** minus **start-position**.

## Description

STR\$REPLACE copies a source string to a destination string, replacing part of the string with another string. The substring to be replaced is specified by its starting and ending positions.

If the starting position is less than 1, 1 is used. If the ending position is greater than the length of the source string, the length of the source string is used. If the starting position is greater than the ending position, the overlapping portion of the source string will be copied twice.

## Condition Values Returned

SS\$_NORMAL	Normal successful completion.
STR\$_ILLSTRPOS	Alternate success. An argument referenced a character position outside the specified string. A default value was used.
STR\$_ILLSTRSPE	Alternate success. The value of <b>end-position</b> was less than the value of <b>start-position</b> or the length of the substring was too long for the specified string. Default values were used.
STR\$_TRU	String truncation warning. The destination string could not contain all of the characters.

## Condition Values Signaled

STR\$_FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
-----------------	--

STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$_INSVIRMEM	Insufficient virtual memory. STR\$REPLACE could not allocate heap storage for a dynamic or temporary string.

### Example

```
10 !+
! This example uses STR$REPLACE to
! replace all characters from the starting
! position (2%) to the ending position (3%)
! with characters from the replacement string
! ('XYZ').
!-

EXTERNAL INTEGER FUNCTION STR$REPLACE
D$ = 'ABCD'
STATUS% = STR$REPLACE (D$, D$, 2%, 3%, 'XYZ')
PRINT D$
END
```

These BASIC statements set D\$ equal to 'AXYZD'.

## STR\$RIGHT

### Extract a Substring of a String

The Extract a Substring of a String routine copies a substring of a source string into a destination string.

#### Format

STR\$RIGHT destination-string ,source-string ,start-position

#### Corresponding JSB Entry Point

STR\$RIGHT\_R8

#### Returns

OpenVMS usage: cond\_value  
type: longword (unsigned)  
access: write only  
mechanism: by value

#### Arguments

##### destination-string

OpenVMS usage: char\_string  
type: character string  
access: write only  
mechanism: by descriptor

Destination string into which STR\$RIGHT copies the substring. The **destination-string** argument is the address of a descriptor pointing to the destination string.

##### source-string

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Source string from which STR\$RIGHT extracts the substring that it copies into the destination string. The **source-string** argument is the address of a descriptor pointing to the source string.

##### start-position

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: read only  
mechanism: by reference for CALL entry point, by value for JSB entry point

Relative position in the source string at which the substring that STR\$RIGHT copies starts. The **start-position** argument is the address of a signed longword containing the starting position.

## Description

STR\$RIGHT extracts a substring from a source string and copies that substring into a destination string. STR\$RIGHT defines the substring by specifying the relative starting position. The relative ending position is equal to the length of the source string. The source string is unchanged, unless it is also the destination string.

If the starting position is less than 2, the entire source string is copied. If the starting position is greater than the length of the source string, a null string is copied.

This is a variation of STR\$POS\_EXTR. Other routines that can be used to extract and copy a substring are STR\$LEFT and STR\$LEN\_EXTR.

## Condition Values Returned

SS\$_NORMAL	Normal successful completion.
STR\$_ILLSTRPOS	Alternate success. An argument referenced a character position outside the specified string. A default value was used.
STR\$_TRU	String truncation warning. The destination string could not contain all the characters copied from the source string.

## Condition Values Signaled

STR\$_FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$_INSVIRMEM	Insufficient virtual memory. STR\$RIGHT could not allocate heap storage for a dynamic or temporary string.

## Example

```
PROGRAM RIGHT(INPUT, OUTPUT);
{+}
  This example uses STR$RIGHT to extract a substring
  from a specified starting position (START_POS) to
  the end (right side) of a source string (SRC_STR)
  and write the result in a destination string (DST_STR).
{-}
  First, declare the external procedure.
```

## STR\$ Routines

### STR\$RIGHT

```
PROCEDURE STR$RIGHT(%DESCR DSTSTR: VARYING
  [A] OF CHAR; SRCSTR : VARYING [B] OF CHAR;
  STARTPOS : INTEGER); EXTERN;
{+}
{ } Declare the variables used in the main program.
{-}
VAR
  SRC_STR      : VARYING [256] OF CHAR;
  DST_STR      : VARYING [256] OF CHAR;
  START_POS    : INTEGER;
{+}
{ } Begin the main program. Read the source string
{ } and starting position. Call STR$RIGHT to extract
{ } the substring. Print the result.
{-}
BEGIN
  WRITELN('ENTER THE SOURCE STRING: ');
  READLN(SRC_STR);
  WRITELN('ENTER THE STARTING POSITION');
  WRITELN('OF THE SUBSTRING: ');
  READLN(START_POS);
  STR$RIGHT(DST_STR, SRC_STR, START_POS);
  WRITELN;
  WRITELN('THE SUBSTRING IS: ', DST_STR);
END.
```

**This Pascal program uses STR\$RIGHT to extract a substring from a specified starting position (START\_POS) to the end of the source string. One sample of the output is as follows:**

```
$ RUN RIGHT
ENTER THE SOURCE STRING: BLUE PLANETS ALWAYS HAVE PURPLE PLANTS
ENTER THE STARTING POSITION
OF THE SUBSTRING: 27
THE SUBSTRING IS: URPLE PLANTS
```

---

## STR\$ROUND

### Round or Truncate a Decimal String

The Round or Truncate a Decimal String routine rounds or truncates a decimal string to a specified number of significant digits and places the result in another decimal string.

#### Format

STR\$ROUND places ,flags ,assign ,aexp ,adigits ,csign ,cexp ,cdigits

#### Returns

OpenVMS usage: cond\_value  
type: longword (unsigned)  
access: write only  
mechanism: by value

#### Arguments

##### places

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: read only  
mechanism: by reference

Maximum number of decimal digits that STR\$ROUND retains in the result. The **places** argument is the address of a signed longword containing the number of decimal digits.

##### flags

OpenVMS usage: mask\_longword  
type: longword (unsigned)  
access: read only  
mechanism: by reference

Function flag. A value of 0 indicates that the decimal string is rounded; a value of 1 indicates that it is truncated. The **flags** argument is the address of an unsigned longword containing this function flag.

##### assign

OpenVMS usage: longword\_unsigned  
type: longword (unsigned)  
access: read only  
mechanism: by reference

Sign of the decimal input string to be rounded or truncated. The **assign** argument is the address of an unsigned longword string containing this sign. A value of 0 indicates that the number is positive, while a value of 1 indicates that the number is negative.

##### aexp

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: read only  
mechanism: by reference

## STR\$ Routines

### STR\$ROUND

Power of 10 by which **adigits** is multiplied to get the absolute value of the decimal input string. The **aexp** argument is the address of a signed longword containing this exponent.

#### **adigits**

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Decimal input string. This is the string of digits to which **asign** and **aexp** are applied. The **adigits** argument is the address of a descriptor pointing to this numeric string. The string must be an unsigned decimal number.

#### **csign**

OpenVMS usage: longword\_unsigned  
type: longword (unsigned)  
access: write only  
mechanism: by reference

Sign of the result. The **csign** argument is the address of an unsigned longword containing the result's sign. A value of 0 indicates that the number is positive, while a value of 1 indicates that the number is negative.

#### **cexp**

OpenVMS usage: longword\_signed  
type: longword (signed)  
access: write only  
mechanism: by reference

Power of 10 by which **cdigits** is multiplied to get the absolute value of the result. The **cexp** argument is the address of a signed longword containing this exponent.

#### **cdigits**

OpenVMS usage: char\_string  
type: character string  
access: write only  
mechanism: by descriptor

Result's numeric text string. The **cdigits** argument is the address of a descriptor pointing to this numeric string. The string is an unsigned decimal number.

## Description

The Round or Truncate a Decimal String routine rounds or truncates a decimal string to a specified number of significant digits and places the result in another decimal string.

## Condition Values Returned

SS\$ _NORMAL	Normal successful completion.
STR\$ _TRU	String truncation warning. The destination string could not contain all of the characters.



**Condition Values Signaled**

LIB\$_INVARG	Invalid argument.
STR\$_FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$_INSVIRMEM	Insufficient virtual memory. STR\$ROUND could not allocate heap storage for a dynamic or temporary string.
STR\$_WRONUMARG	Wrong number of arguments.

**Example**

```

100 !+
! This example shows the difference between
! the values obtained when rounding or truncating
! a decimal string.
!-

ASIGN% = 0%
AEXP% = -4%
ADIGITS$ = '9999998'
CSIGN% = 0%
CEXP% = 0%
CDIGITS$ = '0'
PRINT "A = "; ASIGN%; AEXP%; ADIGITS$

!+
! First, call STR$ROUND to round the value of A.
!-

CALL STR$ROUND      (3%, 0%, ASIGN%, AEXP%, ADIGITS$, &
                    CSIGN%, CEXP%, CDIGITS$)
PRINT "ROUNDED: C = "; CSIGN%; CEXP%; CDIGITS$

!+
! Now, call STR$ROUND to truncate the value of A.
!-

CALL STR$ROUND      (3%, 1%, ASIGN%, AEXP%, ADIGITS$, &
                    CSIGN%, CEXP%, CDIGITS$)
PRINT "TRUNCATED: C = "; CSIGN%; CEXP%; CDIGITS$
999 END

```

## STR\$ Routines

### STR\$ROUND

This BASIC example uses STR\$ROUND to first round and then truncate the value of A to the number of decimal places specified by **places**. The following values apply:

A = 999.9998 (ASIGN = 0, AEXP = -4, ADIGITS = '9999998')

The output generated by this program is as follows; note that the decimal value of C equals 1000 when rounded and 999 when truncated.

A = 0 -4 9999998

ROUNDED: C = 0 1 100

TRUNCATED: C = 0 0 999

---

## STR\$TRANSLATE

### Translate Matched Characters

The Translate Matched Characters routine successively compares each character in a source string to all characters in a match string. If a source character has a match, the destination character is taken from the translate string. Otherwise, STR\$TRANSLATE moves the source character to the destination string.

#### Format

STR\$TRANSLATE destination-string ,source-string ,translation-string ,match-string

#### Returns

OpenVMS usage: cond\_value  
 type: longword (unsigned)  
 access: write only  
 mechanism: by value

#### Arguments

##### destination-string

OpenVMS usage: char\_string  
 type: character string  
 access: write only  
 mechanism: by descriptor

Destination string. The **destination-string** argument is the address of a descriptor pointing to the destination string.

##### source-string

OpenVMS usage: char\_string  
 type: character string  
 access: read only  
 mechanism: by descriptor

Source string. The **source-string** argument is the address of a descriptor pointing to the source string.

##### translation-string

OpenVMS usage: char\_string  
 type: character string  
 access: read only  
 mechanism: by descriptor

Translate string. The **translation-string** argument is the address of a descriptor pointing to the translate string.

##### match-string

OpenVMS usage: char\_string  
 type: character string  
 access: read only  
 mechanism: by descriptor

Match string. The **match-string** argument is the address of a descriptor pointing to the match string.

## STR\$ Routines

### STR\$TRANSLATE

#### Description

STR\$TRANSLATE successively compares each character in a source string to all characters in a match string. If a source character matches any of the characters in the match string, STR\$TRANSLATE moves a character from the translate string to the destination string. Otherwise, STR\$TRANSLATE moves the character from the source string to the destination string.

The character taken from the translate string has the same relative position as the matching character had in the match string. When a character appears more than once in the match string, the position of the leftmost occurrence of the multiply-defined character is used to select the translate string character. If the translate string is shorter than the match string and the matched character position is greater than the translate string length, the destination character is a space.

#### Condition Values Returned

SS\$NORMAL	Normal successful completion.
STR\$_TRU	String truncation warning. The destination string could not contain all of the characters.

#### Condition Values Signaled

STR\$_FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$_INSVIRMEM	Insufficient virtual memory. STR\$TRANSLATE could not allocate heap storage for a dynamic or temporary string.

#### Example

```
10      !+
      ! This example program uses STR$TRANSLATE to
      ! translate all characters of a source string
      ! from uppercase to lowercase characters.
      !-

      EXTERNAL INTEGER FUNCTION STR$TRANSLATE (STRING,STRING,STRING,STRING)
      TO$='abcdefghijklmnopqrstuvwxyz'
      FROM$='ABCDEFGHIJKLMNOPQRSTUVWXYZ'
      X% = STR$TRANSLATE (OUT$, 'TEST', TO$, FROM$)
      PRINT 'Status = ',X%
      PRINT 'Resulting string = ',out$
32767  END
```

This BASIC example translates uppercase letters to lowercase letters, thus performing a function similar to but the opposite of STR\$UPCASE.

The output generated by this example is as follows:

```
$ RUN TRANSLATE  
Status = 1  
Resulting string = test
```

A more practical although more complicated use for STR\$TRANSLATE is to encrypt data by translating the characters to obscure combinations of numbers and alphabetic characters.

## STR\$TRIM

### Trim Trailing Blanks and Tabs

The Trim Trailing Blanks and Tabs routine copies a source string to a destination string and deletes the trailing blank and tab characters.

#### Format

STR\$TRIM destination-string ,source-string [,resultant-length]

#### Returns

OpenVMS usage: cond\_value  
type: longword (unsigned)  
access: write only  
mechanism: by value

#### Arguments

##### destination-string

OpenVMS usage: char\_string  
type: character string  
access: write only  
mechanism: by descriptor

Destination string into which STR\$TRIM copies the trimmed string. The **destination-string** argument is the address of a descriptor pointing to the destination string.

##### source-string

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Source string which STR\$TRIM trims and then copies into the destination string. The **source-string** argument is the address of a descriptor pointing to the source string.

##### resultant-length

OpenVMS usage: word\_unsigned  
type: word (unsigned)  
access: write only  
mechanism: by reference

Number of bytes that STR\$TRIM writes into **destination-string**, not counting padding in the case of a fixed-length string. The **resultant-length** argument is the address of an unsigned word into which STR\$TRIM writes the length of the output string. If the input string is truncated to the size specified in the **destination-string** description, **resultant-length** is set to this size. Therefore, **resultant-length** can always be used by the calling program to access a valid substring of **destination-string**.

## **Description**

STR\$TRIM copies a source string to a destination string and deletes the trailing blank and tab characters.

## **Condition Values Returned**

SS\$ _NORMAL	Normal successful completion.
STR\$ _TRU	String truncation warning. The destination string could not contain all the characters.

## **Condition Values Signaled**

STR\$ _FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
STR\$ _ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$ _INSVIRMEM	Insufficient virtual memory. STR\$TRIM could not allocate heap storage for a dynamic or temporary string.

---

## STR\$UPCASE

### Convert String to All Uppercase Characters

The Convert String to All Uppercase Characters routine converts a source string to uppercase.

#### Format

STR\$UPCASE destination-string ,source-string

#### Returns

OpenVMS usage: cond\_value  
type: longword (unsigned)  
access: write only  
mechanism: by value

#### Arguments

##### destination-string

OpenVMS usage: char\_string  
type: character string  
access: write only  
mechanism: by descriptor

Destination string into which STR\$UPCASE writes the string it has converted to uppercase. The **destination-string** argument is the address of a descriptor pointing to the destination string.

##### source-string

OpenVMS usage: char\_string  
type: character string  
access: read only  
mechanism: by descriptor

Source string that STR\$UPCASE converts to uppercase. The **source-string** argument is the address of a descriptor pointing to the source string.

#### Description

STR\$UPCASE converts successive characters in a source string to uppercase and writes the converted character into the destination string. The routine converts all characters in the DEC Multinational Character Set.

#### Condition Values Returned

SS\$_NORMAL	Normal successful completion.
STR\$_TRU	String truncation warning. The destination string could not contain all the characters.



## Condition Values Signaled

STR\$_FATINTERR	Fatal internal error. An internal consistency check has failed. This usually indicates an internal error in the Run-Time Library and should be reported to Digital in a Software Performance Report (SPR).
STR\$_ILLSTRCLA	Illegal string class. The class code found in the class field of a descriptor is not a string class code allowed by the OpenVMS Calling Standard.
STR\$_INSVIRMEM	Insufficient virtual memory. STR\$UPCASE could not allocate heap storage for a dynamic or temporary string.

## Examples

```
1. 30 !+
    ! This example uses STR$UPCASE
    ! to convert all characters in
    ! the source string (SRC$) to
    ! uppercase and write the result
    ! in the destination string (DST$).
    !-

SRC$ = 'abcd'
PRINT "SRC$ =";SRC$
CALL STR$UPCASE (DST$, SRC$)
PRINT "DST$ =";DST$
END
```

This BASIC program generates the following output:

```
SCR$ =abcd
DST$ =ABCD
```



---

# Index

## A

---

Addition of decimal strings, STR-5

## D

---

DEC Multinational Character Set  
string comparison, STR-13, STR-20  
string conversion, STR-92

Descriptors, 2-7  
analysis of, 2-4, STR-7

Dynamic length strings, 2-2, 2-4, STR-71  
allocating, STR-49 to STR-51  
deallocating, STR-47

## E

---

Entry points  
CALL entry points, 2-9  
JSB entry points, 2-9

## F

---

Fixed length strings, 2-1  
Function return values, 2-7  
returned in output argument, 2-7  
returned in R0/R1, 2-7

## H

---

Heap storage, 2-3

## L

---

LIB\$ANALYZE\_SDESC routine, 2-4  
LIB\$ANALYZE\_SDESC\_64 routine, 2-4  
LIB\$GET\_INPUT routine, 2-8  
LIB\$GET\_VM routine, 2-3  
LIB\$GET\_VM\_64 routine, 2-3  
LIB\$SCOPY\_DXDX routine, 2-7

## M

---

Memory allocation  
for dynamic length strings, STR-49 to STR-51  
freeing dynamic length strings, STR-47

Multiplication of decimal strings, STR-64

## O

---

OT\$SCOPY\_DXDX routine, 2-7

## R

---

Routines  
See String manipulation routines  
Run-Time Library Routines  
string Manipulation, 2-1

## S

---

STR\$ADD routine, STR-3  
STR\$ANALYZE\_SDESC routine, 2-4, STR-7  
STR\$ANALYZE\_SDESC\_64 routine, 2-4, STR-9  
STR\$APPEND routine, 2-9, STR-11  
STR\$CASE\_BLIND\_COMPARE routine, STR-13  
STR\$COMPARE routine, STR-15  
STR\$COMPARE\_EQL routine, STR-17  
STR\$COMPARE\_MULTI routine, STR-19  
STR\$CONCAT routine, 2-9, STR-22  
STR\$COPY\_DX routine, 2-7, 2-8, STR-25  
STR\$COPY\_R routine, STR-27  
STR\$COPY\_R\_64 routine, STR-29  
STR\$DIVIDE routine, STR-31  
STR\$DUPL\_CHAR routine, STR-35  
STR\$ELEMENT routine, STR-37  
STR\$FIND\_FIRST\_IN\_SET routine, STR-39  
STR\$FIND\_FIRST\_NOT\_IN\_SET routine,  
STR-41  
STR\$FIND\_FIRST\_SUBSTRING routine, STR-44  
STR\$FREE1\_DX routine, STR-47  
STR\$GET1\_DX routine, STR-49  
STR\$GET1\_DX\_64 routine, STR-51  
STR\$LEFT routine, 2-9, STR-53  
STR\$LEN\_EXTR routine, STR-56  
STR\$MATCH\_WILD routine, STR-59  
STR\$MUL routine, STR-62  
STR\$POSITION routine, STR-66  
STR\$POS\_EXTRA routine, 2-9  
STR\$POS\_EXTR routine, STR-69  
STR\$PREFIX routine, 2-9, STR-71

- STR\$RECIP routine, STR-73
- STR\$REPLACE routine, STR-77
- STR\$RIGHT routine, 2-9, STR-80
- STR\$ROUND routine, STR-83
- STR\$TRANSLATE routine, STR-87
- STR\$TRIM routine, STR-90
- STR\$UPCASE routine, STR-92
- String arithmetic
  - addition of decimal strings, STR-5
  - division of decimal strings, STR-33
  - multiplication, STR-64
- String descriptors, STR-7, STR-10
- String manipulation routines, 2-1
  - descriptor classes and string semantics, 2-4
  - how to select, 2-8
  - list of severe errors, 2-11
  - reading input string arguments, 2-6
  - writing output string arguments, 2-6
- Strings
  - See also Descriptors
  - See also String manipulation routines
  - appending, STR-11
  - comparing for equality, no padding, STR-17
  - comparing two, STR-15
  - comparing without regard to case, STR-13
  - concatenating, STR-22
  - converting to uppercase, STR-92
  - copying by descriptor, STR-25

- copying by reference, STR-27 to STR-29
- dividing two decimal strings, STR-33
- duplicating characters in, STR-35
- dynamic length, 2-2, 2-3, 2-11, 2-12
  - allocating, STR-49 to STR-51
  - deallocating, STR-47
- evaluation rules, 2-1
- fixed length, 2-1
- inserting source string at front of destination, STR-71
- maximum length of, 2-1
- null strings, 2-11
- output length argument, 2-8
- position of character in, STR-39, STR-41
- position of substring in, STR-66
- reciprocal of decimal string, STR-74
- removing trailing blanks and tabs, STR-91
- rounding or truncating a decimal string, STR-84
  - semantics of, 2-1, 2-4
  - translating matched characters, STR-88
- Substrings, 2-1
  - replacing, STR-78

## V

---

Varying length strings, 2-2, 2-4, STR-25, STR-71